

NVIDIA Performance Primitives (NPP)
Version 5.5

March 27, 2013

Contents

1	NVIDIA Performance Primitives	1
1.1	What is NPP?	1
1.2	Documentation	1
1.3	Technical Specifications	2
1.4	Files	2
1.4.1	Header Files	2
1.4.2	Library Files	2
1.5	Supported NVIDIA Hardware	3
2	General API Conventions	5
2.1	Memory Management	6
2.1.1	Scratch Buffer and Host Pointer	6
2.2	Function Naming	7
2.3	Integer Result Scaling	7
2.4	Rounding Modes	8
2.4.1	Rounding Mode Parameter	8
3	Signal-Processing Specific API Conventions	9
3.1	Signal Data	10
3.1.1	Parameter Names for Signal Data	10
3.1.1.1	Source Signal Pointer	10
3.1.1.2	Destination Signal Pointer	10
3.1.1.3	In-Place Signal Pointer	10
3.1.2	Signal Data Alignment Requirements	11
3.1.3	Signal Data Related Error Codes	11
3.2	Signal Length	11
3.2.1	Length Related Error Codes	11
4	Imaging-Processing Specific API Conventions	13

4.1	Function Naming	14
4.2	Image Data	14
4.2.1	Line Step	15
4.2.2	Parameter Names for Image Data	15
4.2.2.1	Passing Source-Image Data	15
4.2.2.2	Passing Destination-Image Data	16
4.2.2.3	Passing In-Place Image Data	18
4.2.2.4	Passing Mask-Image Data	18
4.2.2.5	Passing Channel-of-Interest Data	18
4.2.3	Image Data Alignment Requirements	18
4.2.4	Image Data Related Error Codes	19
4.3	Region-of-Interest (ROI)	19
4.3.1	ROI Related Error Codes	19
4.4	Masked Operation	20
4.5	Channel-of-Interest API	20
4.5.1	Select-Channel Source-Image Pointer	20
4.5.2	Select-Channel Source-Image	20
4.5.3	Select-Channel Destination-Image Pointer	20
4.6	Source-Image Sampling	21
4.6.1	Point-Wise Operations	21
4.6.2	Neighborhood Operations	21
4.6.2.1	Mask-Size Parameter	21
4.6.2.2	Anchor-Point Parameter	22
4.6.2.3	Sampling Beyond Image Boundaries	22
5	Module Index	23
5.1	Modules	23
6	Data Structure Index	29
6.1	Data Structures	29
7	Module Documentation	31
7.1	NPP Core	31
7.1.1	Detailed Description	31
7.1.2	Function Documentation	32
7.1.2.1	nppGetGpuComputeCapability	32
7.1.2.2	nppGetGpuName	32
7.1.2.3	nppGetGpuNumSMs	32

7.1.2.4	<code>nppGetLibVersion</code>	32
7.1.2.5	<code>nppGetMaxThreadsPerBlock</code>	32
7.1.2.6	<code>nppGetMaxThreadsPerSM</code>	33
7.1.2.7	<code>nppGetStream</code>	33
7.1.2.8	<code>nppSetStream</code>	33
7.2	NPP Type Definitions and Constants	34
7.2.1	Define Documentation	39
7.2.1.1	<code>NPP_MAX_16S</code>	39
7.2.1.2	<code>NPP_MAX_16U</code>	39
7.2.1.3	<code>NPP_MAX_32S</code>	39
7.2.1.4	<code>NPP_MAX_32U</code>	39
7.2.1.5	<code>NPP_MAX_64S</code>	39
7.2.1.6	<code>NPP_MAX_64U</code>	39
7.2.1.7	<code>NPP_MAX_8S</code>	39
7.2.1.8	<code>NPP_MAX_8U</code>	39
7.2.1.9	<code>NPP_MAXABS_32F</code>	40
7.2.1.10	<code>NPP_MAXABS_64F</code>	40
7.2.1.11	<code>NPP_MIN_16S</code>	40
7.2.1.12	<code>NPP_MIN_16U</code>	40
7.2.1.13	<code>NPP_MIN_32S</code>	40
7.2.1.14	<code>NPP_MIN_32U</code>	40
7.2.1.15	<code>NPP_MIN_64S</code>	40
7.2.1.16	<code>NPP_MIN_64U</code>	40
7.2.1.17	<code>NPP_MIN_8S</code>	40
7.2.1.18	<code>NPP_MIN_8U</code>	40
7.2.1.19	<code>NPP_MINABS_32F</code>	40
7.2.1.20	<code>NPP_MINABS_64F</code>	41
7.2.2	Enumeration Type Documentation	41
7.2.2.1	<code>NppCmpOp</code>	41
7.2.2.2	<code>NppGpuComputeCapability</code>	41
7.2.2.3	<code>NppHintAlgorithm</code>	41
7.2.2.4	<code>NppiAlphaOp</code>	41
7.2.2.5	<code>NppiAxis</code>	42
7.2.2.6	<code>NppiBorderType</code>	42
7.2.2.7	<code>NppiInterpolationMode</code>	42
7.2.2.8	<code>NppiMaskSize</code>	43

7.2.2.9	NppRoundMode	43
7.2.2.10	NppStatus	44
7.2.2.11	NppsZCType	46
7.3	Basic NPP Data Types	47
7.3.1	Typedef Documentation	48
7.3.1.1	Npp16s	48
7.3.1.2	Npp16u	48
7.3.1.3	Npp32f	48
7.3.1.4	Npp32fc	48
7.3.1.5	Npp32s	48
7.3.1.6	Npp32sc	49
7.3.1.7	Npp32u	49
7.3.1.8	Npp32uc	49
7.3.1.9	Npp64f	49
7.3.1.10	Npp64fc	49
7.3.1.11	Npp64s	49
7.3.1.12	Npp64sc	49
7.3.1.13	Npp64u	49
7.3.1.14	Npp8s	49
7.3.1.15	Npp8u	49
7.3.2	Function Documentation	49
7.3.2.1	__align__	49
7.3.2.2	__align__	50
7.3.3	Variable Documentation	50
7.3.3.1	Npp16sc	50
7.3.3.2	Npp16uc	50
7.3.3.3	Npp8uc	50
7.4	NPP Image Processing	51
7.5	Arithmetic and Logical Operations	52
7.6	Arithmetic Operations	53
7.7	AddC	55
7.7.1	Detailed Description	60
7.7.2	Function Documentation	60
7.7.2.1	nppiAddC_16s_AC4RSfs	60
7.7.2.2	nppiAddC_16s_AC4RSfs	60
7.7.2.3	nppiAddC_16s_C1IRSfs	60

7.7.2.4	nppiAddC_16s_C1RSfs	61
7.7.2.5	nppiAddC_16s_C3RSfs	61
7.7.2.6	nppiAddC_16s_C4RSfs	62
7.7.2.7	nppiAddC_16s_C4RSfs	62
7.7.2.8	nppiAddC_16s_C4RSfs	62
7.7.2.9	nppiAddC_16sc_AC4RSfs	63
7.7.2.10	nppiAddC_16sc_AC4RSfs	63
7.7.2.11	nppiAddC_16sc_C1RSfs	64
7.7.2.12	nppiAddC_16sc_C1RSfs	64
7.7.2.13	nppiAddC_16sc_C3RSfs	64
7.7.2.14	nppiAddC_16sc_C3RSfs	65
7.7.2.15	nppiAddC_16u_AC4RSfs	65
7.7.2.16	nppiAddC_16u_AC4RSfs	66
7.7.2.17	nppiAddC_16u_C1RSfs	66
7.7.2.18	nppiAddC_16u_C1RSfs	66
7.7.2.19	nppiAddC_16u_C3RSfs	67
7.7.2.20	nppiAddC_16u_C3RSfs	67
7.7.2.21	nppiAddC_16u_C4RSfs	68
7.7.2.22	nppiAddC_16u_C4RSfs	68
7.7.2.23	nppiAddC_32f_AC4IR	68
7.7.2.24	nppiAddC_32f_AC4R	69
7.7.2.25	nppiAddC_32f_C1IR	69
7.7.2.26	nppiAddC_32f_C1R	69
7.7.2.27	nppiAddC_32f_C3IR	70
7.7.2.28	nppiAddC_32f_C3R	70
7.7.2.29	nppiAddC_32f_C4IR	70
7.7.2.30	nppiAddC_32f_C4R	71
7.7.2.31	nppiAddC_32fc_AC4IR	71
7.7.2.32	nppiAddC_32fc_AC4R	71
7.7.2.33	nppiAddC_32fc_C1IR	72
7.7.2.34	nppiAddC_32fc_C1R	72
7.7.2.35	nppiAddC_32fc_C3IR	72
7.7.2.36	nppiAddC_32fc_C3R	73
7.7.2.37	nppiAddC_32fc_C4IR	73
7.7.2.38	nppiAddC_32fc_C4R	73
7.7.2.39	nppiAddC_32s_C1RSfs	74

7.7.2.40	nppiAddC_32s_C1RSfs	74
7.7.2.41	nppiAddC_32s_C3IRSfs	74
7.7.2.42	nppiAddC_32s_C3RSfs	75
7.7.2.43	nppiAddC_32sc_AC4IRSfs	75
7.7.2.44	nppiAddC_32sc_AC4RSfs	76
7.7.2.45	nppiAddC_32sc_C1IRSfs	76
7.7.2.46	nppiAddC_32sc_C1RSfs	76
7.7.2.47	nppiAddC_32sc_C3IRSfs	77
7.7.2.48	nppiAddC_32sc_C3RSfs	77
7.7.2.49	nppiAddC_8u_AC4IRSfs	78
7.7.2.50	nppiAddC_8u_AC4RSfs	78
7.7.2.51	nppiAddC_8u_C1IRSfs	78
7.7.2.52	nppiAddC_8u_C1RSfs	79
7.7.2.53	nppiAddC_8u_C3IRSfs	79
7.7.2.54	nppiAddC_8u_C3RSfs	79
7.7.2.55	nppiAddC_8u_C4IRSfs	80
7.7.2.56	nppiAddC_8u_C4RSfs	80
7.8	MulC	81
7.8.1	Detailed Description	86
7.8.2	Function Documentation	86
7.8.2.1	nppiMulC_16s_AC4IRSfs	86
7.8.2.2	nppiMulC_16s_AC4RSfs	86
7.8.2.3	nppiMulC_16s_C1IRSfs	87
7.8.2.4	nppiMulC_16s_C1RSfs	87
7.8.2.5	nppiMulC_16s_C3IRSfs	87
7.8.2.6	nppiMulC_16s_C3RSfs	88
7.8.2.7	nppiMulC_16s_C4IRSfs	88
7.8.2.8	nppiMulC_16s_C4RSfs	88
7.8.2.9	nppiMulC_16sc_AC4IRSfs	89
7.8.2.10	nppiMulC_16sc_AC4RSfs	89
7.8.2.11	nppiMulC_16sc_C1IRSfs	90
7.8.2.12	nppiMulC_16sc_C1RSfs	90
7.8.2.13	nppiMulC_16sc_C3IRSfs	90
7.8.2.14	nppiMulC_16sc_C3RSfs	91
7.8.2.15	nppiMulC_16u_AC4IRSfs	91
7.8.2.16	nppiMulC_16u_AC4RSfs	92

7.8.2.17	nppiMulC_16u_C1RSfs	92
7.8.2.18	nppiMulC_16u_C1RSfs	92
7.8.2.19	nppiMulC_16u_C3RSfs	93
7.8.2.20	nppiMulC_16u_C3RSfs	93
7.8.2.21	nppiMulC_16u_C4RSfs	94
7.8.2.22	nppiMulC_16u_C4RSfs	94
7.8.2.23	nppiMulC_32f_AC4IR	94
7.8.2.24	nppiMulC_32f_AC4R	95
7.8.2.25	nppiMulC_32f_C1IR	95
7.8.2.26	nppiMulC_32f_C1R	95
7.8.2.27	nppiMulC_32f_C3IR	96
7.8.2.28	nppiMulC_32f_C3R	96
7.8.2.29	nppiMulC_32f_C4IR	96
7.8.2.30	nppiMulC_32f_C4R	97
7.8.2.31	nppiMulC_32fc_AC4IR	97
7.8.2.32	nppiMulC_32fc_AC4R	97
7.8.2.33	nppiMulC_32fc_C1IR	98
7.8.2.34	nppiMulC_32fc_C1R	98
7.8.2.35	nppiMulC_32fc_C3IR	98
7.8.2.36	nppiMulC_32fc_C3R	99
7.8.2.37	nppiMulC_32fc_C4IR	99
7.8.2.38	nppiMulC_32fc_C4R	99
7.8.2.39	nppiMulC_32s_C1RSfs	100
7.8.2.40	nppiMulC_32s_C1RSfs	100
7.8.2.41	nppiMulC_32s_C3RSfs	100
7.8.2.42	nppiMulC_32s_C3RSfs	101
7.8.2.43	nppiMulC_32sc_AC4RSfs	101
7.8.2.44	nppiMulC_32sc_AC4RSfs	102
7.8.2.45	nppiMulC_32sc_C1RSfs	102
7.8.2.46	nppiMulC_32sc_C1RSfs	102
7.8.2.47	nppiMulC_32sc_C3RSfs	103
7.8.2.48	nppiMulC_32sc_C3RSfs	103
7.8.2.49	nppiMulC_8u_AC4RSfs	104
7.8.2.50	nppiMulC_8u_AC4RSfs	104
7.8.2.51	nppiMulC_8u_C1RSfs	104
7.8.2.52	nppiMulC_8u_C1RSfs	105

7.8.2.53	nppiMulC_8u_C3IRSfs	105
7.8.2.54	nppiMulC_8u_C3RSfs	105
7.8.2.55	nppiMulC_8u_C4IRSfs	106
7.8.2.56	nppiMulC_8u_C4RSfs	106
7.9	MulCScale	107
7.9.1	Detailed Description	108
7.9.2	Function Documentation	108
7.9.2.1	nppiMulCScale_16u_AC4IR	108
7.9.2.2	nppiMulCScale_16u_AC4R	109
7.9.2.3	nppiMulCScale_16u_C1IR	109
7.9.2.4	nppiMulCScale_16u_C1R	109
7.9.2.5	nppiMulCScale_16u_C3IR	110
7.9.2.6	nppiMulCScale_16u_C3R	110
7.9.2.7	nppiMulCScale_16u_C4IR	110
7.9.2.8	nppiMulCScale_16u_C4R	111
7.9.2.9	nppiMulCScale_8u_AC4IR	111
7.9.2.10	nppiMulCScale_8u_AC4R	111
7.9.2.11	nppiMulCScale_8u_C1IR	112
7.9.2.12	nppiMulCScale_8u_C1R	112
7.9.2.13	nppiMulCScale_8u_C3IR	112
7.9.2.14	nppiMulCScale_8u_C3R	113
7.9.2.15	nppiMulCScale_8u_C4IR	113
7.9.2.16	nppiMulCScale_8u_C4R	113
7.10	SubC	114
7.10.1	Detailed Description	119
7.10.2	Function Documentation	119
7.10.2.1	nppiSubC_16s_AC4IRSfs	119
7.10.2.2	nppiSubC_16s_AC4RSfs	119
7.10.2.3	nppiSubC_16s_C1IRSfs	119
7.10.2.4	nppiSubC_16s_C1RSfs	120
7.10.2.5	nppiSubC_16s_C3IRSfs	120
7.10.2.6	nppiSubC_16s_C3RSfs	121
7.10.2.7	nppiSubC_16s_C4IRSfs	121
7.10.2.8	nppiSubC_16s_C4RSfs	121
7.10.2.9	nppiSubC_16sc_AC4IRSfs	122
7.10.2.10	nppiSubC_16sc_AC4RSfs	122

7.10.2.11 nppiSubC_16sc_C1IRSfs	123
7.10.2.12 nppiSubC_16sc_C1RSfs	123
7.10.2.13 nppiSubC_16sc_C3IRSfs	123
7.10.2.14 nppiSubC_16sc_C3RSfs	124
7.10.2.15 nppiSubC_16u_AC4IRSfs	124
7.10.2.16 nppiSubC_16u_AC4RSfs	125
7.10.2.17 nppiSubC_16u_C1IRSfs	125
7.10.2.18 nppiSubC_16u_C1RSfs	125
7.10.2.19 nppiSubC_16u_C3IRSfs	126
7.10.2.20 nppiSubC_16u_C3RSfs	126
7.10.2.21 nppiSubC_16u_C4IRSfs	127
7.10.2.22 nppiSubC_16u_C4RSfs	127
7.10.2.23 nppiSubC_32f_AC4IR	127
7.10.2.24 nppiSubC_32f_AC4R	128
7.10.2.25 nppiSubC_32f_C1IR	128
7.10.2.26 nppiSubC_32f_C1R	128
7.10.2.27 nppiSubC_32f_C3IR	129
7.10.2.28 nppiSubC_32f_C3R	129
7.10.2.29 nppiSubC_32f_C4IR	129
7.10.2.30 nppiSubC_32f_C4R	130
7.10.2.31 nppiSubC_32fc_AC4IR	130
7.10.2.32 nppiSubC_32fc_AC4R	130
7.10.2.33 nppiSubC_32fc_C1IR	131
7.10.2.34 nppiSubC_32fc_C1R	131
7.10.2.35 nppiSubC_32fc_C3IR	131
7.10.2.36 nppiSubC_32fc_C3R	132
7.10.2.37 nppiSubC_32fc_C4IR	132
7.10.2.38 nppiSubC_32fc_C4R	132
7.10.2.39 nppiSubC_32s_C1IRSfs	133
7.10.2.40 nppiSubC_32s_C1RSfs	133
7.10.2.41 nppiSubC_32s_C3IRSfs	133
7.10.2.42 nppiSubC_32s_C3RSfs	134
7.10.2.43 nppiSubC_32sc_AC4IRSfs	134
7.10.2.44 nppiSubC_32sc_AC4RSfs	135
7.10.2.45 nppiSubC_32sc_C1IRSfs	135
7.10.2.46 nppiSubC_32sc_C1RSfs	135

7.10.2.47	nppiSubC_32sc_C3IRSfs	136
7.10.2.48	nppiSubC_32sc_C3RSfs	136
7.10.2.49	nppiSubC_8u_AC4IRSfs	137
7.10.2.50	nppiSubC_8u_AC4RSfs	137
7.10.2.51	nppiSubC_8u_C1IRSfs	137
7.10.2.52	nppiSubC_8u_C1RSfs	138
7.10.2.53	nppiSubC_8u_C3IRSfs	138
7.10.2.54	nppiSubC_8u_C3RSfs	138
7.10.2.55	nppiSubC_8u_C4IRSfs	139
7.10.2.56	nppiSubC_8u_C4RSfs	139
7.11	DivC	140
7.11.1	Detailed Description	145
7.11.2	Function Documentation	145
7.11.2.1	nppiDivC_16s_AC4IRSfs	145
7.11.2.2	nppiDivC_16s_AC4RSfs	145
7.11.2.3	nppiDivC_16s_C1IRSfs	146
7.11.2.4	nppiDivC_16s_C1RSfs	146
7.11.2.5	nppiDivC_16s_C3IRSfs	146
7.11.2.6	nppiDivC_16s_C3RSfs	147
7.11.2.7	nppiDivC_16s_C4IRSfs	147
7.11.2.8	nppiDivC_16s_C4RSfs	147
7.11.2.9	nppiDivC_16sc_AC4IRSfs	148
7.11.2.10	nppiDivC_16sc_AC4RSfs	148
7.11.2.11	nppiDivC_16sc_C1IRSfs	149
7.11.2.12	nppiDivC_16sc_C1RSfs	149
7.11.2.13	nppiDivC_16sc_C3IRSfs	149
7.11.2.14	nppiDivC_16sc_C3RSfs	150
7.11.2.15	nppiDivC_16u_AC4IRSfs	150
7.11.2.16	nppiDivC_16u_AC4RSfs	151
7.11.2.17	nppiDivC_16u_C1IRSfs	151
7.11.2.18	nppiDivC_16u_C1RSfs	151
7.11.2.19	nppiDivC_16u_C3IRSfs	152
7.11.2.20	nppiDivC_16u_C3RSfs	152
7.11.2.21	nppiDivC_16u_C4IRSfs	153
7.11.2.22	nppiDivC_16u_C4RSfs	153
7.11.2.23	nppiDivC_32f_AC4IR	153

7.11.2.24	<code>nppiDivC_32f_AC4R</code>	154
7.11.2.25	<code>nppiDivC_32f_C1IR</code>	154
7.11.2.26	<code>nppiDivC_32f_C1R</code>	154
7.11.2.27	<code>nppiDivC_32f_C3IR</code>	155
7.11.2.28	<code>nppiDivC_32f_C3R</code>	155
7.11.2.29	<code>nppiDivC_32f_C4IR</code>	155
7.11.2.30	<code>nppiDivC_32f_C4R</code>	156
7.11.2.31	<code>nppiDivC_32fc_AC4IR</code>	156
7.11.2.32	<code>nppiDivC_32fc_AC4R</code>	156
7.11.2.33	<code>nppiDivC_32fc_C1IR</code>	157
7.11.2.34	<code>nppiDivC_32fc_C1R</code>	157
7.11.2.35	<code>nppiDivC_32fc_C3IR</code>	157
7.11.2.36	<code>nppiDivC_32fc_C3R</code>	158
7.11.2.37	<code>nppiDivC_32fc_C4IR</code>	158
7.11.2.38	<code>nppiDivC_32fc_C4R</code>	158
7.11.2.39	<code>nppiDivC_32s_C1IRSfs</code>	159
7.11.2.40	<code>nppiDivC_32s_C1RSfs</code>	159
7.11.2.41	<code>nppiDivC_32s_C3IRSfs</code>	159
7.11.2.42	<code>nppiDivC_32s_C3RSfs</code>	160
7.11.2.43	<code>nppiDivC_32sc_AC4IRSfs</code>	160
7.11.2.44	<code>nppiDivC_32sc_AC4RSfs</code>	161
7.11.2.45	<code>nppiDivC_32sc_C1IRSfs</code>	161
7.11.2.46	<code>nppiDivC_32sc_C1RSfs</code>	161
7.11.2.47	<code>nppiDivC_32sc_C3IRSfs</code>	162
7.11.2.48	<code>nppiDivC_32sc_C3RSfs</code>	162
7.11.2.49	<code>nppiDivC_8u_AC4IRSfs</code>	163
7.11.2.50	<code>nppiDivC_8u_AC4RSfs</code>	163
7.11.2.51	<code>nppiDivC_8u_C1IRSfs</code>	163
7.11.2.52	<code>nppiDivC_8u_C1RSfs</code>	164
7.11.2.53	<code>nppiDivC_8u_C3IRSfs</code>	164
7.11.2.54	<code>nppiDivC_8u_C3RSfs</code>	164
7.11.2.55	<code>nppiDivC_8u_C4IRSfs</code>	165
7.11.2.56	<code>nppiDivC_8u_C4RSfs</code>	165
7.12	<code>AbsDiffC</code>	166
7.12.1	Detailed Description	166
7.12.2	Function Documentation	166

7.12.2.1	nppiAbsDiffC_16u_C1R	166
7.12.2.2	nppiAbsDiffC_32f_C1R	166
7.12.2.3	nppiAbsDiffC_8u_C1R	167
7.13	Add	168
7.13.1	Detailed Description	173
7.13.2	Function Documentation	173
7.13.2.1	nppiAdd_16s_AC4IRSfs	173
7.13.2.2	nppiAdd_16s_AC4RSfs	173
7.13.2.3	nppiAdd_16s_C1IRSfs	174
7.13.2.4	nppiAdd_16s_C1RSfs	174
7.13.2.5	nppiAdd_16s_C3IRSfs	175
7.13.2.6	nppiAdd_16s_C3RSfs	175
7.13.2.7	nppiAdd_16s_C4IRSfs	176
7.13.2.8	nppiAdd_16s_C4RSfs	176
7.13.2.9	nppiAdd_16sc_AC4IRSfs	176
7.13.2.10	nppiAdd_16sc_AC4RSfs	177
7.13.2.11	nppiAdd_16sc_C1IRSfs	177
7.13.2.12	nppiAdd_16sc_C1RSfs	178
7.13.2.13	nppiAdd_16sc_C3IRSfs	178
7.13.2.14	nppiAdd_16sc_C3RSfs	178
7.13.2.15	nppiAdd_16u_AC4IRSfs	179
7.13.2.16	nppiAdd_16u_AC4RSfs	179
7.13.2.17	nppiAdd_16u_C1IRSfs	180
7.13.2.18	nppiAdd_16u_C1RSfs	180
7.13.2.19	nppiAdd_16u_C3IRSfs	181
7.13.2.20	nppiAdd_16u_C3RSfs	181
7.13.2.21	nppiAdd_16u_C4IRSfs	181
7.13.2.22	nppiAdd_16u_C4RSfs	182
7.13.2.23	nppiAdd_32f_AC4IR	182
7.13.2.24	nppiAdd_32f_AC4R	183
7.13.2.25	nppiAdd_32f_C1IR	183
7.13.2.26	nppiAdd_32f_C1R	183
7.13.2.27	nppiAdd_32f_C3IR	184
7.13.2.28	nppiAdd_32f_C3R	184
7.13.2.29	nppiAdd_32f_C4IR	185
7.13.2.30	nppiAdd_32f_C4R	185

7.13.2.31	<code>nppiAdd_32fc_AC4IR</code>	185
7.13.2.32	<code>nppiAdd_32fc_AC4R</code>	186
7.13.2.33	<code>nppiAdd_32fc_C1IR</code>	186
7.13.2.34	<code>nppiAdd_32fc_C1R</code>	186
7.13.2.35	<code>nppiAdd_32fc_C3IR</code>	187
7.13.2.36	<code>nppiAdd_32fc_C3R</code>	187
7.13.2.37	<code>nppiAdd_32fc_C4IR</code>	188
7.13.2.38	<code>nppiAdd_32fc_C4R</code>	188
7.13.2.39	<code>nppiAdd_32s_C1IRSfs</code>	188
7.13.2.40	<code>nppiAdd_32s_C1R</code>	189
7.13.2.41	<code>nppiAdd_32s_C1RSfs</code>	189
7.13.2.42	<code>nppiAdd_32s_C3IRSfs</code>	190
7.13.2.43	<code>nppiAdd_32s_C3RSfs</code>	190
7.13.2.44	<code>nppiAdd_32sc_AC4IRSfs</code>	190
7.13.2.45	<code>nppiAdd_32sc_AC4RSfs</code>	191
7.13.2.46	<code>nppiAdd_32sc_C1IRSfs</code>	191
7.13.2.47	<code>nppiAdd_32sc_C1RSfs</code>	192
7.13.2.48	<code>nppiAdd_32sc_C3IRSfs</code>	192
7.13.2.49	<code>nppiAdd_32sc_C3RSfs</code>	192
7.13.2.50	<code>nppiAdd_8u_AC4IRSfs</code>	193
7.13.2.51	<code>nppiAdd_8u_AC4RSfs</code>	193
7.13.2.52	<code>nppiAdd_8u_C1IRSfs</code>	194
7.13.2.53	<code>nppiAdd_8u_C1RSfs</code>	194
7.13.2.54	<code>nppiAdd_8u_C3IRSfs</code>	195
7.13.2.55	<code>nppiAdd_8u_C3RSfs</code>	195
7.13.2.56	<code>nppiAdd_8u_C4IRSfs</code>	195
7.13.2.57	<code>nppiAdd_8u_C4RSfs</code>	196
7.14	<code>AddSquare</code>	197
7.14.1	Detailed Description	197
7.14.2	Function Documentation	197
7.14.2.1	<code>nppiAddSquare_16u32f_C1IMR</code>	197
7.14.2.2	<code>nppiAddSquare_16u32f_C1IR</code>	198
7.14.2.3	<code>nppiAddSquare_32f_C1IMR</code>	198
7.14.2.4	<code>nppiAddSquare_32f_C1IR</code>	199
7.14.2.5	<code>nppiAddSquare_8u32f_C1IMR</code>	199
7.14.2.6	<code>nppiAddSquare_8u32f_C1IR</code>	199

7.15	AddProduct	200
7.15.1	Detailed Description	200
7.15.2	Function Documentation	200
7.15.2.1	nppiAddProduct_16u32f_C1IMR	200
7.15.2.2	nppiAddProduct_16u32f_C1IR	201
7.15.2.3	nppiAddProduct_32f_C1IMR	201
7.15.2.4	nppiAddProduct_32f_C1IR	202
7.15.2.5	nppiAddProduct_8u32f_C1IMR	202
7.15.2.6	nppiAddProduct_8u32f_C1IR	203
7.16	AddWeighted	204
7.16.1	Detailed Description	204
7.16.2	Function Documentation	204
7.16.2.1	nppiAddWeighted_16u32f_C1IMR	204
7.16.2.2	nppiAddWeighted_16u32f_C1IR	205
7.16.2.3	nppiAddWeighted_32f_C1IMR	205
7.16.2.4	nppiAddWeighted_32f_C1IR	206
7.16.2.5	nppiAddWeighted_8u32f_C1IMR	206
7.16.2.6	nppiAddWeighted_8u32f_C1IR	207
7.17	Mul	208
7.17.1	Detailed Description	213
7.17.2	Function Documentation	213
7.17.2.1	nppiMul_16s_AC4IRSfs	213
7.17.2.2	nppiMul_16s_AC4RSfs	214
7.17.2.3	nppiMul_16s_C1IRSfs	214
7.17.2.4	nppiMul_16s_C1RSfs	214
7.17.2.5	nppiMul_16s_C3IRSfs	215
7.17.2.6	nppiMul_16s_C3RSfs	215
7.17.2.7	nppiMul_16s_C4IRSfs	216
7.17.2.8	nppiMul_16s_C4RSfs	216
7.17.2.9	nppiMul_16sc_AC4IRSfs	216
7.17.2.10	nppiMul_16sc_AC4RSfs	217
7.17.2.11	nppiMul_16sc_C1IRSfs	217
7.17.2.12	nppiMul_16sc_C1RSfs	218
7.17.2.13	nppiMul_16sc_C3IRSfs	218
7.17.2.14	nppiMul_16sc_C3RSfs	218
7.17.2.15	nppiMul_16u_AC4IRSfs	219

7.17.2.16	nppiMul_16u_AC4RSfs	219
7.17.2.17	nppiMul_16u_C1IRSfs	220
7.17.2.18	nppiMul_16u_C1RSfs	220
7.17.2.19	nppiMul_16u_C3IRSfs	221
7.17.2.20	nppiMul_16u_C3RSfs	221
7.17.2.21	nppiMul_16u_C4IRSfs	221
7.17.2.22	nppiMul_16u_C4RSfs	222
7.17.2.23	nppiMul_32f_AC4IR	222
7.17.2.24	nppiMul_32f_AC4R	223
7.17.2.25	nppiMul_32f_C1IR	223
7.17.2.26	nppiMul_32f_C1R	223
7.17.2.27	nppiMul_32f_C3IR	224
7.17.2.28	nppiMul_32f_C3R	224
7.17.2.29	nppiMul_32f_C4IR	225
7.17.2.30	nppiMul_32f_C4R	225
7.17.2.31	nppiMul_32fc_AC4IR	225
7.17.2.32	nppiMul_32fc_AC4R	226
7.17.2.33	nppiMul_32fc_C1IR	226
7.17.2.34	nppiMul_32fc_C1R	226
7.17.2.35	nppiMul_32fc_C3IR	227
7.17.2.36	nppiMul_32fc_C3R	227
7.17.2.37	nppiMul_32fc_C4IR	228
7.17.2.38	nppiMul_32fc_C4R	228
7.17.2.39	nppiMul_32s_C1IRSfs	228
7.17.2.40	nppiMul_32s_C1R	229
7.17.2.41	nppiMul_32s_C1RSfs	229
7.17.2.42	nppiMul_32s_C3IRSfs	230
7.17.2.43	nppiMul_32s_C3RSfs	230
7.17.2.44	nppiMul_32sc_AC4IRSfs	230
7.17.2.45	nppiMul_32sc_AC4RSfs	231
7.17.2.46	nppiMul_32sc_C1IRSfs	231
7.17.2.47	nppiMul_32sc_C1RSfs	232
7.17.2.48	nppiMul_32sc_C3IRSfs	232
7.17.2.49	nppiMul_32sc_C3RSfs	232
7.17.2.50	nppiMul_8u_AC4IRSfs	233
7.17.2.51	nppiMul_8u_AC4RSfs	233

7.17.2.52	nppiMul_8u_C1RSfs	234
7.17.2.53	nppiMul_8u_C1RSfs	234
7.17.2.54	nppiMul_8u_C3RSfs	235
7.17.2.55	nppiMul_8u_C3RSfs	235
7.17.2.56	nppiMul_8u_C4RSfs	235
7.17.2.57	nppiMul_8u_C4RSfs	236
7.18	MulScale	237
7.18.1	Detailed Description	238
7.18.2	Function Documentation	238
7.18.2.1	nppiMulScale_16u_AC4IR	238
7.18.2.2	nppiMulScale_16u_AC4R	239
7.18.2.3	nppiMulScale_16u_C1IR	239
7.18.2.4	nppiMulScale_16u_C1R	240
7.18.2.5	nppiMulScale_16u_C3IR	240
7.18.2.6	nppiMulScale_16u_C3R	240
7.18.2.7	nppiMulScale_16u_C4IR	241
7.18.2.8	nppiMulScale_16u_C4R	241
7.18.2.9	nppiMulScale_8u_AC4IR	242
7.18.2.10	nppiMulScale_8u_AC4R	242
7.18.2.11	nppiMulScale_8u_C1IR	242
7.18.2.12	nppiMulScale_8u_C1R	243
7.18.2.13	nppiMulScale_8u_C3IR	243
7.18.2.14	nppiMulScale_8u_C3R	244
7.18.2.15	nppiMulScale_8u_C4IR	244
7.18.2.16	nppiMulScale_8u_C4R	244
7.19	Sub	246
7.19.1	Detailed Description	251
7.19.2	Function Documentation	251
7.19.2.1	nppiSub_16s_AC4IRSfs	251
7.19.2.2	nppiSub_16s_AC4RSfs	252
7.19.2.3	nppiSub_16s_C1IRSfs	252
7.19.2.4	nppiSub_16s_C1RSfs	253
7.19.2.5	nppiSub_16s_C3IRSfs	253
7.19.2.6	nppiSub_16s_C3RSfs	253
7.19.2.7	nppiSub_16s_C4IRSfs	254
7.19.2.8	nppiSub_16s_C4RSfs	254

7.19.2.9	nppiSub_16sc_AC4IRSfs	255
7.19.2.10	nppiSub_16sc_AC4RSfs	255
7.19.2.11	nppiSub_16sc_C1IRSfs	255
7.19.2.12	nppiSub_16sc_C1RSfs	256
7.19.2.13	nppiSub_16sc_C3IRSfs	256
7.19.2.14	nppiSub_16sc_C3RSfs	257
7.19.2.15	nppiSub_16u_AC4IRSfs	257
7.19.2.16	nppiSub_16u_AC4RSfs	257
7.19.2.17	nppiSub_16u_C1IRSfs	258
7.19.2.18	nppiSub_16u_C1RSfs	258
7.19.2.19	nppiSub_16u_C3IRSfs	259
7.19.2.20	nppiSub_16u_C3RSfs	259
7.19.2.21	nppiSub_16u_C4IRSfs	260
7.19.2.22	nppiSub_16u_C4RSfs	260
7.19.2.23	nppiSub_32f_AC4IR	260
7.19.2.24	nppiSub_32f_AC4R	261
7.19.2.25	nppiSub_32f_C1IR	261
7.19.2.26	nppiSub_32f_C1R	262
7.19.2.27	nppiSub_32f_C3IR	262
7.19.2.28	nppiSub_32f_C3R	262
7.19.2.29	nppiSub_32f_C4IR	263
7.19.2.30	nppiSub_32f_C4R	263
7.19.2.31	nppiSub_32fc_AC4IR	264
7.19.2.32	nppiSub_32fc_AC4R	264
7.19.2.33	nppiSub_32fc_C1IR	264
7.19.2.34	nppiSub_32fc_C1R	265
7.19.2.35	nppiSub_32fc_C3IR	265
7.19.2.36	nppiSub_32fc_C3R	266
7.19.2.37	nppiSub_32fc_C4IR	266
7.19.2.38	nppiSub_32fc_C4R	266
7.19.2.39	nppiSub_32s_C1IRSfs	267
7.19.2.40	nppiSub_32s_C1R	267
7.19.2.41	nppiSub_32s_C1RSfs	268
7.19.2.42	nppiSub_32s_C3IRSfs	268
7.19.2.43	nppiSub_32s_C3RSfs	268
7.19.2.44	nppiSub_32s_C4IRSfs	269

7.19.2.45	nppiSub_32s_C4RSfs	269
7.19.2.46	nppiSub_32sc_AC4IRSfs	270
7.19.2.47	nppiSub_32sc_AC4RSfs	270
7.19.2.48	nppiSub_32sc_C1IRSfs	271
7.19.2.49	nppiSub_32sc_C1RSfs	271
7.19.2.50	nppiSub_32sc_C3IRSfs	271
7.19.2.51	nppiSub_32sc_C3RSfs	272
7.19.2.52	nppiSub_8u_AC4IRSfs	272
7.19.2.53	nppiSub_8u_AC4RSfs	273
7.19.2.54	nppiSub_8u_C1IRSfs	273
7.19.2.55	nppiSub_8u_C1RSfs	273
7.19.2.56	nppiSub_8u_C3IRSfs	274
7.19.2.57	nppiSub_8u_C3RSfs	274
7.19.2.58	nppiSub_8u_C4IRSfs	275
7.19.2.59	nppiSub_8u_C4RSfs	275
7.20	Div	276
7.20.1	Detailed Description	281
7.20.2	Function Documentation	281
7.20.2.1	nppiDiv_16s_AC4IRSfs	281
7.20.2.2	nppiDiv_16s_AC4RSfs	281
7.20.2.3	nppiDiv_16s_C1IRSfs	282
7.20.2.4	nppiDiv_16s_C1RSfs	282
7.20.2.5	nppiDiv_16s_C3IRSfs	283
7.20.2.6	nppiDiv_16s_C3RSfs	283
7.20.2.7	nppiDiv_16s_C4IRSfs	283
7.20.2.8	nppiDiv_16s_C4RSfs	284
7.20.2.9	nppiDiv_16sc_AC4IRSfs	284
7.20.2.10	nppiDiv_16sc_AC4RSfs	285
7.20.2.11	nppiDiv_16sc_C1IRSfs	285
7.20.2.12	nppiDiv_16sc_C1RSfs	285
7.20.2.13	nppiDiv_16sc_C3IRSfs	286
7.20.2.14	nppiDiv_16sc_C3RSfs	286
7.20.2.15	nppiDiv_16u_AC4IRSfs	287
7.20.2.16	nppiDiv_16u_AC4RSfs	287
7.20.2.17	nppiDiv_16u_C1IRSfs	288
7.20.2.18	nppiDiv_16u_C1RSfs	288

7.20.2.19 nppiDiv_16u_C3IRSfs	288
7.20.2.20 nppiDiv_16u_C3RSfs	289
7.20.2.21 nppiDiv_16u_C4IRSfs	289
7.20.2.22 nppiDiv_16u_C4RSfs	290
7.20.2.23 nppiDiv_32f_AC4IR	290
7.20.2.24 nppiDiv_32f_AC4R	290
7.20.2.25 nppiDiv_32f_C1IR	291
7.20.2.26 nppiDiv_32f_C1R	291
7.20.2.27 nppiDiv_32f_C3IR	292
7.20.2.28 nppiDiv_32f_C3R	292
7.20.2.29 nppiDiv_32f_C4IR	292
7.20.2.30 nppiDiv_32f_C4R	293
7.20.2.31 nppiDiv_32fc_AC4IR	293
7.20.2.32 nppiDiv_32fc_AC4R	293
7.20.2.33 nppiDiv_32fc_C1IR	294
7.20.2.34 nppiDiv_32fc_C1R	294
7.20.2.35 nppiDiv_32fc_C3IR	295
7.20.2.36 nppiDiv_32fc_C3R	295
7.20.2.37 nppiDiv_32fc_C4IR	295
7.20.2.38 nppiDiv_32fc_C4R	296
7.20.2.39 nppiDiv_32s_C1IRSfs	296
7.20.2.40 nppiDiv_32s_C1R	296
7.20.2.41 nppiDiv_32s_C1RSfs	297
7.20.2.42 nppiDiv_32s_C3IRSfs	297
7.20.2.43 nppiDiv_32s_C3RSfs	298
7.20.2.44 nppiDiv_32sc_AC4IRSfs	298
7.20.2.45 nppiDiv_32sc_AC4RSfs	298
7.20.2.46 nppiDiv_32sc_C1IRSfs	299
7.20.2.47 nppiDiv_32sc_C1RSfs	299
7.20.2.48 nppiDiv_32sc_C3IRSfs	300
7.20.2.49 nppiDiv_32sc_C3RSfs	300
7.20.2.50 nppiDiv_8u_AC4IRSfs	301
7.20.2.51 nppiDiv_8u_AC4RSfs	301
7.20.2.52 nppiDiv_8u_C1IRSfs	301
7.20.2.53 nppiDiv_8u_C1RSfs	302
7.20.2.54 nppiDiv_8u_C3IRSfs	302

7.20.2.55	nppiDiv_8u_C3RSfs	303
7.20.2.56	nppiDiv_8u_C4IRSfs	303
7.20.2.57	nppiDiv_8u_C4RSfs	303
7.21	Div_Round	305
7.21.1	Detailed Description	307
7.21.2	Function Documentation	307
7.21.2.1	nppiDiv_Round_16s_AC4IRSfs	307
7.21.2.2	nppiDiv_Round_16s_AC4RSfs	308
7.21.2.3	nppiDiv_Round_16s_C1IRSfs	308
7.21.2.4	nppiDiv_Round_16s_C1RSfs	309
7.21.2.5	nppiDiv_Round_16s_C3IRSfs	309
7.21.2.6	nppiDiv_Round_16s_C3RSfs	310
7.21.2.7	nppiDiv_Round_16s_C4IRSfs	310
7.21.2.8	nppiDiv_Round_16s_C4RSfs	311
7.21.2.9	nppiDiv_Round_16u_AC4IRSfs	311
7.21.2.10	nppiDiv_Round_16u_AC4RSfs	312
7.21.2.11	nppiDiv_Round_16u_C1IRSfs	312
7.21.2.12	nppiDiv_Round_16u_C1RSfs	313
7.21.2.13	nppiDiv_Round_16u_C3IRSfs	313
7.21.2.14	nppiDiv_Round_16u_C3RSfs	314
7.21.2.15	nppiDiv_Round_16u_C4IRSfs	314
7.21.2.16	nppiDiv_Round_16u_C4RSfs	315
7.21.2.17	nppiDiv_Round_8u_AC4IRSfs	315
7.21.2.18	nppiDiv_Round_8u_AC4RSfs	316
7.21.2.19	nppiDiv_Round_8u_C1IRSfs	316
7.21.2.20	nppiDiv_Round_8u_C1RSfs	317
7.21.2.21	nppiDiv_Round_8u_C3IRSfs	317
7.21.2.22	nppiDiv_Round_8u_C3RSfs	318
7.21.2.23	nppiDiv_Round_8u_C4IRSfs	318
7.21.2.24	nppiDiv_Round_8u_C4RSfs	319
7.22	Abs	320
7.22.1	Detailed Description	321
7.22.2	Function Documentation	321
7.22.2.1	nppiAbs_16s_AC4IR	321
7.22.2.2	nppiAbs_16s_AC4R	321
7.22.2.3	nppiAbs_16s_C1IR	322

7.22.2.4	nppiAbs_16s_C1R	322
7.22.2.5	nppiAbs_16s_C3IR	322
7.22.2.6	nppiAbs_16s_C3R	323
7.22.2.7	nppiAbs_16s_C4IR	323
7.22.2.8	nppiAbs_16s_C4R	323
7.22.2.9	nppiAbs_32f_AC4IR	324
7.22.2.10	nppiAbs_32f_AC4R	324
7.22.2.11	nppiAbs_32f_C1IR	324
7.22.2.12	nppiAbs_32f_C1R	325
7.22.2.13	nppiAbs_32f_C3IR	325
7.22.2.14	nppiAbs_32f_C3R	325
7.22.2.15	nppiAbs_32f_C4IR	326
7.22.2.16	nppiAbs_32f_C4R	326
7.23	AbsDiff	327
7.23.1	Detailed Description	327
7.23.2	Function Documentation	327
7.23.2.1	nppiAbsDiff_16u_C1R	327
7.23.2.2	nppiAbsDiff_32f_C1R	328
7.23.2.3	nppiAbsDiff_8u_C1R	328
7.23.2.4	nppiAbsDiff_8u_C3R	328
7.23.2.5	nppiAbsDiff_8u_C4R	329
7.24	Sqr	330
7.24.1	Detailed Description	332
7.24.2	Function Documentation	333
7.24.2.1	nppiSqr_16s_AC4IRSfs	333
7.24.2.2	nppiSqr_16s_AC4RSfs	333
7.24.2.3	nppiSqr_16s_C1IRSfs	333
7.24.2.4	nppiSqr_16s_C1RSfs	334
7.24.2.5	nppiSqr_16s_C3IRSfs	334
7.24.2.6	nppiSqr_16s_C3RSfs	334
7.24.2.7	nppiSqr_16s_C4IRSfs	335
7.24.2.8	nppiSqr_16s_C4RSfs	335
7.24.2.9	nppiSqr_16u_AC4IRSfs	335
7.24.2.10	nppiSqr_16u_AC4RSfs	336
7.24.2.11	nppiSqr_16u_C1IRSfs	336
7.24.2.12	nppiSqr_16u_C1RSfs	336

7.24.2.13	nppiSqr_16u_C3IRSfs	337
7.24.2.14	nppiSqr_16u_C3RSfs	337
7.24.2.15	nppiSqr_16u_C4IRSfs	337
7.24.2.16	nppiSqr_16u_C4RSfs	338
7.24.2.17	nppiSqr_32f_AC4IR	338
7.24.2.18	nppiSqr_32f_AC4R	338
7.24.2.19	nppiSqr_32f_C1IR	339
7.24.2.20	nppiSqr_32f_C1R	339
7.24.2.21	nppiSqr_32f_C3IR	339
7.24.2.22	nppiSqr_32f_C3R	340
7.24.2.23	nppiSqr_32f_C4IR	340
7.24.2.24	nppiSqr_32f_C4R	340
7.24.2.25	nppiSqr_8u_AC4IRSfs	341
7.24.2.26	nppiSqr_8u_AC4RSfs	341
7.24.2.27	nppiSqr_8u_C1IRSfs	341
7.24.2.28	nppiSqr_8u_C1RSfs	342
7.24.2.29	nppiSqr_8u_C3IRSfs	342
7.24.2.30	nppiSqr_8u_C3RSfs	342
7.24.2.31	nppiSqr_8u_C4IRSfs	343
7.24.2.32	nppiSqr_8u_C4RSfs	343
7.25	Sqrt	344
7.25.1	Detailed Description	346
7.25.2	Function Documentation	346
7.25.2.1	nppiSqrt_16s_AC4IRSfs	346
7.25.2.2	nppiSqrt_16s_AC4RSfs	347
7.25.2.3	nppiSqrt_16s_C1IRSfs	347
7.25.2.4	nppiSqrt_16s_C1RSfs	347
7.25.2.5	nppiSqrt_16s_C3IRSfs	348
7.25.2.6	nppiSqrt_16s_C3RSfs	348
7.25.2.7	nppiSqrt_16u_AC4IRSfs	348
7.25.2.8	nppiSqrt_16u_AC4RSfs	349
7.25.2.9	nppiSqrt_16u_C1IRSfs	349
7.25.2.10	nppiSqrt_16u_C1RSfs	350
7.25.2.11	nppiSqrt_16u_C3IRSfs	350
7.25.2.12	nppiSqrt_16u_C3RSfs	350
7.25.2.13	nppiSqrt_32f_AC4IR	351

7.25.2.14	nppiSqrt_32f_AC4R	351
7.25.2.15	nppiSqrt_32f_C1IR	351
7.25.2.16	nppiSqrt_32f_C1R	352
7.25.2.17	nppiSqrt_32f_C3IR	352
7.25.2.18	nppiSqrt_32f_C3R	352
7.25.2.19	nppiSqrt_32f_C4IR	353
7.25.2.20	nppiSqrt_32f_C4R	353
7.25.2.21	nppiSqrt_8u_AC4IRSfs	353
7.25.2.22	nppiSqrt_8u_AC4RSfs	354
7.25.2.23	nppiSqrt_8u_C1IRSfs	354
7.25.2.24	nppiSqrt_8u_C1RSfs	354
7.25.2.25	nppiSqrt_8u_C3IRSfs	355
7.25.2.26	nppiSqrt_8u_C3RSfs	355
7.26	Ln	356
7.26.1	Detailed Description	357
7.26.2	Function Documentation	357
7.26.2.1	nppiLn_16s_C1IRSfs	357
7.26.2.2	nppiLn_16s_C1RSfs	358
7.26.2.3	nppiLn_16s_C3IRSfs	358
7.26.2.4	nppiLn_16s_C3RSfs	358
7.26.2.5	nppiLn_16u_C1IRSfs	359
7.26.2.6	nppiLn_16u_C1RSfs	359
7.26.2.7	nppiLn_16u_C3IRSfs	359
7.26.2.8	nppiLn_16u_C3RSfs	360
7.26.2.9	nppiLn_32f_C1IR	360
7.26.2.10	nppiLn_32f_C1R	360
7.26.2.11	nppiLn_32f_C3IR	361
7.26.2.12	nppiLn_32f_C3R	361
7.26.2.13	nppiLn_8u_C1IRSfs	361
7.26.2.14	nppiLn_8u_C1RSfs	362
7.26.2.15	nppiLn_8u_C3IRSfs	362
7.26.2.16	nppiLn_8u_C3RSfs	362
7.27	Exp	363
7.27.1	Detailed Description	364
7.27.2	Function Documentation	364
7.27.2.1	nppiExp_16s_C1IRSfs	364

7.27.2.2	nppiExp_16s_C1RSfs	365
7.27.2.3	nppiExp_16s_C3IRSfs	365
7.27.2.4	nppiExp_16s_C3RSfs	365
7.27.2.5	nppiExp_16u_C1IRSfs	366
7.27.2.6	nppiExp_16u_C1RSfs	366
7.27.2.7	nppiExp_16u_C3IRSfs	366
7.27.2.8	nppiExp_16u_C3RSfs	367
7.27.2.9	nppiExp_32f_C1IR	367
7.27.2.10	nppiExp_32f_C1R	367
7.27.2.11	nppiExp_32f_C3IR	368
7.27.2.12	nppiExp_32f_C3R	368
7.27.2.13	nppiExp_8u_C1IRSfs	368
7.27.2.14	nppiExp_8u_C1RSfs	369
7.27.2.15	nppiExp_8u_C3IRSfs	369
7.27.2.16	nppiExp_8u_C3RSfs	369
7.28	Logical Operations	370
7.29	AndC	371
7.29.1	Detailed Description	373
7.29.2	Function Documentation	373
7.29.2.1	nppiAndC_16u_AC4IR	373
7.29.2.2	nppiAndC_16u_AC4R	373
7.29.2.3	nppiAndC_16u_C1IR	373
7.29.2.4	nppiAndC_16u_C1R	374
7.29.2.5	nppiAndC_16u_C3IR	374
7.29.2.6	nppiAndC_16u_C3R	374
7.29.2.7	nppiAndC_16u_C4IR	375
7.29.2.8	nppiAndC_16u_C4R	375
7.29.2.9	nppiAndC_32s_AC4IR	376
7.29.2.10	nppiAndC_32s_AC4R	376
7.29.2.11	nppiAndC_32s_C1IR	376
7.29.2.12	nppiAndC_32s_C1R	377
7.29.2.13	nppiAndC_32s_C3IR	377
7.29.2.14	nppiAndC_32s_C3R	377
7.29.2.15	nppiAndC_32s_C4IR	378
7.29.2.16	nppiAndC_32s_C4R	378
7.29.2.17	nppiAndC_8u_AC4IR	378

7.29.2.18	nppiAndC_8u_AC4R	379
7.29.2.19	nppiAndC_8u_C1IR	379
7.29.2.20	nppiAndC_8u_C1R	379
7.29.2.21	nppiAndC_8u_C3IR	380
7.29.2.22	nppiAndC_8u_C3R	380
7.29.2.23	nppiAndC_8u_C4IR	380
7.29.2.24	nppiAndC_8u_C4R	381
7.30	OrC	382
7.30.1	Detailed Description	384
7.30.2	Function Documentation	384
7.30.2.1	nppiOrC_16u_AC4IR	384
7.30.2.2	nppiOrC_16u_AC4R	384
7.30.2.3	nppiOrC_16u_C1IR	384
7.30.2.4	nppiOrC_16u_C1R	385
7.30.2.5	nppiOrC_16u_C3IR	385
7.30.2.6	nppiOrC_16u_C3R	385
7.30.2.7	nppiOrC_16u_C4IR	386
7.30.2.8	nppiOrC_16u_C4R	386
7.30.2.9	nppiOrC_32s_AC4IR	387
7.30.2.10	nppiOrC_32s_AC4R	387
7.30.2.11	nppiOrC_32s_C1IR	387
7.30.2.12	nppiOrC_32s_C1R	388
7.30.2.13	nppiOrC_32s_C3IR	388
7.30.2.14	nppiOrC_32s_C3R	388
7.30.2.15	nppiOrC_32s_C4IR	389
7.30.2.16	nppiOrC_32s_C4R	389
7.30.2.17	nppiOrC_8u_AC4IR	389
7.30.2.18	nppiOrC_8u_AC4R	390
7.30.2.19	nppiOrC_8u_C1IR	390
7.30.2.20	nppiOrC_8u_C1R	390
7.30.2.21	nppiOrC_8u_C3IR	391
7.30.2.22	nppiOrC_8u_C3R	391
7.30.2.23	nppiOrC_8u_C4IR	391
7.30.2.24	nppiOrC_8u_C4R	392
7.31	XorC	393
7.31.1	Detailed Description	395

7.31.2	Function Documentation	395
7.31.2.1	nppiXorC_16u_AC4IR	395
7.31.2.2	nppiXorC_16u_AC4R	395
7.31.2.3	nppiXorC_16u_C1IR	395
7.31.2.4	nppiXorC_16u_C1R	396
7.31.2.5	nppiXorC_16u_C3IR	396
7.31.2.6	nppiXorC_16u_C3R	396
7.31.2.7	nppiXorC_16u_C4IR	397
7.31.2.8	nppiXorC_16u_C4R	397
7.31.2.9	nppiXorC_32s_AC4IR	398
7.31.2.10	nppiXorC_32s_AC4R	398
7.31.2.11	nppiXorC_32s_C1IR	398
7.31.2.12	nppiXorC_32s_C1R	399
7.31.2.13	nppiXorC_32s_C3IR	399
7.31.2.14	nppiXorC_32s_C3R	399
7.31.2.15	nppiXorC_32s_C4IR	400
7.31.2.16	nppiXorC_32s_C4R	400
7.31.2.17	nppiXorC_8u_AC4IR	400
7.31.2.18	nppiXorC_8u_AC4R	401
7.31.2.19	nppiXorC_8u_C1IR	401
7.31.2.20	nppiXorC_8u_C1R	401
7.31.2.21	nppiXorC_8u_C3IR	402
7.31.2.22	nppiXorC_8u_C3R	402
7.31.2.23	nppiXorC_8u_C4IR	402
7.31.2.24	nppiXorC_8u_C4R	403
7.32	RShiftC	404
7.32.1	Detailed Description	407
7.32.2	Function Documentation	407
7.32.2.1	nppiRShiftC_16s_AC4IR	407
7.32.2.2	nppiRShiftC_16s_AC4R	407
7.32.2.3	nppiRShiftC_16s_C1IR	408
7.32.2.4	nppiRShiftC_16s_C1R	408
7.32.2.5	nppiRShiftC_16s_C3IR	408
7.32.2.6	nppiRShiftC_16s_C3R	409
7.32.2.7	nppiRShiftC_16s_C4IR	409
7.32.2.8	nppiRShiftC_16s_C4R	409

7.32.2.9	nppiRShiftC_16u_AC4IR	410
7.32.2.10	nppiRShiftC_16u_AC4R	410
7.32.2.11	nppiRShiftC_16u_C1IR	411
7.32.2.12	nppiRShiftC_16u_C1R	411
7.32.2.13	nppiRShiftC_16u_C3IR	411
7.32.2.14	nppiRShiftC_16u_C3R	412
7.32.2.15	nppiRShiftC_16u_C4IR	412
7.32.2.16	nppiRShiftC_16u_C4R	412
7.32.2.17	nppiRShiftC_32s_AC4IR	413
7.32.2.18	nppiRShiftC_32s_AC4R	413
7.32.2.19	nppiRShiftC_32s_C1IR	413
7.32.2.20	nppiRShiftC_32s_C1R	414
7.32.2.21	nppiRShiftC_32s_C3IR	414
7.32.2.22	nppiRShiftC_32s_C3R	414
7.32.2.23	nppiRShiftC_32s_C4IR	415
7.32.2.24	nppiRShiftC_32s_C4R	415
7.32.2.25	nppiRShiftC_8s_AC4IR	415
7.32.2.26	nppiRShiftC_8s_AC4R	416
7.32.2.27	nppiRShiftC_8s_C1IR	416
7.32.2.28	nppiRShiftC_8s_C1R	416
7.32.2.29	nppiRShiftC_8s_C3IR	417
7.32.2.30	nppiRShiftC_8s_C3R	417
7.32.2.31	nppiRShiftC_8s_C4IR	417
7.32.2.32	nppiRShiftC_8s_C4R	418
7.32.2.33	nppiRShiftC_8u_AC4IR	418
7.32.2.34	nppiRShiftC_8u_AC4R	418
7.32.2.35	nppiRShiftC_8u_C1IR	419
7.32.2.36	nppiRShiftC_8u_C1R	419
7.32.2.37	nppiRShiftC_8u_C3IR	419
7.32.2.38	nppiRShiftC_8u_C3R	420
7.32.2.39	nppiRShiftC_8u_C4IR	420
7.32.2.40	nppiRShiftC_8u_C4R	420
7.33	LShiftC	421
7.33.1	Detailed Description	423
7.33.2	Function Documentation	423
7.33.2.1	nppiLShiftC_16u_AC4IR	423

7.33.2.2	nppiLShiftC_16u_AC4R	423
7.33.2.3	nppiLShiftC_16u_C1IR	423
7.33.2.4	nppiLShiftC_16u_C1R	424
7.33.2.5	nppiLShiftC_16u_C3IR	424
7.33.2.6	nppiLShiftC_16u_C3R	424
7.33.2.7	nppiLShiftC_16u_C4IR	425
7.33.2.8	nppiLShiftC_16u_C4R	425
7.33.2.9	nppiLShiftC_32s_AC4IR	426
7.33.2.10	nppiLShiftC_32s_AC4R	426
7.33.2.11	nppiLShiftC_32s_C1IR	426
7.33.2.12	nppiLShiftC_32s_C1R	427
7.33.2.13	nppiLShiftC_32s_C3IR	427
7.33.2.14	nppiLShiftC_32s_C3R	427
7.33.2.15	nppiLShiftC_32s_C4IR	428
7.33.2.16	nppiLShiftC_32s_C4R	428
7.33.2.17	nppiLShiftC_8u_AC4IR	428
7.33.2.18	nppiLShiftC_8u_AC4R	429
7.33.2.19	nppiLShiftC_8u_C1IR	429
7.33.2.20	nppiLShiftC_8u_C1R	429
7.33.2.21	nppiLShiftC_8u_C3IR	430
7.33.2.22	nppiLShiftC_8u_C3R	430
7.33.2.23	nppiLShiftC_8u_C4IR	430
7.33.2.24	nppiLShiftC_8u_C4R	431
7.34	And	432
7.34.1	Detailed Description	434
7.34.2	Function Documentation	434
7.34.2.1	nppiAnd_16u_AC4IR	434
7.34.2.2	nppiAnd_16u_AC4R	434
7.34.2.3	nppiAnd_16u_C1IR	434
7.34.2.4	nppiAnd_16u_C1R	435
7.34.2.5	nppiAnd_16u_C3IR	435
7.34.2.6	nppiAnd_16u_C3R	436
7.34.2.7	nppiAnd_16u_C4IR	436
7.34.2.8	nppiAnd_16u_C4R	436
7.34.2.9	nppiAnd_32s_AC4IR	437
7.34.2.10	nppiAnd_32s_AC4R	437

7.34.2.11	nppiAnd_32s_C1IR	438
7.34.2.12	nppiAnd_32s_C1R	438
7.34.2.13	nppiAnd_32s_C3IR	438
7.34.2.14	nppiAnd_32s_C3R	439
7.34.2.15	nppiAnd_32s_C4IR	439
7.34.2.16	nppiAnd_32s_C4R	439
7.34.2.17	nppiAnd_8u_AC4IR	440
7.34.2.18	nppiAnd_8u_AC4R	440
7.34.2.19	nppiAnd_8u_C1IR	441
7.34.2.20	nppiAnd_8u_C1R	441
7.34.2.21	nppiAnd_8u_C3IR	441
7.34.2.22	nppiAnd_8u_C3R	442
7.34.2.23	nppiAnd_8u_C4IR	442
7.34.2.24	nppiAnd_8u_C4R	442
7.35	Or	444
7.35.1	Detailed Description	446
7.35.2	Function Documentation	446
7.35.2.1	nppiOr_16u_AC4IR	446
7.35.2.2	nppiOr_16u_AC4R	446
7.35.2.3	nppiOr_16u_C1IR	446
7.35.2.4	nppiOr_16u_C1R	447
7.35.2.5	nppiOr_16u_C3IR	447
7.35.2.6	nppiOr_16u_C3R	448
7.35.2.7	nppiOr_16u_C4IR	448
7.35.2.8	nppiOr_16u_C4R	448
7.35.2.9	nppiOr_32s_AC4IR	449
7.35.2.10	nppiOr_32s_AC4R	449
7.35.2.11	nppiOr_32s_C1IR	450
7.35.2.12	nppiOr_32s_C1R	450
7.35.2.13	nppiOr_32s_C3IR	450
7.35.2.14	nppiOr_32s_C3R	451
7.35.2.15	nppiOr_32s_C4IR	451
7.35.2.16	nppiOr_32s_C4R	451
7.35.2.17	nppiOr_8u_AC4IR	452
7.35.2.18	nppiOr_8u_AC4R	452
7.35.2.19	nppiOr_8u_C1IR	453

7.35.2.20	nppiOr_8u_C1R	453
7.35.2.21	nppiOr_8u_C3IR	453
7.35.2.22	nppiOr_8u_C3R	454
7.35.2.23	nppiOr_8u_C4IR	454
7.35.2.24	nppiOr_8u_C4R	454
7.36	Xor	456
7.36.1	Detailed Description	458
7.36.2	Function Documentation	458
7.36.2.1	nppiXor_16u_AC4IR	458
7.36.2.2	nppiXor_16u_AC4R	458
7.36.2.3	nppiXor_16u_C1IR	458
7.36.2.4	nppiXor_16u_C1R	459
7.36.2.5	nppiXor_16u_C3IR	459
7.36.2.6	nppiXor_16u_C3R	460
7.36.2.7	nppiXor_16u_C4IR	460
7.36.2.8	nppiXor_16u_C4R	460
7.36.2.9	nppiXor_32s_AC4IR	461
7.36.2.10	nppiXor_32s_AC4R	461
7.36.2.11	nppiXor_32s_C1IR	462
7.36.2.12	nppiXor_32s_C1R	462
7.36.2.13	nppiXor_32s_C3IR	462
7.36.2.14	nppiXor_32s_C3R	463
7.36.2.15	nppiXor_32s_C4IR	463
7.36.2.16	nppiXor_32s_C4R	463
7.36.2.17	nppiXor_8u_AC4IR	464
7.36.2.18	nppiXor_8u_AC4R	464
7.36.2.19	nppiXor_8u_C1IR	465
7.36.2.20	nppiXor_8u_C1R	465
7.36.2.21	nppiXor_8u_C3IR	465
7.36.2.22	nppiXor_8u_C3R	466
7.36.2.23	nppiXor_8u_C4IR	466
7.36.2.24	nppiXor_8u_C4R	466
7.37	Not	468
7.37.1	Detailed Description	468
7.37.2	Function Documentation	468
7.37.2.1	nppiNot_8u_AC4IR	468

7.37.2.2	nppiNot_8u_AC4R	469
7.37.2.3	nppiNot_8u_C1IR	469
7.37.2.4	nppiNot_8u_C1R	469
7.37.2.5	nppiNot_8u_C3IR	470
7.37.2.6	nppiNot_8u_C3R	470
7.37.2.7	nppiNot_8u_C4IR	470
7.37.2.8	nppiNot_8u_C4R	471
7.38	Alpha Composition	472
7.39	AlphaCompC	473
7.39.1	Detailed Description	474
7.39.2	Function Documentation	474
7.39.2.1	nppiAlphaCompC_16s_C1R	474
7.39.2.2	nppiAlphaCompC_16u_AC4R	475
7.39.2.3	nppiAlphaCompC_16u_C1R	475
7.39.2.4	nppiAlphaCompC_16u_C3R	476
7.39.2.5	nppiAlphaCompC_16u_C4R	476
7.39.2.6	nppiAlphaCompC_32f_C1R	477
7.39.2.7	nppiAlphaCompC_32s_C1R	477
7.39.2.8	nppiAlphaCompC_32u_C1R	478
7.39.2.9	nppiAlphaCompC_8s_C1R	478
7.39.2.10	nppiAlphaCompC_8u_AC4R	479
7.39.2.11	nppiAlphaCompC_8u_C1R	479
7.39.2.12	nppiAlphaCompC_8u_C3R	480
7.39.2.13	nppiAlphaCompC_8u_C4R	480
7.40	AlphaPremulC	481
7.40.1	Detailed Description	482
7.40.2	Function Documentation	482
7.40.2.1	nppiAlphaPremulC_16u_AC4IR	482
7.40.2.2	nppiAlphaPremulC_16u_AC4R	482
7.40.2.3	nppiAlphaPremulC_16u_C1IR	483
7.40.2.4	nppiAlphaPremulC_16u_C1R	483
7.40.2.5	nppiAlphaPremulC_16u_C3IR	484
7.40.2.6	nppiAlphaPremulC_16u_C3R	484
7.40.2.7	nppiAlphaPremulC_16u_C4IR	484
7.40.2.8	nppiAlphaPremulC_16u_C4R	485
7.40.2.9	nppiAlphaPremulC_8u_AC4IR	485

7.40.2.10	<code>nppiAlphaPremulC_8u_AC4R</code>	485
7.40.2.11	<code>nppiAlphaPremulC_8u_C1IR</code>	486
7.40.2.12	<code>nppiAlphaPremulC_8u_C1R</code>	486
7.40.2.13	<code>nppiAlphaPremulC_8u_C3IR</code>	486
7.40.2.14	<code>nppiAlphaPremulC_8u_C3R</code>	487
7.40.2.15	<code>nppiAlphaPremulC_8u_C4IR</code>	487
7.40.2.16	<code>nppiAlphaPremulC_8u_C4R</code>	487
7.41	AlphaComp	488
7.41.1	Detailed Description	489
7.41.2	Function Documentation	489
7.41.2.1	<code>nppiAlphaComp_16s_AC1R</code>	489
7.41.2.2	<code>nppiAlphaComp_16u_AC1R</code>	489
7.41.2.3	<code>nppiAlphaComp_16u_AC4R</code>	490
7.41.2.4	<code>nppiAlphaComp_32f_AC1R</code>	490
7.41.2.5	<code>nppiAlphaComp_32f_AC4R</code>	491
7.41.2.6	<code>nppiAlphaComp_32s_AC1R</code>	491
7.41.2.7	<code>nppiAlphaComp_32s_AC4R</code>	492
7.41.2.8	<code>nppiAlphaComp_32u_AC1R</code>	492
7.41.2.9	<code>nppiAlphaComp_32u_AC4R</code>	493
7.41.2.10	<code>nppiAlphaComp_8s_AC1R</code>	493
7.41.2.11	<code>nppiAlphaComp_8u_AC1R</code>	493
7.41.2.12	<code>nppiAlphaComp_8u_AC4R</code>	494
7.42	AlphaPremul	495
7.42.1	Detailed Description	495
7.42.2	Function Documentation	495
7.42.2.1	<code>nppiAlphaPremul_16u_AC4IR</code>	495
7.42.2.2	<code>nppiAlphaPremul_16u_AC4R</code>	496
7.42.2.3	<code>nppiAlphaPremul_8u_AC4IR</code>	496
7.42.2.4	<code>nppiAlphaPremul_8u_AC4R</code>	496
7.43	Color and Sampling Conversion	497
7.43.1	Detailed Description	497
7.44	Color Model Conversion	498
7.44.1	Detailed Description	522
7.44.2	Function Documentation	523
7.44.2.1	<code>nppiBGRToCbYCr422_709HDTV_8u_AC4C2R</code>	523
7.44.2.2	<code>nppiBGRToCbYCr422_709HDTV_8u_C3C2R</code>	523

7.44.2.3	nppiBGRTToCbYCr422_8u_AC4C2R	523
7.44.2.4	nppiBGRTToHLS_8u_AC4P4R	524
7.44.2.5	nppiBGRTToHLS_8u_AC4R	524
7.44.2.6	nppiBGRTToHLS_8u_AP4C4R	525
7.44.2.7	nppiBGRTToHLS_8u_AP4R	525
7.44.2.8	nppiBGRTToHLS_8u_C3P3R	525
7.44.2.9	nppiBGRTToHLS_8u_P3C3R	526
7.44.2.10	nppiBGRTToHLS_8u_P3R	526
7.44.2.11	nppiBGRTToLab_8u_C3R	526
7.44.2.12	nppiBGRTToYCbCr411_8u_AC4P3R	527
7.44.2.13	nppiBGRTToYCbCr411_8u_C3P3R	527
7.44.2.14	nppiBGRTToYCbCr420_709CSC_8u_AC4P3R	527
7.44.2.15	nppiBGRTToYCbCr420_709CSC_8u_C3P3R	528
7.44.2.16	nppiBGRTToYCbCr420_709HDTV_8u_AC4P3R	528
7.44.2.17	nppiBGRTToYCbCr420_8u_AC4P3R	529
7.44.2.18	nppiBGRTToYCbCr420_8u_C3P3R	529
7.44.2.19	nppiBGRTToYCbCr422_8u_AC4C2R	529
7.44.2.20	nppiBGRTToYCbCr422_8u_AC4P3R	530
7.44.2.21	nppiBGRTToYCbCr422_8u_C3C2R	530
7.44.2.22	nppiBGRTToYCbCr422_8u_C3P3R	531
7.44.2.23	nppiBGRTToYCrCb420_709CSC_8u_AC4P3R	531
7.44.2.24	nppiBGRTToYCrCb420_709CSC_8u_C3P3R	531
7.44.2.25	nppiBGRTToYCrCb420_8u_AC4P3R	532
7.44.2.26	nppiBGRTToYCrCb420_8u_C3P3R	532
7.44.2.27	nppiBGRTToYUV420_8u_AC4P3R	533
7.44.2.28	nppiCbYCr422ToBGR_709HDTV_8u_C2C3R	533
7.44.2.29	nppiCbYCr422ToBGR_709HDTV_8u_C2C4R	533
7.44.2.30	nppiCbYCr422ToBGR_8u_C2C4R	534
7.44.2.31	nppiCbYCr422ToRGB_8u_C2C3R	534
7.44.2.32	nppiColorToGray_16s_AC4C1R	535
7.44.2.33	nppiColorToGray_16s_C3C1R	535
7.44.2.34	nppiColorToGray_16u_AC4C1R	535
7.44.2.35	nppiColorToGray_16u_C3C1R	536
7.44.2.36	nppiColorToGray_32f_AC4C1R	536
7.44.2.37	nppiColorToGray_32f_C3C1R	536
7.44.2.38	nppiColorToGray_8u_AC4C1R	537

7.44.2.39	nppiColorToGray_8u_C3C1R	537
7.44.2.40	nppiHLSToBGR_8u_AC4P4R	538
7.44.2.41	nppiHLSToBGR_8u_AC4R	538
7.44.2.42	nppiHLSToBGR_8u_AP4C4R	538
7.44.2.43	nppiHLSToBGR_8u_AP4R	539
7.44.2.44	nppiHLSToBGR_8u_C3P3R	539
7.44.2.45	nppiHLSToBGR_8u_P3C3R	539
7.44.2.46	nppiHLSToBGR_8u_P3R	540
7.44.2.47	nppiHLSToRGB_8u_AC4R	540
7.44.2.48	nppiHLSToRGB_8u_C3R	540
7.44.2.49	nppiHSVToRGB_8u_AC4R	541
7.44.2.50	nppiHSVToRGB_8u_C3R	541
7.44.2.51	nppiLabToBGR_8u_C3R	541
7.44.2.52	nppiLUVToRGB_8u_AC4R	542
7.44.2.53	nppiLUVToRGB_8u_C3R	542
7.44.2.54	nppiRGBToCbYCr422_8u_C3C2R	542
7.44.2.55	nppiRGBToCbYCr422Gamma_8u_C3C2R	543
7.44.2.56	nppiRGBToGray_16s_AC4C1R	543
7.44.2.57	nppiRGBToGray_16s_C3C1R	543
7.44.2.58	nppiRGBToGray_16u_AC4C1R	544
7.44.2.59	nppiRGBToGray_16u_C3C1R	544
7.44.2.60	nppiRGBToGray_32f_AC4C1R	544
7.44.2.61	nppiRGBToGray_32f_C3C1R	545
7.44.2.62	nppiRGBToGray_8u_AC4C1R	545
7.44.2.63	nppiRGBToGray_8u_C3C1R	545
7.44.2.64	nppiRGBToHLS_8u_AC4R	546
7.44.2.65	nppiRGBToHLS_8u_C3R	546
7.44.2.66	nppiRGBToHSV_8u_AC4R	546
7.44.2.67	nppiRGBToHSV_8u_C3R	547
7.44.2.68	nppiRGBToLUV_8u_AC4R	547
7.44.2.69	nppiRGBToLUV_8u_C3R	547
7.44.2.70	nppiRGBToXYZ_8u_AC4R	548
7.44.2.71	nppiRGBToXYZ_8u_C3R	548
7.44.2.72	nppiRGBToYCbCr420_8u_C3P3R	548
7.44.2.73	nppiRGBToYCbCr422_8u_C3C2R	549
7.44.2.74	nppiRGBToYCbCr422_8u_C3P3R	549

7.44.2.75	nppiRGBToYCbCr422_8u_P3C2R	549
7.44.2.76	nppiRGBToYCbCr_8u_AC4P3R	550
7.44.2.77	nppiRGBToYCbCr_8u_AC4R	550
7.44.2.78	nppiRGBToYCbCr_8u_C3P3R	550
7.44.2.79	nppiRGBToYCbCr_8u_C3R	551
7.44.2.80	nppiRGBToYCbCr_8u_P3R	551
7.44.2.81	nppiRGBToYCC_8u_AC4R	552
7.44.2.82	nppiRGBToYCC_8u_C3R	552
7.44.2.83	nppiRGBToYCrCb420_8u_AC4P3R	552
7.44.2.84	nppiRGBToYCrCb422_8u_C3C2R	553
7.44.2.85	nppiRGBToYCrCb422_8u_P3C2R	553
7.44.2.86	nppiRGBToYUV420_8u_C3P3R	553
7.44.2.87	nppiRGBToYUV420_8u_P3R	554
7.44.2.88	nppiRGBToYUV422_8u_C3C2R	554
7.44.2.89	nppiRGBToYUV422_8u_C3P3R	554
7.44.2.90	nppiRGBToYUV422_8u_P3R	555
7.44.2.91	nppiRGBToYUV_8u_AC4P4R	555
7.44.2.92	nppiRGBToYUV_8u_AC4R	555
7.44.2.93	nppiRGBToYUV_8u_C3P3R	556
7.44.2.94	nppiRGBToYUV_8u_C3R	556
7.44.2.95	nppiRGBToYUV_8u_P3R	556
7.44.2.96	nppiXYZToRGB_8u_AC4R	557
7.44.2.97	nppiXYZToRGB_8u_C3R	557
7.44.2.98	nppiYCbCr411ToBGR_8u_P3C3R	558
7.44.2.99	nppiYCbCr411ToBGR_8u_P3C4R	558
7.44.2.100	nppiYCbCr420ToBGR_709CSC_8u_P3C3R	558
7.44.2.101	nppiYCbCr420ToBGR_709HDTV_8u_P3C4R	559
7.44.2.102	nppiYCbCr420ToBGR_8u_P3C3R	559
7.44.2.103	nppiYCbCr420ToBGR_8u_P3C4R	559
7.44.2.104	nppiYCbCr420ToRGB_8u_P3C3R	560
7.44.2.105	nppiYCbCr422ToBGR_8u_C2C3R	560
7.44.2.106	nppiYCbCr422ToBGR_8u_C2C4R	560
7.44.2.107	nppiYCbCr422ToBGR_8u_P3C3R	561
7.44.2.108	nppiYCbCr422ToRGB_8u_C2C3R	561
7.44.2.109	nppiYCbCr422ToRGB_8u_C2P3R	562
7.44.2.110	nppiYCbCr422ToRGB_8u_P3C3R	562

7.44.2.11	<code>nppiYCbCrToBGR_709CSC_8u_P3C3R</code>	562
7.44.2.112	<code>nppiYCbCrToBGR_709CSC_8u_P3C4R</code>	563
7.44.2.113	<code>nppiYCbCrToBGR_8u_P3C3R</code>	563
7.44.2.114	<code>nppiYCbCrToBGR_8u_P3C4R</code>	563
7.44.2.115	<code>nppiYCbCrToRGB_8u_AC4R</code>	564
7.44.2.116	<code>nppiYCbCrToRGB_8u_C3R</code>	564
7.44.2.117	<code>nppiYCbCrToRGB_8u_P3C3R</code>	564
7.44.2.118	<code>nppiYCbCrToRGB_8u_P3C4R</code>	565
7.44.2.119	<code>nppiYCbCrToRGB_8u_P3R</code>	565
7.44.2.120	<code>nppiYCCToRGB_8u_AC4R</code>	566
7.44.2.121	<code>nppiYCCToRGB_8u_C3R</code>	566
7.44.2.122	<code>nppiYCrCb420ToRGB_8u_P3C4R</code>	566
7.44.2.123	<code>nppiYCrCb422ToRGB_8u_C2C3R</code>	567
7.44.2.124	<code>nppiYCrCb422ToRGB_8u_C2P3R</code>	567
7.44.2.125	<code>nppiYUV420ToBGR_8u_P3C3R</code>	567
7.44.2.126	<code>nppiYUV420ToRGB_8u_P3AC4R</code>	568
7.44.2.127	<code>nppiYUV420ToRGB_8u_P3C3R</code>	568
7.44.2.128	<code>nppiYUV420ToRGB_8u_P3R</code>	568
7.44.2.129	<code>nppiYUV422ToRGB_8u_C2C3R</code>	569
7.44.2.130	<code>nppiYUV422ToRGB_8u_P3AC4R</code>	569
7.44.2.131	<code>nppiYUV422ToRGB_8u_P3C3R</code>	569
7.44.2.132	<code>nppiYUV422ToRGB_8u_P3R</code>	570
7.44.2.133	<code>nppiYUVToRGB_8u_AC4R</code>	570
7.44.2.134	<code>nppiYUVToRGB_8u_C3R</code>	570
7.44.2.135	<code>nppiYUVToRGB_8u_P3C3R</code>	571
7.44.2.136	<code>nppiYUVToRGB_8u_P3R</code>	571
7.45	Color Sampling Format Conversion	572
7.45.1	Detailed Description	579
7.45.2	Function Documentation	579
7.45.2.1	<code>nppiCbYCr422ToYCbCr411_8u_C2P3R</code>	579
7.45.2.2	<code>nppiCbYCr422ToYCbCr420_8u_C2P2R</code>	580
7.45.2.3	<code>nppiCbYCr422ToYCbCr420_8u_C2P3R</code>	580
7.45.2.4	<code>nppiCbYCr422ToYCbCr422_8u_C2P3R</code>	581
7.45.2.5	<code>nppiCbYCr422ToYCbCr422_8u_C2R</code>	581
7.45.2.6	<code>nppiCbYCr422ToYCrCb420_8u_C2P3R</code>	581
7.45.2.7	<code>nppiYCbCr411_8u_P2P3R</code>	582

7.45.2.8 nppiYCbCr411_8u_P3P2R 582

7.45.2.9 nppiYCbCr411ToYCbCr420_8u_P2P3R 583

7.45.2.10 nppiYCbCr411ToYCbCr420_8u_P3P2R 583

7.45.2.11 nppiYCbCr411ToYCbCr420_8u_P3R 583

7.45.2.12 nppiYCbCr411ToYCbCr422_8u_P2C2R 584

7.45.2.13 nppiYCbCr411ToYCbCr422_8u_P2P3R 584

7.45.2.14 nppiYCbCr411ToYCbCr422_8u_P3C2R 585

7.45.2.15 nppiYCbCr411ToYCbCr422_8u_P3R 585

7.45.2.16 nppiYCbCr411ToYCrCb420_8u_P2P3R 585

7.45.2.17 nppiYCbCr411ToYCrCb422_8u_P3C2R 586

7.45.2.18 nppiYCbCr411ToYCrCb422_8u_P3R 586

7.45.2.19 nppiYCbCr420_8u_P2P3R 587

7.45.2.20 nppiYCbCr420_8u_P3P2R 587

7.45.2.21 nppiYCbCr420ToCbYCr422_8u_P2C2R 587

7.45.2.22 nppiYCbCr420ToYCbCr411_8u_P2P3R 588

7.45.2.23 nppiYCbCr420ToYCbCr411_8u_P3P2R 588

7.45.2.24 nppiYCbCr420ToYCbCr422_8u_P2C2R 589

7.45.2.25 nppiYCbCr420ToYCbCr422_8u_P2P3R 589

7.45.2.26 nppiYCbCr420ToYCbCr422_8u_P3R 590

7.45.2.27 nppiYCbCr420ToYCrCb420_8u_P2P3R 590

7.45.2.28 nppiYCbCr422_8u_C2P3R 590

7.45.2.29 nppiYCbCr422_8u_P3C2R 591

7.45.2.30 nppiYCbCr422ToCbYCr422_8u_C2R 591

7.45.2.31 nppiYCbCr422ToYCbCr411_8u_C2P2R 592

7.45.2.32 nppiYCbCr422ToYCbCr411_8u_C2P3R 592

7.45.2.33 nppiYCbCr422ToYCbCr411_8u_P3P2R 592

7.45.2.34 nppiYCbCr422ToYCbCr411_8u_P3R 593

7.45.2.35 nppiYCbCr422ToYCbCr420_8u_C2P2R 593

7.45.2.36 nppiYCbCr422ToYCbCr420_8u_C2P3R 594

7.45.2.37 nppiYCbCr422ToYCbCr420_8u_P3P2R 594

7.45.2.38 nppiYCbCr422ToYCbCr420_8u_P3R 595

7.45.2.39 nppiYCbCr422ToYCrCb420_8u_C2P3R 595

7.45.2.40 nppiYCbCr422ToYCrCb422_8u_C2R 595

7.45.2.41 nppiYCbCr422ToYCrCb422_8u_P3C2R 596

7.45.2.42 nppiYCrCb420ToCbYCr422_8u_P3C2R 596

7.45.2.43 nppiYCrCb420ToYCbCr411_8u_P3P2R 597

7.45.2.44	<code>nppiYCrCb420ToYCbCr420_8u_P3P2R</code>	597
7.45.2.45	<code>nppiYCrCb420ToYCbCr422_8u_P3C2R</code>	598
7.45.2.46	<code>nppiYCrCb420ToYCbCr422_8u_P3R</code>	598
7.45.2.47	<code>nppiYCrCb422ToYCbCr411_8u_C2P3R</code>	598
7.45.2.48	<code>nppiYCrCb422ToYCbCr420_8u_C2P3R</code>	599
7.45.2.49	<code>nppiYCrCb422ToYCbCr422_8u_C2P3R</code>	599
7.46	Color Gamma Correction	600
7.46.1	Detailed Description	601
7.46.2	Function Documentation	601
7.46.2.1	<code>nppiGammaFwd_8u_AC4IR</code>	601
7.46.2.2	<code>nppiGammaFwd_8u_AC4R</code>	601
7.46.2.3	<code>nppiGammaFwd_8u_C3IR</code>	602
7.46.2.4	<code>nppiGammaFwd_8u_C3R</code>	602
7.46.2.5	<code>nppiGammaFwd_8u_IP3R</code>	602
7.46.2.6	<code>nppiGammaFwd_8u_P3R</code>	603
7.46.2.7	<code>nppiGammaInv_8u_AC4IR</code>	603
7.46.2.8	<code>nppiGammaInv_8u_AC4R</code>	603
7.46.2.9	<code>nppiGammaInv_8u_C3IR</code>	604
7.46.2.10	<code>nppiGammaInv_8u_C3R</code>	604
7.46.2.11	<code>nppiGammaInv_8u_IP3R</code>	604
7.46.2.12	<code>nppiGammaInv_8u_P3R</code>	605
7.47	Complement Color Key	606
7.47.1	Detailed Description	606
7.47.2	Function Documentation	606
7.47.2.1	<code>nppiAlphaCompColorKey_8u_AC4R</code>	606
7.47.2.2	<code>nppiCompColorKey_8u_C1R</code>	607
7.47.2.3	<code>nppiCompColorKey_8u_C3R</code>	607
7.47.2.4	<code>nppiCompColorKey_8u_C4R</code>	608
7.48	Color Processing	609
7.48.1	Detailed Description	621
7.48.2	Function Documentation	621
7.48.2.1	<code>nppiColorTwist32f_16s_AC4IR</code>	621
7.48.2.2	<code>nppiColorTwist32f_16s_AC4R</code>	621
7.48.2.3	<code>nppiColorTwist32f_16s_C3IR</code>	622
7.48.2.4	<code>nppiColorTwist32f_16s_C3R</code>	622
7.48.2.5	<code>nppiColorTwist32f_16s_IP3R</code>	622

7.48.2.6	nppiColorTwist32f_16s_P3R	623
7.48.2.7	nppiColorTwist32f_16u_AC4IR	623
7.48.2.8	nppiColorTwist32f_16u_AC4R	623
7.48.2.9	nppiColorTwist32f_16u_C3IR	624
7.48.2.10	nppiColorTwist32f_16u_C3R	624
7.48.2.11	nppiColorTwist32f_16u_IP3R	625
7.48.2.12	nppiColorTwist32f_16u_P3R	625
7.48.2.13	nppiColorTwist32f_8s_AC4IR	625
7.48.2.14	nppiColorTwist32f_8s_AC4R	626
7.48.2.15	nppiColorTwist32f_8s_C3IR	626
7.48.2.16	nppiColorTwist32f_8s_C3R	626
7.48.2.17	nppiColorTwist32f_8s_IP3R	627
7.48.2.18	nppiColorTwist32f_8s_P3R	627
7.48.2.19	nppiColorTwist32f_8u_AC4IR	628
7.48.2.20	nppiColorTwist32f_8u_AC4R	628
7.48.2.21	nppiColorTwist32f_8u_C3IR	628
7.48.2.22	nppiColorTwist32f_8u_C3R	629
7.48.2.23	nppiColorTwist32f_8u_IP3R	629
7.48.2.24	nppiColorTwist32f_8u_P3R	630
7.48.2.25	nppiColorTwist_32f_AC4IR	630
7.48.2.26	nppiColorTwist_32f_AC4R	630
7.48.2.27	nppiColorTwist_32f_C3IR	631
7.48.2.28	nppiColorTwist_32f_C3R	631
7.48.2.29	nppiColorTwist_32f_IP3R	632
7.48.2.30	nppiColorTwist_32f_P3R	632
7.48.2.31	nppiLUT_16s_AC4IR	632
7.48.2.32	nppiLUT_16s_AC4R	633
7.48.2.33	nppiLUT_16s_C1IR	633
7.48.2.34	nppiLUT_16s_C1R	634
7.48.2.35	nppiLUT_16s_C3IR	634
7.48.2.36	nppiLUT_16s_C3R	635
7.48.2.37	nppiLUT_16s_C4IR	635
7.48.2.38	nppiLUT_16s_C4R	636
7.48.2.39	nppiLUT_16u_AC4IR	637
7.48.2.40	nppiLUT_16u_AC4R	637
7.48.2.41	nppiLUT_16u_C1IR	638

7.48.2.42 nppiLUT_16u_C1R	638
7.48.2.43 nppiLUT_16u_C3IR	639
7.48.2.44 nppiLUT_16u_C3R	639
7.48.2.45 nppiLUT_16u_C4IR	640
7.48.2.46 nppiLUT_16u_C4R	640
7.48.2.47 nppiLUT_32f_AC4IR	641
7.48.2.48 nppiLUT_32f_AC4R	641
7.48.2.49 nppiLUT_32f_C1IR	642
7.48.2.50 nppiLUT_32f_C1R	642
7.48.2.51 nppiLUT_32f_C3IR	643
7.48.2.52 nppiLUT_32f_C3R	643
7.48.2.53 nppiLUT_32f_C4IR	644
7.48.2.54 nppiLUT_32f_C4R	644
7.48.2.55 nppiLUT_8u_AC4IR	645
7.48.2.56 nppiLUT_8u_AC4R	645
7.48.2.57 nppiLUT_8u_C1IR	646
7.48.2.58 nppiLUT_8u_C1R	646
7.48.2.59 nppiLUT_8u_C3IR	647
7.48.2.60 nppiLUT_8u_C3R	647
7.48.2.61 nppiLUT_8u_C4IR	648
7.48.2.62 nppiLUT_8u_C4R	648
7.48.2.63 nppiLUT_Cubic_16s_AC4IR	649
7.48.2.64 nppiLUT_Cubic_16s_AC4R	649
7.48.2.65 nppiLUT_Cubic_16s_C1IR	650
7.48.2.66 nppiLUT_Cubic_16s_C1R	650
7.48.2.67 nppiLUT_Cubic_16s_C3IR	651
7.48.2.68 nppiLUT_Cubic_16s_C3R	651
7.48.2.69 nppiLUT_Cubic_16s_C4IR	652
7.48.2.70 nppiLUT_Cubic_16s_C4R	652
7.48.2.71 nppiLUT_Cubic_16u_AC4IR	653
7.48.2.72 nppiLUT_Cubic_16u_AC4R	653
7.48.2.73 nppiLUT_Cubic_16u_C1IR	654
7.48.2.74 nppiLUT_Cubic_16u_C1R	654
7.48.2.75 nppiLUT_Cubic_16u_C3IR	655
7.48.2.76 nppiLUT_Cubic_16u_C3R	655
7.48.2.77 nppiLUT_Cubic_16u_C4IR	656

7.48.2.78 nppiLUT_Cubic_16u_C4R	656
7.48.2.79 nppiLUT_Cubic_32f_AC4IR	657
7.48.2.80 nppiLUT_Cubic_32f_AC4R	657
7.48.2.81 nppiLUT_Cubic_32f_C1IR	658
7.48.2.82 nppiLUT_Cubic_32f_C1R	658
7.48.2.83 nppiLUT_Cubic_32f_C3IR	659
7.48.2.84 nppiLUT_Cubic_32f_C3R	659
7.48.2.85 nppiLUT_Cubic_32f_C4IR	660
7.48.2.86 nppiLUT_Cubic_32f_C4R	660
7.48.2.87 nppiLUT_Cubic_8u_AC4IR	661
7.48.2.88 nppiLUT_Cubic_8u_AC4R	661
7.48.2.89 nppiLUT_Cubic_8u_C1IR	662
7.48.2.90 nppiLUT_Cubic_8u_C1R	662
7.48.2.91 nppiLUT_Cubic_8u_C3IR	663
7.48.2.92 nppiLUT_Cubic_8u_C3R	663
7.48.2.93 nppiLUT_Cubic_8u_C4IR	664
7.48.2.94 nppiLUT_Cubic_8u_C4R	664
7.48.2.95 nppiLUT_Linear_16s_AC4IR	665
7.48.2.96 nppiLUT_Linear_16s_AC4R	665
7.48.2.97 nppiLUT_Linear_16s_C1IR	666
7.48.2.98 nppiLUT_Linear_16s_C1R	666
7.48.2.99 nppiLUT_Linear_16s_C3IR	667
7.48.2.100 nppiLUT_Linear_16s_C3R	667
7.48.2.101 nppiLUT_Linear_16s_C4IR	668
7.48.2.102 nppiLUT_Linear_16s_C4R	668
7.48.2.103 nppiLUT_Linear_16u_AC4IR	669
7.48.2.104 nppiLUT_Linear_16u_AC4R	669
7.48.2.105 nppiLUT_Linear_16u_C1IR	670
7.48.2.106 nppiLUT_Linear_16u_C1R	670
7.48.2.107 nppiLUT_Linear_16u_C3IR	671
7.48.2.108 nppiLUT_Linear_16u_C3R	671
7.48.2.109 nppiLUT_Linear_16u_C4IR	672
7.48.2.110 nppiLUT_Linear_16u_C4R	672
7.48.2.111 nppiLUT_Linear_32f_AC4IR	673
7.48.2.112 nppiLUT_Linear_32f_AC4R	673
7.48.2.113 nppiLUT_Linear_32f_C1IR	674

7.48.2.114	nppiLUT_Linear_32f_C1R	674
7.48.2.115	nppiLUT_Linear_32f_C3IR	675
7.48.2.116	nppiLUT_Linear_32f_C3R	675
7.48.2.117	nppiLUT_Linear_32f_C4IR	676
7.48.2.118	nppiLUT_Linear_32f_C4R	676
7.48.2.119	nppiLUT_Linear_8u_AC4IR	677
7.48.2.120	nppiLUT_Linear_8u_AC4R	677
7.48.2.121	nppiLUT_Linear_8u_C1IR	678
7.48.2.122	nppiLUT_Linear_8u_C1R	678
7.48.2.123	nppiLUT_Linear_8u_C3IR	679
7.48.2.124	nppiLUT_Linear_8u_C3R	679
7.48.2.125	nppiLUT_Linear_8u_C4IR	680
7.48.2.126	nppiLUT_Linear_8u_C4R	680
7.48.2.127	nppiLUTPalette_16u24u_C1R	681
7.48.2.128	nppiLUTPalette_16u32u_C1R	682
7.48.2.129	nppiLUTPalette_16u8u_C1R	682
7.48.2.130	nppiLUTPalette_16u_AC4R	683
7.48.2.131	nppiLUTPalette_16u_C1R	683
7.48.2.132	nppiLUTPalette_16u_C3R	684
7.48.2.133	nppiLUTPalette_16u_C4R	684
7.48.2.134	nppiLUTPalette_8u24u_C1R	685
7.48.2.135	nppiLUTPalette_8u32u_C1R	685
7.48.2.136	nppiLUTPalette_8u_AC4R	686
7.48.2.137	nppiLUTPalette_8u_C1R	686
7.48.2.138	nppiLUTPalette_8u_C3R	687
7.48.2.139	nppiLUTPalette_8u_C4R	687
7.48.2.140	nppiLUTPaletteSwap_16u_C3A0C4R	688
7.48.2.141	nppiLUTPaletteSwap_8u_C3A0C4R	688
7.49	Compression	690
7.49.1	Detailed Description	690
7.49.2	Function Documentation	690
7.49.2.1	nppiDecodeHuffmanScanHost_JPEG_8u16s_P1R	690
7.49.2.2	nppiDecodeHuffmanScanHost_JPEG_8u16s_P3R	691
7.50	Quantization Functions	692
7.50.1	Typedef Documentation	693
7.50.1.1	NppiDCTState	693

7.50.2	Function Documentation	693
7.50.2.1	nppiDCTFree	693
7.50.2.2	nppiDCTInitAlloc	693
7.50.2.3	nppiDCTQuantFwd8x8LS_JPEG_8u16s_C1R	693
7.50.2.4	nppiDCTQuantFwd8x8LS_JPEG_8u16s_C1R_NEW	694
7.50.2.5	nppiDCTQuantInv8x8LS_JPEG_16s8u_C1R	694
7.50.2.6	nppiDCTQuantInv8x8LS_JPEG_16s8u_C1R_NEW	695
7.50.2.7	nppiQuantFwdRawTableInit_JPEG_8u	696
7.50.2.8	nppiQuantFwdTableInit_JPEG_8u16u	696
7.50.2.9	nppiQuantInvTableInit_JPEG_8u16u	696
7.51	Labeling and Segmentation	698
7.51.1	Detailed Description	698
7.51.2	Typedef Documentation	698
7.51.2.1	NppiGraphcutState	698
7.52	GraphCut	699
7.52.1	Function Documentation	700
7.52.1.1	nppiGraphcut8_32f8u	700
7.52.1.2	nppiGraphcut8_32s8u	701
7.52.1.3	nppiGraphcut8GetSize	701
7.52.1.4	nppiGraphcut8InitAlloc	702
7.52.1.5	nppiGraphcut_32f8u	702
7.52.1.6	nppiGraphcut_32s8u	703
7.52.1.7	nppiGraphcutFree	704
7.52.1.8	nppiGraphcutGetSize	704
7.52.1.9	nppiGraphcutInitAlloc	705
7.53	Data Exchange and Initialization	706
7.53.1	Detailed Description	706
7.54	Set	707
7.54.1	Detailed Description	712
7.54.2	Function Documentation	712
7.54.2.1	nppiSet_16s_AC4MR	712
7.54.2.2	nppiSet_16s_AC4R	713
7.54.2.3	nppiSet_16s_C1MR	713
7.54.2.4	nppiSet_16s_C1R	714
7.54.2.5	nppiSet_16s_C2R	714
7.54.2.6	nppiSet_16s_C3CR	714

7.54.2.7	nppiSet_16s_C3MR	715
7.54.2.8	nppiSet_16s_C3R	715
7.54.2.9	nppiSet_16s_C4CR	715
7.54.2.10	nppiSet_16s_C4MR	716
7.54.2.11	nppiSet_16s_C4R	716
7.54.2.12	nppiSet_16sc_AC4R	716
7.54.2.13	nppiSet_16sc_C1R	717
7.54.2.14	nppiSet_16sc_C2R	717
7.54.2.15	nppiSet_16sc_C3R	717
7.54.2.16	nppiSet_16sc_C4R	718
7.54.2.17	nppiSet_16u_AC4MR	718
7.54.2.18	nppiSet_16u_AC4R	718
7.54.2.19	nppiSet_16u_C1MR	719
7.54.2.20	nppiSet_16u_C1R	719
7.54.2.21	nppiSet_16u_C2R	719
7.54.2.22	nppiSet_16u_C3CR	720
7.54.2.23	nppiSet_16u_C3MR	720
7.54.2.24	nppiSet_16u_C3R	720
7.54.2.25	nppiSet_16u_C4CR	721
7.54.2.26	nppiSet_16u_C4MR	721
7.54.2.27	nppiSet_16u_C4R	721
7.54.2.28	nppiSet_32f_AC4MR	722
7.54.2.29	nppiSet_32f_AC4R	722
7.54.2.30	nppiSet_32f_C1MR	722
7.54.2.31	nppiSet_32f_C1R	723
7.54.2.32	nppiSet_32f_C3CR	723
7.54.2.33	nppiSet_32f_C3MR	723
7.54.2.34	nppiSet_32f_C3R	724
7.54.2.35	nppiSet_32f_C4CR	724
7.54.2.36	nppiSet_32f_C4MR	724
7.54.2.37	nppiSet_32f_C4R	725
7.54.2.38	nppiSet_32fc_AC4R	725
7.54.2.39	nppiSet_32fc_C1R	725
7.54.2.40	nppiSet_32fc_C2R	726
7.54.2.41	nppiSet_32fc_C3R	726
7.54.2.42	nppiSet_32fc_C4R	726

7.54.2.43	nppiSet_32s_AC4MR	727
7.54.2.44	nppiSet_32s_AC4R	727
7.54.2.45	nppiSet_32s_C1MR	727
7.54.2.46	nppiSet_32s_C1R	728
7.54.2.47	nppiSet_32s_C3CR	728
7.54.2.48	nppiSet_32s_C3MR	728
7.54.2.49	nppiSet_32s_C3R	729
7.54.2.50	nppiSet_32s_C4CR	729
7.54.2.51	nppiSet_32s_C4MR	729
7.54.2.52	nppiSet_32s_C4R	730
7.54.2.53	nppiSet_32sc_AC4R	730
7.54.2.54	nppiSet_32sc_C1R	730
7.54.2.55	nppiSet_32sc_C2R	731
7.54.2.56	nppiSet_32sc_C3R	731
7.54.2.57	nppiSet_32sc_C4R	731
7.54.2.58	nppiSet_8s_AC4R	732
7.54.2.59	nppiSet_8s_C1R	732
7.54.2.60	nppiSet_8s_C2R	732
7.54.2.61	nppiSet_8s_C3R	733
7.54.2.62	nppiSet_8s_C4R	733
7.54.2.63	nppiSet_8u_AC4MR	733
7.54.2.64	nppiSet_8u_AC4R	734
7.54.2.65	nppiSet_8u_C1MR	734
7.54.2.66	nppiSet_8u_C1R	734
7.54.2.67	nppiSet_8u_C3CR	735
7.54.2.68	nppiSet_8u_C3MR	735
7.54.2.69	nppiSet_8u_C3R	735
7.54.2.70	nppiSet_8u_C4CR	736
7.54.2.71	nppiSet_8u_C4MR	736
7.54.2.72	nppiSet_8u_C4R	736
7.55	Copy	737
7.55.1	Function Documentation	746
7.55.1.1	nppiCopy_16s_AC4MR	746
7.55.1.2	nppiCopy_16s_AC4R	747
7.55.1.3	nppiCopy_16s_C1C3R	747
7.55.1.4	nppiCopy_16s_C1C4R	748

7.55.1.5	nppiCopy_16s_C1MR	748
7.55.1.6	nppiCopy_16s_C1R	748
7.55.1.7	nppiCopy_16s_C3C1R	749
7.55.1.8	nppiCopy_16s_C3CR	749
7.55.1.9	nppiCopy_16s_C3MR	749
7.55.1.10	nppiCopy_16s_C3P3R	750
7.55.1.11	nppiCopy_16s_C3R	750
7.55.1.12	nppiCopy_16s_C4C1R	750
7.55.1.13	nppiCopy_16s_C4CR	751
7.55.1.14	nppiCopy_16s_C4MR	751
7.55.1.15	nppiCopy_16s_C4P4R	751
7.55.1.16	nppiCopy_16s_C4R	752
7.55.1.17	nppiCopy_16s_P3C3R	752
7.55.1.18	nppiCopy_16s_P4C4R	752
7.55.1.19	nppiCopy_16sc_AC4R	753
7.55.1.20	nppiCopy_16sc_C1R	753
7.55.1.21	nppiCopy_16sc_C2R	753
7.55.1.22	nppiCopy_16sc_C3R	754
7.55.1.23	nppiCopy_16sc_C4R	754
7.55.1.24	nppiCopy_16u_AC4MR	754
7.55.1.25	nppiCopy_16u_AC4R	755
7.55.1.26	nppiCopy_16u_C1C3R	755
7.55.1.27	nppiCopy_16u_C1C4R	755
7.55.1.28	nppiCopy_16u_C1MR	756
7.55.1.29	nppiCopy_16u_C1R	756
7.55.1.30	nppiCopy_16u_C3C1R	756
7.55.1.31	nppiCopy_16u_C3CR	757
7.55.1.32	nppiCopy_16u_C3MR	757
7.55.1.33	nppiCopy_16u_C3P3R	757
7.55.1.34	nppiCopy_16u_C3R	758
7.55.1.35	nppiCopy_16u_C4C1R	758
7.55.1.36	nppiCopy_16u_C4CR	758
7.55.1.37	nppiCopy_16u_C4MR	759
7.55.1.38	nppiCopy_16u_C4P4R	759
7.55.1.39	nppiCopy_16u_C4R	759
7.55.1.40	nppiCopy_16u_P3C3R	760

7.55.1.41 nppiCopy_16u_P4C4R	760
7.55.1.42 nppiCopy_32f_AC4MR	760
7.55.1.43 nppiCopy_32f_AC4R	761
7.55.1.44 nppiCopy_32f_C1C3R	761
7.55.1.45 nppiCopy_32f_C1C4R	761
7.55.1.46 nppiCopy_32f_C1MR	762
7.55.1.47 nppiCopy_32f_C1R	762
7.55.1.48 nppiCopy_32f_C3C1R	762
7.55.1.49 nppiCopy_32f_C3CR	763
7.55.1.50 nppiCopy_32f_C3MR	763
7.55.1.51 nppiCopy_32f_C3P3R	763
7.55.1.52 nppiCopy_32f_C3R	764
7.55.1.53 nppiCopy_32f_C4C1R	764
7.55.1.54 nppiCopy_32f_C4CR	764
7.55.1.55 nppiCopy_32f_C4MR	765
7.55.1.56 nppiCopy_32f_C4P4R	765
7.55.1.57 nppiCopy_32f_C4R	765
7.55.1.58 nppiCopy_32f_P3C3R	766
7.55.1.59 nppiCopy_32f_P4C4R	766
7.55.1.60 nppiCopy_32fc_AC4R	766
7.55.1.61 nppiCopy_32fc_C1R	767
7.55.1.62 nppiCopy_32fc_C2R	767
7.55.1.63 nppiCopy_32fc_C3R	767
7.55.1.64 nppiCopy_32fc_C4R	768
7.55.1.65 nppiCopy_32s_AC4MR	768
7.55.1.66 nppiCopy_32s_AC4R	768
7.55.1.67 nppiCopy_32s_C1C3R	769
7.55.1.68 nppiCopy_32s_C1C4R	769
7.55.1.69 nppiCopy_32s_C1MR	769
7.55.1.70 nppiCopy_32s_C1R	770
7.55.1.71 nppiCopy_32s_C3C1R	770
7.55.1.72 nppiCopy_32s_C3CR	770
7.55.1.73 nppiCopy_32s_C3MR	771
7.55.1.74 nppiCopy_32s_C3P3R	771
7.55.1.75 nppiCopy_32s_C3R	771
7.55.1.76 nppiCopy_32s_C4C1R	772

7.55.1.77	nppiCopy_32s_C4CR	772
7.55.1.78	nppiCopy_32s_C4MR	772
7.55.1.79	nppiCopy_32s_C4P4R	773
7.55.1.80	nppiCopy_32s_C4R	773
7.55.1.81	nppiCopy_32s_P3C3R	773
7.55.1.82	nppiCopy_32s_P4C4R	774
7.55.1.83	nppiCopy_32sc_AC4R	774
7.55.1.84	nppiCopy_32sc_C1R	774
7.55.1.85	nppiCopy_32sc_C2R	775
7.55.1.86	nppiCopy_32sc_C3R	775
7.55.1.87	nppiCopy_32sc_C4R	775
7.55.1.88	nppiCopy_8s_AC4R	776
7.55.1.89	nppiCopy_8s_C1R	776
7.55.1.90	nppiCopy_8s_C2R	776
7.55.1.91	nppiCopy_8s_C3R	777
7.55.1.92	nppiCopy_8s_C4R	777
7.55.1.93	nppiCopy_8u_AC4MR	777
7.55.1.94	nppiCopy_8u_AC4R	778
7.55.1.95	nppiCopy_8u_C1C3R	778
7.55.1.96	nppiCopy_8u_C1C4R	778
7.55.1.97	nppiCopy_8u_C1MR	779
7.55.1.98	nppiCopy_8u_C1R	779
7.55.1.99	nppiCopy_8u_C3C1R	779
7.55.1.100	nppiCopy_8u_C3CR	780
7.55.1.101	nppiCopy_8u_C3MR	780
7.55.1.102	nppiCopy_8u_C3P3R	780
7.55.1.103	nppiCopy_8u_C3R	781
7.55.1.104	nppiCopy_8u_C4C1R	781
7.55.1.105	nppiCopy_8u_C4CR	781
7.55.1.106	nppiCopy_8u_C4MR	782
7.55.1.107	nppiCopy_8u_C4P4R	782
7.55.1.108	nppiCopy_8u_C4R	782
7.55.1.109	nppiCopy_8u_P3C3R	783
7.55.1.110	nppiCopy_8u_P4C4R	783
7.56	Convert	784
7.56.1	Function Documentation	792

7.56.1.1	nppiConvert_16s16u_C1Rs	792
7.56.1.2	nppiConvert_16s32f_AC4R	792
7.56.1.3	nppiConvert_16s32f_C1R	793
7.56.1.4	nppiConvert_16s32f_C3R	793
7.56.1.5	nppiConvert_16s32f_C4R	793
7.56.1.6	nppiConvert_16s32s_AC4R	794
7.56.1.7	nppiConvert_16s32s_C1R	794
7.56.1.8	nppiConvert_16s32s_C3R	794
7.56.1.9	nppiConvert_16s32s_C4R	795
7.56.1.10	nppiConvert_16s32u_C1Rs	795
7.56.1.11	nppiConvert_16s8s_C1RSfs	795
7.56.1.12	nppiConvert_16s8u_AC4R	796
7.56.1.13	nppiConvert_16s8u_C1R	796
7.56.1.14	nppiConvert_16s8u_C3R	797
7.56.1.15	nppiConvert_16s8u_C4R	797
7.56.1.16	nppiConvert_16u16s_C1RSfs	797
7.56.1.17	nppiConvert_16u32f_AC4R	798
7.56.1.18	nppiConvert_16u32f_C1R	798
7.56.1.19	nppiConvert_16u32f_C3R	798
7.56.1.20	nppiConvert_16u32f_C4R	799
7.56.1.21	nppiConvert_16u32s_AC4R	799
7.56.1.22	nppiConvert_16u32s_C1R	799
7.56.1.23	nppiConvert_16u32s_C3R	800
7.56.1.24	nppiConvert_16u32s_C4R	800
7.56.1.25	nppiConvert_16u32u_C1R	800
7.56.1.26	nppiConvert_16u8s_C1RSfs	801
7.56.1.27	nppiConvert_16u8u_AC4R	801
7.56.1.28	nppiConvert_16u8u_C1R	801
7.56.1.29	nppiConvert_16u8u_C3R	802
7.56.1.30	nppiConvert_16u8u_C4R	802
7.56.1.31	nppiConvert_32f16s_AC4R	802
7.56.1.32	nppiConvert_32f16s_C1R	803
7.56.1.33	nppiConvert_32f16s_C1RSfs	803
7.56.1.34	nppiConvert_32f16s_C3R	803
7.56.1.35	nppiConvert_32f16s_C4R	804
7.56.1.36	nppiConvert_32f16u_AC4R	804

7.56.1.37	nppiConvert_32f16u_C1R	805
7.56.1.38	nppiConvert_32f16u_C1RSfs	805
7.56.1.39	nppiConvert_32f16u_C3R	805
7.56.1.40	nppiConvert_32f16u_C4R	806
7.56.1.41	nppiConvert_32f32s_C1RSfs	806
7.56.1.42	nppiConvert_32f32u_C1RSfs	807
7.56.1.43	nppiConvert_32f8s_AC4R	807
7.56.1.44	nppiConvert_32f8s_C1R	807
7.56.1.45	nppiConvert_32f8s_C1RSfs	808
7.56.1.46	nppiConvert_32f8s_C3R	808
7.56.1.47	nppiConvert_32f8s_C4R	809
7.56.1.48	nppiConvert_32f8u_AC4R	809
7.56.1.49	nppiConvert_32f8u_C1R	809
7.56.1.50	nppiConvert_32f8u_C1RSfs	810
7.56.1.51	nppiConvert_32f8u_C3R	810
7.56.1.52	nppiConvert_32f8u_C4R	810
7.56.1.53	nppiConvert_32s16s_C1RSfs	811
7.56.1.54	nppiConvert_32s16u_C1RSfs	811
7.56.1.55	nppiConvert_32s32f_C1R	812
7.56.1.56	nppiConvert_32s32u_C1Rs	812
7.56.1.57	nppiConvert_32s8s_AC4R	812
7.56.1.58	nppiConvert_32s8s_C1R	813
7.56.1.59	nppiConvert_32s8s_C3R	813
7.56.1.60	nppiConvert_32s8s_C4R	813
7.56.1.61	nppiConvert_32s8u_AC4R	814
7.56.1.62	nppiConvert_32s8u_C1R	814
7.56.1.63	nppiConvert_32s8u_C3R	814
7.56.1.64	nppiConvert_32s8u_C4R	815
7.56.1.65	nppiConvert_32u16s_C1RSfs	815
7.56.1.66	nppiConvert_32u16u_C1RSfs	815
7.56.1.67	nppiConvert_32u32f_C1R	816
7.56.1.68	nppiConvert_32u32s_C1RSfs	816
7.56.1.69	nppiConvert_32u8s_C1RSfs	817
7.56.1.70	nppiConvert_32u8u_C1RSfs	817
7.56.1.71	nppiConvert_8s16s_C1R	817
7.56.1.72	nppiConvert_8s16u_C1Rs	818

7.56.1.73	nppiConvert_8s32f_AC4R	818
7.56.1.74	nppiConvert_8s32f_C1R	818
7.56.1.75	nppiConvert_8s32f_C3R	819
7.56.1.76	nppiConvert_8s32f_C4R	819
7.56.1.77	nppiConvert_8s32s_AC4R	820
7.56.1.78	nppiConvert_8s32s_C1R	820
7.56.1.79	nppiConvert_8s32s_C3R	820
7.56.1.80	nppiConvert_8s32s_C4R	821
7.56.1.81	nppiConvert_8s32u_C1Rs	821
7.56.1.82	nppiConvert_8s8u_C1Rs	821
7.56.1.83	nppiConvert_8u16s_AC4R	822
7.56.1.84	nppiConvert_8u16s_C1R	822
7.56.1.85	nppiConvert_8u16s_C3R	822
7.56.1.86	nppiConvert_8u16s_C4R	823
7.56.1.87	nppiConvert_8u16u_AC4R	823
7.56.1.88	nppiConvert_8u16u_C1R	823
7.56.1.89	nppiConvert_8u16u_C3R	824
7.56.1.90	nppiConvert_8u16u_C4R	824
7.56.1.91	nppiConvert_8u32f_AC4R	824
7.56.1.92	nppiConvert_8u32f_C1R	825
7.56.1.93	nppiConvert_8u32f_C3R	825
7.56.1.94	nppiConvert_8u32f_C4R	825
7.56.1.95	nppiConvert_8u32s_AC4R	826
7.56.1.96	nppiConvert_8u32s_C1R	826
7.56.1.97	nppiConvert_8u32s_C3R	826
7.56.1.98	nppiConvert_8u32s_C4R	827
7.56.1.99	nppiConvert_8u8s_C1RSfs	827
7.57	Scale	828
7.57.1	Function Documentation	831
7.57.1.1	nppiScale_16s8u_AC4R	831
7.57.1.2	nppiScale_16s8u_C1R	831
7.57.1.3	nppiScale_16s8u_C3R	831
7.57.1.4	nppiScale_16s8u_C4R	832
7.57.1.5	nppiScale_16u8u_AC4R	832
7.57.1.6	nppiScale_16u8u_C1R	833
7.57.1.7	nppiScale_16u8u_C3R	833

7.57.1.8	nppiScale_16u8u_C4R	833
7.57.1.9	nppiScale_32f8u_AC4R	834
7.57.1.10	nppiScale_32f8u_C1R	834
7.57.1.11	nppiScale_32f8u_C3R	834
7.57.1.12	nppiScale_32f8u_C4R	835
7.57.1.13	nppiScale_32s8u_AC4R	835
7.57.1.14	nppiScale_32s8u_C1R	836
7.57.1.15	nppiScale_32s8u_C3R	836
7.57.1.16	nppiScale_32s8u_C4R	836
7.57.1.17	nppiScale_8u16s_AC4R	837
7.57.1.18	nppiScale_8u16s_C1R	837
7.57.1.19	nppiScale_8u16s_C3R	837
7.57.1.20	nppiScale_8u16s_C4R	838
7.57.1.21	nppiScale_8u16u_AC4R	838
7.57.1.22	nppiScale_8u16u_C1R	838
7.57.1.23	nppiScale_8u16u_C3R	839
7.57.1.24	nppiScale_8u16u_C4R	839
7.57.1.25	nppiScale_8u32f_AC4R	839
7.57.1.26	nppiScale_8u32f_C1R	840
7.57.1.27	nppiScale_8u32f_C3R	840
7.57.1.28	nppiScale_8u32f_C4R	840
7.57.1.29	nppiScale_8u32s_AC4R	841
7.57.1.30	nppiScale_8u32s_C1R	841
7.57.1.31	nppiScale_8u32s_C3R	842
7.57.1.32	nppiScale_8u32s_C4R	842
7.58	Copy Constant Border	843
7.58.1	Function Documentation	845
7.58.1.1	nppiCopyConstBorder_16s_AC4R	845
7.58.1.2	nppiCopyConstBorder_16s_C1R	845
7.58.1.3	nppiCopyConstBorder_16s_C3R	846
7.58.1.4	nppiCopyConstBorder_16s_C4R	846
7.58.1.5	nppiCopyConstBorder_16u_AC4R	847
7.58.1.6	nppiCopyConstBorder_16u_C1R	847
7.58.1.7	nppiCopyConstBorder_16u_C3R	848
7.58.1.8	nppiCopyConstBorder_16u_C4R	848
7.58.1.9	nppiCopyConstBorder_32f_AC4R	849

7.58.1.10	nppiCopyConstBorder_32f_C1R	849
7.58.1.11	nppiCopyConstBorder_32f_C3R	850
7.58.1.12	nppiCopyConstBorder_32f_C4R	850
7.58.1.13	nppiCopyConstBorder_32s_AC4R	851
7.58.1.14	nppiCopyConstBorder_32s_C1R	851
7.58.1.15	nppiCopyConstBorder_32s_C3R	852
7.58.1.16	nppiCopyConstBorder_32s_C4R	852
7.58.1.17	nppiCopyConstBorder_8u_AC4R	853
7.58.1.18	nppiCopyConstBorder_8u_C1R	853
7.58.1.19	nppiCopyConstBorder_8u_C3R	854
7.58.1.20	nppiCopyConstBorder_8u_C4R	854
7.59	Copy Replicate Border	856
7.59.1	Function Documentation	858
7.59.1.1	nppiCopyReplicateBorder_16s_AC4R	858
7.59.1.2	nppiCopyReplicateBorder_16s_C1R	858
7.59.1.3	nppiCopyReplicateBorder_16s_C3R	859
7.59.1.4	nppiCopyReplicateBorder_16s_C4R	859
7.59.1.5	nppiCopyReplicateBorder_16u_AC4R	860
7.59.1.6	nppiCopyReplicateBorder_16u_C1R	860
7.59.1.7	nppiCopyReplicateBorder_16u_C3R	861
7.59.1.8	nppiCopyReplicateBorder_16u_C4R	861
7.59.1.9	nppiCopyReplicateBorder_32f_AC4R	862
7.59.1.10	nppiCopyReplicateBorder_32f_C1R	862
7.59.1.11	nppiCopyReplicateBorder_32f_C3R	863
7.59.1.12	nppiCopyReplicateBorder_32f_C4R	863
7.59.1.13	nppiCopyReplicateBorder_32s_AC4R	864
7.59.1.14	nppiCopyReplicateBorder_32s_C1R	864
7.59.1.15	nppiCopyReplicateBorder_32s_C3R	865
7.59.1.16	nppiCopyReplicateBorder_32s_C4R	865
7.59.1.17	nppiCopyReplicateBorder_8u_AC4R	866
7.59.1.18	nppiCopyReplicateBorder_8u_C1R	866
7.59.1.19	nppiCopyReplicateBorder_8u_C3R	867
7.59.1.20	nppiCopyReplicateBorder_8u_C4R	867
7.60	Copy Wrap Border	868
7.60.1	Function Documentation	870
7.60.1.1	nppiCopyWrapBorder_16s_AC4R	870

7.60.1.2	nppiCopyWrapBorder_16s_C1R	871
7.60.1.3	nppiCopyWrapBorder_16s_C3R	871
7.60.1.4	nppiCopyWrapBorder_16s_C4R	872
7.60.1.5	nppiCopyWrapBorder_16u_AC4R	872
7.60.1.6	nppiCopyWrapBorder_16u_C1R	873
7.60.1.7	nppiCopyWrapBorder_16u_C3R	873
7.60.1.8	nppiCopyWrapBorder_16u_C4R	874
7.60.1.9	nppiCopyWrapBorder_32f_AC4R	874
7.60.1.10	nppiCopyWrapBorder_32f_C1R	875
7.60.1.11	nppiCopyWrapBorder_32f_C3R	875
7.60.1.12	nppiCopyWrapBorder_32f_C4R	876
7.60.1.13	nppiCopyWrapBorder_32s_AC4R	876
7.60.1.14	nppiCopyWrapBorder_32s_C1R	877
7.60.1.15	nppiCopyWrapBorder_32s_C3R	877
7.60.1.16	nppiCopyWrapBorder_32s_C4R	878
7.60.1.17	nppiCopyWrapBorder_8u_AC4R	878
7.60.1.18	nppiCopyWrapBorder_8u_C1R	879
7.60.1.19	nppiCopyWrapBorder_8u_C3R	879
7.60.1.20	nppiCopyWrapBorder_8u_C4R	880
7.61	Copy Sub-Pixel	881
7.61.1	Function Documentation	882
7.61.1.1	nppiCopySubpix_16s_AC4R	882
7.61.1.2	nppiCopySubpix_16s_C1R	883
7.61.1.3	nppiCopySubpix_16s_C3R	883
7.61.1.4	nppiCopySubpix_16s_C4R	884
7.61.1.5	nppiCopySubpix_16u_AC4R	884
7.61.1.6	nppiCopySubpix_16u_C1R	885
7.61.1.7	nppiCopySubpix_16u_C3R	885
7.61.1.8	nppiCopySubpix_16u_C4R	885
7.61.1.9	nppiCopySubpix_32f_AC4R	886
7.61.1.10	nppiCopySubpix_32f_C1R	886
7.61.1.11	nppiCopySubpix_32f_C3R	887
7.61.1.12	nppiCopySubpix_32f_C4R	887
7.61.1.13	nppiCopySubpix_32s_AC4R	887
7.61.1.14	nppiCopySubpix_32s_C1R	888
7.61.1.15	nppiCopySubpix_32s_C3R	888

7.61.1.16	nppiCopySubpix_32s_C4R	889
7.61.1.17	nppiCopySubpix_8u_AC4R	889
7.61.1.18	nppiCopySubpix_8u_C1R	890
7.61.1.19	nppiCopySubpix_8u_C3R	890
7.61.1.20	nppiCopySubpix_8u_C4R	890
7.62	Duplicate Channel	892
7.62.1	Function Documentation	893
7.62.1.1	nppiDup_16s_C1AC4R	893
7.62.1.2	nppiDup_16s_C1C3R	893
7.62.1.3	nppiDup_16s_C1C4R	894
7.62.1.4	nppiDup_16u_C1AC4R	894
7.62.1.5	nppiDup_16u_C1C3R	895
7.62.1.6	nppiDup_16u_C1C4R	895
7.62.1.7	nppiDup_32f_C1AC4R	895
7.62.1.8	nppiDup_32f_C1C3R	896
7.62.1.9	nppiDup_32f_C1C4R	896
7.62.1.10	nppiDup_32s_C1AC4R	896
7.62.1.11	nppiDup_32s_C1C3R	897
7.62.1.12	nppiDup_32s_C1C4R	897
7.62.1.13	nppiDup_8u_C1AC4R	897
7.62.1.14	nppiDup_8u_C1C3R	898
7.62.1.15	nppiDup_8u_C1C4R	898
7.63	Transpose	899
7.63.1	Function Documentation	900
7.63.1.1	nppiTranspose_16s_C1R	900
7.63.1.2	nppiTranspose_16s_C3R	900
7.63.1.3	nppiTranspose_16s_C4R	901
7.63.1.4	nppiTranspose_16u_C1R	901
7.63.1.5	nppiTranspose_16u_C3R	901
7.63.1.6	nppiTranspose_16u_C4R	902
7.63.1.7	nppiTranspose_32f_C1R	902
7.63.1.8	nppiTranspose_32f_C3R	902
7.63.1.9	nppiTranspose_32f_C4R	903
7.63.1.10	nppiTranspose_32s_C1R	903
7.63.1.11	nppiTranspose_32s_C3R	904
7.63.1.12	nppiTranspose_32s_C4R	904

7.63.1.13	nppiTranspose_8u_C1R	904
7.63.1.14	nppiTranspose_8u_C3R	905
7.63.1.15	nppiTranspose_8u_C4R	905
7.64	Swap Channels	906
7.64.1	Function Documentation	909
7.64.1.1	nppiSwapChannels_16s_AC4R	909
7.64.1.2	nppiSwapChannels_16s_C3C4R	909
7.64.1.3	nppiSwapChannels_16s_C3IR	910
7.64.1.4	nppiSwapChannels_16s_C3R	910
7.64.1.5	nppiSwapChannels_16s_C4C3R	910
7.64.1.6	nppiSwapChannels_16s_C4IR	911
7.64.1.7	nppiSwapChannels_16s_C4R	911
7.64.1.8	nppiSwapChannels_16u_AC4R	912
7.64.1.9	nppiSwapChannels_16u_C3C4R	912
7.64.1.10	nppiSwapChannels_16u_C3IR	913
7.64.1.11	nppiSwapChannels_16u_C3R	913
7.64.1.12	nppiSwapChannels_16u_C4C3R	913
7.64.1.13	nppiSwapChannels_16u_C4IR	914
7.64.1.14	nppiSwapChannels_16u_C4R	914
7.64.1.15	nppiSwapChannels_32f_AC4R	915
7.64.1.16	nppiSwapChannels_32f_C3C4R	915
7.64.1.17	nppiSwapChannels_32f_C3IR	916
7.64.1.18	nppiSwapChannels_32f_C3R	916
7.64.1.19	nppiSwapChannels_32f_C4C3R	916
7.64.1.20	nppiSwapChannels_32f_C4IR	917
7.64.1.21	nppiSwapChannels_32f_C4R	917
7.64.1.22	nppiSwapChannels_32s_AC4R	918
7.64.1.23	nppiSwapChannels_32s_C3C4R	918
7.64.1.24	nppiSwapChannels_32s_C3IR	919
7.64.1.25	nppiSwapChannels_32s_C3R	919
7.64.1.26	nppiSwapChannels_32s_C4C3R	919
7.64.1.27	nppiSwapChannels_32s_C4IR	920
7.64.1.28	nppiSwapChannels_32s_C4R	920
7.64.1.29	nppiSwapChannels_8u_AC4R	921
7.64.1.30	nppiSwapChannels_8u_C3C4R	921
7.64.1.31	nppiSwapChannels_8u_C3IR	922

7.64.1.32	nppiSwapChannels_8u_C3R	922
7.64.1.33	nppiSwapChannels_8u_C4C3R	922
7.64.1.34	nppiSwapChannels_8u_C4IR	923
7.64.1.35	nppiSwapChannels_8u_C4R	923
7.65	Filtering Functions	924
7.65.1	Detailed Description	924
7.66	1D Linear Filter	925
7.66.1	Function Documentation	941
7.66.1.1	nppiFilterColumn32f_16s_AC4R	941
7.66.1.2	nppiFilterColumn32f_16s_C1R	941
7.66.1.3	nppiFilterColumn32f_16s_C3R	942
7.66.1.4	nppiFilterColumn32f_16s_C4R	942
7.66.1.5	nppiFilterColumn32f_16u_AC4R	943
7.66.1.6	nppiFilterColumn32f_16u_C1R	943
7.66.1.7	nppiFilterColumn32f_16u_C3R	944
7.66.1.8	nppiFilterColumn32f_16u_C4R	944
7.66.1.9	nppiFilterColumn32f_8u_AC4R	945
7.66.1.10	nppiFilterColumn32f_8u_C1R	945
7.66.1.11	nppiFilterColumn32f_8u_C3R	946
7.66.1.12	nppiFilterColumn32f_8u_C4R	946
7.66.1.13	nppiFilterColumn_16s_AC4R	947
7.66.1.14	nppiFilterColumn_16s_C1R	947
7.66.1.15	nppiFilterColumn_16s_C3R	948
7.66.1.16	nppiFilterColumn_16s_C4R	948
7.66.1.17	nppiFilterColumn_16u_AC4R	949
7.66.1.18	nppiFilterColumn_16u_C1R	949
7.66.1.19	nppiFilterColumn_16u_C3R	950
7.66.1.20	nppiFilterColumn_16u_C4R	950
7.66.1.21	nppiFilterColumn_32f_AC4R	951
7.66.1.22	nppiFilterColumn_32f_C1R	951
7.66.1.23	nppiFilterColumn_32f_C3R	952
7.66.1.24	nppiFilterColumn_32f_C4R	952
7.66.1.25	nppiFilterColumn_64f_C1R	953
7.66.1.26	nppiFilterColumn_8u_AC4R	953
7.66.1.27	nppiFilterColumn_8u_C1R	954
7.66.1.28	nppiFilterColumn_8u_C3R	954

7.66.1.29 nppiFilterColumn_8u_C4R	955
7.66.1.30 nppiFilterGauss_16s_AC4R	955
7.66.1.31 nppiFilterGauss_16s_C1R	955
7.66.1.32 nppiFilterGauss_16s_C3R	956
7.66.1.33 nppiFilterGauss_16s_C4R	956
7.66.1.34 nppiFilterGauss_16u_AC4R	957
7.66.1.35 nppiFilterGauss_16u_C1R	957
7.66.1.36 nppiFilterGauss_16u_C3R	957
7.66.1.37 nppiFilterGauss_16u_C4R	958
7.66.1.38 nppiFilterGauss_32f_AC4R	958
7.66.1.39 nppiFilterGauss_32f_C1R	958
7.66.1.40 nppiFilterGauss_32f_C3R	959
7.66.1.41 nppiFilterGauss_32f_C4R	959
7.66.1.42 nppiFilterGauss_8u_AC4R	959
7.66.1.43 nppiFilterGauss_8u_C1R	960
7.66.1.44 nppiFilterGauss_8u_C3R	960
7.66.1.45 nppiFilterGauss_8u_C4R	960
7.66.1.46 nppiFilterHighPass_16s_AC4R	961
7.66.1.47 nppiFilterHighPass_16s_C1R	961
7.66.1.48 nppiFilterHighPass_16s_C3R	961
7.66.1.49 nppiFilterHighPass_16s_C4R	962
7.66.1.50 nppiFilterHighPass_16u_AC4R	962
7.66.1.51 nppiFilterHighPass_16u_C1R	962
7.66.1.52 nppiFilterHighPass_16u_C3R	963
7.66.1.53 nppiFilterHighPass_16u_C4R	963
7.66.1.54 nppiFilterHighPass_32f_AC4R	963
7.66.1.55 nppiFilterHighPass_32f_C1R	964
7.66.1.56 nppiFilterHighPass_32f_C3R	964
7.66.1.57 nppiFilterHighPass_32f_C4R	964
7.66.1.58 nppiFilterHighPass_8u_AC4R	965
7.66.1.59 nppiFilterHighPass_8u_C1R	965
7.66.1.60 nppiFilterHighPass_8u_C3R	965
7.66.1.61 nppiFilterHighPass_8u_C4R	966
7.66.1.62 nppiFilterLaplace_16s_AC4R	966
7.66.1.63 nppiFilterLaplace_16s_C1R	966
7.66.1.64 nppiFilterLaplace_16s_C3R	967

7.66.1.65	nppiFilterLaplace_16s_C4R	967
7.66.1.66	nppiFilterLaplace_32f_AC4R	967
7.66.1.67	nppiFilterLaplace_32f_C1R	968
7.66.1.68	nppiFilterLaplace_32f_C3R	968
7.66.1.69	nppiFilterLaplace_32f_C4R	968
7.66.1.70	nppiFilterLaplace_8s16s_C1R	969
7.66.1.71	nppiFilterLaplace_8u16s_C1R	969
7.66.1.72	nppiFilterLaplace_8u_AC4R	969
7.66.1.73	nppiFilterLaplace_8u_C1R	970
7.66.1.74	nppiFilterLaplace_8u_C3R	970
7.66.1.75	nppiFilterLaplace_8u_C4R	970
7.66.1.76	nppiFilterLowPass_16s_AC4R	971
7.66.1.77	nppiFilterLowPass_16s_C1R	971
7.66.1.78	nppiFilterLowPass_16s_C3R	971
7.66.1.79	nppiFilterLowPass_16s_C4R	972
7.66.1.80	nppiFilterLowPass_16u_AC4R	972
7.66.1.81	nppiFilterLowPass_16u_C1R	972
7.66.1.82	nppiFilterLowPass_16u_C3R	973
7.66.1.83	nppiFilterLowPass_16u_C4R	973
7.66.1.84	nppiFilterLowPass_32f_AC4R	973
7.66.1.85	nppiFilterLowPass_32f_C1R	974
7.66.1.86	nppiFilterLowPass_32f_C3R	974
7.66.1.87	nppiFilterLowPass_32f_C4R	974
7.66.1.88	nppiFilterLowPass_8u_AC4R	975
7.66.1.89	nppiFilterLowPass_8u_C1R	975
7.66.1.90	nppiFilterLowPass_8u_C3R	975
7.66.1.91	nppiFilterLowPass_8u_C4R	976
7.66.1.92	nppiFilterRobertsDown_16s_AC4R	976
7.66.1.93	nppiFilterRobertsDown_16s_C1R	976
7.66.1.94	nppiFilterRobertsDown_16s_C3R	977
7.66.1.95	nppiFilterRobertsDown_16s_C4R	977
7.66.1.96	nppiFilterRobertsDown_32f_AC4R	977
7.66.1.97	nppiFilterRobertsDown_32f_C1R	978
7.66.1.98	nppiFilterRobertsDown_32f_C3R	978
7.66.1.99	nppiFilterRobertsDown_32f_C4R	978
7.66.1.100	nppiFilterRobertsDown_8u_AC4R	979

7.66.1.101nppiFilterRobertsDown_8u_C1R	979
7.66.1.102nppiFilterRobertsDown_8u_C3R	979
7.66.1.103nppiFilterRobertsDown_8u_C4R	980
7.66.1.104nppiFilterRobertsUp_16s_AC4R	980
7.66.1.105nppiFilterRobertsUp_16s_C1R	980
7.66.1.106nppiFilterRobertsUp_16s_C3R	981
7.66.1.107nppiFilterRobertsUp_16s_C4R	981
7.66.1.108nppiFilterRobertsUp_32f_AC4R	981
7.66.1.109nppiFilterRobertsUp_32f_C1R	982
7.66.1.110nppiFilterRobertsUp_32f_C3R	982
7.66.1.111nppiFilterRobertsUp_32f_C4R	982
7.66.1.112nppiFilterRobertsUp_8u_AC4R	983
7.66.1.113nppiFilterRobertsUp_8u_C1R	983
7.66.1.114nppiFilterRobertsUp_8u_C3R	983
7.66.1.115nppiFilterRobertsUp_8u_C4R	984
7.66.1.116nppiFilterRow32f_16s_AC4R	984
7.66.1.117nppiFilterRow32f_16s_C1R	984
7.66.1.118nppiFilterRow32f_16s_C3R	985
7.66.1.119nppiFilterRow32f_16s_C4R	985
7.66.1.120nppiFilterRow32f_16u_AC4R	986
7.66.1.121nppiFilterRow32f_16u_C1R	986
7.66.1.122nppiFilterRow32f_16u_C3R	987
7.66.1.123nppiFilterRow32f_16u_C4R	987
7.66.1.124nppiFilterRow32f_8u_AC4R	988
7.66.1.125nppiFilterRow32f_8u_C1R	988
7.66.1.126nppiFilterRow32f_8u_C3R	989
7.66.1.127nppiFilterRow32f_8u_C4R	989
7.66.1.128nppiFilterRow_16s_AC4R	990
7.66.1.129nppiFilterRow_16s_C1R	990
7.66.1.130nppiFilterRow_16s_C3R	991
7.66.1.131nppiFilterRow_16s_C4R	991
7.66.1.132nppiFilterRow_16u_AC4R	992
7.66.1.133nppiFilterRow_16u_C1R	992
7.66.1.134nppiFilterRow_16u_C3R	993
7.66.1.135nppiFilterRow_16u_C4R	993
7.66.1.136nppiFilterRow_32f_AC4R	994

7.66.1.137	<code>nppiFilterRow_32f_C1R</code>	994
7.66.1.138	<code>nppiFilterRow_32f_C3R</code>	995
7.66.1.139	<code>nppiFilterRow_32f_C4R</code>	995
7.66.1.140	<code>nppiFilterRow_64f_C1R</code>	996
7.66.1.141	<code>nppiFilterRow_8u_AC4R</code>	996
7.66.1.142	<code>nppiFilterRow_8u_C1R</code>	997
7.66.1.143	<code>nppiFilterRow_8u_C3R</code>	997
7.66.1.144	<code>nppiFilterRow_8u_C4R</code>	998
7.66.1.145	<code>nppiFilterSharpen_16s_AC4R</code>	998
7.66.1.146	<code>nppiFilterSharpen_16s_C1R</code>	998
7.66.1.147	<code>nppiFilterSharpen_16s_C3R</code>	999
7.66.1.148	<code>nppiFilterSharpen_16s_C4R</code>	999
7.66.1.149	<code>nppiFilterSharpen_16u_AC4R</code>	1000
7.66.1.150	<code>nppiFilterSharpen_16u_C1R</code>	1000
7.66.1.151	<code>nppiFilterSharpen_16u_C3R</code>	1000
7.66.1.152	<code>nppiFilterSharpen_16u_C4R</code>	1001
7.66.1.153	<code>nppiFilterSharpen_32f_AC4R</code>	1001
7.66.1.154	<code>nppiFilterSharpen_32f_C1R</code>	1001
7.66.1.155	<code>nppiFilterSharpen_32f_C3R</code>	1002
7.66.1.156	<code>nppiFilterSharpen_32f_C4R</code>	1002
7.66.1.157	<code>nppiFilterSharpen_8u_AC4R</code>	1002
7.66.1.158	<code>nppiFilterSharpen_8u_C1R</code>	1003
7.66.1.159	<code>nppiFilterSharpen_8u_C3R</code>	1003
7.66.1.160	<code>nppiFilterSharpen_8u_C4R</code>	1003
7.66.1.161	<code>nppiFilterSobelCross_32f_C1R</code>	1004
7.66.1.162	<code>nppiFilterSobelCross_8s16s_C1R</code>	1004
7.66.1.163	<code>nppiFilterSobelCross_8u16s_C1R</code>	1004
7.66.1.164	<code>nppiFilterSobelVertSecond_32f_C1R</code>	1005
7.66.1.165	<code>nppiFilterSobelVertSecond_8s16s_C1R</code>	1005
7.66.1.166	<code>nppiFilterSobelVertSecond_8u16s_C1R</code>	1005
7.67	1D Window Sum	1007
7.67.1	Function Documentation	1007
7.67.1.1	<code>nppiSumWindowColumn_8u32f_C1R</code>	1007
7.67.1.2	<code>nppiSumWindowRow_8u32f_C1R</code>	1007
7.68	Convolution	1009
7.68.1	Function Documentation	1013

7.68.1.1	nppiFilter32f_16s_AC4R	1013
7.68.1.2	nppiFilter32f_16s_C1R	1013
7.68.1.3	nppiFilter32f_16s_C3R	1014
7.68.1.4	nppiFilter32f_16s_C4R	1014
7.68.1.5	nppiFilter32f_16u_AC4R	1015
7.68.1.6	nppiFilter32f_16u_C1R	1015
7.68.1.7	nppiFilter32f_16u_C3R	1016
7.68.1.8	nppiFilter32f_16u_C4R	1016
7.68.1.9	nppiFilter32f_32s_AC4R	1017
7.68.1.10	nppiFilter32f_32s_C1R	1017
7.68.1.11	nppiFilter32f_32s_C3R	1018
7.68.1.12	nppiFilter32f_32s_C4R	1018
7.68.1.13	nppiFilter32f_8s16s_AC4R	1019
7.68.1.14	nppiFilter32f_8s16s_C1R	1019
7.68.1.15	nppiFilter32f_8s16s_C3R	1020
7.68.1.16	nppiFilter32f_8s16s_C4R	1020
7.68.1.17	nppiFilter32f_8s_AC4R	1021
7.68.1.18	nppiFilter32f_8s_C1R	1021
7.68.1.19	nppiFilter32f_8s_C3R	1022
7.68.1.20	nppiFilter32f_8s_C4R	1022
7.68.1.21	nppiFilter32f_8u16s_AC4R	1023
7.68.1.22	nppiFilter32f_8u16s_C1R	1023
7.68.1.23	nppiFilter32f_8u16s_C3R	1024
7.68.1.24	nppiFilter32f_8u16s_C4R	1024
7.68.1.25	nppiFilter32f_8u_AC4R	1025
7.68.1.26	nppiFilter32f_8u_C1R	1025
7.68.1.27	nppiFilter32f_8u_C3R	1026
7.68.1.28	nppiFilter32f_8u_C4R	1026
7.68.1.29	nppiFilter_16s_AC4R	1027
7.68.1.30	nppiFilter_16s_C1R	1027
7.68.1.31	nppiFilter_16s_C3R	1028
7.68.1.32	nppiFilter_16s_C4R	1028
7.68.1.33	nppiFilter_16u_AC4R	1029
7.68.1.34	nppiFilter_16u_C1R	1029
7.68.1.35	nppiFilter_16u_C3R	1030
7.68.1.36	nppiFilter_16u_C4R	1030

7.68.1.37	nppiFilter_32f_AC4R	1031
7.68.1.38	nppiFilter_32f_C1R	1031
7.68.1.39	nppiFilter_32f_C3R	1032
7.68.1.40	nppiFilter_32f_C4R	1032
7.68.1.41	nppiFilter_64f_C1R	1033
7.68.1.42	nppiFilter_8u_AC4R	1033
7.68.1.43	nppiFilter_8u_C1R	1034
7.68.1.44	nppiFilter_8u_C3R	1034
7.68.1.45	nppiFilter_8u_C4R	1035
7.69	2D Fixed Linear Filters	1036
7.69.1	Function Documentation	1037
7.69.1.1	nppiFilterBox_16s_AC4R	1037
7.69.1.2	nppiFilterBox_16s_C1R	1038
7.69.1.3	nppiFilterBox_16s_C3R	1038
7.69.1.4	nppiFilterBox_16s_C4R	1038
7.69.1.5	nppiFilterBox_16u_AC4R	1039
7.69.1.6	nppiFilterBox_16u_C1R	1039
7.69.1.7	nppiFilterBox_16u_C3R	1040
7.69.1.8	nppiFilterBox_16u_C4R	1040
7.69.1.9	nppiFilterBox_32f_AC4R	1040
7.69.1.10	nppiFilterBox_32f_C1R	1041
7.69.1.11	nppiFilterBox_32f_C3R	1041
7.69.1.12	nppiFilterBox_32f_C4R	1042
7.69.1.13	nppiFilterBox_64f_C1R	1042
7.69.1.14	nppiFilterBox_8u_AC4R	1042
7.69.1.15	nppiFilterBox_8u_C1R	1043
7.69.1.16	nppiFilterBox_8u_C3R	1043
7.69.1.17	nppiFilterBox_8u_C4R	1044
7.70	Rank Filters	1045
7.70.1	Function Documentation	1047
7.70.1.1	nppiFilterMax_16s_AC4R	1047
7.70.1.2	nppiFilterMax_16s_C1R	1048
7.70.1.3	nppiFilterMax_16s_C3R	1048
7.70.1.4	nppiFilterMax_16s_C4R	1049
7.70.1.5	nppiFilterMax_16u_AC4R	1049
7.70.1.6	nppiFilterMax_16u_C1R	1049

7.70.1.7	nppiFilterMax_16u_C3R	1050
7.70.1.8	nppiFilterMax_16u_C4R	1050
7.70.1.9	nppiFilterMax_32f_AC4R	1051
7.70.1.10	nppiFilterMax_32f_C1R	1051
7.70.1.11	nppiFilterMax_32f_C3R	1051
7.70.1.12	nppiFilterMax_32f_C4R	1052
7.70.1.13	nppiFilterMax_8u_AC4R	1052
7.70.1.14	nppiFilterMax_8u_C1R	1053
7.70.1.15	nppiFilterMax_8u_C3R	1053
7.70.1.16	nppiFilterMax_8u_C4R	1053
7.70.1.17	nppiFilterMin_16s_AC4R	1054
7.70.1.18	nppiFilterMin_16s_C1R	1054
7.70.1.19	nppiFilterMin_16s_C3R	1055
7.70.1.20	nppiFilterMin_16s_C4R	1055
7.70.1.21	nppiFilterMin_16u_AC4R	1055
7.70.1.22	nppiFilterMin_16u_C1R	1056
7.70.1.23	nppiFilterMin_16u_C3R	1056
7.70.1.24	nppiFilterMin_16u_C4R	1057
7.70.1.25	nppiFilterMin_32f_AC4R	1057
7.70.1.26	nppiFilterMin_32f_C1R	1057
7.70.1.27	nppiFilterMin_32f_C3R	1058
7.70.1.28	nppiFilterMin_32f_C4R	1058
7.70.1.29	nppiFilterMin_8u_AC4R	1059
7.70.1.30	nppiFilterMin_8u_C1R	1059
7.70.1.31	nppiFilterMin_8u_C3R	1059
7.70.1.32	nppiFilterMin_8u_C4R	1060
7.71	Fixed Filters	1061
7.71.1	Detailed Description	1067
7.71.2	Function Documentation	1067
7.71.2.1	nppiFilterPrewittHoriz_16s_AC4R	1067
7.71.2.2	nppiFilterPrewittHoriz_16s_C1R	1068
7.71.2.3	nppiFilterPrewittHoriz_16s_C3R	1068
7.71.2.4	nppiFilterPrewittHoriz_16s_C4R	1068
7.71.2.5	nppiFilterPrewittHoriz_32f_AC4R	1069
7.71.2.6	nppiFilterPrewittHoriz_32f_C1R	1069
7.71.2.7	nppiFilterPrewittHoriz_32f_C3R	1069

7.71.2.8	nppiFilterPrewittHoriz_32f_C4R	1070
7.71.2.9	nppiFilterPrewittHoriz_8u_AC4R	1070
7.71.2.10	nppiFilterPrewittHoriz_8u_C1R	1070
7.71.2.11	nppiFilterPrewittHoriz_8u_C3R	1071
7.71.2.12	nppiFilterPrewittHoriz_8u_C4R	1071
7.71.2.13	nppiFilterPrewittVert_16s_AC4R	1071
7.71.2.14	nppiFilterPrewittVert_16s_C1R	1072
7.71.2.15	nppiFilterPrewittVert_16s_C3R	1072
7.71.2.16	nppiFilterPrewittVert_16s_C4R	1072
7.71.2.17	nppiFilterPrewittVert_32f_AC4R	1073
7.71.2.18	nppiFilterPrewittVert_32f_C1R	1073
7.71.2.19	nppiFilterPrewittVert_32f_C3R	1073
7.71.2.20	nppiFilterPrewittVert_32f_C4R	1074
7.71.2.21	nppiFilterPrewittVert_8u_AC4R	1074
7.71.2.22	nppiFilterPrewittVert_8u_C1R	1074
7.71.2.23	nppiFilterPrewittVert_8u_C3R	1075
7.71.2.24	nppiFilterPrewittVert_8u_C4R	1075
7.71.2.25	nppiFilterScharrHoriz_32f_C1R	1075
7.71.2.26	nppiFilterScharrHoriz_8s16s_C1R	1076
7.71.2.27	nppiFilterScharrHoriz_8u16s_C1R	1076
7.71.2.28	nppiFilterScharrVert_32f_C1R	1076
7.71.2.29	nppiFilterScharrVert_8s16s_C1R	1077
7.71.2.30	nppiFilterScharrVert_8u16s_C1R	1077
7.71.2.31	nppiFilterSobelHoriz_16s_AC4R	1077
7.71.2.32	nppiFilterSobelHoriz_16s_C1R	1078
7.71.2.33	nppiFilterSobelHoriz_16s_C3R	1078
7.71.2.34	nppiFilterSobelHoriz_16s_C4R	1078
7.71.2.35	nppiFilterSobelHoriz_32f_AC4R	1079
7.71.2.36	nppiFilterSobelHoriz_32f_C1R	1079
7.71.2.37	nppiFilterSobelHoriz_32f_C3R	1079
7.71.2.38	nppiFilterSobelHoriz_32f_C4R	1080
7.71.2.39	nppiFilterSobelHoriz_8s16s_C1R	1080
7.71.2.40	nppiFilterSobelHoriz_8u16s_C1R	1080
7.71.2.41	nppiFilterSobelHoriz_8u_AC4R	1081
7.71.2.42	nppiFilterSobelHoriz_8u_C1R	1081
7.71.2.43	nppiFilterSobelHoriz_8u_C3R	1081

7.71.2.44	<code>nppiFilterSobelHoriz_8u_C4R</code>	1082
7.71.2.45	<code>nppiFilterSobelHorizMask_32f_C1R</code>	1082
7.71.2.46	<code>nppiFilterSobelHorizSecond_32f_C1R</code>	1082
7.71.2.47	<code>nppiFilterSobelHorizSecond_8s16s_C1R</code>	1083
7.71.2.48	<code>nppiFilterSobelHorizSecond_8u16s_C1R</code>	1083
7.71.2.49	<code>nppiFilterSobelVert_16s_AC4R</code>	1083
7.71.2.50	<code>nppiFilterSobelVert_16s_C1R</code>	1084
7.71.2.51	<code>nppiFilterSobelVert_16s_C3R</code>	1084
7.71.2.52	<code>nppiFilterSobelVert_16s_C4R</code>	1084
7.71.2.53	<code>nppiFilterSobelVert_32f_AC4R</code>	1085
7.71.2.54	<code>nppiFilterSobelVert_32f_C1R</code>	1085
7.71.2.55	<code>nppiFilterSobelVert_32f_C3R</code>	1085
7.71.2.56	<code>nppiFilterSobelVert_32f_C4R</code>	1086
7.71.2.57	<code>nppiFilterSobelVert_8s16s_C1R</code>	1086
7.71.2.58	<code>nppiFilterSobelVert_8u16s_C1R</code>	1087
7.71.2.59	<code>nppiFilterSobelVert_8u_AC4R</code>	1087
7.71.2.60	<code>nppiFilterSobelVert_8u_C1R</code>	1087
7.71.2.61	<code>nppiFilterSobelVert_8u_C3R</code>	1088
7.71.2.62	<code>nppiFilterSobelVert_8u_C4R</code>	1088
7.71.2.63	<code>nppiFilterSobelVertMask_32f_C1R</code>	1088
7.72	Geometry Transforms	1089
7.72.1	Detailed Description	1089
7.72.2	Geometric Transform API Specifics	1089
7.72.2.1	Geometric Transforms and ROIs	1089
7.72.2.2	Pixel Interpolation	1089
7.73	ResizeSqrPixel	1091
7.73.1	Detailed Description	1094
7.73.2	Error Codes	1094
7.73.3	Function Documentation	1095
7.73.3.1	<code>nppiGetResizeRect</code>	1095
7.73.3.2	<code>nppiResizeSqrPixel_16s_AC4R</code>	1095
7.73.3.3	<code>nppiResizeSqrPixel_16s_C1R</code>	1096
7.73.3.4	<code>nppiResizeSqrPixel_16s_C3R</code>	1096
7.73.3.5	<code>nppiResizeSqrPixel_16s_C4R</code>	1097
7.73.3.6	<code>nppiResizeSqrPixel_16s_P3R</code>	1097
7.73.3.7	<code>nppiResizeSqrPixel_16s_P4R</code>	1098

7.73.3.8	<code>nppiResizeSqrPixel_16u_AC4R</code>	1098
7.73.3.9	<code>nppiResizeSqrPixel_16u_C1R</code>	1099
7.73.3.10	<code>nppiResizeSqrPixel_16u_C3R</code>	1099
7.73.3.11	<code>nppiResizeSqrPixel_16u_C4R</code>	1100
7.73.3.12	<code>nppiResizeSqrPixel_16u_P3R</code>	1101
7.73.3.13	<code>nppiResizeSqrPixel_16u_P4R</code>	1101
7.73.3.14	<code>nppiResizeSqrPixel_32f_AC4R</code>	1102
7.73.3.15	<code>nppiResizeSqrPixel_32f_C1R</code>	1102
7.73.3.16	<code>nppiResizeSqrPixel_32f_C3R</code>	1103
7.73.3.17	<code>nppiResizeSqrPixel_32f_C4R</code>	1103
7.73.3.18	<code>nppiResizeSqrPixel_32f_P3R</code>	1104
7.73.3.19	<code>nppiResizeSqrPixel_32f_P4R</code>	1105
7.73.3.20	<code>nppiResizeSqrPixel_64f_AC4R</code>	1105
7.73.3.21	<code>nppiResizeSqrPixel_64f_C1R</code>	1106
7.73.3.22	<code>nppiResizeSqrPixel_64f_C3R</code>	1106
7.73.3.23	<code>nppiResizeSqrPixel_64f_C4R</code>	1107
7.73.3.24	<code>nppiResizeSqrPixel_64f_P3R</code>	1107
7.73.3.25	<code>nppiResizeSqrPixel_64f_P4R</code>	1108
7.73.3.26	<code>nppiResizeSqrPixel_8u_AC4R</code>	1109
7.73.3.27	<code>nppiResizeSqrPixel_8u_C1R</code>	1109
7.73.3.28	<code>nppiResizeSqrPixel_8u_C3R</code>	1110
7.73.3.29	<code>nppiResizeSqrPixel_8u_C4R</code>	1110
7.73.3.30	<code>nppiResizeSqrPixel_8u_P3R</code>	1111
7.73.3.31	<code>nppiResizeSqrPixel_8u_P4R</code>	1111
7.74	Resize	1113
7.74.1	Detailed Description	1114
7.74.2	Error Codes	1115
7.74.3	Function Documentation	1115
7.74.3.1	<code>nppiResize_16u_AC4R</code>	1115
7.74.3.2	<code>nppiResize_16u_C1R</code>	1116
7.74.3.3	<code>nppiResize_16u_C3R</code>	1116
7.74.3.4	<code>nppiResize_16u_C4R</code>	1117
7.74.3.5	<code>nppiResize_16u_P3R</code>	1117
7.74.3.6	<code>nppiResize_16u_P4R</code>	1118
7.74.3.7	<code>nppiResize_32f_AC4R</code>	1118
7.74.3.8	<code>nppiResize_32f_C1R</code>	1119

7.74.3.9	nppiResize_32f_C3R	1119
7.74.3.10	nppiResize_32f_C4R	1120
7.74.3.11	nppiResize_32f_P3R	1120
7.74.3.12	nppiResize_32f_P4R	1121
7.74.3.13	nppiResize_8u_AC4R	1121
7.74.3.14	nppiResize_8u_C1R	1122
7.74.3.15	nppiResize_8u_C3R	1122
7.74.3.16	nppiResize_8u_C4R	1123
7.74.3.17	nppiResize_8u_P3R	1123
7.74.3.18	nppiResize_8u_P4R	1124
7.75	Remap	1125
7.75.1	Detailed Description	1128
7.75.2	Error Codes	1128
7.75.3	Function Documentation	1128
7.75.3.1	nppiRemap_16s_AC4R	1128
7.75.3.2	nppiRemap_16s_C1R	1129
7.75.3.3	nppiRemap_16s_C3R	1130
7.75.3.4	nppiRemap_16s_C4R	1130
7.75.3.5	nppiRemap_16s_P3R	1131
7.75.3.6	nppiRemap_16s_P4R	1131
7.75.3.7	nppiRemap_16u_AC4R	1132
7.75.3.8	nppiRemap_16u_C1R	1133
7.75.3.9	nppiRemap_16u_C3R	1133
7.75.3.10	nppiRemap_16u_C4R	1134
7.75.3.11	nppiRemap_16u_P3R	1134
7.75.3.12	nppiRemap_16u_P4R	1135
7.75.3.13	nppiRemap_32f_AC4R	1136
7.75.3.14	nppiRemap_32f_C1R	1136
7.75.3.15	nppiRemap_32f_C3R	1137
7.75.3.16	nppiRemap_32f_C4R	1137
7.75.3.17	nppiRemap_32f_P3R	1138
7.75.3.18	nppiRemap_32f_P4R	1139
7.75.3.19	nppiRemap_64f_AC4R	1139
7.75.3.20	nppiRemap_64f_C1R	1140
7.75.3.21	nppiRemap_64f_C3R	1140
7.75.3.22	nppiRemap_64f_C4R	1141

7.75.3.23	nppiRemap_64f_P3R	1142
7.75.3.24	nppiRemap_64f_P4R	1142
7.75.3.25	nppiRemap_8u_AC4R	1143
7.75.3.26	nppiRemap_8u_C1R	1143
7.75.3.27	nppiRemap_8u_C3R	1144
7.75.3.28	nppiRemap_8u_C4R	1145
7.75.3.29	nppiRemap_8u_P3R	1145
7.75.3.30	nppiRemap_8u_P4R	1146
7.76	Rotate	1147
7.76.1	Detailed Description	1148
7.76.2	Rotate Error Codes	1148
7.76.3	Function Documentation	1148
7.76.3.1	nppiGetRotateBound	1148
7.76.3.2	nppiGetRotateQuad	1149
7.76.3.3	nppiRotate_16u_AC4R	1149
7.76.3.4	nppiRotate_16u_C1R	1150
7.76.3.5	nppiRotate_16u_C3R	1150
7.76.3.6	nppiRotate_16u_C4R	1151
7.76.3.7	nppiRotate_32f_AC4R	1151
7.76.3.8	nppiRotate_32f_C1R	1152
7.76.3.9	nppiRotate_32f_C3R	1152
7.76.3.10	nppiRotate_32f_C4R	1153
7.76.3.11	nppiRotate_8u_AC4R	1153
7.76.3.12	nppiRotate_8u_C1R	1154
7.76.3.13	nppiRotate_8u_C3R	1154
7.76.3.14	nppiRotate_8u_C4R	1155
7.77	Mirror	1156
7.77.1	Detailed Description	1159
7.77.2	Mirror Error Codes	1159
7.77.3	Function Documentation	1159
7.77.3.1	nppiMirror_16s_AC4IR	1159
7.77.3.2	nppiMirror_16s_AC4R	1159
7.77.3.3	nppiMirror_16s_C1IR	1160
7.77.3.4	nppiMirror_16s_C1R	1160
7.77.3.5	nppiMirror_16s_C3IR	1160
7.77.3.6	nppiMirror_16s_C3R	1161

7.77.3.7	nppiMirror_16s_C4IR	1161
7.77.3.8	nppiMirror_16s_C4R	1161
7.77.3.9	nppiMirror_16u_AC4IR	1162
7.77.3.10	nppiMirror_16u_AC4R	1162
7.77.3.11	nppiMirror_16u_C1IR	1163
7.77.3.12	nppiMirror_16u_C1R	1163
7.77.3.13	nppiMirror_16u_C3IR	1163
7.77.3.14	nppiMirror_16u_C3R	1164
7.77.3.15	nppiMirror_16u_C4IR	1164
7.77.3.16	nppiMirror_16u_C4R	1164
7.77.3.17	nppiMirror_32f_AC4IR	1165
7.77.3.18	nppiMirror_32f_AC4R	1165
7.77.3.19	nppiMirror_32f_C1IR	1165
7.77.3.20	nppiMirror_32f_C1R	1166
7.77.3.21	nppiMirror_32f_C3IR	1166
7.77.3.22	nppiMirror_32f_C3R	1166
7.77.3.23	nppiMirror_32f_C4IR	1167
7.77.3.24	nppiMirror_32f_C4R	1167
7.77.3.25	nppiMirror_32s_AC4IR	1167
7.77.3.26	nppiMirror_32s_AC4R	1168
7.77.3.27	nppiMirror_32s_C1IR	1168
7.77.3.28	nppiMirror_32s_C1R	1168
7.77.3.29	nppiMirror_32s_C3IR	1169
7.77.3.30	nppiMirror_32s_C3R	1169
7.77.3.31	nppiMirror_32s_C4IR	1169
7.77.3.32	nppiMirror_32s_C4R	1170
7.77.3.33	nppiMirror_8u_AC4IR	1170
7.77.3.34	nppiMirror_8u_AC4R	1170
7.77.3.35	nppiMirror_8u_C1IR	1171
7.77.3.36	nppiMirror_8u_C1R	1171
7.77.3.37	nppiMirror_8u_C3IR	1171
7.77.3.38	nppiMirror_8u_C3R	1172
7.77.3.39	nppiMirror_8u_C4IR	1172
7.77.3.40	nppiMirror_8u_C4R	1172
7.78	Affine Transforms	1173
7.78.1	Detailed Description	1182

7.78.2	Affine Transform Error Codes	1182
7.78.3	Function Documentation	1182
7.78.3.1	nppiGetAffineBound	1182
7.78.3.2	nppiGetAffineQuad	1182
7.78.3.3	nppiGetAffineTransform	1183
7.78.3.4	nppiWarpAffine_16u_AC4R	1184
7.78.3.5	nppiWarpAffine_16u_C1R	1184
7.78.3.6	nppiWarpAffine_16u_C3R	1185
7.78.3.7	nppiWarpAffine_16u_C4R	1185
7.78.3.8	nppiWarpAffine_16u_P3R	1186
7.78.3.9	nppiWarpAffine_16u_P4R	1186
7.78.3.10	nppiWarpAffine_32f_AC4R	1187
7.78.3.11	nppiWarpAffine_32f_C1R	1187
7.78.3.12	nppiWarpAffine_32f_C3R	1188
7.78.3.13	nppiWarpAffine_32f_C4R	1188
7.78.3.14	nppiWarpAffine_32f_P3R	1189
7.78.3.15	nppiWarpAffine_32f_P4R	1189
7.78.3.16	nppiWarpAffine_32s_AC4R	1190
7.78.3.17	nppiWarpAffine_32s_C1R	1190
7.78.3.18	nppiWarpAffine_32s_C3R	1191
7.78.3.19	nppiWarpAffine_32s_C4R	1191
7.78.3.20	nppiWarpAffine_32s_P3R	1192
7.78.3.21	nppiWarpAffine_32s_P4R	1192
7.78.3.22	nppiWarpAffine_64f_AC4R	1193
7.78.3.23	nppiWarpAffine_64f_C1R	1193
7.78.3.24	nppiWarpAffine_64f_C3R	1194
7.78.3.25	nppiWarpAffine_64f_C4R	1194
7.78.3.26	nppiWarpAffine_64f_P3R	1195
7.78.3.27	nppiWarpAffine_64f_P4R	1195
7.78.3.28	nppiWarpAffine_8u_AC4R	1196
7.78.3.29	nppiWarpAffine_8u_C1R	1196
7.78.3.30	nppiWarpAffine_8u_C3R	1197
7.78.3.31	nppiWarpAffine_8u_C4R	1197
7.78.3.32	nppiWarpAffine_8u_P3R	1198
7.78.3.33	nppiWarpAffine_8u_P4R	1198
7.78.3.34	nppiWarpAffineBack_16u_AC4R	1199

7.78.3.35 nppiWarpAffineBack_16u_C1R	1199
7.78.3.36 nppiWarpAffineBack_16u_C3R	1200
7.78.3.37 nppiWarpAffineBack_16u_C4R	1200
7.78.3.38 nppiWarpAffineBack_16u_P3R	1201
7.78.3.39 nppiWarpAffineBack_16u_P4R	1201
7.78.3.40 nppiWarpAffineBack_32f_AC4R	1202
7.78.3.41 nppiWarpAffineBack_32f_C1R	1202
7.78.3.42 nppiWarpAffineBack_32f_C3R	1203
7.78.3.43 nppiWarpAffineBack_32f_C4R	1203
7.78.3.44 nppiWarpAffineBack_32f_P3R	1204
7.78.3.45 nppiWarpAffineBack_32f_P4R	1204
7.78.3.46 nppiWarpAffineBack_32s_AC4R	1205
7.78.3.47 nppiWarpAffineBack_32s_C1R	1205
7.78.3.48 nppiWarpAffineBack_32s_C3R	1206
7.78.3.49 nppiWarpAffineBack_32s_C4R	1206
7.78.3.50 nppiWarpAffineBack_32s_P3R	1207
7.78.3.51 nppiWarpAffineBack_32s_P4R	1207
7.78.3.52 nppiWarpAffineBack_8u_AC4R	1208
7.78.3.53 nppiWarpAffineBack_8u_C1R	1208
7.78.3.54 nppiWarpAffineBack_8u_C3R	1209
7.78.3.55 nppiWarpAffineBack_8u_C4R	1209
7.78.3.56 nppiWarpAffineBack_8u_P3R	1210
7.78.3.57 nppiWarpAffineBack_8u_P4R	1210
7.78.3.58 nppiWarpAffineQuad_16u_AC4R	1211
7.78.3.59 nppiWarpAffineQuad_16u_C1R	1211
7.78.3.60 nppiWarpAffineQuad_16u_C3R	1212
7.78.3.61 nppiWarpAffineQuad_16u_C4R	1212
7.78.3.62 nppiWarpAffineQuad_16u_P3R	1213
7.78.3.63 nppiWarpAffineQuad_16u_P4R	1213
7.78.3.64 nppiWarpAffineQuad_32f_AC4R	1214
7.78.3.65 nppiWarpAffineQuad_32f_C1R	1214
7.78.3.66 nppiWarpAffineQuad_32f_C3R	1215
7.78.3.67 nppiWarpAffineQuad_32f_C4R	1215
7.78.3.68 nppiWarpAffineQuad_32f_P3R	1216
7.78.3.69 nppiWarpAffineQuad_32f_P4R	1216
7.78.3.70 nppiWarpAffineQuad_32s_AC4R	1217

7.78.3.71	<code>nppiWarpAffineQuad_32s_C1R</code>	1217
7.78.3.72	<code>nppiWarpAffineQuad_32s_C3R</code>	1218
7.78.3.73	<code>nppiWarpAffineQuad_32s_C4R</code>	1218
7.78.3.74	<code>nppiWarpAffineQuad_32s_P3R</code>	1219
7.78.3.75	<code>nppiWarpAffineQuad_32s_P4R</code>	1219
7.78.3.76	<code>nppiWarpAffineQuad_8u_AC4R</code>	1220
7.78.3.77	<code>nppiWarpAffineQuad_8u_C1R</code>	1220
7.78.3.78	<code>nppiWarpAffineQuad_8u_C3R</code>	1221
7.78.3.79	<code>nppiWarpAffineQuad_8u_C4R</code>	1221
7.78.3.80	<code>nppiWarpAffineQuad_8u_P3R</code>	1222
7.78.3.81	<code>nppiWarpAffineQuad_8u_P4R</code>	1222
7.79	Perspective Transform	1223
7.79.1	Detailed Description	1231
7.79.2	Perspective Transform Error Codes	1231
7.79.3	Function Documentation	1231
7.79.3.1	<code>nppiGetPerspectiveBound</code>	1231
7.79.3.2	<code>nppiGetPerspectiveQuad</code>	1232
7.79.3.3	<code>nppiGetPerspectiveTransform</code>	1232
7.79.3.4	<code>nppiWarpPerspective_16u_AC4R</code>	1232
7.79.3.5	<code>nppiWarpPerspective_16u_C1R</code>	1233
7.79.3.6	<code>nppiWarpPerspective_16u_C3R</code>	1233
7.79.3.7	<code>nppiWarpPerspective_16u_C4R</code>	1234
7.79.3.8	<code>nppiWarpPerspective_16u_P3R</code>	1234
7.79.3.9	<code>nppiWarpPerspective_16u_P4R</code>	1235
7.79.3.10	<code>nppiWarpPerspective_32f_AC4R</code>	1235
7.79.3.11	<code>nppiWarpPerspective_32f_C1R</code>	1236
7.79.3.12	<code>nppiWarpPerspective_32f_C3R</code>	1236
7.79.3.13	<code>nppiWarpPerspective_32f_C4R</code>	1237
7.79.3.14	<code>nppiWarpPerspective_32f_P3R</code>	1237
7.79.3.15	<code>nppiWarpPerspective_32f_P4R</code>	1238
7.79.3.16	<code>nppiWarpPerspective_32s_AC4R</code>	1238
7.79.3.17	<code>nppiWarpPerspective_32s_C1R</code>	1239
7.79.3.18	<code>nppiWarpPerspective_32s_C3R</code>	1239
7.79.3.19	<code>nppiWarpPerspective_32s_C4R</code>	1240
7.79.3.20	<code>nppiWarpPerspective_32s_P3R</code>	1240
7.79.3.21	<code>nppiWarpPerspective_32s_P4R</code>	1241

7.79.3.22	nppiWarpPerspective_8u_AC4R	1241
7.79.3.23	nppiWarpPerspective_8u_C1R	1242
7.79.3.24	nppiWarpPerspective_8u_C3R	1242
7.79.3.25	nppiWarpPerspective_8u_C4R	1243
7.79.3.26	nppiWarpPerspective_8u_P3R	1243
7.79.3.27	nppiWarpPerspective_8u_P4R	1244
7.79.3.28	nppiWarpPerspectiveBack_16u_AC4R	1244
7.79.3.29	nppiWarpPerspectiveBack_16u_C1R	1245
7.79.3.30	nppiWarpPerspectiveBack_16u_C3R	1245
7.79.3.31	nppiWarpPerspectiveBack_16u_C4R	1246
7.79.3.32	nppiWarpPerspectiveBack_16u_P3R	1246
7.79.3.33	nppiWarpPerspectiveBack_16u_P4R	1247
7.79.3.34	nppiWarpPerspectiveBack_32f_AC4R	1247
7.79.3.35	nppiWarpPerspectiveBack_32f_C1R	1248
7.79.3.36	nppiWarpPerspectiveBack_32f_C3R	1248
7.79.3.37	nppiWarpPerspectiveBack_32f_C4R	1249
7.79.3.38	nppiWarpPerspectiveBack_32f_P3R	1249
7.79.3.39	nppiWarpPerspectiveBack_32f_P4R	1250
7.79.3.40	nppiWarpPerspectiveBack_32s_AC4R	1250
7.79.3.41	nppiWarpPerspectiveBack_32s_C1R	1251
7.79.3.42	nppiWarpPerspectiveBack_32s_C3R	1251
7.79.3.43	nppiWarpPerspectiveBack_32s_C4R	1252
7.79.3.44	nppiWarpPerspectiveBack_32s_P3R	1252
7.79.3.45	nppiWarpPerspectiveBack_32s_P4R	1253
7.79.3.46	nppiWarpPerspectiveBack_8u_AC4R	1253
7.79.3.47	nppiWarpPerspectiveBack_8u_C1R	1254
7.79.3.48	nppiWarpPerspectiveBack_8u_C3R	1254
7.79.3.49	nppiWarpPerspectiveBack_8u_C4R	1255
7.79.3.50	nppiWarpPerspectiveBack_8u_P3R	1255
7.79.3.51	nppiWarpPerspectiveBack_8u_P4R	1256
7.79.3.52	nppiWarpPerspectiveQuad_16u_AC4R	1256
7.79.3.53	nppiWarpPerspectiveQuad_16u_C1R	1257
7.79.3.54	nppiWarpPerspectiveQuad_16u_C3R	1257
7.79.3.55	nppiWarpPerspectiveQuad_16u_C4R	1258
7.79.3.56	nppiWarpPerspectiveQuad_16u_P3R	1258
7.79.3.57	nppiWarpPerspectiveQuad_16u_P4R	1259

7.79.3.58	nppiWarpPerspectiveQuad_32f_AC4R	1259
7.79.3.59	nppiWarpPerspectiveQuad_32f_C1R	1260
7.79.3.60	nppiWarpPerspectiveQuad_32f_C3R	1260
7.79.3.61	nppiWarpPerspectiveQuad_32f_C4R	1261
7.79.3.62	nppiWarpPerspectiveQuad_32f_P3R	1261
7.79.3.63	nppiWarpPerspectiveQuad_32f_P4R	1262
7.79.3.64	nppiWarpPerspectiveQuad_32s_AC4R	1262
7.79.3.65	nppiWarpPerspectiveQuad_32s_C1R	1263
7.79.3.66	nppiWarpPerspectiveQuad_32s_C3R	1263
7.79.3.67	nppiWarpPerspectiveQuad_32s_C4R	1264
7.79.3.68	nppiWarpPerspectiveQuad_32s_P3R	1264
7.79.3.69	nppiWarpPerspectiveQuad_32s_P4R	1265
7.79.3.70	nppiWarpPerspectiveQuad_8u_AC4R	1265
7.79.3.71	nppiWarpPerspectiveQuad_8u_C1R	1266
7.79.3.72	nppiWarpPerspectiveQuad_8u_C3R	1266
7.79.3.73	nppiWarpPerspectiveQuad_8u_C4R	1267
7.79.3.74	nppiWarpPerspectiveQuad_8u_P3R	1267
7.79.3.75	nppiWarpPerspectiveQuad_8u_P4R	1268
7.80	Linear Transforms	1269
7.80.1	Detailed Description	1269
7.81	Fourier Transforms	1270
7.81.1	Function Documentation	1270
7.81.1.1	nppiMagnitude_32fc32f_C1R	1270
7.81.1.2	nppiMagnitudeSqr_32fc32f_C1R	1270
7.82	Morphological Operations	1272
7.82.1	Detailed Description	1272
7.83	Dilation	1273
7.83.1	Detailed Description	1274
7.83.2	Function Documentation	1274
7.83.2.1	nppiDilate_16u_AC4R	1274
7.83.2.2	nppiDilate_16u_C1R	1274
7.83.2.3	nppiDilate_16u_C3R	1275
7.83.2.4	nppiDilate_16u_C4R	1275
7.83.2.5	nppiDilate_32f_AC4R	1276
7.83.2.6	nppiDilate_32f_C1R	1276
7.83.2.7	nppiDilate_32f_C3R	1276

7.83.2.8	nppiDilate_32f_C4R	1277
7.83.2.9	nppiDilate_8u_AC4R	1277
7.83.2.10	nppiDilate_8u_C1R	1278
7.83.2.11	nppiDilate_8u_C3R	1278
7.83.2.12	nppiDilate_8u_C4R	1279
7.84	Erode	1280
7.84.1	Detailed Description	1281
7.84.2	Function Documentation	1281
7.84.2.1	nppiErode_16u_AC4R	1281
7.84.2.2	nppiErode_16u_C1R	1281
7.84.2.3	nppiErode_16u_C3R	1282
7.84.2.4	nppiErode_16u_C4R	1282
7.84.2.5	nppiErode_32f_AC4R	1283
7.84.2.6	nppiErode_32f_C1R	1283
7.84.2.7	nppiErode_32f_C3R	1283
7.84.2.8	nppiErode_32f_C4R	1284
7.84.2.9	nppiErode_8u_AC4R	1284
7.84.2.10	nppiErode_8u_C1R	1285
7.84.2.11	nppiErode_8u_C3R	1285
7.84.2.12	nppiErode_8u_C4R	1286
7.85	Dilate3x3	1287
7.85.1	Detailed Description	1288
7.85.2	Function Documentation	1288
7.85.2.1	nppiDilate3x3_16u_AC4R	1288
7.85.2.2	nppiDilate3x3_16u_C1R	1288
7.85.2.3	nppiDilate3x3_16u_C3R	1289
7.85.2.4	nppiDilate3x3_16u_C4R	1289
7.85.2.5	nppiDilate3x3_32f_AC4R	1289
7.85.2.6	nppiDilate3x3_32f_C1R	1290
7.85.2.7	nppiDilate3x3_32f_C3R	1290
7.85.2.8	nppiDilate3x3_32f_C4R	1290
7.85.2.9	nppiDilate3x3_64f_C1R	1291
7.85.2.10	nppiDilate3x3_8u_AC4R	1291
7.85.2.11	nppiDilate3x3_8u_C1R	1291
7.85.2.12	nppiDilate3x3_8u_C3R	1292
7.85.2.13	nppiDilate3x3_8u_C4R	1292

7.86 Erode3x3	1293
7.86.1 Detailed Description	1294
7.86.2 Function Documentation	1294
7.86.2.1 nppiErode3x3_16u_AC4R	1294
7.86.2.2 nppiErode3x3_16u_C1R	1294
7.86.2.3 nppiErode3x3_16u_C3R	1295
7.86.2.4 nppiErode3x3_16u_C4R	1295
7.86.2.5 nppiErode3x3_32f_AC4R	1295
7.86.2.6 nppiErode3x3_32f_C1R	1296
7.86.2.7 nppiErode3x3_32f_C3R	1296
7.86.2.8 nppiErode3x3_32f_C4R	1296
7.86.2.9 nppiErode3x3_64f_C1R	1297
7.86.2.10 nppiErode3x3_8u_AC4R	1297
7.86.2.11 nppiErode3x3_8u_C1R	1297
7.86.2.12 nppiErode3x3_8u_C3R	1298
7.86.2.13 nppiErode3x3_8u_C4R	1298
7.87 Statistical Operations	1299
7.87.1 Detailed Description	1300
7.88 Sum	1301
7.88.1 Detailed Description	1303
7.88.2 Function Documentation	1304
7.88.2.1 nppiSum_16s_AC4R	1304
7.88.2.2 nppiSum_16s_C1R	1304
7.88.2.3 nppiSum_16s_C3R	1304
7.88.2.4 nppiSum_16s_C4R	1305
7.88.2.5 nppiSum_16u_AC4R	1305
7.88.2.6 nppiSum_16u_C1R	1305
7.88.2.7 nppiSum_16u_C3R	1306
7.88.2.8 nppiSum_16u_C4R	1306
7.88.2.9 nppiSum_32f_AC4R	1307
7.88.2.10 nppiSum_32f_C1R	1307
7.88.2.11 nppiSum_32f_C3R	1307
7.88.2.12 nppiSum_32f_C4R	1308
7.88.2.13 nppiSum_8u64s_C1R	1308
7.88.2.14 nppiSum_8u64s_C4R	1308
7.88.2.15 nppiSum_8u_AC4R	1309

7.88.2.16	nppiSum_8u_C1R	1309
7.88.2.17	nppiSum_8u_C3R	1310
7.88.2.18	nppiSum_8u_C4R	1310
7.88.2.19	nppiSumGetBufferHostSize_16s_AC4R	1310
7.88.2.20	nppiSumGetBufferHostSize_16s_C1R	1311
7.88.2.21	nppiSumGetBufferHostSize_16s_C3R	1311
7.88.2.22	nppiSumGetBufferHostSize_16s_C4R	1311
7.88.2.23	nppiSumGetBufferHostSize_16u_AC4R	1311
7.88.2.24	nppiSumGetBufferHostSize_16u_C1R	1312
7.88.2.25	nppiSumGetBufferHostSize_16u_C3R	1312
7.88.2.26	nppiSumGetBufferHostSize_16u_C4R	1312
7.88.2.27	nppiSumGetBufferHostSize_32f_AC4R	1313
7.88.2.28	nppiSumGetBufferHostSize_32f_C1R	1313
7.88.2.29	nppiSumGetBufferHostSize_32f_C3R	1313
7.88.2.30	nppiSumGetBufferHostSize_32f_C4R	1313
7.88.2.31	nppiSumGetBufferHostSize_8u64s_C1R	1314
7.88.2.32	nppiSumGetBufferHostSize_8u64s_C4R	1314
7.88.2.33	nppiSumGetBufferHostSize_8u_AC4R	1314
7.88.2.34	nppiSumGetBufferHostSize_8u_C1R	1315
7.88.2.35	nppiSumGetBufferHostSize_8u_C3R	1315
7.88.2.36	nppiSumGetBufferHostSize_8u_C4R	1315
7.89	Min	1316
7.89.1	Detailed Description	1318
7.89.2	Function Documentation	1318
7.89.2.1	nppiMin_16s_AC4R	1318
7.89.2.2	nppiMin_16s_C1R	1319
7.89.2.3	nppiMin_16s_C3R	1319
7.89.2.4	nppiMin_16s_C4R	1319
7.89.2.5	nppiMin_16u_AC4R	1320
7.89.2.6	nppiMin_16u_C1R	1320
7.89.2.7	nppiMin_16u_C3R	1320
7.89.2.8	nppiMin_16u_C4R	1321
7.89.2.9	nppiMin_32f_AC4R	1321
7.89.2.10	nppiMin_32f_C1R	1321
7.89.2.11	nppiMin_32f_C3R	1322
7.89.2.12	nppiMin_32f_C4R	1322

7.89.2.13	nppiMin_8u_AC4R	1323
7.89.2.14	nppiMin_8u_C1R	1323
7.89.2.15	nppiMin_8u_C3R	1323
7.89.2.16	nppiMin_8u_C4R	1324
7.89.2.17	nppiMinGetBufferHostSize_16s_AC4R	1324
7.89.2.18	nppiMinGetBufferHostSize_16s_C1R	1324
7.89.2.19	nppiMinGetBufferHostSize_16s_C3R	1325
7.89.2.20	nppiMinGetBufferHostSize_16s_C4R	1325
7.89.2.21	nppiMinGetBufferHostSize_16u_AC4R	1325
7.89.2.22	nppiMinGetBufferHostSize_16u_C1R	1325
7.89.2.23	nppiMinGetBufferHostSize_16u_C3R	1326
7.89.2.24	nppiMinGetBufferHostSize_16u_C4R	1326
7.89.2.25	nppiMinGetBufferHostSize_32f_AC4R	1326
7.89.2.26	nppiMinGetBufferHostSize_32f_C1R	1327
7.89.2.27	nppiMinGetBufferHostSize_32f_C3R	1327
7.89.2.28	nppiMinGetBufferHostSize_32f_C4R	1327
7.89.2.29	nppiMinGetBufferHostSize_8u_AC4R	1327
7.89.2.30	nppiMinGetBufferHostSize_8u_C1R	1328
7.89.2.31	nppiMinGetBufferHostSize_8u_C3R	1328
7.89.2.32	nppiMinGetBufferHostSize_8u_C4R	1328
7.90	MinIndx	1329
7.90.1	Detailed Description	1331
7.90.2	Function Documentation	1331
7.90.2.1	nppiMinIndx_16s_AC4R	1331
7.90.2.2	nppiMinIndx_16s_C1R	1332
7.90.2.3	nppiMinIndx_16s_C3R	1332
7.90.2.4	nppiMinIndx_16s_C4R	1333
7.90.2.5	nppiMinIndx_16u_AC4R	1333
7.90.2.6	nppiMinIndx_16u_C1R	1333
7.90.2.7	nppiMinIndx_16u_C3R	1334
7.90.2.8	nppiMinIndx_16u_C4R	1334
7.90.2.9	nppiMinIndx_32f_AC4R	1335
7.90.2.10	nppiMinIndx_32f_C1R	1335
7.90.2.11	nppiMinIndx_32f_C3R	1335
7.90.2.12	nppiMinIndx_32f_C4R	1336
7.90.2.13	nppiMinIndx_8u_AC4R	1336

7.90.2.14	nppiMinIndx_8u_C1R	1337
7.90.2.15	nppiMinIndx_8u_C3R	1337
7.90.2.16	nppiMinIndx_8u_C4R	1337
7.90.2.17	nppiMinIndxGetBufferHostSize_16s_AC4R	1338
7.90.2.18	nppiMinIndxGetBufferHostSize_16s_C1R	1338
7.90.2.19	nppiMinIndxGetBufferHostSize_16s_C3R	1338
7.90.2.20	nppiMinIndxGetBufferHostSize_16s_C4R	1339
7.90.2.21	nppiMinIndxGetBufferHostSize_16u_AC4R	1339
7.90.2.22	nppiMinIndxGetBufferHostSize_16u_C1R	1339
7.90.2.23	nppiMinIndxGetBufferHostSize_16u_C3R	1340
7.90.2.24	nppiMinIndxGetBufferHostSize_16u_C4R	1340
7.90.2.25	nppiMinIndxGetBufferHostSize_32f_AC4R	1340
7.90.2.26	nppiMinIndxGetBufferHostSize_32f_C1R	1340
7.90.2.27	nppiMinIndxGetBufferHostSize_32f_C3R	1341
7.90.2.28	nppiMinIndxGetBufferHostSize_32f_C4R	1341
7.90.2.29	nppiMinIndxGetBufferHostSize_8u_AC4R	1341
7.90.2.30	nppiMinIndxGetBufferHostSize_8u_C1R	1342
7.90.2.31	nppiMinIndxGetBufferHostSize_8u_C3R	1342
7.90.2.32	nppiMinIndxGetBufferHostSize_8u_C4R	1342
7.91	Max	1343
7.91.1	Detailed Description	1345
7.91.2	Function Documentation	1345
7.91.2.1	nppiMax_16s_AC4R	1345
7.91.2.2	nppiMax_16s_C1R	1346
7.91.2.3	nppiMax_16s_C3R	1346
7.91.2.4	nppiMax_16s_C4R	1346
7.91.2.5	nppiMax_16u_AC4R	1347
7.91.2.6	nppiMax_16u_C1R	1347
7.91.2.7	nppiMax_16u_C3R	1347
7.91.2.8	nppiMax_16u_C4R	1348
7.91.2.9	nppiMax_32f_AC4R	1348
7.91.2.10	nppiMax_32f_C1R	1348
7.91.2.11	nppiMax_32f_C3R	1349
7.91.2.12	nppiMax_32f_C4R	1349
7.91.2.13	nppiMax_8u_AC4R	1350
7.91.2.14	nppiMax_8u_C1R	1350

7.91.2.15	nppiMax_8u_C3R	1350
7.91.2.16	nppiMax_8u_C4R	1351
7.91.2.17	nppiMaxGetBufferHostSize_16s_AC4R	1351
7.91.2.18	nppiMaxGetBufferHostSize_16s_C1R	1351
7.91.2.19	nppiMaxGetBufferHostSize_16s_C3R	1352
7.91.2.20	nppiMaxGetBufferHostSize_16s_C4R	1352
7.91.2.21	nppiMaxGetBufferHostSize_16u_AC4R	1352
7.91.2.22	nppiMaxGetBufferHostSize_16u_C1R	1352
7.91.2.23	nppiMaxGetBufferHostSize_16u_C3R	1353
7.91.2.24	nppiMaxGetBufferHostSize_16u_C4R	1353
7.91.2.25	nppiMaxGetBufferHostSize_32f_AC4R	1353
7.91.2.26	nppiMaxGetBufferHostSize_32f_C1R	1354
7.91.2.27	nppiMaxGetBufferHostSize_32f_C3R	1354
7.91.2.28	nppiMaxGetBufferHostSize_32f_C4R	1354
7.91.2.29	nppiMaxGetBufferHostSize_8u_AC4R	1354
7.91.2.30	nppiMaxGetBufferHostSize_8u_C1R	1355
7.91.2.31	nppiMaxGetBufferHostSize_8u_C3R	1355
7.91.2.32	nppiMaxGetBufferHostSize_8u_C4R	1355
7.92	MaxIndx	1356
7.92.1	Detailed Description	1358
7.92.2	Function Documentation	1358
7.92.2.1	nppiMaxIndx_16s_AC4R	1358
7.92.2.2	nppiMaxIndx_16s_C1R	1359
7.92.2.3	nppiMaxIndx_16s_C3R	1359
7.92.2.4	nppiMaxIndx_16s_C4R	1360
7.92.2.5	nppiMaxIndx_16u_AC4R	1360
7.92.2.6	nppiMaxIndx_16u_C1R	1360
7.92.2.7	nppiMaxIndx_16u_C3R	1361
7.92.2.8	nppiMaxIndx_16u_C4R	1361
7.92.2.9	nppiMaxIndx_32f_AC4R	1362
7.92.2.10	nppiMaxIndx_32f_C1R	1362
7.92.2.11	nppiMaxIndx_32f_C3R	1362
7.92.2.12	nppiMaxIndx_32f_C4R	1363
7.92.2.13	nppiMaxIndx_8u_AC4R	1363
7.92.2.14	nppiMaxIndx_8u_C1R	1364
7.92.2.15	nppiMaxIndx_8u_C3R	1364

7.92.2.16	nppiMaxIndx_8u_C4R	1364
7.92.2.17	nppiMaxIndxGetBufferHostSize_16s_AC4R	1365
7.92.2.18	nppiMaxIndxGetBufferHostSize_16s_C1R	1365
7.92.2.19	nppiMaxIndxGetBufferHostSize_16s_C3R	1365
7.92.2.20	nppiMaxIndxGetBufferHostSize_16s_C4R	1366
7.92.2.21	nppiMaxIndxGetBufferHostSize_16u_AC4R	1366
7.92.2.22	nppiMaxIndxGetBufferHostSize_16u_C1R	1366
7.92.2.23	nppiMaxIndxGetBufferHostSize_16u_C3R	1367
7.92.2.24	nppiMaxIndxGetBufferHostSize_16u_C4R	1367
7.92.2.25	nppiMaxIndxGetBufferHostSize_32f_AC4R	1367
7.92.2.26	nppiMaxIndxGetBufferHostSize_32f_C1R	1367
7.92.2.27	nppiMaxIndxGetBufferHostSize_32f_C3R	1368
7.92.2.28	nppiMaxIndxGetBufferHostSize_32f_C4R	1368
7.92.2.29	nppiMaxIndxGetBufferHostSize_8u_AC4R	1368
7.92.2.30	nppiMaxIndxGetBufferHostSize_8u_C1R	1369
7.92.2.31	nppiMaxIndxGetBufferHostSize_8u_C3R	1369
7.92.2.32	nppiMaxIndxGetBufferHostSize_8u_C4R	1369
7.93	MinMax	1370
7.93.1	Detailed Description	1372
7.93.2	Function Documentation	1372
7.93.2.1	nppiMinMax_16s_AC4R	1372
7.93.2.2	nppiMinMax_16s_C1R	1373
7.93.2.3	nppiMinMax_16s_C3R	1373
7.93.2.4	nppiMinMax_16s_C4R	1373
7.93.2.5	nppiMinMax_16u_AC4R	1374
7.93.2.6	nppiMinMax_16u_C1R	1374
7.93.2.7	nppiMinMax_16u_C3R	1375
7.93.2.8	nppiMinMax_16u_C4R	1375
7.93.2.9	nppiMinMax_32f_AC4R	1375
7.93.2.10	nppiMinMax_32f_C1R	1376
7.93.2.11	nppiMinMax_32f_C3R	1376
7.93.2.12	nppiMinMax_32f_C4R	1377
7.93.2.13	nppiMinMax_8u_AC4R	1377
7.93.2.14	nppiMinMax_8u_C1R	1377
7.93.2.15	nppiMinMax_8u_C3R	1378
7.93.2.16	nppiMinMax_8u_C4R	1378

7.93.2.17	nppiMinMaxGetBufferHostSize_16s_AC4R	1379
7.93.2.18	nppiMinMaxGetBufferHostSize_16s_C1R	1379
7.93.2.19	nppiMinMaxGetBufferHostSize_16s_C3R	1379
7.93.2.20	nppiMinMaxGetBufferHostSize_16s_C4R	1379
7.93.2.21	nppiMinMaxGetBufferHostSize_16u_AC4R	1380
7.93.2.22	nppiMinMaxGetBufferHostSize_16u_C1R	1380
7.93.2.23	nppiMinMaxGetBufferHostSize_16u_C3R	1380
7.93.2.24	nppiMinMaxGetBufferHostSize_16u_C4R	1381
7.93.2.25	nppiMinMaxGetBufferHostSize_32f_AC4R	1381
7.93.2.26	nppiMinMaxGetBufferHostSize_32f_C1R	1381
7.93.2.27	nppiMinMaxGetBufferHostSize_32f_C3R	1381
7.93.2.28	nppiMinMaxGetBufferHostSize_32f_C4R	1382
7.93.2.29	nppiMinMaxGetBufferHostSize_8u_AC4R	1382
7.93.2.30	nppiMinMaxGetBufferHostSize_8u_C1R	1382
7.93.2.31	nppiMinMaxGetBufferHostSize_8u_C3R	1383
7.93.2.32	nppiMinMaxGetBufferHostSize_8u_C4R	1383
7.94	MinMaxIndx	1384
7.94.1	Detailed Description	1387
7.94.2	Function Documentation	1387
7.94.2.1	nppiMinMaxIndx_16u_C1MR	1387
7.94.2.2	nppiMinMaxIndx_16u_C1R	1388
7.94.2.3	nppiMinMaxIndx_16u_C3CMR	1388
7.94.2.4	nppiMinMaxIndx_16u_C3CR	1389
7.94.2.5	nppiMinMaxIndx_32f_C1MR	1390
7.94.2.6	nppiMinMaxIndx_32f_C1R	1390
7.94.2.7	nppiMinMaxIndx_32f_C3CMR	1391
7.94.2.8	nppiMinMaxIndx_32f_C3CR	1391
7.94.2.9	nppiMinMaxIndx_8s_C1MR	1392
7.94.2.10	nppiMinMaxIndx_8s_C1R	1392
7.94.2.11	nppiMinMaxIndx_8s_C3CMR	1393
7.94.2.12	nppiMinMaxIndx_8s_C3CR	1393
7.94.2.13	nppiMinMaxIndx_8u_C1MR	1394
7.94.2.14	nppiMinMaxIndx_8u_C1R	1395
7.94.2.15	nppiMinMaxIndx_8u_C3CMR	1395
7.94.2.16	nppiMinMaxIndx_8u_C3CR	1396
7.94.2.17	nppiMinMaxIndxGetBufferHostSize_16u_C1MR	1396

7.94.2.18	nppiMinMaxIdxGetBufferHostSize_16u_C1R	1396
7.94.2.19	nppiMinMaxIdxGetBufferHostSize_16u_C3CMR	1397
7.94.2.20	nppiMinMaxIdxGetBufferHostSize_16u_C3CR	1397
7.94.2.21	nppiMinMaxIdxGetBufferHostSize_32f_C1MR	1397
7.94.2.22	nppiMinMaxIdxGetBufferHostSize_32f_C1R	1397
7.94.2.23	nppiMinMaxIdxGetBufferHostSize_32f_C3CMR	1398
7.94.2.24	nppiMinMaxIdxGetBufferHostSize_32f_C3CR	1398
7.94.2.25	nppiMinMaxIdxGetBufferHostSize_8s_C1MR	1398
7.94.2.26	nppiMinMaxIdxGetBufferHostSize_8s_C1R	1399
7.94.2.27	nppiMinMaxIdxGetBufferHostSize_8s_C3CMR	1399
7.94.2.28	nppiMinMaxIdxGetBufferHostSize_8s_C3CR	1399
7.94.2.29	nppiMinMaxIdxGetBufferHostSize_8u_C1MR	1399
7.94.2.30	nppiMinMaxIdxGetBufferHostSize_8u_C1R	1400
7.94.2.31	nppiMinMaxIdxGetBufferHostSize_8u_C3CMR	1400
7.94.2.32	nppiMinMaxIdxGetBufferHostSize_8u_C3CR	1400
7.95	Mean	1401
7.95.1	Detailed Description	1404
7.95.2	Function Documentation	1405
7.95.2.1	nppiMean_16s_AC4R	1405
7.95.2.2	nppiMean_16s_C1R	1405
7.95.2.3	nppiMean_16s_C3R	1405
7.95.2.4	nppiMean_16s_C4R	1406
7.95.2.5	nppiMean_16u_AC4R	1406
7.95.2.6	nppiMean_16u_C1MR	1406
7.95.2.7	nppiMean_16u_C1R	1407
7.95.2.8	nppiMean_16u_C3CMR	1407
7.95.2.9	nppiMean_16u_C3R	1408
7.95.2.10	nppiMean_16u_C4R	1408
7.95.2.11	nppiMean_32f_AC4R	1408
7.95.2.12	nppiMean_32f_C1MR	1409
7.95.2.13	nppiMean_32f_C1R	1409
7.95.2.14	nppiMean_32f_C3CMR	1410
7.95.2.15	nppiMean_32f_C3R	1410
7.95.2.16	nppiMean_32f_C4R	1410
7.95.2.17	nppiMean_8s_C1MR	1411
7.95.2.18	nppiMean_8s_C3CMR	1411

7.95.2.19	nppiMean_8u_AC4R	1412
7.95.2.20	nppiMean_8u_C1MR	1412
7.95.2.21	nppiMean_8u_C1R	1413
7.95.2.22	nppiMean_8u_C3CMR	1413
7.95.2.23	nppiMean_8u_C3R	1413
7.95.2.24	nppiMean_8u_C4R	1414
7.95.2.25	nppiMeanGetBufferHostSize_16s_AC4R	1414
7.95.2.26	nppiMeanGetBufferHostSize_16s_C1R	1414
7.95.2.27	nppiMeanGetBufferHostSize_16s_C3R	1415
7.95.2.28	nppiMeanGetBufferHostSize_16s_C4R	1415
7.95.2.29	nppiMeanGetBufferHostSize_16u_AC4R	1415
7.95.2.30	nppiMeanGetBufferHostSize_16u_C1MR	1416
7.95.2.31	nppiMeanGetBufferHostSize_16u_C1R	1416
7.95.2.32	nppiMeanGetBufferHostSize_16u_C3CMR	1416
7.95.2.33	nppiMeanGetBufferHostSize_16u_C3R	1416
7.95.2.34	nppiMeanGetBufferHostSize_16u_C4R	1417
7.95.2.35	nppiMeanGetBufferHostSize_32f_AC4R	1417
7.95.2.36	nppiMeanGetBufferHostSize_32f_C1MR	1417
7.95.2.37	nppiMeanGetBufferHostSize_32f_C1R	1418
7.95.2.38	nppiMeanGetBufferHostSize_32f_C3CMR	1418
7.95.2.39	nppiMeanGetBufferHostSize_32f_C3R	1418
7.95.2.40	nppiMeanGetBufferHostSize_32f_C4R	1418
7.95.2.41	nppiMeanGetBufferHostSize_8s_C1MR	1419
7.95.2.42	nppiMeanGetBufferHostSize_8s_C3CMR	1419
7.95.2.43	nppiMeanGetBufferHostSize_8u_AC4R	1419
7.95.2.44	nppiMeanGetBufferHostSize_8u_C1MR	1420
7.95.2.45	nppiMeanGetBufferHostSize_8u_C1R	1420
7.95.2.46	nppiMeanGetBufferHostSize_8u_C3CMR	1420
7.95.2.47	nppiMeanGetBufferHostSize_8u_C3R	1420
7.95.2.48	nppiMeanGetBufferHostSize_8u_C4R	1421
7.96	Mean_StdDev	1422
7.96.1	Detailed Description	1425
7.96.2	Function Documentation	1425
7.96.2.1	nppiMean_StdDev_16u_C1MR	1425
7.96.2.2	nppiMean_StdDev_16u_C1R	1426
7.96.2.3	nppiMean_StdDev_16u_C3CMR	1426

7.96.2.4	nppiMean_StdDev_16u_C3CR	1427
7.96.2.5	nppiMean_StdDev_32f_C1MR	1427
7.96.2.6	nppiMean_StdDev_32f_C1R	1428
7.96.2.7	nppiMean_StdDev_32f_C3CMR	1428
7.96.2.8	nppiMean_StdDev_32f_C3CR	1429
7.96.2.9	nppiMean_StdDev_8s_C1MR	1429
7.96.2.10	nppiMean_StdDev_8s_C1R	1430
7.96.2.11	nppiMean_StdDev_8s_C3CMR	1430
7.96.2.12	nppiMean_StdDev_8s_C3CR	1431
7.96.2.13	nppiMean_StdDev_8u_C1MR	1431
7.96.2.14	nppiMean_StdDev_8u_C1R	1432
7.96.2.15	nppiMean_StdDev_8u_C3CMR	1432
7.96.2.16	nppiMean_StdDev_8u_C3CR	1433
7.96.2.17	nppiMeanStdDevGetBufferHostSize_16u_C1MR	1433
7.96.2.18	nppiMeanStdDevGetBufferHostSize_16u_C1R	1433
7.96.2.19	nppiMeanStdDevGetBufferHostSize_16u_C3CMR	1434
7.96.2.20	nppiMeanStdDevGetBufferHostSize_16u_C3CR	1434
7.96.2.21	nppiMeanStdDevGetBufferHostSize_32f_C1MR	1434
7.96.2.22	nppiMeanStdDevGetBufferHostSize_32f_C1R	1434
7.96.2.23	nppiMeanStdDevGetBufferHostSize_32f_C3CMR	1435
7.96.2.24	nppiMeanStdDevGetBufferHostSize_32f_C3CR	1435
7.96.2.25	nppiMeanStdDevGetBufferHostSize_8s_C1MR	1435
7.96.2.26	nppiMeanStdDevGetBufferHostSize_8s_C1R	1436
7.96.2.27	nppiMeanStdDevGetBufferHostSize_8s_C3CMR	1436
7.96.2.28	nppiMeanStdDevGetBufferHostSize_8s_C3CR	1436
7.96.2.29	nppiMeanStdDevGetBufferHostSize_8u_C1MR	1436
7.96.2.30	nppiMeanStdDevGetBufferHostSize_8u_C1R	1437
7.96.2.31	nppiMeanStdDevGetBufferHostSize_8u_C3CMR	1437
7.96.2.32	nppiMeanStdDevGetBufferHostSize_8u_C3CR	1437
7.97	Image Norms	1438
7.97.1	Detailed Description	1438
7.98	Norm_Inf	1440
7.98.1	Detailed Description	1444
7.98.2	Function Documentation	1444
7.98.2.1	nppiNorm_Inf_16s_AC4R	1444
7.98.2.2	nppiNorm_Inf_16s_C1R	1444

7.98.2.3	nppiNorm_Inf_16s_C3R	1444
7.98.2.4	nppiNorm_Inf_16s_C4R	1445
7.98.2.5	nppiNorm_Inf_16u_AC4R	1445
7.98.2.6	nppiNorm_Inf_16u_C1MR	1446
7.98.2.7	nppiNorm_Inf_16u_C1R	1446
7.98.2.8	nppiNorm_Inf_16u_C3CMR	1446
7.98.2.9	nppiNorm_Inf_16u_C3R	1447
7.98.2.10	nppiNorm_Inf_16u_C4R	1447
7.98.2.11	nppiNorm_Inf_32f_AC4R	1448
7.98.2.12	nppiNorm_Inf_32f_C1MR	1448
7.98.2.13	nppiNorm_Inf_32f_C1R	1448
7.98.2.14	nppiNorm_Inf_32f_C3CMR	1449
7.98.2.15	nppiNorm_Inf_32f_C3R	1449
7.98.2.16	nppiNorm_Inf_32f_C4R	1450
7.98.2.17	nppiNorm_Inf_32s_C1R	1450
7.98.2.18	nppiNorm_Inf_8s_C1MR	1450
7.98.2.19	nppiNorm_Inf_8s_C3CMR	1451
7.98.2.20	nppiNorm_Inf_8u_AC4R	1451
7.98.2.21	nppiNorm_Inf_8u_C1MR	1452
7.98.2.22	nppiNorm_Inf_8u_C1R	1452
7.98.2.23	nppiNorm_Inf_8u_C3CMR	1452
7.98.2.24	nppiNorm_Inf_8u_C3R	1453
7.98.2.25	nppiNorm_Inf_8u_C4R	1453
7.98.2.26	nppiNormInfGetBufferHostSize_16s_AC4R	1454
7.98.2.27	nppiNormInfGetBufferHostSize_16s_C1R	1454
7.98.2.28	nppiNormInfGetBufferHostSize_16s_C3R	1454
7.98.2.29	nppiNormInfGetBufferHostSize_16s_C4R	1454
7.98.2.30	nppiNormInfGetBufferHostSize_16u_AC4R	1455
7.98.2.31	nppiNormInfGetBufferHostSize_16u_C1MR	1455
7.98.2.32	nppiNormInfGetBufferHostSize_16u_C1R	1455
7.98.2.33	nppiNormInfGetBufferHostSize_16u_C3CMR	1456
7.98.2.34	nppiNormInfGetBufferHostSize_16u_C3R	1456
7.98.2.35	nppiNormInfGetBufferHostSize_16u_C4R	1456
7.98.2.36	nppiNormInfGetBufferHostSize_32f_AC4R	1456
7.98.2.37	nppiNormInfGetBufferHostSize_32f_C1MR	1457
7.98.2.38	nppiNormInfGetBufferHostSize_32f_C1R	1457

7.98.2.39	nppiNormInfGetBufferHostSize_32f_C3CMR	1457
7.98.2.40	nppiNormInfGetBufferHostSize_32f_C3R	1458
7.98.2.41	nppiNormInfGetBufferHostSize_32f_C4R	1458
7.98.2.42	nppiNormInfGetBufferHostSize_32s_C1R	1458
7.98.2.43	nppiNormInfGetBufferHostSize_8s_C1MR	1458
7.98.2.44	nppiNormInfGetBufferHostSize_8s_C3CMR	1459
7.98.2.45	nppiNormInfGetBufferHostSize_8u_AC4R	1459
7.98.2.46	nppiNormInfGetBufferHostSize_8u_C1MR	1459
7.98.2.47	nppiNormInfGetBufferHostSize_8u_C1R	1460
7.98.2.48	nppiNormInfGetBufferHostSize_8u_C3CMR	1460
7.98.2.49	nppiNormInfGetBufferHostSize_8u_C3R	1460
7.98.2.50	nppiNormInfGetBufferHostSize_8u_C4R	1460
7.99	Norm_L1	1462
7.99.1	Detailed Description	1465
7.99.2	Function Documentation	1466
7.99.2.1	nppiNorm_L1_16s_AC4R	1466
7.99.2.2	nppiNorm_L1_16s_C1R	1466
7.99.2.3	nppiNorm_L1_16s_C3R	1466
7.99.2.4	nppiNorm_L1_16s_C4R	1467
7.99.2.5	nppiNorm_L1_16u_AC4R	1467
7.99.2.6	nppiNorm_L1_16u_C1MR	1467
7.99.2.7	nppiNorm_L1_16u_C1R	1468
7.99.2.8	nppiNorm_L1_16u_C3CMR	1468
7.99.2.9	nppiNorm_L1_16u_C3R	1469
7.99.2.10	nppiNorm_L1_16u_C4R	1469
7.99.2.11	nppiNorm_L1_32f_AC4R	1469
7.99.2.12	nppiNorm_L1_32f_C1MR	1470
7.99.2.13	nppiNorm_L1_32f_C1R	1470
7.99.2.14	nppiNorm_L1_32f_C3CMR	1471
7.99.2.15	nppiNorm_L1_32f_C3R	1471
7.99.2.16	nppiNorm_L1_32f_C4R	1471
7.99.2.17	nppiNorm_L1_8s_C1MR	1472
7.99.2.18	nppiNorm_L1_8s_C3CMR	1472
7.99.2.19	nppiNorm_L1_8u_AC4R	1473
7.99.2.20	nppiNorm_L1_8u_C1MR	1473
7.99.2.21	nppiNorm_L1_8u_C1R	1473

7.99.2.22	nppiNorm_L1_8u_C3CMR	1474
7.99.2.23	nppiNorm_L1_8u_C3R	1474
7.99.2.24	nppiNorm_L1_8u_C4R	1475
7.99.2.25	nppiNormL1GetBufferHostSize_16s_AC4R	1475
7.99.2.26	nppiNormL1GetBufferHostSize_16s_C1R	1475
7.99.2.27	nppiNormL1GetBufferHostSize_16s_C3R	1476
7.99.2.28	nppiNormL1GetBufferHostSize_16s_C4R	1476
7.99.2.29	nppiNormL1GetBufferHostSize_16u_AC4R	1476
7.99.2.30	nppiNormL1GetBufferHostSize_16u_C1MR	1476
7.99.2.31	nppiNormL1GetBufferHostSize_16u_C1R	1477
7.99.2.32	nppiNormL1GetBufferHostSize_16u_C3CMR	1477
7.99.2.33	nppiNormL1GetBufferHostSize_16u_C3R	1477
7.99.2.34	nppiNormL1GetBufferHostSize_16u_C4R	1478
7.99.2.35	nppiNormL1GetBufferHostSize_32f_AC4R	1478
7.99.2.36	nppiNormL1GetBufferHostSize_32f_C1MR	1478
7.99.2.37	nppiNormL1GetBufferHostSize_32f_C1R	1478
7.99.2.38	nppiNormL1GetBufferHostSize_32f_C3CMR	1479
7.99.2.39	nppiNormL1GetBufferHostSize_32f_C3R	1479
7.99.2.40	nppiNormL1GetBufferHostSize_32f_C4R	1479
7.99.2.41	nppiNormL1GetBufferHostSize_8s_C1MR	1480
7.99.2.42	nppiNormL1GetBufferHostSize_8s_C3CMR	1480
7.99.2.43	nppiNormL1GetBufferHostSize_8u_AC4R	1480
7.99.2.44	nppiNormL1GetBufferHostSize_8u_C1MR	1480
7.99.2.45	nppiNormL1GetBufferHostSize_8u_C1R	1481
7.99.2.46	nppiNormL1GetBufferHostSize_8u_C3CMR	1481
7.99.2.47	nppiNormL1GetBufferHostSize_8u_C3R	1481
7.99.2.48	nppiNormL1GetBufferHostSize_8u_C4R	1482
7.100	Norm_L2	1483
7.100.1	Detailed Description	1486
7.100.2	Function Documentation	1487
7.100.2.1	nppiNorm_L2_16s_AC4R	1487
7.100.2.2	nppiNorm_L2_16s_C1R	1487
7.100.2.3	nppiNorm_L2_16s_C3R	1487
7.100.2.4	nppiNorm_L2_16s_C4R	1488
7.100.2.5	nppiNorm_L2_16u_AC4R	1488
7.100.2.6	nppiNorm_L2_16u_C1MR	1488

7.100.2.7	nppiNorm_L2_16u_C1R	1489
7.100.2.8	nppiNorm_L2_16u_C3CMR	1489
7.100.2.9	nppiNorm_L2_16u_C3R	1490
7.100.2.10	nppiNorm_L2_16u_C4R	1490
7.100.2.11	nppiNorm_L2_32f_AC4R	1490
7.100.2.12	nppiNorm_L2_32f_C1MR	1491
7.100.2.13	nppiNorm_L2_32f_C1R	1491
7.100.2.14	nppiNorm_L2_32f_C3CMR	1492
7.100.2.15	nppiNorm_L2_32f_C3R	1492
7.100.2.16	nppiNorm_L2_32f_C4R	1492
7.100.2.17	nppiNorm_L2_8s_C1MR	1493
7.100.2.18	nppiNorm_L2_8s_C3CMR	1493
7.100.2.19	nppiNorm_L2_8u_AC4R	1494
7.100.2.20	nppiNorm_L2_8u_C1MR	1494
7.100.2.21	nppiNorm_L2_8u_C1R	1494
7.100.2.22	nppiNorm_L2_8u_C3CMR	1495
7.100.2.23	nppiNorm_L2_8u_C3R	1495
7.100.2.24	nppiNorm_L2_8u_C4R	1496
7.100.2.25	nppiNormL2GetBufferHostSize_16s_AC4R	1496
7.100.2.26	nppiNormL2GetBufferHostSize_16s_C1R	1496
7.100.2.27	nppiNormL2GetBufferHostSize_16s_C3R	1497
7.100.2.28	nppiNormL2GetBufferHostSize_16s_C4R	1497
7.100.2.29	nppiNormL2GetBufferHostSize_16u_AC4R	1497
7.100.2.30	nppiNormL2GetBufferHostSize_16u_C1MR	1497
7.100.2.31	nppiNormL2GetBufferHostSize_16u_C1R	1498
7.100.2.32	nppiNormL2GetBufferHostSize_16u_C3CMR	1498
7.100.2.33	nppiNormL2GetBufferHostSize_16u_C3R	1498
7.100.2.34	nppiNormL2GetBufferHostSize_16u_C4R	1499
7.100.2.35	nppiNormL2GetBufferHostSize_32f_AC4R	1499
7.100.2.36	nppiNormL2GetBufferHostSize_32f_C1MR	1499
7.100.2.37	nppiNormL2GetBufferHostSize_32f_C1R	1499
7.100.2.38	nppiNormL2GetBufferHostSize_32f_C3CMR	1500
7.100.2.39	nppiNormL2GetBufferHostSize_32f_C3R	1500
7.100.2.40	nppiNormL2GetBufferHostSize_32f_C4R	1500
7.100.2.41	nppiNormL2GetBufferHostSize_8s_C1MR	1501
7.100.2.42	nppiNormL2GetBufferHostSize_8s_C3CMR	1501

7.100.2.43	ippiNormL2GetBufferHostSize_8u_AC4R	1501
7.100.2.44	ippiNormL2GetBufferHostSize_8u_C1MR	1501
7.100.2.45	ippiNormL2GetBufferHostSize_8u_C1R	1502
7.100.2.46	ippiNormL2GetBufferHostSize_8u_C3CMR	1502
7.100.2.47	ippiNormL2GetBufferHostSize_8u_C3R	1502
7.100.2.48	ippiNormL2GetBufferHostSize_8u_C4R	1503
7.101	NormDiff_Inf	1504
7.101.1	Detailed Description	1508
7.101.2	Function Documentation	1508
7.101.2.1	ippiNormDiff_Inf_16s_AC4R	1508
7.101.2.2	ippiNormDiff_Inf_16s_C1R	1509
7.101.2.3	ippiNormDiff_Inf_16s_C3R	1509
7.101.2.4	ippiNormDiff_Inf_16s_C4R	1509
7.101.2.5	ippiNormDiff_Inf_16u_AC4R	1510
7.101.2.6	ippiNormDiff_Inf_16u_C1MR	1510
7.101.2.7	ippiNormDiff_Inf_16u_C1R	1511
7.101.2.8	ippiNormDiff_Inf_16u_C3CMR	1511
7.101.2.9	ippiNormDiff_Inf_16u_C3R	1512
7.101.2.10	ippiNormDiff_Inf_16u_C4R	1512
7.101.2.11	ippiNormDiff_Inf_32f_AC4R	1513
7.101.2.12	ippiNormDiff_Inf_32f_C1MR	1513
7.101.2.13	ippiNormDiff_Inf_32f_C1R	1514
7.101.2.14	ippiNormDiff_Inf_32f_C3CMR	1514
7.101.2.15	ippiNormDiff_Inf_32f_C3R	1515
7.101.2.16	ippiNormDiff_Inf_32f_C4R	1515
7.101.2.17	ippiNormDiff_Inf_8s_C1MR	1515
7.101.2.18	ippiNormDiff_Inf_8s_C3CMR	1516
7.101.2.19	ippiNormDiff_Inf_8u_AC4R	1516
7.101.2.20	ippiNormDiff_Inf_8u_C1MR	1517
7.101.2.21	ippiNormDiff_Inf_8u_C1R	1517
7.101.2.22	ippiNormDiff_Inf_8u_C3CMR	1518
7.101.2.23	ippiNormDiff_Inf_8u_C3R	1518
7.101.2.24	ippiNormDiff_Inf_8u_C4R	1519
7.101.2.25	ippiNormDiffInfGetBufferHostSize_16s_AC4R	1519
7.101.2.26	ippiNormDiffInfGetBufferHostSize_16s_C1R	1520
7.101.2.27	ippiNormDiffInfGetBufferHostSize_16s_C3R	1520

7.101.2.28	nppiNormDiffInfGetBufferHostSize_16s_C4R	1520
7.101.2.29	nppiNormDiffInfGetBufferHostSize_16u_AC4R	1520
7.101.2.30	nppiNormDiffInfGetBufferHostSize_16u_C1MR	1521
7.101.2.31	nppiNormDiffInfGetBufferHostSize_16u_C1R	1521
7.101.2.32	nppiNormDiffInfGetBufferHostSize_16u_C3CMR	1521
7.101.2.33	nppiNormDiffInfGetBufferHostSize_16u_C3R	1522
7.101.2.34	nppiNormDiffInfGetBufferHostSize_16u_C4R	1522
7.101.2.35	nppiNormDiffInfGetBufferHostSize_32f_AC4R	1522
7.101.2.36	nppiNormDiffInfGetBufferHostSize_32f_C1MR	1522
7.101.2.37	nppiNormDiffInfGetBufferHostSize_32f_C1R	1523
7.101.2.38	nppiNormDiffInfGetBufferHostSize_32f_C3CMR	1523
7.101.2.39	nppiNormDiffInfGetBufferHostSize_32f_C3R	1523
7.101.2.40	nppiNormDiffInfGetBufferHostSize_32f_C4R	1524
7.101.2.41	nppiNormDiffInfGetBufferHostSize_8s_C1MR	1524
7.101.2.42	nppiNormDiffInfGetBufferHostSize_8s_C3CMR	1524
7.101.2.43	nppiNormDiffInfGetBufferHostSize_8u_AC4R	1524
7.101.2.44	nppiNormDiffInfGetBufferHostSize_8u_C1MR	1525
7.101.2.45	nppiNormDiffInfGetBufferHostSize_8u_C1R	1525
7.101.2.46	nppiNormDiffInfGetBufferHostSize_8u_C3CMR	1525
7.101.2.47	nppiNormDiffInfGetBufferHostSize_8u_C3R	1526
7.101.2.48	nppiNormDiffInfGetBufferHostSize_8u_C4R	1526
7.102	NormDiff_L1	1527
7.102.1	Detailed Description	1531
7.102.2	Function Documentation	1531
7.102.2.1	nppiNormDiff_L1_16s_AC4R	1531
7.102.2.2	nppiNormDiff_L1_16s_C1R	1531
7.102.2.3	nppiNormDiff_L1_16s_C3R	1532
7.102.2.4	nppiNormDiff_L1_16s_C4R	1532
7.102.2.5	nppiNormDiff_L1_16u_AC4R	1533
7.102.2.6	nppiNormDiff_L1_16u_C1MR	1533
7.102.2.7	nppiNormDiff_L1_16u_C1R	1534
7.102.2.8	nppiNormDiff_L1_16u_C3CMR	1534
7.102.2.9	nppiNormDiff_L1_16u_C3R	1535
7.102.2.10	nppiNormDiff_L1_16u_C4R	1535
7.102.2.11	nppiNormDiff_L1_32f_AC4R	1535
7.102.2.12	nppiNormDiff_L1_32f_C1MR	1536

7.102.2.13	nppiNormDiff_L1_32f_C1R	1536
7.102.2.14	nppiNormDiff_L1_32f_C3CMR	1537
7.102.2.15	nppiNormDiff_L1_32f_C3R	1537
7.102.2.16	nppiNormDiff_L1_32f_C4R	1538
7.102.2.17	nppiNormDiff_L1_8s_C1MR	1538
7.102.2.18	nppiNormDiff_L1_8s_C3CMR	1539
7.102.2.19	nppiNormDiff_L1_8u_AC4R	1539
7.102.2.20	nppiNormDiff_L1_8u_C1MR	1540
7.102.2.21	nppiNormDiff_L1_8u_C1R	1540
7.102.2.22	nppiNormDiff_L1_8u_C3CMR	1541
7.102.2.23	nppiNormDiff_L1_8u_C3R	1541
7.102.2.24	nppiNormDiff_L1_8u_C4R	1542
7.102.2.25	nppiNormDiffL1GetBufferHostSize_16s_AC4R	1542
7.102.2.26	nppiNormDiffL1GetBufferHostSize_16s_C1R	1542
7.102.2.27	nppiNormDiffL1GetBufferHostSize_16s_C3R	1543
7.102.2.28	nppiNormDiffL1GetBufferHostSize_16s_C4R	1543
7.102.2.29	nppiNormDiffL1GetBufferHostSize_16u_AC4R	1543
7.102.2.30	nppiNormDiffL1GetBufferHostSize_16u_C1MR	1543
7.102.2.31	nppiNormDiffL1GetBufferHostSize_16u_C1R	1544
7.102.2.32	nppiNormDiffL1GetBufferHostSize_16u_C3CMR	1544
7.102.2.33	nppiNormDiffL1GetBufferHostSize_16u_C3R	1544
7.102.2.34	nppiNormDiffL1GetBufferHostSize_16u_C4R	1545
7.102.2.35	nppiNormDiffL1GetBufferHostSize_32f_AC4R	1545
7.102.2.36	nppiNormDiffL1GetBufferHostSize_32f_C1MR	1545
7.102.2.37	nppiNormDiffL1GetBufferHostSize_32f_C1R	1545
7.102.2.38	nppiNormDiffL1GetBufferHostSize_32f_C3CMR	1546
7.102.2.39	nppiNormDiffL1GetBufferHostSize_32f_C3R	1546
7.102.2.40	nppiNormDiffL1GetBufferHostSize_32f_C4R	1546
7.102.2.41	nppiNormDiffL1GetBufferHostSize_8s_C1MR	1547
7.102.2.42	nppiNormDiffL1GetBufferHostSize_8s_C3CMR	1547
7.102.2.43	nppiNormDiffL1GetBufferHostSize_8u_AC4R	1547
7.102.2.44	nppiNormDiffL1GetBufferHostSize_8u_C1MR	1547
7.102.2.45	nppiNormDiffL1GetBufferHostSize_8u_C1R	1548
7.102.2.46	nppiNormDiffL1GetBufferHostSize_8u_C3CMR	1548
7.102.2.47	nppiNormDiffL1GetBufferHostSize_8u_C3R	1548
7.102.2.48	nppiNormDiffL1GetBufferHostSize_8u_C4R	1549

7.103 NormDiff_L2	1550
7.103.1 Detailed Description	1554
7.103.2 Function Documentation	1554
7.103.2.1 nppiNormDiff_L2_16s_AC4R	1554
7.103.2.2 nppiNormDiff_L2_16s_C1R	1554
7.103.2.3 nppiNormDiff_L2_16s_C3R	1555
7.103.2.4 nppiNormDiff_L2_16s_C4R	1555
7.103.2.5 nppiNormDiff_L2_16u_AC4R	1556
7.103.2.6 nppiNormDiff_L2_16u_C1MR	1556
7.103.2.7 nppiNormDiff_L2_16u_C1R	1557
7.103.2.8 nppiNormDiff_L2_16u_C3CMR	1557
7.103.2.9 nppiNormDiff_L2_16u_C3R	1558
7.103.2.10 nppiNormDiff_L2_16u_C4R	1558
7.103.2.11 nppiNormDiff_L2_32f_AC4R	1558
7.103.2.12 nppiNormDiff_L2_32f_C1MR	1559
7.103.2.13 nppiNormDiff_L2_32f_C1R	1559
7.103.2.14 nppiNormDiff_L2_32f_C3CMR	1560
7.103.2.15 nppiNormDiff_L2_32f_C3R	1560
7.103.2.16 nppiNormDiff_L2_32f_C4R	1561
7.103.2.17 nppiNormDiff_L2_8s_C1MR	1561
7.103.2.18 nppiNormDiff_L2_8s_C3CMR	1562
7.103.2.19 nppiNormDiff_L2_8u_AC4R	1562
7.103.2.20 nppiNormDiff_L2_8u_C1MR	1563
7.103.2.21 nppiNormDiff_L2_8u_C1R	1563
7.103.2.22 nppiNormDiff_L2_8u_C3CMR	1564
7.103.2.23 nppiNormDiff_L2_8u_C3R	1564
7.103.2.24 nppiNormDiff_L2_8u_C4R	1565
7.103.2.25 nppiNormDiffL2GetBufferHostSize_16s_AC4R	1565
7.103.2.26 nppiNormDiffL2GetBufferHostSize_16s_C1R	1565
7.103.2.27 nppiNormDiffL2GetBufferHostSize_16s_C3R	1566
7.103.2.28 nppiNormDiffL2GetBufferHostSize_16s_C4R	1566
7.103.2.29 nppiNormDiffL2GetBufferHostSize_16u_AC4R	1566
7.103.2.30 nppiNormDiffL2GetBufferHostSize_16u_C1MR	1566
7.103.2.31 nppiNormDiffL2GetBufferHostSize_16u_C1R	1567
7.103.2.32 nppiNormDiffL2GetBufferHostSize_16u_C3CMR	1567
7.103.2.33 nppiNormDiffL2GetBufferHostSize_16u_C3R	1567

7.103.2.34	nppiNormDiffL2GetBufferHostSize_16u_C4R	1568
7.103.2.35	nppiNormDiffL2GetBufferHostSize_32f_AC4R	1568
7.103.2.36	nppiNormDiffL2GetBufferHostSize_32f_C1MR	1568
7.103.2.37	nppiNormDiffL2GetBufferHostSize_32f_C1R	1568
7.103.2.38	nppiNormDiffL2GetBufferHostSize_32f_C3CMR	1569
7.103.2.39	nppiNormDiffL2GetBufferHostSize_32f_C3R	1569
7.103.2.40	nppiNormDiffL2GetBufferHostSize_32f_C4R	1569
7.103.2.41	nppiNormDiffL2GetBufferHostSize_8s_C1MR	1570
7.103.2.42	nppiNormDiffL2GetBufferHostSize_8s_C3CMR	1570
7.103.2.43	nppiNormDiffL2GetBufferHostSize_8u_AC4R	1570
7.103.2.44	nppiNormDiffL2GetBufferHostSize_8u_C1MR	1570
7.103.2.45	nppiNormDiffL2GetBufferHostSize_8u_C1R	1571
7.103.2.46	nppiNormDiffL2GetBufferHostSize_8u_C3CMR	1571
7.103.2.47	nppiNormDiffL2GetBufferHostSize_8u_C3R	1571
7.103.2.48	nppiNormDiffL2GetBufferHostSize_8u_C4R	1572
7.104	NormRel_Inf	1573
7.104.1	Detailed Description	1577
7.104.2	Function Documentation	1577
7.104.2.1	nppiNormRel_Inf_16s_AC4R	1577
7.104.2.2	nppiNormRel_Inf_16s_C1R	1577
7.104.2.3	nppiNormRel_Inf_16s_C3R	1578
7.104.2.4	nppiNormRel_Inf_16s_C4R	1578
7.104.2.5	nppiNormRel_Inf_16u_AC4R	1579
7.104.2.6	nppiNormRel_Inf_16u_C1MR	1579
7.104.2.7	nppiNormRel_Inf_16u_C1R	1580
7.104.2.8	nppiNormRel_Inf_16u_C3CMR	1580
7.104.2.9	nppiNormRel_Inf_16u_C3R	1581
7.104.2.10	nppiNormRel_Inf_16u_C4R	1581
7.104.2.11	nppiNormRel_Inf_32f_AC4R	1582
7.104.2.12	nppiNormRel_Inf_32f_C1MR	1582
7.104.2.13	nppiNormRel_Inf_32f_C1R	1583
7.104.2.14	nppiNormRel_Inf_32f_C3CMR	1583
7.104.2.15	nppiNormRel_Inf_32f_C3R	1584
7.104.2.16	nppiNormRel_Inf_32f_C4R	1584
7.104.2.17	nppiNormRel_Inf_8s_C1MR	1585
7.104.2.18	nppiNormRel_Inf_8s_C3CMR	1585

7.104.2.19	nppiNormRel_Inf_8u_AC4R	1586
7.104.2.20	nppiNormRel_Inf_8u_C1MR	1586
7.104.2.21	nppiNormRel_Inf_8u_C1R	1587
7.104.2.22	nppiNormRel_Inf_8u_C3CMR	1587
7.104.2.23	nppiNormRel_Inf_8u_C3R	1588
7.104.2.24	nppiNormRel_Inf_8u_C4R	1588
7.104.2.25	nppiNormRelInfGetBufferHostSize_16s_AC4R	1588
7.104.2.26	nppiNormRelInfGetBufferHostSize_16s_C1R	1589
7.104.2.27	nppiNormRelInfGetBufferHostSize_16s_C3R	1589
7.104.2.28	nppiNormRelInfGetBufferHostSize_16s_C4R	1589
7.104.2.29	nppiNormRelInfGetBufferHostSize_16u_AC4R	1590
7.104.2.30	nppiNormRelInfGetBufferHostSize_16u_C1MR	1590
7.104.2.31	nppiNormRelInfGetBufferHostSize_16u_C1R	1590
7.104.2.32	nppiNormRelInfGetBufferHostSize_16u_C3CMR	1590
7.104.2.33	nppiNormRelInfGetBufferHostSize_16u_C3R	1591
7.104.2.34	nppiNormRelInfGetBufferHostSize_16u_C4R	1591
7.104.2.35	nppiNormRelInfGetBufferHostSize_32f_AC4R	1591
7.104.2.36	nppiNormRelInfGetBufferHostSize_32f_C1MR	1592
7.104.2.37	nppiNormRelInfGetBufferHostSize_32f_C1R	1592
7.104.2.38	nppiNormRelInfGetBufferHostSize_32f_C3CMR	1592
7.104.2.39	nppiNormRelInfGetBufferHostSize_32f_C3R	1592
7.104.2.40	nppiNormRelInfGetBufferHostSize_32f_C4R	1593
7.104.2.41	nppiNormRelInfGetBufferHostSize_32s_C1R	1593
7.104.2.42	nppiNormRelInfGetBufferHostSize_8s_C1MR	1593
7.104.2.43	nppiNormRelInfGetBufferHostSize_8s_C3CMR	1594
7.104.2.44	nppiNormRelInfGetBufferHostSize_8u_AC4R	1594
7.104.2.45	nppiNormRelInfGetBufferHostSize_8u_C1MR	1594
7.104.2.46	nppiNormRelInfGetBufferHostSize_8u_C1R	1594
7.104.2.47	nppiNormRelInfGetBufferHostSize_8u_C3CMR	1595
7.104.2.48	nppiNormRelInfGetBufferHostSize_8u_C3R	1595
7.104.2.49	nppiNormRelInfGetBufferHostSize_8u_C4R	1595
7.105	NormRel_L1	1596
7.105.1	Detailed Description	1600
7.105.2	Function Documentation	1600
7.105.2.1	nppiNormRel_L1_16s_AC4R	1600
7.105.2.2	nppiNormRel_L1_16s_C1R	1600

7.105.2.3 nppiNormRel_L1_16s_C3R 1601

7.105.2.4 nppiNormRel_L1_16s_C4R 1601

7.105.2.5 nppiNormRel_L1_16u_AC4R 1602

7.105.2.6 nppiNormRel_L1_16u_C1MR 1602

7.105.2.7 nppiNormRel_L1_16u_C1R 1603

7.105.2.8 nppiNormRel_L1_16u_C3CMR 1603

7.105.2.9 nppiNormRel_L1_16u_C3R 1604

7.105.2.10 nppiNormRel_L1_16u_C4R 1604

7.105.2.11 nppiNormRel_L1_32f_AC4R 1604

7.105.2.12 nppiNormRel_L1_32f_C1MR 1605

7.105.2.13 nppiNormRel_L1_32f_C1R 1605

7.105.2.14 nppiNormRel_L1_32f_C3CMR 1606

7.105.2.15 nppiNormRel_L1_32f_C3R 1606

7.105.2.16 nppiNormRel_L1_32f_C4R 1607

7.105.2.17 nppiNormRel_L1_8s_C1MR 1607

7.105.2.18 nppiNormRel_L1_8s_C3CMR 1608

7.105.2.19 nppiNormRel_L1_8u_AC4R 1608

7.105.2.20 nppiNormRel_L1_8u_C1MR 1609

7.105.2.21 nppiNormRel_L1_8u_C1R 1609

7.105.2.22 nppiNormRel_L1_8u_C3CMR 1610

7.105.2.23 nppiNormRel_L1_8u_C3R 1610

7.105.2.24 nppiNormRel_L1_8u_C4R 1611

7.105.2.25 nppiNormRelL1GetBufferHostSize_16s_AC4R 1611

7.105.2.26 nppiNormRelL1GetBufferHostSize_16s_C1R 1612

7.105.2.27 nppiNormRelL1GetBufferHostSize_16s_C3R 1612

7.105.2.28 nppiNormRelL1GetBufferHostSize_16s_C4R 1612

7.105.2.29 nppiNormRelL1GetBufferHostSize_16u_AC4R 1612

7.105.2.30 nppiNormRelL1GetBufferHostSize_16u_C1MR 1613

7.105.2.31 nppiNormRelL1GetBufferHostSize_16u_C1R 1613

7.105.2.32 nppiNormRelL1GetBufferHostSize_16u_C3CMR 1613

7.105.2.33 nppiNormRelL1GetBufferHostSize_16u_C3R 1614

7.105.2.34 nppiNormRelL1GetBufferHostSize_16u_C4R 1614

7.105.2.35 nppiNormRelL1GetBufferHostSize_32f_AC4R 1614

7.105.2.36 nppiNormRelL1GetBufferHostSize_32f_C1MR 1614

7.105.2.37 nppiNormRelL1GetBufferHostSize_32f_C1R 1615

7.105.2.38 nppiNormRelL1GetBufferHostSize_32f_C3CMR 1615

7.105.2.39	ippiNormRelL1GetBufferHostSize_32f_C3R	1615
7.105.2.40	ippiNormRelL1GetBufferHostSize_32f_C4R	1616
7.105.2.41	ippiNormRelL1GetBufferHostSize_8s_C1MR	1616
7.105.2.42	ippiNormRelL1GetBufferHostSize_8s_C3CMR	1616
7.105.2.43	ippiNormRelL1GetBufferHostSize_8u_AC4R	1616
7.105.2.44	ippiNormRelL1GetBufferHostSize_8u_C1MR	1617
7.105.2.45	ippiNormRelL1GetBufferHostSize_8u_C1R	1617
7.105.2.46	ippiNormRelL1GetBufferHostSize_8u_C3CMR	1617
7.105.2.47	ippiNormRelL1GetBufferHostSize_8u_C3R	1618
7.105.2.48	ippiNormRelL1GetBufferHostSize_8u_C4R	1618
7.106	NormRel_L2	1619
7.106.1	Detailed Description	1623
7.106.2	Function Documentation	1623
7.106.2.1	ippiNormRel_L2_16s_AC4R	1623
7.106.2.2	ippiNormRel_L2_16s_C1R	1623
7.106.2.3	ippiNormRel_L2_16s_C3R	1624
7.106.2.4	ippiNormRel_L2_16s_C4R	1624
7.106.2.5	ippiNormRel_L2_16u_AC4R	1625
7.106.2.6	ippiNormRel_L2_16u_C1MR	1625
7.106.2.7	ippiNormRel_L2_16u_C1R	1626
7.106.2.8	ippiNormRel_L2_16u_C3CMR	1626
7.106.2.9	ippiNormRel_L2_16u_C3R	1627
7.106.2.10	ippiNormRel_L2_16u_C4R	1627
7.106.2.11	ippiNormRel_L2_32f_AC4R	1627
7.106.2.12	ippiNormRel_L2_32f_C1MR	1628
7.106.2.13	ippiNormRel_L2_32f_C1R	1628
7.106.2.14	ippiNormRel_L2_32f_C3CMR	1629
7.106.2.15	ippiNormRel_L2_32f_C3R	1629
7.106.2.16	ippiNormRel_L2_32f_C4R	1630
7.106.2.17	ippiNormRel_L2_8s_C1MR	1630
7.106.2.18	ippiNormRel_L2_8s_C3CMR	1631
7.106.2.19	ippiNormRel_L2_8u_AC4R	1631
7.106.2.20	ippiNormRel_L2_8u_C1MR	1632
7.106.2.21	ippiNormRel_L2_8u_C1R	1632
7.106.2.22	ippiNormRel_L2_8u_C3CMR	1633
7.106.2.23	ippiNormRel_L2_8u_C3R	1633

7.106.2.24 nppiNormRel_L2_8u_C4R 1634

7.106.2.25 nppiNormRelL2GetBufferHostSize_16s_AC4R 1634

7.106.2.26 nppiNormRelL2GetBufferHostSize_16s_C1R 1635

7.106.2.27 nppiNormRelL2GetBufferHostSize_16s_C3R 1635

7.106.2.28 nppiNormRelL2GetBufferHostSize_16s_C4R 1635

7.106.2.29 nppiNormRelL2GetBufferHostSize_16u_AC4R 1635

7.106.2.30 nppiNormRelL2GetBufferHostSize_16u_C1MR 1636

7.106.2.31 nppiNormRelL2GetBufferHostSize_16u_C1R 1636

7.106.2.32 nppiNormRelL2GetBufferHostSize_16u_C3CMR 1636

7.106.2.33 nppiNormRelL2GetBufferHostSize_16u_C3R 1637

7.106.2.34 nppiNormRelL2GetBufferHostSize_16u_C4R 1637

7.106.2.35 nppiNormRelL2GetBufferHostSize_32f_AC4R 1637

7.106.2.36 nppiNormRelL2GetBufferHostSize_32f_C1MR 1637

7.106.2.37 nppiNormRelL2GetBufferHostSize_32f_C1R 1638

7.106.2.38 nppiNormRelL2GetBufferHostSize_32f_C3CMR 1638

7.106.2.39 nppiNormRelL2GetBufferHostSize_32f_C3R 1638

7.106.2.40 nppiNormRelL2GetBufferHostSize_32f_C4R 1639

7.106.2.41 nppiNormRelL2GetBufferHostSize_8s_C1MR 1639

7.106.2.42 nppiNormRelL2GetBufferHostSize_8s_C3CMR 1639

7.106.2.43 nppiNormRelL2GetBufferHostSize_8u_AC4R 1639

7.106.2.44 nppiNormRelL2GetBufferHostSize_8u_C1MR 1640

7.106.2.45 nppiNormRelL2GetBufferHostSize_8u_C1R 1640

7.106.2.46 nppiNormRelL2GetBufferHostSize_8u_C3CMR 1640

7.106.2.47 nppiNormRelL2GetBufferHostSize_8u_C3R 1641

7.106.2.48 nppiNormRelL2GetBufferHostSize_8u_C4R 1641

7.107 DotProd 1642

 7.107.1 Detailed Description 1646

 7.107.2 Function Documentation 1646

 7.107.2.1 nppiDotProd_16s64f_AC4R 1646

 7.107.2.2 nppiDotProd_16s64f_C1R 1647

 7.107.2.3 nppiDotProd_16s64f_C3R 1647

 7.107.2.4 nppiDotProd_16s64f_C4R 1647

 7.107.2.5 nppiDotProd_16u64f_AC4R 1648

 7.107.2.6 nppiDotProd_16u64f_C1R 1648

 7.107.2.7 nppiDotProd_16u64f_C3R 1649

 7.107.2.8 nppiDotProd_16u64f_C4R 1649

7.107.2.9 nppiDotProd_32f64f_AC4R	1650
7.107.2.10 nppiDotProd_32f64f_C1R	1650
7.107.2.11 nppiDotProd_32f64f_C3R	1650
7.107.2.12 nppiDotProd_32f64f_C4R	1651
7.107.2.13 nppiDotProd_32s64f_AC4R	1651
7.107.2.14 nppiDotProd_32s64f_C1R	1652
7.107.2.15 nppiDotProd_32s64f_C3R	1652
7.107.2.16 nppiDotProd_32s64f_C4R	1653
7.107.2.17 nppiDotProd_32u64f_AC4R	1653
7.107.2.18 nppiDotProd_32u64f_C1R	1653
7.107.2.19 nppiDotProd_32u64f_C3R	1654
7.107.2.20 nppiDotProd_32u64f_C4R	1654
7.107.2.21 nppiDotProd_8s64f_AC4R	1655
7.107.2.22 nppiDotProd_8s64f_C1R	1655
7.107.2.23 nppiDotProd_8s64f_C3R	1656
7.107.2.24 nppiDotProd_8s64f_C4R	1656
7.107.2.25 nppiDotProd_8u64f_AC4R	1656
7.107.2.26 nppiDotProd_8u64f_C1R	1657
7.107.2.27 nppiDotProd_8u64f_C3R	1657
7.107.2.28 nppiDotProd_8u64f_C4R	1658
7.107.2.29 nppiDotProdGetBufferHostSize_16s64f_AC4R	1658
7.107.2.30 nppiDotProdGetBufferHostSize_16s64f_C1R	1658
7.107.2.31 nppiDotProdGetBufferHostSize_16s64f_C3R	1659
7.107.2.32 nppiDotProdGetBufferHostSize_16s64f_C4R	1659
7.107.2.33 nppiDotProdGetBufferHostSize_16u64f_AC4R	1659
7.107.2.34 nppiDotProdGetBufferHostSize_16u64f_C1R	1660
7.107.2.35 nppiDotProdGetBufferHostSize_16u64f_C3R	1660
7.107.2.36 nppiDotProdGetBufferHostSize_16u64f_C4R	1660
7.107.2.37 nppiDotProdGetBufferHostSize_32f64f_AC4R	1660
7.107.2.38 nppiDotProdGetBufferHostSize_32f64f_C1R	1661
7.107.2.39 nppiDotProdGetBufferHostSize_32f64f_C3R	1661
7.107.2.40 nppiDotProdGetBufferHostSize_32f64f_C4R	1661
7.107.2.41 nppiDotProdGetBufferHostSize_32s64f_AC4R	1662
7.107.2.42 nppiDotProdGetBufferHostSize_32s64f_C1R	1662
7.107.2.43 nppiDotProdGetBufferHostSize_32s64f_C3R	1662
7.107.2.44 nppiDotProdGetBufferHostSize_32s64f_C4R	1662

7.107.2.45	nppiDotProdGetBufferHostSize_32u64f_AC4R	1663
7.107.2.46	nppiDotProdGetBufferHostSize_32u64f_C1R	1663
7.107.2.47	nppiDotProdGetBufferHostSize_32u64f_C3R	1663
7.107.2.48	nppiDotProdGetBufferHostSize_32u64f_C4R	1664
7.107.2.49	nppiDotProdGetBufferHostSize_8s64f_AC4R	1664
7.107.2.50	nppiDotProdGetBufferHostSize_8s64f_C1R	1664
7.107.2.51	nppiDotProdGetBufferHostSize_8s64f_C3R	1664
7.107.2.52	nppiDotProdGetBufferHostSize_8s64f_C4R	1665
7.107.2.53	nppiDotProdGetBufferHostSize_8u64f_AC4R	1665
7.107.2.54	nppiDotProdGetBufferHostSize_8u64f_C1R	1665
7.107.2.55	nppiDotProdGetBufferHostSize_8u64f_C3R	1666
7.107.2.56	nppiDotProdGetBufferHostSize_8u64f_C4R	1666
7.108	CountInRange	1667
7.108.1	Detailed Description	1668
7.108.2	Function Documentation	1668
7.108.2.1	nppiCountInRange_32f_AC4R	1668
7.108.2.2	nppiCountInRange_32f_C1R	1668
7.108.2.3	nppiCountInRange_32f_C3R	1669
7.108.2.4	nppiCountInRange_8u_AC4R	1669
7.108.2.5	nppiCountInRange_8u_C1R	1670
7.108.2.6	nppiCountInRange_8u_C3R	1670
7.108.2.7	nppiCountInRangeGetBufferHostSize_32f_AC4R	1671
7.108.2.8	nppiCountInRangeGetBufferHostSize_32f_C1R	1671
7.108.2.9	nppiCountInRangeGetBufferHostSize_32f_C3R	1671
7.108.2.10	nppiCountInRangeGetBufferHostSize_8u_AC4R	1672
7.108.2.11	nppiCountInRangeGetBufferHostSize_8u_C1R	1672
7.108.2.12	nppiCountInRangeGetBufferHostSize_8u_C3R	1672
7.109	MaxEvery	1673
7.109.1	Detailed Description	1674
7.109.2	Function Documentation	1674
7.109.2.1	nppiMaxEvery_16s_AC4IR	1674
7.109.2.2	nppiMaxEvery_16s_C1IR	1675
7.109.2.3	nppiMaxEvery_16s_C3IR	1675
7.109.2.4	nppiMaxEvery_16s_C4IR	1675
7.109.2.5	nppiMaxEvery_16u_AC4IR	1676
7.109.2.6	nppiMaxEvery_16u_C1IR	1676

7.109.2.7	nppiMaxEvery_16u_C3IR	1676
7.109.2.8	nppiMaxEvery_16u_C4IR	1677
7.109.2.9	nppiMaxEvery_32f_AC4IR	1677
7.109.2.10	nppiMaxEvery_32f_C1IR	1677
7.109.2.11	nppiMaxEvery_32f_C3IR	1678
7.109.2.12	nppiMaxEvery_32f_C4IR	1678
7.109.2.13	nppiMaxEvery_8u_AC4IR	1678
7.109.2.14	nppiMaxEvery_8u_C1IR	1679
7.109.2.15	nppiMaxEvery_8u_C3IR	1679
7.109.2.16	nppiMaxEvery_8u_C4IR	1679
7.110	MinEvery	1680
7.110.1	Detailed Description	1681
7.110.2	Function Documentation	1681
7.110.2.1	nppiMinEvery_16s_AC4IR	1681
7.110.2.2	nppiMinEvery_16s_C1IR	1682
7.110.2.3	nppiMinEvery_16s_C3IR	1682
7.110.2.4	nppiMinEvery_16s_C4IR	1682
7.110.2.5	nppiMinEvery_16u_AC4IR	1683
7.110.2.6	nppiMinEvery_16u_C1IR	1683
7.110.2.7	nppiMinEvery_16u_C3IR	1683
7.110.2.8	nppiMinEvery_16u_C4IR	1684
7.110.2.9	nppiMinEvery_32f_AC4IR	1684
7.110.2.10	nppiMinEvery_32f_C1IR	1684
7.110.2.11	nppiMinEvery_32f_C3IR	1685
7.110.2.12	nppiMinEvery_32f_C4IR	1685
7.110.2.13	nppiMinEvery_8u_AC4IR	1685
7.110.2.14	nppiMinEvery_8u_C1IR	1686
7.110.2.15	nppiMinEvery_8u_C3IR	1686
7.110.2.16	nppiMinEvery_8u_C4IR	1686
7.111	Integral	1687
7.111.1	Detailed Description	1687
7.111.2	Function Documentation	1687
7.111.2.1	nppiIntegral_8u32f_C1R	1687
7.111.2.2	nppiIntegral_8u32s_C1R	1688
7.112	SqrIntegral	1689
7.112.1	Detailed Description	1689

7.112.2 Function Documentation	1689
7.112.2.1 nppiSqrIntegral_8u32f64f_C1R	1689
7.112.2.2 nppiSqrIntegral_8u32s64f_C1R	1690
7.112.2.3 nppiSqrIntegral_8u32s_C1R	1690
7.113 RectStdDev	1692
7.113.1 Detailed Description	1692
7.113.2 Function Documentation	1692
7.113.2.1 nppiRectStdDev_32f_C1R	1692
7.113.2.2 nppiRectStdDev_32s32f_C1R	1693
7.113.2.3 nppiRectStdDev_32s_C1RSfs	1693
7.114 HistogramEven	1695
7.114.1 Detailed Description	1697
7.114.2 Function Documentation	1697
7.114.2.1 nppiEvenLevelsHost_32s	1697
7.114.2.2 nppiHistogramEven_16s_AC4R	1698
7.114.2.3 nppiHistogramEven_16s_C1R	1698
7.114.2.4 nppiHistogramEven_16s_C3R	1699
7.114.2.5 nppiHistogramEven_16s_C4R	1699
7.114.2.6 nppiHistogramEven_16u_AC4R	1700
7.114.2.7 nppiHistogramEven_16u_C1R	1700
7.114.2.8 nppiHistogramEven_16u_C3R	1701
7.114.2.9 nppiHistogramEven_16u_C4R	1701
7.114.2.10 nppiHistogramEven_8u_AC4R	1702
7.114.2.11 nppiHistogramEven_8u_C1R	1702
7.114.2.12 nppiHistogramEven_8u_C3R	1702
7.114.2.13 nppiHistogramEven_8u_C4R	1703
7.114.2.14 nppiHistogramEvenGetBufferSize_16s_AC4R	1703
7.114.2.15 nppiHistogramEvenGetBufferSize_16s_C1R	1704
7.114.2.16 nppiHistogramEvenGetBufferSize_16s_C3R	1704
7.114.2.17 nppiHistogramEvenGetBufferSize_16s_C4R	1704
7.114.2.18 nppiHistogramEvenGetBufferSize_16u_AC4R	1705
7.114.2.19 nppiHistogramEvenGetBufferSize_16u_C1R	1705
7.114.2.20 nppiHistogramEvenGetBufferSize_16u_C3R	1705
7.114.2.21 nppiHistogramEvenGetBufferSize_16u_C4R	1706
7.114.2.22 nppiHistogramEvenGetBufferSize_8u_AC4R	1706
7.114.2.23 nppiHistogramEvenGetBufferSize_8u_C1R	1706

7.114.2.24	nppiHistogramEvenGetBufferSize_8u_C3R	1707
7.114.2.25	nppiHistogramEvenGetBufferSize_8u_C4R	1707
7.115	HistogramRange	1708
7.115.1	Detailed Description	1710
7.115.2	Function Documentation	1711
7.115.2.1	nppiHistogramRange_16s_AC4R	1711
7.115.2.2	nppiHistogramRange_16s_C1R	1711
7.115.2.3	nppiHistogramRange_16s_C3R	1712
7.115.2.4	nppiHistogramRange_16s_C4R	1712
7.115.2.5	nppiHistogramRange_16u_AC4R	1712
7.115.2.6	nppiHistogramRange_16u_C1R	1713
7.115.2.7	nppiHistogramRange_16u_C3R	1713
7.115.2.8	nppiHistogramRange_16u_C4R	1714
7.115.2.9	nppiHistogramRange_32f_AC4R	1714
7.115.2.10	nppiHistogramRange_32f_C1R	1715
7.115.2.11	nppiHistogramRange_32f_C3R	1715
7.115.2.12	nppiHistogramRange_32f_C4R	1716
7.115.2.13	nppiHistogramRange_8u_AC4R	1716
7.115.2.14	nppiHistogramRange_8u_C1R	1717
7.115.2.15	nppiHistogramRange_8u_C3R	1717
7.115.2.16	nppiHistogramRange_8u_C4R	1717
7.115.2.17	nppiHistogramRangeGetBufferSize_16s_AC4R	1718
7.115.2.18	nppiHistogramRangeGetBufferSize_16s_C1R	1718
7.115.2.19	nppiHistogramRangeGetBufferSize_16s_C3R	1719
7.115.2.20	nppiHistogramRangeGetBufferSize_16s_C4R	1719
7.115.2.21	nppiHistogramRangeGetBufferSize_16u_AC4R	1719
7.115.2.22	nppiHistogramRangeGetBufferSize_16u_C1R	1720
7.115.2.23	nppiHistogramRangeGetBufferSize_16u_C3R	1720
7.115.2.24	nppiHistogramRangeGetBufferSize_16u_C4R	1720
7.115.2.25	nppiHistogramRangeGetBufferSize_32f_AC4R	1721
7.115.2.26	nppiHistogramRangeGetBufferSize_32f_C1R	1721
7.115.2.27	nppiHistogramRangeGetBufferSize_32f_C3R	1721
7.115.2.28	nppiHistogramRangeGetBufferSize_32f_C4R	1722
7.115.2.29	nppiHistogramRangeGetBufferSize_8u_AC4R	1722
7.115.2.30	nppiHistogramRangeGetBufferSize_8u_C1R	1722
7.115.2.31	nppiHistogramRangeGetBufferSize_8u_C3R	1723

7.115.2.32	nppiHistogramRangeGetBufferSize_8u_C4R	1723
7.116	Image Proximity	1724
7.116.1	Detailed Description	1724
7.116.2	General Introduction	1724
7.116.3	Categorizations	1726
7.117	SqrDistanceFull_Norm	1727
7.117.1	Detailed Description	1728
7.117.2	Function Documentation	1729
7.117.2.1	nppiSqrDistanceFull_Norm_16u32f_AC4R	1729
7.117.2.2	nppiSqrDistanceFull_Norm_16u32f_C1R	1729
7.117.2.3	nppiSqrDistanceFull_Norm_16u32f_C3R	1730
7.117.2.4	nppiSqrDistanceFull_Norm_16u32f_C4R	1730
7.117.2.5	nppiSqrDistanceFull_Norm_32f_AC4R	1730
7.117.2.6	nppiSqrDistanceFull_Norm_32f_C1R	1731
7.117.2.7	nppiSqrDistanceFull_Norm_32f_C3R	1731
7.117.2.8	nppiSqrDistanceFull_Norm_32f_C4R	1732
7.117.2.9	nppiSqrDistanceFull_Norm_8s32f_AC4R	1732
7.117.2.10	nppiSqrDistanceFull_Norm_8s32f_C1R	1733
7.117.2.11	nppiSqrDistanceFull_Norm_8s32f_C3R	1733
7.117.2.12	nppiSqrDistanceFull_Norm_8s32f_C4R	1733
7.117.2.13	nppiSqrDistanceFull_Norm_8u32f_AC4R	1734
7.117.2.14	nppiSqrDistanceFull_Norm_8u32f_C1R	1734
7.117.2.15	nppiSqrDistanceFull_Norm_8u32f_C3R	1735
7.117.2.16	nppiSqrDistanceFull_Norm_8u32f_C4R	1735
7.117.2.17	nppiSqrDistanceFull_Norm_8u_AC4RSfs	1736
7.117.2.18	nppiSqrDistanceFull_Norm_8u_C1RSfs	1736
7.117.2.19	nppiSqrDistanceFull_Norm_8u_C3RSfs	1737
7.117.2.20	nppiSqrDistanceFull_Norm_8u_C4RSfs	1737
7.118	SqrDistanceSame_Norm	1738
7.118.1	Detailed Description	1740
7.118.2	Function Documentation	1740
7.118.2.1	nppiSqrDistanceSame_Norm_16u32f_AC4R	1740
7.118.2.2	nppiSqrDistanceSame_Norm_16u32f_C1R	1740
7.118.2.3	nppiSqrDistanceSame_Norm_16u32f_C3R	1741
7.118.2.4	nppiSqrDistanceSame_Norm_16u32f_C4R	1741
7.118.2.5	nppiSqrDistanceSame_Norm_32f_AC4R	1742

7.118.2.6	nppiSqrDistanceSame_Norm_32f_C1R	1742
7.118.2.7	nppiSqrDistanceSame_Norm_32f_C3R	1742
7.118.2.8	nppiSqrDistanceSame_Norm_32f_C4R	1743
7.118.2.9	nppiSqrDistanceSame_Norm_8s32f_AC4R	1743
7.118.2.10	nppiSqrDistanceSame_Norm_8s32f_C1R	1744
7.118.2.11	nppiSqrDistanceSame_Norm_8s32f_C3R	1744
7.118.2.12	nppiSqrDistanceSame_Norm_8s32f_C4R	1745
7.118.2.13	nppiSqrDistanceSame_Norm_8u32f_AC4R	1745
7.118.2.14	nppiSqrDistanceSame_Norm_8u32f_C1R	1745
7.118.2.15	nppiSqrDistanceSame_Norm_8u32f_C3R	1746
7.118.2.16	nppiSqrDistanceSame_Norm_8u32f_C4R	1746
7.118.2.17	nppiSqrDistanceSame_Norm_8u_AC4RSfs	1747
7.118.2.18	nppiSqrDistanceSame_Norm_8u_C1RSfs	1747
7.118.2.19	nppiSqrDistanceSame_Norm_8u_C3RSfs	1748
7.118.2.20	nppiSqrDistanceSame_Norm_8u_C4RSfs	1748
7.119	SqrDistanceValid_Norm	1749
7.119.1	Detailed Description	1751
7.119.2	Function Documentation	1751
7.119.2.1	nppiSqrDistanceValid_Norm_16u32f_AC4R	1751
7.119.2.2	nppiSqrDistanceValid_Norm_16u32f_C1R	1751
7.119.2.3	nppiSqrDistanceValid_Norm_16u32f_C3R	1752
7.119.2.4	nppiSqrDistanceValid_Norm_16u32f_C4R	1752
7.119.2.5	nppiSqrDistanceValid_Norm_32f_AC4R	1753
7.119.2.6	nppiSqrDistanceValid_Norm_32f_C1R	1753
7.119.2.7	nppiSqrDistanceValid_Norm_32f_C3R	1753
7.119.2.8	nppiSqrDistanceValid_Norm_32f_C4R	1754
7.119.2.9	nppiSqrDistanceValid_Norm_8s32f_AC4R	1754
7.119.2.10	nppiSqrDistanceValid_Norm_8s32f_C1R	1755
7.119.2.11	nppiSqrDistanceValid_Norm_8s32f_C3R	1755
7.119.2.12	nppiSqrDistanceValid_Norm_8s32f_C4R	1756
7.119.2.13	nppiSqrDistanceValid_Norm_8u32f_AC4R	1756
7.119.2.14	nppiSqrDistanceValid_Norm_8u32f_C1R	1756
7.119.2.15	nppiSqrDistanceValid_Norm_8u32f_C3R	1757
7.119.2.16	nppiSqrDistanceValid_Norm_8u32f_C4R	1757
7.119.2.17	nppiSqrDistanceValid_Norm_8u_AC4RSfs	1758
7.119.2.18	nppiSqrDistanceValid_Norm_8u_C1RSfs	1758

7.119.2.19	nppiSqrDistanceValid_Norm_8u_C3RSfs	1759
7.119.2.20	nppiSqrDistanceValid_Norm_8u_C4RSfs	1759
7.120	CrossCorrFull_Norm	1760
7.120.1	Detailed Description	1761
7.120.2	Function Documentation	1762
7.120.2.1	nppiCrossCorrFull_Norm_16u32f_AC4R	1762
7.120.2.2	nppiCrossCorrFull_Norm_16u32f_C1R	1762
7.120.2.3	nppiCrossCorrFull_Norm_16u32f_C3R	1763
7.120.2.4	nppiCrossCorrFull_Norm_16u32f_C4R	1763
7.120.2.5	nppiCrossCorrFull_Norm_32f_AC4R	1763
7.120.2.6	nppiCrossCorrFull_Norm_32f_C1R	1764
7.120.2.7	nppiCrossCorrFull_Norm_32f_C3R	1764
7.120.2.8	nppiCrossCorrFull_Norm_32f_C4R	1765
7.120.2.9	nppiCrossCorrFull_Norm_8s32f_AC4R	1765
7.120.2.10	nppiCrossCorrFull_Norm_8s32f_C1R	1766
7.120.2.11	nppiCrossCorrFull_Norm_8s32f_C3R	1766
7.120.2.12	nppiCrossCorrFull_Norm_8s32f_C4R	1766
7.120.2.13	nppiCrossCorrFull_Norm_8u32f_AC4R	1767
7.120.2.14	nppiCrossCorrFull_Norm_8u32f_C1R	1767
7.120.2.15	nppiCrossCorrFull_Norm_8u32f_C3R	1768
7.120.2.16	nppiCrossCorrFull_Norm_8u32f_C4R	1768
7.120.2.17	nppiCrossCorrFull_Norm_8u_AC4RSfs	1769
7.120.2.18	nppiCrossCorrFull_Norm_8u_C1RSfs	1769
7.120.2.19	nppiCrossCorrFull_Norm_8u_C3RSfs	1770
7.120.2.20	nppiCrossCorrFull_Norm_8u_C4RSfs	1770
7.121	CrossCorrSame_Norm	1771
7.121.1	Detailed Description	1772
7.121.2	Function Documentation	1773
7.121.2.1	nppiCrossCorrSame_Norm_16u32f_AC4R	1773
7.121.2.2	nppiCrossCorrSame_Norm_16u32f_C1R	1773
7.121.2.3	nppiCrossCorrSame_Norm_16u32f_C3R	1774
7.121.2.4	nppiCrossCorrSame_Norm_16u32f_C4R	1774
7.121.2.5	nppiCrossCorrSame_Norm_32f_AC4R	1774
7.121.2.6	nppiCrossCorrSame_Norm_32f_C1R	1775
7.121.2.7	nppiCrossCorrSame_Norm_32f_C3R	1775
7.121.2.8	nppiCrossCorrSame_Norm_32f_C4R	1776

7.121.2.9	nppiCrossCorrSame_Norm_8s32f_AC4R	1776
7.121.2.10	nppiCrossCorrSame_Norm_8s32f_C1R	1777
7.121.2.11	nppiCrossCorrSame_Norm_8s32f_C3R	1777
7.121.2.12	nppiCrossCorrSame_Norm_8s32f_C4R	1777
7.121.2.13	nppiCrossCorrSame_Norm_8u32f_AC4R	1778
7.121.2.14	nppiCrossCorrSame_Norm_8u32f_C1R	1778
7.121.2.15	nppiCrossCorrSame_Norm_8u32f_C3R	1779
7.121.2.16	nppiCrossCorrSame_Norm_8u32f_C4R	1779
7.121.2.17	nppiCrossCorrSame_Norm_8u_AC4RSfs	1780
7.121.2.18	nppiCrossCorrSame_Norm_8u_C1RSfs	1780
7.121.2.19	nppiCrossCorrSame_Norm_8u_C3RSfs	1781
7.121.2.20	nppiCrossCorrSame_Norm_8u_C4RSfs	1781
7.122	CrossCorrValid_Norm	1782
7.122.1	Detailed Description	1783
7.122.2	Function Documentation	1784
7.122.2.1	nppiCrossCorrValid_Norm_16u32f_AC4R	1784
7.122.2.2	nppiCrossCorrValid_Norm_16u32f_C1R	1784
7.122.2.3	nppiCrossCorrValid_Norm_16u32f_C3R	1785
7.122.2.4	nppiCrossCorrValid_Norm_16u32f_C4R	1785
7.122.2.5	nppiCrossCorrValid_Norm_32f_AC4R	1785
7.122.2.6	nppiCrossCorrValid_Norm_32f_C1R	1786
7.122.2.7	nppiCrossCorrValid_Norm_32f_C3R	1786
7.122.2.8	nppiCrossCorrValid_Norm_32f_C4R	1787
7.122.2.9	nppiCrossCorrValid_Norm_8s32f_AC4R	1787
7.122.2.10	nppiCrossCorrValid_Norm_8s32f_C1R	1788
7.122.2.11	nppiCrossCorrValid_Norm_8s32f_C3R	1788
7.122.2.12	nppiCrossCorrValid_Norm_8s32f_C4R	1788
7.122.2.13	nppiCrossCorrValid_Norm_8u32f_AC4R	1789
7.122.2.14	nppiCrossCorrValid_Norm_8u32f_C1R	1789
7.122.2.15	nppiCrossCorrValid_Norm_8u32f_C3R	1790
7.122.2.16	nppiCrossCorrValid_Norm_8u32f_C4R	1790
7.122.2.17	nppiCrossCorrValid_Norm_8u_AC4RSfs	1791
7.122.2.18	nppiCrossCorrValid_Norm_8u_C1RSfs	1791
7.122.2.19	nppiCrossCorrValid_Norm_8u_C3RSfs	1792
7.122.2.20	nppiCrossCorrValid_Norm_8u_C4RSfs	1792
7.123	CrossCorrValid	1793

7.123.1 Detailed Description	1793
7.123.2 Function Documentation	1793
7.123.2.1 nppiCrossCorrValid_16u32f_C1R	1793
7.123.2.2 nppiCrossCorrValid_32f_C1R	1794
7.123.2.3 nppiCrossCorrValid_8s32f_C1R	1794
7.123.2.4 nppiCrossCorrValid_8u32f_C1R	1795
7.124 CrossCorrFull_NormLevel	1796
7.124.1 Detailed Description	1799
7.124.2 Function Documentation	1800
7.124.2.1 nppiCrossCorrFull_NormLevel_16u32f_AC4R	1800
7.124.2.2 nppiCrossCorrFull_NormLevel_16u32f_C1R	1800
7.124.2.3 nppiCrossCorrFull_NormLevel_16u32f_C3R	1801
7.124.2.4 nppiCrossCorrFull_NormLevel_16u32f_C4R	1801
7.124.2.5 nppiCrossCorrFull_NormLevel_32f_AC4R	1802
7.124.2.6 nppiCrossCorrFull_NormLevel_32f_C1R	1802
7.124.2.7 nppiCrossCorrFull_NormLevel_32f_C3R	1803
7.124.2.8 nppiCrossCorrFull_NormLevel_32f_C4R	1803
7.124.2.9 nppiCrossCorrFull_NormLevel_8s32f_AC4R	1804
7.124.2.10 nppiCrossCorrFull_NormLevel_8s32f_C1R	1804
7.124.2.11 nppiCrossCorrFull_NormLevel_8s32f_C3R	1805
7.124.2.12 nppiCrossCorrFull_NormLevel_8s32f_C4R	1805
7.124.2.13 nppiCrossCorrFull_NormLevel_8u32f_AC4R	1806
7.124.2.14 nppiCrossCorrFull_NormLevel_8u32f_C1R	1806
7.124.2.15 nppiCrossCorrFull_NormLevel_8u32f_C3R	1807
7.124.2.16 nppiCrossCorrFull_NormLevel_8u32f_C4R	1807
7.124.2.17 nppiCrossCorrFull_NormLevel_8u_AC4RSfs	1808
7.124.2.18 nppiCrossCorrFull_NormLevel_8u_C1RSfs	1808
7.124.2.19 nppiCrossCorrFull_NormLevel_8u_C3RSfs	1809
7.124.2.20 nppiCrossCorrFull_NormLevel_8u_C4RSfs	1809
7.124.2.21 nppiFullNormLevelGetBufferHostSize_16u32f_AC4R	1810
7.124.2.22 nppiFullNormLevelGetBufferHostSize_16u32f_C1R	1810
7.124.2.23 nppiFullNormLevelGetBufferHostSize_16u32f_C3R	1810
7.124.2.24 nppiFullNormLevelGetBufferHostSize_16u32f_C4R	1810
7.124.2.25 nppiFullNormLevelGetBufferHostSize_32f_AC4R	1811
7.124.2.26 nppiFullNormLevelGetBufferHostSize_32f_C1R	1811
7.124.2.27 nppiFullNormLevelGetBufferHostSize_32f_C3R	1811

7.124.2.28	nppiFullNormLevelGetBufferHostSize_32f_C4R	1812
7.124.2.29	nppiFullNormLevelGetBufferHostSize_8s32f_AC4R	1812
7.124.2.30	nppiFullNormLevelGetBufferHostSize_8s32f_C1R	1812
7.124.2.31	nppiFullNormLevelGetBufferHostSize_8s32f_C3R	1812
7.124.2.32	nppiFullNormLevelGetBufferHostSize_8s32f_C4R	1813
7.124.2.33	nppiFullNormLevelGetBufferHostSize_8u32f_AC4R	1813
7.124.2.34	nppiFullNormLevelGetBufferHostSize_8u32f_C1R	1813
7.124.2.35	nppiFullNormLevelGetBufferHostSize_8u32f_C3R	1814
7.124.2.36	nppiFullNormLevelGetBufferHostSize_8u32f_C4R	1814
7.124.2.37	nppiFullNormLevelGetBufferHostSize_8u_AC4RSfs	1814
7.124.2.38	nppiFullNormLevelGetBufferHostSize_8u_C1RSfs	1814
7.124.2.39	nppiFullNormLevelGetBufferHostSize_8u_C3RSfs	1815
7.124.2.40	nppiFullNormLevelGetBufferHostSize_8u_C4RSfs	1815
7.125	CrossCorrSame_NormLevel	1816
7.125.1	Detailed Description	1819
7.125.2	Function Documentation	1820
7.125.2.1	nppiCrossCorrSame_NormLevel_16u32f_AC4R	1820
7.125.2.2	nppiCrossCorrSame_NormLevel_16u32f_C1R	1820
7.125.2.3	nppiCrossCorrSame_NormLevel_16u32f_C3R	1821
7.125.2.4	nppiCrossCorrSame_NormLevel_16u32f_C4R	1821
7.125.2.5	nppiCrossCorrSame_NormLevel_32f_AC4R	1822
7.125.2.6	nppiCrossCorrSame_NormLevel_32f_C1R	1822
7.125.2.7	nppiCrossCorrSame_NormLevel_32f_C3R	1823
7.125.2.8	nppiCrossCorrSame_NormLevel_32f_C4R	1823
7.125.2.9	nppiCrossCorrSame_NormLevel_8s32f_AC4R	1824
7.125.2.10	nppiCrossCorrSame_NormLevel_8s32f_C1R	1824
7.125.2.11	nppiCrossCorrSame_NormLevel_8s32f_C3R	1825
7.125.2.12	nppiCrossCorrSame_NormLevel_8s32f_C4R	1825
7.125.2.13	nppiCrossCorrSame_NormLevel_8u32f_AC4R	1826
7.125.2.14	nppiCrossCorrSame_NormLevel_8u32f_C1R	1826
7.125.2.15	nppiCrossCorrSame_NormLevel_8u32f_C3R	1827
7.125.2.16	nppiCrossCorrSame_NormLevel_8u32f_C4R	1827
7.125.2.17	nppiCrossCorrSame_NormLevel_8u_AC4RSfs	1828
7.125.2.18	nppiCrossCorrSame_NormLevel_8u_C1RSfs	1828
7.125.2.19	nppiCrossCorrSame_NormLevel_8u_C3RSfs	1829
7.125.2.20	nppiCrossCorrSame_NormLevel_8u_C4RSfs	1829

7.125.2.2	nppiSameNormLevelGetBufferHostSize_16u32f_AC4R	1830
7.125.2.22	nppiSameNormLevelGetBufferHostSize_16u32f_C1R	1830
7.125.2.23	nppiSameNormLevelGetBufferHostSize_16u32f_C3R	1830
7.125.2.24	nppiSameNormLevelGetBufferHostSize_16u32f_C4R	1830
7.125.2.25	nppiSameNormLevelGetBufferHostSize_32f_AC4R	1831
7.125.2.26	nppiSameNormLevelGetBufferHostSize_32f_C1R	1831
7.125.2.27	nppiSameNormLevelGetBufferHostSize_32f_C3R	1831
7.125.2.28	nppiSameNormLevelGetBufferHostSize_32f_C4R	1832
7.125.2.29	nppiSameNormLevelGetBufferHostSize_8s32f_AC4R	1832
7.125.2.30	nppiSameNormLevelGetBufferHostSize_8s32f_C1R	1832
7.125.2.31	nppiSameNormLevelGetBufferHostSize_8s32f_C3R	1832
7.125.2.32	nppiSameNormLevelGetBufferHostSize_8s32f_C4R	1833
7.125.2.33	nppiSameNormLevelGetBufferHostSize_8u32f_AC4R	1833
7.125.2.34	nppiSameNormLevelGetBufferHostSize_8u32f_C1R	1833
7.125.2.35	nppiSameNormLevelGetBufferHostSize_8u32f_C3R	1834
7.125.2.36	nppiSameNormLevelGetBufferHostSize_8u32f_C4R	1834
7.125.2.37	nppiSameNormLevelGetBufferHostSize_8u_AC4RSfs	1834
7.125.2.38	nppiSameNormLevelGetBufferHostSize_8u_C1RSfs	1834
7.125.2.39	nppiSameNormLevelGetBufferHostSize_8u_C3RSfs	1835
7.125.2.40	nppiSameNormLevelGetBufferHostSize_8u_C4RSfs	1835
7.126	CrossCorrValid_NormLevel	1836
7.126.1	Detailed Description	1839
7.126.2	Function Documentation	1840
7.126.2.1	nppiCrossCorrValid_NormLevel_16u32f_AC4R	1840
7.126.2.2	nppiCrossCorrValid_NormLevel_16u32f_C1R	1840
7.126.2.3	nppiCrossCorrValid_NormLevel_16u32f_C3R	1841
7.126.2.4	nppiCrossCorrValid_NormLevel_16u32f_C4R	1841
7.126.2.5	nppiCrossCorrValid_NormLevel_32f_AC4R	1842
7.126.2.6	nppiCrossCorrValid_NormLevel_32f_C1R	1842
7.126.2.7	nppiCrossCorrValid_NormLevel_32f_C3R	1843
7.126.2.8	nppiCrossCorrValid_NormLevel_32f_C4R	1843
7.126.2.9	nppiCrossCorrValid_NormLevel_8s32f_AC4R	1844
7.126.2.10	nppiCrossCorrValid_NormLevel_8s32f_C1R	1844
7.126.2.11	nppiCrossCorrValid_NormLevel_8s32f_C3R	1845
7.126.2.12	nppiCrossCorrValid_NormLevel_8s32f_C4R	1845
7.126.2.13	nppiCrossCorrValid_NormLevel_8u32f_AC4R	1846

7.126.2.14	nppiCrossCorrValid_NormLevel_8u32f_C1R	1846
7.126.2.15	nppiCrossCorrValid_NormLevel_8u32f_C3R	1847
7.126.2.16	nppiCrossCorrValid_NormLevel_8u32f_C4R	1847
7.126.2.17	nppiCrossCorrValid_NormLevel_8u_AC4RSfs	1848
7.126.2.18	nppiCrossCorrValid_NormLevel_8u_C1RSfs	1848
7.126.2.19	nppiCrossCorrValid_NormLevel_8u_C3RSfs	1849
7.126.2.20	nppiCrossCorrValid_NormLevel_8u_C4RSfs	1849
7.126.2.21	nppiValidNormLevelGetBufferHostSize_16u32f_AC4R	1850
7.126.2.22	nppiValidNormLevelGetBufferHostSize_16u32f_C1R	1850
7.126.2.23	nppiValidNormLevelGetBufferHostSize_16u32f_C3R	1850
7.126.2.24	nppiValidNormLevelGetBufferHostSize_16u32f_C4R	1850
7.126.2.25	nppiValidNormLevelGetBufferHostSize_32f_AC4R	1851
7.126.2.26	nppiValidNormLevelGetBufferHostSize_32f_C1R	1851
7.126.2.27	nppiValidNormLevelGetBufferHostSize_32f_C3R	1851
7.126.2.28	nppiValidNormLevelGetBufferHostSize_32f_C4R	1852
7.126.2.29	nppiValidNormLevelGetBufferHostSize_8s32f_AC4R	1852
7.126.2.30	nppiValidNormLevelGetBufferHostSize_8s32f_C1R	1852
7.126.2.31	nppiValidNormLevelGetBufferHostSize_8s32f_C3R	1852
7.126.2.32	nppiValidNormLevelGetBufferHostSize_8s32f_C4R	1853
7.126.2.33	nppiValidNormLevelGetBufferHostSize_8u32f_AC4R	1853
7.126.2.34	nppiValidNormLevelGetBufferHostSize_8u32f_C1R	1853
7.126.2.35	nppiValidNormLevelGetBufferHostSize_8u32f_C3R	1854
7.126.2.36	nppiValidNormLevelGetBufferHostSize_8u32f_C4R	1854
7.126.2.37	nppiValidNormLevelGetBufferHostSize_8u_AC4RSfs	1854
7.126.2.38	nppiValidNormLevelGetBufferHostSize_8u_C1RSfs	1854
7.126.2.39	nppiValidNormLevelGetBufferHostSize_8u_C3RSfs	1855
7.126.2.40	nppiValidNormLevelGetBufferHostSize_8u_C4RSfs	1855
7.127	Image Quality Index	1856
7.127.1	Detailed Description	1858
7.127.2	Function Documentation	1858
7.127.2.1	nppiQualityIndex_16u32f_AC4R	1858
7.127.2.2	nppiQualityIndex_16u32f_C1R	1858
7.127.2.3	nppiQualityIndex_16u32f_C3R	1859
7.127.2.4	nppiQualityIndex_32f_AC4R	1859
7.127.2.5	nppiQualityIndex_32f_C1R	1860
7.127.2.6	nppiQualityIndex_32f_C3R	1860

7.127.2.7	nppiQualityIndex_8u32f_AC4R	1861
7.127.2.8	nppiQualityIndex_8u32f_C1R	1861
7.127.2.9	nppiQualityIndex_8u32f_C3R	1861
7.127.2.10	nppiQualityIndexGetBufferHostSize_16u32f_AC4R	1862
7.127.2.11	nppiQualityIndexGetBufferHostSize_16u32f_C1R	1862
7.127.2.12	nppiQualityIndexGetBufferHostSize_16u32f_C3R	1863
7.127.2.13	nppiQualityIndexGetBufferHostSize_32f_AC4R	1863
7.127.2.14	nppiQualityIndexGetBufferHostSize_32f_C1R	1863
7.127.2.15	nppiQualityIndexGetBufferHostSize_32f_C3R	1863
7.127.2.16	nppiQualityIndexGetBufferHostSize_8u32f_AC4R	1864
7.127.2.17	nppiQualityIndexGetBufferHostSize_8u32f_C1R	1864
7.127.2.18	nppiQualityIndexGetBufferHostSize_8u32f_C3R	1864
7.128	Memory Management	1865
7.128.1	Detailed Description	1867
7.128.2	Function Documentation	1867
7.128.2.1	nppiFree	1867
7.128.2.2	nppiMalloc_16s_C1	1867
7.128.2.3	nppiMalloc_16s_C2	1868
7.128.2.4	nppiMalloc_16s_C4	1868
7.128.2.5	nppiMalloc_16sc_C1	1868
7.128.2.6	nppiMalloc_16sc_C2	1868
7.128.2.7	nppiMalloc_16sc_C3	1869
7.128.2.8	nppiMalloc_16sc_C4	1869
7.128.2.9	nppiMalloc_16u_C1	1869
7.128.2.10	nppiMalloc_16u_C2	1870
7.128.2.11	nppiMalloc_16u_C3	1870
7.128.2.12	nppiMalloc_16u_C4	1870
7.128.2.13	nppiMalloc_32f_C1	1870
7.128.2.14	nppiMalloc_32f_C2	1871
7.128.2.15	nppiMalloc_32f_C3	1871
7.128.2.16	nppiMalloc_32f_C4	1871
7.128.2.17	nppiMalloc_32fc_C1	1872
7.128.2.18	nppiMalloc_32fc_C2	1872
7.128.2.19	nppiMalloc_32fc_C3	1872
7.128.2.20	nppiMalloc_32fc_C4	1872
7.128.2.21	nppiMalloc_32s_C1	1873

7.128.2.22	ippiMalloc_32s_C3	1873
7.128.2.23	ippiMalloc_32s_C4	1873
7.128.2.24	ippiMalloc_32sc_C1	1874
7.128.2.25	ippiMalloc_32sc_C2	1874
7.128.2.26	ippiMalloc_32sc_C3	1874
7.128.2.27	ippiMalloc_32sc_C4	1874
7.128.2.28	ippiMalloc_8u_C1	1875
7.128.2.29	ippiMalloc_8u_C2	1875
7.128.2.30	ippiMalloc_8u_C3	1875
7.128.2.31	ippiMalloc_8u_C4	1876
7.129	Threshold and Compare Operations	1877
7.129.1	Detailed Description	1877
7.130	Threshold Operations	1878
7.130.1	Detailed Description	1892
7.130.2	Function Documentation	1892
7.130.2.1	ippiThreshold_16s_AC4IR	1892
7.130.2.2	ippiThreshold_16s_AC4R	1892
7.130.2.3	ippiThreshold_16s_C1IR	1893
7.130.2.4	ippiThreshold_16s_C1R	1893
7.130.2.5	ippiThreshold_16s_C3IR	1894
7.130.2.6	ippiThreshold_16s_C3R	1894
7.130.2.7	ippiThreshold_16u_AC4IR	1895
7.130.2.8	ippiThreshold_16u_AC4R	1895
7.130.2.9	ippiThreshold_16u_C1IR	1896
7.130.2.10	ippiThreshold_16u_C1R	1896
7.130.2.11	ippiThreshold_16u_C3IR	1896
7.130.2.12	ippiThreshold_16u_C3R	1897
7.130.2.13	ippiThreshold_32f_AC4IR	1897
7.130.2.14	ippiThreshold_32f_AC4R	1898
7.130.2.15	ippiThreshold_32f_C1IR	1898
7.130.2.16	ippiThreshold_32f_C1R	1899
7.130.2.17	ippiThreshold_32f_C3IR	1899
7.130.2.18	ippiThreshold_32f_C3R	1900
7.130.2.19	ippiThreshold_8u_AC4IR	1900
7.130.2.20	ippiThreshold_8u_AC4R	1901
7.130.2.21	ippiThreshold_8u_C1IR	1901

7.130.2.22	nppiThreshold_8u_C1R	1902
7.130.2.23	nppiThreshold_8u_C3IR	1902
7.130.2.24	nppiThreshold_8u_C3R	1903
7.130.2.25	nppiThreshold_GT_16s_AC4IR	1903
7.130.2.26	nppiThreshold_GT_16s_AC4R	1903
7.130.2.27	nppiThreshold_GT_16s_C1IR	1904
7.130.2.28	nppiThreshold_GT_16s_C1R	1904
7.130.2.29	nppiThreshold_GT_16s_C3IR	1905
7.130.2.30	nppiThreshold_GT_16s_C3R	1905
7.130.2.31	nppiThreshold_GT_16u_AC4IR	1905
7.130.2.32	nppiThreshold_GT_16u_AC4R	1906
7.130.2.33	nppiThreshold_GT_16u_C1IR	1906
7.130.2.34	nppiThreshold_GT_16u_C1R	1907
7.130.2.35	nppiThreshold_GT_16u_C3IR	1907
7.130.2.36	nppiThreshold_GT_16u_C3R	1907
7.130.2.37	nppiThreshold_GT_32f_AC4IR	1908
7.130.2.38	nppiThreshold_GT_32f_AC4R	1908
7.130.2.39	nppiThreshold_GT_32f_C1IR	1909
7.130.2.40	nppiThreshold_GT_32f_C1R	1909
7.130.2.41	nppiThreshold_GT_32f_C3IR	1909
7.130.2.42	nppiThreshold_GT_32f_C3R	1910
7.130.2.43	nppiThreshold_GT_8u_AC4IR	1910
7.130.2.44	nppiThreshold_GT_8u_AC4R	1911
7.130.2.45	nppiThreshold_GT_8u_C1IR	1911
7.130.2.46	nppiThreshold_GT_8u_C1R	1911
7.130.2.47	nppiThreshold_GT_8u_C3IR	1912
7.130.2.48	nppiThreshold_GT_8u_C3R	1912
7.130.2.49	nppiThreshold_GTVVal_16s_AC4IR	1913
7.130.2.50	nppiThreshold_GTVVal_16s_AC4R	1913
7.130.2.51	nppiThreshold_GTVVal_16s_C1IR	1913
7.130.2.52	nppiThreshold_GTVVal_16s_C1R	1914
7.130.2.53	nppiThreshold_GTVVal_16s_C3IR	1914
7.130.2.54	nppiThreshold_GTVVal_16s_C3R	1915
7.130.2.55	nppiThreshold_GTVVal_16u_AC4IR	1915
7.130.2.56	nppiThreshold_GTVVal_16u_AC4R	1915
7.130.2.57	nppiThreshold_GTVVal_16u_C1IR	1916

7.130.2.58	nppiThreshold_GTVal_16u_C1R	1916
7.130.2.59	nppiThreshold_GTVal_16u_C3IR	1917
7.130.2.60	nppiThreshold_GTVal_16u_C3R	1917
7.130.2.61	nppiThreshold_GTVal_32f_AC4IR	1918
7.130.2.62	nppiThreshold_GTVal_32f_AC4R	1918
7.130.2.63	nppiThreshold_GTVal_32f_C1IR	1918
7.130.2.64	nppiThreshold_GTVal_32f_C1R	1919
7.130.2.65	nppiThreshold_GTVal_32f_C3IR	1919
7.130.2.66	nppiThreshold_GTVal_32f_C3R	1920
7.130.2.67	nppiThreshold_GTVal_8u_AC4IR	1920
7.130.2.68	nppiThreshold_GTVal_8u_AC4R	1920
7.130.2.69	nppiThreshold_GTVal_8u_C1IR	1921
7.130.2.70	nppiThreshold_GTVal_8u_C1R	1921
7.130.2.71	nppiThreshold_GTVal_8u_C3IR	1922
7.130.2.72	nppiThreshold_GTVal_8u_C3R	1922
7.130.2.73	nppiThreshold_LT_16s_AC4IR	1923
7.130.2.74	nppiThreshold_LT_16s_AC4R	1923
7.130.2.75	nppiThreshold_LT_16s_C1IR	1923
7.130.2.76	nppiThreshold_LT_16s_C1R	1924
7.130.2.77	nppiThreshold_LT_16s_C3IR	1924
7.130.2.78	nppiThreshold_LT_16s_C3R	1925
7.130.2.79	nppiThreshold_LT_16u_AC4IR	1925
7.130.2.80	nppiThreshold_LT_16u_AC4R	1925
7.130.2.81	nppiThreshold_LT_16u_C1IR	1926
7.130.2.82	nppiThreshold_LT_16u_C1R	1926
7.130.2.83	nppiThreshold_LT_16u_C3IR	1927
7.130.2.84	nppiThreshold_LT_16u_C3R	1927
7.130.2.85	nppiThreshold_LT_32f_AC4IR	1927
7.130.2.86	nppiThreshold_LT_32f_AC4R	1928
7.130.2.87	nppiThreshold_LT_32f_C1IR	1928
7.130.2.88	nppiThreshold_LT_32f_C1R	1929
7.130.2.89	nppiThreshold_LT_32f_C3IR	1929
7.130.2.90	nppiThreshold_LT_32f_C3R	1929
7.130.2.91	nppiThreshold_LT_8u_AC4IR	1930
7.130.2.92	nppiThreshold_LT_8u_AC4R	1930
7.130.2.93	nppiThreshold_LT_8u_C1IR	1931

7.130.2.94	nppiThreshold_LT_8u_C1R	1931
7.130.2.95	nppiThreshold_LT_8u_C3IR	1931
7.130.2.96	nppiThreshold_LT_8u_C3R	1932
7.130.2.97	nppiThreshold_LTV_16s_AC4IR	1932
7.130.2.98	nppiThreshold_LTV_16s_AC4R	1933
7.130.2.99	nppiThreshold_LTV_16s_C1IR	1933
7.130.2.100	nppiThreshold_LTV_16s_C1R	1933
7.130.2.101	nppiThreshold_LTV_16s_C3IR	1934
7.130.2.102	nppiThreshold_LTV_16s_C3R	1934
7.130.2.103	nppiThreshold_LTV_16u_AC4IR	1935
7.130.2.104	nppiThreshold_LTV_16u_AC4R	1935
7.130.2.105	nppiThreshold_LTV_16u_C1IR	1936
7.130.2.106	nppiThreshold_LTV_16u_C1R	1936
7.130.2.107	nppiThreshold_LTV_16u_C3IR	1936
7.130.2.108	nppiThreshold_LTV_16u_C3R	1937
7.130.2.109	nppiThreshold_LTV_32f_AC4IR	1937
7.130.2.110	nppiThreshold_LTV_32f_AC4R	1938
7.130.2.111	nppiThreshold_LTV_32f_C1IR	1938
7.130.2.112	nppiThreshold_LTV_32f_C1R	1938
7.130.2.113	nppiThreshold_LTV_32f_C3IR	1939
7.130.2.114	nppiThreshold_LTV_32f_C3R	1939
7.130.2.115	nppiThreshold_LTV_8u_AC4IR	1940
7.130.2.116	nppiThreshold_LTV_8u_AC4R	1940
7.130.2.117	nppiThreshold_LTV_8u_C1IR	1941
7.130.2.118	nppiThreshold_LTV_8u_C1R	1941
7.130.2.119	nppiThreshold_LTV_8u_C3IR	1941
7.130.2.120	nppiThreshold_LTV_8u_C3R	1942
7.130.2.121	nppiThreshold_LTV_GTV_16s_AC4IR	1942
7.130.2.122	nppiThreshold_LTV_GTV_16s_AC4R	1943
7.130.2.123	nppiThreshold_LTV_GTV_16s_C1IR	1943
7.130.2.124	nppiThreshold_LTV_GTV_16s_C1R	1944
7.130.2.125	nppiThreshold_LTV_GTV_16s_C3IR	1944
7.130.2.126	nppiThreshold_LTV_GTV_16s_C3R	1945
7.130.2.127	nppiThreshold_LTV_GTV_16u_AC4IR	1945
7.130.2.128	nppiThreshold_LTV_GTV_16u_AC4R	1946
7.130.2.129	nppiThreshold_LTV_GTV_16u_C1IR	1946

7.130.2.130	ppiThreshold_LTVaGTVal_16u_C1R	1947
7.130.2.131	ppiThreshold_LTVaGTVal_16u_C3IR	1947
7.130.2.132	ppiThreshold_LTVaGTVal_16u_C3R	1948
7.130.2.133	ppiThreshold_LTVaGTVal_32f_AC4IR	1948
7.130.2.134	ppiThreshold_LTVaGTVal_32f_AC4R	1949
7.130.2.135	ppiThreshold_LTVaGTVal_32f_C1IR	1949
7.130.2.136	ppiThreshold_LTVaGTVal_32f_C1R	1950
7.130.2.137	ppiThreshold_LTVaGTVal_32f_C3IR	1950
7.130.2.138	ppiThreshold_LTVaGTVal_32f_C3R	1951
7.130.2.139	ppiThreshold_LTVaGTVal_8u_AC4IR	1951
7.130.2.140	ppiThreshold_LTVaGTVal_8u_AC4R	1952
7.130.2.141	ppiThreshold_LTVaGTVal_8u_C1IR	1952
7.130.2.142	ppiThreshold_LTVaGTVal_8u_C1R	1953
7.130.2.143	ppiThreshold_LTVaGTVal_8u_C3IR	1953
7.130.2.144	ppiThreshold_LTVaGTVal_8u_C3R	1954
7.130.2.145	ppiThreshold_Val_16s_AC4IR	1954
7.130.2.146	ppiThreshold_Val_16s_AC4R	1955
7.130.2.147	ppiThreshold_Val_16s_C1IR	1955
7.130.2.148	ppiThreshold_Val_16s_C1R	1956
7.130.2.149	ppiThreshold_Val_16s_C3IR	1956
7.130.2.150	ppiThreshold_Val_16s_C3R	1957
7.130.2.151	ppiThreshold_Val_16u_AC4IR	1957
7.130.2.152	ppiThreshold_Val_16u_AC4R	1958
7.130.2.153	ppiThreshold_Val_16u_C1IR	1958
7.130.2.154	ppiThreshold_Val_16u_C1R	1959
7.130.2.155	ppiThreshold_Val_16u_C3IR	1959
7.130.2.156	ppiThreshold_Val_16u_C3R	1960
7.130.2.157	ppiThreshold_Val_32f_AC4IR	1960
7.130.2.158	ppiThreshold_Val_32f_AC4R	1961
7.130.2.159	ppiThreshold_Val_32f_C1IR	1961
7.130.2.160	ppiThreshold_Val_32f_C1R	1962
7.130.2.161	ppiThreshold_Val_32f_C3IR	1962
7.130.2.162	ppiThreshold_Val_32f_C3R	1963
7.130.2.163	ppiThreshold_Val_8u_AC4IR	1963
7.130.2.164	ppiThreshold_Val_8u_AC4R	1964
7.130.2.165	ppiThreshold_Val_8u_C1IR	1964

7.130.2.16	nppiThreshold_Val_8u_C1R	1965
7.130.2.17	nppiThreshold_Val_8u_C3IR	1965
7.130.2.18	nppiThreshold_Val_8u_C3R	1966
7.131	Compare Operations	1967
7.131.1	Detailed Description	1970
7.131.2	Function Documentation	1970
7.131.2.1	nppiCompare_16s_AC4R	1970
7.131.2.2	nppiCompare_16s_C1R	1971
7.131.2.3	nppiCompare_16s_C3R	1971
7.131.2.4	nppiCompare_16s_C4R	1972
7.131.2.5	nppiCompare_16u_AC4R	1972
7.131.2.6	nppiCompare_16u_C1R	1973
7.131.2.7	nppiCompare_16u_C3R	1973
7.131.2.8	nppiCompare_16u_C4R	1974
7.131.2.9	nppiCompare_32f_AC4R	1974
7.131.2.10	nppiCompare_32f_C1R	1975
7.131.2.11	nppiCompare_32f_C3R	1975
7.131.2.12	nppiCompare_32f_C4R	1976
7.131.2.13	nppiCompare_8u_AC4R	1976
7.131.2.14	nppiCompare_8u_C1R	1977
7.131.2.15	nppiCompare_8u_C3R	1977
7.131.2.16	nppiCompare_8u_C4R	1978
7.131.2.17	nppiCompareC_16s_AC4R	1978
7.131.2.18	nppiCompareC_16s_C1R	1978
7.131.2.19	nppiCompareC_16s_C3R	1979
7.131.2.20	nppiCompareC_16s_C4R	1979
7.131.2.21	nppiCompareC_16u_AC4R	1980
7.131.2.22	nppiCompareC_16u_C1R	1980
7.131.2.23	nppiCompareC_16u_C3R	1981
7.131.2.24	nppiCompareC_16u_C4R	1981
7.131.2.25	nppiCompareC_32f_AC4R	1981
7.131.2.26	nppiCompareC_32f_C1R	1982
7.131.2.27	nppiCompareC_32f_C3R	1982
7.131.2.28	nppiCompareC_32f_C4R	1983
7.131.2.29	nppiCompareC_8u_AC4R	1983
7.131.2.30	nppiCompareC_8u_C1R	1984

7.131.2.3	<code>ippiCompareC_8u_C3R</code>	1984
7.131.2.32	<code>ippiCompareC_8u_C4R</code>	1984
7.131.2.33	<code>ippiCompareEqualEps_32f_AC4R</code>	1985
7.131.2.34	<code>ippiCompareEqualEps_32f_C1R</code>	1985
7.131.2.35	<code>ippiCompareEqualEps_32f_C3R</code>	1986
7.131.2.36	<code>ippiCompareEqualEps_32f_C4R</code>	1986
7.131.2.37	<code>ippiCompareEqualEpsC_32f_AC4R</code>	1987
7.131.2.38	<code>ippiCompareEqualEpsC_32f_C1R</code>	1987
7.131.2.39	<code>ippiCompareEqualEpsC_32f_C3R</code>	1988
7.131.2.40	<code>ippiCompareEqualEpsC_32f_C4R</code>	1988
7.132	NPP Signal Processing	1990
7.133	Arithmetic and Logical Operations	1991
7.134	Arithmetic Operations	1992
7.135	AddC	1994
7.135.1	Detailed Description	1995
7.135.2	Function Documentation	1995
7.135.2.1	<code>nppsAddC_16s_ISfs</code>	1995
7.135.2.2	<code>nppsAddC_16s_Sfs</code>	1996
7.135.2.3	<code>nppsAddC_16sc_ISfs</code>	1996
7.135.2.4	<code>nppsAddC_16sc_Sfs</code>	1996
7.135.2.5	<code>nppsAddC_16u_ISfs</code>	1997
7.135.2.6	<code>nppsAddC_16u_Sfs</code>	1997
7.135.2.7	<code>nppsAddC_32f</code>	1997
7.135.2.8	<code>nppsAddC_32f_I</code>	1998
7.135.2.9	<code>nppsAddC_32fc</code>	1998
7.135.2.10	<code>nppsAddC_32fc_I</code>	1998
7.135.2.11	<code>ippiAddC_32s_ISfs</code>	1998
7.135.2.12	<code>ippiAddC_32s_Sfs</code>	1999
7.135.2.13	<code>ippiAddC_32sc_ISfs</code>	1999
7.135.2.14	<code>ippiAddC_32sc_Sfs</code>	2000
7.135.2.15	<code>ippiAddC_64f</code>	2000
7.135.2.16	<code>ippiAddC_64f_I</code>	2000
7.135.2.17	<code>ippiAddC_64fc</code>	2001
7.135.2.18	<code>ippiAddC_64fc_I</code>	2001
7.135.2.19	<code>ippiAddC_8u_ISfs</code>	2001
7.135.2.20	<code>ippiAddC_8u_Sfs</code>	2002

7.136AddProductC	2003
7.136.1 Detailed Description	2003
7.136.2 Function Documentation	2003
7.136.2.1 nppsAddProductC_32f	2003
7.137MulC	2004
7.137.1 Detailed Description	2005
7.137.2 Function Documentation	2005
7.137.2.1 nppsMulC_16s_ISfs	2005
7.137.2.2 nppsMulC_16s_Sfs	2006
7.137.2.3 nppsMulC_16sc_ISfs	2006
7.137.2.4 nppsMulC_16sc_Sfs	2007
7.137.2.5 nppsMulC_16u_ISfs	2007
7.137.2.6 nppsMulC_16u_Sfs	2007
7.137.2.7 nppsMulC_32f	2008
7.137.2.8 nppsMulC_32f16s_Sfs	2008
7.137.2.9 nppsMulC_32f_I	2008
7.137.2.10nppsMulC_32fc	2009
7.137.2.11nppsMulC_32fc_I	2009
7.137.2.12nppsMulC_32s_ISfs	2009
7.137.2.13nppsMulC_32s_Sfs	2010
7.137.2.14nppsMulC_32sc_ISfs	2010
7.137.2.15nppsMulC_32sc_Sfs	2010
7.137.2.16nppsMulC_64f	2011
7.137.2.17nppsMulC_64f64s_ISfs	2011
7.137.2.18nppsMulC_64f_I	2011
7.137.2.19nppsMulC_64fc	2012
7.137.2.20nppsMulC_64fc_I	2012
7.137.2.21nppsMulC_8u_ISfs	2012
7.137.2.22nppsMulC_8u_Sfs	2013
7.137.2.23nppsMulC_Low_32f16s	2013
7.138SubC	2014
7.138.1 Detailed Description	2015
7.138.2 Function Documentation	2015
7.138.2.1 nppsSubC_16s_ISfs	2015
7.138.2.2 nppsSubC_16s_Sfs	2016
7.138.2.3 nppsSubC_16sc_ISfs	2016

7.138.2.4	nppsSubC_16sc_Sfs	2016
7.138.2.5	nppsSubC_16u_ISfs	2017
7.138.2.6	nppsSubC_16u_Sfs	2017
7.138.2.7	nppsSubC_32f	2017
7.138.2.8	nppsSubC_32f_I	2018
7.138.2.9	nppsSubC_32fc	2018
7.138.2.10	nppsSubC_32fc_I	2018
7.138.2.11	nppsSubC_32s_ISfs	2018
7.138.2.12	nppsSubC_32s_Sfs	2019
7.138.2.13	nppsSubC_32sc_ISfs	2019
7.138.2.14	nppsSubC_32sc_Sfs	2020
7.138.2.15	nppsSubC_64f	2020
7.138.2.16	nppsSubC_64f_I	2020
7.138.2.17	nppsSubC_64fc	2021
7.138.2.18	nppsSubC_64fc_I	2021
7.138.2.19	nppsSubC_8u_ISfs	2021
7.138.2.20	nppsSubC_8u_Sfs	2022
7.139	SubCRev	2023
7.139.1	Detailed Description	2024
7.139.2	Function Documentation	2024
7.139.2.1	nppsSubCRev_16s_ISfs	2024
7.139.2.2	nppsSubCRev_16s_Sfs	2025
7.139.2.3	nppsSubCRev_16sc_ISfs	2025
7.139.2.4	nppsSubCRev_16sc_Sfs	2025
7.139.2.5	nppsSubCRev_16u_ISfs	2026
7.139.2.6	nppsSubCRev_16u_Sfs	2026
7.139.2.7	nppsSubCRev_32f	2026
7.139.2.8	nppsSubCRev_32f_I	2027
7.139.2.9	nppsSubCRev_32fc	2027
7.139.2.10	nppsSubCRev_32fc_I	2027
7.139.2.11	nppsSubCRev_32s_ISfs	2028
7.139.2.12	nppsSubCRev_32s_Sfs	2028
7.139.2.13	nppsSubCRev_32sc_ISfs	2028
7.139.2.14	nppsSubCRev_32sc_Sfs	2029
7.139.2.15	nppsSubCRev_64f	2029
7.139.2.16	nppsSubCRev_64f_I	2029

7.139.2.17	nppsSubCRev_64fc	2030
7.139.2.18	nppsSubCRev_64fc_I	2030
7.139.2.19	nppsSubCRev_8u_ISfs	2030
7.139.2.20	nppsSubCRev_8u_Sfs	2031
7.140	DivC	2032
7.140.1	Detailed Description	2033
7.140.2	Function Documentation	2033
7.140.2.1	nppsDivC_16s_ISfs	2033
7.140.2.2	nppsDivC_16s_Sfs	2033
7.140.2.3	nppsDivC_16sc_ISfs	2034
7.140.2.4	nppsDivC_16sc_Sfs	2034
7.140.2.5	nppsDivC_16u_ISfs	2034
7.140.2.6	nppsDivC_16u_Sfs	2035
7.140.2.7	nppsDivC_32f	2035
7.140.2.8	nppsDivC_32f_I	2035
7.140.2.9	nppsDivC_32fc	2036
7.140.2.10	nppsDivC_32fc_I	2036
7.140.2.11	nppsDivC_64f	2036
7.140.2.12	nppsDivC_64f_I	2037
7.140.2.13	nppsDivC_64fc	2037
7.140.2.14	nppsDivC_64fc_I	2037
7.140.2.15	nppsDivC_8u_ISfs	2037
7.140.2.16	nppsDivC_8u_Sfs	2038
7.141	DivCRev	2039
7.141.1	Detailed Description	2039
7.141.2	Function Documentation	2039
7.141.2.1	nppsDivCRev_16u	2039
7.141.2.2	nppsDivCRev_16u_I	2039
7.141.2.3	nppsDivCRev_32f	2040
7.141.2.4	nppsDivCRev_32f_I	2040
7.142	Add	2041
7.142.1	Detailed Description	2043
7.142.2	Function Documentation	2043
7.142.2.1	nppsAdd_16s	2043
7.142.2.2	nppsAdd_16s32f	2043
7.142.2.3	nppsAdd_16s32s_I	2044

7.142.2.4	nppsAdd_16s_I	2044
7.142.2.5	nppsAdd_16s_ISfs	2044
7.142.2.6	nppsAdd_16s_Sfs	2045
7.142.2.7	nppsAdd_16sc_ISfs	2045
7.142.2.8	nppsAdd_16sc_Sfs	2045
7.142.2.9	nppsAdd_16u	2046
7.142.2.10	nppsAdd_16u_ISfs	2046
7.142.2.11	nppsAdd_16u_Sfs	2046
7.142.2.12	nppsAdd_32f	2047
7.142.2.13	nppsAdd_32f_I	2047
7.142.2.14	nppsAdd_32fc	2047
7.142.2.15	nppsAdd_32fc_I	2048
7.142.2.16	nppsAdd_32s_ISfs	2048
7.142.2.17	nppsAdd_32s_Sfs	2048
7.142.2.18	nppsAdd_32sc_ISfs	2049
7.142.2.19	nppsAdd_32sc_Sfs	2049
7.142.2.20	nppsAdd_32u	2049
7.142.2.21	nppsAdd_64f	2050
7.142.2.22	nppsAdd_64f_I	2050
7.142.2.23	nppsAdd_64fc	2050
7.142.2.24	nppsAdd_64fc_I	2051
7.142.2.25	nppsAdd_64s_Sfs	2051
7.142.2.26	nppsAdd_8u16u	2051
7.142.2.27	nppsAdd_8u_ISfs	2052
7.142.2.28	nppsAdd_8u_Sfs	2052
7.143	AddProduct	2053
7.143.1	Detailed Description	2053
7.143.2	Function Documentation	2054
7.143.2.1	nppsAddProduct_16s32s_Sfs	2054
7.143.2.2	nppsAddProduct_16s_Sfs	2054
7.143.2.3	nppsAddProduct_32f	2054
7.143.2.4	nppsAddProduct_32fc	2055
7.143.2.5	nppsAddProduct_32s_Sfs	2055
7.143.2.6	nppsAddProduct_64f	2056
7.143.2.7	nppsAddProduct_64fc	2056
7.144	Mul	2057

7.144.1 Detailed Description	2059
7.144.2 Function Documentation	2059
7.144.2.1 nppsMul_16s	2059
7.144.2.2 nppsMul_16s32f	2060
7.144.2.3 nppsMul_16s32s_Sfs	2060
7.144.2.4 nppsMul_16s_I	2060
7.144.2.5 nppsMul_16s_ISfs	2061
7.144.2.6 nppsMul_16s_Sfs	2061
7.144.2.7 nppsMul_16sc_ISfs	2061
7.144.2.8 nppsMul_16sc_Sfs	2062
7.144.2.9 nppsMul_16u16s_Sfs	2062
7.144.2.10 nppsMul_16u_ISfs	2062
7.144.2.11 nppsMul_16u_Sfs	2063
7.144.2.12 nppsMul_32f	2063
7.144.2.13 nppsMul_32f32fc	2063
7.144.2.14 nppsMul_32f32fc_I	2064
7.144.2.15 nppsMul_32f_I	2064
7.144.2.16 nppsMul_32fc	2064
7.144.2.17 nppsMul_32fc_I	2065
7.144.2.18 nppsMul_32s32sc_ISfs	2065
7.144.2.19 nppsMul_32s32sc_Sfs	2065
7.144.2.20 nppsMul_32s_ISfs	2066
7.144.2.21 nppsMul_32s_Sfs	2066
7.144.2.22 nppsMul_32sc_ISfs	2066
7.144.2.23 nppsMul_32sc_Sfs	2067
7.144.2.24 nppsMul_64f	2067
7.144.2.25 nppsMul_64f_I	2067
7.144.2.26 nppsMul_64fc	2068
7.144.2.27 nppsMul_64fc_I	2068
7.144.2.28 nppsMul_8u16u	2068
7.144.2.29 nppsMul_8u_ISfs	2069
7.144.2.30 nppsMul_8u_Sfs	2069
7.144.2.31 nppsMul_Low_32s_Sfs	2069
7.145 Sub	2070
7.145.1 Detailed Description	2071
7.145.2 Function Documentation	2071

7.145.2.1	nppsSub_16s	2071
7.145.2.2	nppsSub_16s32f	2072
7.145.2.3	nppsSub_16s_I	2072
7.145.2.4	nppsSub_16s_ISfs	2072
7.145.2.5	nppsSub_16s_Sfs	2073
7.145.2.6	nppsSub_16sc_ISfs	2073
7.145.2.7	nppsSub_16sc_Sfs	2073
7.145.2.8	nppsSub_16u_ISfs	2074
7.145.2.9	nppsSub_16u_Sfs	2074
7.145.2.10	nppsSub_32f	2074
7.145.2.11	nppsSub_32f_I	2075
7.145.2.12	nppsSub_32fc	2075
7.145.2.13	nppsSub_32fc_I	2075
7.145.2.14	nppsSub_32s_ISfs	2076
7.145.2.15	nppsSub_32s_Sfs	2076
7.145.2.16	nppsSub_32sc_ISfs	2076
7.145.2.17	nppsSub_32sc_Sfs	2077
7.145.2.18	nppsSub_64f	2077
7.145.2.19	nppsSub_64f_I	2077
7.145.2.20	nppsSub_64fc	2078
7.145.2.21	nppsSub_64fc_I	2078
7.145.2.22	nppsSub_8u_ISfs	2078
7.145.2.23	nppsSub_8u_Sfs	2079
7.146	Div	2080
7.146.1	Detailed Description	2081
7.146.2	Function Documentation	2081
7.146.2.1	nppsDiv_16s_ISfs	2081
7.146.2.2	nppsDiv_16s_Sfs	2082
7.146.2.3	nppsDiv_16sc_ISfs	2082
7.146.2.4	nppsDiv_16sc_Sfs	2082
7.146.2.5	nppsDiv_16u_ISfs	2083
7.146.2.6	nppsDiv_16u_Sfs	2083
7.146.2.7	nppsDiv_32f	2083
7.146.2.8	nppsDiv_32f_I	2084
7.146.2.9	nppsDiv_32fc	2084
7.146.2.10	nppsDiv_32fc_I	2084

7.146.2.1	nppsDiv_32s16s_Sfs	2084
7.146.2.2	nppsDiv_32s_ISfs	2085
7.146.2.3	nppsDiv_32s_Sfs	2085
7.146.2.4	nppsDiv_64f	2086
7.146.2.5	nppsDiv_64f_I	2086
7.146.2.6	nppsDiv_64fc	2086
7.146.2.7	nppsDiv_64fc_I	2087
7.146.2.8	nppsDiv_8u_ISfs	2087
7.146.2.9	nppsDiv_8u_Sfs	2087
7.147	Div_Round	2088
7.147.1	Detailed Description	2088
7.147.2	Function Documentation	2088
7.147.2.1	nppsDiv_Round_16s_ISfs	2088
7.147.2.2	nppsDiv_Round_16s_Sfs	2089
7.147.2.3	nppsDiv_Round_16u_ISfs	2089
7.147.2.4	nppsDiv_Round_16u_Sfs	2089
7.147.2.5	nppsDiv_Round_8u_ISfs	2090
7.147.2.6	nppsDiv_Round_8u_Sfs	2090
7.148	Abs	2091
7.148.1	Detailed Description	2091
7.148.2	Function Documentation	2091
7.148.2.1	nppsAbs_16s	2091
7.148.2.2	nppsAbs_16s_I	2092
7.148.2.3	nppsAbs_32f	2092
7.148.2.4	nppsAbs_32f_I	2092
7.148.2.5	nppsAbs_32s	2092
7.148.2.6	nppsAbs_32s_I	2093
7.148.2.7	nppsAbs_64f	2093
7.148.2.8	nppsAbs_64f_I	2093
7.149	Sqr	2094
7.149.1	Detailed Description	2095
7.149.2	Function Documentation	2095
7.149.2.1	nppsSqr_16s_ISfs	2095
7.149.2.2	nppsSqr_16s_Sfs	2095
7.149.2.3	nppsSqr_16sc_ISfs	2095
7.149.2.4	nppsSqr_16sc_Sfs	2096

7.149.2.5	nppsSqr_16u_ISfs	2096
7.149.2.6	nppsSqr_16u_Sfs	2096
7.149.2.7	nppsSqr_32f	2097
7.149.2.8	nppsSqr_32f_I	2097
7.149.2.9	nppsSqr_32fc	2097
7.149.2.10	nppsSqr_32fc_I	2097
7.149.2.11	nppsSqr_64f	2098
7.149.2.12	nppsSqr_64f_I	2098
7.149.2.13	nppsSqr_64fc	2098
7.149.2.14	nppsSqr_64fc_I	2098
7.149.2.15	nppsSqr_8u_ISfs	2099
7.149.2.16	nppsSqr_8u_Sfs	2099
7.150	Sqrt	2100
7.150.1	Detailed Description	2101
7.150.2	Function Documentation	2101
7.150.2.1	nppsSqrt_16s_ISfs	2101
7.150.2.2	nppsSqrt_16s_Sfs	2101
7.150.2.3	nppsSqrt_16sc_ISfs	2102
7.150.2.4	nppsSqrt_16sc_Sfs	2102
7.150.2.5	nppsSqrt_16u_ISfs	2102
7.150.2.6	nppsSqrt_16u_Sfs	2103
7.150.2.7	nppsSqrt_32f	2103
7.150.2.8	nppsSqrt_32f_I	2103
7.150.2.9	nppsSqrt_32fc	2103
7.150.2.10	nppsSqrt_32fc_I	2104
7.150.2.11	nppsSqrt_32s16s_Sfs	2104
7.150.2.12	nppsSqrt_64f	2104
7.150.2.13	nppsSqrt_64f_I	2105
7.150.2.14	nppsSqrt_64fc	2105
7.150.2.15	nppsSqrt_64fc_I	2105
7.150.2.16	nppsSqrt_64s16s_Sfs	2105
7.150.2.17	nppsSqrt_64s_ISfs	2106
7.150.2.18	nppsSqrt_64s_Sfs	2106
7.150.2.19	nppsSqrt_8u_ISfs	2106
7.150.2.20	nppsSqrt_8u_Sfs	2106
7.151	Cubrt	2108

7.151.1 Detailed Description	2108
7.151.2 Function Documentation	2108
7.151.2.1 nppsCubrt_32f	2108
7.151.2.2 nppsCubrt_32s16s_Sfs	2108
7.152Exp	2109
7.152.1 Detailed Description	2109
7.152.2 Function Documentation	2109
7.152.2.1 nppsExp_16s_ISfs	2109
7.152.2.2 nppsExp_16s_Sfs	2110
7.152.2.3 nppsExp_32f	2110
7.152.2.4 nppsExp_32f64f	2110
7.152.2.5 nppsExp_32f_I	2111
7.152.2.6 nppsExp_32s_ISfs	2111
7.152.2.7 nppsExp_32s_Sfs	2111
7.152.2.8 nppsExp_64f	2111
7.152.2.9 nppsExp_64f_I	2112
7.152.2.10 nppsExp_64s_ISfs	2112
7.152.2.11 nppsExp_64s_Sfs	2112
7.153Ln	2113
7.153.1 Detailed Description	2113
7.153.2 Function Documentation	2113
7.153.2.1 nppsLn_16s_ISfs	2113
7.153.2.2 nppsLn_16s_Sfs	2114
7.153.2.3 nppsLn_32f	2114
7.153.2.4 nppsLn_32f_I	2114
7.153.2.5 nppsLn_32s16s_Sfs	2115
7.153.2.6 nppsLn_32s_ISfs	2115
7.153.2.7 nppsLn_32s_Sfs	2115
7.153.2.8 nppsLn_64f	2116
7.153.2.9 nppsLn_64f32f	2116
7.153.2.10 nppsLn_64f_I	2116
7.15410Log10	2117
7.154.1 Detailed Description	2117
7.154.2 Function Documentation	2117
7.154.2.1 npps10Log10_32s_ISfs	2117
7.154.2.2 npps10Log10_32s_Sfs	2117

7.155SumLn	2118
7.155.1 Detailed Description	2118
7.155.2 Function Documentation	2118
7.155.2.1 nppsSumLn_16s32f	2118
7.155.2.2 nppsSumLn_32f	2119
7.155.2.3 nppsSumLn_32f64f	2119
7.155.2.4 nppsSumLn_64f	2119
7.155.2.5 nppsSumLnGetBufferSize_16s32f	2120
7.155.2.6 nppsSumLnGetBufferSize_32f	2120
7.155.2.7 nppsSumLnGetBufferSize_32f64f	2120
7.155.2.8 nppsSumLnGetBufferSize_64f	2121
7.156Arctan	2122
7.156.1 Detailed Description	2122
7.156.2 Function Documentation	2122
7.156.2.1 nppsArctan_32f	2122
7.156.2.2 nppsArctan_32f_I	2122
7.156.2.3 nppsArctan_64f	2123
7.156.2.4 nppsArctan_64f_I	2123
7.157Normalize	2124
7.157.1 Detailed Description	2124
7.157.2 Function Documentation	2124
7.157.2.1 nppsNormalize_16s_Sfs	2124
7.157.2.2 nppsNormalize_16sc_Sfs	2125
7.157.2.3 nppsNormalize_32f	2125
7.157.2.4 nppsNormalize_32fc	2125
7.157.2.5 nppsNormalize_64f	2126
7.157.2.6 nppsNormalize_64fc	2126
7.158Cauchy, CauchyD, and CauchyDD2	2127
7.158.1 Detailed Description	2127
7.158.2 Function Documentation	2127
7.158.2.1 nppsCauchy_32f_I	2127
7.158.2.2 nppsCauchyD_32f_I	2127
7.158.2.3 nppsCauchyDD2_32f_I	2128
7.159Logical And Shift Operations	2129
7.160AndC	2130
7.160.1 Detailed Description	2130

7.160.2 Function Documentation	2130
7.160.2.1 nppsAndC_16u	2130
7.160.2.2 nppsAndC_16u_I	2131
7.160.2.3 nppsAndC_32u	2131
7.160.2.4 nppsAndC_32u_I	2131
7.160.2.5 nppsAndC_8u	2131
7.160.2.6 nppsAndC_8u_I	2132
7.161 And	2133
7.161.1 Detailed Description	2133
7.161.2 Function Documentation	2133
7.161.2.1 nppsAnd_16u	2133
7.161.2.2 nppsAnd_16u_I	2134
7.161.2.3 nppsAnd_32u	2134
7.161.2.4 nppsAnd_32u_I	2134
7.161.2.5 nppsAnd_8u	2134
7.161.2.6 nppsAnd_8u_I	2135
7.162 OrC	2136
7.162.1 Detailed Description	2136
7.162.2 Function Documentation	2136
7.162.2.1 nppsOrC_16u	2136
7.162.2.2 nppsOrC_16u_I	2137
7.162.2.3 nppsOrC_32u	2137
7.162.2.4 nppsOrC_32u_I	2137
7.162.2.5 nppsOrC_8u	2137
7.162.2.6 nppsOrC_8u_I	2138
7.163 Or	2139
7.163.1 Detailed Description	2139
7.163.2 Function Documentation	2139
7.163.2.1 nppsOr_16u	2139
7.163.2.2 nppsOr_16u_I	2140
7.163.2.3 nppsOr_32u	2140
7.163.2.4 nppsOr_32u_I	2140
7.163.2.5 nppsOr_8u	2140
7.163.2.6 nppsOr_8u_I	2141
7.164 XorC	2142
7.164.1 Detailed Description	2142

7.164.2 Function Documentation	2142
7.164.2.1 nppsXorC_16u	2142
7.164.2.2 nppsXorC_16u_I	2143
7.164.2.3 nppsXorC_32u	2143
7.164.2.4 nppsXorC_32u_I	2143
7.164.2.5 nppsXorC_8u	2143
7.164.2.6 nppsXorC_8u_I	2144
7.165Xor	2145
7.165.1 Detailed Description	2145
7.165.2 Function Documentation	2145
7.165.2.1 nppsXor_16u	2145
7.165.2.2 nppsXor_16u_I	2146
7.165.2.3 nppsXor_32u	2146
7.165.2.4 nppsXor_32u_I	2146
7.165.2.5 nppsXor_8u	2146
7.165.2.6 nppsXor_8u_I	2147
7.166Not	2148
7.166.1 Detailed Description	2148
7.166.2 Function Documentation	2148
7.166.2.1 nppsNot_16u	2148
7.166.2.2 nppsNot_16u_I	2149
7.166.2.3 nppsNot_32u	2149
7.166.2.4 nppsNot_32u_I	2149
7.166.2.5 nppsNot_8u	2149
7.166.2.6 nppsNot_8u_I	2150
7.167LShiftC	2151
7.167.1 Detailed Description	2151
7.167.2 Function Documentation	2151
7.167.2.1 nppsLShiftC_16s	2151
7.167.2.2 nppsLShiftC_16s_I	2152
7.167.2.3 nppsLShiftC_16u	2152
7.167.2.4 nppsLShiftC_16u_I	2152
7.167.2.5 nppsLShiftC_32s	2153
7.167.2.6 nppsLShiftC_32s_I	2153
7.167.2.7 nppsLShiftC_32u	2153
7.167.2.8 nppsLShiftC_32u_I	2154

7.167.2.9	nppsLShiftC_8u	2154
7.167.2.10	nppsLShiftC_8u_I	2154
7.168	RShiftC	2155
7.168.1	Detailed Description	2155
7.168.2	Function Documentation	2155
7.168.2.1	nppsRShiftC_16s	2155
7.168.2.2	nppsRShiftC_16s_I	2156
7.168.2.3	nppsRShiftC_16u	2156
7.168.2.4	nppsRShiftC_16u_I	2156
7.168.2.5	nppsRShiftC_32s	2157
7.168.2.6	nppsRShiftC_32s_I	2157
7.168.2.7	nppsRShiftC_32u	2157
7.168.2.8	nppsRShiftC_32u_I	2158
7.168.2.9	nppsRShiftC_8u	2158
7.168.2.10	nppsRShiftC_8u_I	2158
7.169	Conversion Functions	2159
7.170	Convert	2160
7.170.1	Function Documentation	2162
7.170.1.1	nppsConvert_16s32f	2162
7.170.1.2	nppsConvert_16s32f_Sfs	2162
7.170.1.3	nppsConvert_16s32s	2162
7.170.1.4	nppsConvert_16s64f_Sfs	2162
7.170.1.5	nppsConvert_16s8s_Sfs	2162
7.170.1.6	nppsConvert_16u32f	2162
7.170.1.7	nppsConvert_32f16s_Sfs	2162
7.170.1.8	nppsConvert_32f16u_Sfs	2162
7.170.1.9	nppsConvert_32f32s_Sfs	2162
7.170.1.10	nppsConvert_32f64f	2162
7.170.1.11	nppsConvert_32f8s_Sfs	2162
7.170.1.12	nppsConvert_32f8u_Sfs	2162
7.170.1.13	nppsConvert_32s16s	2162
7.170.1.14	nppsConvert_32s16s_Sfs	2162
7.170.1.15	nppsConvert_32s32f	2162
7.170.1.16	nppsConvert_32s32f_Sfs	2162
7.170.1.17	nppsConvert_32s64f	2162
7.170.1.18	nppsConvert_32s64f_Sfs	2162

7.170.1.19	nppsConvert_64f16s_Sfs	2162
7.170.1.20	nppsConvert_64f32f	2162
7.170.1.21	nppsConvert_64f32s_Sfs	2162
7.170.1.22	nppsConvert_64f64s_Sfs	2162
7.170.1.23	nppsConvert_64s32s_Sfs	2162
7.170.1.24	nppsConvert_64s64f	2162
7.170.1.25	nppsConvert_8s16s	2162
7.170.1.26	nppsConvert_8s32f	2162
7.170.1.27	nppsConvert_8u32f	2162
7.171	Threshold	2163
7.171.1	Function Documentation	2167
7.171.1.1	nppsThreshold_16s	2167
7.171.1.2	nppsThreshold_16s_I	2168
7.171.1.3	nppsThreshold_16sc	2168
7.171.1.4	nppsThreshold_16sc_I	2168
7.171.1.5	nppsThreshold_32f	2169
7.171.1.6	nppsThreshold_32f_I	2169
7.171.1.7	nppsThreshold_32fc	2169
7.171.1.8	nppsThreshold_32fc_I	2170
7.171.1.9	nppsThreshold_64f	2170
7.171.1.10	nppsThreshold_64f_I	2171
7.171.1.11	nppsThreshold_64fc	2171
7.171.1.12	nppsThreshold_64fc_I	2171
7.171.1.13	nppsThreshold_GT_16s	2172
7.171.1.14	nppsThreshold_GT_16s_I	2172
7.171.1.15	nppsThreshold_GT_16sc	2172
7.171.1.16	nppsThreshold_GT_16sc_I	2173
7.171.1.17	nppsThreshold_GT_32f	2173
7.171.1.18	nppsThreshold_GT_32f_I	2173
7.171.1.19	nppsThreshold_GT_32fc	2174
7.171.1.20	nppsThreshold_GT_32fc_I	2174
7.171.1.21	nppsThreshold_GT_64f	2174
7.171.1.22	nppsThreshold_GT_64f_I	2175
7.171.1.23	nppsThreshold_GT_64fc	2175
7.171.1.24	nppsThreshold_GT_64fc_I	2175
7.171.1.25	nppsThreshold_GTVAl_16s	2176

7.171.1.26	nppsThreshold_GTVal_16s_I	2176
7.171.1.27	nppsThreshold_GTVal_16sc	2176
7.171.1.28	nppsThreshold_GTVal_16sc_I	2177
7.171.1.29	nppsThreshold_GTVal_32f	2177
7.171.1.30	nppsThreshold_GTVal_32f_I	2177
7.171.1.31	nppsThreshold_GTVal_32fc	2178
7.171.1.32	nppsThreshold_GTVal_32fc_I	2178
7.171.1.33	nppsThreshold_GTVal_64f	2178
7.171.1.34	nppsThreshold_GTVal_64f_I	2179
7.171.1.35	nppsThreshold_GTVal_64fc	2179
7.171.1.36	nppsThreshold_GTVal_64fc_I	2179
7.171.1.37	nppsThreshold_LT_16s	2180
7.171.1.38	nppsThreshold_LT_16s_I	2180
7.171.1.39	nppsThreshold_LT_16sc	2180
7.171.1.40	nppsThreshold_LT_16sc_I	2181
7.171.1.41	nppsThreshold_LT_32f	2181
7.171.1.42	nppsThreshold_LT_32f_I	2181
7.171.1.43	nppsThreshold_LT_32fc	2182
7.171.1.44	nppsThreshold_LT_32fc_I	2182
7.171.1.45	nppsThreshold_LT_64f	2182
7.171.1.46	nppsThreshold_LT_64f_I	2183
7.171.1.47	nppsThreshold_LT_64fc	2183
7.171.1.48	nppsThreshold_LT_64fc_I	2183
7.171.1.49	nppsThreshold_LTVAl_16s	2184
7.171.1.50	nppsThreshold_LTVAl_16s_I	2184
7.171.1.51	nppsThreshold_LTVAl_16sc	2184
7.171.1.52	nppsThreshold_LTVAl_16sc_I	2185
7.171.1.53	nppsThreshold_LTVAl_32f	2185
7.171.1.54	nppsThreshold_LTVAl_32f_I	2185
7.171.1.55	nppsThreshold_LTVAl_32fc	2186
7.171.1.56	nppsThreshold_LTVAl_32fc_I	2186
7.171.1.57	nppsThreshold_LTVAl_64f	2186
7.171.1.58	nppsThreshold_LTVAl_64f_I	2187
7.171.1.59	nppsThreshold_LTVAl_64fc	2187
7.171.1.60	nppsThreshold_LTVAl_64fc_I	2187
7.172	Filtering Functions	2188

7.172.1 Detailed Description	2188
7.173Integral	2189
7.173.1 Detailed Description	2189
7.173.2 Function Documentation	2189
7.173.2.1 nppsIntegral_32s	2189
7.173.2.2 nppsIntegralGetBufferSize_32s	2189
7.174Initialization	2190
7.175Set	2191
7.175.1 Function Documentation	2191
7.175.1.1 nppsSet_16s	2191
7.175.1.2 nppsSet_16sc	2192
7.175.1.3 nppsSet_32f	2192
7.175.1.4 nppsSet_32fc	2192
7.175.1.5 nppsSet_32s	2193
7.175.1.6 nppsSet_32sc	2193
7.175.1.7 nppsSet_64f	2193
7.175.1.8 nppsSet_64fc	2193
7.175.1.9 nppsSet_64s	2194
7.175.1.10nppsSet_64sc	2194
7.175.1.11nppsSet_8u	2194
7.176Zero	2195
7.176.1 Function Documentation	2195
7.176.1.1 nppsZero_16s	2195
7.176.1.2 nppsZero_16sc	2196
7.176.1.3 nppsZero_32f	2196
7.176.1.4 nppsZero_32fc	2196
7.176.1.5 nppsZero_32s	2196
7.176.1.6 nppsZero_32sc	2197
7.176.1.7 nppsZero_64f	2197
7.176.1.8 nppsZero_64fc	2197
7.176.1.9 nppsZero_64s	2197
7.176.1.10nppsZero_64sc	2198
7.176.1.11nppsZero_8u	2198
7.177Copy	2199
7.177.1 Function Documentation	2199
7.177.1.1 nppsCopy_16s	2199

7.177.1.2	nppsCopy_16sc	2200
7.177.1.3	nppsCopy_32f	2200
7.177.1.4	nppsCopy_32fc	2200
7.177.1.5	nppsCopy_32s	2201
7.177.1.6	nppsCopy_32sc	2201
7.177.1.7	nppsCopy_64fc	2201
7.177.1.8	nppsCopy_64s	2201
7.177.1.9	nppsCopy_64sc	2202
7.177.1.10	nppsCopy_8u	2202
7.178	Statistical Functions	2203
7.178.1	Detailed Description	2203
7.179	MinEvery And MaxEvery Functions	2204
7.179.1	Detailed Description	2204
7.179.2	Function Documentation	2204
7.179.2.1	nppsMaxEvery_16s_I	2204
7.179.2.2	nppsMaxEvery_16u_I	2205
7.179.2.3	nppsMaxEvery_32f_I	2205
7.179.2.4	nppsMaxEvery_32s_I	2205
7.179.2.5	nppsMaxEvery_8u_I	2206
7.179.2.6	nppsMinEvery_16s_I	2206
7.179.2.7	nppsMinEvery_16u_I	2206
7.179.2.8	nppsMinEvery_32f_I	2206
7.179.2.9	nppsMinEvery_32s_I	2207
7.179.2.10	nppsMinEvery_64f_I	2207
7.179.2.11	nppsMinEvery_8u_I	2207
7.180	Sum	2208
7.180.1	Detailed Description	2209
7.180.2	Function Documentation	2209
7.180.2.1	nppsSum_16s32s_Sfs	2209
7.180.2.2	nppsSum_16s_Sfs	2209
7.180.2.3	nppsSum_16sc32sc_Sfs	2210
7.180.2.4	nppsSum_16sc_Sfs	2210
7.180.2.5	nppsSum_32f	2211
7.180.2.6	nppsSum_32fc	2211
7.180.2.7	nppsSum_32s_Sfs	2211
7.180.2.8	nppsSum_64f	2212

7.180.2.9	nppsSum_64fc	2212
7.180.2.10	nppsSumGetBufferSize_16s32s_Sfs	2212
7.180.2.11	nppsSumGetBufferSize_16s_Sfs	2213
7.180.2.12	nppsSumGetBufferSize_16sc32sc_Sfs	2213
7.180.2.13	nppsSumGetBufferSize_16sc_Sfs	2213
7.180.2.14	nppsSumGetBufferSize_32f	2213
7.180.2.15	nppsSumGetBufferSize_32fc	2214
7.180.2.16	nppsSumGetBufferSize_32s_Sfs	2214
7.180.2.17	nppsSumGetBufferSize_64f	2214
7.180.2.18	nppsSumGetBufferSize_64fc	2214
7.181	Maximum	2215
7.181.1	Function Documentation	2216
7.181.1.1	nppsMax_16s	2216
7.181.1.2	nppsMax_32f	2217
7.181.1.3	nppsMax_32s	2217
7.181.1.4	nppsMax_64f	2217
7.181.1.5	nppsMaxAbs_16s	2218
7.181.1.6	nppsMaxAbs_32s	2218
7.181.1.7	nppsMaxAbsGetBufferSize_16s	2218
7.181.1.8	nppsMaxAbsGetBufferSize_32s	2219
7.181.1.9	nppsMaxAbsIndx_16s	2219
7.181.1.10	nppsMaxAbsIndx_32s	2219
7.181.1.11	nppsMaxAbsIndxGetBufferSize_16s	2220
7.181.1.12	nppsMaxAbsIndxGetBufferSize_32s	2220
7.181.1.13	nppsMaxGetBufferSize_16s	2220
7.181.1.14	nppsMaxGetBufferSize_32f	2221
7.181.1.15	nppsMaxGetBufferSize_32s	2221
7.181.1.16	nppsMaxGetBufferSize_64f	2221
7.181.1.17	nppsMaxIndx_16s	2221
7.181.1.18	nppsMaxIndx_32f	2222
7.181.1.19	nppsMaxIndx_32s	2222
7.181.1.20	nppsMaxIndx_64f	2223
7.181.1.21	nppsMaxIndxGetBufferSize_16s	2223
7.181.1.22	nppsMaxIndxGetBufferSize_32f	2223
7.181.1.23	nppsMaxIndxGetBufferSize_32s	2224
7.181.1.24	nppsMaxIndxGetBufferSize_64f	2224

7.182	Minimum	2225
7.182.1	Function Documentation	2226
7.182.1.1	nppsMin_16s	2226
7.182.1.2	nppsMin_32f	2227
7.182.1.3	nppsMin_32s	2227
7.182.1.4	nppsMin_64f	2227
7.182.1.5	nppsMinAbs_16s	2228
7.182.1.6	nppsMinAbs_32s	2228
7.182.1.7	nppsMinAbsGetBufferSize_16s	2228
7.182.1.8	nppsMinAbsGetBufferSize_32s	2229
7.182.1.9	nppsMinAbsIndx_16s	2229
7.182.1.10	nppsMinAbsIndx_32s	2229
7.182.1.11	nppsMinAbsIndxGetBufferSize_16s	2230
7.182.1.12	nppsMinAbsIndxGetBufferSize_32s	2230
7.182.1.13	nppsMinGetBufferSize_16s	2230
7.182.1.14	nppsMinGetBufferSize_32f	2231
7.182.1.15	nppsMinGetBufferSize_32s	2231
7.182.1.16	nppsMinGetBufferSize_64f	2231
7.182.1.17	nppsMinIndx_16s	2231
7.182.1.18	nppsMinIndx_32f	2232
7.182.1.19	nppsMinIndx_32s	2232
7.182.1.20	nppsMinIndx_64f	2233
7.182.1.21	nppsMinIndxGetBufferSize_16s	2233
7.182.1.22	nppsMinIndxGetBufferSize_32f	2233
7.182.1.23	nppsMinIndxGetBufferSize_32s	2234
7.182.1.24	nppsMinIndxGetBufferSize_64f	2234
7.183	Mean	2235
7.183.1	Function Documentation	2236
7.183.1.1	nppsMean_16s_Sfs	2236
7.183.1.2	nppsMean_16sc_Sfs	2236
7.183.1.3	nppsMean_32f	2236
7.183.1.4	nppsMean_32fc	2237
7.183.1.5	nppsMean_32s_Sfs	2237
7.183.1.6	nppsMean_64f	2238
7.183.1.7	nppsMean_64fc	2238
7.183.1.8	nppsMeanGetBufferSize_16s_Sfs	2238

7.183.1.9 nppsMeanGetBufferSize_16sc_Sfs	2239
7.183.1.10 nppsMeanGetBufferSize_32f	2239
7.183.1.11 nppsMeanGetBufferSize_32fc	2239
7.183.1.12 nppsMeanGetBufferSize_32s_Sfs	2239
7.183.1.13 nppsMeanGetBufferSize_64f	2240
7.183.1.14 nppsMeanGetBufferSize_64fc	2240
7.184 Standard Deviation	2241
7.184.1 Function Documentation	2241
7.184.1.1 nppsStdDev_16s32s_Sfs	2241
7.184.1.2 nppsStdDev_16s_Sfs	2242
7.184.1.3 nppsStdDev_32f	2242
7.184.1.4 nppsStdDev_64f	2242
7.184.1.5 nppsStdDevGetBufferSize_16s32s_Sfs	2243
7.184.1.6 nppsStdDevGetBufferSize_16s_Sfs	2243
7.184.1.7 nppsStdDevGetBufferSize_32f	2243
7.184.1.8 nppsStdDevGetBufferSize_64f	2243
7.185 Mean And Standard Deviation	2244
7.185.1 Function Documentation	2244
7.185.1.1 nppsMeanStdDev_16s32s_Sfs	2244
7.185.1.2 nppsMeanStdDev_16s_Sfs	2245
7.185.1.3 nppsMeanStdDev_32f	2245
7.185.1.4 nppsMeanStdDev_64f	2245
7.185.1.5 nppsMeanStdDevGetBufferSize_16s32s_Sfs	2246
7.185.1.6 nppsMeanStdDevGetBufferSize_16s_Sfs	2246
7.185.1.7 nppsMeanStdDevGetBufferSize_32f	2246
7.185.1.8 nppsMeanStdDevGetBufferSize_64f	2247
7.186 Minimum_Maximum	2248
7.186.1 Function Documentation	2250
7.186.1.1 nppsMinMax_16s	2250
7.186.1.2 nppsMinMax_16u	2250
7.186.1.3 nppsMinMax_32f	2250
7.186.1.4 nppsMinMax_32s	2251
7.186.1.5 nppsMinMax_32u	2251
7.186.1.6 nppsMinMax_64f	2251
7.186.1.7 nppsMinMax_8u	2252
7.186.1.8 nppsMinMaxGetBufferSize_16s	2252

7.186.1.9	nppsMinMaxGetBufferSize_16u	2252
7.186.1.10	nppsMinMaxGetBufferSize_32f	2253
7.186.1.11	nppsMinMaxGetBufferSize_32s	2253
7.186.1.12	nppsMinMaxGetBufferSize_32u	2253
7.186.1.13	nppsMinMaxGetBufferSize_64f	2254
7.186.1.14	nppsMinMaxGetBufferSize_8u	2254
7.186.1.15	nppsMinMaxIndx_16s	2254
7.186.1.16	nppsMinMaxIndx_16u	2255
7.186.1.17	nppsMinMaxIndx_32f	2255
7.186.1.18	nppsMinMaxIndx_32s	2255
7.186.1.19	nppsMinMaxIndx_32u	2256
7.186.1.20	nppsMinMaxIndx_64f	2256
7.186.1.21	nppsMinMaxIndx_8u	2257
7.186.1.22	nppsMinMaxIndxGetBufferSize_16s	2257
7.186.1.23	nppsMinMaxIndxGetBufferSize_16u	2257
7.186.1.24	nppsMinMaxIndxGetBufferSize_32f	2258
7.186.1.25	nppsMinMaxIndxGetBufferSize_32s	2258
7.186.1.26	nppsMinMaxIndxGetBufferSize_32u	2258
7.186.1.27	nppsMinMaxIndxGetBufferSize_64f	2258
7.186.1.28	nppsMinMaxIndxGetBufferSize_8u	2259
7.187	Infinity Norm	2260
7.187.1	Function Documentation	2261
7.187.1.1	nppsNorm_Inf_16s32f	2261
7.187.1.2	nppsNorm_Inf_16s32s_Sfs	2261
7.187.1.3	nppsNorm_Inf_32f	2261
7.187.1.4	nppsNorm_Inf_32fc32f	2262
7.187.1.5	nppsNorm_Inf_64f	2262
7.187.1.6	nppsNorm_Inf_64fc64f	2262
7.187.1.7	nppsNormInfGetBufferSize_16s32f	2263
7.187.1.8	nppsNormInfGetBufferSize_16s32s_Sfs	2263
7.187.1.9	nppsNormInfGetBufferSize_32f	2263
7.187.1.10	nppsNormInfGetBufferSize_32fc32f	2263
7.187.1.11	nppsNormInfGetBufferSize_64f	2264
7.187.1.12	nppsNormInfGetBufferSize_64fc64f	2264
7.188	L1 Norm	2265
7.188.1	Function Documentation	2266

7.188.1.1	nppsNorm_L1_16s32f	2266
7.188.1.2	nppsNorm_L1_16s32s_Sfs	2266
7.188.1.3	nppsNorm_L1_16s64s_Sfs	2266
7.188.1.4	nppsNorm_L1_32f	2267
7.188.1.5	nppsNorm_L1_32fc64f	2267
7.188.1.6	nppsNorm_L1_64f	2267
7.188.1.7	nppsNorm_L1_64fc64f	2268
7.188.1.8	nppsNormL1GetBufferSize_16s32f	2268
7.188.1.9	nppsNormL1GetBufferSize_16s32s_Sfs	2268
7.188.1.10	nppsNormL1GetBufferSize_16s64s_Sfs	2269
7.188.1.11	nppsNormL1GetBufferSize_32f	2269
7.188.1.12	nppsNormL1GetBufferSize_32fc64f	2269
7.188.1.13	nppsNormL1GetBufferSize_64f	2269
7.188.1.14	nppsNormL1GetBufferSize_64fc64f	2270
7.189	L2 Norm	2271
7.189.1	Function Documentation	2272
7.189.1.1	nppsNorm_L2_16s32f	2272
7.189.1.2	nppsNorm_L2_16s32s_Sfs	2272
7.189.1.3	nppsNorm_L2_32f	2272
7.189.1.4	nppsNorm_L2_32fc64f	2273
7.189.1.5	nppsNorm_L2_64f	2273
7.189.1.6	nppsNorm_L2_64fc64f	2273
7.189.1.7	nppsNorm_L2Sqr_16s64s_Sfs	2274
7.189.1.8	nppsNormL2GetBufferSize_16s32f	2274
7.189.1.9	nppsNormL2GetBufferSize_16s32s_Sfs	2274
7.189.1.10	nppsNormL2GetBufferSize_32f	2275
7.189.1.11	nppsNormL2GetBufferSize_32fc64f	2275
7.189.1.12	nppsNormL2GetBufferSize_64f	2275
7.189.1.13	nppsNormL2GetBufferSize_64fc64f	2275
7.189.1.14	nppsNormL2SqrGetBufferSize_16s64s_Sfs	2276
7.190	Infinity Norm Diff	2277
7.190.1	Function Documentation	2278
7.190.1.1	nppsNormDiff_Inf_16s32f	2278
7.190.1.2	nppsNormDiff_Inf_16s32s_Sfs	2278
7.190.1.3	nppsNormDiff_Inf_32f	2278
7.190.1.4	nppsNormDiff_Inf_32fc32f	2279

7.190.1.5	nppsNormDiff_Inf_64f	2279
7.190.1.6	nppsNormDiff_Inf_64fc64f	2280
7.190.1.7	nppsNormDiffInfGetBufferSize_16s32f	2280
7.190.1.8	nppsNormDiffInfGetBufferSize_16s32s_Sfs	2280
7.190.1.9	nppsNormDiffInfGetBufferSize_32f	2280
7.190.1.10	nppsNormDiffInfGetBufferSize_32fc32f	2281
7.190.1.11	nppsNormDiffInfGetBufferSize_64f	2281
7.190.1.12	nppsNormDiffInfGetBufferSize_64fc64f	2281
7.191L1	Norm Diff	2282
7.191.1	Function Documentation	2283
7.191.1.1	nppsNormDiff_L1_16s32f	2283
7.191.1.2	nppsNormDiff_L1_16s32s_Sfs	2283
7.191.1.3	nppsNormDiff_L1_16s64s_Sfs	2283
7.191.1.4	nppsNormDiff_L1_32f	2284
7.191.1.5	nppsNormDiff_L1_32fc64f	2284
7.191.1.6	nppsNormDiff_L1_64f	2285
7.191.1.7	nppsNormDiff_L1_64fc64f	2285
7.191.1.8	nppsNormDiffL1GetBufferSize_16s32f	2285
7.191.1.9	nppsNormDiffL1GetBufferSize_16s32s_Sfs	2286
7.191.1.10	nppsNormDiffL1GetBufferSize_16s64s_Sfs	2286
7.191.1.11	nppsNormDiffL1GetBufferSize_32f	2286
7.191.1.12	nppsNormDiffL1GetBufferSize_32fc64f	2286
7.191.1.13	nppsNormDiffL1GetBufferSize_64f	2287
7.191.1.14	nppsNormDiffL1GetBufferSize_64fc64f	2287
7.192L2	Norm Diff	2288
7.192.1	Function Documentation	2289
7.192.1.1	nppsNormDiff_L2_16s32f	2289
7.192.1.2	nppsNormDiff_L2_16s32s_Sfs	2289
7.192.1.3	nppsNormDiff_L2_32f	2289
7.192.1.4	nppsNormDiff_L2_32fc64f	2290
7.192.1.5	nppsNormDiff_L2_64f	2290
7.192.1.6	nppsNormDiff_L2_64fc64f	2291
7.192.1.7	nppsNormDiff_L2Sqr_16s64s_Sfs	2291
7.192.1.8	nppsNormDiffL2GetBufferSize_16s32f	2291
7.192.1.9	nppsNormDiffL2GetBufferSize_16s32s_Sfs	2292
7.192.1.10	nppsNormDiffL2GetBufferSize_32f	2292

7.192.1.1	InppsNormDiffL2GetBufferSize_32fc64f	2292
7.192.1.12	nppsNormDiffL2GetBufferSize_64f	2292
7.192.1.13	nppsNormDiffL2GetBufferSize_64fc64f	2293
7.192.1.14	nppsNormDiffL2SqrGetBufferSize_16s64s_Sfs	2293
7.193	Dot Product	2294
7.193.1	Function Documentation	2297
7.193.1.1	nppsDotProd_16s16sc32fc	2297
7.193.1.2	nppsDotProd_16s16sc32sc_Sfs	2298
7.193.1.3	nppsDotProd_16s16sc64sc	2298
7.193.1.4	nppsDotProd_16s16sc_Sfs	2299
7.193.1.5	nppsDotProd_16s32f	2299
7.193.1.6	nppsDotProd_16s32s32s_Sfs	2299
7.193.1.7	nppsDotProd_16s32s_Sfs	2300
7.193.1.8	nppsDotProd_16s64s	2300
7.193.1.9	nppsDotProd_16s_Sfs	2301
7.193.1.10	nppsDotProd_16sc32fc	2301
7.193.1.11	InppsDotProd_16sc32sc_Sfs	2301
7.193.1.12	nppsDotProd_16sc64sc	2302
7.193.1.13	nppsDotProd_16sc_Sfs	2302
7.193.1.14	nppsDotProd_32f	2303
7.193.1.15	nppsDotProd_32f32fc	2303
7.193.1.16	nppsDotProd_32f32fc64fc	2303
7.193.1.17	nppsDotProd_32f64f	2304
7.193.1.18	nppsDotProd_32fc	2304
7.193.1.19	nppsDotProd_32fc64fc	2304
7.193.1.20	nppsDotProd_32s32sc_Sfs	2305
7.193.1.21	InppsDotProd_32s_Sfs	2305
7.193.1.22	nppsDotProd_32sc_Sfs	2305
7.193.1.23	nppsDotProd_64f	2306
7.193.1.24	nppsDotProd_64f64fc	2306
7.193.1.25	nppsDotProd_64fc	2307
7.193.1.26	nppsDotProdGetBufferSize_16s16sc32fc	2307
7.193.1.27	nppsDotProdGetBufferSize_16s16sc32sc_Sfs	2307
7.193.1.28	nppsDotProdGetBufferSize_16s16sc64sc	2307
7.193.1.29	nppsDotProdGetBufferSize_16s16sc_Sfs	2308
7.193.1.30	nppsDotProdGetBufferSize_16s32f	2308

7.193.1.3	nppsDotProdGetBufferSize_16s32s32s_Sfs	2308
7.193.1.32	nppsDotProdGetBufferSize_16s32s_Sfs	2309
7.193.1.33	nppsDotProdGetBufferSize_16s64s	2309
7.193.1.34	nppsDotProdGetBufferSize_16s_Sfs	2309
7.193.1.35	nppsDotProdGetBufferSize_16sc32fc	2309
7.193.1.36	nppsDotProdGetBufferSize_16sc32sc_Sfs	2310
7.193.1.37	nppsDotProdGetBufferSize_16sc64sc	2310
7.193.1.38	nppsDotProdGetBufferSize_16sc_Sfs	2310
7.193.1.39	nppsDotProdGetBufferSize_32f	2310
7.193.1.40	nppsDotProdGetBufferSize_32f32fc	2311
7.193.1.41	nppsDotProdGetBufferSize_32f32fc64fc	2311
7.193.1.42	nppsDotProdGetBufferSize_32f64f	2311
7.193.1.43	nppsDotProdGetBufferSize_32fc	2311
7.193.1.44	nppsDotProdGetBufferSize_32fc64fc	2312
7.193.1.45	nppsDotProdGetBufferSize_32s32sc_Sfs	2312
7.193.1.46	nppsDotProdGetBufferSize_32s_Sfs	2312
7.193.1.47	nppsDotProdGetBufferSize_32sc_Sfs	2312
7.193.1.48	nppsDotProdGetBufferSize_64f	2313
7.193.1.49	nppsDotProdGetBufferSize_64f64fc	2313
7.193.1.50	nppsDotProdGetBufferSize_64fc	2313
7.194	Count In Range	2314
7.194.1	Function Documentation	2314
7.194.1.1	nppsCountInRange_32s	2314
7.194.1.2	nppsCountInRangeGetBufferSize_32s	2314
7.195	Count Zero Crossings	2315
7.195.1	Function Documentation	2315
7.195.1.1	nppsZeroCrossing_16s32f	2315
7.195.1.2	nppsZeroCrossing_32f	2315
7.195.1.3	nppsZeroCrossingGetBufferSize_16s32f	2316
7.195.1.4	nppsZeroCrossingGetBufferSize_32f	2316
7.196	Memory Management	2317
7.197	Malloc	2318
7.197.1	Detailed Description	2319
7.197.2	Function Documentation	2319
7.197.2.1	nppsMalloc_16s	2319
7.197.2.2	nppsMalloc_16sc	2319

7.197.2.3	nppsMalloc_16u	2319
7.197.2.4	nppsMalloc_32f	2320
7.197.2.5	nppsMalloc_32fc	2320
7.197.2.6	nppsMalloc_32s	2320
7.197.2.7	nppsMalloc_32sc	2320
7.197.2.8	nppsMalloc_32u	2321
7.197.2.9	nppsMalloc_64f	2321
7.197.2.10	nppsMalloc_64fc	2321
7.197.2.11	nppsMalloc_64s	2321
7.197.2.12	nppsMalloc_64sc	2322
7.197.2.13	nppsMalloc_8s	2322
7.197.2.14	nppsMalloc_8u	2322
7.198	Free	2323
7.198.1	Detailed Description	2323
7.198.2	Function Documentation	2323
7.198.2.1	nppsFree	2323
8	Data Structure Documentation	2325
8.1	NPP_ALIGN_16 Struct Reference	2325
8.1.1	Detailed Description	2325
8.1.2	Field Documentation	2325
8.1.2.1	im	2325
8.1.2.2	im	2326
8.1.2.3	re	2326
8.1.2.4	re	2326
8.2	NPP_ALIGN_8 Struct Reference	2327
8.2.1	Detailed Description	2327
8.2.2	Field Documentation	2327
8.2.2.1	im	2327
8.2.2.2	im	2327
8.2.2.3	im	2327
8.2.2.4	re	2328
8.2.2.5	re	2328
8.2.2.6	re	2328
8.3	NppiHaarBuffer Struct Reference	2329
8.3.1	Field Documentation	2329
8.3.1.1	haarBuffer	2329

8.3.1.2	haarBufferSize	2329
8.4	NppiHaarClassifier_32f Struct Reference	2330
8.4.1	Field Documentation	2330
8.4.1.1	classifiers	2330
8.4.1.2	classifierSize	2330
8.4.1.3	classifierStep	2330
8.4.1.4	counterDevice	2330
8.4.1.5	numClassifiers	2330
8.5	NppiPoint Struct Reference	2331
8.5.1	Detailed Description	2331
8.5.2	Field Documentation	2331
8.5.2.1	x	2331
8.5.2.2	y	2331
8.6	NppiRect Struct Reference	2332
8.6.1	Detailed Description	2332
8.6.2	Field Documentation	2332
8.6.2.1	height	2332
8.6.2.2	width	2332
8.6.2.3	x	2332
8.6.2.4	y	2332
8.7	NppiSize Struct Reference	2333
8.7.1	Detailed Description	2333
8.7.2	Field Documentation	2333
8.7.2.1	height	2333
8.7.2.2	width	2333
8.8	NppLibraryVersion Struct Reference	2334
8.8.1	Field Documentation	2334
8.8.1.1	build	2334
8.8.1.2	major	2334
8.8.1.3	minor	2334

Chapter 1

NVIDIA Performance Primitives

IMPORTANT SPECIAL NOTICE IMPORTANT SPECIAL NOTICE IMPORTANT SPECIAL NOTICE
As of NPP version 5.0 and beyond a few parameters for a few pre-5.0 existing image LUT functions have changed from host memory pointers to device memory pointers. Your application will fail (crash or report an error) if you use these functions with host memory pointers. The functions are the `nppiLUT_Linear_8u_xxx` functions.

Also, pre-5.0 function `nppiMeanStdDev8uC1RGetBufferHostSize` has been renamed `nppiMeanStdDevGetBufferHostSize_8u_C1R`.

1.1 What is NPP?

NVIDIA NPP is a library of functions for performing CUDA accelerated processing. The initial set of functionality in the library focuses on imaging and video processing and is widely applicable for developers in these areas. NPP will evolve over time to encompass more of the compute heavy tasks in a variety of problem domains. The NPP library is written to maximize flexibility, while maintaining high performance.

NPP can be used in one of two ways:

- A stand-alone library for adding GPU acceleration to an application with minimal effort. Using this route allows developers to add GPU acceleration to their applications in a matter of hours.
- A cooperative library for interoperating with a developer's GPU code efficiently.

Either route allows developers to harness the massive compute resources of NVIDIA GPUs, while simultaneously reducing development times.

1.2 Documentation

- [General API Conventions](#)
- [Signal-Processing Specific API Conventions](#)
- [Imaging-Processing Specific API Conventions](#)

1.3 Technical Specifications

Supported Platforms:

- Microsoft Windows 7 (64-bit and 32-bit)
- Microsoft Windows Vista (64-bit and 32-bit)
- Microsoft Windows XP (64-bit and 32-bit)
- Linux (Centos & Ubuntu) (64-bit and 32-bit)
- Mac OS X

1.4 Files

NPP is comprises the following files:

1.4.1 Header Files

- [nppdefs.h](#)
- [nppcore.h](#)
- [nppi.h](#)
- [npps.h](#)
- [nppversion.h](#)
- [npp.h](#)

All those header files are located in the CUDA Toolkit's

`/include/`

directory.

1.4.2 Library Files

Starting with Version 5.5 NPP's functionality is now split up into 3 distinct libraries:

- A core library (NPPC) containing basic functionality from the [npp.h](#) header files as well as functionality shared by the other two libraries.
- The image processing library NPPI. Any functions from the [nppi.h](#) header file (or the various header files named "nppi_XXX.h" are bundled into the NPPI library.
- The signal processing library NPPS. Any function from the [npps.h](#) header file (or the various header files named "npps_XXX.h" are bundled into the NPPS library.

On the Windows platform the NPP stub libraries are found in the CUDA Toolkit's library directory:

```
/lib/nppc.lib
```

```
/lib/nppi.lib
```

```
/lib/npps.lib
```

The matching DLLs are located in the CUDA Toolkit's binary directory. Example

```
/bin/nppi64_55_<build_no>.dll // Dynamic image-processing library for 64-bit Windows.
```

On Linux and Mac platforms the dynamic libraries are located in the lib directory

```
/lib/libnppc32.so.5.5.<build_no> // NPP 32-bit dynamic core library for Linux
```

```
/lib/libnpps32.5.5.dylib // NPP 32-bit dynamic signal processing library for Mac
```

1.5 Supported NVIDIA Hardware

NPP runs on all CUDA capable NVIDIA hardware. For details please see http://www.nvidia.com/object/cuda_learn_products.html

Chapter 2

General API Conventions

2.1 Memory Management

The design of all the NPP functions follows the same guidelines as other NVIDIA CUDA libraries like cuFFT and cuBLAS. That is that all pointer arguments in those APIs are device pointers.

This convention enables the individual developer to make smart choices about memory management that minimize the number of memory transfers. It also allows the user the maximum flexibility regarding which of the various memory transfer mechanisms offered by the CUDA runtime is used, e.g. synchronous or asynchronous memory transfers, zero-copy and pinned memory, etc.

The most basic steps involved in using NPP for processing data is as follows:

1. Transfer input data from the host to device using

```
cudaMemcpy(...)
```

2. Process data using one or several NPP functions or custom CUDA kernels

3. Transfer the result data from the device to the host using

```
cudaMemcpy(...)
```

2.1.1 Scratch Buffer and Host Pointer

Some primitives of NPP require additional device memory buffers (scratch buffers) for calculations, e.g. signal and image reductions (Sum, Max, Min, MinMax, etc.). In order to give the NPP user maximum control regarding memory allocations and performance, it is the user's responsibility to allocate and delete those temporary buffers. For one this has the benefit that the library will not allocate memory unbeknownst to the user. It also allows developers who invoke the same primitive repeatedly to allocate the scratch only once, improving performance and potential device-memory fragmentation.

Scratch-buffer memory is unstructured and may be passed to the primitive in uninitialized form. This allows for reuse of the same scratch buffers with any primitive require scratch memory, as long as it is sufficiently sized.

The minimum scratch-buffer size for a given primitive (e.g. [nppsSum_32f\(\)](#)) can be obtained by a companion function (e.g. [nppsSumGetBufferSize_32f\(\)](#)). The buffer size is returned via a host pointer as allocation of the scratch-buffer is performed via CUDA runtime host code.

An example to invoke signal sum primitive and allocate and free the necessary scratch memory:

```
// pSrc, pSum, pDeviceBuffer are all device pointers.
Npp32f * pSrc;
Npp32f * pSum;
Npp8u * pDeviceBuffer;
int nLength = 1024;

// Allocate the device memroy.
cudaMalloc((void **)(&pSrc), sizeof(Npp32f) * nLength);
nppsSet_32f(1.0f, pSrc, nLength);
cudaMalloc((void **)(&pSum), sizeof(Npp32f) * 1);

// Compute the appropriate size of the scratch-memory buffer
int nBufferSize;
nppsSumGetBufferSize_32f(nLength, &nBufferSize);
// Allocate the scratch buffer
cudaMalloc((void **)(&pDeviceBuffer), nBufferSize);

// Call the primitive with the scratch buffer
```

```
nppsSum_32f(pSrc, nLength, pSum, pDeviceBuffer);
Npp32f nSumHost;
cudaMemcpy(&nSumHost, pSum, sizeof(Npp32f) * 1, cudaMemcpyDeviceToHost);
printf("sum = %f\n", nSumHost); // nSumHost = 1024.0f;

// Free the device memory
cudaFree(pSrc);
cudaFree(pDeviceBuffer);
cudaFree(pSum);
```

2.2 Function Naming

Since NPP is a C API and therefore does not allow for function overloading for different data-types the NPP naming convention addresses the need to differentiate between different flavors of the same algorithm or primitive function but for various data types. This disambiguation of different flavors of a primitive is done via a suffix containing data type and other disambiguating information.

In addition to the flavor suffix, all NPP functions are prefixed with by the letters "npp". Primitives belonging to NPP's image-processing module add the letter "i" to the npp prefix, i.e. are prefixed by "nppi". Similarly signal-processing primitives are prefixed with "npps".

The general naming scheme is:

```
npp<module info><PrimitiveName>_<data-type info>[_<additional flavor info>](<parameter list>)
```

The data-type information uses the same names as the [Basic NPP Data Types](#). For example the data-type information "8u" would imply that the primitive operates on [Npp8u](#) data.

If a primitive consumes different type data from what it produces, both types will be listed in the order of consumed to produced data type.

Details about the "additional flavor information" is provided for each of the NPP modules, since each problem domain uses different flavor information suffixes.

2.3 Integer Result Scaling

NPP signal processing and imaging primitives often operate on integer data. This integer data is usually a fixed point fractional representation of some physical magnitue (e.g. luminance). Because of this fixed-point nature of the representation many numerical operations (e.g. addition or multiplication) tend to produce results exceeding the original fixed-point range if treated as regular integers.

In cases where the results exceed the original range, these functions clamp the result values back to the valid range. E.g. the maximum positive value for a 16-bit unsigned integer is 32767. A multiplication operation of $4 * 10000 = 40000$ would exceed this range. The result would be clamped to be 32767.

To avoid the level of lost information due to clamping most integer primitives allow for result scaling. Primitives with result scaling have the "Sfs" suffix in their name and provide a parameter "nScaleFactor" that controls the amount of scaling. Before the results of an operation are clamped to the valid output-data range by multiplying them with $2^{-nScaleFactor}$.

Example: The primitive [nppsSqr_8u_Sfs\(\)](#) computes the square of 8-bit unsigned sample values in a signal (1D array of values). The maximum value of a 8-bit value is 255. The square of $255^2 = 65025$ which would be clamped to 255 if no result scaling is performed. In order to map the maximum value of 255 to 255 in the result, one would specify an integer result scaling factor of 8, i.e. multiply each result with $2^{-8} = \frac{1}{2^8} = \frac{1}{256}$. The final result for a signal value of 255 being squared and scaled would be:

$$255^2 \cdot 2^{-8} = 254.00390625$$

which would be rounded to a final result of 254.

A medium gray value of 128 would result in

$$128^2 * 2^{-8} = 64$$

2.4 Rounding Modes

Many NPP functions require converting floating-point values to integers. The [NppRoundMode](#) enum lists NPP's supported rounding modes. Not all primitives in NPP that perform rounding as part of their functionality allow the user to specify the round-mode used. Instead they use NPP's default rounding mode, which is [NPP_RND_FINANCIAL](#).

2.4.1 Rounding Mode Parameter

A subset of NPP functions performing rounding as part of their functionality do allow the user to specify which rounding mode is used through a parameter of the [NppRoundMode](#) type.

Chapter 3

Signal-Processing Specific API Conventions

3.1 Signal Data

Signal data is passed to and from NPPS primitives via a pointer to the signal's data type.

The general idea behind this fairly low-level way of passing signal data is ease-of-adoption into existing software projects:

- Passing the data pointer rather than a higher-level signal struct allows for easy adoption by not requiring a specific signal representation (that could include total signal size offset, or other additional information). This avoids awkward packing and unpacking of signal data from the host application to an NPP specific signal representation.

3.1.1 Parameter Names for Signal Data

There are three general cases of image-data passing throughout NPP detailed in the following sections.

Those are signals consumed by the algorithm.

3.1.1.1 Source Signal Pointer

The source signal data is generally passed via a pointer named

```
pSrc
```

The source signal pointer is generally defined constant, enforcing that the primitive does not change any image data pointed to by that pointer. E.g.

```
nppsPrimitive_32s(const Npp32s * pSrc, ...)
```

In case the primitive consumes multiple signals as inputs the source pointers are numbered like this:

```
pSrc1, pSrc2, ...
```

3.1.1.2 Destination Signal Pointer

The destination signal data is generally passed via a pointer named

```
pDst
```

In case the primitive consumes multiple signals as inputs the source pointers are numbered like this:

```
pDst1, pDst2, ...
```

3.1.1.3 In-Place Signal Pointer

In the case of in-place processing, source and destination are served by the same pointer and thus pointers to in-place signal data are called:

```
pSrcDst
```

3.1.2 Signal Data Alignment Requirements

NPP requires signal sample data to be naturally aligned, i.e. any pointer

```
NppType * p;
```

to a sample in a signal needs to fulfill:

```
assert(p % sizeof(p) == 0);
```

3.1.3 Signal Data Related Error Codes

All NPPI primitives operating on signal data validate the signal-data pointer for proper alignment and test that the point is not null.

Failed validation results in one of the following error codes being returned and the primitive not being executed:

- [NPP_NULL_POINTER_ERROR](#) is returned if the image-data pointer is 0 (NULL).
- [NPP_ALIGNMENT_ERROR](#) if the signal-data pointer address is not a multiple of the signal's data-type size.

3.2 Signal Length

The vast majority of NPPS functions take a

```
nLength
```

parameter that tells the primitive how many of the signal's samples starting from the given data pointer are to be processed.

3.2.1 Length Related Error Codes

All NPPS primitives taking a length parameter validate this input.

Failed validation results in the following error code being returned and the primitive not being executed:

- [NPP_SIZE_ERROR](#) is returned if the length is negative.

Chapter 4

Imaging-Processing Specific API Conventions

4.1 Function Naming

Image processing related functions use a number of suffixes to indicate various different flavors of a primitive beyond just different data types. The flavor suffix uses the following abbreviations:

- "A" if the image is a 4 channel image this indicates the result alpha channel is not affected by the primitive.
- "Cn" the image consists of n channel packed pixels, where n can be 1, 2, 3 or 4.
- "Pn" the image consists of n separate image planes, where n can be 1, 2, 3 or 4.
- "C" (following the channel information) indicates that the primitive only operates on one of the color channels, the "channel-of-interest". All other output channels are not affected by the primitive.
- "I" indicates that the primitive works "in-place". In this case the image-data pointer is usually named "pSrcDst" to indicate that the image data serves as source and destination at the same time.
- "M" indicates "masked operation". These types of primitives have an additional "mask image" as input. Each pixel in the destination image corresponds to a pixel in the mask image. Only pixels with a corresponding non-zero mask pixel are being processed.
- "R" indicates the primitive operates only on a rectangular "region-of-interest" or "ROI". All ROI primitives take an additional input parameter of type [NppiSize](#), which specifies the width and height of the rectangular region that the primitive should process. For details on how primitives operate on ROIs see: [Region-of-Interest \(ROI\)](#).
- "Sfs" indicates the result values are processed by fixed scaling and saturation before they're written out.

The suffixes above always appear in alphabetical order. E.g. a 4 channel primitive not affecting the alpha channel with masked operation, in place and with scaling/saturation and ROI would have the postfix: "AC4IMRSfs".

4.2 Image Data

Image data is passed to and from NPPI primitives via a pair of parameters:

1. A pointer to the image's underlying data type.
2. A line step in bytes (also sometimes called line stride).

The general idea behind this fairly low-level way of passing image data is ease-of-adoption into existing software projects:

- Passing a raw pointer to the underlying pixel data type, rather than structured (by color) channel pixel data allows usage of the function in a wide variety of situations avoiding risky type cast or expensive image data copies.
- Passing the data pointer and line step individually rather than a higher-level image struct again allows for easy adoption by not requiring a specific image representation and thus avoiding awkward packing and unpacking of image data from the host application to an NPP specific image representation.

4.2.1 Line Step

The line step (also called "line stride" or "row step") allows lines of oddly sized images to start on well-aligned addresses by adding a number of unused bytes at the ends of the lines. This type of line padding has been common practice in digital image processing for a long time and is not particular to GPU image processing.

The line step is the number of bytes in a line **including the padding**. An other way to interpret this number is to say that it is the number of bytes between the first pixel of successive rows in the image, or generally the number of bytes between two neighboring pixels in any column of pixels.

The general reason for the existence of the line step it is that uniformly aligned rows of pixel enable optimizations of memory-access patterns.

Even though all functions in NPP will work with arbitrarily aligned images, best performance can only be achieved with well aligned image data. Any image data allocated with the NPP image allocators or the 2D memory allocators in the CUDA runtime, is well aligned.

Particularly on older CUDA capable GPUs it is likely that the performance decrease for misaligned data is substantial (orders of magnitude).

All image data passed to NPPI primitives requires a line step to be provided. It is important to keep in mind that this line step is always specified in terms of bytes, not pixels.

4.2.2 Parameter Names for Image Data

There are three general cases of image-data passing throughout NPP detailed in the following sections.

4.2.2.1 Passing Source-Image Data

Those are images consumed by the algorithm.

4.2.2.1.1 Source-Image Pointer

The source image data is generally passed via a pointer named

```
pSrc
```

The source image pointer is generally defined constant, enforcing that the primitive does not change any image data pointed to by that pointer. E.g.

```
nppiPrimitive_32s_C1R(const Npp32s * pSrc, ...)
```

In case the primitive consumes multiple images as inputs the source pointers are numbered like this:

```
pSrc1, pSrc2, ...
```

4.2.2.1.2 Source-Planar-Image Pointer Array

The planar source image data is generally passed via an array of pointers named

```
pSrc[]
```

The planar source image pointer array is generally defined a constant array of constant pointers, enforcing that the primitive does not change any image data pointed to by those pointers. E.g.

```
nppiPrimitive_8u_P3R(const Npp8u * const pSrc[3], ...)
```

Each pointer in the array points to a different image plane.

4.2.2.1.3 Source-Planar-Image Pointer

The multiple plane source image data is passed via a set of pointers named

```
pSrc1, pSrc2, ...
```

The planar source image pointer is generally defined as one of a set of constant pointers with each pointer pointing to a different input image plane.

4.2.2.1.4 Source-Image Line Step

The source image line step is the number of bytes between successive rows in the image. The source image line step parameter is

```
nSrcStep
```

or in the case of multiple source images

```
nSrcStep1, nSrcStep2, ...
```

4.2.2.1.5 Source-Planar-Image Line Step Array

The source planar image line step array is an array where each element of the array contains the number of bytes between successive rows for a particular plane in the input image. The source planar image line step array parameter is

```
rSrcStep[]
```

4.2.2.1.6 Source-Planar-Image Line Step

The source planar image line step is the number of bytes between successive rows in a particular plane of the multiplane input image. The source planar image line step parameter is

```
nSrcStep1, nSrcStep2, ...
```

4.2.2.2 Passing Destination-Image Data

Those are images produced by the algorithm.

4.2.2.2.1 Destination-Image Pointer

The destination image data is generally passed via a pointer named

```
pDst
```

In case the primitive generates multiple images as outputs the destination pointers are numbered like this:

```
pDst1, pDst2, ...
```

4.2.2.2.2 Destination-Planar-Image Pointer Array

The planar destination image data pointers are generally passed via an array of pointers named

```
pDst[]
```

Each pointer in the array points to a different image plane.

4.2.2.2.3 Destination-Planar-Image Pointer

The destination planar image data is generally passed via a pointer to each plane of a multiplane output image named

```
pDst1, pDst2, ...
```

4.2.2.2.4 Destination-Image Line Step

The destination image line step parameter is

```
nDstStep
```

or in the case of multiple destination images

```
nDstStep1, nDstStep2, ...
```

4.2.2.2.5 Destination-Planar-Image Line Step Array

The destination planar image line step array is an array where each element of the array contains the number of bytes between successive rows for a particular plane in the output image. The destination planar image line step array parameter is

```
rDstStep[]
```

4.2.2.2.6 Destination-Planar-Image Line Step

The destination planar image line step is the number of bytes between successive rows for a particular plane in a multiplane output image. The destination planar image line step parameter is

```
nDstStep1, nDstStep2, ...
```

4.2.2.3 Passing In-Place Image Data

4.2.2.3.1 In-Place Image Pointer

In the case of in-place processing, source and destination are served by the same pointer and thus pointers to in-place image data are called:

```
pSrcDst
```

4.2.2.3.2 In-Place-Image Line Step

The in-place line step parameter is

```
nSrcDstStep
```

4.2.2.4 Passing Mask-Image Data

Some image processing primitives have variants supporting [Masked Operation](#).

4.2.2.4.1 Mask-Image Pointer

The mask-image data is generally passed via a pointer named

```
pMask
```

4.2.2.4.2 Mask-Image Line Step

The mask-image line step parameter is

```
nMaskStep
```

4.2.2.5 Passing Channel-of-Interest Data

Some image processing primitives support [Channel-of-Interest API](#).

4.2.2.5.1 Channel_of_Interest Number

The channel-of-interest data is generally an integer (either 1, 2, or 3):

```
nCOI
```

4.2.3 Image Data Alignment Requirements

NPP requires pixel data to adhere to certain alignment constraints: For 2 and 4 channel images the following alignment requirement holds: `data_pointer % (#channels * sizeof(channel type)) == 0`. E.g. a 4 channel image with underlying type `Npp8u` (8-bit unsigned) would require all pixels to fall on addresses that are multiples of 4 (4 channels * 1 byte size).

As a logical consequence of all pixels being aligned to their natural size the image line steps of 2 and 4 channel images also need to be multiples of the pixel size.

1 and 3 channel images only require that pixel pointers are aligned to the underlying data type, i.e. `pData % sizeof(data type) == 0`. And consequentially line steps are also held to this requirement.

4.2.4 Image Data Related Error Codes

All NPPI primitives operating on image data validate the image-data pointer for proper alignment and test that the point is not null. They also validate the line stride for proper alignment and guard against the step being less or equal to 0. Failed validation results in one of the following error codes being returned and the primitive not being executed:

- `NPP_STEP_ERROR` is returned if the data step is 0 or negative.
- `NPP_NOT_EVEN_STEP_ERROR` is returned if the line step is not a multiple of the pixel size for 2 and 4 channel images.
- `NPP_NULL_POINTER_ERROR` is returned if the image-data pointer is 0 (NULL).
- `NPP_ALIGNMENT_ERROR` if the image-data pointer address is not a multiple of the pixel size for 2 and 4 channel images.

4.3 Region-of-Interest (ROI)

In practice processing a rectangular sub-region of an image is often more common than processing complete images. The vast majority of NPP's image-processing primitives allow for processing of such sub regions also referred to as regions-of-interest or ROIs.

All primitives supporting ROI processing are marked by a "R" in their name suffix. In most cases the ROI is passed as a single `NppiSize` struct, which provides the width and height of the ROI. This raises the question how the primitive knows where in the image this rectangle of (width, height) is located. The "start pixel" of the ROI is implicitly given by the image-data pointer. I.e. instead of explicitly passing a pixel coordinate for the upper-right corner, the user simply offsets the image-data pointers to point to the first pixel of the ROI.

In practice this means that for an image (`pSrc`, `nSrcStep`) and the start-pixel of the ROI being at location (`xROI`, `yROI`), one would pass

```
pSrcOffset = pSrc + yROI * nSrcStep + xROI * PixelSize;
```

as the image-data source to the primitive. `PixelSize` is typically computed as

```
PixelSize = NumberOfColorChannels * sizeof(PixelDataType).
```

E.g. for a primitive like `nppiSet_16s_C4R()` we would have

- `NumberOfColorChannels == 4;`
- `sizeof(Npp16s) == 2;`
- and thus `PixelSize = 4 * 2 = 8;`

4.3.1 ROI Related Error Codes

All NPPI primitives operating on ROIs of image data validate the ROI size and image's step size. Failed validation results in one of the following error codes being returned and the primitive not being executed:

- `NPP_SIZE_ERROR` is returned if either the ROI width or ROI height are negative.
- `NPP_STEP_ERROR` is returned if the ROI width exceeds the image's line step. In mathematical terms $(\text{widthROI} * \text{PixelSize}) > \text{nLinStep}$ indicates an error.

4.4 Masked Operation

Some primitive support masked operation. An "M" in the suffix of those variants indicates masked operation. Primitives supporting masked operation consume an additional input image provided via a [Mask-Image Pointer](#) and [Mask-Image Line Step](#). The mask image is interpreted by these primitives as a boolean image. The values of type `Npp8u` are interpreted as boolean values where a values of 0 indicates false, any non-zero values true.

Unless otherwise indicated the operation is only performed on pixels where its spatially corresponding mask pixel is true (non-zero). E.g. a masked copy operation would only copy those pixels in the ROI that have corresponding non-zero mask pixels.

4.5 Channel-of-Interest API

Some primitives allow restricting operations to a single channel of interest within a multi-channel image. These primitives are suffixed with the letter "C" (after the channel information, e.g. `nppiCopy_8u_C3CR(...)`). The channel-of-interest is generally selected by offsetting the image-data pointer to point directly to the channel- of-interest rather than the base of the first pixel in the ROI. Some primitives also explicitly specify the selected channel number and pass it via an integer, e.g. `nppiMean_StdDev_8u_C3CR(...)`.

4.5.1 Select-Channel Source-Image Pointer

This is a pointer to the channel-of-interest within the first pixel of the source image. E.g. if `pSrc` is the pointer to the first pixel inside the ROI of a three channel image. Using the appropriate select-channel copy primitive one could copy the second channel of this source image into the first channel of a destination image given by `pDst` by offsetting the pointer by one:

```
nppiCopy_8u_C3CR(pSrc + 1, nSrcStep, pDst, nDstStep, oSizeROI);
```

4.5.2 Select-Channel Source-Image

Some primitives allow the user to select the channel-of-interest by specifying the channle number (`nCOI`). This approach is typically used in the image statistical functions. For example,

```
nppiMean_StdDev_8u_C3CR(pSrc, nSrcStep, oSizeROI, nCOI, pDeviceBuffer, pMean, pStdDev );
```

The channel-of-interest number can be either 1, 2, or 3.

4.5.3 Select-Channel Destination-Image Pointer

This is a pointer to the channel-of-interest within the first pixel of the destination image. E.g. if `pDst` is the pointer to the first pixel inside the ROI of a three channel image. Using the appropriate select-channel

copy primitive one could copy data into the second channel of this destination image from the first channel of a source image given by pSrc by offsetting the destination pointer by one:

```
nppiCopy_8u_C3CR(pSrc, nSrcStep, pDst + 1, nDstStep, oSizeROI);
```

4.6 Source-Image Sampling

A large number of NPP image-processing functions consume at least one source image and produce an output image (e.g. [nppiAddC_8u_C1RSfs\(\)](#) or [nppiFilterBox_8u_C1R\(\)](#)). All NPP functions falling into this category also operate on ROIs (see [Region-of-Interest \(ROI\)](#)) which for these functions should be considered to describe the destination ROI. In other words the ROI describes a rectangular region in the destination image and all pixels inside of this region are being written by the function in question.

In order to use such functions successfully it is important to understand how the user defined destination ROI affects which pixels in the input image(s) are being read by the algorithms. To simplify the discussion of ROI propagation (i.e. given a destination ROI, what are the ROIs in the source(s)), it makes sense to distinguish two major cases:

1. Point-Wise Operations: These are primitives like [nppiAddC_8u_C1RSfs\(\)](#). Each output pixel requires exactly one input pixel to be read.
2. Neighborhood Operations: These are primitives like [nppiFilterBox_8u_C1R\(\)](#), which require a group of pixels from the source image(s) to be read in order to produce a single output.

4.6.1 Point-Wise Operations

As mentioned above, point-wise operations consume a single pixel from the input image (or a single pixel from each input image, if the operation in question has more than one input image) in order to produce a single output pixel.

4.6.2 Neighborhood Operations

In the case of neighborhood operations a number of input pixels (a "neighborhood" of pixels) is read in the input image (or images) in order to compute a single output pixel. All of the functions for [Filtering Functions](#) and [Morphological Operations](#) are neighborhood operations.

Most of these functions have parameters that affect the size and relative location of the neighborhood: a mask-size structure and an anchor-point structure. Both parameters are described in more detail in the next subsections.

4.6.2.1 Mask-Size Parameter

Many NPP neighborhood operations allow the user to specify the size of the neighborhood via a parameter usually named oMaskSize of type [NppiSize](#). In those cases the neighborhood of pixels read from the source(s) is exactly the size of the mask. Assuming the mask is anchored at location (0, 0) (see [Anchor-Point Parameter](#) below) and has a size of (w, h), i.e.

```
assert(oMaskSize.w == w);  
assert(oMaskSize.h == h);  
assert(oAnchor.x == 0);  
assert(oAnchor.y == 0);
```

a neighborhood operation would read the following source pixels in order to compute destination pixel $D_{i,j}$:

$$\begin{array}{cccc} S_{i,j} & S_{i,j+1} & \cdots & S_{i,j+w-1} \\ S_{i+1,j} & S_{i+1,j+1} & \cdots & S_{i+1,j+w-1} \\ \vdots & \vdots & \ddots & \vdots \\ S_{i+h-1,j} & S_{i+h-1,j+1} & \cdots & S_{i+h-1,j+w-1} \end{array}$$

4.6.2.2 Anchor-Point Parameter

Many NPP primitives performing neighborhood operations allow the user to specify the relative location of the neighborhood via a parameter usually named `oAnchor` of type [NppiPoint](#). Using the anchor a developer can choose the position of the mask (see [Mask-Size Parameter](#)) relative to current pixel index.

Using the same example as in [Mask-Size Parameter](#), but this time with an anchor position of (a, b):

```
assert(oMaskSize.w == w);
assert(oMaskSize.h == h);
assert(oAnchor.x == a);
assert(oAnchor.y == b);
```

the following pixels from the source image would be read:

$$\begin{array}{cccc} S_{i-a,j-b} & S_{i-a,j-b+1} & \cdots & S_{i-a,j-b+w-1} \\ S_{i-a+1,j-b} & S_{i-a+1,j-b+1} & \cdots & S_{i-a+1,j-b+w-1} \\ \vdots & \vdots & \ddots & \vdots \\ S_{i-a+h-1,j-b} & S_{i-a+h-1,j-b+1} & \cdots & S_{i-a+h-1,j-b+w-1} \end{array}$$

4.6.2.3 Sampling Beyond Image Boundaries

NPP primitives in general and NPP neighborhood operations in particular require that all pixel locations read and written are valid and within the boundaries of the respective images. Sampling outside of the defined image data regions results in undefined behavior and may lead to system instability.

This poses a problem in practice: when processing full-size images one cannot choose the destination ROI to be the same size as the source image. Because neighborhood operations read pixels from an enlarged source ROI, the destination ROI must be shrunk so that the expanded source ROI does not exceed the source image's size.

For cases where this "shrinking" of the destination image size is unacceptable, NPP provides a set of border-expanding Copy primitives. E.g. [nppiCopyConstBorder_8u_C1R\(\)](#), [nppiCopyReplicateBorder_8u_C1R\(\)](#) and [nppiCopyWrapBorder_8u_C1R\(\)](#). The user can use these primitives to "expand" the source image's size using one of the three expansion modes. The expanded image can then be safely passed to a neighborhood operation producing a full-size result.

Chapter 5

Module Index

5.1 Modules

Here is a list of all modules:

NPP Core	31
NPP Type Definitions and Constants	34
Basic NPP Data Types	47
NPP Image Processing	51
Arithmetic and Logical Operations	52
Arithmetic Operations	53
AddC	55
MulC	81
MulCScale	107
SubC	114
DivC	140
AbsDiffC	166
Add	168
AddSquare	197
AddProduct	200
AddWeighted	204
Mul	208
MulScale	237
Sub	246
Div	276
Div_Round	305
Abs	320
AbsDiff	327
Sqr	330
Sqrt	344
Ln	356
Exp	363
Logical Operations	370
AndC	371
OrC	382
XorC	393
RShiftC	404
LShiftC	421

And	432
Or	444
Xor	456
Not	468
Alpha Composition	472
AlphaCompC	473
AlphaPremulC	481
AlphaComp	488
AlphaPremul	495
Color and Sampling Conversion	497
Color Model Conversion	498
Color Sampling Format Conversion	572
Color Gamma Correction	600
Complement Color Key	606
Color Processing	609
Compression	690
Quantization Functions	692
Labeling and Segmentation	698
GraphCut	699
Data Exchange and Initialization	706
Set	707
Copy	737
Convert	784
Scale	828
Copy Constant Border	843
Copy Replicate Border	856
Copy Wrap Border	868
Copy Sub-Pixel	881
Duplicate Channel	892
Transpose	899
Swap Channels	906
Filtering Functions	924
1D Linear Filter	925
1D Window Sum	1007
Convolution	1009
2D Fixed Linear Filters	1036
Rank Filters	1045
Fixed Filters	1061
Geometry Transforms	1089
ResizeSqrPixel	1091
Resize	1113
Remap	1125
Rotate	1147
Mirror	1156
Affine Transforms	1173
Perspective Transform	1223
Linear Transforms	1269
Fourier Transforms	1270
Morphological Operations	1272
Dilation	1273
Erode	1280
Dilate3x3	1287
Erode3x3	1293

Statistical Operations	1299
Sum	1301
Min	1316
MinIndx	1329
Max	1343
MaxIndx	1356
MinMax	1370
MinMaxIndx	1384
Mean	1401
Mean_StdDev	1422
Image Norms	1438
Norm_Inf	1440
Norm_L1	1462
Norm_L2	1483
NormDiff_Inf	1504
NormDiff_L1	1527
NormDiff_L2	1550
NormRel_Inf	1573
NormRel_L1	1596
NormRel_L2	1619
DotProd	1642
CountInRange.	1667
MaxEvery	1673
MinEvery	1680
Integral	1687
SqrIntegral	1689
RectStdDev	1692
HistogramEven	1695
HistogramRange	1708
Image Proximity	1724
SqrDistanceFull_Norm	1727
SqrDistanceSame_Norm	1738
SqrDistanceValid_Norm	1749
CrossCorrFull_Norm	1760
CrossCorrSame_Norm	1771
CrossCorrValid_Norm	1782
CrossCorrValid	1793
CrossCorrFull_NormLevel	1796
CrossCorrSame_NormLevel	1816
CrossCorrValid_NormLevel	1836
Image Quality Index	1856
Memory Management	1865
Threshold and Compare Operations	1877
Threshold Operations	1878
Compare Operations	1967
NPP Signal Processing	1990
Arithmetic and Logical Operations	1991
Arithmetic Operations	1992
AddC	1994
AddProductC	2003
MulC	2004
SubC	2014
SubCRev	2023

DivC	2032
DivCRev	2039
Add	2041
AddProduct	2053
Mul	2057
Sub	2070
Div	2080
Div_Round	2088
Abs	2091
Sqr	2094
Sqrt	2100
Cubrt	2108
Exp	2109
Ln	2113
10Log10	2117
SumLn	2118
Arctan	2122
Normalize	2124
Cauchy, CauchyD, and CauchyDD2	2127
Logical And Shift Operations	2129
AndC	2130
And	2133
OrC	2136
Or	2139
XorC	2142
Xor	2145
Not	2148
LShiftC	2151
RShiftC	2155
Conversion Functions	2159
Convert	2160
Threshold	2163
Filtering Functions	2188
Integral	2189
Initialization	2190
Set	2191
Zero	2195
Copy	2199
Statistical Functions	2203
MinEvery And MaxEvery Functions	2204
Sum	2208
Maximum	2215
Minimum	2225
Mean	2235
Standard Deviation	2241
Mean And Standard Deviation	2244
Minimum_Maximum	2248
Infinity Norm	2260
L1 Norm	2265
L2 Norm	2271
Infinity Norm Diff	2277
L1 Norm Diff	2282
L2 Norm Diff	2288

Dot Product	2294
Count In Range	2314
Count Zero Crossings	2315
Memory Management	2317
Malloc	2318
Free	2323

Chapter 6

Data Structure Index

6.1 Data Structures

Here are the data structures with brief descriptions:

NPP_ALIGN_16 (Complex Number This struct represents a long long complex number)	2325
NPP_ALIGN_8 (Complex Number This struct represents an unsigned int complex number) . .	2327
NppiHaarBuffer	2329
NppiHaarClassifier_32f	2330
NppiPoint (2D Point)	2331
NppiRect (2D Rectangle This struct contains position and size information of a rectangle in two space)	2332
NppiSize (2D Size This struct typically represents the size of a a rectangular region in two space)	2333
NppLibraryVersion	2334

Chapter 7

Module Documentation

7.1 NPP Core

Basic functions for library management, in particular library version and device property query functions.

Functions

- const [NppLibraryVersion](#) * [nppGetLibVersion](#) (void)
Get the NPP library version.
- [NppGpuComputeCapability](#) [nppGetGpuComputeCapability](#) (void)
What CUDA compute model is supported by the active CUDA device?
- int [nppGetGpuNumSMs](#) (void)
Get the number of Streaming Multiprocessors (SM) on the active CUDA device.
- int [nppGetMaxThreadsPerBlock](#) (void)
Get the maximum number of threads per block on the active CUDA device.
- int [nppGetMaxThreadsPerSM](#) (void)
Get the maximum number of threads per SM for the active GPU.
- const char * [nppGetGpuName](#) (void)
Get the name of the active CUDA device.
- [cudaStream_t](#) [nppGetStream](#) (void)
Get the NPP CUDA stream.
- void [nppSetStream](#) ([cudaStream_t](#) hStream)
Set the NPP CUDA stream.

7.1.1 Detailed Description

Basic functions for library management, in particular library version and device property query functions.

7.1.2 Function Documentation

7.1.2.1 `NppGpuComputeCapability nppGetGpuComputeCapability (void)`

What CUDA compute model is supported by the active CUDA device?

Before trying to call any NPP functions, the user should make a call this function to ensure that the current machine has a CUDA capable device.

Returns:

An enum value representing if a CUDA capable device was found and what level of compute capabilities it supports.

7.1.2.2 `const char* nppGetGpuName (void)`

Get the name of the active CUDA device.

Returns:

Name string of the active graphics-card/compute device in a system.

7.1.2.3 `int nppGetGpuNumSMs (void)`

Get the number of Streaming Multiprocessors (SM) on the active CUDA device.

Returns:

Number of SMs of the default CUDA device.

7.1.2.4 `const NppLibraryVersion* nppGetLibVersion (void)`

Get the NPP library version.

Returns:

A struct containing separate values for major and minor revision and build number.

7.1.2.5 `int nppGetMaxThreadsPerBlock (void)`

Get the maximum number of threads per block on the active CUDA device.

Returns:

Maximum number of threads per block on the active CUDA device.

7.1.2.6 int nppGetMaxThreadsPerSM (void)

Get the maximum number of threads per SM for the active GPU.

Returns:

Maximum number of threads per SM for the active GPU

7.1.2.7 cudaStream_t nppGetStream (void)

Get the NPP CUDA stream.

NPP enables concurrent device tasks via a global stream state variable. The NPP stream by default is set to stream 0, i.e. non-concurrent mode. A user can set the NPP stream to any valid CUDA stream. All CUDA commands issued by NPP (e.g. kernels launched by the NPP library) are then issued to that NPP stream.

7.1.2.8 void nppSetStream (cudaStream_t *hStream*)

Set the NPP CUDA stream.

See also:

[nppGetStream\(\)](#)

7.2 NPP Type Definitions and Constants

Data Structures

- struct [NppLibraryVersion](#)
- struct [NppiPoint](#)
2D Point
- struct [NppiSize](#)
2D Size This struct typically represents the size of a rectangular region in two space.
- struct [NppiRect](#)
2D Rectangle This struct contains position and size information of a rectangle in two space.
- struct [NppiHaarClassifier_32f](#)
- struct [NppiHaarBuffer](#)

Modules

- [Basic NPP Data Types](#)

Defines

- #define [NPP_MIN_8U](#) (0)
Minimum 8-bit unsigned integer.
- #define [NPP_MAX_8U](#) (255)
Maximum 8-bit unsigned integer.
- #define [NPP_MIN_16U](#) (0)
Minimum 16-bit unsigned integer.
- #define [NPP_MAX_16U](#) (65535)
Maximum 16-bit unsigned integer.
- #define [NPP_MIN_32U](#) (0)
Minimum 32-bit unsigned integer.
- #define [NPP_MAX_32U](#) (4294967295U)
Maximum 32-bit unsigned integer.
- #define [NPP_MIN_64U](#) (0)
Minimum 64-bit unsigned integer.
- #define [NPP_MAX_64U](#) (18446744073709551615ULL)
Maximum 64-bit unsigned integer.
- #define [NPP_MIN_8S](#) (-127 - 1)
Minimum 8-bit signed integer.

- #define `NPP_MAX_8S` (127)
Maximum 8-bit signed integer.
- #define `NPP_MIN_16S` (-32767 - 1)
Minimum 16-bit signed integer.
- #define `NPP_MAX_16S` (32767)
Maximum 16-bit signed integer.
- #define `NPP_MIN_32S` (-2147483647 - 1)
Minimum 32-bit signed integer.
- #define `NPP_MAX_32S` (2147483647)
Maximum 32-bit signed integer.
- #define `NPP_MAX_64S` (9223372036854775807LL)
Maximum 64-bit signed integer.
- #define `NPP_MIN_64S` (-9223372036854775807LL - 1)
Minimum 64-bit signed integer.
- #define `NPP_MINABS_32F` (1.175494351e-38f)
Smallest positive 32-bit floating point value.
- #define `NPP_MAXABS_32F` (3.402823466e+38f)
Largest positive 32-bit floating point value.
- #define `NPP_MINABS_64F` (2.2250738585072014e-308)
Smallest positive 64-bit floating point value.
- #define `NPP_MAXABS_64F` (1.7976931348623158e+308)
Largest positive 64-bit floating point value.

Enumerations

- enum `NppiInterpolationMode` {
 `NPPI_INTER_UNDEFINED` = 0,
 `NPPI_INTER_NN` = 1,
 `NPPI_INTER_LINEAR` = 2,
 `NPPI_INTER_CUBIC` = 4,
 `NPPI_INTER_CUBIC2P_BSPLINE`,
 `NPPI_INTER_CUBIC2P_CATMULLROM`,
 `NPPI_INTER_CUBIC2P_B05C03`,
 `NPPI_INTER_SUPER` = 8,
 `NPPI_INTER_LANCZOS` = 16,
 `NPPI_SMOOTH_EDGE` = (1 << 31) }

Filtering methods.

- enum `NppiMaskSize` {
`NPP_MASK_SIZE_1_X_3`,
`NPP_MASK_SIZE_1_X_5`,
`NPP_MASK_SIZE_3_X_1` = 100,
`NPP_MASK_SIZE_5_X_1`,
`NPP_MASK_SIZE_3_X_3` = 200,
`NPP_MASK_SIZE_5_X_5` }

Fixed filter-kernel sizes.

- enum `NppStatus` {
`NPP_NOT_SUPPORTED_MODE_ERROR` = -9999,
`NPP_INVALID_HOST_POINTER_ERROR` = -1032,
`NPP_INVALID_DEVICE_POINTER_ERROR` = -1031,
`NPP_LUT_PALETTE_BITSIZE_ERROR` = -1030,
`NPP_ZC_MODE_NOT_SUPPORTED_ERROR` = -1028,
`NPP_NOT_SUFFICIENT_COMPUTE_CAPABILITY` = -1027,
`NPP_TEXTURE_BIND_ERROR` = -1024,
`NPP_WRONG_INTERSECTION_ROI_ERROR` = -1020,
`NPP_HAAR_CLASSIFIER_PIXEL_MATCH_ERROR` = -1006,
`NPP_MEMFREE_ERR` = -1005,
`NPP_MEMSET_ERR` = -1004,
`NPP_MEMCPY_ERROR` = -1003,
`NPP_ALIGNMENT_ERROR` = -1002,
`NPP_CUDA_KERNEL_EXECUTION_ERROR` = -1000,
`NPP_ROUND_MODE_NOT_SUPPORTED_ERROR` = -213,
`NPP_QUALITY_INDEX_ERROR` = -210,
`NPP_RESIZE_NO_OPERATION_ERROR` = -201,
`NPP_NOT_EVEN_STEP_ERROR` = -108,
`NPP_HISTOGRAM_NUMBER_OF_LEVELS_ERROR` = -107,
`NPP_LUT_NUMBER_OF_LEVELS_ERROR` = -106,
`NPP_CHANNEL_ORDER_ERROR` = -60,
`NPP_ZERO_MASK_VALUE_ERROR` = -59,
`NPP_QUADRANGLE_ERROR` = -58,
`NPP_RECTANGLE_ERROR` = -57,
`NPP_COEFFICIENT_ERROR` = -56,
`NPP_NUMBER_OF_CHANNELS_ERROR` = -53,
`NPP_COI_ERROR` = -52,
`NPP_DIVISOR_ERROR` = -51,
`NPP_CHANNEL_ERROR` = -47,
`NPP_STRIDE_ERROR` = -37,

```
NPP_ANCHOR_ERROR = -34,  
NPP_MASK_SIZE_ERROR = -33,  
NPP_RESIZE_FACTOR_ERROR = -23,  
NPP_INTERPOLATION_ERROR = -22,  
NPP_MIRROR_FLIP_ERR = -21,  
NPP_MOMENT_00_ZERO_ERROR = -20,  
NPP_THRESHOLD_NEGATIVE_LEVEL_ERROR = -19,  
NPP_THRESHOLD_ERROR = -18,  
NPP_CONTEXT_MATCH_ERROR = -17,  
NPP_FFT_FLAG_ERROR = -16,  
NPP_FFT_ORDER_ERROR = -15,  
NPP_STEP_ERROR = -14,  
NPP_SCALE_RANGE_ERROR = -13,  
NPP_DATA_TYPE_ERROR = -12,  
NPP_OUT_OFF_RANGE_ERROR = -11,  
NPP_DIVIDE_BY_ZERO_ERROR = -10,  
NPP_MEMORY_ALLOCATION_ERR = -9,  
NPP_NULL_POINTER_ERROR = -8,  
NPP_RANGE_ERROR = -7,  
NPP_SIZE_ERROR = -6,  
NPP_BAD_ARGUMENT_ERROR = -5,  
NPP_NO_MEMORY_ERROR = -4,  
NPP_NOT_IMPLEMENTED_ERROR = -3,  
NPP_ERROR = -2,  
NPP_ERROR_RESERVED = -1,  
NPP_NO_ERROR = 0,  
NPP_SUCCESS = NPP_NO_ERROR,  
NPP_NO_OPERATION_WARNING = 1,  
NPP_DIVIDE_BY_ZERO_WARNING = 6,  
NPP_AFFINE_QUAD_INCORRECT_WARNING = 28,  
NPP_WRONG_INTERSECTION_ROI_WARNING = 29,  
NPP_WRONG_INTERSECTION_QUAD_WARNING = 30,  
NPP_DOUBLE_SIZE_WARNING = 35,  
NPP_MISALIGNED_DST_ROI_WARNING = 10000 }
```

Error Status Codes.

- enum NppGpuComputeCapability {
NPP_CUDA_UNKNOWN_VERSION = -1,
NPP_CUDA_NOT_CAPABLE,
NPP_CUDA_1_0,
NPP_CUDA_1_1,

- NPP_CUDA_1_2,
- NPP_CUDA_1_3,
- NPP_CUDA_2_0,
- NPP_CUDA_2_1,
- NPP_CUDA_3_0,
- NPP_CUDA_3_5 }
- enum NppiAxis {
 - NPP_HORIZONTAL_AXIS,
 - NPP_VERTICAL_AXIS,
 - NPP_BOTH_AXIS }
- enum NppCmpOp {
 - NPP_CMP_LESS,
 - NPP_CMP_LESS_EQ,
 - NPP_CMP_EQ,
 - NPP_CMP_GREATER_EQ,
 - NPP_CMP_GREATER }
- enum NppRoundMode {
 - NPP_RND_NEAR,
 - NPP_ROUND_NEAREST_TIES_TO_EVEN = NPP_RND_NEAR,
 - NPP_RND_FINANCIAL,
 - NPP_ROUND_NEAREST_TIES_AWAY_FROM_ZERO = NPP_RND_FINANCIAL,
 - NPP_RND_ZERO,
 - NPP_ROUND_TOWARD_ZERO = NPP_RND_ZERO }

Rounding Modes.
- enum NppiBorderType {
 - NPP_BORDER_UNDEFINED = 0,
 - NPP_BORDER_NONE = NPP_BORDER_UNDEFINED,
 - NPP_BORDER_CONSTANT = 1,
 - NPP_BORDER_REPLICATE = 2,
 - NPP_BORDER_WRAP = 3 }
- enum NppHintAlgorithm {
 - NPP_ALG_HINT_NONE,
 - NPP_ALG_HINT_FAST,
 - NPP_ALG_HINT_ACCURATE }
- enum NppiAlphaOp {
 - NPPI_OP_ALPHA_OVER,
 - NPPI_OP_ALPHA_IN,
 - NPPI_OP_ALPHA_OUT,
 - NPPI_OP_ALPHA_ATOP,
 - NPPI_OP_ALPHA_XOR,
 - NPPI_OP_ALPHA_PLUS,

```
NPPI_OP_ALPHA_OVER_PREMUL,  
NPPI_OP_ALPHA_IN_PREMUL,  
NPPI_OP_ALPHA_OUT_PREMUL,  
NPPI_OP_ALPHA_ATOP_PREMUL,  
NPPI_OP_ALPHA_XOR_PREMUL,  
NPPI_OP_ALPHA_PLUS_PREMUL,  
NPPI_OP_ALPHA_PREMUL }  
• enum NppsZCType {  
    nppZCR,  
    nppZCXor,  
    nppZCC }
```

7.2.1 Define Documentation

7.2.1.1 #define NPP_MAX_16S (32767)

Maximum 16-bit signed integer.

7.2.1.2 #define NPP_MAX_16U (65535)

Maximum 16-bit unsigned integer.

7.2.1.3 #define NPP_MAX_32S (2147483647)

Maximum 32-bit signed integer.

7.2.1.4 #define NPP_MAX_32U (4294967295U)

Maximum 32-bit unsigned integer.

7.2.1.5 #define NPP_MAX_64S (9223372036854775807LL)

Maximum 64-bit signed integer.

7.2.1.6 #define NPP_MAX_64U (18446744073709551615ULL)

Maximum 64-bit unsigned integer.

7.2.1.7 #define NPP_MAX_8S (127)

Maximum 8-bit signed integer.

7.2.1.8 #define NPP_MAX_8U (255)

Maximum 8-bit unsigned integer.

7.2.1.9 #define NPP_MAXABS_32F (3.402823466e+38f)

Largest positive 32-bit floating point value.

7.2.1.10 #define NPP_MAXABS_64F (1.7976931348623158e+308)

Largest positive 64-bit floating point value.

7.2.1.11 #define NPP_MIN_16S (-32767 - 1)

Minimum 16-bit signed integer.

7.2.1.12 #define NPP_MIN_16U (0)

Minimum 16-bit unsigned integer.

7.2.1.13 #define NPP_MIN_32S (-2147483647 - 1)

Minimum 32-bit signed integer.

7.2.1.14 #define NPP_MIN_32U (0)

Minimum 32-bit unsigned integer.

7.2.1.15 #define NPP_MIN_64S (-9223372036854775807LL - 1)

Minimum 64-bit signed integer.

7.2.1.16 #define NPP_MIN_64U (0)

Minimum 64-bit unsigned integer.

7.2.1.17 #define NPP_MIN_8S (-127 - 1)

Minimum 8-bit signed integer.

7.2.1.18 #define NPP_MIN_8U (0)

Minimum 8-bit unsigned integer.

7.2.1.19 #define NPP_MINABS_32F (1.175494351e-38f)

Smallest positive 32-bit floating point value.

7.2.1.20 #define NPP_MINABS_64F (2.2250738585072014e-308)

Smallest positive 64-bit floating point value.

7.2.2 Enumeration Type Documentation**7.2.2.1 enum NppCmpOp**

Enumerator:

NPP_CMP_LESS
NPP_CMP_LESS_EQ
NPP_CMP_EQ
NPP_CMP_GREATER_EQ
NPP_CMP_GREATER

7.2.2.2 enum NppGpuComputeCapability

Enumerator:

NPP_CUDA_UNKNOWN_VERSION Indicates that the compute-capability query failed.
NPP_CUDA_NOT_CAPABLE Indicates that no CUDA capable device was found.
NPP_CUDA_1_0 Indicates that CUDA 1.0 capable device is machine's default device.
NPP_CUDA_1_1 Indicates that CUDA 1.1 capable device is machine's default device.
NPP_CUDA_1_2 Indicates that CUDA 1.2 capable device is machine's default device.
NPP_CUDA_1_3 Indicates that CUDA 1.3 capable device is machine's default device.
NPP_CUDA_2_0 Indicates that CUDA 2.0 capable device is machine's default device.
NPP_CUDA_2_1 Indicates that CUDA 2.1 capable device is machine's default device.
NPP_CUDA_3_0 Indicates that CUDA 3.0 capable device is machine's default device.
NPP_CUDA_3_5 Indicates that CUDA 3.5 or better is machine's default device.

7.2.2.3 enum NppHintAlgorithm

Enumerator:

NPP_ALG_HINT_NONE
NPP_ALG_HINT_FAST
NPP_ALG_HINT_ACCURATE

7.2.2.4 enum NppiAlphaOp

Enumerator:

NPPI_OP_ALPHA_OVER
NPPI_OP_ALPHA_IN
NPPI_OP_ALPHA_OUT

NPPI_OP_ALPHA_ATOP
NPPI_OP_ALPHA_XOR
NPPI_OP_ALPHA_PLUS
NPPI_OP_ALPHA_OVER_PREMUL
NPPI_OP_ALPHA_IN_PREMUL
NPPI_OP_ALPHA_OUT_PREMUL
NPPI_OP_ALPHA_ATOP_PREMUL
NPPI_OP_ALPHA_XOR_PREMUL
NPPI_OP_ALPHA_PLUS_PREMUL
NPPI_OP_ALPHA_PREMUL

7.2.2.5 enum NppiAxis

Enumerator:

NPP_HORIZONTAL_AXIS
NPP_VERTICAL_AXIS
NPP_BOTH_AXIS

7.2.2.6 enum NppiBorderType

Enumerator:

NPP_BORDER_UNDEFINED
NPP_BORDER_NONE
NPP_BORDER_CONSTANT
NPP_BORDER_REPLICATE
NPP_BORDER_WRAP

7.2.2.7 enum NppiInterpolationMode

Filtering methods.

Enumerator:

NPPI_INTER_UNDEFINED
NPPI_INTER_NN Nearest neighbor filtering.
NPPI_INTER_LINEAR Linear interpolation.
NPPI_INTER_CUBIC Cubic interpolation.
NPPI_INTER_CUBIC2P_BSPLINE Two-parameter cubic filter (B=1, C=0).
NPPI_INTER_CUBIC2P_CATMULLROM Two-parameter cubic filter (B=0, C=1/2).
NPPI_INTER_CUBIC2P_B05C03 Two-parameter cubic filter (B=1/2, C=3/10).
NPPI_INTER_SUPER Super sampling.
NPPI_INTER_LANCZOS Lanczos filtering.
NPPI_SMOOTH_EDGE Smooth edge filtering.

7.2.2.8 enum NppiMaskSize

Fixed filter-kernel sizes.

Enumerator:

NPP_MASK_SIZE_1_X_3
NPP_MASK_SIZE_1_X_5
NPP_MASK_SIZE_3_X_1
NPP_MASK_SIZE_5_X_1
NPP_MASK_SIZE_3_X_3
NPP_MASK_SIZE_5_X_5

7.2.2.9 enum NppRoundMode

Rounding Modes.

The enumerated rounding modes are used by a large number of NPP primitives to allow the user to specify the method by which fractional values are converted to integer values. Also see [Rounding Modes](#).

For NPP release 5.5 new names for the three rounding modes are introduced that are based on the naming conventions for rounding modes set forth in the IEEE-754 floating-point standard. Developers are encouraged to use the new, longer names to be future proof as the legacy names will be deprecated in subsequent NPP releases.

Enumerator:

NPP_RND_NEAR Round to the nearest even integer.

All fractional numbers are rounded to their nearest integer. The ambiguous cases (i.e. $\langle \text{integer} \rangle.5$) are rounded to the closest even integer. E.g.

- `roundNear(0.5) = 0`
- `roundNear(0.6) = 1`
- `roundNear(1.5) = 2`
- `roundNear(-1.5) = -2`

NPP_ROUND_NEAREST_TIES_TO_EVEN Alias name for [NPP_RND_NEAR](#).

NPP_RND_FINANCIAL Round according to financial rule.

All fractional numbers are rounded to their nearest integer. The ambiguous cases (i.e. $\langle \text{integer} \rangle.5$) are rounded away from zero. E.g.

- `roundFinancial(0.4) = 0`
- `roundFinancial(0.5) = 1`
- `roundFinancial(-1.5) = -2`

NPP_ROUND_NEAREST_TIES_AWAY_FROM_ZERO Alias name for [NPP_RND_FINANCIAL](#).

NPP_RND_ZERO Round towards zero (truncation).

All fractional numbers of the form $\langle \text{integer} \rangle.\langle \text{decimals} \rangle$ are truncated to $\langle \text{integer} \rangle$.

- `roundZero(1.5) = 1`
- `roundZero(1.9) = 1`
- `roundZero(-2.5) = -2`

NPP_ROUND_TOWARD_ZERO Alias name for [NPP_RND_ZERO](#).

7.2.2.10 enum NppStatus

Error Status Codes.

Almost all NPP function return error-status information using these return codes. Negative return codes indicate errors, positive return codes indicate warnings, a return code of 0 indicates success.

Enumerator:

NPP_NOT_SUPPORTED_MODE_ERROR

NPP_INVALID_HOST_POINTER_ERROR

NPP_INVALID_DEVICE_POINTER_ERROR

NPP_LUT_PALETTE_BITSIZE_ERROR

NPP_ZC_MODE_NOT_SUPPORTED_ERROR ZeroCrossing mode not supported.

NPP_NOT_SUFFICIENT_COMPUTE_CAPABILITY

NPP_TEXTURE_BIND_ERROR

NPP_WRONG_INTERSECTION_ROI_ERROR

NPP_HAAR_CLASSIFIER_PIXEL_MATCH_ERROR

NPP_MEMFREE_ERR

NPP_MEMSET_ERR

NPP_MEMCPY_ERROR

NPP_ALIGNMENT_ERROR

NPP_CUDA_KERNEL_EXECUTION_ERROR

NPP_ROUND_MODE_NOT_SUPPORTED_ERROR Unsupported round mode.

NPP_QUALITY_INDEX_ERROR Image pixels are constant for quality index.

NPP_RESIZE_NO_OPERATION_ERROR One of the output image dimensions is less than 1 pixel.

NPP_NOT_EVEN_STEP_ERROR Step value is not pixel multiple.

NPP_HISTOGRAM_NUMBER_OF_LEVELS_ERROR Number of levels for histogram is less than 2.

NPP_LUT_NUMBER_OF_LEVELS_ERROR Number of levels for LUT is less than 2.

NPP_CHANNEL_ORDER_ERROR Wrong order of the destination channels.

NPP_ZERO_MASK_VALUE_ERROR All values of the mask are zero.

NPP_QUADRANGLE_ERROR The quadrangle is nonconvex or degenerates into triangle, line or point.

NPP_RECTANGLE_ERROR Size of the rectangle region is less than or equal to 1.

NPP_COEFFICIENT_ERROR Unallowable values of the transformation coefficients.

NPP_NUMBER_OF_CHANNELS_ERROR Bad or unsupported number of channels.

NPP_COI_ERROR Channel of interest is not 1, 2, or 3.

NPP_DIVISOR_ERROR Divisor is equal to zero.

NPP_CHANNEL_ERROR Illegal channel index.

NPP_STRIDE_ERROR Stride is less than the row length.

NPP_ANCHOR_ERROR Anchor point is outside mask.

NPP_MASK_SIZE_ERROR Lower bound is larger than upper bound.

NPP_RESIZE_FACTOR_ERROR

NPP_INTERPOLATION_ERROR

NPP_MIRROR_FLIP_ERR

NPP_MOMENT_00_ZERO_ERROR

NPP_THRESHOLD_NEGATIVE_LEVEL_ERROR

NPP_THRESHOLD_ERROR

NPP_CONTEXT_MATCH_ERROR

NPP_FFT_FLAG_ERROR

NPP_FFT_ORDER_ERROR

NPP_STEP_ERROR Step is less or equal zero.

NPP_SCALE_RANGE_ERROR

NPP_DATA_TYPE_ERROR

NPP_OUT_OFF_RANGE_ERROR

NPP_DIVIDE_BY_ZERO_ERROR

NPP_MEMORY_ALLOCATION_ERR

NPP_NULL_POINTER_ERROR

NPP_RANGE_ERROR

NPP_SIZE_ERROR

NPP_BAD_ARGUMENT_ERROR

NPP_NO_MEMORY_ERROR

NPP_NOT_IMPLEMENTED_ERROR

NPP_ERROR

NPP_ERROR_RESERVED

NPP_NO_ERROR Error free operation.

NPP_SUCCESS Successful operation (same as *NPP_NO_ERROR*).

NPP_NO_OPERATION_WARNING Indicates that no operation was performed.

NPP_DIVIDE_BY_ZERO_WARNING Divisor is zero however does not terminate the execution.

NPP_AFFINE_QUAD_INCORRECT_WARNING Indicates that the quadrangle passed to one of affine warping functions doesn't have necessary properties.

First 3 vertices are used, the fourth vertex discarded.

NPP_WRONG_INTERSECTION_ROI_WARNING The given ROI has no interestion with either the source or destination ROI.

Thus no operation was performed.

NPP_WRONG_INTERSECTION_QUAD_WARNING The given quadrangle has no intersection with either the source or destination ROI.

Thus no operation was performed.

NPP_DOUBLE_SIZE_WARNING Image size isn't multiple of two.

Indicates that in case of 422/411/420 sampling the ROI width/height was modified for proper processing.

NPP_MISALIGNED_DST_ROI_WARNING Speed reduction due to uncoalesced memory accesses warning.

7.2.2.11 enum NppsZCType

Enumerator:

- nppZCR* sign change
- nppZCXor* sign change XOR
- nppZCC* sign change count_0

7.3 Basic NPP Data Types

Data Structures

- struct [NPP_ALIGN_8](#)
Complex Number This struct represents an unsigned int complex number.
- struct [NPP_ALIGN_16](#)
Complex Number This struct represents a long long complex number.

Typedefs

- typedef unsigned char [Npp8u](#)
8-bit unsigned chars
- typedef signed char [Npp8s](#)
8-bit signed chars
- typedef unsigned short [Npp16u](#)
16-bit unsigned integers
- typedef short [Npp16s](#)
16-bit signed integers
- typedef unsigned int [Npp32u](#)
32-bit unsigned integers
- typedef int [Npp32s](#)
32-bit signed integers
- typedef unsigned long long [Npp64u](#)
64-bit unsigned integers
- typedef long long [Npp64s](#)
64-bit signed integers
- typedef float [Npp32f](#)
32-bit (IEEE) floating-point numbers
- typedef double [Npp64f](#)
64-bit floating-point numbers
- typedef struct [NPP_ALIGN_8](#) [Npp32uc](#)
Complex Number This struct represents an unsigned int complex number.
- typedef struct [NPP_ALIGN_8](#) [Npp32sc](#)
Complex Number This struct represents a signed int complex number.

- typedef struct [NPP_ALIGN_8 Npp32fc](#)
Complex Number This struct represents a single floating-point complex number.
- typedef struct [NPP_ALIGN_16 Npp64sc](#)
Complex Number This struct represents a long long complex number.
- typedef struct [NPP_ALIGN_16 Npp64fc](#)
Complex Number This struct represents a double floating-point complex number.

Functions

- struct [__align__](#) (2)
Complex Number This struct represents an unsigned char complex number.
- struct [__align__](#) (4)
Complex Number This struct represents an unsigned short complex number.

Variables

- [Npp8uc](#)
- [Npp16uc](#)
- [Npp16sc](#)

7.3.1 Typedef Documentation

7.3.1.1 typedef short Npp16s

16-bit signed integers

7.3.1.2 typedef unsigned short Npp16u

16-bit unsigned integers

7.3.1.3 typedef float Npp32f

32-bit (IEEE) floating-point numbers

7.3.1.4 typedef struct NPP_ALIGN_8 Npp32fc

Complex Number This struct represents a single floating-point complex number.

7.3.1.5 typedef int Npp32s

32-bit signed integers

7.3.1.6 typedef struct NPP_ALIGN_8 Npp32sc

Complex Number This struct represents a signed int complex number.

7.3.1.7 typedef unsigned int Npp32u

32-bit unsigned integers

7.3.1.8 typedef struct NPP_ALIGN_8 Npp32uc

Complex Number This struct represents an unsigned int complex number.

7.3.1.9 typedef double Npp64f

64-bit floating-point numbers

7.3.1.10 typedef struct NPP_ALIGN_16 Npp64fc

Complex Number This struct represents a double floating-point complex number.

7.3.1.11 typedef long long Npp64s

64-bit signed integers

7.3.1.12 typedef struct NPP_ALIGN_16 Npp64sc

Complex Number This struct represents a long long complex number.

7.3.1.13 typedef unsigned long long Npp64u

64-bit unsigned integers

7.3.1.14 typedef signed char Npp8s

8-bit signed chars

7.3.1.15 typedef unsigned char Npp8u

8-bit unsigned chars

7.3.2 Function Documentation**7.3.2.1 struct __align__ (4) [read]**

Complex Number This struct represents an unsigned short complex number.

Complex Number This struct represents a short complex number.

< Real part

< Imaginary part

< Real part

< Imaginary part

7.3.2.2 struct __align__ (2) [read]

Complex Number This struct represents an unsigned char complex number.

< Real part

< Imaginary part

7.3.3 Variable Documentation

7.3.3.1 Npp16sc

7.3.3.2 Npp16uc

7.3.3.3 Npp8uc

7.4 NPP Image Processing

Modules

- [Arithmetic and Logical Operations](#)
 - [Color and Sampling Conversion](#)
Routines manipulating an image's color model and sampling format.
- [Compression](#)
Image compression primitives.
- [Labeling and Segmentation](#)
Pixel labeling and image segmentation operations.
- [Data Exchange and Initialization](#)
Primitives for initializing, copying and converting image data.
- [Filtering Functions](#)
Linear and non-linear image filtering functions.
- [Geometry Transforms](#)
Routines manipulating an image's geometry.
- [Linear Transforms](#)
Linear image transformations.
- [Morphological Operations](#)
Morphological image operations.
- [Statistical Operations](#)
Primitives for computing the statistical properties of an image.
- [Memory Management](#)
Routines for allocating and deallocating pitched image storage.
- [Threshold and Compare Operations](#)
Methods for pixel-wise threshold and compare operations.

7.5 Arithmetic and Logical Operations

Modules

- [Arithmetic Operations](#)
- [Logical Operations](#)
- [Alpha Composition](#)

7.6 Arithmetic Operations

Modules

- **AddC**
Adds a constant value to each pixel of an image.
- **MulC**
Multiplies each pixel of an image by a constant value.
- **MulCScale**
Multiplies each pixel of an image by a constant value then scales the result by the maximum value for the data bit width.
- **SubC**
Subtracts a constant value from each pixel of an image.
- **DivC**
Divides each pixel of an image by a constant value.
- **AbsDiffC**
Determines absolute difference between each pixel of an image and a constant value.
- **Add**
Pixel by pixel addition of two images.
- **AddSquare**
Pixel by pixel addition of squared pixels from source image to floating point pixel values of destination image.
- **AddProduct**
Pixel by pixel addition of product of pixels from two source images to floating point pixel values of destination image.
- **AddWeighted**
Pixel by pixel addition of alpha weighted pixel values from a source image to floating point pixel values of destination image.
- **Mul**
Pixel by pixel multiply of two images.
- **MulScale**
Pixel by pixel multiplies each pixel of two images then scales the result by the maximum value for the data bit width.
- **Sub**
Pixel by pixel subtraction of two images.
- **Div**
Pixel by pixel division of two images.

- [Div_Round](#)
Pixel by pixel division of two images using result rounding modes.
- [Abs](#)
Absolute value of each pixel value in an image.
- [AbsDiff](#)
Pixel by pixel absolute difference between two images.
- [Sqr](#)
Square each pixel in an image.
- [Sqrt](#)
Pixel by pixel square root of each pixel in an image.
- [Ln](#)
Pixel by pixel natural logarithm of each pixel in an image.
- [Exp](#)
Exponential value of each pixel in an image.

7.7 AddC

Adds a constant value to each pixel of an image.

Functions

- **NppStatus nppiAddC_8u_C1RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** nConstant, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel image add constant, scale, then clamp to saturated value.
- **NppStatus nppiAddC_8u_C1IRSfs** (const **Npp8u** nConstant, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel in place image add constant, scale, then clamp to saturated value.
- **NppStatus nppiAddC_8u_C3RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel image add constant, scale, then clamp to saturated value.
- **NppStatus nppiAddC_8u_C3IRSfs** (const **Npp8u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel 8-bit unsigned char in place image add constant, scale, then clamp to saturated value.
- **NppStatus nppiAddC_8u_AC4RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha image add constant, scale, then clamp to saturated value.
- **NppStatus nppiAddC_8u_AC4IRSfs** (const **Npp8u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha in place image add constant, scale, then clamp to saturated value.
- **NppStatus nppiAddC_8u_C4RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[4], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel image add constant, scale, then clamp to saturated value.
- **NppStatus nppiAddC_8u_C4IRSfs** (const **Npp8u** aConstants[4], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel in place image add constant, scale, then clamp to saturated value.
- **NppStatus nppiAddC_16u_C1RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** nConstant, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel image add constant, scale, then clamp to saturated value.
- **NppStatus nppiAddC_16u_C1IRSfs** (const **Npp16u** nConstant, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel in place image add constant, scale, then clamp to saturated value.
- **NppStatus nppiAddC_16u_C3RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** aConstants[3], **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16u_C3IRSfs` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel in place image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16u_AC4RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[3], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16u_AC4IRSfs` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha in place image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16u_C4RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[4], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16u_C4IRSfs` (const `Npp16u` aConstants[4], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel in place image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16s_C1RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` nConstant, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short channel image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16s_C1IRSfs` (const `Npp16s` nConstant, `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16s_C3RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` aConstants[3], `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16s_C3IRSfs` (const `Npp16s` aConstants[3], `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short channel in place image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16s_AC4RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` aConstants[3], `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16s_AC4IRSfs` (const `Npp16s` aConstants[3], `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha in place image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16s_C4RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` aConstants[4], `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16s_C4IRSfs` (const `Npp16s` aConstants[4], `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel in place image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16sc_C1RSfs` (const `Npp16sc` *pSrc1, int nSrc1Step, const `Npp16sc` nConstant, `Npp16sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16sc_C1IRSfs` (const `Npp16sc` nConstant, `Npp16sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16sc_C3RSfs` (const `Npp16sc` *pSrc1, int nSrc1Step, const `Npp16sc` aConstants[3], `Npp16sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16sc_C3IRSfs` (const `Npp16sc` aConstants[3], `Npp16sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16sc_AC4RSfs` (const `Npp16sc` *pSrc1, int nSrc1Step, const `Npp16sc` aConstants[3], `Npp16sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16sc_AC4IRSfs` (const `Npp16sc` aConstants[3], `Npp16sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_32s_C1RSfs` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` nConstant, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer channel image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_32s_C1IRSfs` (const `Npp32s` nConstant, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer channel in place image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_32s_C3RSfs` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` aConstants[3], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer channel image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_32s_C3IRSfs` (const `Npp32s` aConstants[3], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer channel in place image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_32sc_C1RSfs` (const `Npp32sc *pSrc1`, int `nSrc1Step`, const `Npp32sc nConstant`, `Npp32sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image add constant, scale, then clamp to saturated value.
- `NppStatus nppiAddC_32sc_C1IRSfs` (const `Npp32sc nConstant`, `Npp32sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image add constant, scale, then clamp to saturated value.
- `NppStatus nppiAddC_32sc_C3RSfs` (const `Npp32sc *pSrc1`, int `nSrc1Step`, const `Npp32sc aConstants[3]`, `Npp32sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image add constant, scale, then clamp to saturated value.
- `NppStatus nppiAddC_32sc_C3IRSfs` (const `Npp32sc aConstants[3]`, `Npp32sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image add constant, scale, then clamp to saturated value.
- `NppStatus nppiAddC_32sc_AC4RSfs` (const `Npp32sc *pSrc1`, int `nSrc1Step`, const `Npp32sc aConstants[3]`, `Npp32sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha image add constant, scale, then clamp to saturated value.
- `NppStatus nppiAddC_32sc_AC4IRSfs` (const `Npp32sc aConstants[3]`, `Npp32sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image add constant, scale, then clamp to saturated value.
- `NppStatus nppiAddC_32f_C1R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f nConstant`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
One 32-bit floating point channel image add constant.
- `NppStatus nppiAddC_32f_C1IR` (const `Npp32f nConstant`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
One 32-bit floating point channel in place image add constant.
- `NppStatus nppiAddC_32f_C3R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f aConstants[3]`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Three 32-bit floating point channel image add constant.
- `NppStatus nppiAddC_32f_C3IR` (const `Npp32f aConstants[3]`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Three 32-bit floating point channel in place image add constant.
- `NppStatus nppiAddC_32f_AC4R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f aConstants[3]`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point channel with unmodified alpha image add constant.
- `NppStatus nppiAddC_32f_AC4IR` (const `Npp32f aConstants[3]`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Four 32-bit floating point channel with unmodified alpha in place image add constant.

- **NppStatus nppiAddC_32f_C4R** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** aConstants[4], **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)

Four 32-bit floating point channel image add constant.

- **NppStatus nppiAddC_32f_C4IR** (const **Npp32f** aConstants[4], **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)

Four 32-bit floating point channel in place image add constant.

- **NppStatus nppiAddC_32fc_C1R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** nConstant, **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)

One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image add constant.

- **NppStatus nppiAddC_32fc_C1IR** (const **Npp32fc** nConstant, **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)

One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image add constant.

- **NppStatus nppiAddC_32fc_C3R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** aConstants[3], **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)

Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image add constant.

- **NppStatus nppiAddC_32fc_C3IR** (const **Npp32fc** aConstants[3], **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)

Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image add constant.

- **NppStatus nppiAddC_32fc_AC4R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** aConstants[3], **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha image add constant.

- **NppStatus nppiAddC_32fc_AC4IR** (const **Npp32fc** aConstants[3], **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha in place image add constant.

- **NppStatus nppiAddC_32fc_C4R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** aConstants[4], **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image add constant.

- **NppStatus nppiAddC_32fc_C4IR** (const **Npp32fc** aConstants[4], **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image add constant.

7.7.1 Detailed Description

Adds a constant value to each pixel of an image.

7.7.2 Function Documentation

7.7.2.1 `NppStatus nppiAddC_16s_AC4IRSfs (const Npp16s aConstants[3], Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel with unmodified alpha in place image add constant, scale, then clamp to saturated value.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.2 `NppStatus nppiAddC_16s_AC4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s aConstants[3], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel with unmodified alpha image add constant, scale, then clamp to saturated value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.3 `NppStatus nppiAddC_16s_C1IRSfs (const Npp16s nConstant, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short channel in place image add constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.4 `NppStatus nppiAddC_16s_C1RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s nConstant, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short channel image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.5 `NppStatus nppiAddC_16s_C3IRSfs (const Npp16s aConstants[3], Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit signed short channel in place image add constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.6 NppStatus nppiAddC_16s_C3RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s aConstants[3], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.7 NppStatus nppiAddC_16s_C4IRSfs (const Npp16s aConstants[4], Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short channel in place image add constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.8 NppStatus nppiAddC_16s_C4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s aConstants[4], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short channel image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.9 NppStatus nppiAddC_16sc_AC4IRSfs (const Npp16sc aConstants[3], Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image add constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.10 NppStatus nppiAddC_16sc_AC4RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc aConstants[3], Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.11 `NppStatus nppiAddC_16sc_C1IRSfs (const Npp16sc nConstant, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image add constant, scale, then clamp to saturated value.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.12 `NppStatus nppiAddC_16sc_C1RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc nConstant, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image add constant, scale, then clamp to saturated value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nConstant* Constant.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.13 `NppStatus nppiAddC_16sc_C3IRSfs (const Npp16sc aConstants[3], Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image add constant, scale, then clamp to saturated value.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.14 NppStatus nppiAddC_16sc_C3RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc aConstants[3], Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.15 NppStatus nppiAddC_16u_AC4IRSfs (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha in place image add constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.16 NppStatus nppiAddC_16u_AC4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.17 NppStatus nppiAddC_16u_C1IRSfs (const Npp16u nConstant, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image add constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.18 NppStatus nppiAddC_16u_C1RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u nConstant, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.19 NppStatus nppiAddC_16u_C3IRSfs (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel in place image add constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.20 NppStatus nppiAddC_16u_C3RSfs (const Npp16u * pSrcI, int nSrcIStep, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image add constant, scale, then clamp to saturated value.

Parameters:

pSrcI Source-Image Pointer.

nSrcIStep Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.21 NppStatus nppiAddC_16u_C4IRSfs (const Npp16u aConstants[4], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel in place image add constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.22 NppStatus nppiAddC_16u_C4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[4], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.23 NppStatus nppiAddC_32f_AC4IR (const Npp32f aConstants[3], Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel with unmodified alpha in place image add constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.24 NppStatus nppiAddC_32f_AC4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f aConstants[3], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel with unmodified alpha image add constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.25 NppStatus nppiAddC_32f_C1IR (const Npp32f nConstant, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit floating point channel in place image add constant.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.26 NppStatus nppiAddC_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f nConstant, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit floating point channel image add constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.27 NppStatus nppiAddC_32f_C3IR (const Npp32f aConstants[3], Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel in place image add constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.28 NppStatus nppiAddC_32f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f aConstants[3], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel image add constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.29 NppStatus nppiAddC_32f_C4IR (const Npp32f aConstants[4], Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel in place image add constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.30 NppStatus nppiAddC_32f_C4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f aConstants[4], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel image add constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.31 NppStatus nppiAddC_32fc_AC4IR (const Npp32fc aConstants[3], Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha in place image add constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.32 NppStatus nppiAddC_32fc_AC4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc aConstants[3], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha image add constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.33 `NppStatus nppiAddC_32fc_C1IR (const Npp32fc nConstant, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image add constant.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.34 `NppStatus nppiAddC_32fc_C1R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc nConstant, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image add constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.35 `NppStatus nppiAddC_32fc_C3IR (const Npp32fc aConstants[3], Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image add constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.36 NppStatus nppiAddC_32fc_C3R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc aConstants[3], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image add constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.37 NppStatus nppiAddC_32fc_C4IR (const Npp32fc aConstants[4], Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image add constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.38 NppStatus nppiAddC_32fc_C4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc aConstants[4], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image add constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.39 `NppStatus nppiAddC_32s_C1IRSfs (const Npp32s nConstant, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer channel in place image add constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.40 `NppStatus nppiAddC_32s_C1RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s nConstant, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer channel image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.41 `NppStatus nppiAddC_32s_C3IRSfs (const Npp32s aConstants[3], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer channel in place image add constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.42 **NppStatus nppiAddC_32s_C3RSfs** (const Npp32s * *pSrc1*, int *nSrc1Step*, const Npp32s *aConstants*[3], Npp32s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Three 32-bit signed integer channel image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.43 **NppStatus nppiAddC_32sc_AC4IRSfs** (const Npp32sc *aConstants*[3], Npp32sc * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image add constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.44 `NppStatus nppiAddC_32sc_AC4RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc aConstants[3], Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha image add constant, scale, then clamp to saturated value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.45 `NppStatus nppiAddC_32sc_C1IRSfs (const Npp32sc nConstant, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image add constant, scale, then clamp to saturated value.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.46 `NppStatus nppiAddC_32sc_C1RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc nConstant, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image add constant, scale, then clamp to saturated value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.

nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.47 NppStatus nppiAddC_32sc_C3IRSfs (const Npp32sc aConstants[3], Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image add constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.48 NppStatus nppiAddC_32sc_C3RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc aConstants[3], Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.49 `NppStatus nppiAddC_8u_AC4IRSfs (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha in place image add constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel..
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.50 `NppStatus nppiAddC_8u_AC4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel..
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.51 `NppStatus nppiAddC_8u_C1IRSfs (const Npp8u nConstant, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel in place image add constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.52 `NppStatus nppiAddC_8u_C1RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u nConstant, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.53 `NppStatus nppiAddC_8u_C3RSfs (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel 8-bit unsigned char in place image add constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel..

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.54 `NppStatus nppiAddC_8u_C3RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel..
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.55 **NppStatus nppiAddC_8u_C4IRSfs** (const Npp8u *aConstants*[4], Npp8u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Four 8-bit unsigned char channel in place image add constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.56 **NppStatus nppiAddC_8u_C4RSfs** (const Npp8u * *pSrc1*, int *nSrc1Step*, const Npp8u *aConstants*[4], Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Four 8-bit unsigned char channel image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel..
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8 MulC

Multiplies each pixel of an image by a constant value.

Functions

- **NppStatus nppiMulC_8u_C1RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** nConstant, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel image multiply by constant, scale, then clamp to saturated value.
- **NppStatus nppiMulC_8u_C1IRSfs** (const **Npp8u** nConstant, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel in place image multiply by constant, scale, then clamp to saturated value.
- **NppStatus nppiMulC_8u_C3RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel image multiply by constant, scale, then clamp to saturated value.
- **NppStatus nppiMulC_8u_C3IRSfs** (const **Npp8u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel 8-bit unsigned char in place image multiply by constant, scale, then clamp to saturated value.
- **NppStatus nppiMulC_8u_AC4RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha image multiply by constant, scale, then clamp to saturated value.
- **NppStatus nppiMulC_8u_AC4IRSfs** (const **Npp8u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha in place image multiply by constant, scale, then clamp to saturated value.
- **NppStatus nppiMulC_8u_C4RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[4], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel image multiply by constant, scale, then clamp to saturated value.
- **NppStatus nppiMulC_8u_C4IRSfs** (const **Npp8u** aConstants[4], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel in place image multiply by constant, scale, then clamp to saturated value.
- **NppStatus nppiMulC_16u_C1RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** nConstant, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel image multiply by constant, scale, then clamp to saturated value.
- **NppStatus nppiMulC_16u_C1IRSfs** (const **Npp16u** nConstant, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel in place image multiply by constant, scale, then clamp to saturated value.
- **NppStatus nppiMulC_16u_C3RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** aConstants[3], **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_16u_C3IRSfs` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel in place image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_16u_AC4RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[3], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_16u_AC4IRSfs` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha in place image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_16u_C4RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[4], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_16u_C4IRSfs` (const `Npp16u` aConstants[4], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel in place image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_16s_C1RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` nConstant, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short channel image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_16s_C1IRSfs` (const `Npp16s` nConstant, `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_16s_C3RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` aConstants[3], `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_16s_C3IRSfs` (const `Npp16s` aConstants[3], `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short channel in place image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_16s_AC4RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` aConstants[3], `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_16s_AC4IRSfs` (const `Npp16s` aConstants[3], `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha in place image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_16s_C4RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` aConstants[4], `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 16-bit signed short channel image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_16s_C4IRSfs` (const `Npp16s` aConstants[4], `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 16-bit signed short channel in place image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_16sc_C1RSfs` (const `Npp16sc` *pSrc1, int nSrc1Step, const `Npp16sc` nConstant, `Npp16sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_16sc_C1IRSfs` (const `Npp16sc` nConstant, `Npp16sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_16sc_C3RSfs` (const `Npp16sc` *pSrc1, int nSrc1Step, const `Npp16sc` aConstants[3], `Npp16sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_16sc_C3IRSfs` (const `Npp16sc` aConstants[3], `Npp16sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_16sc_AC4RSfs` (const `Npp16sc` *pSrc1, int nSrc1Step, const `Npp16sc` aConstants[3], `Npp16sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_16sc_AC4IRSfs` (const `Npp16sc` aConstants[3], `Npp16sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_32s_C1RSfs` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` nConstant, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 32-bit signed integer channel image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_32s_C1IRSfs` (const `Npp32s` nConstant, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 32-bit signed integer channel in place image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_32s_C3RSfs` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` aConstants[3], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Three 32-bit signed integer channel image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_32s_C3IRSfs` (const `Npp32s` aConstants[3], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer channel in place image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_32sc_C1RSfs` (const `Npp32sc *pSrc1`, int `nSrc1Step`, const `Npp32sc nConstant`, `Npp32sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_32sc_C1IRSfs` (const `Npp32sc nConstant`, `Npp32sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_32sc_C3RSfs` (const `Npp32sc *pSrc1`, int `nSrc1Step`, const `Npp32sc aConstants[3]`, `Npp32sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_32sc_C3IRSfs` (const `Npp32sc aConstants[3]`, `Npp32sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_32sc_AC4RSfs` (const `Npp32sc *pSrc1`, int `nSrc1Step`, const `Npp32sc aConstants[3]`, `Npp32sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_32sc_AC4IRSfs` (const `Npp32sc aConstants[3]`, `Npp32sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_32f_C1R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f nConstant`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
One 32-bit floating point channel image multiply by constant.
- `NppStatus nppiMulC_32f_C1IR` (const `Npp32f nConstant`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
One 32-bit floating point channel in place image multiply by constant.
- `NppStatus nppiMulC_32f_C3R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f aConstants[3]`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Three 32-bit floating point channel image multiply by constant.
- `NppStatus nppiMulC_32f_C3IR` (const `Npp32f aConstants[3]`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Three 32-bit floating point channel in place image multiply by constant.
- `NppStatus nppiMulC_32f_AC4R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f aConstants[3]`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point channel with unmodified alpha image multiply by constant.

- **NppStatus nppiMulC_32f_AC4IR** (const **Npp32f** aConstants[3], **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point channel with unmodified alpha in place image multiply by constant.
- **NppStatus nppiMulC_32f_C4R** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** aConstants[4], **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point channel image multiply by constant.
- **NppStatus nppiMulC_32f_C4IR** (const **Npp32f** aConstants[4], **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point channel in place image multiply by constant.
- **NppStatus nppiMulC_32fc_C1R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** nConstant, **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image multiply by constant.
- **NppStatus nppiMulC_32fc_C1IR** (const **Npp32fc** nConstant, **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image multiply by constant.
- **NppStatus nppiMulC_32fc_C3R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** aConstants[3], **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image multiply by constant.
- **NppStatus nppiMulC_32fc_C3IR** (const **Npp32fc** aConstants[3], **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image multiply by constant.
- **NppStatus nppiMulC_32fc_AC4R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** aConstants[3], **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha image multiply by constant.
- **NppStatus nppiMulC_32fc_AC4IR** (const **Npp32fc** aConstants[3], **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha in place image multiply by constant.
- **NppStatus nppiMulC_32fc_C4R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** aConstants[4], **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image multiply by constant.
- **NppStatus nppiMulC_32fc_C4IR** (const **Npp32fc** aConstants[4], **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image multiply by constant.

7.8.1 Detailed Description

Multiplies each pixel of an image by a constant value.

7.8.2 Function Documentation

7.8.2.1 `NppStatus nppiMulC_16s_AC4IRSfs (const Npp16s aConstants[3], Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel with unmodified alpha in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.2 `NppStatus nppiMulC_16s_AC4RSfs (const Npp16s * pSrcI, int nSrcIStep, const Npp16s aConstants[3], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel with unmodified alpha image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrcI Source-Image Pointer.

nSrcIStep Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.3 NppStatus nppiMulC_16s_C1IRSfs (const Npp16s *nConstant*, Npp16s * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

One 16-bit signed short channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.4 NppStatus nppiMulC_16s_C1RSfs (const Npp16s * *pSrc1*, int *nSrc1Step*, const Npp16s *nConstant*, Npp16s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

One 16-bit signed short channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.5 NppStatus nppiMulC_16s_C3IRSfs (const Npp16s *aConstants*[3], Npp16s * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Three 16-bit signed short channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.6 `NppStatus nppiMulC_16s_C3RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s aConstants[3], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit signed short channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.7 `NppStatus nppiMulC_16s_C4IRSfs (const Npp16s aConstants[4], Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.8 `NppStatus nppiMulC_16s_C4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s aConstants[4], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.9 NppStatus nppiMulC_16sc_AC4IRSfs (const Npp16sc aConstants[3], Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.10 NppStatus nppiMulC_16sc_AC4RSfs (const Npp16sc * pSrcI, int nSrcIStep, const Npp16sc aConstants[3], Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrcI Source-Image Pointer.

nSrcIStep Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.11 `NppStatus nppiMulC_16sc_C1IRSfs (const Npp16sc nConstant, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.12 `NppStatus nppiMulC_16sc_C1RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc nConstant, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nConstant* Constant.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.13 `NppStatus nppiMulC_16sc_C3IRSfs (const Npp16sc aConstants[3], Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.14 NppStatus nppiMulC_16sc_C3RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc aConstants[3], Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.15 NppStatus nppiMulC_16u_AC4IRSfs (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.16 NppStatus nppiMulC_16u_AC4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.17 NppStatus nppiMulC_16u_C1IRSfs (const Npp16u nConstant, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.18 NppStatus nppiMulC_16u_C1RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u nConstant, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.19 NppStatus nppiMulC_16u_C3IRSfs (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.20 NppStatus nppiMulC_16u_C3RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.21 `NppStatus nppiMulC_16u_C4IRSfs (const Npp16u aConstants[4], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.22 `NppStatus nppiMulC_16u_C4RSfs (const Npp16u * pSrcI, int nSrcIStep, const Npp16u aConstants[4], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrcI Source-Image Pointer.
nSrcIStep Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.23 `NppStatus nppiMulC_32f_AC4IR (const Npp32f aConstants[3], Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel with unmodified alpha in place image multiply by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.24 NppStatus nppiMulC_32f_AC4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f aConstants[3], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel with unmodified alpha image multiply by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.25 NppStatus nppiMulC_32f_C1IR (const Npp32f nConstant, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit floating point channel in place image multiply by constant.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.26 NppStatus nppiMulC_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f nConstant, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit floating point channel image multiply by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.27 NppStatus nppiMulC_32f_C3IR (const Npp32f aConstants[3], Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel in place image multiply by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.28 NppStatus nppiMulC_32f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f aConstants[3], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel image multiply by constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.29 NppStatus nppiMulC_32f_C4IR (const Npp32f aConstants[4], Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel in place image multiply by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.30 NppStatus nppiMulC_32f_C4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f aConstants[4], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel image multiply by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.31 NppStatus nppiMulC_32fc_AC4IR (const Npp32fc aConstants[3], Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha in place image multiply by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.32 NppStatus nppiMulC_32fc_AC4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc aConstants[3], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha image multiply by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.33 NppStatus nppiMulC_32fc_C1IR (const Npp32fc *nConstant*, Npp32fc * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image multiply by constant.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.34 NppStatus nppiMulC_32fc_C1R (const Npp32fc * *pSrc1*, int *nSrc1Step*, const Npp32fc *nConstant*, Npp32fc * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image multiply by constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.35 NppStatus nppiMulC_32fc_C3IR (const Npp32fc *aConstants*[3], Npp32fc * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image multiply by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.36 NppStatus nppiMulC_32fc_C3R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc aConstants[3], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image multiply by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.37 NppStatus nppiMulC_32fc_C4IR (const Npp32fc aConstants[4], Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image multiply by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.38 NppStatus nppiMulC_32fc_C4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc aConstants[4], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image multiply by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.39 NppStatus nppiMulC_32s_C1RSfs (const Npp32s nConstant, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 32-bit signed integer channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.40 NppStatus nppiMulC_32s_C1RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s nConstant, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 32-bit signed integer channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.41 NppStatus nppiMulC_32s_C3IRSfs (const Npp32s aConstants[3], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 32-bit signed integer channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.42 NppStatus nppiMulC_32s_C3RSfs (const Npp32s * *pSrc1*, int *nSrc1Step*, const Npp32s *aConstants*[3], Npp32s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Three 32-bit signed integer channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.43 NppStatus nppiMulC_32sc_AC4IRSfs (const Npp32sc *aConstants*[3], Npp32sc * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.44 `NppStatus nppiMulC_32sc_AC4RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc aConstants[3], Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.45 `NppStatus nppiMulC_32sc_C1IRSfs (const Npp32sc nConstant, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.46 `NppStatus nppiMulC_32sc_C1RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc nConstant, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.47 **NppStatus nppiMulC_32sc_C3IRSfs** (const Npp32sc *aConstants*[3], Npp32sc * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.48 **NppStatus nppiMulC_32sc_C3RSfs** (const Npp32sc * *pSrc1*, int *nSrc1Step*, const Npp32sc *aConstants*[3], Npp32sc * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.49 `NppStatus nppiMulC_8u_AC4IRSfs (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.50 `NppStatus nppiMulC_8u_AC4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.51 `NppStatus nppiMulC_8u_C1IRSfs (const Npp8u nConstant, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.52 `NppStatus nppiMulC_8u_C1RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u nConstant, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.53 `NppStatus nppiMulC_8u_C3IRSfs (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel 8-bit unsigned char in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.54 `NppStatus nppiMulC_8u_C3RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.55 `NppStatus nppiMulC_8u_C4IRSfs (const Npp8u aConstants[4], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.56 `NppStatus nppiMulC_8u_C4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[4], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9 MulCScale

Multiplies each pixel of an image by a constant value then scales the result by the maximum value for the data bit width.

Functions

- **NppStatus nppiMulCScale_8u_C1R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** nConstant, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel image multiply by constant and scale by max bit width value.
- **NppStatus nppiMulCScale_8u_C1IR** (const **Npp8u** nConstant, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel in place image multiply by constant and scale by max bit width value.
- **NppStatus nppiMulCScale_8u_C3R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 8-bit unsigned char channel image multiply by constant and scale by max bit width value.
- **NppStatus nppiMulCScale_8u_C3IR** (const **Npp8u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 8-bit unsigned char channel 8-bit unsigned char in place image multiply by constant and scale by max bit width value.
- **NppStatus nppiMulCScale_8u_AC4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel with unmodified alpha image multiply by constant and scale by max bit width value.
- **NppStatus nppiMulCScale_8u_AC4IR** (const **Npp8u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel with unmodified alpha in place image multiply by constant, scale and scale by max bit width value.
- **NppStatus nppiMulCScale_8u_C4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[4], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel image multiply by constant and scale by max bit width value.
- **NppStatus nppiMulCScale_8u_C4IR** (const **Npp8u** aConstants[4], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel in place image multiply by constant and scale by max bit width value.
- **NppStatus nppiMulCScale_16u_C1R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** nConstant, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel image multiply by constant and scale by max bit width value.
- **NppStatus nppiMulCScale_16u_C1IR** (const **Npp16u** nConstant, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel in place image multiply by constant and scale by max bit width value.

- `NppStatus nppiMulCScale_16u_C3R` (const `Npp16u *pSrc1`, int `nSrc1Step`, const `Npp16u aConstants[3]`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Three 16-bit unsigned short channel image multiply by constant and scale by max bit width value.
- `NppStatus nppiMulCScale_16u_C3IR` (const `Npp16u aConstants[3]`, `Npp16u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Three 16-bit unsigned short channel in place image multiply by constant and scale by max bit width value.
- `NppStatus nppiMulCScale_16u_AC4R` (const `Npp16u *pSrc1`, int `nSrc1Step`, const `Npp16u aConstants[3]`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four 16-bit unsigned short channel with unmodified alpha image multiply by constant and scale by max bit width value.
- `NppStatus nppiMulCScale_16u_AC4IR` (const `Npp16u aConstants[3]`, `Npp16u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Four 16-bit unsigned short channel with unmodified alpha in place image multiply by constant and scale by max bit width value.
- `NppStatus nppiMulCScale_16u_C4R` (const `Npp16u *pSrc1`, int `nSrc1Step`, const `Npp16u aConstants[4]`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four 16-bit unsigned short channel image multiply by constant and scale by max bit width value.
- `NppStatus nppiMulCScale_16u_C4IR` (const `Npp16u aConstants[4]`, `Npp16u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Four 16-bit unsigned short channel in place image multiply by constant and scale by max bit width value.

7.9.1 Detailed Description

Multiplies each pixel of an image by a constant value then scales the result by the maximum value for the data bit width.

7.9.2 Function Documentation

7.9.2.1 `NppStatus nppiMulCScale_16u_AC4IR` (const `Npp16u aConstants[3]`, `Npp16u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Four 16-bit unsigned short channel with unmodified alpha in place image multiply by constant and scale by max bit width value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.2 NppStatus nppiMulCScale_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel with unmodified alpha image multiply by constant and scale by max bit width value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.3 NppStatus nppiMulCScale_16u_C1IR (const Npp16u nConstant, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 16-bit unsigned short channel in place image multiply by constant and scale by max bit width value.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.4 NppStatus nppiMulCScale_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u nConstant, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

One 16-bit unsigned short channel image multiply by constant and scale by max bit width value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nConstant* Constant.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.5 NppStatus nppiMulCScale_16u_C3IR (const Npp16u *aConstants*[3], Npp16u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

Three 16-bit unsigned short channel in place image multiply by constant and scale by max bit width value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.6 NppStatus nppiMulCScale_16u_C3R (const Npp16u * *pSrc1*, int *nSrc1Step*, const Npp16u *aConstants*[3], Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

Three 16-bit unsigned short channel image multiply by constant and scale by max bit width value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.7 NppStatus nppiMulCScale_16u_C4IR (const Npp16u *aConstants*[4], Npp16u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

Four 16-bit unsigned short channel in place image multiply by constant and scale by max bit width value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.8 NppStatus nppiMulCScale_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[4], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel image multiply by constant and scale by max bit width value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.9 NppStatus nppiMulCScale_8u_AC4IR (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel with unmodified alpha in place image multiply by constant, scale and scale by max bit width value.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.10 NppStatus nppiMulCScale_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel with unmodified alpha image multiply by constant and scale by max bit width value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.11 `NppStatus nppiMulCScale_8u_C1IR (const Npp8u nConstant, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel in place image multiply by constant and scale by max bit width value.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.12 `NppStatus nppiMulCScale_8u_C1R (const Npp8u * pSrcI, int nSrcIStep, const Npp8u nConstant, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel image multiply by constant and scale by max bit width value.

Parameters:

pSrcI Source-Image Pointer.
nSrcIStep Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.13 `NppStatus nppiMulCScale_8u_C3IR (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Three 8-bit unsigned char channel 8-bit unsigned char in place image multiply by constant and scale by max bit width value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.14 NppStatus nppiMulCScale_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel image multiply by constant and scale by max bit width value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.15 NppStatus nppiMulCScale_8u_C4IR (const Npp8u aConstants[4], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel in place image multiply by constant and scale by max bit width value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.16 NppStatus nppiMulCScale_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[4], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel image multiply by constant and scale by max bit width value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10 SubC

Subtracts a constant value from each pixel of an image.

Functions

- `NppStatus nppiSubC_8u_C1RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` nConstant, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_8u_C1IRSfs` (const `Npp8u` nConstant, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel in place image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_8u_C3RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` aConstants[3], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_8u_C3IRSfs` (const `Npp8u` aConstants[3], `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel 8-bit unsigned char in place image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_8u_AC4RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` aConstants[3], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_8u_AC4IRSfs` (const `Npp8u` aConstants[3], `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha in place image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_8u_C4RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` aConstants[4], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_8u_C4IRSfs` (const `Npp8u` aConstants[4], `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel in place image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_16u_C1RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` nConstant, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_16u_C1IRSfs` (const `Npp16u` nConstant, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel in place image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_16u_C3RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[3], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16u_C3IRSfs` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel in place image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16u_AC4RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[3], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16u_AC4IRSfs` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha in place image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16u_C4RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[4], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16u_C4IRSfs` (const `Npp16u` aConstants[4], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel in place image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16s_C1RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` nConstant, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short channel image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16s_C1IRSfs` (const `Npp16s` nConstant, `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16s_C3RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` aConstants[3], `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16s_C3IRSfs` (const `Npp16s` aConstants[3], `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short channel in place image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16s_AC4RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` aConstants[3], `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16s_AC4IRSfs` (const `Npp16s` aConstants[3], `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha in place image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16s_C4RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` aConstants[4], `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16s_C4IRSfs` (const `Npp16s` aConstants[4], `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel in place image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16sc_C1RSfs` (const `Npp16sc` *pSrc1, int nSrc1Step, const `Npp16sc` nConstant, `Npp16sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16sc_C1IRSfs` (const `Npp16sc` nConstant, `Npp16sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16sc_C3RSfs` (const `Npp16sc` *pSrc1, int nSrc1Step, const `Npp16sc` aConstants[3], `Npp16sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16sc_C3IRSfs` (const `Npp16sc` aConstants[3], `Npp16sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16sc_AC4RSfs` (const `Npp16sc` *pSrc1, int nSrc1Step, const `Npp16sc` aConstants[3], `Npp16sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16sc_AC4IRSfs` (const `Npp16sc` aConstants[3], `Npp16sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_32s_C1RSfs` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` nConstant, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer channel image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_32s_C1IRSfs` (const `Npp32s` nConstant, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer channel in place image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_32s_C3RSfs` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` aConstants[3], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer channel image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_32s_C3IRSfs` (const `Npp32s` aConstants[3], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer channel in place image subtract constant, scale, then clamp to saturated value.

- **NppStatus nppiSubC_32sc_C1RSfs** (const **Npp32sc** *pSrc1, int nSrc1Step, const **Npp32sc** nConstant, **Npp32sc** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image subtract constant, scale, then clamp to saturated value.
- **NppStatus nppiSubC_32sc_C1IRSfs** (const **Npp32sc** nConstant, **Npp32sc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image subtract constant, scale, then clamp to saturated value.
- **NppStatus nppiSubC_32sc_C3RSfs** (const **Npp32sc** *pSrc1, int nSrc1Step, const **Npp32sc** aConstants[3], **Npp32sc** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image subtract constant, scale, then clamp to saturated value.
- **NppStatus nppiSubC_32sc_C3IRSfs** (const **Npp32sc** aConstants[3], **Npp32sc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image subtract constant, scale, then clamp to saturated value.
- **NppStatus nppiSubC_32sc_AC4RSfs** (const **Npp32sc** *pSrc1, int nSrc1Step, const **Npp32sc** aConstants[3], **Npp32sc** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha image subtract constant, scale, then clamp to saturated value.
- **NppStatus nppiSubC_32sc_AC4IRSfs** (const **Npp32sc** aConstants[3], **Npp32sc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image subtract constant, scale, then clamp to saturated value.
- **NppStatus nppiSubC_32f_C1R** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** nConstant, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 32-bit floating point channel image subtract constant.
- **NppStatus nppiSubC_32f_C1IR** (const **Npp32f** nConstant, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 32-bit floating point channel in place image subtract constant.
- **NppStatus nppiSubC_32f_C3R** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** aConstants[3], **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 32-bit floating point channel image subtract constant.
- **NppStatus nppiSubC_32f_C3IR** (const **Npp32f** aConstants[3], **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 32-bit floating point channel in place image subtract constant.
- **NppStatus nppiSubC_32f_AC4R** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** aConstants[3], **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point channel with unmodified alpha image subtract constant.
- **NppStatus nppiSubC_32f_AC4IR** (const **Npp32f** aConstants[3], **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)

Four 32-bit floating point channel with unmodified alpha in place image subtract constant.

- `NppStatus nppiSubC_32f_C4R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f aConstants[4]`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Four 32-bit floating point channel image subtract constant.

- `NppStatus nppiSubC_32f_C4IR` (const `Npp32f aConstants[4]`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Four 32-bit floating point channel in place image subtract constant.

- `NppStatus nppiSubC_32fc_C1R` (const `Npp32fc *pSrc1`, int `nSrc1Step`, const `Npp32fc nConstant`, `Npp32fc *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image subtract constant.

- `NppStatus nppiSubC_32fc_C1IR` (const `Npp32fc nConstant`, `Npp32fc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image subtract constant.

- `NppStatus nppiSubC_32fc_C3R` (const `Npp32fc *pSrc1`, int `nSrc1Step`, const `Npp32fc aConstants[3]`, `Npp32fc *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image subtract constant.

- `NppStatus nppiSubC_32fc_C3IR` (const `Npp32fc aConstants[3]`, `Npp32fc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image subtract constant.

- `NppStatus nppiSubC_32fc_AC4R` (const `Npp32fc *pSrc1`, int `nSrc1Step`, const `Npp32fc aConstants[3]`, `Npp32fc *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha image subtract constant.

- `NppStatus nppiSubC_32fc_AC4IR` (const `Npp32fc aConstants[3]`, `Npp32fc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha in place image subtract constant.

- `NppStatus nppiSubC_32fc_C4R` (const `Npp32fc *pSrc1`, int `nSrc1Step`, const `Npp32fc aConstants[4]`, `Npp32fc *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image subtract constant.

- `NppStatus nppiSubC_32fc_C4IR` (const `Npp32fc aConstants[4]`, `Npp32fc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image subtract constant.

7.10.1 Detailed Description

Subtracts a constant value from each pixel of an image.

7.10.2 Function Documentation

7.10.2.1 `NppStatus nppiSubC_16s_AC4IRSfs (const Npp16s aConstants[3], Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel with unmodified alpha in place image subtract constant, scale, then clamp to saturated value.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.2 `NppStatus nppiSubC_16s_AC4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s aConstants[3], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel with unmodified alpha image subtract constant, scale, then clamp to saturated value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.3 `NppStatus nppiSubC_16s_C1IRSfs (const Npp16s nConstant, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.4 **NppStatus nppiSubC_16s_C1RSfs** (const Npp16s * *pSrc1*, int *nSrc1Step*, const Npp16s *nConstant*, Npp16s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

One 16-bit signed short channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.5 **NppStatus nppiSubC_16s_C3IRSfs** (const Npp16s *aConstants*[3], Npp16s * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Three 16-bit signed short channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.6 NppStatus nppiSubC_16s_C3RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s aConstants[3], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.7 NppStatus nppiSubC_16s_C4IRSfs (const Npp16s aConstants[4], Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.8 NppStatus nppiSubC_16s_C4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s aConstants[4], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.9 NppStatus nppiSubC_16sc_AC4IRSfs (const Npp16sc aConstants[3], Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image subtract constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.10 NppStatus nppiSubC_16sc_AC4RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc aConstants[3], Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.11 NppStatus nppiSubC_16sc_C1IRSfs (const Npp16sc *nConstant*, Npp16sc * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.12 NppStatus nppiSubC_16sc_C1RSfs (const Npp16sc * *pSrcI*, int *nSrcIStep*, const Npp16sc *nConstant*, Npp16sc * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image subtract constant, scale, then clamp to saturated value.

Parameters:

- pSrcI* Source-Image Pointer.
- nSrcIStep* Source-Image Line Step.
- nConstant* Constant.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.13 NppStatus nppiSubC_16sc_C3IRSfs (const Npp16sc *aConstants*[3], Npp16sc * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.14 `NppStatus nppiSubC_16sc_C3RSfs (const Npp16sc * pSrcI, int nSrcIStep, const Npp16sc aConstants[3], Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrcI Source-Image Pointer.

nSrcIStep Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.15 `NppStatus nppiSubC_16u_AC4IRSfs (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel with unmodified alpha in place image subtract constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.16 `NppStatus nppiSubC_16u_AC4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel with unmodified alpha image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.17 `NppStatus nppiSubC_16u_C1IRSfs (const Npp16u nConstant, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit unsigned short channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.18 `NppStatus nppiSubC_16u_C1RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u nConstant, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit unsigned short channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.19 `NppStatus nppiSubC_16u_C3IRSfs (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit unsigned short channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.20 `NppStatus nppiSubC_16u_C3RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit unsigned short channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.21 NppStatus nppiSubC_16u_C4IRSfs (const Npp16u aConstants[4], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.22 NppStatus nppiSubC_16u_C4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[4], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.23 NppStatus nppiSubC_32f_AC4IR (const Npp32f aConstants[3], Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel with unmodified alpha in place image subtract constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.24 `NppStatus nppiSubC_32f_AC4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f aConstants[3], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel with unmodified alpha image subtract constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.25 `NppStatus nppiSubC_32f_C1IR (const Npp32f nConstant, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 32-bit floating point channel in place image subtract constant.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.26 `NppStatus nppiSubC_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f nConstant, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit floating point channel image subtract constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.27 NppStatus nppiSubC_32f_C3IR (const Npp32f aConstants[3], Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel in place image subtract constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.28 NppStatus nppiSubC_32f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f aConstants[3], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel image subtract constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.29 NppStatus nppiSubC_32f_C4IR (const Npp32f aConstants[4], Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel in place image subtract constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.30 NppStatus nppiSubC_32f_C4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f aConstants[4], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel image subtract constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.31 NppStatus nppiSubC_32fc_AC4IR (const Npp32fc aConstants[3], Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha in place image subtract constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.32 NppStatus nppiSubC_32fc_AC4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc aConstants[3], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha image subtract constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.33 NppStatus nppiSubC_32fc_C1IR (const Npp32fc *nConstant*, Npp32fc * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image subtract constant.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.34 NppStatus nppiSubC_32fc_C1R (const Npp32fc * *pSrc1*, int *nSrc1Step*, const Npp32fc *nConstant*, Npp32fc * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image subtract constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.35 NppStatus nppiSubC_32fc_C3IR (const Npp32fc *aConstants*[3], Npp32fc * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image subtract constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.36 `NppStatus nppiSubC_32fc_C3R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc aConstants[3], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image subtract constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.37 `NppStatus nppiSubC_32fc_C4IR (const Npp32fc aConstants[4], Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image subtract constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.38 `NppStatus nppiSubC_32fc_C4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc aConstants[4], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image subtract constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.39 `NppStatus nppiSubC_32s_C1IRSfs (const Npp32s nConstant, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.40 `NppStatus nppiSubC_32s_C1RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s nConstant, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.41 `NppStatus nppiSubC_32s_C3IRSfs (const Npp32s aConstants[3], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.42 `NppStatus nppiSubC_32s_C3RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s aConstants[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.43 `NppStatus nppiSubC_32sc_AC4IRSfs (const Npp32sc aConstants[3], Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image subtract constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.44 `NppStatus nppiSubC_32sc_AC4RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc aConstants[3], Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.45 `NppStatus nppiSubC_32sc_C1IRSfs (const Npp32sc nConstant, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.46 `NppStatus nppiSubC_32sc_C1RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc nConstant, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.47 `NppStatus nppiSubC_32sc_C3IRSfs (const Npp32sc aConstants[3], Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.48 `NppStatus nppiSubC_32sc_C3RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc aConstants[3], Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.49 `NppStatus nppiSubC_8u_AC4IRSfs (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha in place image subtract constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.50 `NppStatus nppiSubC_8u_AC4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.51 `NppStatus nppiSubC_8u_C1IRSfs (const Npp8u nConstant, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.52 NppStatus nppiSubC_8u_C1RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u nConstant, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 8-bit unsigned char channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.53 NppStatus nppiSubC_8u_C3RSfs (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 8-bit unsigned char channel 8-bit unsigned char in place image subtract constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.54 NppStatus nppiSubC_8u_C3RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 8-bit unsigned char channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.55 `NppStatus nppiSubC_8u_C4IRSfs (const Npp8u aConstants[4], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.56 `NppStatus nppiSubC_8u_C4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[4], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11 DivC

Divides each pixel of an image by a constant value.

Functions

- `NppStatus nppiDivC_8u_C1RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` nConstant, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_8u_C1IRSfs` (const `Npp8u` nConstant, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel in place image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_8u_C3RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` aConstants[3], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_8u_C3IRSfs` (const `Npp8u` aConstants[3], `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel 8-bit unsigned char in place image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_8u_AC4RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` aConstants[3], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_8u_AC4IRSfs` (const `Npp8u` aConstants[3], `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha in place image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_8u_C4RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` aConstants[4], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_8u_C4IRSfs` (const `Npp8u` aConstants[4], `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel in place image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_16u_C1RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` nConstant, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_16u_C1IRSfs` (const `Npp16u` nConstant, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel in place image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_16u_C3RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[3], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_16u_C3IRSfs` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel in place image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_16u_AC4RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[3], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_16u_AC4IRSfs` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha in place image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_16u_C4RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[4], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_16u_C4IRSfs` (const `Npp16u` aConstants[4], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel in place image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_16s_C1RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` nConstant, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short channel image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_16s_C1IRSfs` (const `Npp16s` nConstant, `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_16s_C3RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` aConstants[3], `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_16s_C3IRSfs` (const `Npp16s` aConstants[3], `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short channel in place image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_16s_AC4RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` aConstants[3], `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_16s_AC4IRSfs` (const `Npp16s` aConstants[3], `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha in place image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_16s_C4RSfs` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp16s aConstants[4]`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 16-bit signed short channel image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_16s_C4IRSfs` (const `Npp16s aConstants[4]`, `Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 16-bit signed short channel in place image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_16sc_C1RSfs` (const `Npp16sc *pSrc1`, int `nSrc1Step`, const `Npp16sc nConstant`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_16sc_C1IRSfs` (const `Npp16sc nConstant`, `Npp16sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_16sc_C3RSfs` (const `Npp16sc *pSrc1`, int `nSrc1Step`, const `Npp16sc aConstants[3]`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_16sc_C3IRSfs` (const `Npp16sc aConstants[3]`, `Npp16sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_16sc_AC4RSfs` (const `Npp16sc *pSrc1`, int `nSrc1Step`, const `Npp16sc aConstants[3]`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_16sc_AC4IRSfs` (const `Npp16sc aConstants[3]`, `Npp16sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_32s_C1RSfs` (const `Npp32s *pSrc1`, int `nSrc1Step`, const `Npp32s nConstant`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
One 32-bit signed integer channel image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_32s_C1IRSfs` (const `Npp32s nConstant`, `Npp32s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
One 32-bit signed integer channel in place image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_32s_C3RSfs` (const `Npp32s *pSrc1`, int `nSrc1Step`, const `Npp32s aConstants[3]`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Three 32-bit signed integer channel image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_32s_C3IRSfs` (const `Npp32s aConstants[3]`, `Npp32s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Three 32-bit signed integer channel in place image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_32sc_C1RSfs` (const `Npp32sc *pSrc1`, int `nSrc1Step`, const `Npp32sc nConstant`, `Npp32sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_32sc_C1IRSfs` (const `Npp32sc nConstant`, `Npp32sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_32sc_C3RSfs` (const `Npp32sc *pSrc1`, int `nSrc1Step`, const `Npp32sc aConstants[3]`, `Npp32sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_32sc_C3IRSfs` (const `Npp32sc aConstants[3]`, `Npp32sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_32sc_AC4RSfs` (const `Npp32sc *pSrc1`, int `nSrc1Step`, const `Npp32sc aConstants[3]`, `Npp32sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_32sc_AC4IRSfs` (const `Npp32sc aConstants[3]`, `Npp32sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_32f_C1R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f nConstant`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

One 32-bit floating point channel image divided by constant.

- `NppStatus nppiDivC_32f_C1IR` (const `Npp32f nConstant`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

One 32-bit floating point channel in place image divided by constant.

- `NppStatus nppiDivC_32f_C3R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f aConstants[3]`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Three 32-bit floating point channel image divided by constant.

- `NppStatus nppiDivC_32f_C3IR` (const `Npp32f aConstants[3]`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Three 32-bit floating point channel in place image divided by constant.

- `NppStatus nppiDivC_32f_AC4R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f aConstants[3]`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Four 32-bit floating point channel with unmodified alpha image divided by constant.

- **NppStatus nppiDivC_32f_AC4R** (const **Npp32f** aConstants[3], **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point channel with unmodified alpha in place image divided by constant.
- **NppStatus nppiDivC_32f_C4R** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** aConstants[4], **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point channel image divided by constant.
- **NppStatus nppiDivC_32f_C4IR** (const **Npp32f** aConstants[4], **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point channel in place image divided by constant.
- **NppStatus nppiDivC_32fc_C1R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** nConstant, **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image divided by constant.
- **NppStatus nppiDivC_32fc_C1IR** (const **Npp32fc** nConstant, **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image divided by constant.
- **NppStatus nppiDivC_32fc_C3R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** aConstants[3], **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image divided by constant.
- **NppStatus nppiDivC_32fc_C3IR** (const **Npp32fc** aConstants[3], **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image divided by constant.
- **NppStatus nppiDivC_32fc_AC4R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** aConstants[3], **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha image divided by constant.
- **NppStatus nppiDivC_32fc_AC4IR** (const **Npp32fc** aConstants[3], **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha in place image divided by constant.
- **NppStatus nppiDivC_32fc_C4R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** aConstants[4], **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image divided by constant.
- **NppStatus nppiDivC_32fc_C4IR** (const **Npp32fc** aConstants[4], **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image divided by constant.

7.11.1 Detailed Description

Divides each pixel of an image by a constant value.

7.11.2 Function Documentation

7.11.2.1 `NppStatus nppiDivC_16s_AC4IRSfs (const Npp16s aConstants[3], Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel with unmodified alpha in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11.2.2 `NppStatus nppiDivC_16s_AC4RSfs (const Npp16s * pSrcI, int nSrcIStep, const Npp16s aConstants[3], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel with unmodified alpha image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrcI Source-Image Pointer.

nSrcIStep Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11.2.3 `NppStatus nppiDivC_16s_C1RSfs (const Npp16s nConstant, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.4 `NppStatus nppiDivC_16s_C1RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s nConstant, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.5 `NppStatus nppiDivC_16s_C3IRSfs (const Npp16s aConstants[3], Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit signed short channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.6 NppStatus nppiDivC_16s_C3RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s aConstants[3], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.7 NppStatus nppiDivC_16s_C4RSfs (const Npp16s aConstants[4], Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.8 NppStatus nppiDivC_16s_C4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s aConstants[4], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11.2.9 NppStatus nppiDivC_16sc_AC4IRSfs (const Npp16sc aConstants[3], Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11.2.10 NppStatus nppiDivC_16sc_AC4RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc aConstants[3], Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11.2.11 NppStatus nppiDivC_16sc_C1IRSfs (const Npp16sc nConstant, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.12 NppStatus nppiDivC_16sc_C1RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc nConstant, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.13 NppStatus nppiDivC_16sc_C3IRSfs (const Npp16sc aConstants[3], Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11.2.14 `NppStatus nppiDivC_16sc_C3RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc aConstants[3], Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11.2.15 `NppStatus nppiDivC_16u_AC4IRSfs (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel with unmodified alpha in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11.2.16 `NppStatus nppiDivC_16u_AC4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel with unmodified alpha image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.17 `NppStatus nppiDivC_16u_C1IRSfs (const Npp16u nConstant, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit unsigned short channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.18 `NppStatus nppiDivC_16u_C1RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u nConstant, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit unsigned short channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11.2.19 NppStatus nppiDivC_16u_C3IRSfs (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11.2.20 NppStatus nppiDivC_16u_C3RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11.2.21 NppStatus nppiDivC_16u_C4IRSfs (const Npp16u aConstants[4], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.22 NppStatus nppiDivC_16u_C4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[4], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.23 NppStatus nppiDivC_32f_AC4IR (const Npp32f aConstants[3], Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel with unmodified alpha in place image divided by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.24 `NppStatus nppiDivC_32f_AC4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f aConstants[3], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel with unmodified alpha image divided by constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11.2.25 `NppStatus nppiDivC_32f_C1IR (const Npp32f nConstant, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 32-bit floating point channel in place image divided by constant.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11.2.26 `NppStatus nppiDivC_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f nConstant, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit floating point channel image divided by constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nConstant* Constant.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11.2.27 NppStatus nppiDivC_32f_C3IR (const Npp32f aConstants[3], Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel in place image divided by constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.28 NppStatus nppiDivC_32f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f aConstants[3], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel image divided by constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.29 NppStatus nppiDivC_32f_C4IR (const Npp32f aConstants[4], Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel in place image divided by constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.30 NppStatus nppiDivC_32f_C4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f aConstants[4], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel image divided by constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11.2.31 NppStatus nppiDivC_32fc_AC4IR (const Npp32fc aConstants[3], Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha in place image divided by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11.2.32 NppStatus nppiDivC_32fc_AC4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc aConstants[3], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha image divided by constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11.2.33 `NppStatus nppiDivC_32fc_C1IR` (`const Npp32fc nConstant`, `Npp32fc * pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`)

One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image divided by constant.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.34 `NppStatus nppiDivC_32fc_C1R` (`const Npp32fc * pSrc1`, `int nSrc1Step`, `const Npp32fc nConstant`, `Npp32fc * pDst`, `int nDstStep`, `NppiSize oSizeROI`)

One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image divided by constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.35 `NppStatus nppiDivC_32fc_C3IR` (`const Npp32fc aConstants[3]`, `Npp32fc * pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`)

Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image divided by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.36 NppStatus nppiDivC_32fc_C3R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc aConstants[3], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image divided by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.37 NppStatus nppiDivC_32fc_C4IR (const Npp32fc aConstants[4], Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image divided by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.38 NppStatus nppiDivC_32fc_C4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc aConstants[4], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image divided by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11.2.39 NppStatus nppiDivC_32s_C1RSfs (const Npp32s nConstant, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 32-bit signed integer channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11.2.40 NppStatus nppiDivC_32s_C1RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s nConstant, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 32-bit signed integer channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11.2.41 NppStatus nppiDivC_32s_C3IRSfs (const Npp32s aConstants[3], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 32-bit signed integer channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.42 `NppStatus nppiDivC_32s_C3RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s aConstants[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.43 `NppStatus nppiDivC_32sc_AC4IRSfs (const Npp32sc aConstants[3], Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.44 `NppStatus nppiDivC_32sc_AC4RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc aConstants[3], Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.45 `NppStatus nppiDivC_32sc_C1IRSfs (const Npp32sc nConstant, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.46 `NppStatus nppiDivC_32sc_C1RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc nConstant, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.47 `NppStatus nppiDivC_32sc_C3IRSfs (const Npp32sc aConstants[3], Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.48 `NppStatus nppiDivC_32sc_C3RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc aConstants[3], Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.49 `NppStatus nppiDivC_8u_AC4IRSfs (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.50 `NppStatus nppiDivC_8u_AC4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.51 `NppStatus nppiDivC_8u_C1IRSfs (const Npp8u nConstant, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11.2.52 NppStatus nppiDivC_8u_C1RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u nConstant, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 8-bit unsigned char channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11.2.53 NppStatus nppiDivC_8u_C3RSfs (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 8-bit unsigned char channel 8-bit unsigned char in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11.2.54 NppStatus nppiDivC_8u_C3RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 8-bit unsigned char channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.55 `NppStatus nppiDivC_8u_C4IRSfs (const Npp8u aConstants[4], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.56 `NppStatus nppiDivC_8u_C4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[4], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.12 AbsDiffC

Determines absolute difference between each pixel of an image and a constant value.

Functions

- `NppStatus nppiAbsDiffC_8u_C1R` (const `Npp8u *pSrc1`, int `nSrc1Step`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `Npp8u nConstant`)
One 8-bit unsigned char channel image absolute difference with constant.
- `NppStatus nppiAbsDiffC_16u_C1R` (const `Npp16u *pSrc1`, int `nSrc1Step`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `Npp16u nConstant`)
One 16-bit unsigned short channel image absolute difference with constant.
- `NppStatus nppiAbsDiffC_32f_C1R` (const `Npp32f *pSrc1`, int `nSrc1Step`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `Npp32f nConstant`)
One 32-bit floating point channel image absolute difference with constant.

7.12.1 Detailed Description

Determines absolute difference between each pixel of an image and a constant value.

7.12.2 Function Documentation

7.12.2.1 `NppStatus nppiAbsDiffC_16u_C1R` (const `Npp16u *pSrc1`, int `nSrc1Step`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `Npp16u nConstant`)

One 16-bit unsigned short channel image absolute difference with constant.

Parameters:

- `pSrc1` Source-Image Pointer.
- `nSrc1Step` Source-Image Line Step.
- `nConstant` Constant.
- `pDst` Destination-Image Pointer.
- `nDstStep` Destination-Image Line Step.
- `oSizeROI` Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.12.2.2 `NppStatus nppiAbsDiffC_32f_C1R` (const `Npp32f *pSrc1`, int `nSrc1Step`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `Npp32f nConstant`)

One 32-bit floating point channel image absolute difference with constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.3 NppStatus nppiAbsDiffC_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, Npp8u nConstant)

One 8-bit unsigned char channel image absolute difference with constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13 Add

Pixel by pixel addition of two images.

Functions

- `NppStatus nppiAdd_8u_C1RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 8-bit unsigned char channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_8u_C1IRSfs` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 8-bit unsigned char channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_8u_C3RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 8-bit unsigned char channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_8u_C3IRSfs` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 8-bit unsigned char channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_8u_AC4RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel with unmodified alpha image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_8u_AC4IRSfs` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel with unmodified alpha in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_8u_C4RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_8u_C4IRSfs` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_16u_C1RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiAdd_16u_C1IRSfs` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_16u_C3RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_16u_C3IRSfs` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_16u_AC4RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_16u_AC4IRSfs` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_16u_C4RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_16u_C4IRSfs` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_16s_C1RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` *pSrc2, int nSrc2Step, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_16s_C1IRSfs` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_16s_C3RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` *pSrc2, int nSrc2Step, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_16s_C3IRSfs` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiAdd_16s_AC4RSfs` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp16s *pSrc2`, int `nSrc2Step`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short channel with unmodified alpha image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiAdd_16s_AC4RSfs` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short channel with unmodified alpha in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiAdd_16s_C4RSfs` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp16s *pSrc2`, int `nSrc2Step`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiAdd_16s_C4IRSfs` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiAdd_16sc_C1RSfs` (const `Npp16sc *pSrc1`, int `nSrc1Step`, const `Npp16sc *pSrc2`, int `nSrc2Step`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiAdd_16sc_C1IRSfs` (const `Npp16sc *pSrc`, int `nSrcStep`, `Npp16sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiAdd_16sc_C3RSfs` (const `Npp16sc *pSrc1`, int `nSrc1Step`, const `Npp16sc *pSrc2`, int `nSrc2Step`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiAdd_16sc_C3IRSfs` (const `Npp16sc *pSrc`, int `nSrcStep`, `Npp16sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiAdd_16sc_AC4RSfs` (const `Npp16sc *pSrc1`, int `nSrc1Step`, const `Npp16sc *pSrc2`, int `nSrc2Step`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiAdd_16sc_AC4IRSfs` (const `Npp16sc *pSrc`, int `nSrcStep`, `Npp16sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiAdd_32s_C1RSfs` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_32s_C1R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)

Note: This function is to be deprecated in future NPP releases, use the function above with a scale factor of 0 instead.
- `NppStatus nppiAdd_32s_C1IRSfs` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_32s_C3RSfs` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_32s_C3IRSfs` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_32sc_C1RSfs` (const `Npp32sc` *pSrc1, int nSrc1Step, const `Npp32sc` *pSrc2, int nSrc2Step, `Npp32sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_32sc_C1IRSfs` (const `Npp32sc` *pSrc, int nSrcStep, `Npp32sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_32sc_C3RSfs` (const `Npp32sc` *pSrc1, int nSrc1Step, const `Npp32sc` *pSrc2, int nSrc2Step, `Npp32sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_32sc_C3IRSfs` (const `Npp32sc` *pSrc, int nSrcStep, `Npp32sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_32sc_AC4RSfs` (const `Npp32sc` *pSrc1, int nSrc1Step, const `Npp32sc` *pSrc2, int nSrc2Step, `Npp32sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_32sc_AC4IRSfs` (const `Npp32sc` *pSrc, int nSrcStep, `Npp32sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image addition, scale by $2^{-nScaleFactor}$, then clamp to saturated value.

- `NppStatus nppiAdd_32f_C1R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f *pSrc2`, int `nSrc2Step`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
One 32-bit floating point channel image addition.
- `NppStatus nppiAdd_32f_C1IR` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
One 32-bit floating point channel in place image addition.
- `NppStatus nppiAdd_32f_C3R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f *pSrc2`, int `nSrc2Step`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Three 32-bit floating point channel image addition.
- `NppStatus nppiAdd_32f_C3IR` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
One 32-bit floating point channel in place image addition.
- `NppStatus nppiAdd_32f_AC4R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f *pSrc2`, int `nSrc2Step`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point channel with unmodified alpha image addition.
- `NppStatus nppiAdd_32f_AC4IR` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point channel with unmodified alpha in place image addition.
- `NppStatus nppiAdd_32f_C4R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f *pSrc2`, int `nSrc2Step`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point channel image addition.
- `NppStatus nppiAdd_32f_C4IR` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point channel in place image addition.
- `NppStatus nppiAdd_32fc_C1R` (const `Npp32fc *pSrc1`, int `nSrc1Step`, const `Npp32fc *pSrc2`, int `nSrc2Step`, `Npp32fc *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image addition.
- `NppStatus nppiAdd_32fc_C1IR` (const `Npp32fc *pSrc`, int `nSrcStep`, `Npp32fc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image addition.
- `NppStatus nppiAdd_32fc_C3R` (const `Npp32fc *pSrc1`, int `nSrc1Step`, const `Npp32fc *pSrc2`, int `nSrc2Step`, `Npp32fc *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Three 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image addition.
- `NppStatus nppiAdd_32fc_C3IR` (const `Npp32fc *pSrc`, int `nSrcStep`, `Npp32fc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image addition.

- **NppStatus nppiAdd_32fc_AC4R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** *pSrc2, int nSrc2Step, **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image addition.
- **NppStatus nppiAdd_32fc_AC4IR** (const **Npp32fc** *pSrc, int nSrcStep, **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image addition.
- **NppStatus nppiAdd_32fc_C4R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** *pSrc2, int nSrc2Step, **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image addition.
- **NppStatus nppiAdd_32fc_C4IR** (const **Npp32fc** *pSrc, int nSrcStep, **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image addition.

7.13.1 Detailed Description

Pixel by pixel addition of two images.

7.13.2 Function Documentation

7.13.2.1 **NppStatus nppiAdd_16s_AC4IRSfs** (const **Npp16s** * pSrc, int nSrcStep, **Npp16s** * pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.13.2.2 **NppStatus nppiAdd_16s_AC4RSfs** (const **Npp16s** * pSrc1, int nSrc1Step, const **Npp16s** * pSrc2, int nSrc2Step, **Npp16s** * pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.3 `NppStatus nppiAdd_16s_C1IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.4 `NppStatus nppiAdd_16s_C1RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.5 NppStatus nppiAdd_16s_C3IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.6 NppStatus nppiAdd_16s_C3RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.7 `NppStatus nppiAdd_16s_C4IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.8 `NppStatus nppiAdd_16s_C4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.9 `NppStatus nppiAdd_16sc_AC4IRSfs (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.10 NppStatus nppiAdd_16sc_AC4RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc * pSrc2, int nSrc2Step, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.11 NppStatus nppiAdd_16sc_C1IRSfs (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.12 NppStatus nppiAdd_16sc_C1RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc * pSrc2, int nSrc2Step, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.13.2.13 NppStatus nppiAdd_16sc_C3RSfs (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.13.2.14 NppStatus nppiAdd_16sc_C3RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc * pSrc2, int nSrc2Step, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.15 NppStatus nppiAdd_16u_AC4IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.16 NppStatus nppiAdd_16u_AC4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.17 NppStatus nppiAdd_16u_C1RSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image addition, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.18 NppStatus nppiAdd_16u_C1RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel image addition, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.19 `NppStatus nppiAdd_16u_C3IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit unsigned short channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.13.2.20 `NppStatus nppiAdd_16u_C3RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit unsigned short channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.13.2.21 `NppStatus nppiAdd_16u_C4IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.22 `NppStatus nppiAdd_16u_C4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.23 `NppStatus nppiAdd_32f_AC4IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel with unmodified alpha in place image addition.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.24 `NppStatus nppiAdd_32f_AC4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel with unmodified alpha image addition.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.13.2.25 `NppStatus nppiAdd_32f_C1IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 32-bit floating point channel in place image addition.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.13.2.26 `NppStatus nppiAdd_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit floating point channel image addition.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.27 NppStatus nppiAdd_32f_C3IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit floating point channel in place image addition.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.28 NppStatus nppiAdd_32f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel image addition.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.29 NppStatus nppiAdd_32f_C4IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel in place image addition.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.30 NppStatus nppiAdd_32f_C4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel image addition.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.31 NppStatus nppiAdd_32fc_AC4IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image addition.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.32 `NppStatus nppiAdd_32fc_AC4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image addition.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.13.2.33 `NppStatus nppiAdd_32fc_C1IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image addition.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.13.2.34 `NppStatus nppiAdd_32fc_C1R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image addition.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.235 `NppStatus nppiAdd_32fc_C3IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image addition.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.236 `NppStatus nppiAdd_32fc_C3R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image addition.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.37 `NppStatus nppiAdd_32fc_C4IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image addition.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.38 `NppStatus nppiAdd_32fc_C4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image addition.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.39 `NppStatus nppiAdd_32s_C1IRSfs (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.40 NppStatus nppiAdd_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Note: This function is to be deprecated in future NPP releases, use the function above with a scale factor of 0 instead.

32-bit image add. Add the pixel values of corresponding pixels in the ROI and write them to the output image.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.41 NppStatus nppiAdd_32s_C1RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 32-bit signed integer channel image addition, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.42 `NppStatus nppiAdd_32s_C3IRSfs (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.13.2.43 `NppStatus nppiAdd_32s_C3RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.13.2.44 `NppStatus nppiAdd_32sc_AC4IRSfs (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.45 NppStatus nppiAdd_32sc_AC4RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc * pSrc2, int nSrc2Step, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image addition, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.46 NppStatus nppiAdd_32sc_C1IRSfs (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image addition, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.47 NppStatus nppiAdd_32sc_C1RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc * pSrc2, int nSrc2Step, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image addition, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.13.2.48 NppStatus nppiAdd_32sc_C3RSfs (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image addition, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.13.2.49 NppStatus nppiAdd_32sc_C3RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc * pSrc2, int nSrc2Step, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image addition, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.50 **NppStatus nppiAdd_8u_AC4IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)**

Four 8-bit unsigned char channel with unmodified alpha in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.51 **NppStatus nppiAdd_8u_AC4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)**

Four 8-bit unsigned char channel with unmodified alpha image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.52 `NppStatus nppiAdd_8u_C1IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.53 `NppStatus nppiAdd_8u_C1RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.54 `NppStatus nppiAdd_8u_C3IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.55 `NppStatus nppiAdd_8u_C3RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.56 `NppStatus nppiAdd_8u_C4IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13.2.57 `NppStatus nppiAdd_8u_C4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.14 AddSquare

Pixel by pixel addition of squared pixels from source image to floating point pixel values of destination image.

Functions

- **NppStatus nppiAddSquare_8u32f_C1IMR** (const **Npp8u** *pSrc, int nSrcStep, const **Npp8u** *pMask, int nMaskStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel image squared then added to in place floating point destination image using filter mask (updates destination when mask is non-zero).
- **NppStatus nppiAddSquare_8u32f_C1IR** (const **Npp8u** *pSrc, int nSrcStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel image squared then added to in place floating point destination image.
- **NppStatus nppiAddSquare_16u32f_C1IMR** (const **Npp16u** *pSrc, int nSrcStep, const **Npp8u** *pMask, int nMaskStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel image squared then added to in place floating point destination image using filter mask (updates destination when mask is non-zero).
- **NppStatus nppiAddSquare_16u32f_C1IR** (const **Npp16u** *pSrc, int nSrcStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel image squared then added to in place floating point destination image.
- **NppStatus nppiAddSquare_32f_C1IMR** (const **Npp32f** *pSrc, int nSrcStep, const **Npp8u** *pMask, int nMaskStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 32-bit floating point channel image squared then added to in place floating point destination image using filter mask (updates destination when mask is non-zero).
- **NppStatus nppiAddSquare_32f_C1IR** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 32-bit floating point channel image squared then added to in place floating point destination image.

7.14.1 Detailed Description

Pixel by pixel addition of squared pixels from source image to floating point pixel values of destination image.

7.14.2 Function Documentation

7.14.2.1 **NppStatus nppiAddSquare_16u32f_C1IMR** (const **Npp16u** *pSrc, int nSrcStep, const **Npp8u** *pMask, int nMaskStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)

One 16-bit unsigned short channel image squared then added to in place floating point destination image using filter mask (updates destination when mask is non-zero).

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.14.2.2 **NppStatus nppiAddSquare_16u32f_C1IR** (const Npp16u * *pSrc*, int *nSrcStep*, Npp32f * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

One 16-bit unsigned short channel image squared then added to in place floating point destination image.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.14.2.3 **NppStatus nppiAddSquare_32f_C1IMR** (const Npp32f * *pSrc*, int *nSrcStep*, const Npp8u * *pMask*, int *nMaskStep*, Npp32f * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

One 32-bit floating point channel image squared then added to in place floating point destination image using filter mask (updates destination when mask is non-zero).

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.14.2.4 NppStatus nppiAddSquare_32f_C1IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit floating point channel image squared then added to in place floating point destination image.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.14.2.5 NppStatus nppiAddSquare_8u32f_C1IMR (const Npp8u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 8-bit unsigned char channel image squared then added to in place floating point destination image using filter mask (updates destination when mask is non-zero).

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.14.2.6 NppStatus nppiAddSquare_8u32f_C1IR (const Npp8u * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 8-bit unsigned char channel image squared then added to in place floating point destination image.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.15 AddProduct

Pixel by pixel addition of product of pixels from two source images to floating point pixel values of destination image.

Functions

- **NppStatus nppiAddProduct_8u32f_C1IMR** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, const **Npp8u** *pMask, int nMaskStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel image product added to in place floating point destination image using filter mask (updates destination when mask is non-zero).
- **NppStatus nppiAddProduct_8u32f_C1IR** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel image product added to in place floating point destination image.
- **NppStatus nppiAddProduct_16u32f_C1IMR** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, const **Npp8u** *pMask, int nMaskStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel image product added to in place floating point destination image using filter mask (updates destination when mask is non-zero).
- **NppStatus nppiAddProduct_16u32f_C1IR** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel image product added to in place floating point destination image.
- **NppStatus nppiAddProduct_32f_C1IMR** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, const **Npp8u** *pMask, int nMaskStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 32-bit floating point channel image product added to in place floating point destination image using filter mask (updates destination when mask is non-zero).
- **NppStatus nppiAddProduct_32f_C1IR** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 32-bit floating point channel image product added to in place floating point destination image.

7.15.1 Detailed Description

Pixel by pixel addition of product of pixels from two source images to floating point pixel values of destination image.

7.15.2 Function Documentation

- 7.15.2.1 NppStatus nppiAddProduct_16u32f_C1IMR** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, const **Npp8u** *pMask, int nMaskStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)

One 16-bit unsigned short channel image product added to in place floating point destination image using filter mask (updates destination when mask is non-zero).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.15.2.2 NppStatus nppiAddProduct_16u32f_C11R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 16-bit unsigned short channel image product added to in place floating point destination image.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.15.2.3 NppStatus nppiAddProduct_32f_C11MR (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit floating point channel image product added to in place floating point destination image using filter mask (updates destination when mask is non-zero).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.15.2.4 **NppStatus nppiAddProduct_32f_C1IR** (const Npp32f * *pSrc1*, int *nSrc1Step*, const Npp32f * *pSrc2*, int *nSrc2Step*, Npp32f * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

One 32-bit floating point channel image product added to in place floating point destination image.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.15.2.5 **NppStatus nppiAddProduct_8u32f_C1IMR** (const Npp8u * *pSrc1*, int *nSrc1Step*, const Npp8u * *pSrc2*, int *nSrc2Step*, const Npp8u * *pMask*, int *nMaskStep*, Npp32f * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

One 8-bit unsigned char channel image product added to in place floating point destination image using filter mask (updates destination when mask is non-zero).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.15.2.6 NppStatus nppiAddProduct_8u32f_C1IR (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 8-bit unsigned char channel image product added to in place floating point destination image.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16 AddWeighted

Pixel by pixel addition of alpha weighted pixel values from a source image to floating point pixel values of destination image.

Functions

- **NppStatus nppiAddWeighted_8u32f_C1IMR** (const **Npp8u** *pSrc, int nSrcStep, const **Npp8u** *pMask, int nMaskStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **Npp32f** nAlpha)
One 8-bit unsigned char channel alpha weighted image added to in place floating point destination image using filter mask (updates destination when mask is non-zero).
- **NppStatus nppiAddWeighted_8u32f_C1IR** (const **Npp8u** *pSrc, int nSrcStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **Npp32f** nAlpha)
One 8-bit unsigned char channel alpha weighted image added to in place floating point destination image.
- **NppStatus nppiAddWeighted_16u32f_C1IMR** (const **Npp16u** *pSrc, int nSrcStep, const **Npp8u** *pMask, int nMaskStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **Npp32f** nAlpha)
One 16-bit unsigned short channel alpha weighted image added to in place floating point destination image using filter mask (updates destination when mask is non-zero).
- **NppStatus nppiAddWeighted_16u32f_C1IR** (const **Npp16u** *pSrc, int nSrcStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **Npp32f** nAlpha)
One 16-bit unsigned short channel alpha weighted image added to in place floating point destination image.
- **NppStatus nppiAddWeighted_32f_C1IMR** (const **Npp32f** *pSrc, int nSrcStep, const **Npp8u** *pMask, int nMaskStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **Npp32f** nAlpha)
One 32-bit floating point channel alpha weighted image added to in place floating point destination image using filter mask (updates destination when mask is non-zero).
- **NppStatus nppiAddWeighted_32f_C1IR** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **Npp32f** nAlpha)
One 32-bit floating point channel alpha weighted image added to in place floating point destination image.

7.16.1 Detailed Description

Pixel by pixel addition of alpha weighted pixel values from a source image to floating point pixel values of destination image.

7.16.2 Function Documentation

7.16.2.1 NppStatus nppiAddWeighted_16u32f_C1IMR (const Npp16u *pSrc, int nSrcStep, const Npp8u *pMask, int nMaskStep, Npp32f *pSrcDst, int nSrcDstStep, NppiSize oSizeROI, Npp32f nAlpha)

One 16-bit unsigned short channel alpha weighted image added to in place floating point destination image using filter mask (updates destination when mask is non-zero).

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nAlpha Alpha weight to be applied to source image pixels (0.0F to 1.0F)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16.2.2 `NppStatus nppiAddWeighted_16u32f_C1IR (const Npp16u * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, Npp32f nAlpha)`

One 16-bit unsigned short channel alpha weighted image added to in place floating point destination image.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nAlpha Alpha weight to be applied to source image pixels (0.0F to 1.0F)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16.2.3 `NppStatus nppiAddWeighted_32f_C1IMR (const Npp32f * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, Npp32f nAlpha)`

One 32-bit floating point channel alpha weighted image added to in place floating point destination image using filter mask (updates destination when mask is non-zero).

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nAlpha Alpha weight to be applied to source image pixels (0.0F to 1.0F)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16.2.4 NppStatus nppiAddWeighted_32f_C1IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, Npp32f nAlpha)

One 32-bit floating point channel alpha weighted image added to in place floating point destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nAlpha Alpha weight to be applied to source image pixels (0.0F to 1.0F)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16.2.5 NppStatus nppiAddWeighted_8u32f_C1IMR (const Npp8u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, Npp32f nAlpha)

One 8-bit unsigned char channel alpha weighted image added to in place floating point destination image using filter mask (updates destination when mask is non-zero).

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nAlpha Alpha weight to be applied to source image pixels (0.0F to 1.0F)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16.2.6 NppStatus nppiAddWeighted_8u32f_C1IR (const Npp8u * *pSrc*, int *nSrcStep*, Npp32f * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, Npp32f *nAlpha*)

One 8-bit unsigned char channel alpha weighted image added to in place floating point destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nAlpha Alpha weight to be applied to source image pixels (0.0F to 1.0F)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17 Mul

Pixel by pixel multiply of two images.

Functions

- **NppStatus nppiMul_8u_C1RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiMul_8u_C1IRSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiMul_8u_C3RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiMul_8u_C3IRSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiMul_8u_AC4RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiMul_8u_AC4IRSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiMul_8u_C4RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiMul_8u_C4IRSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiMul_16u_C1RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_16u_C1RSfs` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_16u_C3RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_16u_C3RSfs` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_16u_AC4RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_16u_AC4RSfs` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_16u_C4RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_16u_C4RSfs` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_16s_C1RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` *pSrc2, int nSrc2Step, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_16s_C1RSfs` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_16s_C3RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` *pSrc2, int nSrc2Step, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_16s_C3RSfs` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_16s_AC4RSfs` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp16s *pSrc2`, int `nSrc2Step`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short channel with unmodified alpha image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_16s_AC4RSfs` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pSrcDst`, int `nSrcDStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short channel with unmodified alpha in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_16s_C4RSfs` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp16s *pSrc2`, int `nSrc2Step`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_16s_C4RSfs` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pSrcDst`, int `nSrcDStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_16sc_C1RSfs` (const `Npp16sc *pSrc1`, int `nSrc1Step`, const `Npp16sc *pSrc2`, int `nSrc2Step`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_16sc_C1RSfs` (const `Npp16sc *pSrc`, int `nSrcStep`, `Npp16sc *pSrcDst`, int `nSrcDStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_16sc_C3RSfs` (const `Npp16sc *pSrc1`, int `nSrc1Step`, const `Npp16sc *pSrc2`, int `nSrc2Step`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_16sc_C3RSfs` (const `Npp16sc *pSrc`, int `nSrcStep`, `Npp16sc *pSrcDst`, int `nSrcDStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_16sc_AC4RSfs` (const `Npp16sc *pSrc1`, int `nSrc1Step`, const `Npp16sc *pSrc2`, int `nSrc2Step`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_16sc_AC4RSfs` (const `Npp16sc *pSrc`, int `nSrcStep`, `Npp16sc *pSrcDst`, int `nSrcDStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_32s_C1RSfs` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_32s_C1R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)

Note: This function is to be deprecated in future NPP releases, use the function above with a scale factor of 0 instead.
- `NppStatus nppiMul_32s_C1IRSfs` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_32s_C3RSfs` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_32s_C3IRSfs` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_32sc_C1RSfs` (const `Npp32sc` *pSrc1, int nSrc1Step, const `Npp32sc` *pSrc2, int nSrc2Step, `Npp32sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_32sc_C1IRSfs` (const `Npp32sc` *pSrc, int nSrcStep, `Npp32sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_32sc_C3RSfs` (const `Npp32sc` *pSrc1, int nSrc1Step, const `Npp32sc` *pSrc2, int nSrc2Step, `Npp32sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_32sc_C3IRSfs` (const `Npp32sc` *pSrc, int nSrcStep, `Npp32sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_32sc_AC4RSfs` (const `Npp32sc` *pSrc1, int nSrc1Step, const `Npp32sc` *pSrc2, int nSrc2Step, `Npp32sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_32sc_AC4IRSfs` (const `Npp32sc` *pSrc, int nSrcStep, `Npp32sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_32f_C1R` (const `Npp32f` *pSrc1, int nSrc1Step, const `Npp32f` *pSrc2, int nSrc2Step, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 32-bit floating point channel image multiplication.
- `NppStatus nppiMul_32f_C1IR` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 32-bit floating point channel in place image multiplication.
- `NppStatus nppiMul_32f_C3R` (const `Npp32f` *pSrc1, int nSrc1Step, const `Npp32f` *pSrc2, int nSrc2Step, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 32-bit floating point channel image multiplication.
- `NppStatus nppiMul_32f_C3IR` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 32-bit floating point channel in place image multiplication.
- `NppStatus nppiMul_32f_AC4R` (const `Npp32f` *pSrc1, int nSrc1Step, const `Npp32f` *pSrc2, int nSrc2Step, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit floating point channel with unmodified alpha image multiplication.
- `NppStatus nppiMul_32f_AC4IR` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit floating point channel with unmodified alpha in place image multiplication.
- `NppStatus nppiMul_32f_C4R` (const `Npp32f` *pSrc1, int nSrc1Step, const `Npp32f` *pSrc2, int nSrc2Step, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit floating point channel image multiplication.
- `NppStatus nppiMul_32f_C4IR` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit floating point channel in place image multiplication.
- `NppStatus nppiMul_32fc_C1R` (const `Npp32fc` *pSrc1, int nSrc1Step, const `Npp32fc` *pSrc2, int nSrc2Step, `Npp32fc` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image multiplication.
- `NppStatus nppiMul_32fc_C1IR` (const `Npp32fc` *pSrc, int nSrcStep, `Npp32fc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image multiplication.
- `NppStatus nppiMul_32fc_C3R` (const `Npp32fc` *pSrc1, int nSrc1Step, const `Npp32fc` *pSrc2, int nSrc2Step, `Npp32fc` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image multiplication.

- **NppStatus nppiMul_32fc_C3IR** (const **Npp32fc** *pSrc, int nSrcStep, **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image multiplication.
- **NppStatus nppiMul_32fc_AC4R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** *pSrc2, int nSrc2Step, **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image multiplication.
- **NppStatus nppiMul_32fc_AC4IR** (const **Npp32fc** *pSrc, int nSrcStep, **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image multiplication.
- **NppStatus nppiMul_32fc_C4R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** *pSrc2, int nSrc2Step, **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image multiplication.
- **NppStatus nppiMul_32fc_C4IR** (const **Npp32fc** *pSrc, int nSrcStep, **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image multiplication.

7.17.1 Detailed Description

Pixel by pixel multiply of two images.

7.17.2 Function Documentation

7.17.2.1 **NppStatus nppiMul_16s_AC4IRSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc** Source-Image Pointer.
- nSrcStep** Source-Image Line Step.
- pSrcDst** In-Place Image Pointer.
- nSrcDstStep** In-Place-Image Line Step.
- oSizeROI** Region-of-Interest (ROI).
- nScaleFactor** Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.2 `NppStatus nppiMul_16s_AC4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel with unmodified alpha image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17.2.3 `NppStatus nppiMul_16s_C1IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17.2.4 `NppStatus nppiMul_16s_C1RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17.2.5 `NppStatus nppiMul_16s_C3IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17.2.6 `NppStatus nppiMul_16s_C3RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit signed short channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17.2.7 NppStatus nppiMul_16s_C4IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17.2.8 NppStatus nppiMul_16s_C4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17.2.9 NppStatus nppiMul_16sc_AC4IRSfs (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.10 **NppStatus nppiMul_16sc_AC4RSfs** (const Npp16sc * *pSrc1*, int *nSrc1Step*, const Npp16sc * *pSrc2*, int *nSrc2Step*, Npp16sc * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.11 **NppStatus nppiMul_16sc_C1IRSfs** (const Npp16sc * *pSrc*, int *nSrcStep*, Npp16sc * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.12 NppStatus nppiMul_16sc_C1RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc * pSrc2, int nSrc2Step, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17.2.13 NppStatus nppiMul_16sc_C3RSfs (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17.2.14 NppStatus nppiMul_16sc_C3RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc * pSrc2, int nSrc2Step, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.15 **NppStatus nppiMul_16u_AC4IRSfs** (const Npp16u * *pSrc*, int *nSrcStep*, Npp16u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Four 16-bit unsigned short channel with unmodified alpha in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.16 **NppStatus nppiMul_16u_AC4RSfs** (const Npp16u * *pSrc1*, int *nSrc1Step*, const Npp16u * *pSrc2*, int *nSrc2Step*, Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Four 16-bit unsigned short channel with unmodified alpha image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.17 NppStatus nppiMul_16u_C1IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.18 NppStatus nppiMul_16u_C1RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.19 `NppStatus nppiMul_16u_C3IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit unsigned short channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17.2.20 `NppStatus nppiMul_16u_C3RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit unsigned short channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17.2.21 `NppStatus nppiMul_16u_C4IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.22 `NppStatus nppiMul_16u_C4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel image multiplication, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.23 `NppStatus nppiMul_32f_AC4IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel with unmodified alpha in place image multiplication.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.24 NppStatus nppiMul_32f_AC4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel with unmodified alpha image multiplication.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17.2.25 NppStatus nppiMul_32f_C1IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit floating point channel in place image multiplication.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17.2.26 NppStatus nppiMul_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit floating point channel image multiplication.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.27 `NppStatus nppiMul_32f_C3IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 32-bit floating point channel in place image multiplication.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.28 `NppStatus nppiMul_32f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit floating point channel image multiplication.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.29 NppStatus nppiMul_32f_C4IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel in place image multiplication.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.30 NppStatus nppiMul_32f_C4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel image multiplication.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.31 NppStatus nppiMul_32fc_AC4IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image multiplication.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.32 `NppStatus nppiMul_32fc_AC4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image multiplication.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.33 `NppStatus nppiMul_32fc_C1IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image multiplication.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.34 `NppStatus nppiMul_32fc_C1R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image multiplication.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.35 `NppStatus nppiMul_32fc_C3IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image multiplication.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.36 `NppStatus nppiMul_32fc_C3R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image multiplication.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.37 `NppStatus nppiMul_32fc_C4IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image multiplication.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17.2.38 `NppStatus nppiMul_32fc_C4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image multiplication.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17.2.39 `NppStatus nppiMul_32s_C1IRSfs (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.40 `NppStatus nppiMul_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Note: This function is to be deprecated in future NPP releases, use the function above with a scale factor of 0 instead.

1 channel 32-bit image multiplication. Multiply corresponding pixels in ROI.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.41 `NppStatus nppiMul_32s_C1RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.42 `NppStatus nppiMul_32s_C3IRSfs (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17.2.43 `NppStatus nppiMul_32s_C3RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17.2.44 `NppStatus nppiMul_32sc_AC4IRSfs (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.45 `NppStatus nppiMul_32sc_AC4RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc * pSrc2, int nSrc2Step, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.46 `NppStatus nppiMul_32sc_C1IRSfs (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.47 `NppStatus nppiMul_32sc_C1RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc * pSrc2, int nSrc2Step, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image multiplication, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17.2.48 `NppStatus nppiMul_32sc_C3IRSfs (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image multiplication, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17.2.49 `NppStatus nppiMul_32sc_C3RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc * pSrc2, int nSrc2Step, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image multiplication, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.50 **NppStatus nppiMul_8u_AC4IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)**

Four 8-bit unsigned char channel with unmodified alpha in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.51 **NppStatus nppiMul_8u_AC4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)**

Four 8-bit unsigned char channel with unmodified alpha image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.52 `NppStatus nppiMul_8u_C1RSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.53 `NppStatus nppiMul_8u_C1RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.54 NppStatus nppiMul_8u_C3IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 8-bit unsigned char channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.55 NppStatus nppiMul_8u_C3RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 8-bit unsigned char channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.56 NppStatus nppiMul_8u_C4IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.57 `NppStatus nppiMul_8u_C4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18 MulScale

Pixel by pixel multiplies each pixel of two images then scales the result by the maximum value for the data bit width.

Functions

- `NppStatus nppiMulScale_8u_C1R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel image multiplication then scale by maximum value for pixel bit width.
- `NppStatus nppiMulScale_8u_C1IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel in place image multiplication then scale by maximum value for pixel bit width.
- `NppStatus nppiMulScale_8u_C3R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 8-bit unsigned char channel image multiplication then scale by maximum value for pixel bit width.
- `NppStatus nppiMulScale_8u_C3IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel in place image multiplication then scale by maximum value for pixel bit width.
- `NppStatus nppiMulScale_8u_AC4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel with unmodified alpha image multiplication then scale by maximum value for pixel bit width.
- `NppStatus nppiMulScale_8u_AC4IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel with unmodified alpha in place image multiplication then scale by maximum value for pixel bit width.
- `NppStatus nppiMulScale_8u_C4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel image multiplication then scale by maximum value for pixel bit width.
- `NppStatus nppiMulScale_8u_C4IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel in place image multiplication then scale by maximum value for pixel bit width.
- `NppStatus nppiMulScale_16u_C1R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 16-bit unsigned short channel image multiplication then scale by maximum value for pixel bit width.
- `NppStatus nppiMulScale_16u_C1IR` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)

One 16-bit unsigned short channel in place image multiplication then scale by maximum value for pixel bit width.

- `NppStatus nppiMulScale_16u_C3R` (const `Npp16u *pSrc1`, int `nSrc1Step`, const `Npp16u *pSrc2`, int `nSrc2Step`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Three 16-bit unsigned short channel image multiplication then scale by maximum value for pixel bit width.

- `NppStatus nppiMulScale_16u_C3IR` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

One 16-bit unsigned short channel in place image multiplication then scale by maximum value for pixel bit width.

- `NppStatus nppiMulScale_16u_AC4R` (const `Npp16u *pSrc1`, int `nSrc1Step`, const `Npp16u *pSrc2`, int `nSrc2Step`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Four 16-bit unsigned short channel with unmodified alpha image multiplication then scale by maximum value for pixel bit width.

- `NppStatus nppiMulScale_16u_AC4IR` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Four 16-bit unsigned short channel with unmodified alpha in place image multiplication then scale by maximum value for pixel bit width.

- `NppStatus nppiMulScale_16u_C4R` (const `Npp16u *pSrc1`, int `nSrc1Step`, const `Npp16u *pSrc2`, int `nSrc2Step`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Four 16-bit unsigned short channel image multiplication then scale by maximum value for pixel bit width.

- `NppStatus nppiMulScale_16u_C4IR` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Four 16-bit unsigned short channel in place image multiplication then scale by maximum value for pixel bit width.

7.18.1 Detailed Description

Pixel by pixel multiplies each pixel of two images then scales the result by the maximum value for the data bit width.

7.18.2 Function Documentation

7.18.2.1 `NppStatus nppiMulScale_16u_AC4IR` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Four 16-bit unsigned short channel with unmodified alpha in place image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.2 NppStatus nppiMulScale_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel with unmodified alpha image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.3 NppStatus nppiMulScale_16u_C11R (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 16-bit unsigned short channel in place image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.4 `NppStatus nppiMulScale_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)`

One 16-bit unsigned short channel image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.5 `NppStatus nppiMulScale_16u_C3IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 16-bit unsigned short channel in place image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.6 `NppStatus nppiMulScale_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)`

Three 16-bit unsigned short channel image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.7 NppStatus nppiMulScale_16u_C4IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel in place image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.8 NppStatus nppiMulScale_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.9 `NppStatus nppiMulScale_8u_AC4IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel with unmodified alpha in place image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.10 `NppStatus nppiMulScale_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel with unmodified alpha image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.11 `NppStatus nppiMulScale_8u_C1IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel in place image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.12 `NppStatus nppiMulScale_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.13 `NppStatus nppiMulScale_8u_C3IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel in place image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.14 `NppStatus nppiMulScale_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Three 8-bit unsigned char channel image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.15 `NppStatus nppiMulScale_8u_C4IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.16 `NppStatus nppiMulScale_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19 Sub

Pixel by pixel subtraction of two images.

Functions

- `NppStatus nppiSub_8u_C1RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiSub_8u_C1IRSfs` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiSub_8u_C3RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiSub_8u_C3IRSfs` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiSub_8u_AC4RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiSub_8u_AC4IRSfs` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiSub_8u_C4RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiSub_8u_C4IRSfs` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiSub_16u_C1RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiSub_16u_C1IRSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16u_C3RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16u_C3IRSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16u_AC4RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16u_AC4IRSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16u_C4RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16u_C4IRSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16s_C1RSfs** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit signed short channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16s_C1IRSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16s_C3RSfs** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16s_C3IRSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiSub_16s_AC4RSfs** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16s_AC4IRSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16s_C4RSfs** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit signed short channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16s_C4IRSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit signed short channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16sc_C1RSfs** (const **Npp16sc** *pSrc1, int nSrc1Step, const **Npp16sc** *pSrc2, int nSrc2Step, **Npp16sc** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16sc_C1IRSfs** (const **Npp16sc** *pSrc, int nSrcStep, **Npp16sc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16sc_C3RSfs** (const **Npp16sc** *pSrc1, int nSrc1Step, const **Npp16sc** *pSrc2, int nSrc2Step, **Npp16sc** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16sc_C3IRSfs** (const **Npp16sc** *pSrc, int nSrcStep, **Npp16sc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16sc_AC4RSfs** (const **Npp16sc** *pSrc1, int nSrc1Step, const **Npp16sc** *pSrc2, int nSrc2Step, **Npp16sc** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16sc_AC4IRSfs** (const **Npp16sc** *pSrc, int nSrcStep, **Npp16sc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus** `nppiSub_32s_C1RSfs` (const **Npp32s** *pSrc1, int nSrc1Step, const **Npp32s** *pSrc2, int nSrc2Step, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 32-bit signed integer channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus** `nppiSub_32s_C1R` (const **Npp32s** *pSrc1, int nSrc1Step, const **Npp32s** *pSrc2, int nSrc2Step, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI)

Note: This function is to be deprecated in future NPP releases, use the function above with a scale factor of 0 instead.
- **NppStatus** `nppiSub_32s_C1RSfs` (const **Npp32s** *pSrc, int nSrcStep, **Npp32s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 32-bit signed integer channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus** `nppiSub_32s_C3RSfs` (const **Npp32s** *pSrc1, int nSrc1Step, const **Npp32s** *pSrc2, int nSrc2Step, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 32-bit signed integer channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus** `nppiSub_32s_C3RSfs` (const **Npp32s** *pSrc, int nSrcStep, **Npp32s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 32-bit signed integer channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus** `nppiSub_32s_C4RSfs` (const **Npp32s** *pSrc1, int nSrc1Step, const **Npp32s** *pSrc2, int nSrc2Step, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 32-bit signed integer channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus** `nppiSub_32s_C4RSfs` (const **Npp32s** *pSrc, int nSrcStep, **Npp32s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 32-bit signed integer channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus** `nppiSub_32sc_C1RSfs` (const **Npp32sc** *pSrc1, int nSrc1Step, const **Npp32sc** *pSrc2, int nSrc2Step, **Npp32sc** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus** `nppiSub_32sc_C1RSfs` (const **Npp32sc** *pSrc, int nSrcStep, **Npp32sc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus** `nppiSub_32sc_C3RSfs` (const **Npp32sc** *pSrc1, int nSrc1Step, const **Npp32sc** *pSrc2, int nSrc2Step, **Npp32sc** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- [NppStatus nppiSub_32sc_C3IRSfs](#) (const [Npp32sc](#) *pSrc, int nSrcStep, [Npp32sc](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI, int nScaleFactor)

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- [NppStatus nppiSub_32sc_AC4RSfs](#) (const [Npp32sc](#) *pSrc1, int nSrc1Step, const [Npp32sc](#) *pSrc2, int nSrc2Step, [Npp32sc](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, int nScaleFactor)

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- [NppStatus nppiSub_32sc_AC4IRSfs](#) (const [Npp32sc](#) *pSrc, int nSrcStep, [Npp32sc](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI, int nScaleFactor)

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- [NppStatus nppiSub_32f_C1R](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)

One 32-bit floating point channel image subtraction.
- [NppStatus nppiSub_32f_C1IR](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)

One 32-bit floating point channel in place image subtraction.
- [NppStatus nppiSub_32f_C3R](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)

Three 32-bit floating point channel image subtraction.
- [NppStatus nppiSub_32f_C3IR](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)

One 32-bit floating point channel in place image subtraction.
- [NppStatus nppiSub_32f_AC4R](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)

Four 32-bit floating point channel with unmodified alpha image subtraction.
- [NppStatus nppiSub_32f_AC4IR](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)

Four 32-bit floating point channel with unmodified alpha in place image subtraction.
- [NppStatus nppiSub_32f_C4R](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)

Four 32-bit floating point channel image subtraction.
- [NppStatus nppiSub_32f_C4IR](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)

Four 32-bit floating point channel in place image subtraction.
- [NppStatus nppiSub_32fc_C1R](#) (const [Npp32fc](#) *pSrc1, int nSrc1Step, const [Npp32fc](#) *pSrc2, int nSrc2Step, [Npp32fc](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)

One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image subtraction.

- **NppStatus nppiSub_32fc_C1IR** (const **Npp32fc** *pSrc, int nSrcStep, **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image subtraction.
- **NppStatus nppiSub_32fc_C3R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** *pSrc2, int nSrc2Step, **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image subtraction.
- **NppStatus nppiSub_32fc_C3IR** (const **Npp32fc** *pSrc, int nSrcStep, **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image subtraction.
- **NppStatus nppiSub_32fc_AC4R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** *pSrc2, int nSrc2Step, **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image subtraction.
- **NppStatus nppiSub_32fc_AC4IR** (const **Npp32fc** *pSrc, int nSrcStep, **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image subtraction.
- **NppStatus nppiSub_32fc_C4R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** *pSrc2, int nSrc2Step, **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image subtraction.
- **NppStatus nppiSub_32fc_C4IR** (const **Npp32fc** *pSrc, int nSrcStep, **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image subtraction.

7.19.1 Detailed Description

Pixel by pixel subtraction of two images.

7.19.2 Function Documentation

7.19.2.1 **NppStatus nppiSub_16s_AC4IRSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha in place image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pSrcDst* In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.2 NppStatus nppiSub_16s_AC4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.3 NppStatus nppiSub_16s_C1IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.4 NppStatus nppiSub_16s_C1RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.5 NppStatus nppiSub_16s_C3RSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.6 NppStatus nppiSub_16s_C3RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.7 **NppStatus nppiSub_16s_C4IRSfs** (const Npp16s * *pSrc*, int *nSrcStep*, Npp16s * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Four 16-bit signed short channel in place image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.8 **NppStatus nppiSub_16s_C4RSfs** (const Npp16s * *pSrc1*, int *nSrc1Step*, const Npp16s * *pSrc2*, int *nSrc2Step*, Npp16s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Four 16-bit signed short channel image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.9 NppStatus nppiSub_16sc_AC4IRSfs (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.10 NppStatus nppiSub_16sc_AC4RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc * pSrc2, int nSrc2Step, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.11 NppStatus nppiSub_16sc_C1IRSfs (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.12 `NppStatus nppiSub_16sc_C1RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc * pSrc2, int nSrc2Step, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.13 `NppStatus nppiSub_16sc_C3IRSfs (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.14 `NppStatus nppiSub_16sc_C3RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc * pSrc2, int nSrc2Step, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.15 `NppStatus nppiSub_16u_AC4RSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel with unmodified alpha in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.16 `NppStatus nppiSub_16u_AC4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel with unmodified alpha image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.17 **NppStatus nppiSub_16u_C1RSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)**

One 16-bit unsigned short channel in place image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.18 **NppStatus nppiSub_16u_C1RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)**

One 16-bit unsigned short channel image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.19 NppStatus nppiSub_16u_C3IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.20 NppStatus nppiSub_16u_C3RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.21 NppStatus nppiSub_16u_C4IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.22 NppStatus nppiSub_16u_C4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.23 NppStatus nppiSub_32f_AC4IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel with unmodified alpha in place image subtraction.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.24 NppStatus nppiSub_32f_AC4R (const Npp32f * *pSrc1*, int *nSrc1Step*, const Npp32f * *pSrc2*, int *nSrc2Step*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

Four 32-bit floating point channel with unmodified alpha image subtraction.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.25 NppStatus nppiSub_32f_C1IR (const Npp32f * *pSrc*, int *nSrcStep*, Npp32f * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

One 32-bit floating point channel in place image subtraction.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.26 `NppStatus nppiSub_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit floating point channel image subtraction.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.27 `NppStatus nppiSub_32f_C3IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 32-bit floating point channel in place image subtraction.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.28 `NppStatus nppiSub_32f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit floating point channel image subtraction.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.29 `NppStatus nppiSub_32f_C4IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel in place image subtraction.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.30 `NppStatus nppiSub_32f_C4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel image subtraction.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.31 `NppStatus nppiSub_32fc_AC4IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image subtraction.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.32 `NppStatus nppiSub_32fc_AC4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image subtraction.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.33 `NppStatus nppiSub_32fc_C1IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image subtraction.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.34 `NppStatus nppiSub_32fc_C1R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image subtraction.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.35 `NppStatus nppiSub_32fc_C3IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image subtraction.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.36 `NppStatus nppiSub_32fc_C3R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image subtraction.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.37 `NppStatus nppiSub_32fc_C4IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image subtraction.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.38 `NppStatus nppiSub_32fc_C4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image subtraction.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.39 `NppStatus nppiSub_32s_C1IRSfs (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer channel in place image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.40 `NppStatus nppiSub_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Note: This function is to be deprecated in future NPP releases, use the function above with a scale factor of 0 instead.

32-bit image subtraction. Subtract pSrc1's pixels from corresponding pixels in pSrc2.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.41 `NppStatus nppiSub_32s_C1RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.42 `NppStatus nppiSub_32s_C3IRSfs (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.43 `NppStatus nppiSub_32s_C3RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.44 NppStatus nppiSub_32s_C4IRSfs (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 32-bit signed integer channel in place image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.45 NppStatus nppiSub_32s_C4RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 32-bit signed integer channel image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.46 NppStatus nppiSub_32sc_AC4IRSfs (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.47 NppStatus nppiSub_32sc_AC4RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc * pSrc2, int nSrc2Step, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.48 `NppStatus nppiSub_32sc_C1IRSfs (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.49 `NppStatus nppiSub_32sc_C1RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc * pSrc2, int nSrc2Step, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.50 `NppStatus nppiSub_32sc_C3IRSfs (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.51 `NppStatus nppiSub_32sc_C3RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc * pSrc2, int nSrc2Step, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.52 `NppStatus nppiSub_8u_AC4IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.53 `NppStatus nppiSub_8u_AC4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.54 `NppStatus nppiSub_8u_C1IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.55 `NppStatus nppiSub_8u_C1RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.56 NppStatus nppiSub_8u_C3IRSfs (const Npp8u * *pSrc*, int *nSrcStep*, Npp8u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

One 8-bit unsigned char channel in place image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.57 NppStatus nppiSub_8u_C3RSfs (const Npp8u * *pSrc1*, int *nSrc1Step*, const Npp8u * *pSrc2*, int *nSrc2Step*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Three 8-bit unsigned char channel image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.58 `NppStatus nppiSub_8u_C4IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.59 `NppStatus nppiSub_8u_C4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20 Div

Pixel by pixel division of two images.

Functions

- `NppStatus nppiDiv_8u_C1RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_8u_C1IRSfs` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_8u_C3RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_8u_C3IRSfs` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_8u_AC4RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_8u_AC4IRSfs` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_8u_C4RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_8u_C4IRSfs` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_16u_C1RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_16u_C1IRSfs` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_16u_C3RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_16u_C3IRSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_16u_AC4RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_16u_AC4IRSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_16u_C4RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_16u_C4IRSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_16s_C1RSfs** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit signed short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_16s_C1IRSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_16s_C3RSfs** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_16s_C3IRSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiDiv_16s_AC4RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` *pSrc2, int nSrc2Step, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_16s_AC4IRSfs` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_16s_C4RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` *pSrc2, int nSrc2Step, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_16s_C4IRSfs` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_16sc_C1RSfs` (const `Npp16sc` *pSrc1, int nSrc1Step, const `Npp16sc` *pSrc2, int nSrc2Step, `Npp16sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_16sc_C1IRSfs` (const `Npp16sc` *pSrc, int nSrcStep, `Npp16sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_16sc_C3RSfs` (const `Npp16sc` *pSrc1, int nSrc1Step, const `Npp16sc` *pSrc2, int nSrc2Step, `Npp16sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_16sc_C3IRSfs` (const `Npp16sc` *pSrc, int nSrcStep, `Npp16sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_16sc_AC4RSfs` (const `Npp16sc` *pSrc1, int nSrc1Step, const `Npp16sc` *pSrc2, int nSrc2Step, `Npp16sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_16sc_AC4IRSfs` (const `Npp16sc` *pSrc, int nSrcStep, `Npp16sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_32s_C1RSfs` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiDiv_32s_C1R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)

Note: This function is to be deprecated in future NPP releases, use the function above with a scale factor of 0 instead.

- `NppStatus nppiDiv_32s_C1IRSfs` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiDiv_32s_C3RSfs` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiDiv_32s_C3IRSfs` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiDiv_32sc_C1RSfs` (const `Npp32sc` *pSrc1, int nSrc1Step, const `Npp32sc` *pSrc2, int nSrc2Step, `Npp32sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiDiv_32sc_C1IRSfs` (const `Npp32sc` *pSrc, int nSrcStep, `Npp32sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiDiv_32sc_C3RSfs` (const `Npp32sc` *pSrc1, int nSrc1Step, const `Npp32sc` *pSrc2, int nSrc2Step, `Npp32sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiDiv_32sc_C3IRSfs` (const `Npp32sc` *pSrc, int nSrcStep, `Npp32sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiDiv_32sc_AC4RSfs` (const `Npp32sc` *pSrc1, int nSrc1Step, const `Npp32sc` *pSrc2, int nSrc2Step, `Npp32sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiDiv_32sc_AC4IRSfs` (const `Npp32sc` *pSrc, int nSrcStep, `Npp32sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- [NppStatus nppiDiv_32f_C1R](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
One 32-bit floating point channel image division.
- [NppStatus nppiDiv_32f_C1IR](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
One 32-bit floating point channel in place image division.
- [NppStatus nppiDiv_32f_C3R](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Three 32-bit floating point channel image division.
- [NppStatus nppiDiv_32f_C3IR](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
One 32-bit floating point channel in place image division.
- [NppStatus nppiDiv_32f_AC4R](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Four 32-bit floating point channel with unmodified alpha image division.
- [NppStatus nppiDiv_32f_AC4IR](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
Four 32-bit floating point channel with unmodified alpha in place image division.
- [NppStatus nppiDiv_32f_C4R](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Four 32-bit floating point channel image division.
- [NppStatus nppiDiv_32f_C4IR](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
Four 32-bit floating point channel in place image division.
- [NppStatus nppiDiv_32fc_C1R](#) (const [Npp32fc](#) *pSrc1, int nSrc1Step, const [Npp32fc](#) *pSrc2, int nSrc2Step, [Npp32fc](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image division.
- [NppStatus nppiDiv_32fc_C1IR](#) (const [Npp32fc](#) *pSrc, int nSrcStep, [Npp32fc](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image division.
- [NppStatus nppiDiv_32fc_C3R](#) (const [Npp32fc](#) *pSrc1, int nSrc1Step, const [Npp32fc](#) *pSrc2, int nSrc2Step, [Npp32fc](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Three 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image division.
- [NppStatus nppiDiv_32fc_C3IR](#) (const [Npp32fc](#) *pSrc, int nSrcStep, [Npp32fc](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image division.
- [NppStatus nppiDiv_32fc_AC4R](#) (const [Npp32fc](#) *pSrc1, int nSrc1Step, const [Npp32fc](#) *pSrc2, int nSrc2Step, [Npp32fc](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image division.

- **NppStatus nppiDiv_32fc_AC4IR** (const **Npp32fc** *pSrc, int nSrcStep, **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image division.

- **NppStatus nppiDiv_32fc_C4R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** *pSrc2, int nSrc2Step, **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image division.

- **NppStatus nppiDiv_32fc_C4IR** (const **Npp32fc** *pSrc, int nSrcStep, **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image division.

7.20.1 Detailed Description

Pixel by pixel division of two images.

7.20.2 Function Documentation

7.20.2.1 NppStatus nppiDiv_16s_AC4IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc** Source-Image Pointer.
- nSrcStep** Source-Image Line Step.
- pSrcDst** In-Place Image Pointer.
- nSrcDstStep** In-Place-Image Line Step.
- oSizeROI** Region-of-Interest (ROI).
- nScaleFactor** Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.2 NppStatus nppiDiv_16s_AC4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc1** Source-Image Pointer.

nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.3 NppStatus nppiDiv_16s_C1IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.4 NppStatus nppiDiv_16s_C1RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short channel image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.5 NppStatus nppiDiv_16s_C3IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.6 NppStatus nppiDiv_16s_C3RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.7 NppStatus nppiDiv_16s_C4IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.8 `NppStatus nppiDiv_16s_C4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.9 `NppStatus nppiDiv_16sc_AC4IRSfs (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.10 NppStatus nppiDiv_16sc_AC4RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc * pSrc2, int nSrc2Step, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.11 NppStatus nppiDiv_16sc_C1IRSfs (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.12 NppStatus nppiDiv_16sc_C1RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc * pSrc2, int nSrc2Step, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.13 **NppStatus nppiDiv_16sc_C3IRSfs (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)**

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.14 **NppStatus nppiDiv_16sc_C3RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc * pSrc2, int nSrc2Step, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)**

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.15 NppStatus nppiDiv_16u_AC4IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.16 NppStatus nppiDiv_16u_AC4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.17 `NppStatus nppiDiv_16u_C1IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit unsigned short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.18 `NppStatus nppiDiv_16u_C1RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit unsigned short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.19 `NppStatus nppiDiv_16u_C3IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit unsigned short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.20 `NppStatus nppiDiv_16u_C3RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit unsigned short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.21 `NppStatus nppiDiv_16u_C4IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.22 `NppStatus nppiDiv_16u_C4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.23 `NppStatus nppiDiv_32f_AC4IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel with unmodified alpha in place image division.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.24 `NppStatus nppiDiv_32f_AC4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel with unmodified alpha image division.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.25 NppStatus nppiDiv_32f_C1IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit floating point channel in place image division.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.26 NppStatus nppiDiv_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit floating point channel image division.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.27 NppStatus nppiDiv_32f_C3IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit floating point channel in place image division.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.28 NppStatus nppiDiv_32f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel image division.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.29 NppStatus nppiDiv_32f_C4IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel in place image division.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.30 `NppStatus nppiDiv_32f_C4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel image division.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.31 `NppStatus nppiDiv_32fc_AC4IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image division.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.32 `NppStatus nppiDiv_32fc_AC4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image division.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.33 `NppStatus nppiDiv_32fc_C1IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image division.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.34 `NppStatus nppiDiv_32fc_C1R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image division.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.35 NppStatus nppiDiv_32fc_C3IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image division.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.36 NppStatus nppiDiv_32fc_C3R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image division.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.37 NppStatus nppiDiv_32fc_C4IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image division.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.38 `NppStatus nppiDiv_32fc_C4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image division.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.39 `NppStatus nppiDiv_32s_C1IRSfs (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.40 `NppStatus nppiDiv_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Note: This function is to be deprecated in future NPP releases, use the function above with a scale factor of 0 instead.

32-bit image division. Divide pixels in pSrc2 by pSrc1's pixels.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.41 NppStatus nppiDiv_32s_C1RSfs (const Npp32s * *pSrc1*, int *nSrc1Step*, const Npp32s * *pSrc2*, int *nSrc2Step*, Npp32s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

One 32-bit signed integer channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.42 NppStatus nppiDiv_32s_C3IRSfs (const Npp32s * *pSrc*, int *nSrcStep*, Npp32s * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

One 32-bit signed integer channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.43 `NppStatus nppiDiv_32s_C3RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer channel image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.44 `NppStatus nppiDiv_32sc_AC4IRSfs (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.45 `NppStatus nppiDiv_32sc_AC4RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc * pSrc2, int nSrc2Step, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.46 `NppStatus nppiDiv_32sc_C1RSfs (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.47 `NppStatus nppiDiv_32sc_C1RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc * pSrc2, int nSrc2Step, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.48 NppStatus nppiDiv_32sc_C3IRSfs (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.49 NppStatus nppiDiv_32sc_C3RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc * pSrc2, int nSrc2Step, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.50 `NppStatus nppiDiv_8u_AC4IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.51 `NppStatus nppiDiv_8u_AC4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.52 `NppStatus nppiDiv_8u_C1IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.53 `NppStatus nppiDiv_8u_C1RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.54 `NppStatus nppiDiv_8u_C3IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.55 `NppStatus nppiDiv_8u_C3RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.56 `NppStatus nppiDiv_8u_C4IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.57 `NppStatus nppiDiv_8u_C4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21 Div_Round

Pixel by pixel division of two images using result rounding modes.

Functions

- **NppStatus nppiDiv_Round_8u_C1RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
One 8-bit unsigned char channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_8u_C1IRSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
One 8-bit unsigned char channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_8u_C3RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
Three 8-bit unsigned char channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_8u_C3IRSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
Three 8-bit unsigned char channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_8u_AC4RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
Four 8-bit unsigned char channel image division with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_8u_AC4IRSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
Four 8-bit unsigned char channel in place image division with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_8u_C4RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
Four 8-bit unsigned char channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_8u_C4IRSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
Four 8-bit unsigned char channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_16u_C1RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)

One 16-bit unsigned short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_Round_16u_C1RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)

One 16-bit unsigned short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_Round_16u_C3RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)

Three 16-bit unsigned short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_Round_16u_C3RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)

Three 16-bit unsigned short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_Round_16u_AC4RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)

Four 16-bit unsigned short channel image division with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_Round_16u_AC4RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)

Four 16-bit unsigned short channel in place image division with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_Round_16u_C4RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)

Four 16-bit unsigned short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_Round_16u_C4RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)

Four 16-bit unsigned short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_Round_16s_C1RSfs** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)

One 16-bit signed short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_Round_16s_C1RSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)

One 16-bit signed short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_Round_16s_C3RSfs** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
Three 16-bit signed short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_16s_C3IRSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
Three 16-bit signed short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_16s_AC4RSfs** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
Four 16-bit signed short channel image division with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_16s_AC4IRSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
Four 16-bit signed short channel in place image division with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_16s_C4RSfs** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
Four 16-bit signed short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_16s_C4IRSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
Four 16-bit signed short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

7.21.1 Detailed Description

Pixel by pixel division of two images using result rounding modes.

7.21.2 Function Documentation

7.21.2.1 **NppStatus nppiDiv_Round_16s_AC4IRSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)

Four 16-bit signed short channel in place image division with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pSrcDst* In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21.2.2 NppStatus nppiDiv_Round_16s_AC4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)

Four 16-bit signed short channel image division with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21.2.3 NppStatus nppiDiv_Round_16s_C1IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)

One 16-bit signed short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21.2.4 NppStatus nppiDiv_Round_16s_C1RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)

One 16-bit signed short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21.2.5 NppStatus nppiDiv_Round_16s_C3IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)

Three 16-bit signed short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21.2.6 NppStatus nppiDiv_Round_16s_C3RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)

Three 16-bit signed short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.21.2.7 NppStatus nppiDiv_Round_16s_C4IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)

Four 16-bit signed short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.21.2.8 NppStatus nppiDiv_Round_16s_C4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)

Four 16-bit signed short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21.2.9 NppStatus nppiDiv_Round_16u_AC4IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)

Four 16-bit unsigned short channel in place image division with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21.2.10 `NppStatus nppiDiv_Round_16u_AC4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)`

Four 16-bit unsigned short channel image division with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.21.2.11 `NppStatus nppiDiv_Round_16u_C1IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)`

One 16-bit unsigned short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.21.2.12 NppStatus nppiDiv_Round_16u_C1RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)

One 16-bit unsigned short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21.2.13 NppStatus nppiDiv_Round_16u_C3IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)

Three 16-bit unsigned short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21.2.14 `NppStatus nppiDiv_Round_16u_C3RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)`

Three 16-bit unsigned short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.21.2.15 `NppStatus nppiDiv_Round_16u_C4IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)`

Four 16-bit unsigned short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.21.2.16 `NppStatus nppiDiv_Round_16u_C4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)`

Four 16-bit unsigned short channel image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.21.2.17 `NppStatus nppiDiv_Round_8u_AC4IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)`

Four 8-bit unsigned char channel in place image division with unmodified alpha, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.21.2.18 `NppStatus nppiDiv_Round_8u_AC4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)`

Four 8-bit unsigned char channel image division with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.21.2.19 `NppStatus nppiDiv_Round_8u_C1IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)`

One 8-bit unsigned char channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.21.2.20 `NppStatus nppiDiv_Round_8u_C1RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)`

One 8-bit unsigned char channel image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.21.2.21 `NppStatus nppiDiv_Round_8u_C3IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)`

Three 8-bit unsigned char channel in place image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.21.2.22 NppStatus nppiDiv_Round_8u_C3RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)

Three 8-bit unsigned char channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.21.2.23 NppStatus nppiDiv_Round_8u_C4IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)

Four 8-bit unsigned char channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.21.2.24 `NppStatus nppiDiv_Round_8u_C4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)`

Four 8-bit unsigned char channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.22 Abs

Absolute value of each pixel value in an image.

Functions

- `NppStatus nppiAbs_16s_C1R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 16-bit signed short channel image absolute value.
- `NppStatus nppiAbs_16s_C1IR` (`Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 16-bit signed short channel in place image absolute value.
- `NppStatus nppiAbs_16s_C3R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 16-bit signed short channel image absolute value.
- `NppStatus nppiAbs_16s_C3IR` (`Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 16-bit signed short channel in place image absolute value.
- `NppStatus nppiAbs_16s_AC4R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit signed short channel image absolute value with unmodified alpha.
- `NppStatus nppiAbs_16s_AC4IR` (`Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit signed short channel in place image absolute value with unmodified alpha.
- `NppStatus nppiAbs_16s_C4R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit signed short channel image absolute value.
- `NppStatus nppiAbs_16s_C4IR` (`Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit signed short channel in place image absolute value.
- `NppStatus nppiAbs_32f_C1R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 32-bit floating point channel image absolute value.
- `NppStatus nppiAbs_32f_C1IR` (`Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 32-bit floating point channel in place image absolute value.
- `NppStatus nppiAbs_32f_C3R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 32-bit floating point channel image absolute value.
- `NppStatus nppiAbs_32f_C3IR` (`Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 32-bit floating point channel in place image absolute value.
- `NppStatus nppiAbs_32f_AC4R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)

Four 32-bit floating point channel image absolute value with unmodified alpha.

- **NppStatus nppiAbs_32f_AC4IR** (**Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point channel in place image absolute value with unmodified alpha.
- **NppStatus nppiAbs_32f_C4R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point channel image absolute value.
- **NppStatus nppiAbs_32f_C4IR** (**Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point channel in place image absolute value.

7.22.1 Detailed Description

Absolute value of each pixel value in an image.

7.22.2 Function Documentation

7.22.2.1 NppStatus nppiAbs_16s_AC4IR (Npp16s *pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 16-bit signed short channel in place image absolute value with unmodified alpha.

Parameters:

- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.22.2.2 NppStatus nppiAbs_16s_AC4R (const Npp16s *pSrc, int nSrcStep, Npp16s *pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit signed short channel image absolute value with unmodified alpha.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.22.2.3 NppStatus nppiAbs_16s_C1IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 16-bit signed short channel in place image absolute value.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.22.2.4 NppStatus nppiAbs_16s_C1R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

One 16-bit signed short channel image absolute value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.22.2.5 NppStatus nppiAbs_16s_C3IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 16-bit signed short channel in place image absolute value.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.22.2.6 NppStatus nppiAbs_16s_C3R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

Three 16-bit signed short channel image absolute value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.22.2.7 NppStatus nppiAbs_16s_C4IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 16-bit signed short channel in place image absolute value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.22.2.8 NppStatus nppiAbs_16s_C4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit signed short channel image absolute value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.22.2.9 NppStatus nppiAbs_32f_AC4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel in place image absolute value with unmodified alpha.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.22.2.10 NppStatus nppiAbs_32f_AC4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel image absolute value with unmodified alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.22.2.11 NppStatus nppiAbs_32f_C1IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit floating point channel in place image absolute value.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.22.2.12 NppStatus nppiAbs_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit floating point channel image absolute value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.22.2.13 NppStatus nppiAbs_32f_C3IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel in place image absolute value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.22.2.14 NppStatus nppiAbs_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel image absolute value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.22.2.15 NppStatus nppiAbs_32f_C4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel in place image absolute value.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.22.2.16 NppStatus nppiAbs_32f_C4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel image absolute value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23 AbsDiff

Pixel by pixel absolute difference between two images.

Functions

- `NppStatus nppiAbsDiff_8u_C1R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel absolute difference of image1 minus image2.
- `NppStatus nppiAbsDiff_8u_C3R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 8-bit unsigned char channels absolute difference of image1 minus image2.
- `NppStatus nppiAbsDiff_8u_C4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channels absolute difference of image1 minus image2.
- `NppStatus nppiAbsDiff_16u_C1R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 16-bit unsigned short channel absolute difference of image1 minus image2.
- `NppStatus nppiAbsDiff_32f_C1R` (const `Npp32f` *pSrc1, int nSrc1Step, const `Npp32f` *pSrc2, int nSrc2Step, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 32-bit floating point channel absolute difference of image1 minus image2.

7.23.1 Detailed Description

Pixel by pixel absolute difference between two images.

7.23.2 Function Documentation

7.23.2.1 `NppStatus nppiAbsDiff_16u_C1R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)

One 16-bit unsigned short channel absolute difference of image1 minus image2.

Parameters:

- `pSrc1` Source-Image Pointer.
- `nSrc1Step` Source-Image Line Step.
- `pSrc2` Source-Image Pointer.
- `nSrc2Step` Source-Image Line Step.
- `pDst` Destination-Image Pointer.
- `nDstStep` Destination-Image Line Step.
- `oSizeROI` Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.23.2.2 `NppStatus nppiAbsDiff_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit floating point channel absolute difference of image1 minus image2.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.23.2.3 `NppStatus nppiAbsDiff_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel absolute difference of image1 minus image2.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.23.2.4 `NppStatus nppiAbsDiff_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Three 8-bit unsigned char channels absolute difference of image1 minus image2.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.5 NppStatus nppiAbsDiff_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channels absolute difference of image1 minus image2.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24 Sqr

Square each pixel in an image.

Functions

- **NppStatus nppiSqr_8u_C1RSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 8-bit unsigned char channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqr_8u_C1IRSfs** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 8-bit unsigned char channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqr_8u_C3RSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 8-bit unsigned char channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqr_8u_C3IRSfs** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 8-bit unsigned char channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqr_8u_AC4RSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel image squared with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqr_8u_AC4IRSfs** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel in place image squared with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqr_8u_C4RSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqr_8u_C4IRSfs** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqr_16u_C1RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqr_16u_C1IRSfs** (**Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

One 16-bit unsigned short channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSqr_16u_C3RSfs` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Three 16-bit unsigned short channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSqr_16u_C3IRSfs` (`Npp16u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Three 16-bit unsigned short channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSqr_16u_AC4RSfs` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit unsigned short channel image squared with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSqr_16u_AC4IRSfs` (`Npp16u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit unsigned short channel in place image squared with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSqr_16u_C4RSfs` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit unsigned short channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSqr_16u_C4IRSfs` (`Npp16u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit unsigned short channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSqr_16s_C1RSfs` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

One 16-bit signed short channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSqr_16s_C1IRSfs` (`Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

One 16-bit signed short channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSqr_16s_C3RSfs` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Three 16-bit signed short channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSqr_16s_C3IRSfs` (`Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Three 16-bit signed short channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSqr_16s_AC4RSfs` (`const Npp16s *pSrc`, `int nSrcStep`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `int nScaleFactor`)
Four 16-bit signed short channel image squared with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiSqr_16s_AC4IRSfs` (`Npp16s *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `int nScaleFactor`)
Four 16-bit signed short channel in place image squared with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiSqr_16s_C4RSfs` (`const Npp16s *pSrc`, `int nSrcStep`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `int nScaleFactor`)
Four 16-bit signed short channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiSqr_16s_C4IRSfs` (`Npp16s *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `int nScaleFactor`)
Four 16-bit signed short channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiSqr_32f_C1R` (`const Npp32f *pSrc`, `int nSrcStep`, `Npp32f *pDst`, `int nDstStep`, `NppiSize oSizeROI`)
One 32-bit floating point channel image squared.
- `NppStatus nppiSqr_32f_C1IR` (`Npp32f *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`)
One 32-bit floating point channel in place image squared.
- `NppStatus nppiSqr_32f_C3R` (`const Npp32f *pSrc`, `int nSrcStep`, `Npp32f *pDst`, `int nDstStep`, `NppiSize oSizeROI`)
Three 32-bit floating point channel image squared.
- `NppStatus nppiSqr_32f_C3IR` (`Npp32f *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`)
Three 32-bit floating point channel in place image squared.
- `NppStatus nppiSqr_32f_AC4R` (`const Npp32f *pSrc`, `int nSrcStep`, `Npp32f *pDst`, `int nDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point channel image squared with unmodified alpha.
- `NppStatus nppiSqr_32f_AC4IR` (`Npp32f *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point channel in place image squared with unmodified alpha.
- `NppStatus nppiSqr_32f_C4R` (`const Npp32f *pSrc`, `int nSrcStep`, `Npp32f *pDst`, `int nDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point channel image squared.
- `NppStatus nppiSqr_32f_C4IR` (`Npp32f *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point channel in place image squared.

7.24.1 Detailed Description

Square each pixel in an image.

7.24.2 Function Documentation

7.24.2.1 NppStatus nppiSqr_16s_AC4IRSfs (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short channel in place image squared with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.24.2.2 NppStatus nppiSqr_16s_AC4RSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short channel image squared with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.24.2.3 NppStatus nppiSqr_16s_C1IRSfs (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.24.2.4 `NppStatus nppiSqr_16s_C1RSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short channel image squared, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.5 `NppStatus nppiSqr_16s_C3IRSfs (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit signed short channel in place image squared, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.6 `NppStatus nppiSqr_16s_C3RSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit signed short channel image squared, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.7 NppStatus nppiSqr_16s_C4IRSfs (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.24.2.8 NppStatus nppiSqr_16s_C4RSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.24.2.9 NppStatus nppiSqr_16u_AC4IRSfs (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel in place image squared with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.24.2.10 `NppStatus nppiSqr_16u_AC4RSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel image squared with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.11 `NppStatus nppiSqr_16u_C1IRSfs (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit unsigned short channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.12 `NppStatus nppiSqr_16u_C1RSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit unsigned short channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.13 `NppStatus nppiSqr_16u_C3IRSfs (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit unsigned short channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.14 `NppStatus nppiSqr_16u_C3RSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit unsigned short channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.15 `NppStatus nppiSqr_16u_C4IRSfs (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.16 `NppStatus nppiSqr_16u_C4RSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel image squared, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.17 `NppStatus nppiSqr_32f_AC4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel in place image squared with unmodified alpha.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.18 `NppStatus nppiSqr_32f_AC4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel image squared with unmodified alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.19 NppStatus nppiSqr_32f_C1IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit floating point channel in place image squared.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.20 NppStatus nppiSqr_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit floating point channel image squared.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.21 NppStatus nppiSqr_32f_C3IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel in place image squared.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.22 NppStatus nppiSqr_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel image squared.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.23 NppStatus nppiSqr_32f_C4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel in place image squared.

Parameters:

- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.24 NppStatus nppiSqr_32f_C4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel image squared.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.25 NppStatus nppiSqr_8u_AC4IRSfs (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel in place image squared with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.26 NppStatus nppiSqr_8u_AC4RSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel image squared with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.27 NppStatus nppiSqr_8u_C1IRSfs (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 8-bit unsigned char channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.28 `NppStatus nppiSqr_8u_C1RSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.29 `NppStatus nppiSqr_8u_C3IRSfs (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.30 `NppStatus nppiSqr_8u_C3RSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.31 NppStatus nppiSqr_8u_C4IRSfs (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel in place image squared, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.32 NppStatus nppiSqr_8u_C4RSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel image squared, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25 Sqrt

Pixel by pixel square root of each pixel in an image.

Functions

- **NppStatus nppiSqrt_8u_C1RSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_8u_C1IRSfs** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel in place image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_8u_C3RSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_8u_C3IRSfs** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel in place image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_8u_AC4RSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel image square root with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_8u_AC4IRSfs** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel in place image square root with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_16u_C1RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_16u_C1IRSfs** (**Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel in place image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_16u_C3RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 16-bit unsigned short channel image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiSqrt_16u_C3IRSfs** (**Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 16-bit unsigned short channel in place image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_16u_AC4RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 16-bit unsigned short channel image square root with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_16u_AC4IRSfs** (**Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 16-bit unsigned short channel in place image square root with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_16s_C1RSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit signed short channel image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_16s_C1IRSfs** (**Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit signed short channel in place image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_16s_C3RSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 16-bit signed short channel image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_16s_C3IRSfs** (**Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 16-bit signed short channel in place image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_16s_AC4RSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 16-bit signed short channel image square root with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_16s_AC4IRSfs** (**Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 16-bit signed short channel in place image square root with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 32-bit floating point channel image square root.
- **NppStatus nppiSqrt_32f_C1IR** (**Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 32-bit floating point channel in place image square root.

- `NppStatus nppiSqrt_32f_C3R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Three 32-bit floating point channel image square root.
- `NppStatus nppiSqrt_32f_C3IR` (`Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Three 32-bit floating point channel in place image square root.
- `NppStatus nppiSqrt_32f_AC4R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point channel image square root with unmodified alpha.
- `NppStatus nppiSqrt_32f_AC4IR` (`Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point channel in place image square root with unmodified alpha.
- `NppStatus nppiSqrt_32f_C4R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point channel image square root.
- `NppStatus nppiSqrt_32f_C4IR` (`Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point channel in place image square root.

7.25.1 Detailed Description

Pixel by pixel square root of each pixel in an image.

7.25.2 Function Documentation

7.25.2.1 `NppStatus nppiSqrt_16s_AC4IRSfs` (`Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short channel in place image square root with unmodified alpha, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.25.2.2 **NppStatus nppiSqrt_16s_AC4RSfs** (const Npp16s * *pSrc*, int *nSrcStep*, Npp16s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Four 16-bit signed short channel image square root with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25.2.3 **NppStatus nppiSqrt_16s_C1IRSfs** (Npp16s * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

One 16-bit signed short channel in place image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25.2.4 **NppStatus nppiSqrt_16s_C1RSfs** (const Npp16s * *pSrc*, int *nSrcStep*, Npp16s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

One 16-bit signed short channel image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.25.2.5 NppStatus nppiSqrt_16s_C3IRSfs (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short channel in place image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.25.2.6 NppStatus nppiSqrt_16s_C3RSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.25.2.7 NppStatus nppiSqrt_16u_AC4IRSfs (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel in place image square root with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25.2.8 NppStatus nppiSqrt_16u_AC4RSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel image square root with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25.2.9 NppStatus nppiSqrt_16u_C1IRSfs (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25.2.10 NppStatus nppiSqrt_16u_C1RSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.25.2.11 NppStatus nppiSqrt_16u_C3IRSfs (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel in place image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.25.2.12 NppStatus nppiSqrt_16u_C3RSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.25.2.13 NppStatus nppiSqrt_32f_AC4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel in place image square root with unmodified alpha.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25.2.14 NppStatus nppiSqrt_32f_AC4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel image square root with unmodified alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25.2.15 NppStatus nppiSqrt_32f_C1IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit floating point channel in place image square root.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25.2.16 NppStatus nppiSqrt_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit floating point channel image square root.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25.2.17 NppStatus nppiSqrt_32f_C3IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel in place image square root.

Parameters:

- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25.2.18 NppStatus nppiSqrt_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel image square root.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25.2.19 NppStatus nppiSqrt_32f_C4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel in place image square root.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25.2.20 NppStatus nppiSqrt_32f_C4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel image square root.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25.2.21 NppStatus nppiSqrt_8u_AC4IRSfs (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel in place image square root with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25.2.22 NppStatus nppiSqrt_8u_AC4RSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel image square root with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25.2.23 NppStatus nppiSqrt_8u_C1IRSfs (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 8-bit unsigned char channel in place image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25.2.24 NppStatus nppiSqrt_8u_C1RSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 8-bit unsigned char channel image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25.2.25 NppStatus nppiSqrt_8u_C3IRSfs (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 8-bit unsigned char channel in place image square root, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25.2.26 NppStatus nppiSqrt_8u_C3RSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 8-bit unsigned char channel image square root, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.26 Ln

Pixel by pixel natural logarithm of each pixel in an image.

Functions

- **NppStatus nppiLn_8u_C1RSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 8-bit unsigned char channel image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiLn_8u_C1IRSfs** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 8-bit unsigned char channel in place image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiLn_8u_C3RSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 8-bit unsigned char channel image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiLn_8u_C3IRSfs** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 8-bit unsigned char channel in place image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiLn_16u_C1RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiLn_16u_C1IRSfs** (**Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiLn_16u_C3RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiLn_16u_C3IRSfs** (**Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel in place image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiLn_16s_C1RSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit signed short channel image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiLn_16s_C1IRSfs** (**Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit signed short channel in place image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiLn_16s_C3RSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 16-bit signed short channel image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiLn_16s_C3IRSfs** (**Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 16-bit signed short channel in place image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiLn_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 32-bit floating point channel image natural logarithm.
- **NppStatus nppiLn_32f_C1IR** (**Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 32-bit floating point channel in place image natural logarithm.
- **NppStatus nppiLn_32f_C3R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 32-bit floating point channel image natural logarithm.
- **NppStatus nppiLn_32f_C3IR** (**Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 32-bit floating point channel in place image natural logarithm.

7.26.1 Detailed Description

Pixel by pixel natural logarithm of each pixel in an image.

7.26.2 Function Documentation

7.26.2.1 **NppStatus nppiLn_16s_C1IRSfs** (**Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrcDst** In-Place Image Pointer.
- nSrcDstStep** In-Place-Image Line Step.
- oSizeROI** Region-of-Interest (ROI).
- nScaleFactor** Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.26.2.2 **NppStatus nppiLn_16s_C1RSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)**

One 16-bit signed short channel image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.26.2.3 **NppStatus nppiLn_16s_C3IRSfs (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)**

Three 16-bit signed short channel in place image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.26.2.4 **NppStatus nppiLn_16s_C3RSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)**

Three 16-bit signed short channel image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.26.2.5 **NppStatus nppiLn_16u_C1IRSfs** (**Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor**)

One 16-bit unsigned short channel in place image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.26.2.6 **NppStatus nppiLn_16u_C1RSfs** (**const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor**)

One 16-bit unsigned short channel image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.26.2.7 **NppStatus nppiLn_16u_C3IRSfs** (**Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor**)

Three 16-bit unsigned short channel in place image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.26.2.8 `NppStatus nppiLn_16u_C3RSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit unsigned short channel image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.26.2.9 `NppStatus nppiLn_32f_C1IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 32-bit floating point channel in place image natural logarithm.

Parameters:

- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.26.2.10 `NppStatus nppiLn_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit floating point channel image natural logarithm.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.26.2.11 NppStatus nppiLn_32f_C3IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel in place image natural logarithm.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.26.2.12 NppStatus nppiLn_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel image natural logarithm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.26.2.13 NppStatus nppiLn_8u_C1IRSfs (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 8-bit unsigned char channel in place image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.26.2.14 `NppStatus nppiLn_8u_C1RSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.26.2.15 `NppStatus nppiLn_8u_C3IRSfs (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel in place image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.26.2.16 `NppStatus nppiLn_8u_C3RSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.27 Exp

Exponential value of each pixel in an image.

Functions

- **NppStatus nppiExp_8u_C1RSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiExp_8u_C1IRSfs** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel in place image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiExp_8u_C3RSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiExp_8u_C3IRSfs** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel in place image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiExp_16u_C1RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiExp_16u_C1IRSfs** (**Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel in place image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiExp_16u_C3RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 16-bit unsigned short channel image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiExp_16u_C3IRSfs** (**Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 16-bit unsigned short channel in place image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiExp_16s_C1RSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit signed short channel image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiExp_16s_C1IRSfs** (**Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit signed short channel in place image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiExp_16s_C3RSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 16-bit signed short channel image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiExp_16s_C3IRSfs** (**Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 16-bit signed short channel in place image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiExp_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 32-bit floating point channel image exponential.
- **NppStatus nppiExp_32f_C1IR** (**Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 32-bit floating point channel in place image exponential.
- **NppStatus nppiExp_32f_C3R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 32-bit floating point channel image exponential.
- **NppStatus nppiExp_32f_C3IR** (**Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 32-bit floating point channel in place image exponential.

7.27.1 Detailed Description

Exponential value of each pixel in an image.

7.27.2 Function Documentation

7.27.2.1 **NppStatus nppiExp_16s_C1IRSfs** (**Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.27.2.2 NppStatus nppiExp_16s_C1RSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short channel image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.27.2.3 NppStatus nppiExp_16s_C3IRSfs (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short channel in place image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.27.2.4 NppStatus nppiExp_16s_C3RSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.27.2.5 NppStatus nppiExp_16u_C1IRSfs (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.27.2.6 NppStatus nppiExp_16u_C1RSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.27.2.7 NppStatus nppiExp_16u_C3IRSfs (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel in place image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.27.2.8 NppStatus nppiExp_16u_C3RSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.27.2.9 NppStatus nppiExp_32f_C1IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit floating point channel in place image exponential.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.27.2.10 NppStatus nppiExp_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit floating point channel image exponential.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.27.2.11 `NppStatus nppiExp_32f_C3IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Three 32-bit floating point channel in place image exponential.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.27.2.12 `NppStatus nppiExp_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit floating point channel image exponential.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.27.2.13 `NppStatus nppiExp_8u_C1IRSfs (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel in place image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.27.2.14 NppStatus nppiExp_8u_C1RSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 8-bit unsigned char channel image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.27.2.15 NppStatus nppiExp_8u_C3IRSfs (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 8-bit unsigned char channel in place image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.27.2.16 NppStatus nppiExp_8u_C3RSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 8-bit unsigned char channel image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.28 Logical Operations

Modules

- [AndC](#)
Pixel by pixel logical and of an image with a constant.
- [OrC](#)
Pixel by pixel logical or of an image with a constant.
- [XorC](#)
Pixel by pixel logical exclusive or of an image with a constant.
- [RShiftC](#)
Pixel by pixel right shift of an image by a constant value.
- [LShiftC](#)
Pixel by pixel left shift of an image by a constant value.
- [And](#)
Pixel by pixel logical and of images.
- [Or](#)
Pixel by pixel logical or of images.
- [Xor](#)
Pixel by pixel logical exclusive or of images.
- [Not](#)
Pixel by pixel logical not of image.

7.29 AndC

Pixel by pixel logical and of an image with a constant.

Functions

- **NppStatus nppiAndC_8u_C1R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** nConstant, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel image logical and with constant.
- **NppStatus nppiAndC_8u_C1IR** (const **Npp8u** nConstant, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel in place image logical and with constant.
- **NppStatus nppiAndC_8u_C3R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 8-bit unsigned char channel image logical and with constant.
- **NppStatus nppiAndC_8u_C3IR** (const **Npp8u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 8-bit unsigned char channel in place image logical and with constant.
- **NppStatus nppiAndC_8u_AC4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel image logical and with constant with unmodified alpha.
- **NppStatus nppiAndC_8u_AC4IR** (const **Npp8u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel in place image logical and with constant with unmodified alpha.
- **NppStatus nppiAndC_8u_C4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[4], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel image logical and with constant.
- **NppStatus nppiAndC_8u_C4IR** (const **Npp8u** aConstants[4], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel in place image logical and with constant.
- **NppStatus nppiAndC_16u_C1R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** nConstant, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel image logical and with constant.
- **NppStatus nppiAndC_16u_C1IR** (const **Npp16u** nConstant, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel in place image logical and with constant.
- **NppStatus nppiAndC_16u_C3R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** aConstants[3], **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 16-bit unsigned short channel image logical and with constant.

- `NppStatus nppiAndC_16u_C3IR` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 16-bit unsigned short channel in place image logical and with constant.
- `NppStatus nppiAndC_16u_AC4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[3], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel image logical and with constant with unmodified alpha.
- `NppStatus nppiAndC_16u_AC4IR` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel in place image logical and with constant with unmodified alpha.
- `NppStatus nppiAndC_16u_C4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[4], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel image logical and with constant.
- `NppStatus nppiAndC_16u_C4IR` (const `Npp16u` aConstants[4], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel in place image logical and with constant.
- `NppStatus nppiAndC_32s_C1R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` nConstant, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 32-bit signed integer channel image logical and with constant.
- `NppStatus nppiAndC_32s_C1IR` (const `Npp32s` nConstant, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 32-bit signed integer channel in place image logical and with constant.
- `NppStatus nppiAndC_32s_C3R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` aConstants[3], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 32-bit signed integer channel image logical and with constant.
- `NppStatus nppiAndC_32s_C3IR` (const `Npp32s` aConstants[3], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 32-bit signed integer channel in place image logical and with constant.
- `NppStatus nppiAndC_32s_AC4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` aConstants[3], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel image logical and with constant with unmodified alpha.
- `NppStatus nppiAndC_32s_AC4IR` (const `Npp32s` aConstants[3], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel in place image logical and with constant with unmodified alpha.
- `NppStatus nppiAndC_32s_C4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` aConstants[4], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel image logical and with constant.
- `NppStatus nppiAndC_32s_C4IR` (const `Npp32s` aConstants[4], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel in place image logical and with constant.

7.29.1 Detailed Description

Pixel by pixel logical and of an image with a constant.

7.29.2 Function Documentation

7.29.2.1 `NppStatus nppiAndC_16u_AC4IR (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 16-bit unsigned short channel in place image logical and with constant with unmodified alpha.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.29.2.2 `NppStatus nppiAndC_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 16-bit unsigned short channel image logical and with constant with unmodified alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.29.2.3 `NppStatus nppiAndC_16u_C1IR (const Npp16u nConstant, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 16-bit unsigned short channel in place image logical and with constant.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.4 NppStatus nppiAndC_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u nConstant, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

One 16-bit unsigned short channel image logical and with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.5 NppStatus nppiAndC_16u_C3IR (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 16-bit unsigned short channel in place image logical and with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.6 NppStatus nppiAndC_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Three 16-bit unsigned short channel image logical and with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.7 NppStatus nppiAndC_16u_C4IR (const Npp16u aConstants[4], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel in place image logical and with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.8 NppStatus nppiAndC_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[4], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel image logical and with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.9 `NppStatus nppiAndC_32s_AC4IR` (`const Npp32s aConstants[3]`, `Npp32s * pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`)

Four 32-bit signed integer channel in place image logical and with constant with unmodified alpha.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.29.2.10 `NppStatus nppiAndC_32s_AC4R` (`const Npp32s * pSrc1`, `int nSrc1Step`, `const Npp32s aConstants[3]`, `Npp32s * pDst`, `int nDstStep`, `NppiSize oSizeROI`)

Four 32-bit signed integer channel image logical and with constant with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.29.2.11 `NppStatus nppiAndC_32s_C1IR` (`const Npp32s nConstant`, `Npp32s * pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`)

One 32-bit signed integer channel in place image logical and with constant.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.29.2.12 `NppStatus nppiAndC_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s nConstant, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit signed integer channel image logical and with constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.13 `NppStatus nppiAndC_32s_C3IR (const Npp32s aConstants[3], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Three 32-bit signed integer channel in place image logical and with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.14 `NppStatus nppiAndC_32s_C3R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s aConstants[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit signed integer channel image logical and with constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.15 `NppStatus nppiAndC_32s_C4IR (const Npp32s aConstants[4], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel in place image logical and with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.29.2.16 `NppStatus nppiAndC_32s_C4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s aConstants[4], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel image logical and with constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.29.2.17 `NppStatus nppiAndC_8u_AC4IR (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image logical and with constant with unmodified alpha.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.29.2.18 `NppStatus nppiAndC_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image logical and with constant with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.19 `NppStatus nppiAndC_8u_C1IR (const Npp8u nConstant, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel in place image logical and with constant.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.20 `NppStatus nppiAndC_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u nConstant, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel image logical and with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.21 NppStatus nppiAndC_8u_C3IR (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel in place image logical and with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.29.2.22 NppStatus nppiAndC_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel image logical and with constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.29.2.23 NppStatus nppiAndC_8u_C4IR (const Npp8u aConstants[4], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel in place image logical and with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.29.2.24 NppStatus nppiAndC_8u_C4R (const Npp8u * *pSrc1*, int *nSrc1Step*, const Npp8u *aConstants*[4], Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

Four 8-bit unsigned char channel image logical and with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30 OrC

Pixel by pixel logical or of an image with a constant.

Functions

- **NppStatus nppiOrC_8u_C1R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** nConstant, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel image logical or with constant.
- **NppStatus nppiOrC_8u_C1IR** (const **Npp8u** nConstant, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel in place image logical or with constant.
- **NppStatus nppiOrC_8u_C3R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 8-bit unsigned char channel image logical or with constant.
- **NppStatus nppiOrC_8u_C3IR** (const **Npp8u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 8-bit unsigned char channel in place image logical or with constant.
- **NppStatus nppiOrC_8u_AC4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel image logical or with constant with unmodified alpha.
- **NppStatus nppiOrC_8u_AC4IR** (const **Npp8u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel in place image logical or with constant with unmodified alpha.
- **NppStatus nppiOrC_8u_C4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[4], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel image logical or with constant.
- **NppStatus nppiOrC_8u_C4IR** (const **Npp8u** aConstants[4], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel in place image logical or with constant.
- **NppStatus nppiOrC_16u_C1R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** nConstant, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel image logical or with constant.
- **NppStatus nppiOrC_16u_C1IR** (const **Npp16u** nConstant, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel in place image logical or with constant.
- **NppStatus nppiOrC_16u_C3R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** aConstants[3], **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 16-bit unsigned short channel image logical or with constant.

- `NppStatus nppiOrC_16u_C3IR` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 16-bit unsigned short channel in place image logical or with constant.
- `NppStatus nppiOrC_16u_AC4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[3], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel image logical or with constant with unmodified alpha.
- `NppStatus nppiOrC_16u_AC4IR` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel in place image logical or with constant with unmodified alpha.
- `NppStatus nppiOrC_16u_C4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[4], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel image logical or with constant.
- `NppStatus nppiOrC_16u_C4IR` (const `Npp16u` aConstants[4], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel in place image logical or with constant.
- `NppStatus nppiOrC_32s_C1R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` nConstant, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 32-bit signed integer channel image logical or with constant.
- `NppStatus nppiOrC_32s_C1IR` (const `Npp32s` nConstant, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 32-bit signed integer channel in place image logical or with constant.
- `NppStatus nppiOrC_32s_C3R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` aConstants[3], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 32-bit signed integer channel image logical or with constant.
- `NppStatus nppiOrC_32s_C3IR` (const `Npp32s` aConstants[3], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 32-bit signed integer channel in place image logical or with constant.
- `NppStatus nppiOrC_32s_AC4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` aConstants[3], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel image logical or with constant with unmodified alpha.
- `NppStatus nppiOrC_32s_AC4IR` (const `Npp32s` aConstants[3], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel in place image logical or with constant with unmodified alpha.
- `NppStatus nppiOrC_32s_C4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` aConstants[4], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel image logical or with constant.
- `NppStatus nppiOrC_32s_C4IR` (const `Npp32s` aConstants[4], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel in place image logical or with constant.

7.30.1 Detailed Description

Pixel by pixel logical or of an image with a constant.

7.30.2 Function Documentation

7.30.2.1 `NppStatus nppiOrC_16u_AC4IR (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 16-bit unsigned short channel in place image logical or with constant with unmodified alpha.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.30.2.2 `NppStatus nppiOrC_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 16-bit unsigned short channel image logical or with constant with unmodified alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.30.2.3 `NppStatus nppiOrC_16u_C1IR (const Npp16u nConstant, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 16-bit unsigned short channel in place image logical or with constant.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.4 NppStatus nppiOrC_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u nConstant, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

One 16-bit unsigned short channel image logical or with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.5 NppStatus nppiOrC_16u_C3IR (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 16-bit unsigned short channel in place image logical or with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.6 NppStatus nppiOrC_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Three 16-bit unsigned short channel image logical or with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.7 NppStatus nppiOrC_16u_C4IR (const Npp16u aConstants[4], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel in place image logical or with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.8 NppStatus nppiOrC_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[4], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel image logical or with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.9 NppStatus nppiOrC_32s_AC4IR (const Npp32s aConstants[3], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel in place image logical or with constant with unmodified alpha.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.10 NppStatus nppiOrC_32s_AC4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s aConstants[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel image logical or with constant with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.11 NppStatus nppiOrC_32s_C1IR (const Npp32s nConstant, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit signed integer channel in place image logical or with constant.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.12 `NppStatus nppiOrC_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s nConstant, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit signed integer channel image logical or with constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.13 `NppStatus nppiOrC_32s_C3IR (const Npp32s aConstants[3], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Three 32-bit signed integer channel in place image logical or with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.14 `NppStatus nppiOrC_32s_C3R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s aConstants[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit signed integer channel image logical or with constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.15 `NppStatus nppiOrC_32s_C4IR (const Npp32s aConstants[4], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel in place image logical or with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.30.2.16 `NppStatus nppiOrC_32s_C4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s aConstants[4], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel image logical or with constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.30.2.17 `NppStatus nppiOrC_8u_AC4IR (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image logical or with constant with unmodified alpha.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.30.2.18 `NppStatus nppiOrC_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image logical or with constant with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.19 `NppStatus nppiOrC_8u_C1IR (const Npp8u nConstant, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel in place image logical or with constant.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.20 `NppStatus nppiOrC_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u nConstant, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel image logical or with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.21 NppStatus nppiOrC_8u_C3IR (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel in place image logical or with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.30.2.22 NppStatus nppiOrC_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel image logical or with constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.30.2.23 NppStatus nppiOrC_8u_C4IR (const Npp8u aConstants[4], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel in place image logical or with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.30.2.24 NppStatus nppiOrC_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[4], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel image logical or with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31 XorC

Pixel by pixel logical exclusive or of an image with a constant.

Functions

- **NppStatus nppiXorC_8u_C1R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** nConstant, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel image logical exclusive or with constant.
- **NppStatus nppiXorC_8u_C1IR** (const **Npp8u** nConstant, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel in place image logical exclusive or with constant.
- **NppStatus nppiXorC_8u_C3R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 8-bit unsigned char channel image logical exclusive or with constant.
- **NppStatus nppiXorC_8u_C3IR** (const **Npp8u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 8-bit unsigned char channel in place image logical exclusive or with constant.
- **NppStatus nppiXorC_8u_AC4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel image logical exclusive or with constant with unmodified alpha.
- **NppStatus nppiXorC_8u_AC4IR** (const **Npp8u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel in place image logical exclusive or with constant with unmodified alpha.
- **NppStatus nppiXorC_8u_C4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[4], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel image logical exclusive or with constant.
- **NppStatus nppiXorC_8u_C4IR** (const **Npp8u** aConstants[4], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel in place image logical exclusive or with constant.
- **NppStatus nppiXorC_16u_C1R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** nConstant, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel image logical exclusive or with constant.
- **NppStatus nppiXorC_16u_C1IR** (const **Npp16u** nConstant, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel in place image logical exclusive or with constant.
- **NppStatus nppiXorC_16u_C3R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** aConstants[3], **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 16-bit unsigned short channel image logical exclusive or with constant.

- `NppStatus nppiXorC_16u_C3IR` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 16-bit unsigned short channel in place image logical exclusive or with constant.
- `NppStatus nppiXorC_16u_AC4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[3], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel image logical exclusive or with constant with unmodified alpha.
- `NppStatus nppiXorC_16u_AC4IR` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel in place image logical exclusive or with constant with unmodified alpha.
- `NppStatus nppiXorC_16u_C4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[4], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel image logical exclusive or with constant.
- `NppStatus nppiXorC_16u_C4IR` (const `Npp16u` aConstants[4], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel in place image logical exclusive or with constant.
- `NppStatus nppiXorC_32s_C1R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` nConstant, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 32-bit signed integer channel image logical exclusive or with constant.
- `NppStatus nppiXorC_32s_C1IR` (const `Npp32s` nConstant, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 32-bit signed integer channel in place image logical exclusive or with constant.
- `NppStatus nppiXorC_32s_C3R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` aConstants[3], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 32-bit signed integer channel image logical exclusive or with constant.
- `NppStatus nppiXorC_32s_C3IR` (const `Npp32s` aConstants[3], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 32-bit signed integer channel in place image logical exclusive or with constant.
- `NppStatus nppiXorC_32s_AC4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` aConstants[3], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel image logical exclusive or with constant with unmodified alpha.
- `NppStatus nppiXorC_32s_AC4IR` (const `Npp32s` aConstants[3], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel in place image logical exclusive or with constant with unmodified alpha.
- `NppStatus nppiXorC_32s_C4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` aConstants[4], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel image logical exclusive or with constant.
- `NppStatus nppiXorC_32s_C4IR` (const `Npp32s` aConstants[4], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel in place image logical exclusive or with constant.

7.31.1 Detailed Description

Pixel by pixel logical exclusive or of an image with a constant.

7.31.2 Function Documentation

7.31.2.1 NppStatus nppiXorC_16u_AC4IR (const Npp16u *aConstants*[3], Npp16u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

Four 16-bit unsigned short channel in place image logical exclusive or with constant with unmodified alpha.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.2 NppStatus nppiXorC_16u_AC4R (const Npp16u * *pSrc1*, int *nSrc1Step*, const Npp16u *aConstants*[3], Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

Four 16-bit unsigned short channel image logical exclusive or with constant with unmodified alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.3 NppStatus nppiXorC_16u_C1IR (const Npp16u *nConstant*, Npp16u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

One 16-bit unsigned short channel in place image logical exclusive or with constant.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.4 NppStatus nppiXorC_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u nConstant, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

One 16-bit unsigned short channel image logical exclusive or with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.5 NppStatus nppiXorC_16u_C3IR (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 16-bit unsigned short channel in place image logical exclusive or with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.6 NppStatus nppiXorC_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Three 16-bit unsigned short channel image logical exclusive or with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.7 NppStatus nppiXorC_16u_C4IR (const Npp16u aConstants[4], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel in place image logical exclusive or with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.8 NppStatus nppiXorC_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[4], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel image logical exclusive or with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.9 `NppStatus nppiXorC_32s_AC4IR (const Npp32s aConstants[3], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel in place image logical exclusive or with constant with unmodified alpha.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.10 `NppStatus nppiXorC_32s_AC4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s aConstants[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel image logical exclusive or with constant with unmodified alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.11 `NppStatus nppiXorC_32s_C1IR (const Npp32s nConstant, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 32-bit signed integer channel in place image logical exclusive or with constant.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.12 NppStatus nppiXorC_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s nConstant, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit signed integer channel image logical exclusive or with constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.13 NppStatus nppiXorC_32s_C3IR (const Npp32s aConstants[3], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit signed integer channel in place image logical exclusive or with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.14 NppStatus nppiXorC_32s_C3R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s aConstants[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit signed integer channel image logical exclusive or with constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.15 `NppStatus nppiXorC_32s_C4IR (const Npp32s aConstants[4], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel in place image logical exclusive or with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.16 `NppStatus nppiXorC_32s_C4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s aConstants[4], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel image logical exclusive or with constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.17 `NppStatus nppiXorC_8u_AC4IR (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image logical exclusive or with constant with unmodified alpha.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.18 `NppStatus nppiXorC_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image logical exclusive or with constant with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.19 `NppStatus nppiXorC_8u_C1IR (const Npp8u nConstant, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel in place image logical exclusive or with constant.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.20 `NppStatus nppiXorC_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u nConstant, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel image logical exclusive or with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.21 NppStatus nppiXorC_8u_C3IR (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel in place image logical exclusive or with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst [In-Place Image Pointer](#).
nSrcDstStep [In-Place-Image Line Step](#).
oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.22 NppStatus nppiXorC_8u_C3R (const Npp8u * pSrcI, int nSrcIStep, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel image logical exclusive or with constant.

Parameters:

pSrcI [Source-Image Pointer](#).
nSrcIStep [Source-Image Line Step](#).
aConstants fixed size array of constant values, one per channel.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.23 NppStatus nppiXorC_8u_C4IR (const Npp8u aConstants[4], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel in place image logical exclusive or with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst [In-Place Image Pointer](#).
nSrcDstStep [In-Place-Image Line Step](#).
oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.24 NppStatus nppiXorC_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[4], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel image logical exclusive or with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32 RShiftC

Pixel by pixel right shift of an image by a constant value.

Functions

- `NppStatus nppiRShiftC_8u_C1R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp32u` nConstant, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel image right shift by constant.
- `NppStatus nppiRShiftC_8u_C1IR` (const `Npp32u` nConstant, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel in place image right shift by constant.
- `NppStatus nppiRShiftC_8u_C3R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp32u` aConstants[3], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 8-bit unsigned char channel image right shift by constant.
- `NppStatus nppiRShiftC_8u_C3IR` (const `Npp32u` aConstants[3], `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 8-bit unsigned char channel in place image right shift by constant.
- `NppStatus nppiRShiftC_8u_AC4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp32u` aConstants[3], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel image right shift by constant with unmodified alpha.
- `NppStatus nppiRShiftC_8u_AC4IR` (const `Npp32u` aConstants[3], `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel in place image right shift by constant with unmodified alpha.
- `NppStatus nppiRShiftC_8u_C4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp32u` aConstants[4], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel image right shift by constant.
- `NppStatus nppiRShiftC_8u_C4IR` (const `Npp32u` aConstants[4], `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel in place image right shift by constant.
- `NppStatus nppiRShiftC_8s_C1R` (const `Npp8s` *pSrc1, int nSrc1Step, const `Npp32u` nConstant, `Npp8s` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 8-bit signed char channel image right shift by constant.
- `NppStatus nppiRShiftC_8s_C1IR` (const `Npp32u` nConstant, `Npp8s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 8-bit signed char channel in place image right shift by constant.
- `NppStatus nppiRShiftC_8s_C3R` (const `Npp8s` *pSrc1, int nSrc1Step, const `Npp32u` aConstants[3], `Npp8s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 8-bit signed char channel image right shift by constant.

- **NppStatus nppiRShiftC_8s_C3IR** (const **Npp32u** aConstants[3], **Npp8s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 8-bit signed char channel in place image right shift by constant.
- **NppStatus nppiRShiftC_8s_AC4R** (const **Npp8s** *pSrc1, int nSrc1Step, const **Npp32u** aConstants[3], **Npp8s** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit signed char channel image right shift by constant with unmodified alpha.
- **NppStatus nppiRShiftC_8s_AC4IR** (const **Npp32u** aConstants[3], **Npp8s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit signed char channel in place image right shift by constant with unmodified alpha.
- **NppStatus nppiRShiftC_8s_C4R** (const **Npp8s** *pSrc1, int nSrc1Step, const **Npp32u** aConstants[4], **Npp8s** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit signed char channel image right shift by constant.
- **NppStatus nppiRShiftC_8s_C4IR** (const **Npp32u** aConstants[4], **Npp8s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit signed char channel in place image right shift by constant.
- **NppStatus nppiRShiftC_16u_C1R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp32u** nConstant, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel image right shift by constant.
- **NppStatus nppiRShiftC_16u_C1IR** (const **Npp32u** nConstant, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel in place image right shift by constant.
- **NppStatus nppiRShiftC_16u_C3R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp32u** aConstants[3], **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 16-bit unsigned short channel image right shift by constant.
- **NppStatus nppiRShiftC_16u_C3IR** (const **Npp32u** aConstants[3], **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 16-bit unsigned short channel in place image right shift by constant.
- **NppStatus nppiRShiftC_16u_AC4R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp32u** aConstants[3], **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 16-bit unsigned short channel image right shift by constant with unmodified alpha.
- **NppStatus nppiRShiftC_16u_AC4IR** (const **Npp32u** aConstants[3], **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 16-bit unsigned short channel in place image right shift by constant with unmodified alpha.
- **NppStatus nppiRShiftC_16u_C4R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp32u** aConstants[4], **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 16-bit unsigned short channel image right shift by constant.
- **NppStatus nppiRShiftC_16u_C4IR** (const **Npp32u** aConstants[4], **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 16-bit unsigned short channel in place image right shift by constant.

- `NppStatus nppiRShiftC_16s_C1R` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp32u nConstant`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
One 16-bit signed short channel image right shift by constant.
- `NppStatus nppiRShiftC_16s_C1IR` (const `Npp32u nConstant`, `Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
One 16-bit signed short channel in place image right shift by constant.
- `NppStatus nppiRShiftC_16s_C3R` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp32u aConstants[3]`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Three 16-bit signed short channel image right shift by constant.
- `NppStatus nppiRShiftC_16s_C3IR` (const `Npp32u aConstants[3]`, `Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Three 16-bit signed short channel in place image right shift by constant.
- `NppStatus nppiRShiftC_16s_AC4R` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp32u aConstants[3]`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four 16-bit signed short channel image right shift by constant with unmodified alpha.
- `NppStatus nppiRShiftC_16s_AC4IR` (const `Npp32u aConstants[3]`, `Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Four 16-bit signed short channel in place image right shift by constant with unmodified alpha.
- `NppStatus nppiRShiftC_16s_C4R` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp32u aConstants[4]`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four 16-bit signed short channel image right shift by constant.
- `NppStatus nppiRShiftC_16s_C4IR` (const `Npp32u aConstants[4]`, `Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Four 16-bit signed short channel in place image right shift by constant.
- `NppStatus nppiRShiftC_32s_C1R` (const `Npp32s *pSrc1`, int `nSrc1Step`, const `Npp32u nConstant`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
One 32-bit signed integer channel image right shift by constant.
- `NppStatus nppiRShiftC_32s_C1IR` (const `Npp32u nConstant`, `Npp32s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
One 32-bit signed integer channel in place image right shift by constant.
- `NppStatus nppiRShiftC_32s_C3R` (const `Npp32s *pSrc1`, int `nSrc1Step`, const `Npp32u aConstants[3]`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Three 32-bit signed integer channel image right shift by constant.
- `NppStatus nppiRShiftC_32s_C3IR` (const `Npp32u aConstants[3]`, `Npp32s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Three 32-bit signed integer channel in place image right shift by constant.
- `NppStatus nppiRShiftC_32s_AC4R` (const `Npp32s *pSrc1`, int `nSrc1Step`, const `Npp32u aConstants[3]`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Four 32-bit signed integer channel image right shift by constant with unmodified alpha.

- `NppStatus nppiRShiftC_32s_AC4IR` (const `Npp32u aConstants[3]`, `Npp32s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Four 32-bit signed integer channel in place image right shift by constant with unmodified alpha.

- `NppStatus nppiRShiftC_32s_C4R` (const `Npp32s *pSrc1`, int `nSrc1Step`, const `Npp32u aConstants[4]`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Four 32-bit signed integer channel image right shift by constant.

- `NppStatus nppiRShiftC_32s_C4IR` (const `Npp32u aConstants[4]`, `Npp32s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Four 32-bit signed integer channel in place image right shift by constant.

7.32.1 Detailed Description

Pixel by pixel right shift of an image by a constant value.

7.32.2 Function Documentation

7.32.2.1 `NppStatus nppiRShiftC_16s_AC4IR` (const `Npp32u aConstants[3]`, `Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Four 16-bit signed short channel in place image right shift by constant with unmodified alpha.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.2 `NppStatus nppiRShiftC_16s_AC4R` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp32u aConstants[3]`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Four 16-bit signed short channel image right shift by constant with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.3 NppStatus nppiRShiftC_16s_C1IR (const Npp32u nConstant, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 16-bit signed short channel in place image right shift by constant.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.4 NppStatus nppiRShiftC_16s_C1R (const Npp16s * pSrc1, int nSrc1Step, const Npp32u nConstant, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

One 16-bit signed short channel image right shift by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.5 NppStatus nppiRShiftC_16s_C3IR (const Npp32u aConstants[3], Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 16-bit signed short channel in place image right shift by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.6 NppStatus nppiRShiftC_16s_C3R (const Npp16s * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

Three 16-bit signed short channel image right shift by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.7 NppStatus nppiRShiftC_16s_C4IR (const Npp32u aConstants[4], Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 16-bit signed short channel in place image right shift by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.8 NppStatus nppiRShiftC_16s_C4R (const Npp16s * pSrc1, int nSrc1Step, const Npp32u aConstants[4], Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit signed short channel image right shift by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.9 NppStatus nppiRShiftC_16u_AC4IR (const Npp32u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel in place image right shift by constant with unmodified alpha.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.10 NppStatus nppiRShiftC_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel image right shift by constant with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.11 NppStatus nppiRShiftC_16u_C1IR (const Npp32u nConstant, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 16-bit unsigned short channel in place image right shift by constant.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.12 NppStatus nppiRShiftC_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, const Npp32u nConstant, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

One 16-bit unsigned short channel image right shift by constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.13 NppStatus nppiRShiftC_16u_C3IR (const Npp32u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 16-bit unsigned short channel in place image right shift by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.14 `NppStatus nppiRShiftC_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)`

Three 16-bit unsigned short channel image right shift by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.15 `NppStatus nppiRShiftC_16u_C4IR (const Npp32u aConstants[4], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 16-bit unsigned short channel in place image right shift by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.16 `NppStatus nppiRShiftC_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp32u aConstants[4], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 16-bit unsigned short channel image right shift by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.17 NppStatus nppiRShiftC_32s_AC4IR (const Npp32u aConstants[3], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel in place image right shift by constant with unmodified alpha.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.18 NppStatus nppiRShiftC_32s_AC4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel image right shift by constant with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.19 NppStatus nppiRShiftC_32s_C1IR (const Npp32u nConstant, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit signed integer channel in place image right shift by constant.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.20 `NppStatus nppiRShiftC_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32u nConstant, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit signed integer channel image right shift by constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nConstant* Constant.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.21 `NppStatus nppiRShiftC_32s_C3IR (const Npp32u aConstants[3], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Three 32-bit signed integer channel in place image right shift by constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.22 `NppStatus nppiRShiftC_32s_C3R (const Npp32s * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit signed integer channel image right shift by constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.23 NppStatus nppiRShiftC_32s_C4IR (const Npp32u aConstants[4], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel in place image right shift by constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.24 NppStatus nppiRShiftC_32s_C4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32u aConstants[4], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel image right shift by constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.25 NppStatus nppiRShiftC_8s_AC4IR (const Npp32u aConstants[3], Npp8s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 8-bit signed char channel in place image right shift by constant with unmodified alpha.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.26 `NppStatus nppiRShiftC_8s_AC4R (const Npp8s * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp8s * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit signed char channel image right shift by constant with unmodified alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.27 `NppStatus nppiRShiftC_8s_C1IR (const Npp32u nConstant, Npp8s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 8-bit signed char channel in place image right shift by constant.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.28 `NppStatus nppiRShiftC_8s_C1R (const Npp8s * pSrc1, int nSrc1Step, const Npp32u nConstant, Npp8s * pDst, int nDstStep, NppiSize oSizeROI)`

One 8-bit signed char channel image right shift by constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nConstant* Constant.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.29 NppStatus nppiRShiftC_8s_C3IR (const Npp32u aConstants[3], Npp8s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 8-bit signed char channel in place image right shift by constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.30 NppStatus nppiRShiftC_8s_C3R (const Npp8s * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp8s * pDst, int nDstStep, NppiSize oSizeROI)

Three 8-bit signed char channel image right shift by constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.31 NppStatus nppiRShiftC_8s_C4IR (const Npp32u aConstants[4], Npp8s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 8-bit signed char channel in place image right shift by constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.32 `NppStatus nppiRShiftC_8s_C4R (const Npp8s * pSrc1, int nSrc1Step, const Npp32u aConstants[4], Npp8s * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit signed char channel image right shift by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.33 `NppStatus nppiRShiftC_8u_AC4IR (const Npp32u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image right shift by constant with unmodified alpha.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.34 `NppStatus nppiRShiftC_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image right shift by constant with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.35 NppStatus nppiRShiftC_8u_C1IR (const Npp32u nConstant, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 8-bit unsigned char channel in place image right shift by constant.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.36 NppStatus nppiRShiftC_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp32u nConstant, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

One 8-bit unsigned char channel image right shift by constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nConstant* Constant.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.37 NppStatus nppiRShiftC_8u_C3IR (const Npp32u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel in place image right shift by constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.38 `NppStatus nppiRShiftC_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Three 8-bit unsigned char channel image right shift by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.39 `NppStatus nppiRShiftC_8u_C4IR (const Npp32u aConstants[4], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image right shift by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.40 `NppStatus nppiRShiftC_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp32u aConstants[4], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image right shift by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.33 LShiftC

Pixel by pixel left shift of an image by a constant value.

Functions

- **NppStatus nppiLShiftC_8u_C1R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp32u** nConstant, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel image left shift by constant.
- **NppStatus nppiLShiftC_8u_C1IR** (const **Npp32u** nConstant, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel in place image left shift by constant.
- **NppStatus nppiLShiftC_8u_C3R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp32u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 8-bit unsigned char channel image left shift by constant.
- **NppStatus nppiLShiftC_8u_C3IR** (const **Npp32u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 8-bit unsigned char channel in place image left shift by constant.
- **NppStatus nppiLShiftC_8u_AC4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp32u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel image left shift by constant with unmodified alpha.
- **NppStatus nppiLShiftC_8u_AC4IR** (const **Npp32u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel in place image left shift by constant with unmodified alpha.
- **NppStatus nppiLShiftC_8u_C4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp32u** aConstants[4], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel image left shift by constant.
- **NppStatus nppiLShiftC_8u_C4IR** (const **Npp32u** aConstants[4], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel in place image left shift by constant.
- **NppStatus nppiLShiftC_16u_C1R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp32u** nConstant, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel image left shift by constant.
- **NppStatus nppiLShiftC_16u_C1IR** (const **Npp32u** nConstant, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel in place image left shift by constant.
- **NppStatus nppiLShiftC_16u_C3R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp32u** aConstants[3], **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 16-bit unsigned short channel image left shift by constant.

- `NppStatus nppiLShiftC_16u_C3IR` (const `Npp32u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 16-bit unsigned short channel in place image left shift by constant.
- `NppStatus nppiLShiftC_16u_AC4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp32u` aConstants[3], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel image left shift by constant with unmodified alpha.
- `NppStatus nppiLShiftC_16u_AC4IR` (const `Npp32u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel in place image left shift by constant with unmodified alpha.
- `NppStatus nppiLShiftC_16u_C4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp32u` aConstants[4], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel image left shift by constant.
- `NppStatus nppiLShiftC_16u_C4IR` (const `Npp32u` aConstants[4], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel in place image left shift by constant.
- `NppStatus nppiLShiftC_32s_C1R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32u` nConstant, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 32-bit signed integer channel image left shift by constant.
- `NppStatus nppiLShiftC_32s_C1IR` (const `Npp32u` nConstant, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 32-bit signed integer channel in place image left shift by constant.
- `NppStatus nppiLShiftC_32s_C3R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32u` aConstants[3], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 32-bit signed integer channel image left shift by constant.
- `NppStatus nppiLShiftC_32s_C3IR` (const `Npp32u` aConstants[3], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 32-bit signed integer channel in place image left shift by constant.
- `NppStatus nppiLShiftC_32s_AC4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32u` aConstants[3], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel image left shift by constant with unmodified alpha.
- `NppStatus nppiLShiftC_32s_AC4IR` (const `Npp32u` aConstants[3], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel in place image left shift by constant with unmodified alpha.
- `NppStatus nppiLShiftC_32s_C4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32u` aConstants[4], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel image left shift by constant.
- `NppStatus nppiLShiftC_32s_C4IR` (const `Npp32u` aConstants[4], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel in place image left shift by constant.

7.33.1 Detailed Description

Pixel by pixel left shift of an image by a constant value.

7.33.2 Function Documentation

7.33.2.1 NppStatus nppiLShiftC_16u_AC4IR (const Npp32u *aConstants*[3], Npp16u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

Four 16-bit unsigned short channel in place image left shift by constant with unmodified alpha.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.33.2.2 NppStatus nppiLShiftC_16u_AC4R (const Npp16u * *pSrc1*, int *nSrc1Step*, const Npp32u *aConstants*[3], Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

Four 16-bit unsigned short channel image left shift by constant with unmodified alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.33.2.3 NppStatus nppiLShiftC_16u_C1IR (const Npp32u *nConstant*, Npp16u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

One 16-bit unsigned short channel in place image left shift by constant.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.33.2.4 NppStatus nppiLShiftC_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, const Npp32u nConstant, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

One 16-bit unsigned short channel image left shift by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.33.2.5 NppStatus nppiLShiftC_16u_C3IR (const Npp32u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 16-bit unsigned short channel in place image left shift by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.33.2.6 NppStatus nppiLShiftC_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Three 16-bit unsigned short channel image left shift by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.33.2.7 NppStatus nppiLShiftC_16u_C4IR (const Npp32u aConstants[4], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel in place image left shift by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.33.2.8 NppStatus nppiLShiftC_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp32u aConstants[4], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel image left shift by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.33.2.9 NppStatus nppiLShiftC_32s_AC4IR (const Npp32u aConstants[3], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel in place image left shift by constant with unmodified alpha.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.33.2.10 NppStatus nppiLShiftC_32s_AC4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel image left shift by constant with unmodified alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.33.2.11 NppStatus nppiLShiftC_32s_C1IR (const Npp32u nConstant, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit signed integer channel in place image left shift by constant.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.33.2.12 `NppStatus nppiLShiftC_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32u nConstant, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit signed integer channel image left shift by constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.33.2.13 `NppStatus nppiLShiftC_32s_C3IR (const Npp32u aConstants[3], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Three 32-bit signed integer channel in place image left shift by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.33.2.14 `NppStatus nppiLShiftC_32s_C3R (const Npp32s * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit signed integer channel image left shift by constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.33.2.15 `NppStatus nppiLShiftC_32s_C4IR (const Npp32u aConstants[4], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel in place image left shift by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.33.2.16 `NppStatus nppiLShiftC_32s_C4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32u aConstants[4], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel image left shift by constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.33.2.17 `NppStatus nppiLShiftC_8u_AC4IR (const Npp32u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image left shift by constant with unmodified alpha.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.33.2.18 NppStatus nppiLShiftC_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel image left shift by constant with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.33.2.19 NppStatus nppiLShiftC_8u_C11R (const Npp32u nConstant, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 8-bit unsigned char channel in place image left shift by constant.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.33.2.20 NppStatus nppiLShiftC_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp32u nConstant, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

One 8-bit unsigned char channel image left shift by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.33.2.21 NppStatus nppiLShiftC_8u_C3IR (const Npp32u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel in place image left shift by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.33.2.22 NppStatus nppiLShiftC_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel image left shift by constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.33.2.23 NppStatus nppiLShiftC_8u_C4IR (const Npp32u aConstants[4], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel in place image left shift by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.33.2.24 `NppStatus nppiLShiftC_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp32u aConstants[4], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image left shift by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34 And

Pixel by pixel logical and of images.

Functions

- `NppStatus nppiAnd_8u_C1R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel image logical and.
- `NppStatus nppiAnd_8u_C1IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel in place image logical and.
- `NppStatus nppiAnd_8u_C3R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 8-bit unsigned char channel image logical and.
- `NppStatus nppiAnd_8u_C3IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 8-bit unsigned char channel in place image logical and.
- `NppStatus nppiAnd_8u_AC4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel image logical and with unmodified alpha.
- `NppStatus nppiAnd_8u_AC4IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel in place image logical and with unmodified alpha.
- `NppStatus nppiAnd_8u_C4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel image logical and.
- `NppStatus nppiAnd_8u_C4IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel in place image logical and.
- `NppStatus nppiAnd_16u_C1R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 16-bit unsigned short channel image logical and.
- `NppStatus nppiAnd_16u_C1IR` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 16-bit unsigned short channel in place image logical and.
- `NppStatus nppiAnd_16u_C3R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 16-bit unsigned short channel image logical and.

- `NppStatus nppiAnd_16u_C3IR` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 16-bit unsigned short channel in place image logical and.
- `NppStatus nppiAnd_16u_AC4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel image logical and with unmodified alpha.
- `NppStatus nppiAnd_16u_AC4IR` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel in place image logical and with unmodified alpha.
- `NppStatus nppiAnd_16u_C4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel image logical and.
- `NppStatus nppiAnd_16u_C4IR` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel in place image logical and.
- `NppStatus nppiAnd_32s_C1R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 32-bit signed integer channel image logical and.
- `NppStatus nppiAnd_32s_C1IR` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 32-bit signed integer channel in place image logical and.
- `NppStatus nppiAnd_32s_C3R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 32-bit signed integer channel image logical and.
- `NppStatus nppiAnd_32s_C3IR` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 32-bit signed integer channel in place image logical and.
- `NppStatus nppiAnd_32s_AC4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel image logical and with unmodified alpha.
- `NppStatus nppiAnd_32s_AC4IR` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel in place image logical and with unmodified alpha.
- `NppStatus nppiAnd_32s_C4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel image logical and.
- `NppStatus nppiAnd_32s_C4IR` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel in place image logical and.

7.34.1 Detailed Description

Pixel by pixel logical and of images.

7.34.2 Function Documentation

7.34.2.1 `NppStatus nppiAnd_16u_AC4IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 16-bit unsigned short channel in place image logical and with unmodified alpha.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.34.2.2 `NppStatus nppiAnd_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 16-bit unsigned short channel image logical and with unmodified alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.34.2.3 `NppStatus nppiAnd_16u_C1IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 16-bit unsigned short channel in place image logical and.

Parameters:

- pSrc* Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.4 NppStatus nppiAnd_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

One 16-bit unsigned short channel image logical and.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.5 NppStatus nppiAnd_16u_C3IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 16-bit unsigned short channel in place image logical and.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.6 NppStatus nppiAnd_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Three 16-bit unsigned short channel image logical and.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.34.2.7 NppStatus nppiAnd_16u_C4IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel in place image logical and.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.34.2.8 NppStatus nppiAnd_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel image logical and.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.9 NppStatus nppiAnd_32s_AC4IR (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel in place image logical and with unmodified alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.10 NppStatus nppiAnd_32s_AC4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel image logical and with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.11 NppStatus nppiAnd_32s_C1IR (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit signed integer channel in place image logical and.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.12 NppStatus nppiAnd_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit signed integer channel image logical and.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.13 NppStatus nppiAnd_32s_C3IR (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit signed integer channel in place image logical and.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.14 `NppStatus nppiAnd_32s_C3R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit signed integer channel image logical and.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.34.2.15 `NppStatus nppiAnd_32s_C4IR (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel in place image logical and.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.34.2.16 `NppStatus nppiAnd_32s_C4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel image logical and.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.17 `NppStatus nppiAnd_8u_AC4IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image logical and with unmodified alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.18 `NppStatus nppiAnd_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image logical and with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.19 NppStatus nppiAnd_8u_C1IR (const Npp8u * *pSrc*, int *nSrcStep*, Npp8u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

One 8-bit unsigned char channel in place image logical and.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.34.2.20 NppStatus nppiAnd_8u_C1R (const Npp8u * *pSrc1*, int *nSrc1Step*, const Npp8u * *pSrc2*, int *nSrc2Step*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

One 8-bit unsigned char channel image logical and.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.34.2.21 NppStatus nppiAnd_8u_C3IR (const Npp8u * *pSrc*, int *nSrcStep*, Npp8u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

Three 8-bit unsigned char channel in place image logical and.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.34.2.22 `NppStatus nppiAnd_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Three 8-bit unsigned char channel image logical and.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.34.2.23 `NppStatus nppiAnd_8u_C4IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image logical and.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.34.2.24 `NppStatus nppiAnd_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image logical and.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35 Or

Pixel by pixel logical or of images.

Functions

- `NppStatus nppiOr_8u_C1R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel image logical or.
- `NppStatus nppiOr_8u_C1IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel in place image logical or.
- `NppStatus nppiOr_8u_C3R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 8-bit unsigned char channel image logical or.
- `NppStatus nppiOr_8u_C3IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 8-bit unsigned char channel in place image logical or.
- `NppStatus nppiOr_8u_AC4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel image logical or with unmodified alpha.
- `NppStatus nppiOr_8u_AC4IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel in place image logical or with unmodified alpha.
- `NppStatus nppiOr_8u_C4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel image logical or.
- `NppStatus nppiOr_8u_C4IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel in place image logical or.
- `NppStatus nppiOr_16u_C1R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 16-bit unsigned short channel image logical or.
- `NppStatus nppiOr_16u_C1IR` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 16-bit unsigned short channel in place image logical or.
- `NppStatus nppiOr_16u_C3R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 16-bit unsigned short channel image logical or.

- `NppStatus nppiOr_16u_C3IR` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 16-bit unsigned short channel in place image logical or.
- `NppStatus nppiOr_16u_AC4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel image logical or with unmodified alpha.
- `NppStatus nppiOr_16u_AC4IR` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel in place image logical or with unmodified alpha.
- `NppStatus nppiOr_16u_C4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel image logical or.
- `NppStatus nppiOr_16u_C4IR` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel in place image logical or.
- `NppStatus nppiOr_32s_C1R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 32-bit signed integer channel image logical or.
- `NppStatus nppiOr_32s_C1IR` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 32-bit signed integer channel in place image logical or.
- `NppStatus nppiOr_32s_C3R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 32-bit signed integer channel image logical or.
- `NppStatus nppiOr_32s_C3IR` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 32-bit signed integer channel in place image logical or.
- `NppStatus nppiOr_32s_AC4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel image logical or with unmodified alpha.
- `NppStatus nppiOr_32s_AC4IR` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel in place image logical or with unmodified alpha.
- `NppStatus nppiOr_32s_C4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel image logical or.
- `NppStatus nppiOr_32s_C4IR` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel in place image logical or.

7.35.1 Detailed Description

Pixel by pixel logical or of images.

7.35.2 Function Documentation

7.35.2.1 `NppStatus nppiOr_16u_AC4IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 16-bit unsigned short channel in place image logical or with unmodified alpha.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.35.2.2 `NppStatus nppiOr_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 16-bit unsigned short channel image logical or with unmodified alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.35.2.3 `NppStatus nppiOr_16u_C1IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 16-bit unsigned short channel in place image logical or.

Parameters:

- pSrc* Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.4 NppStatus nppiOr_16u_C1R (const Npp16u * *pSrc1*, int *nSrc1Step*, const Npp16u * *pSrc2*, int *nSrc2Step*, Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

One 16-bit unsigned short channel image logical or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.5 NppStatus nppiOr_16u_C3IR (const Npp16u * *pSrc*, int *nSrcStep*, Npp16u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

Three 16-bit unsigned short channel in place image logical or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.6 NppStatus nppiOr_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Three 16-bit unsigned short channel image logical or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.35.2.7 NppStatus nppiOr_16u_C4IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel in place image logical or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.35.2.8 NppStatus nppiOr_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel image logical or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.9 `NppStatus nppiOr_32s_AC4IR (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel in place image logical or with unmodified alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.10 `NppStatus nppiOr_32s_AC4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel image logical or with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.11 NppStatus nppiOr_32s_C1IR (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit signed integer channel in place image logical or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.12 NppStatus nppiOr_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit signed integer channel image logical or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.13 NppStatus nppiOr_32s_C3IR (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit signed integer channel in place image logical or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.14 `NppStatus nppiOr_32s_C3R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit signed integer channel image logical or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.35.2.15 `NppStatus nppiOr_32s_C4IR (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel in place image logical or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.35.2.16 `NppStatus nppiOr_32s_C4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel image logical or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.17 `NppStatus nppiOr_8u_AC4IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image logical or with unmodified alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.18 `NppStatus nppiOr_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image logical or with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.19 NppStatus nppiOr_8u_C1IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 8-bit unsigned char channel in place image logical or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.20 NppStatus nppiOr_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

One 8-bit unsigned char channel image logical or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.21 NppStatus nppiOr_8u_C3IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel in place image logical or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.22 `NppStatus nppiOr_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Three 8-bit unsigned char channel image logical or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.35.2.23 `NppStatus nppiOr_8u_C4IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image logical or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.35.2.24 `NppStatus nppiOr_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image logical or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.36 Xor

Pixel by pixel logical exclusive or of images.

Functions

- `NppStatus nppiXor_8u_C1R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel image logical exclusive or.
- `NppStatus nppiXor_8u_C1IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel in place image logical exclusive or.
- `NppStatus nppiXor_8u_C3R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 8-bit unsigned char channel image logical exclusive or.
- `NppStatus nppiXor_8u_C3IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 8-bit unsigned char channel in place image logical exclusive or.
- `NppStatus nppiXor_8u_AC4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel image logical exclusive or with unmodified alpha.
- `NppStatus nppiXor_8u_AC4IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel in place image logical exclusive or with unmodified alpha.
- `NppStatus nppiXor_8u_C4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel image logical exclusive or.
- `NppStatus nppiXor_8u_C4IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel in place image logical exclusive or.
- `NppStatus nppiXor_16u_C1R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 16-bit unsigned short channel image logical exclusive or.
- `NppStatus nppiXor_16u_C1IR` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 16-bit unsigned short channel in place image logical exclusive or.
- `NppStatus nppiXor_16u_C3R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 16-bit unsigned short channel image logical exclusive or.

- **NppStatus nppiXor_16u_C3IR** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 16-bit unsigned short channel in place image logical exclusive or.
- **NppStatus nppiXor_16u_AC4R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 16-bit unsigned short channel image logical exclusive or with unmodified alpha.
- **NppStatus nppiXor_16u_AC4IR** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 16-bit unsigned short channel in place image logical exclusive or with unmodified alpha.
- **NppStatus nppiXor_16u_C4R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 16-bit unsigned short channel image logical exclusive or.
- **NppStatus nppiXor_16u_C4IR** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 16-bit unsigned short channel in place image logical exclusive or.
- **NppStatus nppiXor_32s_C1R** (const **Npp32s** *pSrc1, int nSrc1Step, const **Npp32s** *pSrc2, int nSrc2Step, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 32-bit signed integer channel image logical exclusive or.
- **NppStatus nppiXor_32s_C1IR** (const **Npp32s** *pSrc, int nSrcStep, **Npp32s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 32-bit signed integer channel in place image logical exclusive or.
- **NppStatus nppiXor_32s_C3R** (const **Npp32s** *pSrc1, int nSrc1Step, const **Npp32s** *pSrc2, int nSrc2Step, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 32-bit signed integer channel image logical exclusive or.
- **NppStatus nppiXor_32s_C3IR** (const **Npp32s** *pSrc, int nSrcStep, **Npp32s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 32-bit signed integer channel in place image logical exclusive or.
- **NppStatus nppiXor_32s_AC4R** (const **Npp32s** *pSrc1, int nSrc1Step, const **Npp32s** *pSrc2, int nSrc2Step, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit signed integer channel image logical exclusive or with unmodified alpha.
- **NppStatus nppiXor_32s_AC4IR** (const **Npp32s** *pSrc, int nSrcStep, **Npp32s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit signed integer channel in place image logical exclusive or with unmodified alpha.
- **NppStatus nppiXor_32s_C4R** (const **Npp32s** *pSrc1, int nSrc1Step, const **Npp32s** *pSrc2, int nSrc2Step, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit signed integer channel image logical exclusive or.
- **NppStatus nppiXor_32s_C4IR** (const **Npp32s** *pSrc, int nSrcStep, **Npp32s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit signed integer channel in place image logical exclusive or.

7.36.1 Detailed Description

Pixel by pixel logical exclusive or of images.

7.36.2 Function Documentation

7.36.2.1 `NppStatus nppiXor_16u_AC4IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 16-bit unsigned short channel in place image logical exclusive or with unmodified alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.36.2.2 `NppStatus nppiXor_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 16-bit unsigned short channel image logical exclusive or with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.36.2.3 `NppStatus nppiXor_16u_C1IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 16-bit unsigned short channel in place image logical exclusive or.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.36.2.4 NppStatus nppiXor_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

One 16-bit unsigned short channel image logical exclusive or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.36.2.5 NppStatus nppiXor_16u_C3IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 16-bit unsigned short channel in place image logical exclusive or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.36.2.6 NppStatus nppiXor_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Three 16-bit unsigned short channel image logical exclusive or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.36.2.7 NppStatus nppiXor_16u_C4IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel in place image logical exclusive or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.36.2.8 NppStatus nppiXor_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel image logical exclusive or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.36.2.9 NppStatus nppiXor_32s_AC4IR (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel in place image logical exclusive or with unmodified alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.36.2.10 NppStatus nppiXor_32s_AC4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel image logical exclusive or with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.36.2.11 NppStatus nppiXor_32s_C1IR (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit signed integer channel in place image logical exclusive or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.36.2.12 NppStatus nppiXor_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit signed integer channel image logical exclusive or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.36.2.13 NppStatus nppiXor_32s_C3IR (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit signed integer channel in place image logical exclusive or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.36.2.14 NppStatus nppiXor_32s_C3R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit signed integer channel image logical exclusive or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.36.2.15 NppStatus nppiXor_32s_C4IR (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel in place image logical exclusive or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.36.2.16 NppStatus nppiXor_32s_C4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel image logical exclusive or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.36.2.17 `NppStatus nppiXor_8u_AC4IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image logical exclusive or with unmodified alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.36.2.18 `NppStatus nppiXor_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image logical exclusive or with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.36.2.19 NppStatus nppiXor_8u_C1IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 8-bit unsigned char channel in place image logical exclusive or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.36.2.20 NppStatus nppiXor_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

One 8-bit unsigned char channel image logical exclusive or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.36.2.21 NppStatus nppiXor_8u_C3IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel in place image logical exclusive or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.36.2.22 `NppStatus nppiXor_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Three 8-bit unsigned char channel image logical exclusive or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.36.2.23 `NppStatus nppiXor_8u_C4IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image logical exclusive or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.36.2.24 `NppStatus nppiXor_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image logical exclusive or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.37 Not

Pixel by pixel logical not of image.

Functions

- `NppStatus nppiNot_8u_C1R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
One 8-bit unsigned char channel image logical not.
- `NppStatus nppiNot_8u_C1IR` (`Npp8u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
One 8-bit unsigned char channel in place image logical not.
- `NppStatus nppiNot_8u_C3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Three 8-bit unsigned char channel image logical not.
- `NppStatus nppiNot_8u_C3IR` (`Npp8u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Three 8-bit unsigned char channel in place image logical not.
- `NppStatus nppiNot_8u_AC4R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four 8-bit unsigned char channel image logical not with unmodified alpha.
- `NppStatus nppiNot_8u_AC4IR` (`Npp8u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Four 8-bit unsigned char channel in place image logical not with unmodified alpha.
- `NppStatus nppiNot_8u_C4R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four 8-bit unsigned char channel image logical not.
- `NppStatus nppiNot_8u_C4IR` (`Npp8u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Four 8-bit unsigned char channel in place image logical not.

7.37.1 Detailed Description

Pixel by pixel logical not of image.

7.37.2 Function Documentation

7.37.2.1 `NppStatus nppiNot_8u_AC4IR` (`Npp8u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Four 8-bit unsigned char channel in place image logical not with unmodified alpha.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.37.2.2 `NppStatus nppiNot_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image logical not with unmodified alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.37.2.3 `NppStatus nppiNot_8u_C1IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel in place image logical not.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.37.2.4 `NppStatus nppiNot_8u_C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel image logical not.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.37.2.5 NppStatus nppiNot_8u_C3IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel in place image logical not.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.37.2.6 NppStatus nppiNot_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel image logical not.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.37.2.7 NppStatus nppiNot_8u_C4IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel in place image logical not.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.37.2.8 NppStatus nppiNot_8u_C4R (const Npp8u * *pSrc*, int *nSrcStep*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

Four 8-bit unsigned char channel image logical not.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.38 Alpha Composition

Modules

- [AlphaCompC](#)
Composite two images using constant alpha values.
- [AlphaPremulC](#)
Premultiplies pixels of an image using a constant alpha value.
- [AlphaComp](#)
Composite two images using alpha opacity values contained in each image.
- [AlphaPremul](#)
Premultiplies image pixels by image alpha opacity values.

7.39 AlphaCompC

Composite two images using constant alpha values.

Functions

- `NppStatus nppiAlphaCompC_8u_C1R` (const `Npp8u` *pSrc1, int nSrc1Step, `Npp8u` nAlpha1, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` nAlpha2, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
One 8-bit unsigned char channel image composition using constant alpha.
- `NppStatus nppiAlphaCompC_8u_C3R` (const `Npp8u` *pSrc1, int nSrc1Step, `Npp8u` nAlpha1, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` nAlpha2, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
Three 8-bit unsigned char channel image composition using constant alpha.
- `NppStatus nppiAlphaCompC_8u_C4R` (const `Npp8u` *pSrc1, int nSrc1Step, `Npp8u` nAlpha1, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` nAlpha2, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
Four 8-bit unsigned char channel image composition using constant alpha.
- `NppStatus nppiAlphaCompC_8u_AC4R` (const `Npp8u` *pSrc1, int nSrc1Step, `Npp8u` nAlpha1, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` nAlpha2, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
Four 8-bit unsigned char channel image composition with alpha using constant source alpha.
- `NppStatus nppiAlphaCompC_8s_C1R` (const `Npp8s` *pSrc1, int nSrc1Step, `Npp8s` nAlpha1, const `Npp8s` *pSrc2, int nSrc2Step, `Npp8s` nAlpha2, `Npp8s` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
One 8-bit signed char channel image composition using constant alpha.
- `NppStatus nppiAlphaCompC_16u_C1R` (const `Npp16u` *pSrc1, int nSrc1Step, `Npp16u` nAlpha1, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` nAlpha2, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
One 16-bit unsigned short channel image composition using constant alpha.
- `NppStatus nppiAlphaCompC_16u_C3R` (const `Npp16u` *pSrc1, int nSrc1Step, `Npp16u` nAlpha1, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` nAlpha2, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
Three 16-bit unsigned short channel image composition using constant alpha.
- `NppStatus nppiAlphaCompC_16u_C4R` (const `Npp16u` *pSrc1, int nSrc1Step, `Npp16u` nAlpha1, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` nAlpha2, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
Four 16-bit unsigned short channel image composition using constant alpha.
- `NppStatus nppiAlphaCompC_16u_AC4R` (const `Npp16u` *pSrc1, int nSrc1Step, `Npp16u` nAlpha1, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` nAlpha2, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
Four 16-bit unsigned short channel image composition with alpha using constant source alpha.

- `NppStatus nppiAlphaCompC_16s_C1R` (const `Npp16s *pSrc1`, int `nSrc1Step`, `Npp16s nAlpha1`, const `Npp16s *pSrc2`, int `nSrc2Step`, `Npp16s nAlpha2`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppiAlphaOp eAlphaOp`)
One 16-bit signed short channel image composition using constant alpha.
- `NppStatus nppiAlphaCompC_32u_C1R` (const `Npp32u *pSrc1`, int `nSrc1Step`, `Npp32u nAlpha1`, const `Npp32u *pSrc2`, int `nSrc2Step`, `Npp32u nAlpha2`, `Npp32u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppiAlphaOp eAlphaOp`)
One 32-bit unsigned integer channel image composition using constant alpha.
- `NppStatus nppiAlphaCompC_32s_C1R` (const `Npp32s *pSrc1`, int `nSrc1Step`, `Npp32s nAlpha1`, const `Npp32s *pSrc2`, int `nSrc2Step`, `Npp32s nAlpha2`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppiAlphaOp eAlphaOp`)
One 32-bit signed integer channel image composition using constant alpha.
- `NppStatus nppiAlphaCompC_32f_C1R` (const `Npp32f *pSrc1`, int `nSrc1Step`, `Npp32f nAlpha1`, const `Npp32f *pSrc2`, int `nSrc2Step`, `Npp32f nAlpha2`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppiAlphaOp eAlphaOp`)
One 32-bit floating point channel image composition using constant alpha.

7.39.1 Detailed Description

Composite two images using constant alpha values.

7.39.2 Function Documentation

7.39.2.1 `NppStatus nppiAlphaCompC_16s_C1R` (const `Npp16s *pSrc1`, int `nSrc1Step`, `Npp16s nAlpha1`, const `Npp16s *pSrc2`, int `nSrc2Step`, `Npp16s nAlpha2`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppiAlphaOp eAlphaOp`)

One 16-bit signed short channel image composition using constant alpha.

Parameters:

- `pSrc1` Source-Image Pointer.
- `nSrc1Step` Source-Image Line Step.
- `nAlpha1` Image alpha opacity (0 - max channel pixel value).
- `pSrc2` Source-Image Pointer.
- `nSrc2Step` Source-Image Line Step.
- `nAlpha2` Image alpha opacity (0 - max channel pixel value).
- `pDst` Destination-Image Pointer.
- `nDstStep` Destination-Image Line Step.
- `oSizeROI` Region-of-Interest (ROI).
- `eAlphaOp` alpha-blending operation..

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.39.2.2 NppStatus nppiAlphaCompC_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, Npp16u nAlpha1, const Npp16u * pSrc2, int nSrc2Step, Npp16u nAlpha2, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)

Four 16-bit unsigned short channel image composition with alpha using constant source alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- nAlpha2* Image alpha opacity (0 - max channel pixel value).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eAlphaOp* alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.39.2.3 NppStatus nppiAlphaCompC_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, Npp16u nAlpha1, const Npp16u * pSrc2, int nSrc2Step, Npp16u nAlpha2, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)

One 16-bit unsigned short channel image composition using constant alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- nAlpha2* Image alpha opacity (0 - max channel pixel value).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eAlphaOp* alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.39.2.4 NppStatus nppiAlphaCompC_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, Npp16u nAlpha1, const Npp16u * pSrc2, int nSrc2Step, Npp16u nAlpha2, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)

Three 16-bit unsigned short channel image composition using constant alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- nAlpha2* Image alpha opacity (0 - max channel pixel value).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eAlphaOp* alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.39.2.5 NppStatus nppiAlphaCompC_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, Npp16u nAlpha1, const Npp16u * pSrc2, int nSrc2Step, Npp16u nAlpha2, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)

Four 16-bit unsigned short channel image composition using constant alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- nAlpha2* Image alpha opacity (0 - max channel pixel value).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eAlphaOp* alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.39.2.6 NppStatus nppiAlphaCompC_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, Npp32f nAlpha1, const Npp32f * pSrc2, int nSrc2Step, Npp32f nAlpha2, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)

One 32-bit floating point channel image composition using constant alpha.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nAlpha1 Image alpha opacity (0.0 - 1.0).
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
nAlpha2 Image alpha opacity (0.0 - 1.0).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eAlphaOp alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.39.2.7 NppStatus nppiAlphaCompC_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, Npp32s nAlpha1, const Npp32s * pSrc2, int nSrc2Step, Npp32s nAlpha2, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)

One 32-bit signed integer channel image composition using constant alpha.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nAlpha1 Image alpha opacity (0 - max channel pixel value).
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
nAlpha2 Image alpha opacity (0 - max channel pixel value).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eAlphaOp alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.39.2.8 NppStatus nppiAlphaCompC_32u_C1R (const Npp32u * pSrc1, int nSrc1Step, Npp32u nAlpha1, const Npp32u * pSrc2, int nSrc2Step, Npp32u nAlpha2, Npp32u * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)

One 32-bit unsigned integer channel image composition using constant alpha.

Parameters:

- pSrc1* [Source-Image Pointer](#).
- nSrc1Step* [Source-Image Line Step](#).
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrc2* [Source-Image Pointer](#).
- nSrc2Step* [Source-Image Line Step](#).
- nAlpha2* Image alpha opacity (0 - max channel pixel value).
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).
- eAlphaOp* [alpha-blending operation..](#)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.39.2.9 NppStatus nppiAlphaCompC_8s_C1R (const Npp8s * pSrc1, int nSrc1Step, Npp8s nAlpha1, const Npp8s * pSrc2, int nSrc2Step, Npp8s nAlpha2, Npp8s * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)

One 8-bit signed char channel image composition using constant alpha.

Parameters:

- pSrc1* [Source-Image Pointer](#).
- nSrc1Step* [Source-Image Line Step](#).
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrc2* [Source-Image Pointer](#).
- nSrc2Step* [Source-Image Line Step](#).
- nAlpha2* Image alpha opacity (0 - max channel pixel value).
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).
- eAlphaOp* [alpha-blending operation..](#)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.39.2.10 `NppStatus nppiAlphaCompC_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, Npp8u nAlpha1, const Npp8u * pSrc2, int nSrc2Step, Npp8u nAlpha2, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)`

Four 8-bit unsigned char channel image composition with alpha using constant source alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- nAlpha2* Image alpha opacity (0 - max channel pixel value).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eAlphaOp* alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.39.2.11 `NppStatus nppiAlphaCompC_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, Npp8u nAlpha1, const Npp8u * pSrc2, int nSrc2Step, Npp8u nAlpha2, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)`

One 8-bit unsigned char channel image composition using constant alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- nAlpha2* Image alpha opacity (0 - max channel pixel value).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eAlphaOp* alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.39.2.12 NppStatus nppiAlphaCompC_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, Npp8u nAlpha1, const Npp8u * pSrc2, int nSrc2Step, Npp8u nAlpha2, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)

Three 8-bit unsigned char channel image composition using constant alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- nAlpha2* Image alpha opacity (0 - max channel pixel value).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eAlphaOp* alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.39.2.13 NppStatus nppiAlphaCompC_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, Npp8u nAlpha1, const Npp8u * pSrc2, int nSrc2Step, Npp8u nAlpha2, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)

Four 8-bit unsigned char channel image composition using constant alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- nAlpha2* Image alpha opacity (0 - max channel pixel value).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eAlphaOp* alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.40 AlphaPremulC

Premultiplies pixels of an image using a constant alpha value.

Functions

- **NppStatus** `nppiAlphaPremulC_8u_C1R` (const **Npp8u** *pSrc1, int nSrc1Step, **Npp8u** nAlpha1, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel image premultiplication using constant alpha.
- **NppStatus** `nppiAlphaPremulC_8u_C1IR` (**Npp8u** nAlpha1, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel in place image premultiplication using constant alpha.
- **NppStatus** `nppiAlphaPremulC_8u_C3R` (const **Npp8u** *pSrc1, int nSrc1Step, **Npp8u** nAlpha1, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 8-bit unsigned char channel image premultiplication using constant alpha.
- **NppStatus** `nppiAlphaPremulC_8u_C3IR` (**Npp8u** nAlpha1, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 8-bit unsigned char channel in place image premultiplication using constant alpha.
- **NppStatus** `nppiAlphaPremulC_8u_C4R` (const **Npp8u** *pSrc1, int nSrc1Step, **Npp8u** nAlpha1, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel image premultiplication using constant alpha.
- **NppStatus** `nppiAlphaPremulC_8u_C4IR` (**Npp8u** nAlpha1, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel in place image premultiplication using constant alpha.
- **NppStatus** `nppiAlphaPremulC_8u_AC4R` (const **Npp8u** *pSrc1, int nSrc1Step, **Npp8u** nAlpha1, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel image premultiplication with alpha using constant alpha.
- **NppStatus** `nppiAlphaPremulC_8u_AC4IR` (**Npp8u** nAlpha1, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel in place image premultiplication with alpha using constant alpha.
- **NppStatus** `nppiAlphaPremulC_16u_C1R` (const **Npp16u** *pSrc1, int nSrc1Step, **Npp16u** nAlpha1, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel image premultiplication using constant alpha.
- **NppStatus** `nppiAlphaPremulC_16u_C1IR` (**Npp16u** nAlpha1, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel in place image premultiplication using constant alpha.
- **NppStatus** `nppiAlphaPremulC_16u_C3R` (const **Npp16u** *pSrc1, int nSrc1Step, **Npp16u** nAlpha1, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 16-bit unsigned short channel image premultiplication using constant alpha.

- `NppStatus nppiAlphaPremulC_16u_C3IR` (`Npp16u nAlpha1`, `Npp16u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`)
Three 16-bit unsigned short channel in place image premultiplication using constant alpha.
- `NppStatus nppiAlphaPremulC_16u_C4R` (`const Npp16u *pSrc1`, `int nSrc1Step`, `Npp16u nAlpha1`, `Npp16u *pDst`, `int nDstStep`, `NppiSize oSizeROI`)
Four 16-bit unsigned short channel image premultiplication using constant alpha.
- `NppStatus nppiAlphaPremulC_16u_C4IR` (`Npp16u nAlpha1`, `Npp16u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`)
Four 16-bit unsigned short channel in place image premultiplication using constant alpha.
- `NppStatus nppiAlphaPremulC_16u_AC4R` (`const Npp16u *pSrc1`, `int nSrc1Step`, `Npp16u nAlpha1`, `Npp16u *pDst`, `int nDstStep`, `NppiSize oSizeROI`)
Four 16-bit unsigned short channel image premultiplication with alpha using constant alpha.
- `NppStatus nppiAlphaPremulC_16u_AC4IR` (`Npp16u nAlpha1`, `Npp16u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`)
Four 16-bit unsigned short channel in place image premultiplication with alpha using constant alpha.

7.40.1 Detailed Description

Premultiplies pixels of an image using a constant alpha value.

7.40.2 Function Documentation

7.40.2.1 `NppStatus nppiAlphaPremulC_16u_AC4IR` (`Npp16u nAlpha1`, `Npp16u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`)

Four 16-bit unsigned short channel in place image premultiplication with alpha using constant alpha.

Parameters:

nAlpha1 Image alpha opacity (0 - max channel pixel value).

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.40.2.2 `NppStatus nppiAlphaPremulC_16u_AC4R` (`const Npp16u *pSrc1`, `int nSrc1Step`, `Npp16u nAlpha1`, `Npp16u *pDst`, `int nDstStep`, `NppiSize oSizeROI`)

Four 16-bit unsigned short channel image premultiplication with alpha using constant alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nAlpha1 Image alpha opacity (0 - max channel pixel value).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.40.2.3 NppStatus nppiAlphaPremulC_16u_C1IR (Npp16u nAlpha1, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 16-bit unsigned short channel in place image premultiplication using constant alpha.

Parameters:

nAlpha1 Image alpha opacity (0 - max channel pixel value).

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.40.2.4 NppStatus nppiAlphaPremulC_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, Npp16u nAlpha1, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

One 16-bit unsigned short channel image premultiplication using constant alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nAlpha1 Image alpha opacity (0 - max channel pixel value).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.40.2.5 NppStatus nppiAlphaPremulC_16u_C3IR (Npp16u *nAlpha1*, Npp16u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

Three 16-bit unsigned short channel in place image premultiplication using constant alpha.

Parameters:

- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.40.2.6 NppStatus nppiAlphaPremulC_16u_C3R (const Npp16u * *pSrc1*, int *nSrc1Step*, Npp16u *nAlpha1*, Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

Three 16-bit unsigned short channel image premultiplication using constant alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.40.2.7 NppStatus nppiAlphaPremulC_16u_C4IR (Npp16u *nAlpha1*, Npp16u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

Four 16-bit unsigned short channel in place image premultiplication using constant alpha.

Parameters:

- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.40.2.8 NppStatus nppiAlphaPremulC_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, Npp16u nAlpha1, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel image premultiplication using constant alpha.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nAlpha1 Image alpha opacity (0 - max channel pixel value).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.40.2.9 NppStatus nppiAlphaPremulC_8u_AC4IR (Npp8u nAlpha1, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel in place image premultiplication with alpha using constant alpha.

Parameters:

nAlpha1 Image alpha opacity (0 - max channel pixel value).
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.40.2.10 NppStatus nppiAlphaPremulC_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, Npp8u nAlpha1, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel image premultiplication with alpha using constant alpha.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nAlpha1 Image alpha opacity (0 - max channel pixel value).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.40.2.11 `NppStatus nppiAlphaPremulC_8u_C1IR` (`Npp8u nAlpha1`, `Npp8u * pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`)

One 8-bit unsigned char channel in place image premultiplication using constant alpha.

Parameters:

nAlpha1 Image alpha opacity (0 - max channel pixel value).
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.40.2.12 `NppStatus nppiAlphaPremulC_8u_C1R` (`const Npp8u * pSrc1`, `int nSrc1Step`, `Npp8u nAlpha1`, `Npp8u * pDst`, `int nDstStep`, `NppiSize oSizeROI`)

One 8-bit unsigned char channel image premultiplication using constant alpha.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nAlpha1 Image alpha opacity (0 - max channel pixel value).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.40.2.13 `NppStatus nppiAlphaPremulC_8u_C3IR` (`Npp8u nAlpha1`, `Npp8u * pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`)

Three 8-bit unsigned char channel in place image premultiplication using constant alpha.

Parameters:

nAlpha1 Image alpha opacity (0 - max channel pixel value).
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.40.2.14 NppStatus nppiAlphaPremulC_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, Npp8u nAlpha1, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel image premultiplication using constant alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.40.2.15 NppStatus nppiAlphaPremulC_8u_C4IR (Npp8u nAlpha1, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel in place image premultiplication using constant alpha.

Parameters:

- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.40.2.16 NppStatus nppiAlphaPremulC_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, Npp8u nAlpha1, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel image premultiplication using constant alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.41 AlphaComp

Composite two images using alpha opacity values contained in each image.

Functions

- `NppStatus nppiAlphaComp_8u_AC1R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
One 8-bit unsigned char channel image composition using image alpha values (0 - max channel pixel value).
- `NppStatus nppiAlphaComp_8u_AC4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
Four 8-bit unsigned char channel image composition using image alpha values (0 - max channel pixel value).
- `NppStatus nppiAlphaComp_8s_AC1R` (const `Npp8s` *pSrc1, int nSrc1Step, const `Npp8s` *pSrc2, int nSrc2Step, `Npp8s` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
One 8-bit signed char channel image composition using image alpha values (0 - max channel pixel value).
- `NppStatus nppiAlphaComp_16u_AC1R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
One 16-bit unsigned short channel image composition using image alpha values (0 - max channel pixel value).
- `NppStatus nppiAlphaComp_16u_AC4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
Four 16-bit unsigned short channel image composition using image alpha values (0 - max channel pixel value).
- `NppStatus nppiAlphaComp_16s_AC1R` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` *pSrc2, int nSrc2Step, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
One 16-bit signed short channel image composition using image alpha values (0 - max channel pixel value).
- `NppStatus nppiAlphaComp_32u_AC1R` (const `Npp32u` *pSrc1, int nSrc1Step, const `Npp32u` *pSrc2, int nSrc2Step, `Npp32u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
One 32-bit unsigned integer channel image composition using image alpha values (0 - max channel pixel value).
- `NppStatus nppiAlphaComp_32u_AC4R` (const `Npp32u` *pSrc1, int nSrc1Step, const `Npp32u` *pSrc2, int nSrc2Step, `Npp32u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
Four 32-bit unsigned integer channel image composition using image alpha values (0 - max channel pixel value).
- `NppStatus nppiAlphaComp_32s_AC1R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
One 32-bit signed integer channel image composition using image alpha values (0 - max channel pixel value).

- **NppStatus nppiAlphaComp_32s_AC4R** (const [Npp32s](#) *pSrc1, int nSrc1Step, const [Npp32s](#) *pSrc2, int nSrc2Step, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, [NppiAlphaOp](#) eAlphaOp)
Four 32-bit signed integer channel image composition using image alpha values (0 - max channel pixel value).
- **NppStatus nppiAlphaComp_32f_AC1R** (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, [NppiAlphaOp](#) eAlphaOp)
One 32-bit floating point channel image composition using image alpha values (0.0 - 1.0).
- **NppStatus nppiAlphaComp_32f_AC4R** (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, [NppiAlphaOp](#) eAlphaOp)
Four 32-bit floating point channel image composition using image alpha values (0.0 - 1.0).

7.41.1 Detailed Description

Composite two images using alpha opacity values contained in each image.

7.41.2 Function Documentation

7.41.2.1 NppStatus nppiAlphaComp_16s_AC1R (const [Npp16s](#) * pSrc1, int nSrc1Step, const [Npp16s](#) * pSrc2, int nSrc2Step, [Npp16s](#) * pDst, int nDstStep, [NppiSize](#) oSizeROI, [NppiAlphaOp](#) eAlphaOp)

One 16-bit signed short channel image composition using image alpha values (0 - max channel pixel value).

Parameters:

- pSrc1* [Source-Image Pointer](#).
- nSrc1Step* [Source-Image Line Step](#).
- pSrc2* [Source-Image Pointer](#).
- nSrc2Step* [Source-Image Line Step](#).
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).
- eAlphaOp* [alpha-blending operation..](#)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.41.2.2 NppStatus nppiAlphaComp_16u_AC1R (const [Npp16u](#) * pSrc1, int nSrc1Step, const [Npp16u](#) * pSrc2, int nSrc2Step, [Npp16u](#) * pDst, int nDstStep, [NppiSize](#) oSizeROI, [NppiAlphaOp](#) eAlphaOp)

One 16-bit unsigned short channel image composition using image alpha values (0 - max channel pixel value).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eAlphaOp alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.41.2.3 `NppStatus nppiAlphaComp_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)`

Four 16-bit unsigned short channel image composition using image alpha values (0 - max channel pixel value).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eAlphaOp alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.41.2.4 `NppStatus nppiAlphaComp_32f_AC1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)`

One 32-bit floating point channel image composition using image alpha values (0.0 - 1.0).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eAlphaOp alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.41.2.5 NppStatus nppiAlphaComp_32f_AC4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)

Four 32-bit floating point channel image composition using image alpha values (0.0 - 1.0).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eAlphaOp alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.41.2.6 NppStatus nppiAlphaComp_32s_AC1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)

One 32-bit signed integer channel image composition using image alpha values (0 - max channel pixel value).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eAlphaOp alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.41.2.7 NppStatus nppiAlphaComp_32s_AC4R (const Npp32s * *pSrc1*, int *nSrc1Step*, const Npp32s * *pSrc2*, int *nSrc2Step*, Npp32s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, NppiAlphaOp *eAlphaOp*)

Four 32-bit signed integer channel image composition using image alpha values (0 - max channel pixel value).

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eAlphaOp* alpha-blending operation..

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.41.2.8 NppStatus nppiAlphaComp_32u_AC1R (const Npp32u * *pSrc1*, int *nSrc1Step*, const Npp32u * *pSrc2*, int *nSrc2Step*, Npp32u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, NppiAlphaOp *eAlphaOp*)

One 32-bit unsigned integer channel image composition using image alpha values (0 - max channel pixel value).

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eAlphaOp* alpha-blending operation..

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.41.2.9 NppStatus nppiAlphaComp_32u_AC4R (const Npp32u * *pSrc1*, int *nSrc1Step*, const Npp32u * *pSrc2*, int *nSrc2Step*, Npp32u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, NppiAlphaOp *eAlphaOp*)

Four 32-bit unsigned integer channel image composition using image alpha values (0 - max channel pixel value).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eAlphaOp alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.41.2.10 NppStatus nppiAlphaComp_8s_AC1R (const Npp8s * *pSrc1*, int *nSrc1Step*, const Npp8s * *pSrc2*, int *nSrc2Step*, Npp8s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, NppiAlphaOp *eAlphaOp*)

One 8-bit signed char channel image composition using image alpha values (0 - max channel pixel value).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eAlphaOp alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.41.2.11 NppStatus nppiAlphaComp_8u_AC1R (const Npp8u * *pSrc1*, int *nSrc1Step*, const Npp8u * *pSrc2*, int *nSrc2Step*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, NppiAlphaOp *eAlphaOp*)

One 8-bit unsigned char channel image composition using image alpha values (0 - max channel pixel value).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eAlphaOp alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.41.2.12 `NppStatus nppiAlphaComp_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)`

Four 8-bit unsigned char channel image composition using image alpha values (0 - max channel pixel value).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eAlphaOp alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.42 AlphaPremul

Premultiplies image pixels by image alpha opacity values.

Functions

- `NppStatus nppiAlphaPremul_8u_AC4R` (const `Npp8u` *pSrc1, int nSrc1Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)

Four 8-bit unsigned char channel image premultiplication with pixel alpha (0 - max channel pixel value).

- `NppStatus nppiAlphaPremul_8u_AC4IR` (`Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)

Four 8-bit unsigned char channel in place image premultiplication with pixel alpha (0 - max channel pixel value).

- `NppStatus nppiAlphaPremul_16u_AC4R` (const `Npp16u` *pSrc1, int nSrc1Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)

Four 16-bit unsigned short channel image premultiplication with pixel alpha (0 - max channel pixel value).

- `NppStatus nppiAlphaPremul_16u_AC4IR` (`Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)

Four 16-bit unsigned short channel in place image premultiplication with pixel alpha (0 - max channel pixel value).

7.42.1 Detailed Description

Premultiplies image pixels by image alpha opacity values.

7.42.2 Function Documentation

7.42.2.1 `NppStatus nppiAlphaPremul_16u_AC4IR` (`Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)

Four 16-bit unsigned short channel in place image premultiplication with pixel alpha (0 - max channel pixel value).

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.42.2.2 **NppStatus nppiAlphaPremul_16u_AC4R** (const Npp16u * *pSrc1*, int *nSrc1Step*, Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

Four 16-bit unsigned short channel image premultiplication with pixel alpha (0 - max channel pixel value).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.42.2.3 **NppStatus nppiAlphaPremul_8u_AC4IR** (Npp8u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

Four 8-bit unsigned char channel in place image premultiplication with pixel alpha (0 - max channel pixel value).

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.42.2.4 **NppStatus nppiAlphaPremul_8u_AC4R** (const Npp8u * *pSrc1*, int *nSrc1Step*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

Four 8-bit unsigned char channel image premultiplication with pixel alpha (0 - max channel pixel value).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.43 Color and Sampling Conversion

Routines manipulating an image's color model and sampling format.

Modules

- [Color Model Conversion](#)
Routines for converting between various image color models.
- [Color Sampling Format Conversion](#)
Routines for converting between various image color sampling formats.
- [Color Gamma Correction](#)
Routines for correcting image color gamma.
- [Complement Color Key](#)
Routines for performing complement color key replacement.
- [Color Processing](#)
Routines for performing image color manipulation.

7.43.1 Detailed Description

Routines manipulating an image's color model and sampling format.

7.44 Color Model Conversion

Routines for converting between various image color models.

RGBToYUV

RGB to YUV color conversion.

Here is how NPP converts gamma corrected RGB or BGR to YUV. For digital RGB values in the range [0..255], Y has the range [0..255], U varies in the range [-112..+112], and V in the range [-157..+157]. To fit in the range of [0..255], a constant value of 128 is added to computed U and V values, and V is then saturated.

```
Npp32f nY = 0.299F * R + 0.587F * G + 0.114F * B;
Npp32f nU = (0.492F * ((Npp32f)nB - nY)) + 128.0F;
Npp32f nV = (0.877F * ((Npp32f)nR - nY)) + 128.0F;
if (nV > 255.0F)
    nV = 255.0F;
```

- **NppStatus nppiRGBToYUV_8u_C3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
3 channel 8-bit unsigned packed RGB to 3 channel 8-bit unsigned packed YUV color conversion.
- **NppStatus nppiRGBToYUV_8u_AC4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 8-bit unsigned packed RGB with alpha to 4 channel 8-bit unsigned packed YUV color conversion with alpha, not affecting alpha.
- **NppStatus nppiRGBToYUV_8u_P3R** (const **Npp8u** *const pSrc[3], int nSrcStep, **Npp8u** *pDst[3], int nDstStep, **NppiSize** oSizeROI)
3 channel 8-bit unsigned planar RGB to 3 channel 8-bit unsigned planar YUV color conversion.
- **NppStatus nppiRGBToYUV_8u_C3P3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst[3], int nDstStep, **NppiSize** oSizeROI)
3 channel 8-bit unsigned packed RGB to 3 channel 8-bit unsigned planar YUV color conversion.
- **NppStatus nppiRGBToYUV_8u_AC4P4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst[4], int nDstStep, **NppiSize** oSizeROI)
4 channel 8-bit unsigned packed RGB with alpha to 4 channel 8-bit unsigned planar YUV color conversion with alpha.

YUVToRGB

YUV to RGB color conversion.

Here is how NPP converts YUV to gamma corrected RGB or BGR.

```
Npp32f nY = (Npp32f) Y;
Npp32f nU = (Npp32f) U - 128.0F;
Npp32f nV = (Npp32f) V - 128.0F;
Npp32f nR = nY + 1.140F * nV;
if (nR < 0.0F)
```

```

    nR = 0.0F;
    if (nR > 255.0F)
        nR = 255.0F;
    Npp32f nG = nY - 0.394F * nU - 0.581F * nV;
    if (nG < 0.0F)
        nG = 0.0F;
    if (nG > 255.0F)
        nG = 255.0F;
    Npp32f nB = nY + 2.032F * nU;
    if (nB < 0.0F)
        nB = 0.0F;
    if (nB > 255.0F)
        nB = 255.0F;

```

- **NppStatus nppiYUVToRGB_8u_C3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
3 channel 8-bit unsigned packed YUV to 3 channel 8-bit unsigned packed RGB color conversion.
- **NppStatus nppiYUVToRGB_8u_AC4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 8-bit packed YUV with alpha to 4 channel 8-bit unsigned packed RGB color conversion with alpha, not affecting alpha.
- **NppStatus nppiYUVToRGB_8u_P3R** (const **Npp8u** *const pSrc[3], int nSrcStep, **Npp8u** *pDst[3], int nDstStep, **NppiSize** oSizeROI)
3 channel 8-bit unsigned planar YUV to 3 channel 8-bit unsigned planar RGB color conversion.
- **NppStatus nppiYUVToRGB_8u_P3C3R** (const **Npp8u** *const pSrc[3], int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
3 channel 8-bit unsigned planar YUV to 3 channel 8-bit unsigned packed RGB color conversion.

RGBToYUV422

RGB to YUV422 color conversion.

- **NppStatus nppiRGBToYUV422_8u_C3C2R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
3 channel 8-bit unsigned packed RGB to 2 channel 8-bit unsigned packed YUV422 color conversion.
- **NppStatus nppiRGBToYUV422_8u_P3R** (const **Npp8u** *const pSrc[3], int nSrcStep, **Npp8u** *pDst[3], int rDstStep[3], **NppiSize** oSizeROI)
3 channel 8-bit unsigned planar RGB to 3 channel 8-bit unsigned planar YUV422 color conversion.
- **NppStatus nppiRGBToYUV422_8u_C3P3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst[3], int rDstStep[3], **NppiSize** oSizeROI)
3 channel 8-bit unsigned packed RGB to 3 channel 8-bit unsigned planar YUV422 color conversion.

YUV422ToRGB

YUV422 to RGB color conversion.

- `NppStatus nppiYUV422ToRGB_8u_C2C3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
2 channel 8-bit unsigned packed YUV422 to 3 channel 8-bit unsigned packed RGB color conversion.
- `NppStatus nppiYUV422ToRGB_8u_P3R` (const `Npp8u *const pSrc[3]`, int `rSrcStep[3]`, `Npp8u *pDst[3]`, int `nDstStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned planar YUV422 to 3 channel 8-bit unsigned planar RGB color conversion.
- `NppStatus nppiYUV422ToRGB_8u_P3C3R` (const `Npp8u *const pSrc[3]`, int `rSrcStep[3]`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned planar YUV422 to 3 channel 8-bit unsigned packed RGB color conversion.
- `NppStatus nppiYUV422ToRGB_8u_P3AC4R` (const `Npp8u *const pSrc[3]`, int `rSrcStep[3]`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned planar YUV422 to 4 channel 8-bit unsigned packed RGB color conversion with alpha.

RGBToYUV420

RGB to YUV420 color conversion.

- `NppStatus nppiRGBToYUV420_8u_P3R` (const `Npp8u *const pSrc[3]`, int `nSrcStep`, `Npp8u *pDst[3]`, int `rDstStep[3]`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned planar RGB to 3 channel 8-bit unsigned planar YUV420 color conversion.
- `NppStatus nppiRGBToYUV420_8u_C3P3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst[3]`, int `rDstStep[3]`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned packed RGB to 3 channel 8-bit unsigned planar YUV420 color conversion.

YUV420ToRGB

YUV420 to RGB color conversion.

- `NppStatus nppiYUV420ToRGB_8u_P3R` (const `Npp8u *const pSrc[3]`, int `rSrcStep[3]`, `Npp8u *pDst[3]`, int `nDstStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned planar YUV420 to 3 channel 8-bit unsigned planar RGB color conversion.
- `NppStatus nppiYUV420ToRGB_8u_P3C3R` (const `Npp8u *const pSrc[3]`, int `rSrcStep[3]`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned planar YUV420 to 3 channel 8-bit unsigned packed RGB color conversion.
- `NppStatus nppiYUV420ToRGB_8u_P3AC4R` (const `Npp8u *const pSrc[3]`, int `rSrcStep[3]`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned planar YUV420 to 4 channel 8-bit unsigned packed RGB color conversion with alpha.

BGRToYUV420

BGR to YUV420 color conversion.

- `NppStatus nppiBGRToYUV420_8u_AC4P3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst[3]`, int `rDstStep[3]`, `NppiSize oSizeROI`)
4 channel 8-bit unsigned packed BGR with alpha to 3 channel 8-bit unsigned planar YUV420 color conversion.

YUV420ToBGR

YUV420 to BGR color conversion.

- `NppStatus nppiYUV420ToBGR_8u_P3C3R` (const `Npp8u *const pSrc[3]`, int `rSrcStep[3]`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned planar YUV420 to 3 channel 8-bit unsigned packed BGR color conversion.

RGBToYCbCr

RGB to YCbCr color conversion.

Here is how NPP converts gamma corrected RGB or BGR to YCbCr. In the YCbCr model, Y is defined to have a nominal range [16..235], while Cb and Cr are defined to have a range [16..240], with the value of 128 as corresponding to zero.

```
Npp32f nY = 0.257F * R + 0.504F * G + 0.098F * B + 16.0F;
Npp32f nCb = -0.148F * R - 0.291F * G + 0.439F * B + 128.0F;
Npp32f nCr = 0.439F * R - 0.368F * G - 0.071F * B + 128.0F;
```

- `NppStatus nppiRGBToYCbCr_8u_C3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned packed RGB to 3 channel unsigned 8-bit packed YCbCr color conversion.
- `NppStatus nppiRGBToYCbCr_8u_AC4R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
4 channel 8-bit unsigned packed RGB with alpha to 4 channel unsigned 8-bit packed YCbCr with alpha color conversion, not affecting alpha.
- `NppStatus nppiRGBToYCbCr_8u_P3R` (const `Npp8u *const pSrc[3]`, int `nSrcStep`, `Npp8u *pDst[3]`, int `nDstStep`, `NppiSize oSizeROI`)
3 channel planar 8-bit unsigned RGB to 3 channel planar 8-bit YCbCr color conversion.
- `NppStatus nppiRGBToYCbCr_8u_C3P3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst[3]`, int `nDstStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned packed RGB to 3 channel unsigned 8-bit planar YCbCr color conversion.
- `NppStatus nppiRGBToYCbCr_8u_AC4P3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst[3]`, int `nDstStep`, `NppiSize oSizeROI`)
4 channel 8-bit unsigned packed RGB with alpha to 3 channel 8-bit unsigned planar YCbCr color conversion.

YCbCrToRGB

YCbCr to RGB color conversion.

Here is how NPP converts YCbCr to gamma corrected RGB or BGR. The output RGB values are saturated to the range [0..255].

```
Npp32f nY = 1.164F * ((Npp32f)Y - 16.0F);
Npp32f nR = ((Npp32f)Cr - 128.0F);
Npp32f nB = ((Npp32f)Cb - 128.0F);
Npp32f nG = nY - 0.813F * nR - 0.392F * nB;
if (nG > 255.0F)
    nG = 255.0F;
nR = nY + 1.596F * nR;
if (nR > 255.0F)
    nR = 255.0F;
nB = nY + 2.017F * nB;
if (nB > 255.0F)
    nB = 255.0F;
```

- **NppStatus nppiYCbCrToRGB_8u_C3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
3 channel 8-bit unsigned packed YCbCr to 3 channel 8-bit unsigned packed RGB color conversion.
- **NppStatus nppiYCbCrToRGB_8u_AC4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 8-bit unsigned packed YCbCr with alpha to 4 channel 8-bit unsigned packed RGB with alpha color conversion, not affecting alpha.
- **NppStatus nppiYCbCrToRGB_8u_P3R** (const **Npp8u** *const pSrc[3], int nSrcStep, **Npp8u** *pDst[3], int nDstStep, **NppiSize** oSizeROI)
3 channel 8-bit unsigned planar YCbCr to 3 channel 8-bit unsigned planar RGB color conversion.
- **NppStatus nppiYCbCrToRGB_8u_P3C3R** (const **Npp8u** *const pSrc[3], int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
3 channel 8-bit unsigned planar YCbCr to 3 channel 8-bit unsigned packed RGB color conversion.
- **NppStatus nppiYCbCrToRGB_8u_P3C4R** (const **Npp8u** *const pSrc[3], int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **Npp8u** nAval)
3 channel 8-bit unsigned planar YCbCr to 4 channel 8-bit unsigned packed RGB color conversion with constant alpha.

YCbCrToBGR

YCbCr to BGR color conversion.

- **NppStatus nppiYCbCrToBGR_8u_P3C3R** (const **Npp8u** *const pSrc[3], int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
3 channel 8-bit unsigned planar YCbCr to 3 channel 8-bit unsigned packed BGR color conversion.
- **NppStatus nppiYCbCrToBGR_8u_P3C4R** (const **Npp8u** *const pSrc[3], int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **Npp8u** nAval)
3 channel 8-bit unsigned planar YCbCr to 4 channel 8-bit unsigned packed BGR color conversion with constant alpha.

YCbCrToBGR_709CSC

YCbCr to BGR_709CSC color conversion.

- `NppStatus nppiYCbCrToBGR_709CSC_8u_P3C3R` (const `Npp8u` *const pSrc[3], int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
3 channel 8-bit unsigned planar YCbCr to 3 channel 8-bit unsigned packed BGR_709CSC color conversion.
- `NppStatus nppiYCbCrToBGR_709CSC_8u_P3C4R` (const `Npp8u` *const pSrc[3], int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `Npp8u` nAval)
3 channel 8-bit unsigned planar YCbCr to 4 channel 8-bit unsigned packed BGR_709CSC color conversion with constant alpha.

RGBToYCbCr422

RGB to YCbCr422 color conversion.

- `NppStatus nppiRGBToYCbCr422_8u_C3C2R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
3 channel 8-bit unsigned packed RGB to 2 channel 8-bit unsigned packed YCbCr422 color conversion.
- `NppStatus nppiRGBToYCbCr422_8u_C3P3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst[3], int rDstStep[3], `NppiSize` oSizeROI)
3 channel 8-bit unsigned packed RGB to 3 channel 8-bit unsigned planar YCbCr422 color conversion.
- `NppStatus nppiRGBToYCbCr422_8u_P3C2R` (const `Npp8u` *const pSrc[3], int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
3 channel 8-bit unsigned planar RGB to 2 channel 8-bit unsigned packed YCbCr422 color conversion.

YCbCr422ToRGB

YCbCr422 to RGB color conversion.

- `NppStatus nppiYCbCr422ToRGB_8u_C2C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
2 channel 8-bit unsigned packed YCbCr422 to 3 channel 8-bit unsigned packed RGB color conversion.
- `NppStatus nppiYCbCr422ToRGB_8u_C2P3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst[3], int nDstStep, `NppiSize` oSizeROI)
2 channel 8-bit unsigned packed YCbCr422 to 3 channel 8-bit unsigned planar RGB color conversion.
- `NppStatus nppiYCbCr422ToRGB_8u_P3C3R` (const `Npp8u` *const pSrc[3], int rSrcStep[3], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
3 channel 8-bit unsigned planar YCbCr422 to 3 channel 8-bit unsigned packed RGB color conversion.

RGBToYCrCb422

RGB to YCrCb422 color conversion.

- `NppStatus nppiRGBToYCrCb422_8u_C3C2R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned packed RGB to 2 channel 8-bit unsigned packed YCrCb422 color conversion.
- `NppStatus nppiRGBToYCrCb422_8u_P3C2R` (const `Npp8u *const pSrc[3]`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned planar RGB to 2 channel 8-bit unsigned packed YCrCb422 color conversion.

YCrCb422ToRGB

YCrCb422 to RGB color conversion.

- `NppStatus nppiYCrCb422ToRGB_8u_C2C3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
2 channel 8-bit unsigned packed YCrCb422 to 3 channel 8-bit unsigned packed RGB color conversion.
- `NppStatus nppiYCrCb422ToRGB_8u_C2P3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst[3]`, int `nDstStep`, `NppiSize oSizeROI`)
2 channel 8-bit unsigned packed YCrCb422 to 3 channel 8-bit unsigned planar RGB color conversion.

BGRToYCbCr422

BGR to YCbCr422 color conversion.

- `NppStatus nppiBGRToYCbCr422_8u_C3C2R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned packed BGR to 2 channel 8-bit unsigned packed YCrCb422 color conversion.
- `NppStatus nppiBGRToYCbCr422_8u_AC4C2R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
4 channel 8-bit unsigned packed BGR with alpha to 2 channel 8-bit unsigned packed YCrCb422 color conversion.
- `NppStatus nppiBGRToYCbCr422_8u_C3P3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst[3]`, int `rDstStep[3]`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned packed BGR to 3 channel 8-bit unsigned planar YCbCr422 color conversion.
- `NppStatus nppiBGRToYCbCr422_8u_AC4P3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst[3]`, int `rDstStep[3]`, `NppiSize oSizeROI`)
4 channel 8-bit unsigned packed BGR with alpha to 3 channel 8-bit unsigned planar YCbCr422 color conversion.

YCbCr422ToBGR

YCbCr422 to BGR color conversion.

- `NppStatus nppiYCbCr422ToBGR_8u_C2C3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
2 channel 8-bit unsigned packed YCrCb422 to 3 channel 8-bit unsigned packed BGR color conversion.
- `NppStatus nppiYCbCr422ToBGR_8u_C2C4R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `Npp8u nAval`)
2 channel 8-bit unsigned packed YCrCb422 to 4 channel 8-bit unsigned packed BGR color conversion with constant alpha.
- `NppStatus nppiYCbCr422ToBGR_8u_P3C3R` (const `Npp8u *const pSrc[3]`, int `rSrcStep[3]`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned planar YCbCr422 to 3 channel 8-bit unsigned packed BGR color conversion.

RGBToCbYCr422

RGB to CbYCr422 color conversion.

- `NppStatus nppiRGBToCbYCr422_8u_C3C2R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned packed RGB to 2 channel 8-bit unsigned packed CbYCr422 color conversion.
- `NppStatus nppiRGBToCbYCr422Gamma_8u_C3C2R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned packed RGB first gets forward gamma corrected then converted to 2 channel 8-bit unsigned packed CbYCr422 color conversion.

CbYCr422ToRGB

CbYCr422 to RGB color conversion.

- `NppStatus nppiCbYCr422ToRGB_8u_C2C3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
2 channel 8-bit unsigned packed CbYCr422 to 3 channel 8-bit unsigned packed RGB color conversion.

BGRToCbYCr422

BGR to CbYCr422 color conversion.

- `NppStatus nppiBGRToCbYCr422_8u_AC4C2R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
4 channel 8-bit unsigned packed BGR with alpha to 2 channel 8-bit unsigned packed CbYCr422 color conversion.

BGRToCbYCr422_709HDTV

BGR to CbYCr422_709HDTV color conversion.

- `NppStatus nppiBGRToCbYCr422_709HDTV_8u_C3C2R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned packed BGR to 2 channel 8-bit unsigned packed CbYCr422_709HDTV color conversion.
- `NppStatus nppiBGRToCbYCr422_709HDTV_8u_AC4C2R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
4 channel 8-bit unsigned packed BGR with alpha to 2 channel 8-bit unsigned packed CbYCr422_709HDTV color conversion.

CbYCr422ToBGR

CbYCr422 to BGR color conversion.

- `NppStatus nppiCbYCr422ToBGR_8u_C2C4R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `Npp8u nAval`)
2 channel 8-bit unsigned packed CbYCr422 to 4 channel 8-bit unsigned packed BGR color conversion with alpha.

CbYCr422ToBGR_709HDTV

CbYCr422 to BGR_709HDTV color conversion.

- `NppStatus nppiCbYCr422ToBGR_709HDTV_8u_C2C3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
2 channel 8-bit unsigned packed CbYCr422 to 3 channel 8-bit unsigned packed BGR_709HDTV color conversion.
- `NppStatus nppiCbYCr422ToBGR_709HDTV_8u_C2C4R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `Npp8u nAval`)
2 channel 8-bit unsigned packed CbYCr422 to 4 channel 8-bit unsigned packed BGR_709HDTV color conversion with constant alpha.

RGBToYCbCr420

RGB to YCbCr420 color conversion.

- `NppStatus nppiRGBToYCbCr420_8u_C3P3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst[3]`, int `rDstStep[3]`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned packed RGB to 3 channel 8-bit unsigned planar YCbCr420 color conversion.

YCbCr420ToRGB

YCbCr420 to RGB color conversion.

- `NppStatus nppiYCbCr420ToRGB_8u_P3C3R` (const `Npp8u` *const pSrc[3], int rSrcStep[3], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
3 channel 8-bit unsigned planar YCbCr420 to 3 channel 8-bit unsigned packed RGB color conversion.

RGBToYCrCb420

RGB to YCrCb420 color conversion.

- `NppStatus nppiRGBToYCrCb420_8u_AC4P3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst[3], int rDstStep[3], `NppiSize` oSizeROI)
4 channel 8-bit unsigned packed RGB with alpha to 3 channel 8-bit unsigned planar YCrCb420 color conversion.

YCrCb420ToRGB

YCrCb420 to RGB color conversion.

- `NppStatus nppiYCrCb420ToRGB_8u_P3C4R` (const `Npp8u` *const pSrc[3], int rSrcStep[3], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `Npp8u` nAval)
3 channel 8-bit unsigned planar YCrCb420 to 4 channel 8-bit unsigned packed RGB color conversion with constant alpha.

BGRToYCbCr420

BGR to YCbCr420 color conversion.

- `NppStatus nppiBGRToYCbCr420_8u_C3P3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst[3], int rDstStep[3], `NppiSize` oSizeROI)
3 channel 8-bit unsigned packed BGR to 3 channel 8-bit unsigned planar YCbCr420 color conversion.
- `NppStatus nppiBGRToYCbCr420_8u_AC4P3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst[3], int rDstStep[3], `NppiSize` oSizeROI)
4 channel 8-bit unsigned packed BGR with alpha to 3 channel 8-bit unsigned planar YCbCr420 color conversion.

BGRToYCbCr420_709CSC

BGR to YCbCr420_709CSC color conversion.

- `NppStatus nppiBGRToYCbCr420_709CSC_8u_C3P3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst[3], int rDstStep[3], `NppiSize` oSizeROI)

3 channel 8-bit unsigned packed BGR to 3 channel 8-bit unsigned planar YCbCr420_709CSC color conversion.

- **NppStatus nppiBGRToYCbCr420_709CSC_8u_AC4P3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst[3], int rDstStep[3], **NppiSize** oSizeROI)

4 channel 8-bit unsigned packed BGR with alpha to 3 channel 8-bit unsigned planar YCbCr420_709CSC color conversion.

BGRToYCbCr420_709HDTV

BGR to YCbCr420_709HDTV color conversion.

- **NppStatus nppiBGRToYCbCr420_709HDTV_8u_AC4P3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst[3], int rDstStep[3], **NppiSize** oSizeROI)

4 channel 8-bit unsigned packed BGR with alpha to 3 channel 8-bit unsigned planar YCbCr420_709HDTV color conversion.

BGRToYCrCb420_709CSC

BGR to YCrCb420_709CSC color conversion.

- **NppStatus nppiBGRToYCrCb420_709CSC_8u_C3P3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst[3], int rDstStep[3], **NppiSize** oSizeROI)

3 channel 8-bit unsigned packed BGR to 3 channel 8-bit unsigned planar YCrCb420_709CSC color conversion.

- **NppStatus nppiBGRToYCrCb420_709CSC_8u_AC4P3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst[3], int rDstStep[3], **NppiSize** oSizeROI)

4 channel 8-bit unsigned packed BGR with alpha to 3 channel 8-bit unsigned planar YCrCb420_709CSC color conversion.

YCbCr420ToBGR

YCbCr420 to BGR color conversion.

- **NppStatus nppiYCbCr420ToBGR_8u_P3C3R** (const **Npp8u** *const pSrc[3], int rSrcStep[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)

3 channel 8-bit unsigned planar YCbCr420 to 3 channel 8-bit unsigned packed BGR color conversion.

- **NppStatus nppiYCbCr420ToBGR_8u_P3C4R** (const **Npp8u** *const pSrc[3], int rSrcStep[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **Npp8u** nAval)

3 channel 8-bit unsigned planar YCbCr420 to 4 channel 8-bit unsigned packed BGR color conversion with constant alpha.

YCbCr420ToBGR_709CSC

YCbCr420_709CSC to BGR color conversion.

- **NppStatus** `nppiYCbCr420ToBGR_709CSC_8u_P3C3R` (const **Npp8u** *const pSrc[3], int rSrcStep[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)

3 channel 8-bit unsigned planar YCbCr420 to 3 channel 8-bit unsigned packed BGR_709CSC color conversion.

YCbCr420ToBGR_709HDTV

YCbCr420_709HDTV to BGR color conversion.

- **NppStatus** `nppiYCbCr420ToBGR_709HDTV_8u_P3C4R` (const **Npp8u** *const pSrc[3], int rSrcStep[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **Npp8u** nAval)

3 channel 8-bit unsigned planar YCbCr420 to 4 channel 8-bit unsigned packed BGR_709HDTV color conversion with constant alpha.

BGRToYCrCb420

BGR to YCrCb420 color conversion.

- **NppStatus** `nppiBGRToYCrCb420_8u_C3P3R` (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst[3], int rDstStep[3], **NppiSize** oSizeROI)

3 channel 8-bit unsigned packed BGR to 3 channel 8-bit unsigned planar YCrCb420 color conversion.

- **NppStatus** `nppiBGRToYCrCb420_8u_AC4P3R` (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst[3], int rDstStep[3], **NppiSize** oSizeROI)

4 channel 8-bit unsigned packed BGR with alpha to 3 channel 8-bit unsigned planar YCrCb420 color conversion.

BGRToYCbCr411

BGR to YCbCr411 color conversion.

- **NppStatus** `nppiBGRToYCbCr411_8u_C3P3R` (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst[3], int rDstStep[3], **NppiSize** oSizeROI)

3 channel 8-bit unsigned packed BGR to 3 channel 8-bit unsigned planar YCbCr411 color conversion.

- **NppStatus** `nppiBGRToYCbCr411_8u_AC4P3R` (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst[3], int rDstStep[3], **NppiSize** oSizeROI)

4 channel 8-bit unsigned packed BGR with alpha to 3 channel 8-bit unsigned planar YCbCr411 color conversion.

YCbCr411ToBGR

YCbCr411 to BGR color conversion.

- `NppStatus nppiYCbCr411ToBGR_8u_P3C3R` (const `Npp8u` *const pSrc[3], int rSrcStep[3], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
3 channel 8-bit unsigned planar YCbCr411 to 3 channel 8-bit unsigned packed BGR color conversion.
- `NppStatus nppiYCbCr411ToBGR_8u_P3C4R` (const `Npp8u` *const pSrc[3], int rSrcStep[3], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `Npp8u` nAval)
3 channel 8-bit unsigned planar YCbCr411 to 4 channel 8-bit unsigned packed BGR color conversion with constant alpha.

RGBToXYZ

RGB to XYZ color conversion.

Here is how NPP converts gamma corrected RGB or BGR to XYZ.

```
Npp32f nNormalizedR = (Npp32f)R * 0.003921569F; // / 255.0F
Npp32f nNormalizedG = (Npp32f)G * 0.003921569F;
Npp32f nNormalizedB = (Npp32f)B * 0.003921569F;
Npp32f nX = 0.412453F * nNormalizedR + 0.35758F * nNormalizedG + 0.180423F * nNormalizedB;
if (nX > 1.0F)
    nX = 1.0F;
Npp32f nY = 0.212671F * nNormalizedR + 0.71516F * nNormalizedG + 0.072169F * nNormalizedB;
if (nY > 1.0F)
    nY = 1.0F;
Npp32f nZ = 0.019334F * nNormalizedR + 0.119193F * nNormalizedG + 0.950227F * nNormalizedB;
if (nZ > 1.0F)
    nZ = 1.0F;
X = (Npp8u) (nX * 255.0F);
Y = (Npp8u) (nY * 255.0F);
Z = (Npp8u) (nZ * 255.0F);
```

- `NppStatus nppiRGBToXYZ_8u_C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
3 channel 8-bit unsigned packed RGB to 3 channel 8-bit unsigned packed XYZ color conversion.
- `NppStatus nppiRGBToXYZ_8u_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
4 channel 8-bit unsigned packed RGB with alpha to 4 channel 8-bit unsigned packed XYZ with alpha color conversion.

XYZToRGB

XYZ to RGB color conversion.

Here is how NPP converts XYZ to gamma corrected RGB or BGR. The code assumes that X, Y, and Z values are in the range [0..1].

```
Npp32f nNormalizedX = (Npp32f)X * 0.003921569F; // / 255.0F
Npp32f nNormalizedY = (Npp32f)Y * 0.003921569F;
```

```

Npp32f nNormalizedZ = (Npp32f)Z * 0.003921569F;
Npp32f nR = 3.240479F * nNormalizedX - 1.53715F * nNormalizedY - 0.498535F * nNormalizedZ;
if (nR > 1.0F)
    nR = 1.0F;
Npp32f nG = -0.969256F * nNormalizedX + 1.875991F * nNormalizedY + 0.041556F * nNormalizedZ;
if (nG > 1.0F)
    nG = 1.0F;
Npp32f nB = 0.055648F * nNormalizedX - 0.204043F * nNormalizedY + 1.057311F * nNormalizedZ;
if (nB > 1.0F)
    nB = 1.0F;
R = (Npp8u)(nR * 255.0F);
G = (Npp8u)(nG * 255.0F);
B = (Npp8u)(nB * 255.0F);

```

- **NppStatus nppiXYZToRGB_8u_C3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)

3 channel 8-bit unsigned packed XYZ to 3 channel 8-bit unsigned packed RGB color conversion.

- **NppStatus nppiXYZToRGB_8u_AC4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)

4 channel 8-bit unsigned packed XYZ with alpha to 4 channel 8-bit unsigned packed RGB with alpha color conversion.

RGBToLUV

RGB to LUV color conversion.

Here is how NPP converts gamma corrected RGB or BGR to CIE LUV using the CIE XYZ D65 white point with a Y luminance of 1.0. The computed values of the L component are in the range [0..100], U component in the range [-134..220], and V component in the range [-140..122]. The code uses `cbtrf()` the 32 bit floating point cube root math function.

```

// use CIE D65 chromaticity coordinates
#define nCIE_XYZ_D65_xn 0.312713F
#define nCIE_XYZ_D65_yn 0.329016F
#define nn_DIVISOR (-2.0F * nCIE_XYZ_D65_xn + 12.0F * nCIE_XYZ_D65_yn + 3.0F)
#define nun (4.0F * nCIE_XYZ_D65_xn / nn_DIVISOR)
#define nvn (9.0F * nCIE_XYZ_D65_yn / nn_DIVISOR)

// First convert to XYZ
Npp32f nNormalizedR = (Npp32f)R * 0.003921569F; // / 255.0F
Npp32f nNormalizedG = (Npp32f)G * 0.003921569F;
Npp32f nNormalizedB = (Npp32f)B * 0.003921569F;
Npp32f nX = 0.412453F * nNormalizedR + 0.35758F * nNormalizedG + 0.180423F * nNormalizedB;
Npp32f nY = 0.212671F * nNormalizedR + 0.71516F * nNormalizedG + 0.072169F * nNormalizedB;
Npp32f nZ = 0.019334F * nNormalizedR + 0.119193F * nNormalizedG + 0.950227F * nNormalizedB;
// Now calculate LUV from the XYZ value
Npp32f nTemp = nX + 15.0F * nY + 3.0F * nZ;
Npp32f nu = 4.0F * nX / nTemp;
Npp32f nv = 9.0F * nY / nTemp;
Npp32f nL = 116.0F * cbtrf(nY) - 16.0F;
if (nL < 0.0F)
    nL = 0.0F;
if (nL > 100.0F)
    nL = 100.0F;
nTemp = 13.0F * nL;
Npp32f nU = nTemp * (nu - nun);
if (nU < -134.0F)
    nU = -134.0F;
if (nU > 220.0F)

```

```

    nU = 220.0F;
Npp32f nV = nTemp * (nv - nvN);
if (nV < -140.0F)
    nV = -140.0F;
if (nV > 122.0F)
    nV = 122.0F;
L = (Npp8u) (nL * 255.0F * 0.01F); // / 100.0F
U = (Npp8u) ((nU + 134.0F) * 255.0F * 0.0028249F); // / 354.0F
V = (Npp8u) ((nV + 140.0F) * 255.0F * 0.0038168F); // / 262.0F

```

- **NppStatus nppiRGBToLUV_8u_C3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)

3 channel 8-bit unsigned packed RGB to 3 channel 8-bit unsigned packed LUV color conversion.

- **NppStatus nppiRGBToLUV_8u_AC4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)

4 channel 8-bit unsigned packed RGB with alpha to 4 channel 8-bit unsigned packed LUV with alpha color conversion.

LUVToRGB

LUV to RGB color conversion.

Here is how NPP converts CIE LUV to gamma corrected RGB or BGR using the CIE XYZ D65 white point with a Y luminance of 1.0. The code uses powf() the 32 bit floating point power math function.

```

// use CIE D65 chromaticity coordinates
#define nCIE_XYZ_D65_xn 0.312713F
#define nCIE_XYZ_D65_yn 0.329016F
#define nn_DIVISOR (-2.0F * nCIE_XYZ_D65_xn + 12.0F * nCIE_XYZ_D65_yn + 3.0F)
#define nun (4.0F * nCIE_XYZ_D65_xn / nn_DIVISOR)
#define nvN (9.0F * nCIE_XYZ_D65_yn / nn_DIVISOR)

// First convert normalized LUV back to original CIE LUV range
Npp32f nL = (Npp32f)L * 100.0F * 0.003921569F; // / 255.0F
Npp32f nU = ((Npp32f)U * 354.0F * 0.003921569F) - 134.0F;
Npp32f nV = ((Npp32f)V * 262.0F * 0.003921569F) - 140.0F;
// Now convert LUV to CIE XYZ
Npp32f nTemp = 13.0F * nL;
Npp32f nu = nU / nTemp + nun;
Npp32f nv = nV / nTemp + nvN;
Npp32f nNormalizedY;
if (nL > 7.9996248F)
{
    nNormalizedY = (nL + 16.0F) * 0.008621F; // / 116.0F
    nNormalizedY = powf(nNormalizedY, 3.0F);
}
else
{
    nNormalizedY = nL * 0.001107F; // / 903.3F
}
Npp32f nNormalizedX = (-9.0F * nNormalizedY * nu) / ((nu - 4.0F) * nv - nu * nv);
Npp32f nNormalizedZ = (9.0F * nNormalizedY - 15.0F * nv * nNormalizedY - nv * nNormalizedX) / (3.0F * nv);
Npp32f nR = 3.240479F * nNormalizedX - 1.53715F * nNormalizedY - 0.498535F * nNormalizedZ;
if (nR > 1.0F)
    nR = 1.0F;
if (nR < 0.0F)
    nR = 0.0F;
Npp32f nG = -0.969256F * nNormalizedX + 1.875991F * nNormalizedY + 0.041556F * nNormalizedZ;
if (nG > 1.0F)
    nG = 1.0F;

```

```

if (nG < 0.0F)
    nG = 0.0F;
Npp32f nB = 0.055648F * nNormalizedX - 0.204043F * nNormalizedY + 1.057311F * nNormalizedZ;
if (nB > 1.0F)
    nB = 1.0F;
if (nB < 0.0F)
    nB = 0.0F;
R = (Npp8u) (nR * 255.0F);
G = (Npp8u) (nG * 255.0F);
B = (Npp8u) (nB * 255.0F);

```

- **NppStatus nppiLUVToRGB_8u_C3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
3 channel 8-bit unsigned packed LUV to 3 channel 8-bit unsigned packed RGB color conversion.
- **NppStatus nppiLUVToRGB_8u_AC4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 8-bit unsigned packed LUV with alpha to 4 channel 8-bit unsigned packed RGB with alpha color conversion.

BGRToLab

BGR to Lab color conversion.

This is how NPP converts gamma corrected BGR or RGB to Lab using the CIE Lab D65 white point with a Y luminance of 1.0. The computed values of the L component are in the range [0..100], a and b component values are in the range [-128..127]. The code uses `cbtrf()` the 32 bit floating point cube root math function.

```

// use CIE Lab chromaticity coordinates
#define nCIE_LAB_D65_xn 0.950455F
#define nCIE_LAB_D65_yn 1.0F
#define nCIE_LAB_D65_zn 1.088753F
// First convert to XYZ
Npp32f nNormalizedR = (Npp32f)R * 0.003921569F; // / 255.0F
Npp32f nNormalizedG = (Npp32f)G * 0.003921569F;
Npp32f nNormalizedB = (Npp32f)B * 0.003921569F;
Npp32f nX = 0.412453F * nNormalizedR + 0.35758F * nNormalizedG + 0.180423F * nNormalizedB;
Npp32f nY = 0.212671F * nNormalizedR + 0.71516F * nNormalizedG + 0.072169F * nNormalizedB;
Npp32f nZ = 0.019334F * nNormalizedR + 0.119193F * nNormalizedG + 0.950227F * nNormalizedB;
Npp32f nL = cbtrf(nY);
Npp32f nA;
Npp32f nB;
Npp32f nfX = nX * 1.052128F; // / nCIE_LAB_D65_xn;
Npp32f nfY = nY;
Npp32f nfZ = nZ * 0.918482F; // / nCIE_LAB_D65_zn;
nfY = nL - 16.0F;
nL = 116.0F * nL - 16.0F;
nA = cbtrf(nfX) - 16.0F;
nA = 500.0F * (nA - nfY);
nB = cbtrf(nfZ) - 16.0F;
nB = 200.0F * (nfY - nB);
// Now scale Lab range
nL = nL * 255.0F * 0.01F; // / 100.0F
nA = nA + 128.0F;
nB = nB + 128.0F;
L = (Npp8u)nL;
a = (Npp8u)nA;
b = (Npp8u)nB;

```

- **NppStatus nppiBGRToLab_8u_C3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)

3 channel 8-bit unsigned packed BGR to 3 channel 8-bit unsigned packed Lab color conversion.

LabToBGR

Lab to BGR color conversion.

This is how NPP converts Lab to gamma corrected BGR or RGB using the CIE Lab D65 white point with a Y luminance of 1.0. The code uses `powf()` the 32 bit floating point power math function.

```
// use CIE Lab chromaticity coordinates
#define nCIE_LAB_D65_xn 0.950455F
#define nCIE_LAB_D65_yn 1.0F
#define nCIE_LAB_D65_zn 1.088753F
// First convert Lab back to original range then to CIE XYZ
Npp32f nL = (Npp32f)L * 100.0F * 0.003921569F; // / 255.0F
Npp32f nA = (Npp32f)a - 128.0F;
Npp32f nB = (Npp32f)b - 128.0F;
Npp32f nP = (nL + 16.0F) * 0.008621F; // / 116.0F
Npp32f nNormalizedY = nP * nP * nP; // powf(nP, 3.0F);
Npp32f nNormalizedX = nCIE_LAB_D65_xn * powf((nP + nA * 0.002F), 3.0F); // / 500.0F
Npp32f nNormalizedZ = nCIE_LAB_D65_zn * powf((nP - nB * 0.005F), 3.0F); // / 200.0F
Npp32f nR = 3.240479F * nNormalizedX - 1.53715F * nNormalizedY - 0.498535F * nNormalizedZ;
if (nR > 1.0F)
    nR = 1.0F;
Npp32f nG = -0.969256F * nNormalizedX + 1.875991F * nNormalizedY + 0.041556F * nNormalizedZ;
if (nG > 1.0F)
    nG = 1.0F;
nB = 0.055648F * nNormalizedX - 0.204043F * nNormalizedY + 1.057311F * nNormalizedZ;
if (nB > 1.0F)
    nB = 1.0F;
R = (Npp8u)(nR * 255.0F);
G = (Npp8u)(nG * 255.0F);
B = (Npp8u)(nB * 255.0F);
```

- [NppStatus nppiLabToBGR_8u_C3R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [Npp8u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)

3 channel 8-bit unsigned packed Lab to 3 channel 8-bit unsigned packed BGR color conversion.

RGBToYCC

RGB to PhotoYCC color conversion.

This is how NPP converts gamma corrected BGR or RGB to PhotoYCC. The computed Y, C1, C2 values are then quantized and converted to fit in the range [0..1] before expanding to 8 bits.

```
Npp32f nNormalizedR = (Npp32f)R * 0.003921569F; // / 255.0F
Npp32f nNormalizedG = (Npp32f)G * 0.003921569F;
Npp32f nNormalizedB = (Npp32f)B * 0.003921569F;
Npp32f nY = 0.299F * nNormalizedR + 0.587F * nNormalizedG + 0.114F * nNormalizedB;
Npp32f nC1 = nNormalizedB - nY;
nC1 = 111.4F * 0.003921569F * nC1 + 156.0F * 0.003921569F;
Npp32f nC2 = nNormalizedR - nY;
nC2 = 135.64F * 0.003921569F * nC2 + 137.0F * 0.003921569F;
nY = 1.0F * 0.713267F * nY; // / 1.402F
Y = (Npp8u)(nY * 255.0F);
C1 = (Npp8u)(nC1 * 255.0F);
C2 = (Npp8u)(nC2 * 255.0F);
```

- `NppStatus nppiRGBToYCC_8u_C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
3 channel 8-bit unsigned packed RGB to 3 channel 8-bit unsigned packed YCC color conversion.
- `NppStatus nppiRGBToYCC_8u_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
4 channel 8-bit unsigned packed RGB with alpha to 4 channel 8-bit unsigned packed YCC with alpha color conversion.

YCCToRGB

PhotoYCC to RGB color conversion.

This is how NPP converts PhotoYCC to gamma corrected RGB or BGR.

```
Npp32f nNormalizedY = ((Npp32f)Y * 0.003921569F) * 1.3584F; // / 255.0F
Npp32f nNormalizedC1 = (((Npp32f)C1 * 0.003921569F) - 156.0F * 0.003921569F) * 2.2179F;
Npp32f nNormalizedC2 = (((Npp32f)C2 * 0.003921569F) - 137.0F * 0.003921569F) * 1.8215F;
Npp32f nR = nNormalizedY + nNormalizedC2;
if (nR > 1.0F)
    nR = 1.0F;
Npp32f nG = nNormalizedY - 0.194F * nNormalizedC1 - 0.509F * nNormalizedC2;
if (nG > 1.0F)
    nG = 1.0F;
Npp32f nB = nNormalizedY + nNormalizedC1;
if (nB > 1.0F)
    nB = 1.0F;
R = (Npp8u) (nR * 255.0F);
G = (Npp8u) (nG * 255.0F);
B = (Npp8u) (nB * 255.0F);
```

- `NppStatus nppiYCCToRGB_8u_C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
3 channel 8-bit unsigned packed YCC to 3 channel 8-bit unsigned packed RGB color conversion.
- `NppStatus nppiYCCToRGB_8u_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
4 channel 8-bit unsigned packed YCC with alpha to 4 channel 8-bit unsigned packed RGB with alpha color conversion.

RGBToHLS

RGB to HLS color conversion.

This is how NPP converts gamma corrected RGB or BGR to HLS. This code uses the `fmaxf()` and `fminf()` 32 bit floating point math functions.

```
Npp32f nNormalizedR = (Npp32f)R * 0.003921569F; // / 255.0F
Npp32f nNormalizedG = (Npp32f)G * 0.003921569F;
Npp32f nNormalizedB = (Npp32f)B * 0.003921569F;
Npp32f nS;
Npp32f nH;
// Lightness
Npp32f nMax = fmaxf(nNormalizedR, nNormalizedG);
```

```

        nMax = fmaxf(nMax, nNormalizedB);
Npp32f nMin = fminf(nNormalizedR, nNormalizedG);
        nMin = fminf(nMin, nNormalizedB);
Npp32f nL = (nMax + nMin) * 0.5F;
Npp32f nDivisor = nMax - nMin;
// Saturation
if (nDivisor == 0.0F) // achromatics case
{
    nS = 0.0F;
    nH = 0.0F;
}
else // chromatics case
{
    if (nL > 0.5F)
        nS = nDivisor / (1.0F - (nMax + nMin - 1.0F));
    else
        nS = nDivisor / (nMax + nMin);
}
// Hue
Npp32f nCr = (nMax - nNormalizedR) / nDivisor;
Npp32f nCg = (nMax - nNormalizedG) / nDivisor;
Npp32f nCb = (nMax - nNormalizedB) / nDivisor;
if (nNormalizedR == nMax)
    nH = nCb - nCg;
else if (nNormalizedG == nMax)
    nH = 2.0F + nCr - nCb;
else if (nNormalizedB == nMax)
    nH = 4.0F + nCg - nCr;
nH = nH * 0.166667F; // / 6.0F
if (nH < 0.0F)
    nH = nH + 1.0F;
H = (Npp8u) (nH * 255.0F);
L = (Npp8u) (nL * 255.0F);
S = (Npp8u) (nS * 255.0F);

```

- **NppStatus nppiRGBToHLS_8u_C3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
3 channel 8-bit unsigned packed RGB to 3 channel 8-bit unsigned packed HLS color conversion.
- **NppStatus nppiRGBToHLS_8u_AC4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 8-bit unsigned packed RGB with alpha to 4 channel 8-bit unsigned packed HLS with alpha color conversion.

HLSToRGB

HLS to RGB color conversion.

This is how NPP converts HLS to gamma corrected RGB or BGR.

```

Npp32f nNormalizedH = (Npp32f)H * 0.003921569F; // / 255.0F
Npp32f nNormalizedL = (Npp32f)L * 0.003921569F;
Npp32f nNormalizedS = (Npp32f)S * 0.003921569F;
Npp32f nM1;
Npp32f nM2;
Npp32f nR;
Npp32f nG;
Npp32f nB;
Npp32f nh = 0.0F;
if (nNormalizedL <= 0.5F)
    nM2 = nNormalizedL * (1.0F + nNormalizedS);

```

```

else
    nM2 = nNormalizedL + nNormalizedS - nNormalizedL * nNormalizedS;
nM1 = 2.0F * nNormalizedL - nM2;
if (nNormalizedS == 0.0F)
    nR = nG = nB = nNormalizedL;
else
    {
        nh = nNormalizedH + 0.3333F;
        if (nh > 1.0F)
            nh -= 1.0F;
    }
Npp32f nMDiff = nM2 - nM1;
if (0.6667F < nh)
    nR = nM1;
else
    {
        if (nh < 0.1667F)
            nR = (nM1 + nMDiff * nh * 6.0F); // / 0.1667F
        else if (nh < 0.5F)
            nR = nM2;
        else
            nR = nM1 + nMDiff * ( 0.6667F - nh ) * 6.0F; // / 0.1667F
    }
if (nR > 1.0F)
    nR = 1.0F;
nh = nNormalizedH;
if (0.6667F < nh)
    nG = nM1;
else
    {
        if (nh < 0.1667F)
            nG = (nM1 + nMDiff * nh * 6.0F); // / 0.1667F
        else if (nh < 0.5F)
            nG = nM2;
        else
            nG = nM1 + nMDiff * (0.6667F - nh ) * 6.0F; // / 0.1667F
    }
if (nG > 1.0F)
    nG = 1.0F;
nh = nNormalizedH - 0.3333F;
if (nh < 0.0F)
    nh += 1.0F;
if (0.6667F < nh)
    nB = nM1;
else
    {
        if (nh < 0.1667F)
            nB = (nM1 + nMDiff * nh * 6.0F); // / 0.1667F
        else if (nh < 0.5F)
            nB = nM2;
        else
            nB = nM1 + nMDiff * (0.6667F - nh ) * 6.0F; // / 0.1667F
    }
if (nB > 1.0F)
    nB = 1.0F;
R = (Npp8u) (nR * 255.0F);
G = (Npp8u) (nG * 255.0F);
B = (Npp8u) (nB * 255.0F);

```

- **NppStatus nppiHLSToRGB_8u_C3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
3 channel 8-bit unsigned packed HLS to 3 channel 8-bit unsigned packed RGB color conversion.
- **NppStatus nppiHLSToRGB_8u_AC4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)

4 channel 8-bit unsigned packed HLS with alpha to 4 channel 8-bit unsigned packed RGB with alpha color conversion.

BGRToHLS

BGR to HLS color conversion.

- **NppStatus nppiBGRToHLS_8u_AC4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 8-bit unsigned packed BGR with alpha to 4 channel 8-bit unsigned packed HLS with alpha color conversion.
- **NppStatus nppiBGRToHLS_8u_C3P3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst[3], int nDstStep, **NppiSize** oSizeROI)
3 channel 8-bit unsigned packed BGR to 3 channel 8-bit unsigned planar HLS color conversion.
- **NppStatus nppiBGRToHLS_8u_AC4P4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst[4], int nDstStep, **NppiSize** oSizeROI)
4 channel 8-bit unsigned packed BGR with alpha to 4 channel 8-bit unsigned planar HLS with alpha color conversion.
- **NppStatus nppiBGRToHLS_8u_P3C3R** (const **Npp8u** *const pSrc[3], int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
3 channel 8-bit unsigned planar BGR to 3 channel 8-bit unsigned packed HLS color conversion.
- **NppStatus nppiBGRToHLS_8u_AP4C4R** (const **Npp8u** *const pSrc[4], int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 8-bit unsigned planar BGR with alpha to 4 channel 8-bit unsigned packed HLS with alpha color conversion.
- **NppStatus nppiBGRToHLS_8u_P3R** (const **Npp8u** *const pSrc[3], int nSrcStep, **Npp8u** *pDst[3], int nDstStep, **NppiSize** oSizeROI)
3 channel 8-bit unsigned planar BGR to 3 channel 8-bit unsigned planar HLS color conversion.
- **NppStatus nppiBGRToHLS_8u_AP4R** (const **Npp8u** *const pSrc[4], int nSrcStep, **Npp8u** *pDst[4], int nDstStep, **NppiSize** oSizeROI)
4 channel 8-bit unsigned planar BGR with alpha to 4 channel 8-bit unsigned planar HLS with alpha color conversion.

HLSToBGR

HLS to BGR color conversion.

- **NppStatus nppiHLSToBGR_8u_C3P3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst[3], int nDstStep, **NppiSize** oSizeROI)
3 channel 8-bit unsigned packed HLS to 3 channel 8-bit unsigned planar BGR color conversion.
- **NppStatus nppiHLSToBGR_8u_AC4P4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst[4], int nDstStep, **NppiSize** oSizeROI)

4 channel 8-bit unsigned packed HLS with alpha to 4 channel 8-bit unsigned planar BGR with alpha color conversion.

- `NppStatus nppiHLSToBGR_8u_P3R` (const `Npp8u` *const pSrc[3], int nSrcStep, `Npp8u` *pDst[3], int nDstStep, `NppiSize` oSizeROI)

3 channel 8-bit unsigned planar HLS to 3 channel 8-bit unsigned planar BGR color conversion.

- `NppStatus nppiHLSToBGR_8u_AP4R` (const `Npp8u` *const pSrc[4], int nSrcStep, `Npp8u` *pDst[4], int nDstStep, `NppiSize` oSizeROI)

4 channel 8-bit unsigned planar HLS with alpha to 4 channel 8-bit unsigned planar BGR with alpha color conversion.

- `NppStatus nppiHLSToBGR_8u_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)

4 channel 8-bit unsigned packed HLS with alpha to 4 channel 8-bit unsigned packed BGR with alpha color conversion.

- `NppStatus nppiHLSToBGR_8u_P3C3R` (const `Npp8u` *const pSrc[3], int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)

3 channel 8-bit unsigned planar HLS to 3 channel 8-bit unsigned packed BGR color conversion.

- `NppStatus nppiHLSToBGR_8u_AP4C4R` (const `Npp8u` *const pSrc[4], int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)

4 channel 8-bit unsigned planar HLS with alpha to 4 channel 8-bit unsigned packed BGR with alpha color conversion.

RGBToHSV

RGB to HSV color conversion.

This is how NPP converts gamma corrected RGB or BGR to HSV. This code uses the `fmaxf()` and `fminf()` 32 bit floating point math functions.

```
Npp32f nNormalizedR = (Npp32f)R * 0.003921569F; // / 255.0F
Npp32f nNormalizedG = (Npp32f)G * 0.003921569F;
Npp32f nNormalizedB = (Npp32f)B * 0.003921569F;
Npp32f nS;
Npp32f nH;
// Value
Npp32f nV = fmaxf(nNormalizedR, nNormalizedG);
nV = fmaxf(nV, nNormalizedB);
// Saturation
Npp32f nTemp = fminf(nNormalizedR, nNormalizedG);
nTemp = fminf(nTemp, nNormalizedB);
Npp32f nDivisor = nV - nTemp;
if (nV == 0.0F) // achromatics case
{
    nS = 0.0F;
    nH = 0.0F;
}
else // chromatics case
    nS = nDivisor / nV;
// Hue:
Npp32f nCr = (nV - nNormalizedR) / nDivisor;
Npp32f nCg = (nV - nNormalizedG) / nDivisor;
Npp32f nCb = (nV - nNormalizedB) / nDivisor;
```

```

if (nNormalizedR == nV)
    nH = nCb - nCg;
else if (nNormalizedG == nV)
    nH = 2.0F + nCr - nCb;
else if (nNormalizedB == nV)
    nH = 4.0F + nCg - nCr;
nH = nH * 0.166667F; // / 6.0F
if (nH < 0.0F)
    nH = nH + 1.0F;
H = (Npp8u) (nH * 255.0F);
S = (Npp8u) (nS * 255.0F);
V = (Npp8u) (nV * 255.0F);

```

- **NppStatus nppiRGBToHSV_8u_C3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
3 channel 8-bit unsigned packed RGB to 3 channel 8-bit unsigned packed HSV color conversion.
- **NppStatus nppiRGBToHSV_8u_AC4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 8-bit unsigned packed RGB with alpha to 4 channel 8-bit unsigned packed HSV with alpha color conversion.

HSVToRGB

HSV to RGB color conversion.

This is how NPP converts HSV to gamma corrected RGB or BGR. This code uses the floorf() 32 bit floating point math function.

```

Npp32f nNormalizedH = (Npp32f)H * 0.003921569F; // / 255.0F
Npp32f nNormalizedS = (Npp32f)S * 0.003921569F;
Npp32f nNormalizedV = (Npp32f)V * 0.003921569F;
Npp32f nR;
Npp32f nG;
Npp32f nB;
if (nNormalizedS == 0.0F)
{
    nR = nG = nB = nNormalizedV;
}
else
{
    if (nNormalizedH == 1.0F)
        nNormalizedH = 0.0F;
    else
        nNormalizedH = nNormalizedH * 6.0F; // / 0.1667F
}
Npp32f nI = floorf(nNormalizedH);
Npp32f nF = nNormalizedH - nI;
Npp32f nM = nNormalizedV * (1.0F - nNormalizedS);
Npp32f nN = nNormalizedV * (1.0F - nNormalizedS * nF);
Npp32f nK = nNormalizedV * (1.0F - nNormalizedS * (1.0F - nF));
if (nI == 0.0F)
    { nR = nNormalizedV; nG = nK; nB = nM; }
else if (nI == 1.0F)
    { nR = nN; nG = nNormalizedV; nB = nM; }
else if (nI == 2.0F)
    { nR = nM; nG = nNormalizedV; nB = nK; }
else if (nI == 3.0F)
    { nR = nM; nG = nN; nB = nNormalizedV; }
else if (nI == 4.0F)
    { nR = nK; nG = nM; nB = nNormalizedV; }

```

```

else if (nI == 5.0F)
    { nR = nNormalizedV; nG = nM; nB = nN; }
R = (Npp8u) (nR * 255.0F);
G = (Npp8u) (nG * 255.0F);
B = (Npp8u) (nB * 255.0F);

```

- **NppStatus nppiHSVToRGB_8u_C3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
3 channel 8-bit unsigned packed HSV to 3 channel 8-bit unsigned packed RGB color conversion.
- **NppStatus nppiHSVToRGB_8u_AC4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 8-bit unsigned packed HSV with alpha to 4 channel 8-bit unsigned packed RGB with alpha color conversion.

RGBToGray

RGB to CCIR601 Gray conversion.

Here is how NPP converts gamma corrected RGB to CCIR601 Gray.

```
nGray = 0.299F * R + 0.587F * G + 0.114F * B;
```

- **NppStatus nppiRGBToGray_8u_C3C1R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
3 channel 8-bit unsigned packed RGB to 1 channel 8-bit unsigned packed Gray conversion.
- **NppStatus nppiRGBToGray_8u_AC4C1R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 8-bit unsigned packed RGB with alpha to 1 channel 8-bit unsigned packed Gray conversion.
- **NppStatus nppiRGBToGray_16u_C3C1R** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
3 channel 16-bit unsigned packed RGB to 1 channel 16-bit unsigned packed Gray conversion.
- **NppStatus nppiRGBToGray_16u_AC4C1R** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 16-bit unsigned packed RGB with alpha to 1 channel 16-bit unsigned packed Gray conversion.
- **NppStatus nppiRGBToGray_16s_C3C1R** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI)
3 channel 16-bit signed packed RGB to 1 channel 16-bit signed packed Gray conversion.
- **NppStatus nppiRGBToGray_16s_AC4C1R** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 16-bit signed packed RGB with alpha to 1 channel 16-bit signed packed Gray conversion.
- **NppStatus nppiRGBToGray_32f_C3C1R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
3 channel 32-bit floating point packed RGB to 1 channel 32-bit floating point packed Gray conversion.

- `NppStatus nppiRGBToGray_32f_AC4C1R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
4 channel 32-bit floating point packed RGB with alpha to 1 channel 32-bit floating point packed Gray conversion.

ColorToGray

RGB Color to Gray conversion using user supplied conversion coefficients.

Here is how NPP converts gamma corrected RGB Color to Gray using user supplied conversion coefficients.

```
nGray = aCoeffs[0] * R + aCoeffs[1] * G + aCoeffs[2] * B;
```

- `NppStatus nppiColorToGray_8u_C3C1R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f aCoeffs[3]`)
3 channel 8-bit unsigned packed RGB to 1 channel 8-bit unsigned packed Gray conversion.
- `NppStatus nppiColorToGray_8u_AC4C1R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f aCoeffs[3]`)
4 channel 8-bit unsigned packed RGB with alpha to 1 channel 8-bit unsigned packed Gray conversion.
- `NppStatus nppiColorToGray_16u_C3C1R` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f aCoeffs[3]`)
3 channel 16-bit unsigned packed RGB to 1 channel 16-bit unsigned packed Gray conversion.
- `NppStatus nppiColorToGray_16u_AC4C1R` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f aCoeffs[3]`)
4 channel 16-bit unsigned packed RGB with alpha to 1 channel 16-bit unsigned packed Gray conversion.
- `NppStatus nppiColorToGray_16s_C3C1R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f aCoeffs[3]`)
3 channel 16-bit signed packed RGB to 1 channel 16-bit signed packed Gray conversion.
- `NppStatus nppiColorToGray_16s_AC4C1R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f aCoeffs[3]`)
4 channel 16-bit signed packed RGB with alpha to 1 channel 16-bit signed packed Gray conversion.
- `NppStatus nppiColorToGray_32f_C3C1R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f aCoeffs[3]`)
3 channel 32-bit floating point packed RGB to 1 channel 32-bit floating point packed Gray conversion.
- `NppStatus nppiColorToGray_32f_AC4C1R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f aCoeffs[3]`)
4 channel 32-bit floating point packed RGB with alpha to 1 channel 32-bit floating point packed Gray conversion.

7.44.1 Detailed Description

Routines for converting between various image color models.

7.44.2 Function Documentation

7.44.2.1 `NppStatus nppiBGRToCbYCr422_709HDTV_8u_AC4C2R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

4 channel 8-bit unsigned packed BGR with alpha to 2 channel 8-bit unsigned packed CbYCr422_709HDTV color conversion.

images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.2 `NppStatus nppiBGRToCbYCr422_709HDTV_8u_C3C2R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned packed BGR to 2 channel 8-bit unsigned packed CbYCr422_709HDTV color conversion.

images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.3 `NppStatus nppiBGRToCbYCr422_8u_AC4C2R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

4 channel 8-bit unsigned packed BGR with alpha to 2 channel 8-bit unsigned packed CbYCr422 color conversion.

images.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.4 **NppStatus nppiBGRToHLS_8u_AC4P4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[4], int nDstStep, NppiSize oSizeROI)**

4 channel 8-bit unsigned packed BGR with alpha to 4 channel 8-bit unsigned planar HLS with alpha color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.5 **NppStatus nppiBGRToHLS_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)**

4 channel 8-bit unsigned packed BGR with alpha to 4 channel 8-bit unsigned packed HLS with alpha color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.6 NppStatus nppiBGRToHLS_8u_AP4C4R (const Npp8u *const pSrc[4], int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 8-bit unsigned planar BGR with alpha to 4 channel 8-bit unsigned packed HLS with alpha color conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.7 NppStatus nppiBGRToHLS_8u_AP4R (const Npp8u *const pSrc[4], int nSrcStep, Npp8u * pDst[4], int nDstStep, NppiSize oSizeROI)

4 channel 8-bit unsigned planar BGR with alpha to 4 channel 8-bit unsigned planar HLS with alpha color conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.8 NppStatus nppiBGRToHLS_8u_C3P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned packed BGR to 3 channel 8-bit unsigned planar HLS color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.9 **NppStatus nppiBGRToHLS_8u_P3C3R** (const Npp8u *const *pSrc*[3], int *nSrcStep*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

3 channel 8-bit unsigned planar BGR to 3 channel 8-bit unsigned packed HLS color conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.10 **NppStatus nppiBGRToHLS_8u_P3R** (const Npp8u *const *pSrc*[3], int *nSrcStep*, Npp8u * *pDst*[3], int *nDstStep*, NppiSize *oSizeROI*)

3 channel 8-bit unsigned planar BGR to 3 channel 8-bit unsigned planar HLS color conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.11 **NppStatus nppiBGRToLab_8u_C3R** (const Npp8u * *pSrc*, int *nSrcStep*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

3 channel 8-bit unsigned packed BGR to 3 channel 8-bit unsigned packed Lab color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.12 NppStatus nppiBGRToYCbCr411_8u_AC4P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)

4 channel 8-bit unsigned packed BGR with alpha to 3 channel 8-bit unsigned planar YCbCr411 color conversion.

images.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Planar-Image Pointer Array.

rDstStep Destination-Planar-Image Line Step Array.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.13 NppStatus nppiBGRToYCbCr411_8u_C3P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)

3 channel 8-bit unsigned packed BGR to 3 channel 8-bit unsigned planar YCbCr411 color conversion.

images.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Planar-Image Pointer Array.

rDstStep Destination-Planar-Image Line Step Array.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.14 NppStatus nppiBGRToYCbCr420_709CSC_8u_AC4P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)

4 channel 8-bit unsigned packed BGR with alpha to 3 channel 8-bit unsigned planar YCbCr420_709CSC color conversion.

images.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.15 **NppStatus nppiBGRToYCbCr420_709CSC_8u_C3P3R** (const Npp8u * *pSrc*, int *nSrcStep*, Npp8u * *pDst*[3], int *rDstStep*[3], NppiSize *oSizeROI*)

3 channel 8-bit unsigned packed BGR to 3 channel 8-bit unsigned planar YCbCr420_709CSC color conversion.

images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.16 **NppStatus nppiBGRToYCbCr420_709HDTV_8u_AC4P3R** (const Npp8u * *pSrc*, int *nSrcStep*, Npp8u * *pDst*[3], int *rDstStep*[3], NppiSize *oSizeROI*)

4 channel 8-bit unsigned packed BGR with alpha to 3 channel 8-bit unsigned planar YCbCr420_709HDTV color conversion.

images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.17 NppStatus nppiBGRToYCbCr420_8u_AC4P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)

4 channel 8-bit unsigned packed BGR with alpha to 3 channel 8-bit unsigned planar YCbCr420 color conversion.

images.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Planar-Image Pointer Array.

rDstStep Destination-Planar-Image Line Step Array.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.18 NppStatus nppiBGRToYCbCr420_8u_C3P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)

3 channel 8-bit unsigned packed BGR to 3 channel 8-bit unsigned planar YCbCr420 color conversion.

images.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Planar-Image Pointer Array.

rDstStep Destination-Planar-Image Line Step Array.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.19 NppStatus nppiBGRToYCbCr422_8u_AC4C2R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 8-bit unsigned packed BGR with alpha to 2 channel 8-bit unsigned packed YCrCb422 color conversion.

images.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.20 `NppStatus nppiBGRToYCbCr422_8u_AC4P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)`

4 channel 8-bit unsigned packed BGR with alpha to 3 channel 8-bit unsigned planar YCbCr422 color conversion.

images.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Planar-Image Pointer Array.

rDstStep Destination-Planar-Image Line Step Array.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.21 `NppStatus nppiBGRToYCbCr422_8u_C3C2R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned packed BGR to 2 channel 8-bit unsigned packed YCrCb422 color conversion.

images.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.22 NppStatus nppiBGRToYCbCr422_8u_C3P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)

3 channel 8-bit unsigned packed BGR to 3 channel 8-bit unsigned planar YCbCr422 color conversion. images.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Planar-Image Pointer Array.
- rDstStep* Destination-Planar-Image Line Step Array.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.23 NppStatus nppiBGRToYCrCb420_709CSC_8u_AC4P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)

4 channel 8-bit unsigned packed BGR with alpha to 3 channel 8-bit unsigned planar YCrCb420_709CSC color conversion. images.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Planar-Image Pointer Array.
- rDstStep* Destination-Planar-Image Line Step Array.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.24 NppStatus nppiBGRToYCrCb420_709CSC_8u_C3P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)

3 channel 8-bit unsigned packed BGR to 3 channel 8-bit unsigned planar YCrCb420_709CSC color conversion. images.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.

pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.25 NppStatus nppiBGRToYCrCb420_8u_AC4P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)

4 channel 8-bit unsigned packed BGR with alpha to 3 channel 8-bit unsigned planar YCrCb420 color conversion.

images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.26 NppStatus nppiBGRToYCrCb420_8u_C3P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)

3 channel 8-bit unsigned packed BGR to 3 channel 8-bit unsigned planar YCrCb420 color conversion.

images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.27 `NppStatus nppiBGRToYUV420_8u_AC4P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)`

4 channel 8-bit unsigned packed BGR with alpha to 3 channel 8-bit unsigned planar YUV420 color conversion.

images.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Planar-Image Pointer Array.

rDstStep Destination-Planar-Image Line Step Array.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.28 `NppStatus nppiCbYCr422ToBGR_709HDTV_8u_C2C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

2 channel 8-bit unsigned packed CbYCr422 to 3 channel 8-bit unsigned packed BGR_709HDTV color conversion.

images.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.29 `NppStatus nppiCbYCr422ToBGR_709HDTV_8u_C2C4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, Npp8u nAval)`

2 channel 8-bit unsigned packed CbYCr422 to 4 channel 8-bit unsigned packed BGR_709HDTV color conversion with constant alpha.

images.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nAval 8-bit unsigned alpha constant.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.30 `NppStatus nppiCbYCr422ToBGR_8u_C2C4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, Npp8u nAval)`

2 channel 8-bit unsigned packed CbYCr422 to 4 channel 8-bit unsigned packed BGR color conversion with alpha.

images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nAval 8-bit unsigned alpha constant.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.31 `NppStatus nppiCbYCr422ToRGB_8u_C2C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

2 channel 8-bit unsigned packed CbYCrC22 to 3 channel 8-bit unsigned packed RGB color conversion.

images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.32 `NppStatus nppiColorToGray_16s_AC4C1R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f aCoeffs[3])`

4 channel 16-bit signed packed RGB with alpha to 1 channel 16-bit signed packed Gray conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aCoeffs fixed size array of constant floating point conversion coefficient values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.33 `NppStatus nppiColorToGray_16s_C3C1R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f aCoeffs[3])`

3 channel 16-bit signed packed RGB to 1 channel 16-bit signed packed Gray conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aCoeffs fixed size array of constant floating point conversion coefficient values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.34 `NppStatus nppiColorToGray_16u_AC4C1R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f aCoeffs[3])`

4 channel 16-bit unsigned packed RGB with alpha to 1 channel 16-bit unsigned packed Gray conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aCoeffs fixed size array of constant floating point conversion coefficient values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.35 `NppStatus nppiColorToGray_16u_C3C1R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f aCoeffs[3])`

3 channel 16-bit unsigned packed RGB to 1 channel 16-bit unsigned packed Gray conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aCoeffs fixed size array of constant floating point conversion coefficient values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.36 `NppStatus nppiColorToGray_32f_AC4C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f aCoeffs[3])`

4 channel 32-bit floating point packed RGB with alpha to 1 channel 32-bit floating point packed Gray conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aCoeffs fixed size array of constant floating point conversion coefficient values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.37 `NppStatus nppiColorToGray_32f_C3C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f aCoeffs[3])`

3 channel 32-bit floating point packed RGB to 1 channel 32-bit floating point packed Gray conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aCoeffs fixed size array of constant floating point conversion coefficient values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.38 `NppStatus nppiColorToGray_8u_AC4C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f aCoeffs[3])`

4 channel 8-bit unsigned packed RGB with alpha to 1 channel 8-bit unsigned packed Gray conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aCoeffs fixed size array of constant floating point conversion coefficient values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.39 `NppStatus nppiColorToGray_8u_C3C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f aCoeffs[3])`

3 channel 8-bit unsigned packed RGB to 1 channel 8-bit unsigned packed Gray conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aCoeffs fixed size array of constant floating point conversion coefficient values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.40 `NppStatus nppiHLSToBGR_8u_AC4P4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[4], int nDstStep, NppiSize oSizeROI)`

4 channel 8-bit unsigned packed HLS with alpha to 4 channel 8-bit unsigned planar BGR with alpha color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.41 `NppStatus nppiHLSToBGR_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

4 channel 8-bit unsigned packed HLS with alpha to 4 channel 8-bit unsigned packed BGR with alpha color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.42 `NppStatus nppiHLSToBGR_8u_AP4C4R (const Npp8u * const pSrc[4], int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

4 channel 8-bit unsigned planar HLS with alpha to 4 channel 8-bit unsigned packed BGR with alpha color conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.43 NppStatus nppiHLSToBGR_8u_AP4R (const Npp8u *const pSrc[4], int nSrcStep, Npp8u *pDst[4], int nDstStep, NppiSize oSizeROI)

4 channel 8-bit unsigned planar HLS with alpha to 4 channel 8-bit unsigned planar BGR with alpha color conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.44 NppStatus nppiHLSToBGR_8u_C3P3R (const Npp8u *pSrc, int nSrcStep, Npp8u *pDst[3], int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned packed HLS to 3 channel 8-bit unsigned planar BGR color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.45 NppStatus nppiHLSToBGR_8u_P3C3R (const Npp8u *const pSrc[3], int nSrcStep, Npp8u *pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned planar HLS to 3 channel 8-bit unsigned packed BGR color conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.46 `NppStatus nppiHLSToBGR_8u_P3R (const Npp8u *const pSrc[3], int nSrcStep, Npp8u *pDst[3], int nDstStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned planar HLS to 3 channel 8-bit unsigned planar BGR color conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.47 `NppStatus nppiHLSToRGB_8u_AC4R (const Npp8u *pSrc, int nSrcStep, Npp8u *pDst, int nDstStep, NppiSize oSizeROI)`

4 channel 8-bit unsigned packed HLS with alpha to 4 channel 8-bit unsigned packed RGB with alpha color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.48 `NppStatus nppiHLSToRGB_8u_C3R (const Npp8u *pSrc, int nSrcStep, Npp8u *pDst, int nDstStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned packed HLS to 3 channel 8-bit unsigned packed RGB color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.49 NppStatus nppiHSVToRGB_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 8-bit unsigned packed HSV with alpha to 4 channel 8-bit unsigned packed RGB with alpha color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.50 NppStatus nppiHSVToRGB_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned packed HSV to 3 channel 8-bit unsigned packed RGB color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.51 NppStatus nppiLabToBGR_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned packed Lab to 3 channel 8-bit unsigned packed BGR color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.52 NppStatus nppiLUVToRGB_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 8-bit unsigned packed LUV with alpha to 4 channel 8-bit unsigned packed RGB with alpha color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.53 NppStatus nppiLUVToRGB_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned packed LUV to 3 channel 8-bit unsigned packed RGB color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.54 NppStatus nppiRGBToCbYCr422_8u_C3C2R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned packed RGB to 2 channel 8-bit unsigned packed CbYCr422 color conversion. images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.55 NppStatus nppiRGBToCbYCr422Gamma_8u_C3C2R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned packed RGB first gets forward gamma corrected then converted to 2 channel 8-bit unsigned packed CbYCr422 color conversion.

images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.56 NppStatus nppiRGBToGray_16s_AC4C1R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 16-bit signed packed RGB with alpha to 1 channel 16-bit signed packed Gray conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.57 NppStatus nppiRGBToGray_16s_C3C1R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 16-bit signed packed RGB to 1 channel 16-bit signed packed Gray conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.58 NppStatus nppiRGBToGray_16u_AC4C1R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 16-bit unsigned packed RGB with alpha to 1 channel 16-bit unsigned packed Gray conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.59 NppStatus nppiRGBToGray_16u_C3C1R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 16-bit unsigned packed RGB to 1 channel 16-bit unsigned packed Gray conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.60 NppStatus nppiRGBToGray_32f_AC4C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 32-bit floating point packed RGB with alpha to 1 channel 32-bit floating point packed Gray conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.61 `NppStatus nppiRGBToGray_32f_C3C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

3 channel 32-bit floating point packed RGB to 1 channel 32-bit floating point packed Gray conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.62 `NppStatus nppiRGBToGray_8u_AC4C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

4 channel 8-bit unsigned packed RGB with alpha to 1 channel 8-bit unsigned packed Gray conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.63 `NppStatus nppiRGBToGray_8u_C3C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned packed RGB to 1 channel 8-bit unsigned packed Gray conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.64 NppStatus nppiRGBToHLS_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 8-bit unsigned packed RGB with alpha to 4 channel 8-bit unsigned packed HLS with alpha color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.65 NppStatus nppiRGBToHLS_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned packed RGB to 3 channel 8-bit unsigned packed HLS color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.66 NppStatus nppiRGBToHSV_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 8-bit unsigned packed RGB with alpha to 4 channel 8-bit unsigned packed HSV with alpha color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.67 NppStatus nppiRGBToHSV_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned packed RGB to 3 channel 8-bit unsigned packed HSV color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.68 NppStatus nppiRGBToLUV_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 8-bit unsigned packed RGB with alpha to 4 channel 8-bit unsigned packed LUV with alpha color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.69 NppStatus nppiRGBToLUV_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned packed RGB to 3 channel 8-bit unsigned packed LUV color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.70 NppStatus nppiRGBToXYZ_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 8-bit unsigned packed RGB with alpha to 4 channel 8-bit unsigned packed XYZ with alpha color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.71 NppStatus nppiRGBToXYZ_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned packed RGB to 3 channel 8-bit unsigned packed XYZ color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.72 NppStatus nppiRGBToYCbCr420_8u_C3P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)

3 channel 8-bit unsigned packed RGB to 3 channel 8-bit unsigned planar YCbCr420 color conversion. images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.73 `NppStatus nppiRGBToYCbCr422_8u_C3C2R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned packed RGB to 2 channel 8-bit unsigned packed YCbCr422 color conversion. images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.74 `NppStatus nppiRGBToYCbCr422_8u_C3P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)`

3 channel 8-bit unsigned packed RGB to 3 channel 8-bit unsigned planar YCbCr422 color conversion. images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.75 `NppStatus nppiRGBToYCbCr422_8u_P3C2R (const Npp8u *const pSrc[3], int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned planar RGB to 2 channel 8-bit unsigned packed YCbCr422 color conversion. images.

Parameters:

pSrc Source-Planar-Image Pointer Array.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.76 `NppStatus nppiRGBToYCbCr_8u_AC4P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int nDstStep, NppiSize oSizeROI)`

4 channel 8-bit unsigned packed RGB with alpha to 3 channel 8-bit unsigned planar YCbCr color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.77 `NppStatus nppiRGBToYCbCr_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

4 channel 8-bit unsigned packed RGB with alpha to 4 channel unsigned 8-bit packed YCbCr with alpha color conversion, not affecting alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.78 `NppStatus nppiRGBToYCbCr_8u_C3P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int nDstStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned packed RGB to 3 channel unsigned 8-bit planar YCbCr color conversion. images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.79 NppStatus nppiRGBToYCbCr_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned packed RGB to 3 channel unsigned 8-bit packed YCbCr color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.80 NppStatus nppiRGBToYCbCr_8u_P3R (const Npp8u *const pSrc[3], int nSrcStep, Npp8u * pDst[3], int nDstStep, NppiSize oSizeROI)

3 channel planar 8-bit unsigned RGB to 3 channel planar 8-bit YCbCr color conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.81 NppStatus nppiRGBToYCC_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 8-bit unsigned packed RGB with alpha to 4 channel 8-bit unsigned packed YCC with alpha color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.82 NppStatus nppiRGBToYCC_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned packed RGB to 3 channel 8-bit unsigned packed YCC color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.83 NppStatus nppiRGBToYCrCb420_8u_AC4P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)

4 channel 8-bit unsigned packed RGB with alpha to 3 channel 8-bit unsigned planar YCrCb420 color conversion.

images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.84 NppStatus nppiRGBToYCrCb422_8u_C3C2R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned packed RGB to 2 channel 8-bit unsigned packed YCrCb422 color conversion. images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.85 NppStatus nppiRGBToYCrCb422_8u_P3C2R (const Npp8u *const pSrc[3], int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned planar RGB to 2 channel 8-bit unsigned packed YCrCb422 color conversion. images.

Parameters:

pSrc Source-Planar-Image Pointer Array.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.86 NppStatus nppiRGBToYUV420_8u_C3P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)

3 channel 8-bit unsigned packed RGB to 3 channel 8-bit unsigned planar YUV420 color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.87 `NppStatus nppiRGBToYUV420_8u_P3R (const Npp8u *const pSrc[3], int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)`

3 channel 8-bit unsigned planar RGB to 3 channel 8-bit unsigned planar YUV420 color conversion. images.

Parameters:

pSrc Source-Planar-Image Pointer Array.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.88 `NppStatus nppiRGBToYUV422_8u_C3C2R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned packed RGB to 2 channel 8-bit unsigned packed YUV422 color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.89 `NppStatus nppiRGBToYUV422_8u_C3P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)`

3 channel 8-bit unsigned packed RGB to 3 channel 8-bit unsigned planar YUV422 color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.90 `NppStatus nppiRGBToYUV422_8u_P3R (const Npp8u *const pSrc[3], int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)`

3 channel 8-bit unsigned planar RGB to 3 channel 8-bit unsigned planar YUV422 color conversion. images.

Parameters:

pSrc Source-Planar-Image Pointer Array.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.91 `NppStatus nppiRGBToYUV_8u_AC4P4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[4], int nDstStep, NppiSize oSizeROI)`

4 channel 8-bit unsigned packed RGB with alpha to 4 channel 8-bit unsigned planar YUV color conversion with alpha. images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.92 `NppStatus nppiRGBToYUV_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

4 channel 8-bit unsigned packed RGB with alpha to 4 channel 8-bit unsigned packed YUV color conversion with alpha, not affecting alpha. images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.93 `NppStatus nppiRGBToYUV_8u_C3P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int nDstStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned packed RGB to 3 channel 8-bit unsigned planar YUV color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.94 `NppStatus nppiRGBToYUV_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned packed RGB to 3 channel 8-bit unsigned packed YUV color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.95 `NppStatus nppiRGBToYUV_8u_P3R (const Npp8u *const pSrc[3], int nSrcStep, Npp8u * pDst[3], int nDstStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned planar RGB to 3 channel 8-bit unsigned planar YUV color conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.

nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.96 NppStatus nppiXYZToRGB_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 8-bit unsigned packed XYZ with alpha to 4 channel 8-bit unsigned packed RGB with alpha color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.97 NppStatus nppiXYZToRGB_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned packed XYZ to 3 channel 8-bit unsigned packed RGB color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.98 `NppStatus nppiYCbCr411ToBGR_8u_P3C3R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned planar YCbCr411 to 3 channel 8-bit unsigned packed BGR color conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.99 `NppStatus nppiYCbCr411ToBGR_8u_P3C4R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, Npp8u nAval)`

3 channel 8-bit unsigned planar YCbCr411 to 4 channel 8-bit unsigned packed BGR color conversion with constant alpha.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nAval 8-bit unsigned alpha constant.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.100 `NppStatus nppiYCbCr420ToBGR_709CSC_8u_P3C3R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned planar YCbCr420 to 3 channel 8-bit unsigned packed BGR_709CSC color conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.101 NppStatus nppiYCbCr420ToBGR_709HDTV_8u_P3C4R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u *pDst, int nDstStep, NppiSize oSizeROI, Npp8u nAval)

3 channel 8-bit unsigned planar YCbCr420 to 4 channel 8-bit unsigned packed BGR_709HDTV color conversion with constant alpha.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nAval 8-bit unsigned alpha constant.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.102 NppStatus nppiYCbCr420ToBGR_8u_P3C3R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u *pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned planar YCbCr420 to 3 channel 8-bit unsigned packed BGR color conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.103 NppStatus nppiYCbCr420ToBGR_8u_P3C4R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u *pDst, int nDstStep, NppiSize oSizeROI, Npp8u nAval)

3 channel 8-bit unsigned planar YCbCr420 to 4 channel 8-bit unsigned packed BGR color conversion with constant alpha.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

nAval 8-bit unsigned alpha constant.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.104 NppStatus nppiYCbCr420ToRGB_8u_P3C3R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u *pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned planar YCbCr420 to 3 channel 8-bit unsigned packed RGB color conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.

rSrcStep Source-Planar-Image Line Step Array.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.105 NppStatus nppiYCbCr422ToBGR_8u_C2C3R (const Npp8u *pSrc, int nSrcStep, Npp8u *pDst, int nDstStep, NppiSize oSizeROI)

2 channel 8-bit unsigned packed YCrCb422 to 3 channel 8-bit unsigned packed BGR color conversion. images.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.106 NppStatus nppiYCbCr422ToBGR_8u_C2C4R (const Npp8u *pSrc, int nSrcStep, Npp8u *pDst, int nDstStep, NppiSize oSizeROI, Npp8u nAval)

2 channel 8-bit unsigned packed YCrCb422 to 4 channel 8-bit unsigned packed BGR color conversion with constant alpha.

images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nAval 8-bit unsigned alpha constant.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.107 NppStatus nppiYCbCr422ToBGR_8u_P3C3R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u *pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned planar YCbCr422 to 3 channel 8-bit unsigned packed BGR color conversion. images.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.108 NppStatus nppiYCbCr422ToRGB_8u_C2C3R (const Npp8u *pSrc, int nSrcStep, Npp8u *pDst, int nDstStep, NppiSize oSizeROI)

2 channel 8-bit unsigned packed YCbCr422 to 3 channel 8-bit unsigned packed RGB color conversion. images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.109 NppStatus nppiYCbCr422ToRGB_8u_C2P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int nDstStep, NppiSize oSizeROI)

2 channel 8-bit unsigned packed YCbCr422 to 3 channel 8-bit unsigned planar RGB color conversion. images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.110 NppStatus nppiYCbCr422ToRGB_8u_P3C3R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned planar YCbCr422 to 3 channel 8-bit unsigned packed RGB color conversion. images.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.111 NppStatus nppiYCbCrToBGR_709CSC_8u_P3C3R (const Npp8u *const pSrc[3], int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned planar YCbCr to 3 channel 8-bit unsigned packed BGR_709CSC color conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.112 NppStatus nppiYCbCrToBGR_709CSC_8u_P3C4R (const Npp8u *const pSrc[3], int nSrcStep, Npp8u *pDst, int nDstStep, NppiSize oSizeROI, Npp8u nAval)

3 channel 8-bit unsigned planar YCbCr to 4 channel 8-bit unsigned packed BGR_709CSC color conversion with constant alpha.

Parameters:

pSrc Source-Planar-Image Pointer Array.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nAval 8-bit unsigned alpha constant.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.113 NppStatus nppiYCbCrToBGR_8u_P3C3R (const Npp8u *const pSrc[3], int nSrcStep, Npp8u *pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned planar YCbCr to 3 channel 8-bit unsigned packed BGR color conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.114 NppStatus nppiYCbCrToBGR_8u_P3C4R (const Npp8u *const pSrc[3], int nSrcStep, Npp8u *pDst, int nDstStep, NppiSize oSizeROI, Npp8u nAval)

3 channel 8-bit unsigned planar YCbCr to 4 channel 8-bit unsigned packed BGR color conversion with constant alpha.

Parameters:

pSrc Source-Planar-Image Pointer Array.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nAval 8-bit unsigned alpha constant.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.115 NppStatus nppiYCbCrToRGB_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 8-bit unsigned packed YCbCr with alpha to 4 channel 8-bit unsigned packed RGB with alpha color conversion, not affecting alpha.

Alpha channel is the last channel and is not processed.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.116 NppStatus nppiYCbCrToRGB_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned packed YCbCr to 3 channel 8-bit unsigned packed RGB color conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.117 NppStatus nppiYCbCrToRGB_8u_P3C3R (const Npp8u * const pSrc[3], int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned planar YCbCr to 3 channel 8-bit unsigned packed RGB color conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.118 NppStatus nppiYCbCrToRGB_8u_P3C4R (const Npp8u *const pSrc[3], int nSrcStep, Npp8u *pDst, int nDstStep, NppiSize oSizeROI, Npp8u nAval)

3 channel 8-bit unsigned planar YCbCr to 4 channel 8-bit unsigned packed RGB color conversion with constant alpha.

Parameters:

pSrc Source-Planar-Image Pointer Array.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nAval 8-bit unsigned alpha constant.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.119 NppStatus nppiYCbCrToRGB_8u_P3R (const Npp8u *const pSrc[3], int nSrcStep, Npp8u *pDst[3], int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned planar YCbCr to 3 channel 8-bit unsigned planar RGB color conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.

nSrcStep Source-Image Line Step.

pDst Destination-Planar-Image Pointer Array.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.120 NppStatus nppiYCCToRGB_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 8-bit unsigned packed YCC with alpha to 4 channel 8-bit unsigned packed RGB with alpha color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.121 NppStatus nppiYCCToRGB_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned packed YCC to 3 channel 8-bit unsigned packed RGB color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.122 NppStatus nppiYCrCb420ToRGB_8u_P3C4R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, Npp8u nAval)

3 channel 8-bit unsigned planar YCrCb420 to 4 channel 8-bit unsigned packed RGB color conversion with constant alpha.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nAval 8-bit unsigned alpha constant.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.123 NppStatus nppiYCrCb422ToRGB_8u_C2C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

2 channel 8-bit unsigned packed YCrCb422 to 3 channel 8-bit unsigned packed RGB color conversion. images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.124 NppStatus nppiYCrCb422ToRGB_8u_C2P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int nDstStep, NppiSize oSizeROI)

2 channel 8-bit unsigned packed YCrCb422 to 3 channel 8-bit unsigned planar RGB color conversion. images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.125 NppStatus nppiYUV420ToBGR_8u_P3C3R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned planar YUV420 to 3 channel 8-bit unsigned packed BGR color conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.126 NppStatus nppiYUV420ToRGB_8u_P3AC4R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u *pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned planar YUV420 to 4 channel 8-bit unsigned packed RGB color conversion with alpha.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.127 NppStatus nppiYUV420ToRGB_8u_P3C3R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u *pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned planar YUV420 to 3 channel 8-bit unsigned packed RGB color conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.128 NppStatus nppiYUV420ToRGB_8u_P3R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u *pDst[3], int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned planar YUV420 to 3 channel 8-bit unsigned planar RGB color conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Planar-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.129 NppStatus nppiYUV422ToRGB_8u_C2C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

2 channel 8-bit unsigned packed YUV422 to 3 channel 8-bit unsigned packed RGB color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.130 NppStatus nppiYUV422ToRGB_8u_P3AC4R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned planar YUV422 to 4 channel 8-bit unsigned packed RGB color conversion with alpha.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.131 NppStatus nppiYUV422ToRGB_8u_P3C3R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned planar YUV422 to 3 channel 8-bit unsigned packed RGB color conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.132 NppStatus nppiYUV422ToRGB_8u_P3R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u *pDst[3], int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned planar YUV422 to 3 channel 8-bit unsigned planar RGB color conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Planar-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.133 NppStatus nppiYUVToRGB_8u_AC4R (const Npp8u *pSrc, int nSrcStep, Npp8u *pDst, int nDstStep, NppiSize oSizeROI)

4 channel 8-bit packed YUV with alpha to 4 channel 8-bit unsigned packed RGB color conversion with alpha, not affecting alpha.

images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.134 NppStatus nppiYUVToRGB_8u_C3R (const Npp8u *pSrc, int nSrcStep, Npp8u *pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned packed YUV to 3 channel 8-bit unsigned packed RGB color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.44.2.135 `NppStatus nppiYUVToRGB_8u_P3C3R (const Npp8u *const pSrc[3], int nSrcStep, Npp8u *pDst, int nDstStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned planar YUV to 3 channel 8-bit unsigned packed RGB color conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.44.2.136 `NppStatus nppiYUVToRGB_8u_P3R (const Npp8u *const pSrc[3], int nSrcStep, Npp8u *pDst[3], int nDstStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned planar YUV to 3 channel 8-bit unsigned planar RGB color conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.

nSrcStep Source-Image Line Step.

pDst Destination-Planar-Image Pointer Array.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45 Color Sampling Format Conversion

Routines for converting between various image color sampling formats.

YCbCr420ToYCbCr411

YCbCr420 to YCbCr411 sampling format conversion.

- `NppStatus nppiYCbCr420ToYCbCr411_8u_P3P2R` (const `Npp8u` *const pSrc[3], int rSrcStep[3], `Npp8u` *pDstY, int nDstYStep, `Npp8u` *pDstCbCr, int nDstCbCrStep, `NppiSize` oSizeROI)
3 channel 8-bit unsigned planar YCbCr420 to 2 channel 8-bit unsigned planar YCbCr411 sampling format conversion.
- `NppStatus nppiYCbCr420ToYCbCr411_8u_P2P3R` (const `Npp8u` *pSrcY, int nSrcYStep, const `Npp8u` *pSrcCbCr, int nSrcCbCrStep, `Npp8u` *pDst[3], int rDstStep[3], `NppiSize` oSizeROI)
2 channel 8-bit unsigned planar YCbCr420 to 3 channel 8-bit unsigned planar YCbCr411 sampling format conversion.

YCbCr422ToYCbCr422

YCbCr422 to YCbCr422 sampling format conversion.

- `NppStatus nppiYCbCr422_8u_C2P3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst[3], int rDstStep[3], `NppiSize` oSizeROI)
2 channel 8-bit unsigned packed YCbCr422 to 3 channel 8-bit unsigned planar YCbCr422 sampling format conversion.
- `NppStatus nppiYCbCr422_8u_P3C2R` (const `Npp8u` *const pSrc[3], int rSrcStep[3], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
3 channel 8-bit unsigned planar YCbCr422 to 2 channel 8-bit unsigned packed YCbCr422 sampling format conversion.

YCbCr422ToYCrCb422

YCbCr422 to YCrCb422 sampling format conversion.

- `NppStatus nppiYCbCr422ToYCrCb422_8u_C2R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
2 channel 8-bit unsigned packed YCbCr422 to 2 channel 8-bit unsigned packed YCrCb422 sampling format conversion.
- `NppStatus nppiYCbCr422ToYCrCb422_8u_P3C2R` (const `Npp8u` *const pSrc[3], int rSrcStep[3], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
3 channel 8-bit unsigned planar YCbCr422 to 2 channel 8-bit unsigned packed YCrCb422 sampling format conversion.

YCbCr422ToCbYCr422

YCbCr422 to CbYCr422 sampling format conversion.

- **NppStatus** **nppiYCbCr422ToCbYCr422_8u_C2R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
2 channel 8-bit unsigned packed YCbCr422 to 2 channel 8-bit unsigned packed CbYCr422 sampling format conversion.

CbYCr422ToYCbCr411

CbYCr422 to YCbCr411 sampling format conversion.

- **NppStatus** **nppiCbYCr422ToYCbCr411_8u_C2P3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst[3], int rDstStep[3], **NppiSize** oSizeROI)
2 channel 8-bit unsigned packed CbYCr422 to 3 channel 8-bit unsigned planar YCbCr411 sampling format conversion.

YCbCr422ToYCbCr420

YCbCr422 to YCbCr420 sampling format conversion.

- **NppStatus** **nppiYCbCr422ToYCbCr420_8u_P3R** (const **Npp8u** *const pSrc[3], int rSrcStep[3], **Npp8u** *pDst[3], int nDstStep[3], **NppiSize** oSizeROI)
3 channel 8-bit unsigned planar YCbCr422 to 3 channel 8-bit unsigned planar YCbCr420 sampling format conversion.
- **NppStatus** **nppiYCbCr422ToYCbCr420_8u_P3P2R** (const **Npp8u** *const pSrc[3], int rSrcStep[3], **Npp8u** *pDstY, int nDstYStep, **Npp8u** *pDstCbCr, int nDstCbCrStep, **NppiSize** oSizeROI)
3 channel 8-bit unsigned planar YCbCr422 to 2 channel 8-bit unsigned planar YCbCr420 sampling format conversion.
- **NppStatus** **nppiYCbCr422ToYCbCr420_8u_C2P3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst[3], int rDstStep[3], **NppiSize** oSizeROI)
2 channel 8-bit unsigned packed YCbCr422 to 3 channel 8-bit unsigned planar YCbCr420 sampling format conversion.
- **NppStatus** **nppiYCbCr422ToYCbCr420_8u_C2P2R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDstY, int nDstYStep, **Npp8u** *pDstCbCr, int nDstCbCrStep, **NppiSize** oSizeROI)
2 channel 8-bit unsigned packed YCbCr422 to 2 channel 8-bit unsigned planar YCbCr420 sampling format conversion.

YCrCb420ToYCbCr422

YCrCb420 to YCbCr422 sampling format conversion.

- **NppStatus** **nppiYCrCb420ToYCbCr422_8u_P3R** (const **Npp8u** *const pSrc[3], int rSrcStep[3], **Npp8u** *pDst[3], int rDstStep[3], **NppiSize** oSizeROI)

3 channel 8-bit unsigned planar YCrCb420 to 3 channel 8-bit unsigned planar YCbCr422 sampling format conversion.

- **NppStatus** **nppiYCrCb420ToYCbCr422_8u_P3C2R** (const **Npp8u** *const pSrc[3], int rSrcStep[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
3 channel 8-bit unsigned planar YCrCb420 to 2 channel 8-bit unsigned packed YCbCr422 sampling format conversion.

YCbCr422ToYCrCb420

YCbCr422 to YCrCb420 sampling format conversion.

- **NppStatus** **nppiYCbCr422ToYCrCb420_8u_C2P3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst[3], int rDstStep[3], **NppiSize** oSizeROI)
2 channel 8-bit unsigned packed YCbCr422 to 3 channel 8-bit unsigned planar YCrCb420 sampling format conversion.

YCbCr422ToYCbCr411

YCbCr422 to YCbCr411 sampling format conversion.

- **NppStatus** **nppiYCbCr422ToYCbCr411_8u_P3R** (const **Npp8u** *const pSrc[3], int rSrcStep[3], **Npp8u** *pDst[3], int rDstStep[3], **NppiSize** oSizeROI)
3 channel 8-bit unsigned planar YCbCr422 to 3 channel 8-bit unsigned planar YCbCr411 sampling format conversion.
- **NppStatus** **nppiYCbCr422ToYCbCr411_8u_P3P2R** (const **Npp8u** *const pSrc[3], int rSrcStep[3], **Npp8u** *pDstY, int nDstYStep, **Npp8u** *pDstCbCr, int nDstCbCrStep, **NppiSize** oSizeROI)
3 channel 8-bit unsigned planar YCbCr422 to 2 channel 8-bit unsigned planar YCbCr411 sampling format conversion.
- **NppStatus** **nppiYCbCr422ToYCbCr411_8u_C2P3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst[3], int rDstStep[3], **NppiSize** oSizeROI)
2 channel 8-bit unsigned packed YCbCr422 to 3 channel 8-bit unsigned planar YCbCr411 sampling format conversion.
- **NppStatus** **nppiYCbCr422ToYCbCr411_8u_C2P2R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDstY, int nDstYStep, **Npp8u** *pDstCbCr, int nDstCbCrStep, **NppiSize** oSizeROI)
2 channel 8-bit unsigned packed YCbCr422 to 2 channel 8-bit unsigned planar YCbCr411 sampling format conversion.

YCrCb422ToYCbCr422

YCrCb422 to YCbCr422 sampling format conversion.

- **NppStatus** **nppiYCrCb422ToYCbCr422_8u_C2P3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst[3], int rDstStep[3], **NppiSize** oSizeROI)

2 channel 8-bit unsigned packed YCrCb422 to 3 channel 8-bit unsigned planar YCbCr422 sampling format conversion.

YCrCb422ToYCbCr420

YCrCb422 to YCbCr420 sampling format conversion.

- `NppStatus nppiYCrCb422ToYCbCr420_8u_C2P3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst[3]`, int `rDstStep[3]`, `NppiSize oSizeROI`)

2 channel 8-bit unsigned packed YCrCb422 to 3 channel 8-bit unsigned planar YCbCr420 sampling format conversion.

YCrCb422ToYCbCr411

YCrCb422 to YCbCr411 sampling format conversion.

- `NppStatus nppiYCrCb422ToYCbCr411_8u_C2P3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst[3]`, int `rDstStep[3]`, `NppiSize oSizeROI`)

2 channel 8-bit unsigned packed YCrCb422 to 3 channel 8-bit unsigned planar YCbCr411 sampling format conversion.

CbYCr422ToYCbCr422

CbYCr422 to YCbCr422 sampling format conversion.

- `NppStatus nppiCbYCr422ToYCbCr422_8u_C2R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

2 channel 8-bit unsigned packed CbYCr422 to 2 channel 8-bit unsigned packed YCbCr422 sampling format conversion.

- `NppStatus nppiCbYCr422ToYCbCr422_8u_C2P3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst[3]`, int `rDstStep[3]`, `NppiSize oSizeROI`)

2 channel 8-bit unsigned packed CbYCr422 to 3 channel 8-bit unsigned planar YCbCr422 sampling format conversion.

CbYCr422ToYCbCr420

CbYCr422 to YCbCr420 sampling format conversion.

- `NppStatus nppiCbYCr422ToYCbCr420_8u_C2P3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst[3]`, int `rDstStep[3]`, `NppiSize oSizeROI`)

2 channel 8-bit unsigned packed CbYCr422 to 3 channel 8-bit unsigned planar YCbCr420 sampling format conversion.

- `NppStatus nppiCbYCr422ToYCbCr420_8u_C2P2R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDstY`, int `nDstYStep`, `Npp8u *pDstCbCr`, int `nDstCbCrStep`, `NppiSize oSizeROI`)

2 channel 8-bit unsigned packed CbYCr422 to 2 channel 8-bit unsigned planar YCbCr420 sampling format conversion.

CbYCr422ToYCrCb420

CbYCr422 to YCrCb420 sampling format conversion.

- `NppStatus nppiCbYCr422ToYCrCb420_8u_C2P3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst[3]`, int `rDstStep[3]`, `NppiSize oSizeROI`)

2 channel 8-bit unsigned packed CbYCr422 to 3 channel 8-bit unsigned planar YCrCb420 sampling format conversion.

YCbCr420ToYCbCr420

YCbCr420 to YCbCr420 sampling format conversion.

- `NppStatus nppiYCbCr420_8u_P3P2R` (const `Npp8u *const pSrc[3]`, int `rSrcStep[3]`, `Npp8u *pDstY`, int `nDstYStep`, `Npp8u *pDstCbCr`, int `nDstCbCrStep`, `NppiSize oSizeROI`)

3 channel 8-bit unsigned planar YCbCr420 to 2 channel 8-bit unsigned planar YCbCr420 sampling format conversion.

- `NppStatus nppiYCbCr420_8u_P2P3R` (const `Npp8u *const pSrcY`, int `nSrcYStep`, const `Npp8u *pSrcCbCr`, int `nSrcCbCrStep`, `Npp8u *pDst[3]`, int `rDstStep[3]`, `NppiSize oSizeROI`)

2 channel 8-bit unsigned planar YCbCr420 to 3 channel 8-bit unsigned planar YCbCr420 sampling format conversion.

YCbCr420ToYCbCr422

YCbCr420 to YCbCr422 sampling format conversion.

- `NppStatus nppiYCbCr420ToYCbCr422_8u_P3R` (const `Npp8u *const pSrc[3]`, int `rSrcStep[3]`, `Npp8u *pDst[3]`, int `nDstStep[3]`, `NppiSize oSizeROI`)

3 channel 8-bit unsigned planar YCbCr420 to 3 channel 8-bit unsigned planar YCbCr422 sampling format conversion.

- `NppStatus nppiYCbCr420ToYCbCr422_8u_P2P3R` (const `Npp8u *pSrcY`, int `nSrcYStep`, const `Npp8u *pSrcCbCr`, int `nSrcCbCrStep`, `Npp8u *pDst[3]`, int `rDstStep[3]`, `NppiSize oSizeROI`)

2 channel 8-bit unsigned planar YCbCr420 to 3 channel 8-bit unsigned planar YCbCr422 sampling format conversion.

- `NppStatus nppiYCbCr420ToYCbCr422_8u_P2C2R` (const `Npp8u *pSrcY`, int `nSrcYStep`, const `Npp8u *pSrcCbCr`, int `nSrcCbCrStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

2 channel 8-bit unsigned planar YCbCr420 to 2 channel 8-bit unsigned packed YCbCr422 sampling format conversion.

YCbCr420ToCbYCr422

YCbCr420 to CbYCr422 sampling format conversion.

- `NppStatus nppiYCbCr420ToCbYCr422_8u_P2C2R` (const `Npp8u *pSrcY`, int `nSrcYStep`, const `Npp8u *pSrcCbCr`, int `nSrcCbCrStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
2 channel 8-bit unsigned planar YCbCr420 to 2 channel 8-bit unsigned packed CbYCr422 sampling format conversion.

YCbCr420ToYCrCb420

YCbCr420 to YCrCb420 sampling format conversion.

- `NppStatus nppiYCbCr420ToYCrCb420_8u_P2P3R` (const `Npp8u *pSrcY`, int `nSrcYStep`, const `Npp8u *pSrcCbCr`, int `nSrcCbCrStep`, `Npp8u *pDst[3]`, int `rDstStep[3]`, `NppiSize oSizeROI`)
2 channel 8-bit unsigned planar YCbCr420 to 3 channel 8-bit unsigned planar YCrCb420 sampling format conversion.

YCrCb420ToCbYCr422

YCrCb420 to CbYCr422 sampling format conversion.

- `NppStatus nppiYCrCb420ToCbYCr422_8u_P3C2R` (const `Npp8u *const pSrc[3]`, int `rSrcStep[3]`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned planar YCrCb420 to 2 channel 8-bit unsigned packed CbYCr422 sampling format conversion.

YCrCb420ToYCbCr420

YCrCb420 to YCbCr420 sampling format conversion.

- `NppStatus nppiYCrCb420ToYCbCr420_8u_P3P2R` (const `Npp8u *const pSrc[3]`, int `rSrcStep[3]`, `Npp8u *pDstY`, int `nDstYStep`, `Npp8u *pDstCbCr`, int `nDstCbCrStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned planar YCrCb420 to 2 channel 8-bit unsigned planar YCbCr420 sampling format conversion.

YCrCb420ToYCbCr411

YCrCb420 to YCbCr411 sampling format conversion.

- `NppStatus nppiYCrCb420ToYCbCr411_8u_P3P2R` (const `Npp8u *const pSrc[3]`, int `rSrcStep[3]`, `Npp8u *pDstY`, int `nDstYStep`, `Npp8u *pDstCbCr`, int `nDstCbCrStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned planar YCrCb420 to 2 channel 8-bit unsigned planar YCbCr411 sampling format conversion.

YCbCr411ToYCbCr411

YCbCr411 to YCbCr411 sampling format conversion.

- `NppStatus nppiYCbCr411_8u_P3P2R` (const `Npp8u` *const pSrc[3], int rSrcStep[3], `Npp8u` *pDstY, int nDstYStep, `Npp8u` *pDstCbCr, int nDstCbCrStep, `NppiSize` oSizeROI)
3 channel 8-bit unsigned planar YCbCr411 to 2 channel 8-bit unsigned planar YCbCr411 sampling format conversion.
- `NppStatus nppiYCbCr411_8u_P2P3R` (const `Npp8u` *pSrcY, int nSrcYStep, const `Npp8u` *pSrcCbCr, int nSrcCbCrStep, `Npp8u` *pDst[3], int rDstStep[3], `NppiSize` oSizeROI)
2 channel 8-bit unsigned planar YCbCr411 to 3 channel 8-bit unsigned planar YCbCr411 sampling format conversion.

YCbCr411ToYCbCr422

YCbCr411 to YCbCr422 sampling format conversion.

- `NppStatus nppiYCbCr411ToYCbCr422_8u_P3R` (const `Npp8u` *const pSrc[3], int rSrcStep[3], `Npp8u` *pDst[3], int nDstStep[3], `NppiSize` oSizeROI)
3 channel 8-bit unsigned planar YCbCr411 to 3 channel 8-bit unsigned planar YCbCr422 sampling format conversion.
- `NppStatus nppiYCbCr411ToYCbCr422_8u_P3C2R` (const `Npp8u` *const pSrc[3], int rSrcStep[3], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
3 channel 8-bit unsigned planar YCbCr411 to 2 channel 8-bit unsigned packed YCbCr422 sampling format conversion.
- `NppStatus nppiYCbCr411ToYCbCr422_8u_P2P3R` (const `Npp8u` *const pSrcY, int nSrcYStep, const `Npp8u` *pSrcCbCr, int nSrcCbCrStep, `Npp8u` *pDst[3], int rDstStep[3], `NppiSize` oSizeROI)
2 channel 8-bit unsigned planar YCbCr411 to 3 channel 8-bit unsigned planar YCbCr422 sampling format conversion.
- `NppStatus nppiYCbCr411ToYCbCr422_8u_P2C2R` (const `Npp8u` *pSrcY, int nSrcYStep, const `Npp8u` *pSrcCbCr, int nSrcCbCrStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
2 channel 8-bit unsigned planar YCbCr411 to 2 channel 8-bit unsigned packed YCbCr422 sampling format conversion.

YCbCr411ToYCrCb422

YCbCr411 to YCrCb422 sampling format conversion.

- `NppStatus nppiYCbCr411ToYCrCb422_8u_P3R` (const `Npp8u` *const pSrc[3], int rSrcStep[3], `Npp8u` *pDst[3], int nDstStep[3], `NppiSize` oSizeROI)
3 channel 8-bit unsigned planar YCbCr411 to 3 channel 8-bit unsigned planar YCrCb422 sampling format conversion.
- `NppStatus nppiYCbCr411ToYCrCb422_8u_P3C2R` (const `Npp8u` *const pSrc[3], int rSrcStep[3], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)

3 channel 8-bit unsigned planar YCbCr411 to 2 channel 8-bit unsigned packed YCrCb422 sampling format conversion.

YCbCr411ToYCbCr420

YCbCr411 to YCbCr420 sampling format conversion.

- `NppStatus nppiYCbCr411ToYCbCr420_8u_P3R` (const `Npp8u *const pSrc[3]`, int `rSrcStep[3]`, `Npp8u *pDst[3]`, int `nDstStep[3]`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned planar YCbCr411 to 3 channel 8-bit unsigned planar YCbCr420 sampling format conversion.
- `NppStatus nppiYCbCr411ToYCbCr420_8u_P3P2R` (const `Npp8u *const pSrc[3]`, int `rSrcStep[3]`, `Npp8u *pDstY`, int `nDstYStep`, `Npp8u *pDstCbCr`, int `nDstCbCrStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned planar YCbCr411 to 2 channel 8-bit unsigned planar YCbCr420 sampling format conversion.
- `NppStatus nppiYCbCr411ToYCbCr420_8u_P2P3R` (const `Npp8u *pSrcY`, int `nSrcYStep`, const `Npp8u *pSrcCbCr`, int `nSrcCbCrStep`, `Npp8u *pDst[3]`, int `rDstStep[3]`, `NppiSize oSizeROI`)
2 channel 8-bit unsigned planar YCbCr411 to 3 channel 8-bit unsigned planar YCbCr420 sampling format conversion.

YCbCr411ToYCrCb420

YCbCr411 to YCrCb420 sampling format conversion.

- `NppStatus nppiYCbCr411ToYCrCb420_8u_P2P3R` (const `Npp8u *pSrcY`, int `nSrcYStep`, const `Npp8u *pSrcCbCr`, int `nSrcCbCrStep`, `Npp8u *pDst[3]`, int `rDstStep[3]`, `NppiSize oSizeROI`)
2 channel 8-bit unsigned planar YCbCr411 to 3 channel 8-bit unsigned planar YCrCb420 sampling format conversion.

7.45.1 Detailed Description

Routines for converting between various image color sampling formats.

7.45.2 Function Documentation

7.45.2.1 `NppStatus nppiCbYCr422ToYCbCr411_8u_C2P3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst[3]`, int `rDstStep[3]`, `NppiSize oSizeROI`)

2 channel 8-bit unsigned packed CbYCr422 to 3 channel 8-bit unsigned planar YCbCr411 sampling format conversion.

images.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.2 **NppStatus nppiCbYCr422ToYCbCr420_8u_C2P2R** (const Npp8u * *pSrc*, int *nSrcStep*, Npp8u * *pDstY*, int *nDstYStep*, Npp8u * *pDstCbCr*, int *nDstCbCrStep*, NppiSize *oSizeROI*)

2 channel 8-bit unsigned packed CbYCr422 to 2 channel 8-bit unsigned planar YCbCr420 sampling format conversion.

images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDstY Destination-Planar-Image Pointer.
nDstYStep Destination-Planar-Image Line Step.
pDstCbCr Destination-Planar-Image Pointer.
nDstCbCrStep Destination-Planar-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.3 **NppStatus nppiCbYCr422ToYCbCr420_8u_C2P3R** (const Npp8u * *pSrc*, int *nSrcStep*, Npp8u * *pDst*[3], int *rDstStep*[3], NppiSize *oSizeROI*)

2 channel 8-bit unsigned packed CbYCr422 to 3 channel 8-bit unsigned planar YCbCr420 sampling format conversion.

images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.4 NppStatus nppiCbYCr422ToYCbCr422_8u_C2P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)

2 channel 8-bit unsigned packed CbYCr422 to 3 channel 8-bit unsigned planar YCbCr422 sampling format conversion.

images.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Planar-Image Pointer Array.

rDstStep Destination-Planar-Image Line Step Array.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.45.2.5 NppStatus nppiCbYCr422ToYCbCr422_8u_C2R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

2 channel 8-bit unsigned packed CbYCr422 to 2 channel 8-bit unsigned packed YCbCr422 sampling format conversion.

images.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.45.2.6 NppStatus nppiCbYCr422ToYCrCb420_8u_C2P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)

2 channel 8-bit unsigned packed CbYCr422 to 3 channel 8-bit unsigned planar YCrCb420 sampling format conversion.

images.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.7 **NppStatus nppiYCbCr411_8u_P2P3R (const Npp8u *pSrcY, int nSrcYStep, const Npp8u *pSrcCbCr, int nSrcCbCrStep, Npp8u *pDst[3], int rDstStep[3], NppiSize oSizeROI)**

2 channel 8-bit unsigned planar YCbCr411 to 3 channel 8-bit unsigned planar YCbCr411 sampling format conversion.

Parameters:

pSrcY Source-Planar-Image Pointer.
nSrcYStep Source-Planar-Image Line Step.
pSrcCbCr Source-Planar-Image Pointer.
nSrcCbCrStep Source-Planar-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.8 **NppStatus nppiYCbCr411_8u_P3P2R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u *pDstY, int nDstYStep, Npp8u *pDstCbCr, int nDstCbCrStep, NppiSize oSizeROI)**

3 channel 8-bit unsigned planar YCbCr411 to 2 channel 8-bit unsigned planar YCbCr411 sampling format conversion.

images.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDstY Destination-Planar-Image Pointer.
nDstYStep Destination-Planar-Image Line Step.
pDstCbCr Destination-Planar-Image Pointer.
nDstCbCrStep Destination-Planar-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.9 NppStatus nppiYCbCr411ToYCbCr420_8u_P2P3R (const Npp8u * *pSrcY*, int *nSrcYStep*, const Npp8u * *pSrcCbCr*, int *nSrcCbCrStep*, Npp8u * *pDst*[3], int *rDstStep*[3], NppiSize *oSizeROI*)

2 channel 8-bit unsigned planar YCbCr411 to 3 channel 8-bit unsigned planar YCbCr420 sampling format conversion.

Parameters:

pSrcY Source-Planar-Image Pointer.
nSrcYStep Source-Planar-Image Line Step.
pSrcCbCr Source-Planar-Image Pointer.
nSrcCbCrStep Source-Planar-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.45.2.10 NppStatus nppiYCbCr411ToYCbCr420_8u_P3P2R (const Npp8u *const *pSrc*[3], int *rSrcStep*[3], Npp8u * *pDstY*, int *nDstYStep*, Npp8u * *pDstCbCr*, int *nDstCbCrStep*, NppiSize *oSizeROI*)

3 channel 8-bit unsigned planar YCbCr411 to 2 channel 8-bit unsigned planar YCbCr420 sampling format conversion.

images.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDstY Destination-Planar-Image Pointer.
nDstYStep Destination-Planar-Image Line Step.
pDstCbCr Destination-Planar-Image Pointer.
nDstCbCrStep Destination-Planar-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.45.2.11 NppStatus nppiYCbCr411ToYCbCr420_8u_P3R (const Npp8u *const *pSrc*[3], int *rSrcStep*[3], Npp8u * *pDst*[3], int *nDstStep*[3], NppiSize *oSizeROI*)

3 channel 8-bit unsigned planar YCbCr411 to 3 channel 8-bit unsigned planar YCbCr420 sampling format conversion.

images.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.12 **NppStatus nppiYCbCr411ToYCbCr422_8u_P2C2R** (const Npp8u * *pSrcY*, int *nSrcYStep*, const Npp8u * *pSrcCbCr*, int *nSrcCbCrStep*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

2 channel 8-bit unsigned planar YCbCr411 to 2 channel 8-bit unsigned packed YCbCr422 sampling format conversion.

Parameters:

pSrcY Source-Planar-Image Pointer.
nSrcYStep Source-Planar-Image Line Step.
pSrcCbCr Source-Planar-Image Pointer.
nSrcCbCrStep Source-Planar-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.13 **NppStatus nppiYCbCr411ToYCbCr422_8u_P2P3R** (const Npp8u *const *pSrcY*, int *nSrcYStep*, const Npp8u * *pSrcCbCr*, int *nSrcCbCrStep*, Npp8u * *pDst*[3], int *rDstStep*[3], NppiSize *oSizeROI*)

2 channel 8-bit unsigned planar YCbCr411 to 3 channel 8-bit unsigned planar YCbCr422 sampling format conversion.

Parameters:

pSrcY Source-Planar-Image Pointer.
nSrcYStep Source-Planar-Image Line Step.
pSrcCbCr Source-Planar-Image Pointer.
nSrcCbCrStep Source-Planar-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.14 `NppStatus nppiYCbCr411ToYCbCr422_8u_P3C2R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u *pDst, int nDstStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned planar YCbCr411 to 2 channel 8-bit unsigned packed YCbCr422 sampling format conversion.

images.

Parameters:

pSrc Source-Planar-Image Pointer Array.

rSrcStep Source-Planar-Image Line Step Array.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.15 `NppStatus nppiYCbCr411ToYCbCr422_8u_P3R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u *pDst[3], int nDstStep[3], NppiSize oSizeROI)`

3 channel 8-bit unsigned planar YCbCr411 to 3 channel 8-bit unsigned planar YCbCr422 sampling format conversion.

images.

Parameters:

pSrc Source-Planar-Image Pointer Array.

rSrcStep Source-Planar-Image Line Step Array.

pDst Destination-Planar-Image Pointer Array.

nDstStep Destination-Planar-Image Line Step Array.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.16 `NppStatus nppiYCbCr411ToYCrCb420_8u_P2P3R (const Npp8u *pSrcY, int nSrcYStep, const Npp8u *pSrcCbCr, int nSrcCbCrStep, Npp8u *pDst[3], int rDstStep[3], NppiSize oSizeROI)`

2 channel 8-bit unsigned planar YCbCr411 to 3 channel 8-bit unsigned planar YCrCb420 sampling format conversion.

Parameters:

pSrcY Source-Planar-Image Pointer.

nSrcYStep Source-Planar-Image Line Step.

pSrcCbCr Source-Planar-Image Pointer.
nSrcCbCrStep Source-Planar-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.17 NppStatus nppiYCbCr411ToYCrCb422_8u_P3C2R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned planar YCbCr411 to 2 channel 8-bit unsigned packed YCrCb422 sampling format conversion.

images.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.18 NppStatus nppiYCbCr411ToYCrCb422_8u_P3R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u * pDst[3], int nDstStep[3], NppiSize oSizeROI)

3 channel 8-bit unsigned planar YCbCr411 to 3 channel 8-bit unsigned planar YCrCb422 sampling format conversion.

images.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.19 `NppStatus nppiYCbCr420_8u_P2P3R (const Npp8u *const pSrcY, int nSrcYStep, const Npp8u * pSrcCbCr, int nSrcCbCrStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)`

2 channel 8-bit unsigned planar YCbCr420 to 3 channel 8-bit unsigned planar YCbCr420 sampling format conversion.

Parameters:

pSrcY Source-Planar-Image Pointer.
nSrcYStep Source-Planar-Image Line Step.
pSrcCbCr Source-Planar-Image Pointer.
nSrcCbCrStep Source-Planar-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.45.2.20 `NppStatus nppiYCbCr420_8u_P3P2R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u * pDstY, int nDstYStep, Npp8u * pDstCbCr, int nDstCbCrStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned planar YCbCr420 to 2 channel 8-bit unsigned planar YCbCr420 sampling format conversion.

images.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDstY Destination-Planar-Image Pointer.
nDstYStep Destination-Planar-Image Line Step.
pDstCbCr Destination-Planar-Image Pointer.
nDstCbCrStep Destination-Planar-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.45.2.21 `NppStatus nppiYCbCr420ToCbYCr422_8u_P2C2R (const Npp8u * pSrcY, int nSrcYStep, const Npp8u * pSrcCbCr, int nSrcCbCrStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

2 channel 8-bit unsigned planar YCbCr420 to 2 channel 8-bit unsigned packed CbYCr422 sampling format conversion.

Parameters:

pSrcY Source-Planar-Image Pointer.
nSrcYStep Source-Planar-Image Line Step.
pSrcCbCr Source-Planar-Image Pointer.
nSrcCbCrStep Source-Planar-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.22 `NppStatus nppiYCbCr420ToYCbCr411_8u_P2P3R (const Npp8u * pSrcY, int nSrcYStep, const Npp8u * pSrcCbCr, int nSrcCbCrStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)`

2 channel 8-bit unsigned planar YCbCr420 to 3 channel 8-bit unsigned planar YCbCr411 sampling format conversion.

Parameters:

pSrcY Source-Planar-Image Pointer.
nSrcYStep Source-Planar-Image Line Step.
pSrcCbCr Source-Planar-Image Pointer.
nSrcCbCrStep Source-Planar-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.23 `NppStatus nppiYCbCr420ToYCbCr411_8u_P3P2R (const Npp8u * const pSrc[3], int rSrcStep[3], Npp8u * pDstY, int nDstYStep, Npp8u * pDstCbCr, int nDstCbCrStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned planar YCbCr420 to 2 channel 8-bit unsigned planar YCbCr411 sampling format conversion.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDstY Destination-Planar-Image Pointer.
nDstYStep Destination-Planar-Image Line Step.

pDstCbCr Destination-Planar-Image Pointer.
nDstCbCrStep Destination-Planar-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.24 `NppStatus nppiYCbCr420ToYCbCr422_8u_P2C2R (const Npp8u * pSrcY, int nSrcYStep, const Npp8u * pSrcCbCr, int nSrcCbCrStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

2 channel 8-bit unsigned planar YCbCr420 to 2 channel 8-bit unsigned packed YCbCr422 sampling format conversion.

Parameters:

pSrcY Source-Planar-Image Pointer.
nSrcYStep Source-Planar-Image Line Step.
pSrcCbCr Source-Planar-Image Pointer.
nSrcCbCrStep Source-Planar-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.25 `NppStatus nppiYCbCr420ToYCbCr422_8u_P2P3R (const Npp8u * pSrcY, int nSrcYStep, const Npp8u * pSrcCbCr, int nSrcCbCrStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)`

2 channel 8-bit unsigned planar YCbCr420 to 3 channel 8-bit unsigned planar YCbCr422 sampling format conversion.

Parameters:

pSrcY Source-Planar-Image Pointer.
nSrcYStep Source-Planar-Image Line Step.
pSrcCbCr Source-Planar-Image Pointer.
nSrcCbCrStep Source-Planar-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.26 `NppStatus nppiYCbCr420ToYCbCr422_8u_P3R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u * pDst[3], int nDstStep[3], NppiSize oSizeROI)`

3 channel 8-bit unsigned planar YCbCr420 to 3 channel 8-bit unsigned planar YCbCr422 sampling format conversion.

images.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.27 `NppStatus nppiYCbCr420ToYCrCb420_8u_P2P3R (const Npp8u * pSrcY, int nSrcYStep, const Npp8u * pSrcCbCr, int nSrcCbCrStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)`

2 channel 8-bit unsigned planar YCbCr420 to 3 channel 8-bit unsigned planar YCrCb420 sampling format conversion.

Parameters:

pSrcY Source-Planar-Image Pointer.
nSrcYStep Source-Planar-Image Line Step.
pSrcCbCr Source-Planar-Image Pointer.
nSrcCbCrStep Source-Planar-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.28 `NppStatus nppiYCbCr422_8u_C2P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)`

2 channel 8-bit unsigned packed YCbCr422 to 3 channel 8-bit unsigned planar YCbCr422 sampling format conversion.

images.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.29 NppStatus nppiYCbCr422_8u_P3C2R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u *pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned planar YCbCr422 to 2 channel 8-bit unsigned packed YCbCr422 sampling format conversion.

images.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.30 NppStatus nppiYCbCr422ToCbYCr422_8u_C2R (const Npp8u *pSrc, int nSrcStep, Npp8u *pDst, int nDstStep, NppiSize oSizeROI)

2 channel 8-bit unsigned packed YCbCr422 to 2 channel 8-bit unsigned packed CbYCr422 sampling format conversion.

images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.31 `NppStatus nppiYCbCr422ToYCbCr411_8u_C2P2R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDstY, int nDstYStep, Npp8u * pDstCbCr, int nDstCbCrStep, NppiSize oSizeROI)`

2 channel 8-bit unsigned packed YCbCr422 to 2 channel 8-bit unsigned planar YCbCr411 sampling format conversion.

images.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDstY* Destination-Planar-Image Pointer.
- nDstYStep* Destination-Planar-Image Line Step.
- pDstCbCr* Destination-Planar-Image Pointer.
- nDstCbCrStep* Destination-Planar-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.45.2.32 `NppStatus nppiYCbCr422ToYCbCr411_8u_C2P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)`

2 channel 8-bit unsigned packed YCbCr422 to 3 channel 8-bit unsigned planar YCbCr411 sampling format conversion.

images.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Planar-Image Pointer Array.
- rDstStep* Destination-Planar-Image Line Step Array.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.45.2.33 `NppStatus nppiYCbCr422ToYCbCr411_8u_P3P2R (const Npp8u * const pSrc[3], int rSrcStep[3], Npp8u * pDstY, int nDstYStep, Npp8u * pDstCbCr, int nDstCbCrStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned planar YCbCr422 to 2 channel 8-bit unsigned planar YCbCr411 sampling format conversion.

images.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDstY Destination-Planar-Image Pointer.
nDstYStep Destination-Planar-Image Line Step.
pDstCbCr Destination-Planar-Image Pointer.
nDstCbCrStep Destination-Planar-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.34 **NppStatus nppiYCbCr422ToYCbCr411_8u_P3R** (const Npp8u *const *pSrc*[3], int *rSrcStep*[3], Npp8u * *pDst*[3], int *rDstStep*[3], NppiSize *oSizeROI*)

3 channel 8-bit unsigned planar YCbCr422 to 3 channel 8-bit unsigned planar YCbCr411 sampling format conversion.

images.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.35 **NppStatus nppiYCbCr422ToYCbCr420_8u_C2P2R** (const Npp8u * *pSrc*, int *nSrcStep*, Npp8u * *pDstY*, int *nDstYStep*, Npp8u * *pDstCbCr*, int *nDstCbCrStep*, NppiSize *oSizeROI*)

2 channel 8-bit unsigned packed YCbCr422 to 2 channel 8-bit unsigned planar YCbCr420 sampling format conversion.

images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDstY Destination-Planar-Image Pointer.
nDstYStep Destination-Planar-Image Line Step.
pDstCbCr Destination-Planar-Image Pointer.

nDstCbCrStep Destination-Planar-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.36 `NppStatus nppiYCbCr422ToYCbCr420_8u_C2P3R` (`const Npp8u * pSrc`, `int nSrcStep`, `Npp8u * pDst[3]`, `int rDstStep[3]`, `NppiSize oSizeROI`)

2 channel 8-bit unsigned packed YCbCr422 to 3 channel 8-bit unsigned planar YCbCr420 sampling format conversion.

images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.37 `NppStatus nppiYCbCr422ToYCbCr420_8u_P3P2R` (`const Npp8u *const pSrc[3]`, `int rSrcStep[3]`, `Npp8u * pDstY`, `int nDstYStep`, `Npp8u * pDstCbCr`, `int nDstCbCrStep`, `NppiSize oSizeROI`)

3 channel 8-bit unsigned planar YCbCr422 to 2 channel 8-bit unsigned planar YCbCr420 sampling format conversion.

images.

Parameters:

pSrc Source-Planar-Image Pointer Array.
rSrcStep Source-Planar-Image Line Step Array.
pDstY Destination-Planar-Image Pointer.
nDstYStep Destination-Planar-Image Line Step.
pDstCbCr Destination-Planar-Image Pointer.
nDstCbCrStep Destination-Planar-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.38 `NppStatus nppiYCbCr422ToYCbCr420_8u_P3R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u * pDst[3], int nDstStep[3], NppiSize oSizeROI)`

3 channel 8-bit unsigned planar YCbCr422 to 3 channel 8-bit unsigned planar YCbCr420 sampling format conversion.

images.

Parameters:

pSrc Source-Planar-Image Pointer Array.

rSrcStep Source-Planar-Image Line Step Array.

pDst Destination-Planar-Image Pointer Array.

nDstStep Destination-Planar-Image Line Step Array.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.45.2.39 `NppStatus nppiYCbCr422ToYCrCb420_8u_C2P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)`

2 channel 8-bit unsigned packed YCbCr422 to 3 channel 8-bit unsigned planar YCrCb420 sampling format conversion.

images.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Planar-Image Pointer Array.

rDstStep Destination-Planar-Image Line Step Array.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.45.2.40 `NppStatus nppiYCbCr422ToYCrCb422_8u_C2R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

2 channel 8-bit unsigned packed YCbCr422 to 2 channel 8-bit unsigned packed YCrCb422 sampling format conversion.

images.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.41 NppStatus nppiYCbCr422ToYCrCb422_8u_P3C2R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned planar YCbCr422 to 2 channel 8-bit unsigned packed YCrCb422 sampling format conversion.

images.

Parameters:

pSrc Source-Planar-Image Pointer Array.

rSrcStep Source-Planar-Image Line Step Array.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.42 NppStatus nppiYCrCb420ToCbYCr422_8u_P3C2R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned planar YCrCb420 to 2 channel 8-bit unsigned packed CbYCr422 sampling format conversion.

images.

Parameters:

pSrc Source-Planar-Image Pointer Array.

rSrcStep Source-Planar-Image Line Step Array.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.43 `NppStatus nppiYCrCb420ToYCbCr411_8u_P3P2R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u *pDstY, int nDstYStep, Npp8u *pDstCbCr, int nDstCbCrStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned planar YCrCb420 to 2 channel 8-bit unsigned planar YCbCr411 sampling format conversion.

images.

Parameters:

pSrc Source-Planar-Image Pointer Array.

rSrcStep Source-Planar-Image Line Step Array.

pDstY Destination-Planar-Image Pointer.

nDstYStep Destination-Planar-Image Line Step.

pDstCbCr Destination-Planar-Image Pointer.

nDstCbCrStep Destination-Planar-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.44 `NppStatus nppiYCrCb420ToYCbCr420_8u_P3P2R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u *pDstY, int nDstYStep, Npp8u *pDstCbCr, int nDstCbCrStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned planar YCrCb420 to 2 channel 8-bit unsigned planar YCbCr420 sampling format conversion.

images.

Parameters:

pSrc Source-Planar-Image Pointer Array.

rSrcStep Source-Planar-Image Line Step Array.

pDstY Destination-Planar-Image Pointer.

nDstYStep Destination-Planar-Image Line Step.

pDstCbCr Destination-Planar-Image Pointer.

nDstCbCrStep Destination-Planar-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.45 `NppStatus nppiYCrCb420ToYCbCr422_8u_P3C2R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned planar YCrCb420 to 2 channel 8-bit unsigned packed YCbCr422 sampling format conversion.

images.

Parameters:

pSrc Source-Planar-Image Pointer Array.

rSrcStep Source-Planar-Image Line Step Array.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.45.2.46 `NppStatus nppiYCrCb420ToYCbCr422_8u_P3R (const Npp8u *const pSrc[3], int rSrcStep[3], Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)`

3 channel 8-bit unsigned planar YCrCb420 to 3 channel 8-bit unsigned planar YCbCr422 sampling format conversion.

images.

Parameters:

pSrc Source-Planar-Image Pointer Array.

rSrcStep Source-Planar-Image Line Step Array.

pDst Destination-Planar-Image Pointer Array.

rDstStep Destination-Planar-Image Line Step Array.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.45.2.47 `NppStatus nppiYCrCb422ToYCbCr411_8u_C2P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)`

2 channel 8-bit unsigned packed YCrCb422 to 3 channel 8-bit unsigned planar YCbCr411 sampling format conversion.

images.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.48 NppStatus nppiYCrCb422ToYCbCr420_8u_C2P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)

2 channel 8-bit unsigned packed YCrCb422 to 3 channel 8-bit unsigned planar YCbCr420 sampling format conversion.

images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.45.2.49 NppStatus nppiYCrCb422ToYCbCr422_8u_C2P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst[3], int rDstStep[3], NppiSize oSizeROI)

2 channel 8-bit unsigned packed YCrCb422 to 3 channel 8-bit unsigned planar YCbCr422 sampling format conversion.

images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Planar-Image Pointer Array.
rDstStep Destination-Planar-Image Line Step Array.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.46 Color Gamma Correction

Routines for correcting image color gamma.

GammaFwd

Forward gamma correction.

- `NppStatus nppiGammaFwd_8u_C3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned packed color not in place forward gamma correction.
- `NppStatus nppiGammaFwd_8u_C3IR` (`Npp8u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned packed color in place forward gamma correction.
- `NppStatus nppiGammaFwd_8u_AC4R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
4 channel 8-bit unsigned packed color with alpha not in place forward gamma correction.
- `NppStatus nppiGammaFwd_8u_AC4IR` (`Npp8u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
4 channel 8-bit unsigned packed color with alpha in place forward gamma correction.
- `NppStatus nppiGammaFwd_8u_P3R` (const `Npp8u *const pSrc[3]`, int `nSrcStep`, `Npp8u *pDst[3]`, int `nDstStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned planar color not in place forward gamma correction.
- `NppStatus nppiGammaFwd_8u_IP3R` (`Npp8u *const pSrcDst[3]`, int `nSrcDstStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned planar color in place forward gamma correction.

GammaInv

Inverse gamma correction.

- `NppStatus nppiGammaInv_8u_C3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned packed color not in place inverse gamma correction.
- `NppStatus nppiGammaInv_8u_C3IR` (`Npp8u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned packed color in place inverse gamma correction.
- `NppStatus nppiGammaInv_8u_AC4R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
4 channel 8-bit unsigned packed color with alpha not in place inverse gamma correction.
- `NppStatus nppiGammaInv_8u_AC4IR` (`Npp8u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
4 channel 8-bit unsigned packed color with alpha in place inverse gamma correction.

- **NppStatus nppiGammaInv_8u_P3R** (const **Npp8u** *const *pSrc*[3], int *nSrcStep*, **Npp8u** **pDst*[3], int *nDstStep*, **NppiSize** *oSizeROI*)
3 channel 8-bit unsigned planar color not in place inverse gamma correction.
- **NppStatus nppiGammaInv_8u_IP3R** (**Npp8u** *const *pSrcDst*[3], int *nSrcDstStep*, **NppiSize** *oSizeROI*)
3 channel 8-bit unsigned planar color in place inverse gamma correction.

7.46.1 Detailed Description

Routines for correcting image color gamma.

7.46.2 Function Documentation

7.46.2.1 **NppStatus nppiGammaFwd_8u_AC4IR** (**Npp8u** **pSrcDst*, int *nSrcDstStep*, **NppiSize** *oSizeROI*)

4 channel 8-bit unsigned packed color with alpha in place forward gamma correction.

Parameters:

- pSrcDst* in place packed pixel format image pointer.
- nSrcDstStep* in place packed pixel format image line step.
- oSizeROI* [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.46.2.2 **NppStatus nppiGammaFwd_8u_AC4R** (const **Npp8u** **pSrc*, int *nSrcStep*, **Npp8u** **pDst*, int *nDstStep*, **NppiSize** *oSizeROI*)

4 channel 8-bit unsigned packed color with alpha not in place forward gamma correction.

Parameters:

- pSrc* [Source-Image Pointer](#).
- nSrcStep* [Source-Image Line Step](#).
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.46.2.3 NppStatus nppiGammaFwd_8u_C3IR (Npp8u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

3 channel 8-bit unsigned packed color in place forward gamma correction.

Parameters:

pSrcDst in place packed pixel image pointer.

nSrcDstStep in place packed pixel format image line step.

oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.46.2.4 NppStatus nppiGammaFwd_8u_C3R (const Npp8u * *pSrc*, int *nSrcStep*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

3 channel 8-bit unsigned packed color not in place forward gamma correction.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.46.2.5 NppStatus nppiGammaFwd_8u_IP3R (Npp8u *const *pSrcDst*[3], int *nSrcDstStep*, NppiSize *oSizeROI*)

3 channel 8-bit unsigned planar color in place forward gamma correction.

Parameters:

pSrcDst in place planar pixel format image pointer array.

nSrcDstStep in place planar pixel format image line step.

oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.46.2.6 NppStatus nppiGammaFwd_8u_P3R (const Npp8u *const pSrc[3], int nSrcStep, Npp8u *pDst[3], int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned planar color not in place forward gamma correction.

Parameters:

pSrc source planar pixel format image pointer array.
nSrcStep source planar pixel format image line step.
pDst destination planar pixel format image pointer array.
nDstStep destination planar pixel format image line step.
oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.46.2.7 NppStatus nppiGammaInv_8u_AC4IR (Npp8u *pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

4 channel 8-bit unsigned packed color with alpha in place inverse gamma correction.

Parameters:

pSrcDst in place packed pixel format image pointer.
nSrcDstStep in place packed pixel format image line step.
oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.46.2.8 NppStatus nppiGammaInv_8u_AC4R (const Npp8u *pSrc, int nSrcStep, Npp8u *pDst, int nDstStep, NppiSize oSizeROI)

4 channel 8-bit unsigned packed color with alpha not in place inverse gamma correction.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.46.2.9 NppStatus nppiGammaInv_8u_C3IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned packed color in place inverse gamma correction.

Parameters:

pSrcDst in place packed pixel format image pointer.
nSrcDstStep in place packed pixel format image line step.
oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.46.2.10 NppStatus nppiGammaInv_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned packed color not in place inverse gamma correction.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.46.2.11 NppStatus nppiGammaInv_8u_IP3R (Npp8u *const pSrcDst[3], int nSrcDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned planar color in place inverse gamma correction.

Parameters:

pSrcDst in place planar pixel format image pointer array.
nSrcDstStep in place planar pixel format image line step.
oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.46.2.12 `NppStatus nppiGammaInv_8u_P3R (const Npp8u *const pSrc[3], int nSrcStep, Npp8u *pDst[3], int nDstStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned planar color not in place inverse gamma correction.

Parameters:

pSrc source planar pixel format image pointer array.

nSrcStep source planar pixel format image line step.

pDst destination planar pixel format image pointer array.

nDstStep destination planar pixel format image line step.

oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.47 Complement Color Key

Routines for performing complement color key replacement.

CompColorKey

Complement color key replacement.

- `NppStatus nppiCompColorKey_8u_C1R` (const `Npp8u *pSrc1`, int `nSrc1Step`, const `Npp8u *pSrc2`, int `nSrc2Step`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `Npp8u nColorKeyConst`)
1 channel 8-bit unsigned packed color complement color key replacement of source image 1 by source image 2.
- `NppStatus nppiCompColorKey_8u_C3R` (const `Npp8u *pSrc1`, int `nSrc1Step`, const `Npp8u *pSrc2`, int `nSrc2Step`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `Npp8u nColorKeyConst[3]`)
3 channel 8-bit unsigned packed color complement color key replacement of source image 1 by source image 2.
- `NppStatus nppiCompColorKey_8u_C4R` (const `Npp8u *pSrc1`, int `nSrc1Step`, const `Npp8u *pSrc2`, int `nSrc2Step`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `Npp8u nColorKeyConst[4]`)
4 channel 8-bit unsigned packed color complement color key replacement of source image 1 by source image 2.
- `NppStatus nppiAlphaCompColorKey_8u_AC4R` (const `Npp8u *pSrc1`, int `nSrc1Step`, `Npp8u nAlpha1`, const `Npp8u *pSrc2`, int `nSrc2Step`, `Npp8u nAlpha2`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `Npp8u nColorKeyConst[4]`, `NppiAlphaOp nppAlphaOp`)
4 channel 8-bit unsigned packed color complement color key replacement of source image 1 by source image 2 with alpha blending.

7.47.1 Detailed Description

Routines for performing complement color key replacement.

7.47.2 Function Documentation

- 7.47.2.1 `NppStatus nppiAlphaCompColorKey_8u_AC4R` (const `Npp8u *pSrc1`, int `nSrc1Step`, `Npp8u nAlpha1`, const `Npp8u *pSrc2`, int `nSrc2Step`, `Npp8u nAlpha2`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `Npp8u nColorKeyConst[4]`, `NppiAlphaOp nppAlphaOp`)**

4 channel 8-bit unsigned packed color complement color key replacement of source image 1 by source image 2 with alpha blending.

Parameters:

- `pSrc1`* source1 packed pixel format image pointer.
- `nSrc1Step`* source1 packed pixel format image line step.
- `nAlpha1`* source1 image alpha opacity (0 - max channel pixel value).
- `pSrc2`* source2 packed pixel format image pointer.

nSrc2Step source2 packed pixel format image line step.
nAlpha2 source2 image alpha opacity (0 - max channel pixel value).
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oSizeROI [Region-of-Interest \(ROI\)](#).
nColorKeyConst color key constant array
nppAlphaOp NppiAlphaOp alpha compositing operation selector (excluding premul ops).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.47.2.2 NppStatus nppiCompColorKey_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, Npp8u nColorKeyConst)

1 channel 8-bit unsigned packed color complement color key replacement of source image 1 by source image 2.

Parameters:

pSrc1 source1 packed pixel format image pointer.
nSrc1Step source1 packed pixel format image line step.
pSrc2 source2 packed pixel format image pointer.
nSrc2Step source2 packed pixel format image line step.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oSizeROI [Region-of-Interest \(ROI\)](#).
nColorKeyConst color key constant

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.47.2.3 NppStatus nppiCompColorKey_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, Npp8u nColorKeyConst[3])

3 channel 8-bit unsigned packed color complement color key replacement of source image 1 by source image 2.

Parameters:

pSrc1 source1 packed pixel format image pointer.
nSrc1Step source1 packed pixel format image line step.
pSrc2 source2 packed pixel format image pointer.
nSrc2Step source2 packed pixel format image line step.

pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nColorKeyConst color key constant array

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.47.2.4 `NppStatus nppiCompColorKey_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, Npp8u nColorKeyConst[4])`

4 channel 8-bit unsigned packed color complement color key replacement of source image 1 by source image 2.

Parameters:

pSrc1 source1 packed pixel format image pointer.
nSrc1Step source1 packed pixel format image line step.
pSrc2 source2 packed pixel format image pointer.
nSrc2Step source2 packed pixel format image line step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nColorKeyConst color key constant array

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48 Color Processing

Routines for performing image color manipulation.

ColorTwist

Perform color twist pixel processing.

Color twist consists of applying the following formula to each image pixel using coefficients from the user supplied color twist host matrix array as follows where `dst[x]` and `src[x]` represent destination pixel and source pixel channel or plane `x`.

$$\begin{aligned} \text{dst}[0] &= \text{aTwist}[0][0] * \text{src}[0] + \text{aTwist}[0][1] * \text{src}[1] + \text{aTwist}[0][2] * \text{src}[2] + \text{aTwist}[0][3] \\ \text{dst}[1] &= \text{aTwist}[1][0] * \text{src}[0] + \text{aTwist}[1][1] * \text{src}[1] + \text{aTwist}[1][2] * \text{src}[2] + \text{aTwist}[1][3] \\ \text{dst}[2] &= \text{aTwist}[2][0] * \text{src}[0] + \text{aTwist}[2][1] * \text{src}[1] + \text{aTwist}[2][2] * \text{src}[2] + \text{aTwist}[2][3] \end{aligned}$$

- `NppStatus nppiColorTwist32f_8u_C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32f` aTwist[3][4])
3 channel 8-bit unsigned color twist.
- `NppStatus nppiColorTwist32f_8u_C3IR` (`Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32f` aTwist[3][4])
3 channel 8-bit unsigned in place color twist.
- `NppStatus nppiColorTwist32f_8u_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32f` aTwist[3][4])
4 channel 8-bit unsigned color twist, not affecting Alpha.
- `NppStatus nppiColorTwist32f_8u_AC4IR` (`Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32f` aTwist[3][4])
4 channel 8-bit unsigned in place color twist, not affecting Alpha.
- `NppStatus nppiColorTwist32f_8u_P3R` (const `Npp8u` *const pSrc[3], int nSrcStep, `Npp8u` *const pDst[3], int nDstStep, `NppiSize` oSizeROI, const `Npp32f` aTwist[3][4])
3 channel 8-bit unsigned planar color twist.
- `NppStatus nppiColorTwist32f_8u_IP3R` (`Npp8u` *const pSrcDst[3], int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32f` aTwist[3][4])
3 channel 8-bit unsigned planar in place color twist.
- `NppStatus nppiColorTwist32f_8s_C3R` (const `Npp8s` *pSrc, int nSrcStep, `Npp8s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32f` aTwist[3][4])
3 channel 8-bit signed color twist.
- `NppStatus nppiColorTwist32f_8s_C3IR` (`Npp8s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32f` aTwist[3][4])
3 channel 8-bit signed in place color twist.
- `NppStatus nppiColorTwist32f_8s_AC4R` (const `Npp8s` *pSrc, int nSrcStep, `Npp8s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32f` aTwist[3][4])
4 channel 8-bit signed color twist, not affecting Alpha.

- `NppStatus nppiColorTwist32f_8s_AC4IR` (`Npp8s *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp32f aTwist[3][4]`)
4 channel 8-bit signed in place color twist, not affecting Alpha.
- `NppStatus nppiColorTwist32f_8s_P3R` (`const Npp8s *const pSrc[3]`, `int nSrcStep`, `Npp8s *const pDst[3]`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp32f aTwist[3][4]`)
3 channel 8-bit signed planar color twist.
- `NppStatus nppiColorTwist32f_8s_IP3R` (`Npp8s *const pSrcDst[3]`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp32f aTwist[3][4]`)
3 channel 8-bit signed planar in place color twist.
- `NppStatus nppiColorTwist32f_16u_C3R` (`const Npp16u *pSrc`, `int nSrcStep`, `Npp16u *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp32f aTwist[3][4]`)
3 channel 16-bit unsigned color twist.
- `NppStatus nppiColorTwist32f_16u_C3IR` (`Npp16u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp32f aTwist[3][4]`)
3 channel 16-bit unsigned in place color twist.
- `NppStatus nppiColorTwist32f_16u_AC4R` (`const Npp16u *pSrc`, `int nSrcStep`, `Npp16u *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp32f aTwist[3][4]`)
4 channel 16-bit unsigned color twist, not affecting Alpha.
- `NppStatus nppiColorTwist32f_16u_AC4IR` (`Npp16u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp32f aTwist[3][4]`)
4 channel 16-bit unsigned in place color twist, not affecting Alpha.
- `NppStatus nppiColorTwist32f_16u_P3R` (`const Npp16u *const pSrc[3]`, `int nSrcStep`, `Npp16u *const pDst[3]`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp32f aTwist[3][4]`)
3 channel 16-bit unsigned planar color twist.
- `NppStatus nppiColorTwist32f_16u_IP3R` (`Npp16u *const pSrcDst[3]`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp32f aTwist[3][4]`)
3 channel 16-bit unsigned planar in place color twist.
- `NppStatus nppiColorTwist32f_16s_C3R` (`const Npp16s *pSrc`, `int nSrcStep`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp32f aTwist[3][4]`)
3 channel 16-bit signed color twist.
- `NppStatus nppiColorTwist32f_16s_C3IR` (`Npp16s *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp32f aTwist[3][4]`)
3 channel 16-bit signed in place color twist.
- `NppStatus nppiColorTwist32f_16s_AC4R` (`const Npp16s *pSrc`, `int nSrcStep`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp32f aTwist[3][4]`)
4 channel 16-bit signed color twist, not affecting Alpha.
- `NppStatus nppiColorTwist32f_16s_AC4IR` (`Npp16s *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp32f aTwist[3][4]`)

4 channel 16-bit signed in place color twist, not affecting Alpha.

- `NppStatus nppiColorTwist32f_16s_P3R` (const `Npp16s` *const pSrc[3], int nSrcStep, `Npp16s` *const pDst[3], int nDstStep, `NppiSize` oSizeROI, const `Npp32f` aTwist[3][4])
3 channel 16-bit signed planar color twist.
- `NppStatus nppiColorTwist32f_16s_IP3R` (`Npp16s` *const pSrcDst[3], int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32f` aTwist[3][4])
3 channel 16-bit signed planar in place color twist.
- `NppStatus nppiColorTwist_32f_C3R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32f` aTwist[3][4])
3 channel 32-bit floating point color twist.
- `NppStatus nppiColorTwist_32f_C3IR` (`Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32f` aTwist[3][4])
3 channel 32-bit floating point in place color twist.
- `NppStatus nppiColorTwist_32f_AC4R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32f` aTwist[3][4])
4 channel 32-bit floating point color twist, not affecting Alpha.
- `NppStatus nppiColorTwist_32f_AC4IR` (`Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32f` aTwist[3][4])
4 channel 32-bit floating point in place color twist, not affecting Alpha.
- `NppStatus nppiColorTwist_32f_P3R` (const `Npp32f` *const pSrc[3], int nSrcStep, `Npp32f` *const pDst[3], int nDstStep, `NppiSize` oSizeROI, const `Npp32f` aTwist[3][4])
3 channel 32-bit floating point planar color twist.
- `NppStatus nppiColorTwist_32f_IP3R` (`Npp32f` *const pSrcDst[3], int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32f` aTwist[3][4])
3 channel 32-bit floating point planar in place color twist.

ColorLUT

Perform image color processing using members of various types of color look up tables.

- `NppStatus nppiLUT_8u_C1R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32s` *pValues, const `Npp32s` *pLevels, int nLevels)
8-bit unsigned look-up-table color conversion.
- `NppStatus nppiLUT_8u_C1IR` (`Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32s` *pValues, const `Npp32s` *pLevels, int nLevels)
8-bit unsigned look-up-table in place color conversion.
- `NppStatus nppiLUT_8u_C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32s` *pValues[3], const `Npp32s` *pLevels[3], int nLevels[3])
3 channel 8-bit unsigned look-up-table color conversion.

- `NppStatus nppiLUT_8u_C3IR (Npp8u *pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s *pValues[3], const Npp32s *pLevels[3], int nLevels[3])`
3 channel 8-bit unsigned look-up-table in place color conversion.
- `NppStatus nppiLUT_8u_C4R (const Npp8u *pSrc, int nSrcStep, Npp8u *pDst, int nDstStep, NppiSize oSizeROI, const Npp32s *pValues[4], const Npp32s *pLevels[4], int nLevels[4])`
4 channel 8-bit unsigned look-up-table color conversion.
- `NppStatus nppiLUT_8u_C4IR (Npp8u *pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s *pValues[4], const Npp32s *pLevels[4], int nLevels[4])`
4 channel 8-bit unsigned look-up-table in place color conversion.
- `NppStatus nppiLUT_8u_AC4R (const Npp8u *pSrc, int nSrcStep, Npp8u *pDst, int nDstStep, NppiSize oSizeROI, const Npp32s *pValues[3], const Npp32s *pLevels[3], int nLevels[3])`
4 channel 8-bit unsigned look-up-table color conversion, not affecting Alpha.
- `NppStatus nppiLUT_8u_AC4IR (Npp8u *pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s *pValues[3], const Npp32s *pLevels[3], int nLevels[3])`
4 channel 8-bit unsigned look-up-table in place color conversion, not affecting Alpha.
- `NppStatus nppiLUT_16u_C1R (const Npp16u *pSrc, int nSrcStep, Npp16u *pDst, int nDstStep, NppiSize oSizeROI, const Npp32s *pValues, const Npp32s *pLevels, int nLevels)`
16-bit unsigned look-up-table color conversion.
- `NppStatus nppiLUT_16u_C1IR (Npp16u *pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s *pValues, const Npp32s *pLevels, int nLevels)`
16-bit unsigned look-up-table in place color conversion.
- `NppStatus nppiLUT_16u_C3R (const Npp16u *pSrc, int nSrcStep, Npp16u *pDst, int nDstStep, NppiSize oSizeROI, const Npp32s *pValues[3], const Npp32s *pLevels[3], int nLevels[3])`
3 channel 16-bit unsigned look-up-table color conversion.
- `NppStatus nppiLUT_16u_C3IR (Npp16u *pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s *pValues[3], const Npp32s *pLevels[3], int nLevels[3])`
3 channel 16-bit unsigned look-up-table in place color conversion.
- `NppStatus nppiLUT_16u_C4R (const Npp16u *pSrc, int nSrcStep, Npp16u *pDst, int nDstStep, NppiSize oSizeROI, const Npp32s *pValues[4], const Npp32s *pLevels[4], int nLevels[4])`
4 channel 16-bit unsigned look-up-table color conversion.
- `NppStatus nppiLUT_16u_C4IR (Npp16u *pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s *pValues[4], const Npp32s *pLevels[4], int nLevels[4])`
4 channel 16-bit unsigned look-up-table in place color conversion.
- `NppStatus nppiLUT_16u_AC4R (const Npp16u *pSrc, int nSrcStep, Npp16u *pDst, int nDstStep, NppiSize oSizeROI, const Npp32s *pValues[3], const Npp32s *pLevels[3], int nLevels[3])`
4 channel 16-bit unsigned look-up-table color conversion, not affecting Alpha.
- `NppStatus nppiLUT_16u_AC4IR (Npp16u *pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s *pValues[3], const Npp32s *pLevels[3], int nLevels[3])`

4 channel 16-bit unsigned look-up-table in place color conversion, not affecting Alpha.

- `NppStatus nppiLUT_16s_C1R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32s *pValues`, const `Npp32s *pLevels`, int `nLevels`)

16-bit signed look-up-table color conversion.

- `NppStatus nppiLUT_16s_C1IR` (`Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, const `Npp32s *pValues`, const `Npp32s *pLevels`, int `nLevels`)

16-bit signed look-up-table in place color conversion.

- `NppStatus nppiLUT_16s_C3R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32s *pValues[3]`, const `Npp32s *pLevels[3]`, int `nLevels[3]`)

3 channel 16-bit signed look-up-table color conversion.

- `NppStatus nppiLUT_16s_C3IR` (`Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, const `Npp32s *pValues[3]`, const `Npp32s *pLevels[3]`, int `nLevels[3]`)

3 channel 16-bit signed look-up-table in place color conversion.

- `NppStatus nppiLUT_16s_C4R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32s *pValues[4]`, const `Npp32s *pLevels[4]`, int `nLevels[4]`)

4 channel 16-bit signed look-up-table color conversion.

- `NppStatus nppiLUT_16s_C4IR` (`Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, const `Npp32s *pValues[4]`, const `Npp32s *pLevels[4]`, int `nLevels[4]`)

4 channel 16-bit signed look-up-table in place color conversion.

- `NppStatus nppiLUT_16s_AC4R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32s *pValues[3]`, const `Npp32s *pLevels[3]`, int `nLevels[3]`)

4 channel 16-bit signed look-up-table color conversion, not affecting Alpha.

- `NppStatus nppiLUT_16s_AC4IR` (`Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, const `Npp32s *pValues[3]`, const `Npp32s *pLevels[3]`, int `nLevels[3]`)

4 channel 16-bit signed look-up-table in place color conversion, not affecting Alpha.

- `NppStatus nppiLUT_32f_C1R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pValues`, const `Npp32f *pLevels`, int `nLevels`)

32-bit floating point look-up-table color conversion.

- `NppStatus nppiLUT_32f_C1IR` (`Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, const `Npp32f *pValues`, const `Npp32f *pLevels`, int `nLevels`)

32-bit floating point look-up-table in place color conversion.

- `NppStatus nppiLUT_32f_C3R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pValues[3]`, const `Npp32f *pLevels[3]`, int `nLevels[3]`)

3 channel 32-bit floating point look-up-table color conversion.

- `NppStatus nppiLUT_32f_C3IR` (`Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, const `Npp32f *pValues[3]`, const `Npp32f *pLevels[3]`, int `nLevels[3]`)

3 channel 32-bit floating point look-up-table in place color conversion.

- `NppStatus nppiLUT_32f_C4R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pValues[4]`, const `Npp32f *pLevels[4]`, int `nLevels[4]`)
4 channel 32-bit floating point look-up-table color conversion.
- `NppStatus nppiLUT_32f_C4IR` (`Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, const `Npp32f *pValues[4]`, const `Npp32f *pLevels[4]`, int `nLevels[4]`)
4 channel 32-bit floating point look-up-table in place color conversion.
- `NppStatus nppiLUT_32f_AC4R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pValues[3]`, const `Npp32f *pLevels[3]`, int `nLevels[3]`)
4 channel 32-bit floating point look-up-table color conversion, not affecting Alpha.
- `NppStatus nppiLUT_32f_AC4IR` (`Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, const `Npp32f *pValues[3]`, const `Npp32f *pLevels[3]`, int `nLevels[3]`)
4 channel 32-bit floating point look-up-table in place color conversion, not affecting Alpha.

ColorLUT_Linear

Perform image color processing using linear interpolation between members of various types of color look up tables.

- `NppStatus nppiLUT_Linear_8u_C1R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32s *pValues`, const `Npp32s *pLevels`, int `nLevels`)
8-bit unsigned linear interpolated look-up-table color conversion.
- `NppStatus nppiLUT_Linear_8u_C1IR` (`Npp8u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, const `Npp32s *pValues`, const `Npp32s *pLevels`, int `nLevels`)
8-bit unsigned linear interpolated look-up-table in place color conversion.
- `NppStatus nppiLUT_Linear_8u_C3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32s *pValues[3]`, const `Npp32s *pLevels[3]`, int `nLevels[3]`)
3 channel 8-bit unsigned linear interpolated look-up-table color conversion.
- `NppStatus nppiLUT_Linear_8u_C3IR` (`Npp8u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, const `Npp32s *pValues[3]`, const `Npp32s *pLevels[3]`, int `nLevels[3]`)
3 channel 8-bit unsigned linear interpolated look-up-table in place color conversion.
- `NppStatus nppiLUT_Linear_8u_C4R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32s *pValues[4]`, const `Npp32s *pLevels[4]`, int `nLevels[4]`)
4 channel 8-bit unsigned linear interpolated look-up-table color conversion.
- `NppStatus nppiLUT_Linear_8u_C4IR` (`Npp8u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, const `Npp32s *pValues[4]`, const `Npp32s *pLevels[4]`, int `nLevels[4]`)
4 channel 8-bit unsigned linear interpolated look-up-table in place color conversion.
- `NppStatus nppiLUT_Linear_8u_AC4R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32s *pValues[3]`, const `Npp32s *pLevels[3]`, int `nLevels[3]`)
4 channel 8-bit unsigned linear interpolated look-up-table color conversion, not affecting Alpha.

- `NppStatus nppiLUT_Linear_8u_AC4IR` (`Npp8u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp32s *pValues[3]`, `const Npp32s *pLevels[3]`, `int nLevels[3]`)
4 channel 8-bit unsigned linear interpolated look-up-table in place color conversion, not affecting Alpha.
- `NppStatus nppiLUT_Linear_16u_C1R` (`const Npp16u *pSrc`, `int nSrcStep`, `Npp16u *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp32s *pValues`, `const Npp32s *pLevels`, `int nLevels`)
16-bit unsigned look-up-table color conversion.
- `NppStatus nppiLUT_Linear_16u_C1IR` (`Npp16u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp32s *pValues`, `const Npp32s *pLevels`, `int nLevels`)
16-bit unsigned look-up-table in place color conversion.
- `NppStatus nppiLUT_Linear_16u_C3R` (`const Npp16u *pSrc`, `int nSrcStep`, `Npp16u *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp32s *pValues[3]`, `const Npp32s *pLevels[3]`, `int nLevels[3]`)
3 channel 16-bit unsigned look-up-table color conversion.
- `NppStatus nppiLUT_Linear_16u_C3IR` (`Npp16u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp32s *pValues[3]`, `const Npp32s *pLevels[3]`, `int nLevels[3]`)
3 channel 16-bit unsigned look-up-table in place color conversion.
- `NppStatus nppiLUT_Linear_16u_C4R` (`const Npp16u *pSrc`, `int nSrcStep`, `Npp16u *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp32s *pValues[4]`, `const Npp32s *pLevels[4]`, `int nLevels[4]`)
4 channel 16-bit unsigned look-up-table color conversion.
- `NppStatus nppiLUT_Linear_16u_C4IR` (`Npp16u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp32s *pValues[4]`, `const Npp32s *pLevels[4]`, `int nLevels[4]`)
4 channel 16-bit unsigned look-up-table in place color conversion.
- `NppStatus nppiLUT_Linear_16u_AC4R` (`const Npp16u *pSrc`, `int nSrcStep`, `Npp16u *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp32s *pValues[3]`, `const Npp32s *pLevels[3]`, `int nLevels[3]`)
4 channel 16-bit unsigned look-up-table color conversion, not affecting Alpha.
- `NppStatus nppiLUT_Linear_16u_AC4IR` (`Npp16u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp32s *pValues[3]`, `const Npp32s *pLevels[3]`, `int nLevels[3]`)
4 channel 16-bit unsigned look-up-table in place color conversion, not affecting Alpha.
- `NppStatus nppiLUT_Linear_16s_C1R` (`const Npp16s *pSrc`, `int nSrcStep`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp32s *pValues`, `const Npp32s *pLevels`, `int nLevels`)
16-bit signed look-up-table color conversion.
- `NppStatus nppiLUT_Linear_16s_C1IR` (`Npp16s *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp32s *pValues`, `const Npp32s *pLevels`, `int nLevels`)
16-bit signed look-up-table in place color conversion.
- `NppStatus nppiLUT_Linear_16s_C3R` (`const Npp16s *pSrc`, `int nSrcStep`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp32s *pValues[3]`, `const Npp32s *pLevels[3]`, `int nLevels[3]`)
3 channel 16-bit signed look-up-table color conversion.
- `NppStatus nppiLUT_Linear_16s_C3IR` (`Npp16s *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp32s *pValues[3]`, `const Npp32s *pLevels[3]`, `int nLevels[3]`)
3 channel 16-bit signed look-up-table in place color conversion.

- `NppStatus nppiLUT_Linear_16s_C4R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32s *pValues[4]`, const `Npp32s *pLevels[4]`, int `nLevels[4]`)
4 channel 16-bit signed look-up-table color conversion.
- `NppStatus nppiLUT_Linear_16s_C4IR` (`Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, const `Npp32s *pValues[4]`, const `Npp32s *pLevels[4]`, int `nLevels[4]`)
4 channel 16-bit signed look-up-table in place color conversion.
- `NppStatus nppiLUT_Linear_16s_AC4R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32s *pValues[3]`, const `Npp32s *pLevels[3]`, int `nLevels[3]`)
4 channel 16-bit signed look-up-table color conversion, not affecting Alpha.
- `NppStatus nppiLUT_Linear_16s_AC4IR` (`Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, const `Npp32s *pValues[3]`, const `Npp32s *pLevels[3]`, int `nLevels[3]`)
4 channel 16-bit signed look-up-table in place color conversion, not affecting Alpha.
- `NppStatus nppiLUT_Linear_32f_C1R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pValues`, const `Npp32f *pLevels`, int `nLevels`)
32-bit floating point look-up-table color conversion.
- `NppStatus nppiLUT_Linear_32f_C1IR` (`Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, const `Npp32f *pValues`, const `Npp32f *pLevels`, int `nLevels`)
32-bit floating point look-up-table in place color conversion.
- `NppStatus nppiLUT_Linear_32f_C3R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pValues[3]`, const `Npp32f *pLevels[3]`, int `nLevels[3]`)
3 channel 32-bit floating point look-up-table color conversion.
- `NppStatus nppiLUT_Linear_32f_C3IR` (`Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, const `Npp32f *pValues[3]`, const `Npp32f *pLevels[3]`, int `nLevels[3]`)
3 channel 32-bit floating point look-up-table in place color conversion.
- `NppStatus nppiLUT_Linear_32f_C4R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pValues[4]`, const `Npp32f *pLevels[4]`, int `nLevels[4]`)
4 channel 32-bit floating point look-up-table color conversion.
- `NppStatus nppiLUT_Linear_32f_C4IR` (`Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, const `Npp32f *pValues[4]`, const `Npp32f *pLevels[4]`, int `nLevels[4]`)
4 channel 32-bit floating point look-up-table in place color conversion.
- `NppStatus nppiLUT_Linear_32f_AC4R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pValues[3]`, const `Npp32f *pLevels[3]`, int `nLevels[3]`)
4 channel 32-bit floating point look-up-table color conversion, not affecting Alpha.
- `NppStatus nppiLUT_Linear_32f_AC4IR` (`Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, const `Npp32f *pValues[3]`, const `Npp32f *pLevels[3]`, int `nLevels[3]`)
4 channel 32-bit floating point look-up-table in place color conversion, not affecting Alpha.

ColorLUT_Cubic

Perform image color processing using linear interpolation between members of various types of color look up tables.

- **NppStatus nppiLUT_Cubic_8u_C1R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp32s** *pValues, const **Npp32s** *pLevels, int nLevels)
8-bit unsigned cubic interpolated look-up-table color conversion.
- **NppStatus nppiLUT_Cubic_8u_C1IR** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, const **Npp32s** *pValues, const **Npp32s** *pLevels, int nLevels)
8-bit unsigned cubic interpolated look-up-table in place color conversion.
- **NppStatus nppiLUT_Cubic_8u_C3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp32s** *pValues[3], const **Npp32s** *pLevels[3], int nLevels[3])
3 channel 8-bit unsigned cubic interpolated look-up-table color conversion.
- **NppStatus nppiLUT_Cubic_8u_C3IR** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, const **Npp32s** *pValues[3], const **Npp32s** *pLevels[3], int nLevels[3])
3 channel 8-bit unsigned cubic interpolated look-up-table in place color conversion.
- **NppStatus nppiLUT_Cubic_8u_C4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp32s** *pValues[4], const **Npp32s** *pLevels[4], int nLevels[4])
4 channel 8-bit unsigned cubic interpolated look-up-table color conversion.
- **NppStatus nppiLUT_Cubic_8u_C4IR** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, const **Npp32s** *pValues[4], const **Npp32s** *pLevels[4], int nLevels[4])
4 channel 8-bit unsigned cubic interpolated look-up-table in place color conversion.
- **NppStatus nppiLUT_Cubic_8u_AC4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp32s** *pValues[3], const **Npp32s** *pLevels[3], int nLevels[3])
4 channel 8-bit unsigned cubic interpolated look-up-table color conversion, not affecting Alpha.
- **NppStatus nppiLUT_Cubic_8u_AC4IR** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, const **Npp32s** *pValues[3], const **Npp32s** *pLevels[3], int nLevels[3])
4 channel 8-bit unsigned cubic interpolated look-up-table in place color conversion, not affecting Alpha.
- **NppStatus nppiLUT_Cubic_16u_C1R** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp32s** *pValues, const **Npp32s** *pLevels, int nLevels)
16-bit unsigned look-up-table color conversion.
- **NppStatus nppiLUT_Cubic_16u_C1IR** (**Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, const **Npp32s** *pValues, const **Npp32s** *pLevels, int nLevels)
16-bit unsigned look-up-table in place color conversion.
- **NppStatus nppiLUT_Cubic_16u_C3R** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp32s** *pValues[3], const **Npp32s** *pLevels[3], int nLevels[3])
3 channel 16-bit unsigned look-up-table color conversion.
- **NppStatus nppiLUT_Cubic_16u_C3IR** (**Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, const **Npp32s** *pValues[3], const **Npp32s** *pLevels[3], int nLevels[3])

3 channel 16-bit unsigned look-up-table in place color conversion.

- `NppStatus nppiLUT_Cubic_16u_C4R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32s` *pValues[4], const `Npp32s` *pLevels[4], int nLevels[4])

4 channel 16-bit unsigned look-up-table color conversion.

- `NppStatus nppiLUT_Cubic_16u_C4IR` (`Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32s` *pValues[4], const `Npp32s` *pLevels[4], int nLevels[4])

4 channel 16-bit unsigned look-up-table in place color conversion.

- `NppStatus nppiLUT_Cubic_16u_AC4R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32s` *pValues[3], const `Npp32s` *pLevels[3], int nLevels[3])

4 channel 16-bit unsigned look-up-table color conversion, not affecting Alpha.

- `NppStatus nppiLUT_Cubic_16u_AC4IR` (`Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32s` *pValues[3], const `Npp32s` *pLevels[3], int nLevels[3])

4 channel 16-bit unsigned look-up-table in place color conversion, not affecting Alpha.

- `NppStatus nppiLUT_Cubic_16s_C1R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32s` *pValues, const `Npp32s` *pLevels, int nLevels)

16-bit signed look-up-table color conversion.

- `NppStatus nppiLUT_Cubic_16s_C1IR` (`Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32s` *pValues, const `Npp32s` *pLevels, int nLevels)

16-bit signed look-up-table in place color conversion.

- `NppStatus nppiLUT_Cubic_16s_C3R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32s` *pValues[3], const `Npp32s` *pLevels[3], int nLevels[3])

3 channel 16-bit signed look-up-table color conversion.

- `NppStatus nppiLUT_Cubic_16s_C3IR` (`Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32s` *pValues[3], const `Npp32s` *pLevels[3], int nLevels[3])

3 channel 16-bit signed look-up-table in place color conversion.

- `NppStatus nppiLUT_Cubic_16s_C4R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32s` *pValues[4], const `Npp32s` *pLevels[4], int nLevels[4])

4 channel 16-bit signed look-up-table color conversion.

- `NppStatus nppiLUT_Cubic_16s_C4IR` (`Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32s` *pValues[4], const `Npp32s` *pLevels[4], int nLevels[4])

4 channel 16-bit signed look-up-table in place color conversion.

- `NppStatus nppiLUT_Cubic_16s_AC4R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32s` *pValues[3], const `Npp32s` *pLevels[3], int nLevels[3])

4 channel 16-bit signed look-up-table color conversion, not affecting Alpha.

- `NppStatus nppiLUT_Cubic_16s_AC4IR` (`Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32s` *pValues[3], const `Npp32s` *pLevels[3], int nLevels[3])

4 channel 16-bit signed look-up-table in place color conversion, not affecting Alpha.

- **NppStatus nppiLUT_Cubic_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp32f** *pValues, const **Npp32f** *pLevels, int nLevels)
32-bit floating point look-up-table color conversion.
- **NppStatus nppiLUT_Cubic_32f_C1IR** (**Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, const **Npp32f** *pValues, const **Npp32f** *pLevels, int nLevels)
32-bit floating point look-up-table in place color conversion.
- **NppStatus nppiLUT_Cubic_32f_C3R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp32f** *pValues[3], const **Npp32f** *pLevels[3], int nLevels[3])
3 channel 32-bit floating point look-up-table color conversion.
- **NppStatus nppiLUT_Cubic_32f_C3IR** (**Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, const **Npp32f** *pValues[3], const **Npp32f** *pLevels[3], int nLevels[3])
3 channel 32-bit floating point look-up-table in place color conversion.
- **NppStatus nppiLUT_Cubic_32f_C4R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp32f** *pValues[4], const **Npp32f** *pLevels[4], int nLevels[4])
4 channel 32-bit floating point look-up-table color conversion.
- **NppStatus nppiLUT_Cubic_32f_C4IR** (**Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, const **Npp32f** *pValues[4], const **Npp32f** *pLevels[4], int nLevels[4])
4 channel 32-bit floating point look-up-table in place color conversion.
- **NppStatus nppiLUT_Cubic_32f_AC4R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp32f** *pValues[3], const **Npp32f** *pLevels[3], int nLevels[3])
4 channel 32-bit floating point look-up-table color conversion, not affecting Alpha.
- **NppStatus nppiLUT_Cubic_32f_AC4IR** (**Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, const **Npp32f** *pValues[3], const **Npp32f** *pLevels[3], int nLevels[3])
4 channel 32-bit floating point look-up-table in place color conversion, not affecting Alpha.

ColorLUTPalette

Perform image color processing using various types of bit range restricted palette color look up tables.

- **NppStatus nppiLUTPalette_8u_C1R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp8u** *pTable, int nBitSize)
One channel 8-bit unsigned bit range restricted palette look-up-table color conversion.
- **NppStatus nppiLUTPalette_8u24u_C1R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp8u** *pTable, int nBitSize)
One channel 8-bit unsigned bit range restricted 24-bit palette look-up-table color conversion with 24-bit destination output per pixel.
- **NppStatus nppiLUTPalette_8u32u_C1R** (const **Npp8u** *pSrc, int nSrcStep, **Npp32u** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp32u** *pTable, int nBitSize)
One channel 8-bit unsigned bit range restricted 32-bit palette look-up-table color conversion with 32-bit destination output per pixel.

- `NppStatus nppiLUTPalette_8u_C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pTables[3], int nBitSize)
Three channel 8-bit unsigned bit range restricted palette look-up-table color conversion.
- `NppStatus nppiLUTPalette_8u_C4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pTables[4], int nBitSize)
Four channel 8-bit unsigned bit range restricted palette look-up-table color conversion.
- `NppStatus nppiLUTPalette_8u_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pTables[3], int nBitSize)
Four channel 8-bit unsigned bit range restricted palette look-up-table color conversion, not affecting Alpha.
- `NppStatus nppiLUTPalette_16u_C1R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16u` *pTable, int nBitSize)
One channel 16-bit unsigned bit range restricted palette look-up-table color conversion.
- `NppStatus nppiLUTPalette_16u8u_C1R` (const `Npp16u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pTable, int nBitSize)
One channel 16-bit unsigned bit range restricted 8-bit unsigned palette look-up-table color conversion with 8-bit unsigned destination output per pixel.
- `NppStatus nppiLUTPalette_16u24u_C1R` (const `Npp16u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pTable, int nBitSize)
One channel 16-bit unsigned bit range restricted 24-bit unsigned palette look-up-table color conversion with 24-bit unsigned destination output per pixel.
- `NppStatus nppiLUTPalette_16u32u_C1R` (const `Npp16u` *pSrc, int nSrcStep, `Npp32u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32u` *pTable, int nBitSize)
One channel 16-bit unsigned bit range restricted 32-bit palette look-up-table color conversion with 32-bit unsigned destination output per pixel.
- `NppStatus nppiLUTPalette_16u_C3R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16u` *pTables[3], int nBitSize)
Three channel 16-bit unsigned bit range restricted palette look-up-table color conversion.
- `NppStatus nppiLUTPalette_16u_C4R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16u` *pTables[4], int nBitSize)
Four channel 16-bit unsigned bit range restricted palette look-up-table color conversion.
- `NppStatus nppiLUTPalette_16u_AC4R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16u` *pTables[3], int nBitSize)
Four channel 16-bit unsigned bit range restricted palette look-up-table color conversion, not affecting Alpha.
- `NppStatus nppiLUTPaletteSwap_8u_C3A0C4R` (const `Npp8u` *pSrc, int nSrcStep, int nAlphaValue, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pTables[3], int nBitSize)
Three channel 8-bit unsigned source bit range restricted palette look-up-table color conversion to four channel 8-bit unsigned destination output with alpha.

- `NppStatus nppiLUTPaletteSwap_16u_C3A0C4R` (const `Npp16u *pSrc`, int `nSrcStep`, int `nAlphaValue`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp16u *pTables[3]`, int `nBitSize`)

Three channel 16-bit unsigned source bit range restricted palette look-up-table color conversion to four channel 16-bit unsigned destination output with alpha.

7.48.1 Detailed Description

Routines for performing image color manipulation.

7.48.2 Function Documentation

- 7.48.2.1** `NppStatus nppiColorTwist32f_16s_AC4IR` (`Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, const `Npp32f aTwist[3][4]`)

4 channel 16-bit signed in place color twist, not affecting Alpha.

An input color twist matrix with floating-point coefficient values is applied with in ROI. Alpha channel is the last channel and is not processed.

Parameters:

pSrcDst in place packed pixel format image pointer.

nSrcDstStep in place packed pixel format image line step.

oSizeROI [Region-of-Interest \(ROI\)](#).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- 7.48.2.2** `NppStatus nppiColorTwist32f_16s_AC4R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f aTwist[3][4]`)

4 channel 16-bit signed color twist, not affecting Alpha.

An input color twist matrix with floating-point coefficient values is applied with in ROI. Alpha channel is the last channel and is not processed.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.3 `NppStatus nppiColorTwist32f_16s_C3IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])`

3 channel 16-bit signed in place color twist.

An input color twist matrix with floating-point coefficient values is applied within ROI.

Parameters:

pSrcDst in place packed pixel format image pointer.

nSrcDstStep in place packed pixel format image line step.

oSizeROI [Region-of-Interest \(ROI\)](#).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.4 `NppStatus nppiColorTwist32f_16s_C3R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])`

3 channel 16-bit signed color twist.

An input color twist matrix with floating-point coefficient values is applied within ROI.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.5 `NppStatus nppiColorTwist32f_16s_IP3R (Npp16s *const pSrcDst[3], int nSrcDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])`

3 channel 16-bit signed planar in place color twist.

An input color twist matrix with floating-point coefficient values is applied within ROI.

Parameters:

pSrcDst in place planar pixel format image pointer array, one pointer per plane.

nSrcDstStep in place planar pixel format image line step.

oSizeROI [Region-of-Interest \(ROI\)](#).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.6 NppStatus nppiColorTwist32f_16s_P3R (const Npp16s *const pSrc[3], int nSrcStep, Npp16s *const pDst[3], int nDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])

3 channel 16-bit signed planar color twist.

An input color twist matrix with floating-point coefficient values is applied within ROI.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.7 NppStatus nppiColorTwist32f_16u_AC4IR (Npp16u *pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])

4 channel 16-bit unsigned in place color twist, not affecting Alpha.

An input color twist matrix with floating-point coefficient values is applied with in ROI. Alpha channel is the last channel and is not processed.

Parameters:

pSrcDst in place packed pixel format image pointer.

nSrcDstStep in place packed pixel format image line step.

oSizeROI Region-of-Interest (ROI).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.8 NppStatus nppiColorTwist32f_16u_AC4R (const Npp16u *pSrc, int nSrcStep, Npp16u *pDst, int nDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])

4 channel 16-bit unsigned color twist, not affecting Alpha.

An input color twist matrix with floating-point coefficient values is applied with in ROI. Alpha channel is the last channel and is not processed.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.9 NppStatus nppiColorTwist32f_16u_C3IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])

3 channel 16-bit unsigned in place color twist.

An input color twist matrix with floating-point coefficient values is applied within ROI.

Parameters:

pSrcDst in place packed pixel format image pointer.

nSrcDstStep in place packed pixel format image line step.

oSizeROI [Region-of-Interest \(ROI\)](#).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.10 NppStatus nppiColorTwist32f_16u_C3R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])

3 channel 16-bit unsigned color twist.

An input color twist matrix with floating-point coefficient values is applied within ROI.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI [Region-of-Interest \(ROI\)](#).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.11 NppStatus nppiColorTwist32f_16u_IP3R (Npp16u *const pSrcDst[3], int nSrcDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])

3 channel 16-bit unsigned planar in place color twist.

An input color twist matrix with floating-point coefficient values is applied within ROI.

Parameters:

pSrcDst in place planar pixel format image pointer array, one pointer per plane.

nSrcDstStep in place planar pixel format image line step.

oSizeROI [Region-of-Interest \(ROI\)](#).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.12 NppStatus nppiColorTwist32f_16u_P3R (const Npp16u *const pSrc[3], int nSrcStep, Npp16u *const pDst[3], int nDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])

3 channel 16-bit unsigned planar color twist.

An input color twist matrix with floating-point coefficient values is applied within ROI.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.13 NppStatus nppiColorTwist32f_8s_AC4IR (Npp8s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])

4 channel 8-bit signed in place color twist, not affecting Alpha.

An input color twist matrix with floating-point coefficient values is applied with in ROI. Alpha channel is the last channel and is not processed.

Parameters:

pSrcDst in place packed pixel format image pointer.

nSrcDstStep in place packed pixel format image line step.

oSizeROI [Region-of-Interest \(ROI\)](#).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.14 NppStatus nppiColorTwist32f_8s_AC4R (const Npp8s * pSrc, int nSrcStep, Npp8s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])

4 channel 8-bit signed color twist, not affecting Alpha.

An input color twist matrix with floating-point coefficient values is applied with in ROI. Alpha channel is the last channel and is not processed.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.15 NppStatus nppiColorTwist32f_8s_C3IR (Npp8s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])

3 channel 8-bit signed in place color twist.

An input color twist matrix with floating-point coefficient values is applied within ROI.

Parameters:

pSrcDst in place packed pixel format image pointer.

nSrcDstStep in place packed pixel format image line step.

oSizeROI Region-of-Interest (ROI).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.16 NppStatus nppiColorTwist32f_8s_C3R (const Npp8s * pSrc, int nSrcStep, Npp8s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])

3 channel 8-bit signed color twist.

An input color twist matrix with floating-point coefficient values is applied within ROI.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.17 NppStatus nppiColorTwist32f_8s_IP3R (Npp8s *const pSrcDst[3], int nSrcDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])

3 channel 8-bit signed planar in place color twist.

An input color twist matrix with floating-point coefficient values is applied within ROI.

Parameters:

pSrcDst in place planar pixel format image pointer array, one pointer per plane.
nSrcDstStep in place planar pixel format image line step.
oSizeROI [Region-of-Interest \(ROI\)](#).
aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.18 NppStatus nppiColorTwist32f_8s_P3R (const Npp8s *const pSrc[3], int nSrcStep, Npp8s *const pDst[3], int nDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])

3 channel 8-bit signed planar color twist.

An input color twist matrix with floating-point coefficient values is applied within ROI.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI [Region-of-Interest \(ROI\)](#).
aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.19 `NppStatus nppiColorTwist32f_8u_AC4IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])`

4 channel 8-bit unsigned in place color twist, not affecting Alpha.

An input color twist matrix with floating-point coefficient values is applied with in ROI. Alpha channel is the last channel and is not processed.

Parameters:

pSrcDst in place packed pixel format image pointer.

nSrcDstStep in place packed pixel format image line step.

oSizeROI [Region-of-Interest \(ROI\)](#).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.20 `NppStatus nppiColorTwist32f_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])`

4 channel 8-bit unsigned color twist, not affecting Alpha.

An input color twist matrix with floating-point coefficient values is applied with in ROI. Alpha channel is the last channel and is not processed.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.21 `NppStatus nppiColorTwist32f_8u_C3IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])`

3 channel 8-bit unsigned in place color twist.

An input color twist matrix with floating-point coefficient values is applied within ROI.

Parameters:

pSrcDst in place packed pixel format image pointer.

nSrcDstStep in place packed pixel format image line step.

oSizeROI Region-of-Interest (ROI).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.22 `NppStatus nppiColorTwist32f_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])`

3 channel 8-bit unsigned color twist.

An input color twist matrix with floating-point coefficient values is applied within ROI.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.23 `NppStatus nppiColorTwist32f_8u_IP3R (Npp8u *const pSrcDst[3], int nSrcDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])`

3 channel 8-bit unsigned planar in place color twist.

An input color twist matrix with floating-point coefficient values is applied within ROI.

Parameters:

pSrcDst in place planar pixel format image pointer array, one pointer per plane.

nSrcDstStep in place planar pixel format image line step.

oSizeROI Region-of-Interest (ROI).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.24 `NppStatus nppiColorTwist32f_8u_P3R (const Npp8u *const pSrc[3], int nSrcStep, Npp8u *const pDst[3], int nDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])`

3 channel 8-bit unsigned planar color twist.

An input color twist matrix with floating-point coefficient values is applied within ROI.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.25 `NppStatus nppiColorTwist_32f_AC4IR (Npp32f *pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])`

4 channel 32-bit floating point in place color twist, not affecting Alpha.

An input color twist matrix with floating-point coefficient values is applied with in ROI. Alpha channel is the last channel and is not processed.

Parameters:

pSrcDst in place packed pixel format image pointer.

nSrcDstStep in place packed pixel format image line step.

oSizeROI Region-of-Interest (ROI).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.26 `NppStatus nppiColorTwist_32f_AC4R (const Npp32f *pSrc, int nSrcStep, Npp32f *pDst, int nDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])`

4 channel 32-bit floating point color twist, not affecting Alpha.

An input color twist matrix with floating-point coefficient values is applied with in ROI. Alpha channel is the last channel and is not processed.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.27 `NppStatus nppiColorTwist_32f_C3IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])`

3 channel 32-bit floating point in place color twist.

An input color twist matrix with floating-point coefficient values is applied within ROI.

Parameters:

pSrcDst in place packed pixel format image pointer.

nSrcDstStep in place packed pixel format image line step.

oSizeROI [Region-of-Interest \(ROI\)](#).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.28 `NppStatus nppiColorTwist_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])`

3 channel 32-bit floating point color twist.

An input color twist matrix with floating-point coefficient values is applied within ROI.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.29 NppStatus nppiColorTwist_32f_IP3R (Npp32f *const pSrcDst[3], int nSrcDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])

3 channel 32-bit floating point planar in place color twist.

An input color twist matrix with floating-point coefficient values is applied within ROI.

Parameters:

pSrcDst in place planar pixel format image pointer array, one pointer per plane.

nSrcDstStep in place planar pixel format image line step.

oSizeROI [Region-of-Interest \(ROI\)](#).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.30 NppStatus nppiColorTwist_32f_P3R (const Npp32f *const pSrc[3], int nSrcStep, Npp32f *const pDst[3], int nDstStep, NppiSize oSizeROI, const Npp32f aTwist[3][4])

3 channel 32-bit floating point planar color twist.

An input color twist matrix with floating-point coefficient values is applied within ROI.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aTwist The color twist matrix with floating-point coefficient values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.48.2.31 NppStatus nppiLUT_16s_AC4IR (Npp16s *pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s *pValues[3], const Npp32s *pLevels[3], int nLevels[3])

4 channel 16-bit signed look-up-table in place color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points using no interpolation. Alpha channel is the last channel and is not processed.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.32 `NppStatus nppiLUT_16s_AC4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

4 channel 16-bit signed look-up-table color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points using no interpolation. Alpha channel is the last channel and is not processed.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.33 `NppStatus nppiLUT_16s_C1IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues, const Npp32s * pLevels, int nLevels)`

16-bit signed look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points with no interpolation.

Parameters:

- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- pValues* Pointer to an array of user defined OUTPUT values (this is a device memory pointer)
- pLevels* Pointer to an array of user defined INPUT values (this is a device memory pointer)
- nLevels* Number of user defined number of input/output mapping points (levels)

Returns:

Image Data Related Error Codes, ROI Related Error Codes

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.34 `NppStatus nppiLUT_16s_C1R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues, const Npp32s * pLevels, int nLevels)`

16-bit signed look-up-table color conversion.

The LUT is derived from a set of user defined mapping points with no interpolation.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- pValues* Pointer to an array of user defined OUTPUT values (this is a device memory pointer)
- pLevels* Pointer to an array of user defined INPUT values (this is a device memory pointer)
- nLevels* Number of user defined number of input/output mapping points (levels)

Returns:

Image Data Related Error Codes, ROI Related Error Codes

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.35 `NppStatus nppiLUT_16s_C3IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

3 channel 16-bit signed look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points with no interpolation.

Parameters:

- pSrcDst* In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.36 `NppStatus nppiLUT_16s_C3R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

3 channel 16-bit signed look-up-table color conversion.

The LUT is derived from a set of user defined mapping points using no interpolation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.37 `NppStatus nppiLUT_16s_C4IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[4], const Npp32s * pLevels[4], int nLevels[4])`

4 channel 16-bit signed look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points using no interpolation.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 4 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.38 `NppStatus nppiLUT_16s_C4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[4], const Npp32s * pLevels[4], int nLevels[4])`

4 channel 16-bit signed look-up-table color conversion.

The LUT is derived from a set of user defined mapping points with no interpolation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 4 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.39 NppStatus nppiLUT_16u_AC4IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])

4 channel 16-bit unsigned look-up-table in place color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points using no interpolation. Alpha channel is the last channel and is not processed.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.40 NppStatus nppiLUT_16u_AC4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])

4 channel 16-bit unsigned look-up-table color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points using no interpolation. Alpha channel is the last channel and is not processed.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.41 `NppStatus nppiLUT_16u_C1IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues, const Npp32s * pLevels, int nLevels)`

16-bit unsigned look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points with no interpolation.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Pointer to an array of user defined OUTPUT values (this is a device memory pointer)

pLevels Pointer to an array of user defined INPUT values (this is a device memory pointer)

nLevels Number of user defined number of input/output mapping points (levels)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.42 `NppStatus nppiLUT_16u_C1R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues, const Npp32s * pLevels, int nLevels)`

16-bit unsigned look-up-table color conversion.

The LUT is derived from a set of user defined mapping points with no interpolation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Pointer to an array of user defined OUTPUT values (this is a device memory pointer)

pLevels Pointer to an array of user defined INPUT values (this is a device memory pointer)

nLevels Number of user defined number of input/output mapping points (levels)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.43 NppStatus nppiLUT_16u_C3IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])

3 channel 16-bit unsigned look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points with no interpolation.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.44 NppStatus nppiLUT_16u_C3R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])

3 channel 16-bit unsigned look-up-table color conversion.

The LUT is derived from a set of user defined mapping points using no interpolation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.45 `NppStatus nppiLUT_16u_C4IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[4], const Npp32s * pLevels[4], int nLevels[4])`

4 channel 16-bit unsigned look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points using no interpolation.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 4 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.46 `NppStatus nppiLUT_16u_C4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[4], const Npp32s * pLevels[4], int nLevels[4])`

4 channel 16-bit unsigned look-up-table color conversion.

The LUT is derived from a set of user defined mapping points with no interpolation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 4 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.47 `NppStatus nppiLUT_32f_AC4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f * pValues[3], const Npp32f * pLevels[3], int nLevels[3])`

4 channel 32-bit floating point look-up-table in place color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points using no interpolation. Alpha channel is the last channel and is not processed.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.48 `NppStatus nppiLUT_32f_AC4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pValues[3], const Npp32f * pLevels[3], int nLevels[3])`

4 channel 32-bit floating point look-up-table color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points using no interpolation. Alpha channel is the last channel and is not processed.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.49 `NppStatus nppiLUT_32f_C1IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f * pValues, const Npp32f * pLevels, int nLevels)`

32-bit floating point look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points with no interpolation.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Pointer to an array of user defined OUTPUT values (this is a device memory pointer)

pLevels Pointer to an array of user defined INPUT values (this is a device memory pointer)

nLevels Number of user defined number of input/output mapping points (levels)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.50 `NppStatus nppiLUT_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pValues, const Npp32f * pLevels, int nLevels)`

32-bit floating point look-up-table color conversion.

The LUT is derived from a set of user defined mapping points with no interpolation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Pointer to an array of user defined OUTPUT values (this is a device memory pointer)

pLevels Pointer to an array of user defined INPUT values (this is a device memory pointer)

nLevels Number of user defined number of input/output mapping points (levels)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.51 `NppStatus nppiLUT_32f_C3IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f * pValues[3], const Npp32f * pLevels[3], int nLevels[3])`

3 channel 32-bit floating point look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points with no interpolation.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.52 `NppStatus nppiLUT_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pValues[3], const Npp32f * pLevels[3], int nLevels[3])`

3 channel 32-bit floating point look-up-table color conversion.

The LUT is derived from a set of user defined mapping points using no interpolation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.53 `NppStatus nppiLUT_32f_C4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f * pValues[4], const Npp32f * pLevels[4], int nLevels[4])`

4 channel 32-bit floating point look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points using no interpolation.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 4 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.54 `NppStatus nppiLUT_32f_C4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pValues[4], const Npp32f * pLevels[4], int nLevels[4])`

4 channel 32-bit floating point look-up-table color conversion.

The LUT is derived from a set of user defined mapping points with no interpolation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 4 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.55 `NppStatus nppiLUT_8u_AC4IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

4 channel 8-bit unsigned look-up-table in place color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points using no interpolation. Alpha channel is the last channel and is not processed.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 256.

7.48.2.56 `NppStatus nppiLUT_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

4 channel 8-bit unsigned look-up-table color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points using no interpolation. Alpha channel is the last channel and is not processed.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 256.

7.48.2.57 `NppStatus nppiLUT_8u_C1IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues, const Npp32s * pLevels, int nLevels)`

8-bit unsigned look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points with no interpolation.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Pointer to an array of user defined OUTPUT values (this is a device memory pointer)

pLevels Pointer to an array of user defined INPUT values (this is a device memory pointer)

nLevels Number of user defined number of input/output mapping points (levels)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 256.

7.48.2.58 `NppStatus nppiLUT_8u_C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues, const Npp32s * pLevels, int nLevels)`

8-bit unsigned look-up-table color conversion.

The LUT is derived from a set of user defined mapping points with no interpolation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Pointer to an array of user defined OUTPUT values (this is a device memory pointer)

pLevels Pointer to an array of user defined INPUT values (this is a device memory pointer)

nLevels Number of user defined number of input/output mapping points (levels)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 256.

7.48.2.59 `NppStatus nppiLUT_8u_C3IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

3 channel 8-bit unsigned look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points with no interpolation.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 256.

7.48.2.60 `NppStatus nppiLUT_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

3 channel 8-bit unsigned look-up-table color conversion.

The LUT is derived from a set of user defined mapping points using no interpolation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 256.

7.48.2.61 `NppStatus nppiLUT_8u_C4IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[4], const Npp32s * pLevels[4], int nLevels[4])`

4 channel 8-bit unsigned look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points using no interpolation.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 4 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 256.

7.48.2.62 `NppStatus nppiLUT_8u_C4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[4], const Npp32s * pLevels[4], int nLevels[4])`

4 channel 8-bit unsigned look-up-table color conversion.

The LUT is derived from a set of user defined mapping points with no interpolation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 4 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 256.

7.48.2.63 `NppStatus nppiLUT_Cubic_16s_AC4IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

4 channel 16-bit signed look-up-table in place color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points using no interpolation. Alpha channel is the last channel and is not processed.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.64 `NppStatus nppiLUT_Cubic_16s_AC4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

4 channel 16-bit signed look-up-table color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points using no interpolation. Alpha channel is the last channel and is not processed.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.65 `NppStatus nppiLUT_Cubic_16s_C1IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues, const Npp32s * pLevels, int nLevels)`

16-bit signed look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points through cubic interpolation.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Pointer to an array of user defined OUTPUT values (this is a device memory pointer)

pLevels Pointer to an array of user defined INPUT values (this is a device memory pointer)

nLevels Number of user defined number of input/output mapping points (levels)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.66 `NppStatus nppiLUT_Cubic_16s_C1R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues, const Npp32s * pLevels, int nLevels)`

16-bit signed look-up-table color conversion.

The LUT is derived from a set of user defined mapping points through cubic interpolation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Pointer to an array of user defined OUTPUT values (this is a device memory pointer)

pLevels Pointer to an array of user defined INPUT values (this is a device memory pointer)

nLevels Number of user defined number of input/output mapping points (levels)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.67 `NppStatus nppiLUT_Cubic_16s_C3IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

3 channel 16-bit signed look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points through cubic interpolation.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.68 `NppStatus nppiLUT_Cubic_16s_C3R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

3 channel 16-bit signed look-up-table color conversion.

The LUT is derived from a set of user defined mapping points using no interpolation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.69 NppStatus nppiLUT_Cubic_16s_C4IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[4], const Npp32s * pLevels[4], int nLevels[4])

4 channel 16-bit signed look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points using no interpolation.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 4 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.70 NppStatus nppiLUT_Cubic_16s_C4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[4], const Npp32s * pLevels[4], int nLevels[4])

4 channel 16-bit signed look-up-table color conversion.

The LUT is derived from a set of user defined mapping points through cubic interpolation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 4 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.71 `NppStatus nppiLUT_Cubic_16u_AC4IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

4 channel 16-bit unsigned look-up-table in place color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points using no interpolation. Alpha channel is the last channel and is not processed.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.72 `NppStatus nppiLUT_Cubic_16u_AC4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

4 channel 16-bit unsigned look-up-table color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points using no interpolation. Alpha channel is the last channel and is not processed.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.73 `NppStatus nppiLUT_Cubic_16u_C1IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues, const Npp32s * pLevels, int nLevels)`

16-bit unsigned look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points through cubic interpolation.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Pointer to an array of user defined OUTPUT values (this is a device memory pointer)

pLevels Pointer to an array of user defined INPUT values (this is a device memory pointer)

nLevels Number of user defined number of input/output mapping points (levels)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.74 `NppStatus nppiLUT_Cubic_16u_C1R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues, const Npp32s * pLevels, int nLevels)`

16-bit unsigned look-up-table color conversion.

The LUT is derived from a set of user defined mapping points through cubic interpolation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Pointer to an array of user defined OUTPUT values (this is a device memory pointer)

pLevels Pointer to an array of user defined INPUT values (this is a device memory pointer)

nLevels Number of user defined number of input/output mapping points (levels)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.75 `NppStatus nppiLUT_Cubic_16u_C3IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

3 channel 16-bit unsigned look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points through cubic interpolation.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.76 `NppStatus nppiLUT_Cubic_16u_C3R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

3 channel 16-bit unsigned look-up-table color conversion.

The LUT is derived from a set of user defined mapping points using no interpolation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.77 `NppStatus nppiLUT_Cubic_16u_C4IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[4], const Npp32s * pLevels[4], int nLevels[4])`

4 channel 16-bit unsigned look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points using no interpolation.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 4 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.78 `NppStatus nppiLUT_Cubic_16u_C4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[4], const Npp32s * pLevels[4], int nLevels[4])`

4 channel 16-bit unsigned look-up-table color conversion.

The LUT is derived from a set of user defined mapping points through cubic interpolation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 4 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.79 `NppStatus nppiLUT_Cubic_32f_AC4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f * pValues[3], const Npp32f * pLevels[3], int nLevels[3])`

4 channel 32-bit floating point look-up-table in place color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points using no interpolation. Alpha channel is the last channel and is not processed.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.80 `NppStatus nppiLUT_Cubic_32f_AC4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pValues[3], const Npp32f * pLevels[3], int nLevels[3])`

4 channel 32-bit floating point look-up-table color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points using no interpolation. Alpha channel is the last channel and is not processed.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.81 `NppStatus nppiLUT_Cubic_32f_C1IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f * pValues, const Npp32f * pLevels, int nLevels)`

32-bit floating point look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points through cubic interpolation.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Pointer to an array of user defined OUTPUT values (this is a device memory pointer)

pLevels Pointer to an array of user defined INPUT values (this is a device memory pointer)

nLevels Number of user defined number of input/output mapping points (levels)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.82 `NppStatus nppiLUT_Cubic_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pValues, const Npp32f * pLevels, int nLevels)`

32-bit floating point look-up-table color conversion.

The LUT is derived from a set of user defined mapping points through cubic interpolation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Pointer to an array of user defined OUTPUT values (this is a device memory pointer)

pLevels Pointer to an array of user defined INPUT values (this is a device memory pointer)

nLevels Number of user defined number of input/output mapping points (levels)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.83 `NppStatus nppiLUT_Cubic_32f_C3IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f * pValues[3], const Npp32f * pLevels[3], int nLevels[3])`

3 channel 32-bit floating point look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points through cubic interpolation.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.84 `NppStatus nppiLUT_Cubic_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pValues[3], const Npp32f * pLevels[3], int nLevels[3])`

3 channel 32-bit floating point look-up-table color conversion.

The LUT is derived from a set of user defined mapping points using no interpolation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.85 `NppStatus nppiLUT_Cubic_32f_C4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f * pValues[4], const Npp32f * pLevels[4], int nLevels[4])`

4 channel 32-bit floating point look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points using no interpolation.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 4 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.86 `NppStatus nppiLUT_Cubic_32f_C4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pValues[4], const Npp32f * pLevels[4], int nLevels[4])`

4 channel 32-bit floating point look-up-table color conversion.

The LUT is derived from a set of user defined mapping points through cubic interpolation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 4 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.87 `NppStatus nppiLUT_Cubic_8u_AC4IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

4 channel 8-bit unsigned cubic interpolated look-up-table in place color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points through cubic interpolation. Alpha channel is the last channel and is not processed.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 256.

7.48.2.88 `NppStatus nppiLUT_Cubic_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

4 channel 8-bit unsigned cubic interpolated look-up-table color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points through cubic interpolation. Alpha channel is the last channel and is not processed.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 256.

7.48.2.89 `NppStatus nppiLUT_Cubic_8u_C1IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues, const Npp32s * pLevels, int nLevels)`

8-bit unsigned cubic interpolated look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points through cubic interpolation.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Pointer to an array of user defined OUTPUT values (this is a device memory pointer)

pLevels Pointer to an array of user defined INPUT values (this is a device memory pointer)

nLevels Number of user defined number of input/output mapping points (levels)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 256.

7.48.2.90 `NppStatus nppiLUT_Cubic_8u_C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues, const Npp32s * pLevels, int nLevels)`

8-bit unsigned cubic interpolated look-up-table color conversion.

The LUT is derived from a set of user defined mapping points through cubic interpolation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Pointer to an array of user defined OUTPUT values (this is a device memory pointer)

pLevels Pointer to an array of user defined INPUT values (this is a device memory pointer)

nLevels Number of user defined number of input/output mapping points (levels)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 256.

7.48.2.91 `NppStatus nppiLUT_Cubic_8u_C3IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

3 channel 8-bit unsigned cubic interpolated look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points through cubic interpolation.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 256.

7.48.2.92 `NppStatus nppiLUT_Cubic_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

3 channel 8-bit unsigned cubic interpolated look-up-table color conversion.

The LUT is derived from a set of user defined mapping points through cubic interpolation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 256.

7.48.2.93 `NppStatus nppiLUT_Cubic_8u_C4IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[4], const Npp32s * pLevels[4], int nLevels[4])`

4 channel 8-bit unsigned cubic interpolated look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points through cubic interpolation.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 4 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 256.

7.48.2.94 `NppStatus nppiLUT_Cubic_8u_C4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[4], const Npp32s * pLevels[4], int nLevels[4])`

4 channel 8-bit unsigned cubic interpolated look-up-table color conversion.

The LUT is derived from a set of user defined mapping points through cubic interpolation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 4 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 256.

7.48.2.95 `NppStatus nppiLUT_Linear_16s_AC4IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

4 channel 16-bit signed look-up-table in place color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points using no interpolation. Alpha channel is the last channel and is not processed.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.96 `NppStatus nppiLUT_Linear_16s_AC4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

4 channel 16-bit signed look-up-table color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points using no interpolation. Alpha channel is the last channel and is not processed.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.97 `NppStatus nppiLUT_Linear_16s_C1IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues, const Npp32s * pLevels, int nLevels)`

16-bit signed look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points using linear interpolation.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Pointer to an array of user defined OUTPUT values (this is a device memory pointer)

pLevels Pointer to an array of user defined INPUT values (this is a device memory pointer)

nLevels Number of user defined number of input/output mapping points (levels)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.98 `NppStatus nppiLUT_Linear_16s_C1R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues, const Npp32s * pLevels, int nLevels)`

16-bit signed look-up-table color conversion.

The LUT is derived from a set of user defined mapping points using linear interpolation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Pointer to an array of user defined OUTPUT values (this is a device memory pointer)

pLevels Pointer to an array of user defined INPUT values (this is a device memory pointer)

nLevels Number of user defined number of input/output mapping points (levels)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.99 `NppStatus nppiLUT_Linear_16s_C3IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

3 channel 16-bit signed look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points using linear interpolation.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.100 `NppStatus nppiLUT_Linear_16s_C3R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

3 channel 16-bit signed look-up-table color conversion.

The LUT is derived from a set of user defined mapping points using no interpolation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.101 NppStatus nppiLUT_Linear_16s_C4IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[4], const Npp32s * pLevels[4], int nLevels[4])

4 channel 16-bit signed look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points using no interpolation.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 4 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.102 NppStatus nppiLUT_Linear_16s_C4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[4], const Npp32s * pLevels[4], int nLevels[4])

4 channel 16-bit signed look-up-table color conversion.

The LUT is derived from a set of user defined mapping points using linear interpolation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 4 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.103 NppStatus nppiLUT_Linear_16u_AC4IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])

4 channel 16-bit unsigned look-up-table in place color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points using no interpolation. Alpha channel is the last channel and is not processed.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.104 NppStatus nppiLUT_Linear_16u_AC4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])

4 channel 16-bit unsigned look-up-table color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points using no interpolation. Alpha channel is the last channel and is not processed.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.105 `NppStatus nppiLUT_Linear_16u_C1IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues, const Npp32s * pLevels, int nLevels)`

16-bit unsigned look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points using linear interpolation.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Pointer to an array of user defined OUTPUT values (this is a device memory pointer)

pLevels Pointer to an array of user defined INPUT values (this is a device memory pointer)

nLevels Number of user defined number of input/output mapping points (levels)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.106 `NppStatus nppiLUT_Linear_16u_C1R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues, const Npp32s * pLevels, int nLevels)`

16-bit unsigned look-up-table color conversion.

The LUT is derived from a set of user defined mapping points using linear interpolation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Pointer to an array of user defined OUTPUT values (this is a device memory pointer)

pLevels Pointer to an array of user defined INPUT values (this is a device memory pointer)

nLevels Number of user defined number of input/output mapping points (levels)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.107 `NppStatus nppiLUT_Linear_16u_C3IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

3 channel 16-bit unsigned look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points using linear interpolation.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.108 `NppStatus nppiLUT_Linear_16u_C3R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

3 channel 16-bit unsigned look-up-table color conversion.

The LUT is derived from a set of user defined mapping points using no interpolation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.109 NppStatus nppiLUT_Linear_16u_C4IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[4], const Npp32s * pLevels[4], int nLevels[4])

4 channel 16-bit unsigned look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points using no interpolation.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 4 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.110 NppStatus nppiLUT_Linear_16u_C4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[4], const Npp32s * pLevels[4], int nLevels[4])

4 channel 16-bit unsigned look-up-table color conversion.

The LUT is derived from a set of user defined mapping points using linear interpolation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 4 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.111 `NppStatus nppiLUT_Linear_32f_AC4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f * pValues[3], const Npp32f * pLevels[3], int nLevels[3])`

4 channel 32-bit floating point look-up-table in place color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points using no interpolation. Alpha channel is the last channel and is not processed.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.112 `NppStatus nppiLUT_Linear_32f_AC4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pValues[3], const Npp32f * pLevels[3], int nLevels[3])`

4 channel 32-bit floating point look-up-table color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points using no interpolation. Alpha channel is the last channel and is not processed.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.113 `NppStatus nppiLUT_Linear_32f_C1IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f * pValues, const Npp32f * pLevels, int nLevels)`

32-bit floating point look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points using linear interpolation.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Pointer to an array of user defined OUTPUT values (this is a device memory pointer)

pLevels Pointer to an array of user defined INPUT values (this is a device memory pointer)

nLevels Number of user defined number of input/output mapping points (levels)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.114 `NppStatus nppiLUT_Linear_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pValues, const Npp32f * pLevels, int nLevels)`

32-bit floating point look-up-table color conversion.

The LUT is derived from a set of user defined mapping points using linear interpolation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Pointer to an array of user defined OUTPUT values (this is a device memory pointer)

pLevels Pointer to an array of user defined INPUT values (this is a device memory pointer)

nLevels Number of user defined number of input/output mapping points (levels)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.115 `NppStatus nppiLUT_Linear_32f_C3IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f * pValues[3], const Npp32f * pLevels[3], int nLevels[3])`

3 channel 32-bit floating point look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points using linear interpolation.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.116 `NppStatus nppiLUT_Linear_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pValues[3], const Npp32f * pLevels[3], int nLevels[3])`

3 channel 32-bit floating point look-up-table color conversion.

The LUT is derived from a set of user defined mapping points using no interpolation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.117 `NppStatus nppiLUT_Linear_32f_C4IR` (`Npp32f * pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp32f * pValues[4]`, `const Npp32f * pLevels[4]`, `int nLevels[4]`)

4 channel 32-bit floating point look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points using no interpolation.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 4 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.118 `NppStatus nppiLUT_Linear_32f_C4R` (`const Npp32f * pSrc`, `int nSrcStep`, `Npp32f * pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp32f * pValues[4]`, `const Npp32f * pLevels[4]`, `int nLevels[4]`)

4 channel 32-bit floating point look-up-table color conversion.

The LUT is derived from a set of user defined mapping points using linear interpolation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 4 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 1024 (the current size limit).

7.48.2.119 `NppStatus nppiLUT_Linear_8u_AC4IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

4 channel 8-bit unsigned linear interpolated look-up-table in place color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points through linear interpolation. Alpha channel is the last channel and is not processed.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2 or greater than 256.

7.48.2.120 `NppStatus nppiLUT_Linear_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

4 channel 8-bit unsigned linear interpolated look-up-table color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points through linear interpolation. Alpha channel is the last channel and is not processed.

>>>>>> ATTENTION ATTENTION <<<<<<<<

NOTE: As of the 5.0 release of NPP, the *pValues* and *pLevels* pointers need to be host memory pointers to arrays of device memory pointers.

>>>>>> <<<<<<<<

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 256.

7.48.2.121 `NppStatus nppiLUT_Linear_8u_C1IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues, const Npp32s * pLevels, int nLevels)`

8-bit unsigned linear interpolated look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points through linear interpolation.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Pointer to an array of user defined OUTPUT values (this is a device memory pointer)

pLevels Pointer to an array of user defined INPUT values (this is a device memory pointer)

nLevels Number of user defined number of input/output mapping points (levels)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 256.

7.48.2.122 `NppStatus nppiLUT_Linear_8u_C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues, const Npp32s * pLevels, int nLevels)`

8-bit unsigned linear interpolated look-up-table color conversion.

The LUT is derived from a set of user defined mapping points through linear interpolation.

>>>>>> ATTENTION ATTENTION <<<<<<<<

NOTE: As of the 5.0 release of NPP, the pValues and pLevels pointers need to be device memory pointers.

>>>>>> <<<<<<<<

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pValues Pointer to an array of user defined OUTPUT values (this is now a device memory pointer)

pLevels Pointer to an array of user defined INPUT values (this is now a device memory pointer)

nLevels Number of user defined number of input/output mapping points (levels)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 256.

7.48.2.123 NppStatus nppiLUT_Linear_8u_C3IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])

3 channel 8-bit unsigned linear interpolated look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points through linear interpolation.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 256.

7.48.2.124 NppStatus nppiLUT_Linear_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])

3 channel 8-bit unsigned linear interpolated look-up-table color conversion.

The LUT is derived from a set of user defined mapping points through linear interpolation.

>>>>>> ATTENTION ATTENTION <<<<<<<<

NOTE: As of the 5.0 release of NPP, the pValues and pLevels pointers need to be host memory pointers to arrays of device memory pointers.

>>>>>> <<<<<<<<

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 3 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 256.

7.48.2.125 `NppStatus nppiLUT_Linear_8u_C4IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32s * pValues[4], const Npp32s * pLevels[4], int nLevels[4])`

4 channel 8-bit unsigned linear interpolated look-up-table in place color conversion.

The LUT is derived from a set of user defined mapping points through linear interpolation.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 4 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 256.

7.48.2.126 `NppStatus nppiLUT_Linear_8u_C4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[4], const Npp32s * pLevels[4], int nLevels[4])`

4 channel 8-bit unsigned linear interpolated look-up-table color conversion.

The LUT is derived from a set of user defined mapping points through linear interpolation.

>>>>>> ATTENTION ATTENTION <<<<<<<<

NOTE: As of the 5.0 release of NPP, the *pValues* and *pLevels* pointers need to be host memory pointers to arrays of device memory pointers.

>>>>>> <<<<<<<<

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT values.

pLevels Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined INPUT values.

nLevels Host pointer to an array of 4 user defined number of input/output mapping points, one per color CHANNEL.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2 or greater than 256.

7.48.2.127 NppStatus nppiLUTPalette_16u24u_C1R (const Npp16u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pTable, int nBitSize)

One channel 16-bit unsigned bit range restricted 24-bit unsigned palette look-up-table color conversion with 24-bit unsigned destination output per pixel.

The LUT is derived from a set of user defined mapping points in a palette and source pixels are then processed using a restricted bit range when looking up palette values.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step (3 unsigned bytes per pixel).

oSizeROI Region-of-Interest (ROI).

pTable Pointer to an array of user defined OUTPUT palette values (this is a device memory pointer)

nBitSize Number of least significant bits (must be > 0 and <= 16) of each source pixel value to use as index into palette table during conversion.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

- [NPP_LUT_PALETTE_BITSIZE_ERROR](#) if *nBitSize* is < 1 or > 16.

7.48.2.128 NppStatus nppiLUTPalette_16u32u_C1R (const Npp16u * pSrc, int nSrcStep, Npp32u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32u * pTable, int nBitSize)

One channel 16-bit unsigned bit range restricted 32-bit palette look-up-table color conversion with 32-bit unsigned destination output per pixel.

The LUT is derived from a set of user defined mapping points in a palette and source pixels are then processed using a restricted bit range when looking up palette values.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step (4 bytes per pixel).

oSizeROI Region-of-Interest (ROI).

pTable Pointer to an array of user defined OUTPUT palette values (this is a device memory pointer)

nBitSize Number of least significant bits (must be > 0 and <= 16) of each source pixel value to use as index into palette table during conversion.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_PALETTE_BITSIZE_ERROR](#) if nBitSize is < 1 or > 16.

7.48.2.129 NppStatus nppiLUTPalette_16u8u_C1R (const Npp16u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pTable, int nBitSize)

One channel 16-bit unsigned bit range restricted 8-bit unsigned palette look-up-table color conversion with 8-bit unsigned destination output per pixel.

The LUT is derived from a set of user defined mapping points in a palette and source pixels are then processed using a restricted bit range when looking up palette values.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step (1 unsigned byte per pixel).

oSizeROI Region-of-Interest (ROI).

pTable Pointer to an array of user defined OUTPUT palette values (this is a device memory pointer)

nBitSize Number of least significant bits (must be > 0 and <= 16) of each source pixel value to use as index into palette table during conversion.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_PALETTE_BITSIZE_ERROR](#) if nBitSize is < 1 or > 16.

7.48.2.130 **NppStatus nppiLUTPalette_16u_AC4R** (const Npp16u * *pSrc*, int *nSrcStep*, Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, const Npp16u * *pTables*[3], int *nBitSize*)

Four channel 16-bit unsigned bit range restricted palette look-up-table color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points in a palette and source pixels are then processed using a restricted bit range when looking up palette values. Alpha channel is the last channel and is not processed.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pTables Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT palette values.

nBitSize Number of least significant bits (must be > 0 and <= 16) of each source pixel value to use as index into palette table during conversion.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

- **NPP_LUT_PALETTE_BITSIZE_ERROR** if *nBitSize* is < 1 or > 16.

7.48.2.131 **NppStatus nppiLUTPalette_16u_C1R** (const Npp16u * *pSrc*, int *nSrcStep*, Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, const Npp16u * *pTable*, int *nBitSize*)

One channel 16-bit unsigned bit range restricted palette look-up-table color conversion.

The LUT is derived from a set of user defined mapping points in a palette and source pixels are then processed using a restricted bit range when looking up palette values.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pTable Pointer to an array of user defined OUTPUT palette values (this is a device memory pointer)

nBitSize Number of least significant bits (must be > 0 and <= 16) of each source pixel value to use as index into palette table during conversion.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

- **NPP_LUT_PALETTE_BITSIZE_ERROR** if *nBitSize* is < 1 or > 16.

7.48.2.132 **NppStatus nppiLUTPalette_16u_C3R** (const Npp16u * *pSrc*, int *nSrcStep*, Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, const Npp16u * *pTables*[3], int *nBitSize*)

Three channel 16-bit unsigned bit range restricted palette look-up-table color conversion.

The LUT is derived from a set of user defined mapping points in a palette and source pixels are then processed using a restricted bit range when looking up palette values.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pTables Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT palette values.

nBitSize Number of least significant bits (must be > 0 and <= 16) of each source pixel value to use as index into palette table during conversion.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_PALETTE_BITSIZE_ERROR](#) if *nBitSize* is < 1 or > 16.

7.48.2.133 **NppStatus nppiLUTPalette_16u_C4R** (const Npp16u * *pSrc*, int *nSrcStep*, Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, const Npp16u * *pTables*[4], int *nBitSize*)

Four channel 16-bit unsigned bit range restricted palette look-up-table color conversion.

The LUT is derived from a set of user defined mapping points in a palette and source pixels are then processed using a restricted bit range when looking up palette values.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pTables Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT palette values.

nBitSize Number of least significant bits (must be > 0 and <= 16) of each source pixel value to use as index into palette table during conversion.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_PALETTE_BITSIZE_ERROR](#) if *nBitSize* is < 1 or > 16.

7.48.2.134 `NppStatus nppiLUTPalette_8u24u_C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pTable, int nBitSize)`

One channel 8-bit unsigned bit range restricted 24-bit palette look-up-table color conversion with 24-bit destination output per pixel.

The LUT is derived from a set of user defined mapping points in a palette and source pixels are then processed using a restricted bit range when looking up palette values.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step (3 bytes per pixel).

oSizeROI Region-of-Interest (ROI).

pTable Pointer to an array of user defined OUTPUT palette values (this is a device memory pointer)

nBitSize Number of least significant bits (must be > 0 and <= 8) of each source pixel value to use as index into palette table during conversion.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_PALETTE_BITSIZE_ERROR` if *nBitSize* is < 1 or > 8.

7.48.2.135 `NppStatus nppiLUTPalette_8u32u_C1R (const Npp8u * pSrc, int nSrcStep, Npp32u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32u * pTable, int nBitSize)`

One channel 8-bit unsigned bit range restricted 32-bit palette look-up-table color conversion with 32-bit destination output per pixel.

The LUT is derived from a set of user defined mapping points in a palette and source pixels are then processed using a restricted bit range when looking up palette values.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step (4 bytes per pixel).

oSizeROI Region-of-Interest (ROI).

pTable Pointer to an array of user defined OUTPUT palette values (this is a device memory pointer)

nBitSize Number of least significant bits (must be > 0 and <= 8) of each source pixel value to use as index into palette table during conversion.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- `NPP_LUT_PALETTE_BITSIZE_ERROR` if *nBitSize* is < 1 or > 8.

7.48.2.136 NppStatus nppiLUTPalette_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pTables[3], int nBitSize)

Four channel 8-bit unsigned bit range restricted palette look-up-table color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points in a palette and source pixels are then processed using a restricted bit range when looking up palette values. Alpha channel is the last channel and is not processed.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pTables Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT palette values.

nBitSize Number of least significant bits (must be > 0 and <= 8) of each source pixel value to use as index into palette table during conversion.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

- [NPP_LUT_PALETTE_BITSIZE_ERROR](#) if nBitSize is < 1 or > 8.

7.48.2.137 NppStatus nppiLUTPalette_8u_C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pTable, int nBitSize)

One channel 8-bit unsigned bit range restricted palette look-up-table color conversion.

The LUT is derived from a set of user defined mapping points in a palette and source pixels are then processed using a restricted bit range when looking up palette values.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pTable Pointer to an array of user defined OUTPUT palette values (this is a device memory pointer)

nBitSize Number of least significant bits (must be > 0 and <= 8) of each source pixel value to use as index into palette table during conversion.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

- [NPP_LUT_PALETTE_BITSIZE_ERROR](#) if nBitSize is < 1 or > 8.

7.48.2.138 NppStatus nppiLUTPalette_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pTables[3], int nBitSize)

Three channel 8-bit unsigned bit range restricted palette look-up-table color conversion.

The LUT is derived from a set of user defined mapping points in a palette and source pixels are then processed using a restricted bit range when looking up palette values.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pTables Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT palette values.

nBitSize Number of least significant bits (must be > 0 and <= 8) of each source pixel value to use as index into palette table during conversion.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

- [NPP_LUT_PALETTE_BITSIZE_ERROR](#) if nBitSize is < 1 or > 8.

7.48.2.139 NppStatus nppiLUTPalette_8u_C4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pTables[4], int nBitSize)

Four channel 8-bit unsigned bit range restricted palette look-up-table color conversion.

The LUT is derived from a set of user defined mapping points in a palette and source pixels are then processed using a restricted bit range when looking up palette values.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pTables Host pointer to an array of 4 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT palette values.

nBitSize Number of least significant bits (must be > 0 and <= 8) of each source pixel value to use as index into palette table during conversion.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

- [NPP_LUT_PALETTE_BITSIZE_ERROR](#) if nBitSize is < 1 or > 8.

7.48.2.140 NppStatus nppiLUTPaletteSwap_16u_C3A0C4R (const Npp16u * pSrc, int nSrcStep, int nAlphaValue, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp16u * pTables[3], int nBitSize)

Three channel 16-bit unsigned source bit range restricted palette look-up-table color conversion to four channel 16-bit unsigned destination output with alpha.

The LUT is derived from a set of user defined mapping points in a palette and source pixels are then processed using a restricted bit range when looking up palette values. This function also reverses the source pixel channel order in the destination so the Alpha channel is the first channel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#) (3 unsigned short integers per pixel).

nAlphaValue Signed alpha value that will be used to initialize the pixel alpha channel position in all modified destination pixels.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#) (4 unsigned short integers per pixel with alpha).

oSizeROI [Region-of-Interest \(ROI\)](#).

pTables Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT palette values. Alpha values < 0 or > 65535 will cause destination pixel alpha channel values to be unmodified.

nBitSize Number of least significant bits (must be > 0 and <= 16) of each source pixel value to use as index into palette table during conversion.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_PALETTE_BITSIZE_ERROR](#) if nBitSize is < 1 or > 16.

7.48.2.141 NppStatus nppiLUTPaletteSwap_8u_C3A0C4R (const Npp8u * pSrc, int nSrcStep, int nAlphaValue, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pTables[3], int nBitSize)

Three channel 8-bit unsigned source bit range restricted palette look-up-table color conversion to four channel 8-bit unsigned destination output with alpha.

The LUT is derived from a set of user defined mapping points in a palette and source pixels are then processed using a restricted bit range when looking up palette values. This function also reverses the source pixel channel order in the destination so the Alpha channel is the first channel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#) (3 bytes per pixel).

nAlphaValue Signed alpha value that will be used to initialize the pixel alpha channel position in all modified destination pixels.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#) (4 bytes per pixel with alpha).

oSizeROI [Region-of-Interest \(ROI\)](#).

pTables Host pointer to an array of 3 device memory pointers, one per color CHANNEL, pointing to user defined OUTPUT palette values. Alpha values < 0 or > 255 will cause destination pixel alpha channel values to be unmodified.

nBitSize Number of least significant bits (must be > 0 and ≤ 8) of each source pixel value to use as index into palette table during conversion.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_PALETTE_BITSIZE_ERROR](#) if *nBitSize* is < 1 or > 8 .

7.49 Compression

Image compression primitives.

Modules

- [Quantization Functions](#)

Functions

- `NppStatus nppiDecodeHuffmanScanHost_JPEG_8u16s_P1R` (const `Npp8u *pSrc`, `Npp32s nLength`, `Npp32s restartInterval`, `Npp32s Ss`, `Npp32s Se`, `Npp32s Ah`, `Npp32s Al`, `Npp16s *pDst`, `Npp32s nDstStep`, `Npp8u *pHuffmanTableDC`, `Npp8u *pHuffmanTableAC`, `NppiSize oSizeROI`)
Huffman Decoding of the JPEG decoding on the host.
- `NppStatus nppiDecodeHuffmanScanHost_JPEG_8u16s_P3R` (const `Npp8u *pSrc`, `Npp32s nLength`, `Npp32s nRestartInterval`, `Npp32s nSs`, `Npp32s nSe`, `Npp32s nAh`, `Npp32s nAl`, `Npp16s *apDst[3]`, `Npp32s aDstStep[3]`, `Npp8u *apHuffmanDCTable[3]`, `Npp8u *apHuffmanACTable[3]`, `NppiSize aSizeROI[3]`)
Huffman Decoding of the JPEG decoding on the host.

7.49.1 Detailed Description

Image compression primitives.

The JPEG standard defines a flow of level shift, DCT and quantization for forward JPEG transform and inverse level shift, IDCT and de-quantization for inverse JPEG transform. This group has the functions for both forward and inverse functions.

7.49.2 Function Documentation

7.49.2.1 `NppStatus nppiDecodeHuffmanScanHost_JPEG_8u16s_P1R` (const `Npp8u *pSrc`, `Npp32s nLength`, `Npp32s restartInterval`, `Npp32s Ss`, `Npp32s Se`, `Npp32s Ah`, `Npp32s Al`, `Npp16s *pDst`, `Npp32s nDstStep`, `Npp8u *pHuffmanTableDC`, `Npp8u *pHuffmanTableAC`, `NppiSize oSizeROI`)

Huffman Decoding of the JPEG decoding on the host.

Input is expected in byte stuffed huffman encoded JPEG scan and output is expected to be 64x1 macro blocks.

Parameters:

pSrc Byte-stuffed huffman encoded JPEG scan.

nLength Byte length of the input.

restartInterval Restart Interval, see JPEG standard.

Ss Start Coefficient, see JPEG standard.

Se End Coefficient, see JPEG standard.

Ah Bit Approximation High, see JPEG standard.

Al Bit Approximation Low, see JPEG standard.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pHuffmanTableDC DC Huffman table for JPEG decoding, format as specified in the JPEG standard.

pHuffmanTableAC AC Huffman table for JPEG decoding, format as specified in the JPEG standard.

oSizeROI Region-of-Interest (ROI).

Returns:

Error codes:

- **NPP_SIZE_ERROR** For negative input height/width or not a multiple of 8 width/height.
- **NPP_STEP_ERROR** If input image width is not multiple of 8 or does not match ROI.
- **NPP_NULL_POINTER_ERROR** If the destination pointer is 0.

7.49.2.2 `NppStatus nppiDecodeHuffmanScanHost_JPEG_8u16s_P3R (const Npp8u * pSrc, Npp32s nLength, Npp32s nRestartInterval, Npp32s nSs, Npp32s nSe, Npp32s nAh, Npp32s nAl, Npp16s * apDst[3], Npp32s aDstStep[3], Npp8u * apHuffmanDCTable[3], Npp8u * apHuffmanACTable[3], NppiSize aSizeROI[3])`

Huffman Decoding of the JPEG decoding on the host.

Input is expected in byte stuffed huffman encoded JPEG scan and output is expected to be 64x1 macro blocks.

Parameters:

pSrc Byte-stuffed huffman encoded JPEG scan.

nLength Byte length of the input.

nRestartInterval Restart Interval, see JPEG standard.

nSs Start Coefficient, see JPEG standard.

nSe End Coefficient, see JPEG standard.

nAh Bit Approximation High, see JPEG standard.

nAl Bit Approximation Low, see JPEG standard.

apDst Destination-Image Pointer.

aDstStep Destination-Image Line Step.

apHuffmanDCTable DC Huffman tables for JPEG decoding, format as specified in the JPEG standard.

apHuffmanACTable AC Huffman tables for JPEG decoding, format as specified in the JPEG standard.

aSizeROI Region-of-Interest (ROI).

Returns:

Error codes:

- **NPP_SIZE_ERROR** For negative input height/width or not a multiple of 8 width/height.
- **NPP_STEP_ERROR** If input image width is not multiple of 8 or does not match ROI.
- **NPP_NULL_POINTER_ERROR** If the destination pointer is 0.

7.50 Quantization Functions

Typedefs

- typedef struct [NppiDCTState](#) [NppiDCTState](#)

Functions

- [NppStatus](#) [nppiQuantFwdRawTableInit_JPEG_8u](#) ([Npp8u](#) *hpQuantRawTable, int nQualityFactor)

Apply quality factor to raw 8-bit quantization table.

- [NppStatus](#) [nppiQuantFwdTableInit_JPEG_8u16u](#) (const [Npp8u](#) *hpQuantRawTable, [Npp16u](#) *hpQuantFwdRawTable)

Initializes a quantization table for [nppiDCTQuantFwd8x8LS_JPEG_8u16s_C1R\(\)](#).

- [NppStatus](#) [nppiQuantInvTableInit_JPEG_8u16u](#) (const [Npp8u](#) *hpQuantRawTable, [Npp16u](#) *hpQuantFwdRawTable)

Initializes a quantization table for [nppiDCTQuantInv8x8LS_JPEG_16s8u_C1R\(\)](#).

- [NppStatus](#) [nppiDCTQuantFwd8x8LS_JPEG_8u16s_C1R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [Npp16s](#) *pDst, int nDstStep, const [Npp16u](#) *pQuantFwdTable, [NppiSize](#) oSizeROI)

Forward DCT, quantization and level shift part of the JPEG encoding.

- [NppStatus](#) [nppiDCTQuantInv8x8LS_JPEG_16s8u_C1R](#) (const [Npp16s](#) *pSrc, int nSrcStep, [Npp8u](#) *pDst, int nDstStep, const [Npp16u](#) *pQuantInvTable, [NppiSize](#) oSizeROI)

Inverse DCT, de-quantization and level shift part of the JPEG decoding.

- [NppStatus](#) [nppiDCTInitAlloc](#) ([NppiDCTState](#) **ppState)

Initializes DCT state structure and allocates additional resources.

- [NppStatus](#) [nppiDCTFree](#) ([NppiDCTState](#) *pState)

Frees the additional resources of the DCT state structure.

- [NppStatus](#) [nppiDCTQuantFwd8x8LS_JPEG_8u16s_C1R_NEW](#) (const [Npp8u](#) *pSrc, int nSrcStep, [Npp16s](#) *pDst, int nDstStep, const [Npp8u](#) *pQuantizationTable, [NppiSize](#) oSizeROI, [NppiDCTState](#) *pState)

Forward DCT, quantization and level shift part of the JPEG encoding.

- [NppStatus](#) [nppiDCTQuantInv8x8LS_JPEG_16s8u_C1R_NEW](#) (const [Npp16s](#) *pSrc, int nSrcStep, [Npp8u](#) *pDst, int nDstStep, const [Npp8u](#) *pQuantizationTable, [NppiSize](#) oSizeROI, [NppiDCTState](#) *pState)

Inverse DCT, de-quantization and level shift part of the JPEG decoding.

7.50.1 Typedef Documentation

7.50.1.1 typedef struct NppiDCTState NppiDCTState

7.50.2 Function Documentation

7.50.2.1 NppStatus nppiDCTFree (NppiDCTState * *pState*)

Frees the additional resources of the DCT state structure.

See also:

[nppiDCTInitAlloc](#)

Parameters:

pState Pointer to DCT state structure.

Returns:

NPP_SUCCESS Indicates no error. Any other value indicates an error or a warning
NPP_SIZE_ERROR Indicates an error condition if any image dimension has zero or negative value
NPP_NULL_POINTER_ERROR Indicates an error condition if *pState* pointer is NULL

7.50.2.2 NppStatus nppiDCTInitAlloc (NppiDCTState ** *ppState*)

Initializes DCT state structure and allocates additional resources.

See also:

[nppiDCTQuantFwd8x8LS_JPEG_8u16s_C1R_NEW\(\)](#), [nppiDCTQuantInv8x8LS_JPEG_16s8u_C1R_NEW](#).

Parameters:

ppState Pointer to pointer to DCT state structure.

Returns:

NPP_SUCCESS Indicates no error. Any other value indicates an error or a warning
NPP_SIZE_ERROR Indicates an error condition if any image dimension has zero or negative value
NPP_NULL_POINTER_ERROR Indicates an error condition if *pBufSize* pointer is NULL

7.50.2.3 NppStatus nppiDCTQuantFwd8x8LS_JPEG_8u16s_C1R (const Npp8u * *pSrc*, int *nSrcStep*, Npp16s * *pDst*, int *nDstStep*, const Npp16u * *pQuantFwdTable*, NppiSize *oSizeROI*)

Forward DCT, quantization and level shift part of the JPEG encoding.

Input is expected in 8x8 macro blocks and output is expected to be in 64x1 macro blocks.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pQuantFwdTable Forward quantization tables for JPEG encoding created using `nppiQuantInvTableInit_JPEG_8u16u()`.

oSizeROI Region-of-Interest (ROI).

Returns:

Error codes:

- [NPP_SIZE_ERROR](#) For negative input height/width or not a multiple of 8 width/height.
- [NPP_STEP_ERROR](#) If input image width is not multiple of 8 or does not match ROI.
- [NPP_NULL_POINTER_ERROR](#) If the destination pointer is 0.

7.50.2.4 `NppStatus nppiDCTQuantFwd8x8LS_JPEG_8u16s_C1R_NEW (const Npp8u * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, const Npp8u * pQuantizationTable, NppiSize oSizeROI, NppiDCTState * pState)`

Forward DCT, quantization and level shift part of the JPEG encoding.

Input is expected in 8x8 macro blocks and output is expected to be in 64x1 macro blocks. The new version of the primitive takes the ROI in image pixel size and works with DCT coefficients that are in zig-zag order.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Image width in pixels x 8 x sizeof(Npp16s).

pQuantizationTable Quantization Table in zig-zag order.

oSizeROI Region-of-Interest (ROI).

pState Pointer to DCT state structure. This structure must be initialized allocated and initialized using `nppiDCTInitAlloc()`.

Returns:

Error codes:

- [NPP_SIZE_ERROR](#) For negative input height/width or not a multiple of 8 width/height.
- [NPP_STEP_ERROR](#) If input image width is not multiple of 8 or does not match ROI.
- [NPP_NULL_POINTER_ERROR](#) If the destination pointer is 0.

7.50.2.5 `NppStatus nppiDCTQuantInv8x8LS_JPEG_16s8u_C1R (const Npp16s * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, const Npp16u * pQuantInvTable, NppiSize oSizeROI)`

Inverse DCT, de-quantization and level shift part of the JPEG decoding.

Input is expected in 64x1 macro blocks and output is expected to be in 8x8 macro blocks.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Image width in pixels x 8 x sizeof(Npp16s).

pDst Destination-Image Pointer.

nDstStep Image width in pixels x 8 x sizeof(Npp16s).

pQuantInvTable Inverse quantization tables for JPEG decoding created using `nppiQuantInvTableInit_JPEG_8u16u()`.

oSizeROI Region-of-Interest (ROI).

Returns:

Error codes:

- `NPP_SIZE_ERROR` For negative input height/width or not a multiple of 8 width/height.
- `NPP_STEP_ERROR` If input image width is not multiple of 8 or does not match ROI.
- `NPP_NULL_POINTER_ERROR` If the destination pointer is 0.

7.50.2.6 `NppStatus nppiDCTQuantInv8x8LS_JPEG_16s8u_C1R_NEW (const Npp16s * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, const Npp8u * pQuantizationTable, NppiSize oSizeROI, NppiDCTState * pState)`

Inverse DCT, de-quantization and level shift part of the JPEG decoding.

Input is expected in 64x1 macro blocks and output is expected to be in 8x8 macro blocks. The new version of the primitive takes the ROI in image pixel size and works with DCT coefficients that are in zig-zag order.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Image width in pixels x 8 x sizeof(Npp16s).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pQuantizationTable Quantization Table in zig-zag order.

oSizeROI Region-of-Interest (ROI).

pState Pointer to DCT state structure. This structure must be initialized allocated and initialized using `nppiDCTInitAlloc()`.

Returns:

Error codes:

- `NPP_SIZE_ERROR` For negative input height/width or not a multiple of 8 width/height.
- `NPP_STEP_ERROR` If input image width is not multiple of 8 or does not match ROI.
- `NPP_NULL_POINTER_ERROR` If the destination pointer is 0.

7.50.2.7 NppStatus nppiQuantFwdRawTableInit_JPEG_8u (Npp8u * hpQuantRawTable, int nQualityFactor)

Apply quality factor to raw 8-bit quantization table.

This is effectively and in-place method that modifies a given raw quantization table based on a quality factor. Note that this method is a host method and that the pointer to the raw quantization table is a host pointer.

Parameters:

hpQuantRawTable Raw quantization table.

nQualityFactor Quality factor for the table. Range is [1:100].

Returns:

Error code: [NPP_NULL_POINTER_ERROR](#) is returned if hpQuantRawTable is 0.

7.50.2.8 NppStatus nppiQuantFwdTableInit_JPEG_8u16u (const Npp8u * hpQuantRawTable, Npp16u * hpQuantFwdRawTable)

Initializes a quantization table for [nppiDCTQuantFwd8x8LS_JPEG_8u16s_C1R\(\)](#).

The method creates a 16-bit version of the raw table and converts the data order from zigzag layout to original row-order layout since raw quantization tables are typically stored in zigzag format.

This method is a host method. It consumes and produces host data. I.e. the pointers passed to this function must be host pointers. The resulting table needs to be transferred to device memory in order to be used with [nppiDCTQuantFwd8x8LS_JPEG_8u16s_C1R\(\)](#) function.

Parameters:

hpQuantRawTable Host pointer to raw quantization table as returned by [nppiQuantFwdRawTableInit_JPEG_8u\(\)](#). The raw quantization table is assumed to be in zigzag order.

hpQuantFwdRawTable Forward quantization table for use with [nppiDCTQuantFwd8x8LS_JPEG_8u16s_C1R\(\)](#).

Returns:

Error code: [NPP_NULL_POINTER_ERROR](#) pQuantRawTable is 0.

7.50.2.9 NppStatus nppiQuantInvTableInit_JPEG_8u16u (const Npp8u * hpQuantRawTable, Npp16u * hpQuantFwdRawTable)

Initializes a quantization table for [nppiDCTQuantInv8x8LS_JPEG_16s8u_C1R\(\)](#).

The [nppiDCTQuantFwd8x8LS_JPEG_8u16s_C1R\(\)](#) method uses a quantization table in a 16-bit format allowing for faster processing. In addition it converts the data order from zigzag layout to original row-order layout. Typically raw quantization tables are stored in zigzag format.

This method is a host method and consumes and produces host data. I.e. the pointers passed to this function must be host pointers. The resulting table needs to be transferred to device memory in order to be used with [nppiDCTQuantFwd8x8LS_JPEG_8u16s_C1R\(\)](#) function.

Parameters:

hpQuantRawTable Raw quantization table.

hpQuantFwdRawTable Inverse quantization table.

Returns:

[NPP_NULL_POINTER_ERROR](#) pQuantRawTable or pQuantFwdRawTable is 0.

7.51 Labeling and Segmentation

Pixel labeling and image segmentation operations.

Modules

- [GraphCut](#)

Typedefs

- typedef struct [NppiGraphcutState](#) [NppiGraphcutState](#)

7.51.1 Detailed Description

Pixel labeling and image segmentation operations.

7.51.2 Typedef Documentation

7.51.2.1 typedef struct [NppiGraphcutState](#) [NppiGraphcutState](#)

7.52 GraphCut

Graphcut

- **NppStatus nppiGraphcutGetSize** (**NppiSize** oSize, int *pBufSize)
Calculates the size of the temporary buffer for graph-cut with 4 neighborhood labeling.
- **NppStatus nppiGraphcut8GetSize** (**NppiSize** oSize, int *pBufSize)
Calculates the size of the temporary buffer for graph-cut with 8 neighborhood labeling.
- **NppStatus nppiGraphcutInitAlloc** (**NppiSize** oSize, **NppiGraphcutState** **ppState, **Npp8u** *pDeviceMem)
Initializes graph-cut state structure and allocates additional resources for graph-cut with 8 neighborhood labeling.
- **NppStatus nppiGraphcut8InitAlloc** (**NppiSize** oSize, **NppiGraphcutState** **ppState, **Npp8u** *pDeviceMem)
Allocates and initializes the graph-cut state structure and additional resources for graph-cut with 8 neighborhood labeling.
- **NppStatus nppiGraphcutFree** (**NppiGraphcutState** *pState)
Frees the additional resources of the graph-cut state structure.
- **NppStatus nppiGraphcut_32s8u** (**Npp32s** *pTerminals, **Npp32s** *pLeftTransposed, **Npp32s** *pRightTransposed, **Npp32s** *pTop, **Npp32s** *pBottom, int nStep, int nTransposedStep, **NppiSize** size, **Npp8u** *pLabel, int nLabelStep, **NppiGraphcutState** *pState)
Graphcut of a flow network (32bit signed integer edge capacities).
- **NppStatus nppiGraphcut8_32s8u** (**Npp32s** *pTerminals, **Npp32s** *pLeftTransposed, **Npp32s** *pRightTransposed, **Npp32s** *pTop, **Npp32s** *pTopLeft, **Npp32s** *pTopRight, **Npp32s** *pBottom, **Npp32s** *pBottomLeft, **Npp32s** *pBottomRight, int nStep, int nTransposedStep, **NppiSize** size, **Npp8u** *pLabel, int nLabelStep, **NppiGraphcutState** *pState)
Graphcut of a flow network (32bit signed integer edge capacities).
- **NppStatus nppiGraphcut_32f8u** (**Npp32f** *pTerminals, **Npp32f** *pLeftTransposed, **Npp32f** *pRightTransposed, **Npp32f** *pTop, **Npp32f** *pBottom, int nStep, int nTransposedStep, **NppiSize** size, **Npp8u** *pLabel, int nLabelStep, **NppiGraphcutState** *pState)
Graphcut of a flow network (32bit float edge capacities).
- **NppStatus nppiGraphcut8_32f8u** (**Npp32f** *pTerminals, **Npp32f** *pLeftTransposed, **Npp32f** *pRightTransposed, **Npp32f** *pTop, **Npp32f** *pTopLeft, **Npp32f** *pTopRight, **Npp32f** *pBottom, **Npp32f** *pBottomLeft, **Npp32f** *pBottomRight, int nStep, int nTransposedStep, **NppiSize** size, **Npp8u** *pLabel, int nLabelStep, **NppiGraphcutState** *pState)
Graphcut of a flow network (32bit float edge capacities).

7.52.1 Function Documentation

7.52.1.1 `NppStatus nppiGraphcut8_32f8u (Npp32f * pTerminals, Npp32f * pLeftTransposed, Npp32f * pRightTransposed, Npp32f * pTop, Npp32f * pTopLeft, Npp32f * pTopRight, Npp32f * pBottom, Npp32f * pBottomLeft, Npp32f * pBottomRight, int nStep, int nTransposedStep, NppiSize size, Npp8u * pLabel, int nLabelStep, NppiGraphcutState * pState)`

Graphcut of a flow network (32bit float edge capacities).

The function computes the minimal cut (graphcut) of a 2D regular 8-connected graph. The inputs are the capacities of the horizontal (in transposed form), vertical and terminal (source and sink) edges. The capacities to source and sink are stored as capacity differences in the terminals array (`terminals(x) = source(x) - sink(x)`). The implementation assumes that the edge capacities for boundary edges that would connect to nodes outside the specified domain are set to 0 (for example `left(0,*) == 0`). If this is not fulfilled the computed labeling may be wrong! The computed binary labeling is encoded as unsigned 8bit values (0 and >0).

See also:

[nppiGraphcut8InitAlloc\(\)](#), [nppiGraphcutFree\(\)](#), [nppiGraphcut8GetSize\(\)](#).

Parameters:

- pTerminals* Pointer to differences of terminal edge capacities (`terminal(x) = source(x) - sink(x)`)
- pLeftTransposed* Pointer to transposed left edge capacities (`left(0,*)` must be 0)
- pRightTransposed* Pointer to transposed right edge capacities (`right(width-1,*)` must be 0)
- pTop* Pointer to top edge capacities (`top(*,0)` must be 0)
- pTopLeft* Pointer to top left edge capacities (`topleft(*,0)` & `topleft(0,*)` must be 0)
- pTopRight* Pointer to top right edge capacities (`topright(*,0)` & `topright(width-1,*)` must be 0)
- pBottom* Pointer to bottom edge capacities (`bottom(*,height-1)` must be 0)
- pBottomLeft* Pointer to bottom left edge capacities (`bottomleft(*,height-1)` && `bottomleft(0,*)` must be 0)
- pBottomRight* Pointer to bottom right edge capacities (`bottomright(*,height-1)` && `bottomright(width-1,*)` must be 0)
- nStep* Step in bytes between any pair of sequential rows of edge capacities
- nTransposedStep* Step in bytes between any pair of sequential rows of transposed edge capacities
- size* Graph size
- pLabel* Pointer to destination label image
- nLabelStep* Step in bytes between any pair of sequential rows of label image
- pState* Pointer to graph-cut state structure. This structure must be initialized allocated and initialized using [nppiGraphcut8InitAlloc\(\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.52.1.2 NppStatus nppiGraphcut8_32s8u (Npp32s * pTerminals, Npp32s * pLeftTransposed, Npp32s * pRightTransposed, Npp32s * pTop, Npp32s * pTopLeft, Npp32s * pTopRight, Npp32s * pBottom, Npp32s * pBottomLeft, Npp32s * pBottomRight, int nStep, int nTransposedStep, NppiSize size, Npp8u * pLabel, int nLabelStep, NppiGraphcutState * pState)

Graphcut of a flow network (32bit signed integer edge capacities).

The function computes the minimal cut (graphcut) of a 2D regular 8-connected graph. The inputs are the capacities of the horizontal (in transposed form), vertical and terminal (source and sink) edges. The capacities to source and sink are stored as capacity differences in the terminals array ($terminals(x) = source(x) - sink(x)$). The implementation assumes that the edge capacities for boundary edges that would connect to nodes outside the specified domain are set to 0 (for example $left(0,*) == 0$). If this is not fulfilled the computed labeling may be wrong! The computed binary labeling is encoded as unsigned 8bit values (0 and >0).

See also:

[nppiGraphcut8InitAlloc\(\)](#), [nppiGraphcutFree\(\)](#), [nppiGraphcut8GetSize\(\)](#).

Parameters:

pTerminals Pointer to differences of terminal edge capacities ($terminal(x) = source(x) - sink(x)$)

pLeftTransposed Pointer to transposed left edge capacities ($left(0,*)$ must be 0)

pRightTransposed Pointer to transposed right edge capacities ($right(width-1,*)$ must be 0)

pTop Pointer to top edge capacities ($top(*,0)$ must be 0)

pTopLeft Pointer to top left edge capacities ($opleft(*,0)$ & $opleft(0,*)$ must be 0)

pTopRight Pointer to top right edge capacities ($topright(*,0)$ & $topright(width-1,*)$ must be 0)

pBottom Pointer to bottom edge capacities ($bottom(*,height-1)$ must be 0)

pBottomLeft Pointer to bottom left edge capacities ($bottomleft(*,height-1)$ && $bottomleft(0,*)$ must be 0)

pBottomRight Pointer to bottom right edge capacities ($bottomright(*,height-1)$ && $bottomright(width-1,*)$ must be 0)

nStep Step in bytes between any pair of sequential rows of edge capacities

nTransposedStep Step in bytes between any pair of sequential rows of tranposed edge capacities

size Graph size

pLabel Pointer to destination label image

nLabelStep Step in bytes between any pair of sequential rows of label image

pState Pointer to graph-cut state structure. This structure must be initialized allocated and initialized using [nppiGraphcut8InitAlloc\(\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.52.1.3 NppStatus nppiGraphcut8GetSize (NppiSize oSize, int * pBufSize)

Calculates the size of the temporary buffer for graph-cut with 8 neighborhood labeling.

See also:

[nppiGraphcut8InitAlloc\(\)](#), [nppiGraphcut8_32s8u\(\)](#).

Parameters:

oSize Graph size.

pBufSize Pointer to variable that returns the size of the temporary buffer.

Returns:

NPP_SUCCESS Indicates no error. Any other value indicates an error or a warning

NPP_SIZE_ERROR Indicates an error condition if any image dimension has zero or negative value

NPP_NULL_POINTER_ERROR Indicates an error condition if pBufSize pointer is NULL

7.52.1.4 NppStatus nppiGraphcut8InitAlloc (NppiSize oSize, NppiGraphcutState ** ppState, Npp8u * pDeviceMem)

Allocates and initializes the graph-cut state structure and additional resources for graph-cut with 8 neighborhood labeling.

See also:

[nppiGraphcut8_32s8u\(\)](#), [nppiGraphcut8GetSize\(\)](#).

Parameters:

oSize Graph size

ppState Pointer to pointer to graph-cut state structure.

pDeviceMem to the sufficient amount of device memory. The CUDA runtime or NPP memory allocators must be used to allocate this memory. The minimum amount of device memory required to run graph-cut on a for a specific image size is computed by [nppiGraphcut8GetSize\(\)](#).

Returns:

NPP_SUCCESS Indicates no error. Any other value indicates an error or a warning

NPP_SIZE_ERROR Indicates an error condition if any image dimension has zero or negative value

NPP_NULL_POINTER_ERROR Indicates an error condition if pBufSize pointer is NULL

7.52.1.5 NppStatus nppiGraphcut_32f8u (Npp32f * pTerminals, Npp32f * pLeftTransposed, Npp32f * pRightTransposed, Npp32f * pTop, Npp32f * pBottom, int nStep, int nTransposedStep, NppiSize size, Npp8u * pLabel, int nLabelStep, NppiGraphcutState * pState)

Graphcut of a flow network (32bit float edge capacities).

The function computes the minimal cut (graphcut) of a 2D regular 4-connected graph. The inputs are the capacities of the horizontal (in transposed form), vertical and terminal (source and sink) edges. The capacities to source and sink are stored as capacity differences in the terminals array (terminals(x) = source(x) - sink(x)). The implementation assumes that the edge capacities for boundary edges that would connect to nodes outside the specified domain are set to 0 (for example left(0,*) == 0). If this is not fulfilled the computed labeling may be wrong! The computed binary labeling is encoded as unsigned 8bit values (0 and >0).

See also:

[nppiGraphcutInitAlloc\(\)](#), [nppiGraphcutFree\(\)](#), [nppiGraphcutGetSize\(\)](#).

Parameters:

pTerminals Pointer to differences of terminal edge capacities (terminal(x) = source(x) - sink(x))
pLeftTransposed Pointer to transposed left edge capacities (left(0,*) must be 0)
pRightTransposed Pointer to transposed right edge capacities (right(width-1,*) must be 0)
pTop Pointer to top edge capacities (top(*,0) must be 0)
pBottom Pointer to bottom edge capacities (bottom(*,height-1) must be 0)
nStep Step in bytes between any pair of sequential rows of edge capacities
nTransposedStep Step in bytes between any pair of sequential rows of transposed edge capacities
size Graph size
pLabel Pointer to destination label image
nLabelStep Step in bytes between any pair of sequential rows of label image
pState Pointer to graph-cut state structure. This structure must be initialized allocated and initialized using [nppiGraphcutInitAlloc\(\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.52.1.6 `NppStatus nppiGraphcut_32s8u (Npp32s * pTerminals, Npp32s * pLeftTransposed, Npp32s * pRightTransposed, Npp32s * pTop, Npp32s * pBottom, int nStep, int nTransposedStep, NppiSize size, Npp8u * pLabel, int nLabelStep, NppiGraphcutState * pState)`

Graphcut of a flow network (32bit signed integer edge capacities).

The function computes the minimal cut (graphcut) of a 2D regular 4-connected graph. The inputs are the capacities of the horizontal (in transposed form), vertical and terminal (source and sink) edges. The capacities to source and sink are stored as capacity differences in the terminals array (terminals(x) = source(x) - sink(x)). The implementation assumes that the edge capacities for boundary edges that would connect to nodes outside the specified domain are set to 0 (for example left(0,*) == 0). If this is not fulfilled the computed labeling may be wrong! The computed binary labeling is encoded as unsigned 8bit values (0 and >0).

See also:

[nppiGraphcutInitAlloc\(\)](#), [nppiGraphcutFree\(\)](#), [nppiGraphcutGetSize\(\)](#).

Parameters:

pTerminals Pointer to differences of terminal edge capacities (terminal(x) = source(x) - sink(x))
pLeftTransposed Pointer to transposed left edge capacities (left(0,*) must be 0)
pRightTransposed Pointer to transposed right edge capacities (right(width-1,*) must be 0)
pTop Pointer to top edge capacities (top(*,0) must be 0)
pBottom Pointer to bottom edge capacities (bottom(*,height-1) must be 0)
nStep Step in bytes between any pair of sequential rows of edge capacities

nTransposedStep Step in bytes between any pair of sequential rows of tranposed edge capacities

size Graph size

pLabel Pointer to destination label image

nLabelStep Step in bytes between any pair of sequential rows of label image

pState Pointer to graph-cut state structure. This structure must be initialized allocated and initialized using [nppiGraphcutInitAlloc\(\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.52.1.7 NppStatus nppiGraphcutFree (NppiGraphcutState * pState)

Frees the additional resources of the graph-cut state structure.

See also:

[nppiGraphcutInitAlloc](#)
[nppiGraphcut8InitAlloc](#)

Parameters:

pState Pointer to graph-cut state structure.

Returns:

NPP_SUCCESS Indicates no error. Any other value indicates an error or a warning
 NPP_SIZE_ERROR Indicates an error condition if any image dimension has zero or negative value
 NPP_NULL_POINTER_ERROR Indicates an error condition if pState pointer is NULL

7.52.1.8 NppStatus nppiGraphcutGetSize (NppiSize oSize, int * pBufSize)

Calculates the size of the temporary buffer for graph-cut with 4 neighborhood labeling.

See also:

[nppiGraphcutInitAlloc\(\)](#), [nppiGraphcut_32s8u\(\)](#).

Parameters:

oSize Graph size.

pBufSize Pointer to variable that returns the size of the temporary buffer.

Returns:

NPP_SUCCESS Indicates no error. Any other value indicates an error or a warning
 NPP_SIZE_ERROR Indicates an error condition if any image dimension has zero or negative value
 NPP_NULL_POINTER_ERROR Indicates an error condition if pBufSize pointer is NULL

7.52.1.9 NppStatus nppiGraphcutInitAlloc (NppiSize *oSize*, NppiGraphcutState ** *ppState*, Npp8u * *pDeviceMem*)

Initializes graph-cut state structure and allocates additional resources for graph-cut with 8 neighborhood labeling.

See also:

[nppiGraphcut_32s8u\(\)](#), [nppiGraphcutGetSize\(\)](#).

Parameters:

oSize Graph size

ppState Pointer to pointer to graph-cut state structure.

pDeviceMem pDeviceMem to the sufficient amount of device memory. The CUDA runtime or NPP memory allocators must be used to allocate this memory. The minimum amount of device memory required to run graph-cut on a for a specific image size is computed by [nppiGraphcutGetSize\(\)](#).

Returns:

NPP_SUCCESS Indicates no error. Any other value indicates an error or a warning

NPP_SIZE_ERROR Indicates an error condition if any image dimension has zero or negative value

NPP_NULL_POINTER_ERROR Indicates an error condition if pBufSize pointer is NULL

7.53 Data Exchange and Initialization

Primitives for initializing, copying and converting image data.

Modules

- [Set](#)

Primitives for setting pixels to a specific value.

- [Copy](#)
- [Convert](#)
- [Scale](#)
- [Copy Constant Border](#)
- [Copy Replicate Border](#)
- [Copy Wrap Border](#)
- [Copy Sub-Pixel](#)
- [Duplicate Channel](#)
- [Transpose](#)
- [Swap Channels](#)

7.53.1 Detailed Description

Primitives for initializing, copying and converting image data.

7.54 Set

Primitives for setting pixels to a specific value.

Set

Set all pixels within the ROI to a specific value.

- **NppStatus nppiSet_8s_C1R** (**Npp8s** nValue, **Npp8s** *pDst, int nDstStep, **NppiSize** oSizeROI)
8-bit image set.
- **NppStatus nppiSet_8s_C2R** (**Npp8s** aValue[2], **Npp8s** *pDst, int nDstStep, **NppiSize** oSizeROI)
8-bit two-channel image set.
- **NppStatus nppiSet_8s_C3R** (**Npp8s** aValue[3], **Npp8s** *pDst, int nDstStep, **NppiSize** oSizeROI)
8-bit three-channel image set.
- **NppStatus nppiSet_8s_C4R** (**Npp8s** aValue[4], **Npp8s** *pDst, int nDstStep, **NppiSize** oSizeROI)
8-bit four-channel image set.
- **NppStatus nppiSet_8s_AC4R** (**Npp8s** aValue[3], **Npp8s** *pDst, int nDstStep, **NppiSize** oSizeROI)
8-bit four-channel image set ignoring alpha channel.
- **NppStatus nppiSet_8u_C1R** (**Npp8u** nValue, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
8-bit unsigned image set.
- **NppStatus nppiSet_8u_C3R** (const **Npp8u** aValue[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
3 channel 8-bit unsigned image set.
- **NppStatus nppiSet_8u_C4R** (const **Npp8u** aValue[4], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 8-bit unsigned image set.
- **NppStatus nppiSet_8u_AC4R** (const **Npp8u** aValue[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 8-bit unsigned image set method, not affecting Alpha channel.
- **NppStatus nppiSet_16u_C1R** (**Npp16u** nValue, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
16-bit unsigned image set.
- **NppStatus nppiSet_16u_C2R** (const **Npp16u** aValue[2], **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
2 channel 16-bit unsigned image set.
- **NppStatus nppiSet_16u_C3R** (const **Npp16u** aValue[3], **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
3 channel 16-bit unsigned image set.

- [NppStatus nppiSet_16u_C4R](#) (const [Npp16u](#) aValue[4], [Npp16u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
4 channel 16-bit unsigned image set.
- [NppStatus nppiSet_16u_AC4R](#) (const [Npp16u](#) aValue[3], [Npp16u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
4 channel 16-bit unsigned image set method, not affecting Alpha channel.
- [NppStatus nppiSet_16s_C1R](#) ([Npp16s](#) nValue, [Npp16s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
16-bit image set.
- [NppStatus nppiSet_16s_C2R](#) (const [Npp16s](#) aValue[2], [Npp16s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
2 channel 16-bit image set.
- [NppStatus nppiSet_16s_C3R](#) (const [Npp16s](#) aValue[3], [Npp16s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
3 channel 16-bit image set.
- [NppStatus nppiSet_16s_C4R](#) (const [Npp16s](#) aValue[4], [Npp16s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
4 channel 16-bit image set.
- [NppStatus nppiSet_16s_AC4R](#) (const [Npp16s](#) aValue[3], [Npp16s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
4 channel 16-bit image set method, not affecting Alpha channel.
- [NppStatus nppiSet_16sc_C1R](#) ([Npp16sc](#) oValue, [Npp16sc](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
16-bit complex integer image set.
- [NppStatus nppiSet_16sc_C2R](#) ([Npp16sc](#) aValue[2], [Npp16sc](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
16-bit complex integer two-channel image set.
- [NppStatus nppiSet_16sc_C3R](#) ([Npp16sc](#) aValue[3], [Npp16sc](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
16-bit complex integer three-channel image set.
- [NppStatus nppiSet_16sc_C4R](#) ([Npp16sc](#) aValue[4], [Npp16sc](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
16-bit complex integer four-channel image set.
- [NppStatus nppiSet_16sc_AC4R](#) ([Npp16sc](#) aValue[3], [Npp16sc](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
16-bit complex integer four-channel image set ignoring alpha.
- [NppStatus nppiSet_32s_C1R](#) ([Npp32s](#) nValue, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
32-bit image set.

- **NppStatus nppiSet_32s_C3R** (const **Npp32s** aValue[3], **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI)
3 channel 32-bit image set.
- **NppStatus nppiSet_32s_C4R** (const **Npp32s** aValue[4], **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 32-bit image set.
- **NppStatus nppiSet_32s_AC4R** (const **Npp32s** aValue[3], **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 16-bit image set method, not affecting Alpha channel.
- **NppStatus nppiSet_32sc_C1R** (**Npp32sc** oValue, **Npp32sc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Single channel 32-bit complex integer image set.
- **NppStatus nppiSet_32sc_C2R** (**Npp32sc** aValue[2], **Npp32sc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Two channel 32-bit complex integer image set.
- **NppStatus nppiSet_32sc_C3R** (**Npp32sc** aValue[3], **Npp32sc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three channel 32-bit complex integer image set.
- **NppStatus nppiSet_32sc_C4R** (**Npp32sc** aValue[4], **Npp32sc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four channel 32-bit complex integer image set.
- **NppStatus nppiSet_32sc_AC4R** (**Npp32sc** aValue[3], **Npp32sc** *pDst, int nDstStep, **NppiSize** oSizeROI)
32-bit complex integer four-channel image set ignoring alpha.
- **NppStatus nppiSet_32f_C1R** (**Npp32f** nValue, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
32-bit floating point image set.
- **NppStatus nppiSet_32f_C3R** (const **Npp32f** aValue[3], **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
3 channel 32-bit floating point image set.
- **NppStatus nppiSet_32f_C4R** (const **Npp32f** aValue[4], **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 32-bit floating point image set.
- **NppStatus nppiSet_32f_AC4R** (const **Npp32f** aValue[3], **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 32-bit floating point image set method, not affecting Alpha channel.
- **NppStatus nppiSet_32fc_C1R** (**Npp32fc** oValue, **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Single channel 32-bit complex image set.

- [NppStatus nppiSet_32fc_C2R](#) ([Npp32fc](#) aValue[2], [Npp32fc](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Two channel 32-bit complex image set.
- [NppStatus nppiSet_32fc_C3R](#) ([Npp32fc](#) aValue[3], [Npp32fc](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Three channel 32-bit complex image set.
- [NppStatus nppiSet_32fc_C4R](#) ([Npp32fc](#) aValue[4], [Npp32fc](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Four channel 32-bit complex image set.
- [NppStatus nppiSet_32fc_AC4R](#) ([Npp32fc](#) aValue[3], [Npp32fc](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
32-bit complex four-channel image set ignoring alpha.

Masked Set

The masked set primitives have an additional "mask image" input.

The mask controls which pixels within the ROI are set. For details see [Masked Operation](#).

- [NppStatus nppiSet_8u_C1MR](#) ([Npp8u](#) nValue, [Npp8u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp8u](#) *pMask, int nMaskStep)
Masked 8-bit unsigned image set.
- [NppStatus nppiSet_8u_C3MR](#) (const [Npp8u](#) aValue[3], [Npp8u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp8u](#) *pMask, int nMaskStep)
Masked 3 channel 8-bit unsigned image set.
- [NppStatus nppiSet_8u_C4MR](#) (const [Npp8u](#) aValue[4], [Npp8u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp8u](#) *pMask, int nMaskStep)
Masked 4 channel 8-bit unsigned image set.
- [NppStatus nppiSet_8u_AC4MR](#) (const [Npp8u](#) aValue[3], [Npp8u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp8u](#) *pMask, int nMaskStep)
Masked 4 channel 8-bit unsigned image set method, not affecting Alpha channel.
- [NppStatus nppiSet_16u_C1MR](#) ([Npp16u](#) nValue, [Npp16u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp8u](#) *pMask, int nMaskStep)
Masked 16-bit unsigned image set.
- [NppStatus nppiSet_16u_C3MR](#) (const [Npp16u](#) aValue[3], [Npp16u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp8u](#) *pMask, int nMaskStep)
Masked 3 channel 16-bit unsigned image set.
- [NppStatus nppiSet_16u_C4MR](#) (const [Npp16u](#) aValue[4], [Npp16u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp8u](#) *pMask, int nMaskStep)
Masked 4 channel 16-bit unsigned image set.

- **NppStatus nppiSet_16u_AC4MR** (const **Npp16u** aValue[3], **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp8u** *pMask, int nMaskStep)
Masked 4 channel 16-bit unsigned image set method, not affecting Alpha channel.
- **NppStatus nppiSet_16s_C1MR** (**Npp16s** nValue, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp8u** *pMask, int nMaskStep)
Masked 16-bit image set.
- **NppStatus nppiSet_16s_C3MR** (const **Npp16s** aValue[3], **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp8u** *pMask, int nMaskStep)
Masked 3 channel 16-bit image set.
- **NppStatus nppiSet_16s_C4MR** (const **Npp16s** aValue[4], **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp8u** *pMask, int nMaskStep)
Masked 4 channel 16-bit image set.
- **NppStatus nppiSet_16s_AC4MR** (const **Npp16s** aValue[3], **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp8u** *pMask, int nMaskStep)
Masked 4 channel 16-bit image set method, not affecting Alpha channel.
- **NppStatus nppiSet_32s_C1MR** (**Npp32s** nValue, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp8u** *pMask, int nMaskStep)
Masked 32-bit image set.
- **NppStatus nppiSet_32s_C3MR** (const **Npp32s** aValue[3], **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp8u** *pMask, int nMaskStep)
Masked 3 channel 32-bit image set.
- **NppStatus nppiSet_32s_C4MR** (const **Npp32s** aValue[4], **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp8u** *pMask, int nMaskStep)
Masked 4 channel 32-bit image set.
- **NppStatus nppiSet_32s_AC4MR** (const **Npp32s** aValue[3], **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp8u** *pMask, int nMaskStep)
Masked 4 channel 16-bit image set method, not affecting Alpha channel.
- **NppStatus nppiSet_32f_C1MR** (**Npp32f** nValue, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp8u** *pMask, int nMaskStep)
Masked 32-bit floating point image set.
- **NppStatus nppiSet_32f_C3MR** (const **Npp32f** aValue[3], **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp8u** *pMask, int nMaskStep)
Masked 3 channel 32-bit floating point image set.
- **NppStatus nppiSet_32f_C4MR** (const **Npp32f** aValue[4], **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp8u** *pMask, int nMaskStep)
Masked 4 channel 32-bit floating point image set.
- **NppStatus nppiSet_32f_AC4MR** (const **Npp32f** aValue[3], **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp8u** *pMask, int nMaskStep)
Masked 4 channel 32-bit floating point image set method, not affecting Alpha channel.

Channel Set

The select-channel set primitives set a single color channel in multi-channel images to a given value.

The channel is selected by adjusting the `pDst` pointer to point to the desired color channel (see [Channel-of-Interest API](#)).

- `NppStatus nppiSet_8u_C3CR` (`Npp8u nValue`, `Npp8u *pDst`, `int nDstStep`, `NppiSize oSizeROI`)
3 channel 8-bit unsigned image set affecting only single channel.
- `NppStatus nppiSet_8u_C4CR` (`Npp8u nValue`, `Npp8u *pDst`, `int nDstStep`, `NppiSize oSizeROI`)
4 channel 8-bit unsigned image set affecting only single channel.
- `NppStatus nppiSet_16u_C3CR` (`Npp16u nValue`, `Npp16u *pDst`, `int nDstStep`, `NppiSize oSizeROI`)
3 channel 16-bit unsigned image set affecting only single channel.
- `NppStatus nppiSet_16u_C4CR` (`Npp16u nValue`, `Npp16u *pDst`, `int nDstStep`, `NppiSize oSizeROI`)
4 channel 16-bit unsigned image set affecting only single channel.
- `NppStatus nppiSet_16s_C3CR` (`Npp16s nValue`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oSizeROI`)
3 channel 16-bit signed image set affecting only single channel.
- `NppStatus nppiSet_16s_C4CR` (`Npp16s nValue`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oSizeROI`)
4 channel 16-bit signed image set affecting only single channel.
- `NppStatus nppiSet_32s_C3CR` (`Npp32s nValue`, `Npp32s *pDst`, `int nDstStep`, `NppiSize oSizeROI`)
3 channel 32-bit unsigned image set affecting only single channel.
- `NppStatus nppiSet_32s_C4CR` (`Npp32s nValue`, `Npp32s *pDst`, `int nDstStep`, `NppiSize oSizeROI`)
4 channel 32-bit unsigned image set affecting only single channel.
- `NppStatus nppiSet_32f_C3CR` (`Npp32f nValue`, `Npp32f *pDst`, `int nDstStep`, `NppiSize oSizeROI`)
3 channel 32-bit floating point image set affecting only single channel.
- `NppStatus nppiSet_32f_C4CR` (`Npp32f nValue`, `Npp32f *pDst`, `int nDstStep`, `NppiSize oSizeROI`)
4 channel 32-bit floating point image set affecting only single channel.

7.54.1 Detailed Description

Primitives for setting pixels to a specific value.

7.54.2 Function Documentation

7.54.2.1 `NppStatus nppiSet_16s_AC4MR` (`const Npp16s aValue[3]`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp8u *pMask`, `int nMaskStep`)

Masked 4 channel 16-bit image set method, not affecting Alpha channel.

Parameters:

aValue The pixel-value to be set.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.54.2.2 NppStatus nppiSet_16s_AC4R (const Npp16s aValue[3], Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 16-bit image set method, not affecting Alpha channel.

Parameters:

aValue The pixel-value to be set.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.54.2.3 NppStatus nppiSet_16s_C1MR (Npp16s nValue, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)

Masked 16-bit image set.

Parameters:

nValue The pixel-value to be set.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.54.2.4 NppStatus nppiSet_16s_C1R (Npp16s *nValue*, Npp16s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

16-bit image set.

Parameters:

nValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.54.2.5 NppStatus nppiSet_16s_C2R (const Npp16s *aValue*[2], Npp16s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

2 channel 16-bit image set.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.54.2.6 NppStatus nppiSet_16s_C3CR (Npp16s *nValue*, Npp16s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

3 channel 16-bit signed image set affecting only single channel.

Parameters:

nValue The pixel-value to be set.

pDst Select-Channel Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.54.2.7 NppStatus nppiSet_16s_C3MR (const Npp16s aValue[3], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)

Masked 3 channel 16-bit image set.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.54.2.8 NppStatus nppiSet_16s_C3R (const Npp16s aValue[3], Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 16-bit image set.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.54.2.9 NppStatus nppiSet_16s_C4CR (Npp16s nValue, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 16-bit signed image set affecting only single channel.

Parameters:

nValue The pixel-value to be set.

pDst Select-Channel Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.54.2.10 NppStatus nppiSet_16s_C4MR (const Npp16s *aValue*[4], Npp16s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, const Npp8u * *pMask*, int *nMaskStep*)

Masked 4 channel 16-bit image set.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.11 NppStatus nppiSet_16s_C4R (const Npp16s *aValue*[4], Npp16s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 16-bit image set.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.12 NppStatus nppiSet_16sc_AC4R (Npp16sc *aValue*[3], Npp16sc * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

16-bit complex integer four-channel image set ignoring alpha.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.13 NppStatus nppiSet_16sc_C1R (Npp16sc oValue, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI)

16-bit complex integer image set.

Parameters:

oValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.14 NppStatus nppiSet_16sc_C2R (Npp16sc aValue[2], Npp16sc * pDst, int nDstStep, NppiSize oSizeROI)

16-bit complex integer two-channel image set.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.15 NppStatus nppiSet_16sc_C3R (Npp16sc aValue[3], Npp16sc * pDst, int nDstStep, NppiSize oSizeROI)

16-bit complex integer three-channel image set.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.16 NppStatus nppiSet_16sc_C4R (Npp16sc aValue[4], Npp16sc * pDst, int nDstStep, NppiSize oSizeROI)

16-bit complex integer four-channel image set.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.17 NppStatus nppiSet_16u_AC4MR (const Npp16u aValue[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)

Masked 4 channel 16-bit unsigned image set method, not affecting Alpha channel.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.18 NppStatus nppiSet_16u_AC4R (const Npp16u aValue[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 16-bit unsigned image set method, not affecting Alpha channel.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.19 NppStatus nppiSet_16u_C1MR (Npp16u nValue, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)

Masked 16-bit unsigned image set.

Parameters:

nValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.54.2.20 NppStatus nppiSet_16u_C1R (Npp16u nValue, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

16-bit unsigned image set.

Parameters:

nValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.54.2.21 NppStatus nppiSet_16u_C2R (const Npp16u aValue[2], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

2 channel 16-bit unsigned image set.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.54.2.22 `NppStatus nppiSet_16u_C3CR` (`Npp16u nValue`, `Npp16u * pDst`, `int nDstStep`, `NppiSize oSizeROI`)

3 channel 16-bit unsigned image set affecting only single channel.

Parameters:

- nValue* The pixel-value to be set.
- pDst* [Select-Channel Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.23 `NppStatus nppiSet_16u_C3MR` (`const Npp16u aValue[3]`, `Npp16u * pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp8u * pMask`, `int nMaskStep`)

Masked 3 channel 16-bit unsigned image set.

Parameters:

- aValue* The pixel-value to be set.
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).
- pMask* [Mask-Image Pointer](#).
- nMaskStep* [Mask-Image Line Step](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.24 `NppStatus nppiSet_16u_C3R` (`const Npp16u aValue[3]`, `Npp16u * pDst`, `int nDstStep`, `NppiSize oSizeROI`)

3 channel 16-bit unsigned image set.

Parameters:

- aValue* The pixel-value to be set.
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.25 NppStatus nppiSet_16u_C4CR (Npp16u nValue, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 16-bit unsigned image set affecting only single channel.

Parameters:

- nValue* The pixel-value to be set.
- pDst* [Select-Channel Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.26 NppStatus nppiSet_16u_C4MR (const Npp16u aValue[4], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)

Masked 4 channel 16-bit unsigned image set.

Parameters:

- aValue* The pixel-value to be set.
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).
- pMask* [Mask-Image Pointer](#).
- nMaskStep* [Mask-Image Line Step](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.27 NppStatus nppiSet_16u_C4R (const Npp16u aValue[4], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 16-bit unsigned image set.

Parameters:

- aValue* The pixel-value to be set.
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.28 `NppStatus nppiSet_32f_AC4MR (const Npp32f aValue[3], Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)`

Masked 4 channel 32-bit floating point image set method, not affecting Alpha channel.

Parameters:

- aValue* The pixel-value to be set.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- pMask* Mask-Image Pointer.
- nMaskStep* Mask-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.29 `NppStatus nppiSet_32f_AC4R (const Npp32f aValue[3], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

4 channel 32-bit floating point image set method, not affecting Alpha channel.

Parameters:

- aValue* The pixel-value to be set.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.30 `NppStatus nppiSet_32f_C1MR (Npp32f nValue, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)`

Masked 32-bit floating point image set.

Parameters:

- nValue* The pixel-value to be set.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- pMask* Mask-Image Pointer.
- nMaskStep* Mask-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.31 NppStatus nppiSet_32f_C1R (Npp32f *nValue*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

32-bit floating point image set.

Parameters:

nValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.32 NppStatus nppiSet_32f_C3CR (Npp32f *nValue*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

3 channel 32-bit floating point image set affecting only single channel.

Parameters:

nValue The pixel-value to be set.

pDst Select-Channel Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.33 NppStatus nppiSet_32f_C3MR (const Npp32f *aValue*[3], Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, const Npp8u * *pMask*, int *nMaskStep*)

Masked 3 channel 32-bit floating point image set.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.34 NppStatus nppiSet_32f_C3R (const Npp32f aValue[3], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 32-bit floating point image set.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.35 NppStatus nppiSet_32f_C4CR (Npp32f nValue, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 32-bit floating point image set affecting only single channel.

Parameters:

nValue The pixel-value to be set.

pDst Select-Channel Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.36 NppStatus nppiSet_32f_C4MR (const Npp32f aValue[4], Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)

Masked 4 channel 32-bit floating point image set.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.37 NppStatus nppiSet_32f_C4R (const Npp32f aValue[4], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 32-bit floating point image set.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.54.2.38 NppStatus nppiSet_32fc_AC4R (Npp32fc aValue[3], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

32-bit complex four-channel image set ignoring alpha.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.54.2.39 NppStatus nppiSet_32fc_C1R (Npp32fc oValue, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

Single channel 32-bit complex image set.

Parameters:

oValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.54.2.40 NppStatus nppiSet_32fc_C2R (Npp32fc aValue[2], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

Two channel 32-bit complex image set.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.41 NppStatus nppiSet_32fc_C3R (Npp32fc aValue[3], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

Three channel 32-bit complex image set.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.42 NppStatus nppiSet_32fc_C4R (Npp32fc aValue[4], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

Four channel 32-bit complex image set.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.43 `NppStatus nppiSet_32s_AC4MR (const Npp32s aValue[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)`

Masked 4 channel 16-bit image set method, not affecting Alpha channel.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.44 `NppStatus nppiSet_32s_AC4R (const Npp32s aValue[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

4 channel 16-bit image set method, not affecting Alpha channel.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.45 `NppStatus nppiSet_32s_C1MR (Npp32s nValue, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)`

Masked 32-bit image set.

Parameters:

nValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.46 NppStatus nppiSet_32s_C1R (Npp32s *nValue*, Npp32s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

32-bit image set.

Parameters:

nValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.47 NppStatus nppiSet_32s_C3CR (Npp32s *nValue*, Npp32s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

3 channel 32-bit unsigned image set affecting only single channel.

Parameters:

nValue The pixel-value to be set.

pDst Select-Channel Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.48 NppStatus nppiSet_32s_C3MR (const Npp32s *aValue*[3], Npp32s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, const Npp8u * *pMask*, int *nMaskStep*)

Masked 3 channel 32-bit image set.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.49 NppStatus nppiSet_32s_C3R (const Npp32s aValue[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 32-bit image set.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.50 NppStatus nppiSet_32s_C4CR (Npp32s nValue, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 32-bit unsigned image set affecting only single channel.

Parameters:

nValue The pixel-value to be set.

pDst Select-Channel Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.51 NppStatus nppiSet_32s_C4MR (const Npp32s aValue[4], Npp32s * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)

Masked 4 channel 32-bit image set.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.52 NppStatus nppiSet_32s_C4R (const Npp32s aValue[4], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 32-bit image set.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.54.2.53 NppStatus nppiSet_32sc_AC4R (Npp32sc aValue[3], Npp32sc * pDst, int nDstStep, NppiSize oSizeROI)

32-bit complex integer four-channel image set ignoring alpha.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.54.2.54 NppStatus nppiSet_32sc_C1R (Npp32sc oValue, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI)

Single channel 32-bit complex integer image set.

Parameters:

oValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.54.2.55 NppStatus nppiSet_32sc_C2R (Npp32sc aValue[2], Npp32sc * pDst, int nDstStep, NppiSize oSizeROI)

Two channel 32-bit complex integer image set.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.56 NppStatus nppiSet_32sc_C3R (Npp32sc aValue[3], Npp32sc * pDst, int nDstStep, NppiSize oSizeROI)

Three channel 32-bit complex integer image set.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.57 NppStatus nppiSet_32sc_C4R (Npp32sc aValue[4], Npp32sc * pDst, int nDstStep, NppiSize oSizeROI)

Four channel 32-bit complex integer image set.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.58 NppStatus nppiSet_8s_AC4R (Npp8s *aValue*[3], Npp8s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

8-bit four-channel image set ignoring alpha channel.

Parameters:

aValue The pixel value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.54.2.59 NppStatus nppiSet_8s_C1R (Npp8s *nValue*, Npp8s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

8-bit image set.

Parameters:

nValue The pixel value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.54.2.60 NppStatus nppiSet_8s_C2R (Npp8s *aValue*[2], Npp8s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

8-bit two-channel image set.

Parameters:

aValue The pixel value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.54.2.61 NppStatus nppiSet_8s_C3R (Npp8s aValue[3], Npp8s * pDst, int nDstStep, NppiSize oSizeROI)

8-bit three-channel image set.

Parameters:

aValue The pixel value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.54.2.62 NppStatus nppiSet_8s_C4R (Npp8s aValue[4], Npp8s * pDst, int nDstStep, NppiSize oSizeROI)

8-bit four-channel image set.

Parameters:

aValue The pixel value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.54.2.63 NppStatus nppiSet_8u_AC4MR (const Npp8u aValue[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)

Masked 4 channel 8-bit unsigned image set method, not affecting Alpha channel.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.54.2.64 NppStatus nppiSet_8u_AC4R (const Npp8u aValue[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 8-bit unsigned image set method, not affecting Alpha channel.

Parameters:

aValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.65 NppStatus nppiSet_8u_C1MR (Npp8u nValue, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)

Masked 8-bit unsigned image set.

Parameters:

nValue The pixel value to be set.

pDst Pointer [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pMask [Mask-Image Pointer](#).

nMaskStep [Mask-Image Line Step](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.66 NppStatus nppiSet_8u_C1R (Npp8u nValue, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

8-bit unsigned image set.

Parameters:

nValue The pixel value to be set.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.67 NppStatus nppiSet_8u_C3CR (Npp8u *nValue*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

3 channel 8-bit unsigned image set affecting only single channel.

Parameters:

- nValue* The pixel-value to be set.
- pDst* [Select-Channel Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.68 NppStatus nppiSet_8u_C3MR (const Npp8u *aValue*[3], Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, const Npp8u * *pMask*, int *nMaskStep*)

Masked 3 channel 8-bit unsigned image set.

Parameters:

- aValue* The pixel-value to be set.
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).
- pMask* [Mask-Image Pointer](#).
- nMaskStep* [Mask-Image Line Step](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.69 NppStatus nppiSet_8u_C3R (const Npp8u *aValue*[3], Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

3 channel 8-bit unsigned image set.

Parameters:

- aValue* The pixel value to be set.
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.70 NppStatus nppiSet_8u_C4CR (Npp8u *nValue*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 8-bit unsigned image set affecting only single channel.

Parameters:

- nValue* The pixel-value to be set.
- pDst* [Select-Channel Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.71 NppStatus nppiSet_8u_C4MR (const Npp8u *aValue*[4], Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, const Npp8u * *pMask*, int *nMaskStep*)

Masked 4 channel 8-bit unsigned image set.

Parameters:

- aValue* The pixel-value to be set.
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).
- pMask* [Mask-Image Pointer](#).
- nMaskStep* [Mask-Image Line Step](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.54.2.72 NppStatus nppiSet_8u_C4R (const Npp8u *aValue*[4], Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 8-bit unsigned image set.

Parameters:

- aValue* The pixel-value to be set.
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55 Copy

Copy

Copy pixels from one image to another.

- **NppStatus nppiCopy_8s_C1R** (const **Npp8s** *pSrc, int nSrcStep, **Npp8s** *pDst, int nDstStep, **NppiSize** oSizeROI)
8-bit image copy.
- **NppStatus nppiCopy_8s_C2R** (const **Npp8s** *pSrc, int nSrcStep, **Npp8s** *pDst, int nDstStep, **NppiSize** oSizeROI)
Two-channel 8-bit image copy.
- **NppStatus nppiCopy_8s_C3R** (const **Npp8s** *pSrc, int nSrcStep, **Npp8s** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three-channel 8-bit image copy.
- **NppStatus nppiCopy_8s_C4R** (const **Npp8s** *pSrc, int nSrcStep, **Npp8s** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four-channel 8-bit image copy.
- **NppStatus nppiCopy_8s_AC4R** (const **Npp8s** *pSrc, int nSrcStep, **Npp8s** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four-channel 8-bit image copy, ignoring alpha channel.
- **NppStatus nppiCopy_8u_C1R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
8-bit unsigned image copy.
- **NppStatus nppiCopy_8u_C3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three channel 8-bit unsigned image copy.
- **NppStatus nppiCopy_8u_C4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 8-bit unsigned image copy.
- **NppStatus nppiCopy_8u_AC4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 8-bit unsigned image copy, not affecting Alpha channel.
- **NppStatus nppiCopy_16u_C1R** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
16-bit unsigned image copy.
- **NppStatus nppiCopy_16u_C3R** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three channel 16-bit unsigned image copy.

- `NppStatus nppiCopy_16u_C4R` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
4 channel 16-bit unsigned image copy.
- `NppStatus nppiCopy_16u_AC4R` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
4 channel 16-bit unsigned image copy, not affecting Alpha channel.
- `NppStatus nppiCopy_16s_C1R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
16-bit image copy.
- `NppStatus nppiCopy_16s_C3R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Three channel 16-bit image copy.
- `NppStatus nppiCopy_16s_C4R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
4 channel 16-bit image copy.
- `NppStatus nppiCopy_16s_AC4R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
4 channel 16-bit image copy, not affecting Alpha.
- `NppStatus nppiCopy_16sc_C1R` (const `Npp16sc *pSrc`, int `nSrcStep`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
16-bit complex image copy.
- `NppStatus nppiCopy_16sc_C2R` (const `Npp16sc *pSrc`, int `nSrcStep`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Two-channel 16-bit complex image copy.
- `NppStatus nppiCopy_16sc_C3R` (const `Npp16sc *pSrc`, int `nSrcStep`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Three-channel 16-bit complex image copy.
- `NppStatus nppiCopy_16sc_C4R` (const `Npp16sc *pSrc`, int `nSrcStep`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four-channel 16-bit complex image copy.
- `NppStatus nppiCopy_16sc_AC4R` (const `Npp16sc *pSrc`, int `nSrcStep`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four-channel 16-bit complex image copy, ignoring alpha.
- `NppStatus nppiCopy_32s_C1R` (const `Npp32s *pSrc`, int `nSrcStep`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
32-bit image copy.
- `NppStatus nppiCopy_32s_C3R` (const `Npp32s *pSrc`, int `nSrcStep`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Three channel 32-bit image copy.

- `NppStatus nppiCopy_32s_C4R` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
4 channel 32-bit image copy.
- `NppStatus nppiCopy_32s_AC4R` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
4 channel 32-bit image copy, not affecting Alpha.
- `NppStatus nppiCopy_32sc_C1R` (const `Npp32sc` *pSrc, int nSrcStep, `Npp32sc` *pDst, int nDstStep, `NppiSize` oSizeROI)
32-bit complex image copy.
- `NppStatus nppiCopy_32sc_C2R` (const `Npp32sc` *pSrc, int nSrcStep, `Npp32sc` *pDst, int nDstStep, `NppiSize` oSizeROI)
Two-channel 32-bit complex image copy.
- `NppStatus nppiCopy_32sc_C3R` (const `Npp32sc` *pSrc, int nSrcStep, `Npp32sc` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three-channel 32-bit complex image copy.
- `NppStatus nppiCopy_32sc_C4R` (const `Npp32sc` *pSrc, int nSrcStep, `Npp32sc` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four-channel 32-bit complex image copy.
- `NppStatus nppiCopy_32sc_AC4R` (const `Npp32sc` *pSrc, int nSrcStep, `Npp32sc` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four-channel 32-bit complex image copy, ignoring alpha.
- `NppStatus nppiCopy_32f_C1R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)
32-bit floating point image copy.
- `NppStatus nppiCopy_32f_C3R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three channel 32-bit floating point image copy.
- `NppStatus nppiCopy_32f_C4R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)
4 channel 32-bit floating point image copy.
- `NppStatus nppiCopy_32f_AC4R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)
4 channel 32-bit floating point image copy, not affecting Alpha.
- `NppStatus nppiCopy_32fc_C1R` (const `Npp32fc` *pSrc, int nSrcStep, `Npp32fc` *pDst, int nDstStep, `NppiSize` oSizeROI)
32-bit floating-point complex image copy.
- `NppStatus nppiCopy_32fc_C2R` (const `Npp32fc` *pSrc, int nSrcStep, `Npp32fc` *pDst, int nDstStep, `NppiSize` oSizeROI)

Two-channel 32-bit floating-point complex image copy.

- `NppStatus nppiCopy_32fc_C3R` (const `Npp32fc` *pSrc, int nSrcStep, `Npp32fc` *pDst, int nDstStep, `NppiSize` oSizeROI)

Three-channel 32-bit floating-point complex image copy.

- `NppStatus nppiCopy_32fc_C4R` (const `Npp32fc` *pSrc, int nSrcStep, `Npp32fc` *pDst, int nDstStep, `NppiSize` oSizeROI)

Four-channel 32-bit floating-point complex image copy.

- `NppStatus nppiCopy_32fc_AC4R` (const `Npp32fc` *pSrc, int nSrcStep, `Npp32fc` *pDst, int nDstStep, `NppiSize` oSizeROI)

Four-channel 32-bit floating-point complex image copy, ignoring alpha.

Masked Copy

The masked copy primitives have an additional "mask image" input.

The mask controls which pixels within the ROI are copied. For details see [Masked Operation](#).

- `NppStatus nppiCopy_8u_C1MR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, int nMaskStep)

Masked Operation 8-bit unsigned image copy.

- `NppStatus nppiCopy_8u_C3MR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, int nMaskStep)

Masked Operation three channel 8-bit unsigned image copy.

- `NppStatus nppiCopy_8u_C4MR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, int nMaskStep)

Masked Operation four channel 8-bit unsigned image copy.

- `NppStatus nppiCopy_8u_AC4MR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, int nMaskStep)

Masked Operation four channel 8-bit unsigned image copy, ignoring alpha.

- `NppStatus nppiCopy_16u_C1MR` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, int nMaskStep)

Masked Operation 16-bit unsigned image copy.

- `NppStatus nppiCopy_16u_C3MR` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, int nMaskStep)

Masked Operation three channel 16-bit unsigned image copy.

- `NppStatus nppiCopy_16u_C4MR` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, int nMaskStep)

Masked Operation four channel 16-bit unsigned image copy.

- `NppStatus nppiCopy_16u_AC4MR` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, int nMaskStep)

Masked Operation four channel 16-bit unsigned image copy, ignoring alpha.

- `NppStatus nppiCopy_16s_C1MR` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, int nMaskStep)

Masked Operation 16-bit signed image copy.

- `NppStatus nppiCopy_16s_C3MR` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, int nMaskStep)

Masked Operation three channel 16-bit signed image copy.

- `NppStatus nppiCopy_16s_C4MR` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, int nMaskStep)

Masked Operation four channel 16-bit signed image copy.

- `NppStatus nppiCopy_16s_AC4MR` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, int nMaskStep)

Masked Operation four channel 16-bit signed image copy, ignoring alpha.

- `NppStatus nppiCopy_32s_C1MR` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, int nMaskStep)

Masked Operation 32-bit signed image copy.

- `NppStatus nppiCopy_32s_C3MR` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, int nMaskStep)

Masked Operation three channel 32-bit signed image copy.

- `NppStatus nppiCopy_32s_C4MR` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, int nMaskStep)

Masked Operation four channel 32-bit signed image copy.

- `NppStatus nppiCopy_32s_AC4MR` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, int nMaskStep)

Masked Operation four channel 32-bit signed image copy, ignoring alpha.

- `NppStatus nppiCopy_32f_C1MR` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, int nMaskStep)

Masked Operation 32-bit float image copy.

- `NppStatus nppiCopy_32f_C3MR` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, int nMaskStep)

Masked Operation three channel 32-bit float image copy.

- `NppStatus nppiCopy_32f_C4MR` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, int nMaskStep)

Masked Operation four channel 32-bit float image copy.

- `NppStatus nppiCopy_32f_AC4MR` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, int nMaskStep)

Masked Operation four channel 32-bit float image copy, ignoring alpha.

Channel Copy

The channel copy primitives copy a single color channel from a multi-channel source image to any other color channel in a multi-channel destination image.

The channel is selected by adjusting the respective image pointers to point to the desired color channel (see [Channel-of-Interest API](#)).

- `NppStatus nppiCopy_8u_C3CR` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Select-channel 8-bit unsigned image copy for three-channel images.

- `NppStatus nppiCopy_8u_C4CR` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Select-channel 8-bit unsigned image copy for four-channel images.

- `NppStatus nppiCopy_16s_C3CR` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Select-channel 16-bit signed image copy for three-channel images.

- `NppStatus nppiCopy_16s_C4CR` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Select-channel 16-bit signed image copy for four-channel images.

- `NppStatus nppiCopy_16u_C3CR` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Select-channel 16-bit unsigned image copy for three-channel images.

- `NppStatus nppiCopy_16u_C4CR` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Select-channel 16-bit unsigned image copy for four-channel images.

- `NppStatus nppiCopy_32s_C3CR` (const `Npp32s *pSrc`, int `nSrcStep`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Select-channel 32-bit signed image copy for three-channel images.

- `NppStatus nppiCopy_32s_C4CR` (const `Npp32s *pSrc`, int `nSrcStep`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Select-channel 32-bit signed image copy for four-channel images.

- `NppStatus nppiCopy_32f_C3CR` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Select-channel 32-bit float image copy for three-channel images.

- `NppStatus nppiCopy_32f_C4CR` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Select-channel 32-bit float image copy for four-channel images.

Extract Channel Copy

The channel extract primitives copy a single color channel from a multi-channel source image to single-channel destination image.

The channel is selected by adjusting the source image pointer to point to the desired color channel (see [Channel-of-Interest API](#)).

- `NppStatus nppiCopy_8u_C3C1R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Three-channel to single-channel 8-bit unsigned image copy.

- `NppStatus nppiCopy_8u_C4C1R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Four-channel to single-channel 8-bit unsigned image copy.

- `NppStatus nppiCopy_16s_C3C1R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Three-channel to single-channel 16-bit signed image copy.

- `NppStatus nppiCopy_16s_C4C1R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Four-channel to single-channel 16-bit signed image copy.

- `NppStatus nppiCopy_16u_C3C1R` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Three-channel to single-channel 16-bit unsigned image copy.

- `NppStatus nppiCopy_16u_C4C1R` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Four-channel to single-channel 16-bit unsigned image copy.

- `NppStatus nppiCopy_32s_C3C1R` (const `Npp32s *pSrc`, int `nSrcStep`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Three-channel to single-channel 32-bit signed image copy.

- `NppStatus nppiCopy_32s_C4C1R` (const `Npp32s *pSrc`, int `nSrcStep`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Four-channel to single-channel 32-bit signed image copy.

- `NppStatus nppiCopy_32f_C3C1R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Three-channel to single-channel 32-bit float image copy.

- `NppStatus nppiCopy_32f_C4C1R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Four-channel to single-channel 32-bit float image copy.

Insert Channel Copy

The channel insert primitives copy a single-channel source image into one of the color channels in a multi-channel destination image.

The channel is selected by adjusting the destination image pointer to point to the desired color channel (see [Channel-of-Interest API](#)).

- `NppStatus nppiCopy_8u_C1C3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Single-channel to three-channel 8-bit unsigned image copy.

- `NppStatus nppiCopy_8u_C1C4R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Single-channel to four-channel 8-bit unsigned image copy.

- `NppStatus nppiCopy_16s_C1C3R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Single-channel to three-channel 16-bit signed image copy.

- `NppStatus nppiCopy_16s_C1C4R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Single-channel to four-channel 16-bit signed image copy.

- `NppStatus nppiCopy_16u_C1C3R` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Single-channel to three-channel 16-bit unsigned image copy.

- `NppStatus nppiCopy_16u_C1C4R` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Single-channel to four-channel 16-bit unsigned image copy.

- `NppStatus nppiCopy_32s_C1C3R` (const `Npp32s *pSrc`, int `nSrcStep`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Single-channel to three-channel 32-bit signed image copy.

- `NppStatus nppiCopy_32s_C1C4R` (const `Npp32s *pSrc`, int `nSrcStep`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Single-channel to four-channel 32-bit signed image copy.

- `NppStatus nppiCopy_32f_C1C3R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Single-channel to three-channel 32-bit float image copy.

- `NppStatus nppiCopy_32f_C1C4R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Single-channel to four-channel 32-bit float image copy.

Packed-to-Planar Copy

Split a packed multi-channel image into a planar image.

E.g. copy the three channels of an RGB image into three separate single-channel images.

- `NppStatus nppiCopy_8u_C3P3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *const aDst[3], int nDstStep, `NppiSize` oSizeROI)
Three-channel 8-bit unsigned packed to planar image copy.
- `NppStatus nppiCopy_8u_C4P4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *const aDst[4], int nDstStep, `NppiSize` oSizeROI)
Four-channel 8-bit unsigned packed to planar image copy.
- `NppStatus nppiCopy_16s_C3P3R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *const aDst[3], int nDstStep, `NppiSize` oSizeROI)
Three-channel 16-bit signed packed to planar image copy.
- `NppStatus nppiCopy_16s_C4P4R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *const aDst[4], int nDstStep, `NppiSize` oSizeROI)
Four-channel 16-bit signed packed to planar image copy.
- `NppStatus nppiCopy_16u_C3P3R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *const aDst[3], int nDstStep, `NppiSize` oSizeROI)
Three-channel 16-bit unsigned packed to planar image copy.
- `NppStatus nppiCopy_16u_C4P4R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *const aDst[4], int nDstStep, `NppiSize` oSizeROI)
Four-channel 16-bit unsigned packed to planar image copy.
- `NppStatus nppiCopy_32s_C3P3R` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *const aDst[3], int nDstStep, `NppiSize` oSizeROI)
Three-channel 32-bit signed packed to planar image copy.
- `NppStatus nppiCopy_32s_C4P4R` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *const aDst[4], int nDstStep, `NppiSize` oSizeROI)
Four-channel 32-bit signed packed to planar image copy.
- `NppStatus nppiCopy_32f_C3P3R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *const aDst[3], int nDstStep, `NppiSize` oSizeROI)
Three-channel 32-bit float packed to planar image copy.
- `NppStatus nppiCopy_32f_C4P4R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *const aDst[4], int nDstStep, `NppiSize` oSizeROI)
Four-channel 32-bit float packed to planar image copy.

Planar-to-Packed Copy

Combine multiple image planes into a packed multi-channel image.

E.g. copy three single-channel images into a single 3-channel image.

- [NppStatus nppiCopy_8u_P3C3R](#) (const [Npp8u](#) *const aSrc[3], int nSrcStep, [Npp8u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Three-channel 8-bit unsigned planar to packed image copy.
- [NppStatus nppiCopy_8u_P4C4R](#) (const [Npp8u](#) *const aSrc[4], int nSrcStep, [Npp8u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Four-channel 8-bit unsigned planar to packed image copy.
- [NppStatus nppiCopy_16u_P3C3R](#) (const [Npp16u](#) *const aSrc[3], int nSrcStep, [Npp16u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Three-channel 16-bit unsigned planar to packed image copy.
- [NppStatus nppiCopy_16u_P4C4R](#) (const [Npp16u](#) *const aSrc[4], int nSrcStep, [Npp16u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Four-channel 16-bit unsigned planar to packed image copy.
- [NppStatus nppiCopy_16s_P3C3R](#) (const [Npp16s](#) *const aSrc[3], int nSrcStep, [Npp16s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Three-channel 16-bit signed planar to packed image copy.
- [NppStatus nppiCopy_16s_P4C4R](#) (const [Npp16s](#) *const aSrc[4], int nSrcStep, [Npp16s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Four-channel 16-bit signed planar to packed image copy.
- [NppStatus nppiCopy_32s_P3C3R](#) (const [Npp32s](#) *const aSrc[3], int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Three-channel 32-bit signed planar to packed image copy.
- [NppStatus nppiCopy_32s_P4C4R](#) (const [Npp32s](#) *const aSrc[4], int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Four-channel 32-bit signed planar to packed image copy.
- [NppStatus nppiCopy_32f_P3C3R](#) (const [Npp32f](#) *const aSrc[3], int nSrcStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Three-channel 32-bit float planar to packed image copy.
- [NppStatus nppiCopy_32f_P4C4R](#) (const [Npp32f](#) *const aSrc[4], int nSrcStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Four-channel 32-bit float planar to packed image copy.

7.55.1 Function Documentation

7.55.1.1 [NppStatus nppiCopy_16s_AC4MR](#) (const [Npp16s](#) *pSrc, int nSrcStep, [Npp16s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp8u](#) *pMask, int nMaskStep)

[Masked Operation](#) four channel 16-bit signed image copy, ignoring alpha.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.2 NppStatus nppiCopy_16s_AC4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 16-bit image copy, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.3 NppStatus nppiCopy_16s_C1C3R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

Single-channel to three-channel 16-bit signed image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Select-Channel Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.4 NppStatus nppiCopy_16s_C1C4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

Single-channel to four-channel 16-bit signed image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Select-Channel Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.5 NppStatus nppiCopy_16s_C1MR (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)

Masked Operation 16-bit signed image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.6 NppStatus nppiCopy_16s_C1R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

16-bit image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.7 NppStatus nppiCopy_16s_C3C1R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

Three-channel to single-channel 16-bit signed image copy.

Parameters:

pSrc Select-Channel Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.8 NppStatus nppiCopy_16s_C3CR (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

Select-channel 16-bit signed image copy for three-channel images.

Parameters:

pSrc Select-Channel Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Select-Channel Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.9 NppStatus nppiCopy_16s_C3MR (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)

Masked Operation three channel 16-bit signed image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.10 NppStatus nppiCopy_16s_C3P3R (const Npp16s * pSrc, int nSrcStep, Npp16s *const aDst[3], int nDstStep, NppiSize oSizeROI)

Three-channel 16-bit signed packed to planar image copy.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- aDst* Destination-Planar-Image Pointer Array.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.11 NppStatus nppiCopy_16s_C3R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

Three channel 16-bit image copy.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.12 NppStatus nppiCopy_16s_C4C1R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

Four-channel to single-channel 16-bit signed image copy.

Parameters:

- pSrc* Select-Channel Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.13 NppStatus nppiCopy_16s_C4CR (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

Select-channel 16-bit signed image copy for four-channel images.

Parameters:

pSrc Select-Channel Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Select-Channel Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.14 NppStatus nppiCopy_16s_C4MR (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)

[Masked Operation](#) four channel 16-bit signed image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.15 NppStatus nppiCopy_16s_C4P4R (const Npp16s * pSrc, int nSrcStep, Npp16s *const aDst[4], int nDstStep, NppiSize oSizeROI)

Four-channel 16-bit signed packed to planar image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
aDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.16 NppStatus nppiCopy_16s_C4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 16-bit image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.17 NppStatus nppiCopy_16s_P3C3R (const Npp16s *const aSrc[3], int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

Three-channel 16-bit signed planar to packed image copy.

Parameters:

aSrc Planar Source-Planar-Image Pointer Array.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.18 NppStatus nppiCopy_16s_P4C4R (const Npp16s *const aSrc[4], int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

Four-channel 16-bit signed planar to packed image copy.

Parameters:

aSrc Planar Source-Planar-Image Pointer Array.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.19 NppStatus nppiCopy_16sc_AC4R (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI)

Four-channel 16-bit complex image copy, ignoring alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.20 NppStatus nppiCopy_16sc_C1R (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI)

16-bit complex image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.21 NppStatus nppiCopy_16sc_C2R (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI)

Two-channel 16-bit complex image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.22 NppStatus nppiCopy_16sc_C3R (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI)

Three-channel 16-bit complex image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.23 NppStatus nppiCopy_16sc_C4R (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI)

Four-channel 16-bit complex image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.24 NppStatus nppiCopy_16u_AC4MR (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)

Masked Operation four channel 16-bit unsigned image copy, ignoring alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.25 NppStatus nppiCopy_16u_AC4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 16-bit unsigned image copy, not affecting Alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.26 NppStatus nppiCopy_16u_C1C3R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Single-channel to three-channel 16-bit unsigned image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Select-Channel Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.27 NppStatus nppiCopy_16u_C1C4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Single-channel to four-channel 16-bit unsigned image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Select-Channel Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.28 `NppStatus nppiCopy_16u_C1MR (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)`

[Masked Operation](#) 16-bit unsigned image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.29 `NppStatus nppiCopy_16u_C1R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)`

16-bit unsigned image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.30 `NppStatus nppiCopy_16u_C3C1R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)`

Three-channel to single-channel 16-bit unsigned image copy.

Parameters:

pSrc Select-Channel Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.31 NppStatus nppiCopy_16u_C3CR (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Select-channel 16-bit unsigned image copy for three-channel images.

Parameters:

pSrc Select-Channel Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Select-Channel Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.32 NppStatus nppiCopy_16u_C3MR (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)

Masked Operation three channel 16-bit unsigned image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.33 NppStatus nppiCopy_16u_C3P3R (const Npp16u * pSrc, int nSrcStep, Npp16u * const aDst[3], int nDstStep, NppiSize oSizeROI)

Three-channel 16-bit unsigned packed to planar image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
aDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.34 NppStatus nppiCopy_16u_C3R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Three channel 16-bit unsigned image copy.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.35 NppStatus nppiCopy_16u_C4C1R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four-channel to single-channel 16-bit unsigned image copy.

Parameters:

- pSrc* Select-Channel Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.36 NppStatus nppiCopy_16u_C4CR (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Select-channel 16-bit unsigned image copy for four-channel images.

Parameters:

- pSrc* Select-Channel Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Select-Channel Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.37 `NppStatus nppiCopy_16u_C4MR (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)`

Masked Operation four channel 16-bit unsigned image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.38 `NppStatus nppiCopy_16u_C4P4R (const Npp16u * pSrc, int nSrcStep, Npp16u *const aDst[4], int nDstStep, NppiSize oSizeROI)`

Four-channel 16-bit unsigned packed to planar image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
aDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.39 `NppStatus nppiCopy_16u_C4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)`

4 channel 16-bit unsigned image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.40 `NppStatus nppiCopy_16u_P3C3R (const Npp16u *const aSrc[3], int nSrcStep, Npp16u *pDst, int nDstStep, NppiSize oSizeROI)`

Three-channel 16-bit unsigned planar to packed image copy.

Parameters:

aSrc Planar [Source-Planar-Image Pointer Array](#).
nSrcStep [Source-Image Line Step](#).
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.41 `NppStatus nppiCopy_16u_P4C4R (const Npp16u *const aSrc[4], int nSrcStep, Npp16u *pDst, int nDstStep, NppiSize oSizeROI)`

Four-channel 16-bit unsigned planar to packed image copy.

Parameters:

aSrc Planar [Source-Planar-Image Pointer Array](#).
nSrcStep [Source-Image Line Step](#).
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.42 `NppStatus nppiCopy_32f_AC4MR (const Npp32f *pSrc, int nSrcStep, Npp32f *pDst, int nDstStep, NppiSize oSizeROI, const Npp8u *pMask, int nMaskStep)`

[Masked Operation](#) four channel 32-bit float image copy, ignoring alpha.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
pMask [Mask-Image Pointer](#).
nMaskStep [Mask-Image Line Step](#).
oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.43 NppStatus nppiCopy_32f_AC4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 32-bit floating point image copy, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.44 NppStatus nppiCopy_32f_C1C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Single-channel to three-channel 32-bit float image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Select-Channel Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.45 NppStatus nppiCopy_32f_C1C4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Single-channel to four-channel 32-bit float image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Select-Channel Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.46 `NppStatus nppiCopy_32f_C1MR (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)`

Masked Operation 32-bit float image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.47 `NppStatus nppiCopy_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

32-bit floating point image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.48 `NppStatus nppiCopy_32f_C3C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Three-channel to single-channel 32-bit float image copy.

Parameters:

pSrc Select-Channel Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.49 NppStatus nppiCopy_32f_C3CR (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Select-channel 32-bit float image copy for three-channel images.

Parameters:

pSrc Select-Channel Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Select-Channel Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.50 NppStatus nppiCopy_32f_C3MR (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)

Masked Operation three channel 32-bit float image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.51 NppStatus nppiCopy_32f_C3P3R (const Npp32f * pSrc, int nSrcStep, Npp32f *const aDst[3], int nDstStep, NppiSize oSizeROI)

Three-channel 32-bit float packed to planar image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
aDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.52 NppStatus nppiCopy_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Three channel 32-bit floating point image copy.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.53 NppStatus nppiCopy_32f_C4C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four-channel to single-channel 32-bit float image copy.

Parameters:

- pSrc* Select-Channel Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.54 NppStatus nppiCopy_32f_C4CR (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Select-channel 32-bit float image copy for four-channel images.

Parameters:

- pSrc* Select-Channel Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Select-Channel Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.55 `NppStatus nppiCopy_32f_C4MR (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)`

Masked Operation four channel 32-bit float image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.56 `NppStatus nppiCopy_32f_C4P4R (const Npp32f * pSrc, int nSrcStep, Npp32f *const aDst[4], int nDstStep, NppiSize oSizeROI)`

Four-channel 32-bit float packed to planar image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
aDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.57 `NppStatus nppiCopy_32f_C4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

4 channel 32-bit floating point image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.58 `NppStatus nppiCopy_32f_P3C3R (const Npp32f *const aSrc[3], int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Three-channel 32-bit float planar to packed image copy.

Parameters:

- aSrc* Planar [Source-Planar-Image Pointer Array](#).
- nSrcStep* [Source-Image Line Step](#).
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.59 `NppStatus nppiCopy_32f_P4C4R (const Npp32f *const aSrc[4], int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Four-channel 32-bit float planar to packed image copy.

Parameters:

- aSrc* Planar [Source-Planar-Image Pointer Array](#).
- nSrcStep* [Source-Image Line Step](#).
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.60 `NppStatus nppiCopy_32fc_AC4R (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Four-channel 32-bit floating-point complex image copy, ignoring alpha.

Parameters:

- pSrc* [Source-Image Pointer](#).
- nSrcStep* [Source-Image Line Step](#).
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.61 NppStatus nppiCopy_32fc_C1R (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

32-bit floating-point complex image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.62 NppStatus nppiCopy_32fc_C2R (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

Two-channel 32-bit floating-point complex image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.63 NppStatus nppiCopy_32fc_C3R (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

Three-channel 32-bit floating-point complex image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.64 `NppStatus nppiCopy_32fc_C4R (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Four-channel 32-bit floating-point complex image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.65 `NppStatus nppiCopy_32s_AC4MR (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)`

Masked Operation four channel 32-bit signed image copy, ignoring alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.66 `NppStatus nppiCopy_32s_AC4R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

4 channel 32-bit image copy, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.67 NppStatus nppiCopy_32s_C1C3R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Single-channel to three-channel 32-bit signed image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Select-Channel Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.68 NppStatus nppiCopy_32s_C1C4R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Single-channel to four-channel 32-bit signed image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Select-Channel Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.69 NppStatus nppiCopy_32s_C1MR (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)

Masked Operation 32-bit signed image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.70 NppStatus nppiCopy_32s_C1R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

32-bit image copy.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.71 NppStatus nppiCopy_32s_C3C1R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Three-channel to single-channel 32-bit signed image copy.

Parameters:

- pSrc* Select-Channel Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.72 NppStatus nppiCopy_32s_C3CR (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Select-channel 32-bit signed image copy for three-channel images.

Parameters:

- pSrc* Select-Channel Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Select-Channel Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.73 `NppStatus nppiCopy_32s_C3MR (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)`

Masked Operation three channel 32-bit signed image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.74 `NppStatus nppiCopy_32s_C3P3R (const Npp32s * pSrc, int nSrcStep, Npp32s *const aDst[3], int nDstStep, NppiSize oSizeROI)`

Three-channel 32-bit signed packed to planar image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
aDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.75 `NppStatus nppiCopy_32s_C3R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Three channel 32-bit image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.76 NppStatus nppiCopy_32s_C4C1R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Four-channel to single-channel 32-bit signed image copy.

Parameters:

pSrc Select-Channel Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.77 NppStatus nppiCopy_32s_C4CR (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Select-channel 32-bit signed image copy for four-channel images.

Parameters:

pSrc Select-Channel Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Select-Channel Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.78 NppStatus nppiCopy_32s_C4MR (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)

Masked Operation four channel 32-bit signed image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.79 NppStatus nppiCopy_32s_C4P4R (const Npp32s * pSrc, int nSrcStep, Npp32s *const aDst[4], int nDstStep, NppiSize oSizeROI)

Four-channel 32-bit signed packed to planar image copy.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- aDst* Destination-Planar-Image Pointer Array.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.80 NppStatus nppiCopy_32s_C4R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 32-bit image copy.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.81 NppStatus nppiCopy_32s_P3C3R (const Npp32s *const aSrc[3], int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Three-channel 32-bit signed planar to packed image copy.

Parameters:

- aSrc* Planar Source-Planar-Image Pointer Array.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.82 NppStatus nppiCopy_32s_P4C4R (const Npp32s *const aSrc[4], int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Four-channel 32-bit signed planar to packed image copy.

Parameters:

aSrc Planar Source-Planar-Image Pointer Array.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.83 NppStatus nppiCopy_32sc_AC4R (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI)

Four-channel 32-bit complex image copy, ignoring alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.84 NppStatus nppiCopy_32sc_C1R (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI)

32-bit complex image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.85 `NppStatus nppiCopy_32sc_C2R (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI)`

Two-channel 32-bit complex image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.86 `NppStatus nppiCopy_32sc_C3R (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI)`

Three-channel 32-bit complex image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.87 `NppStatus nppiCopy_32sc_C4R (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI)`

Four-channel 32-bit complex image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.88 NppStatus nppiCopy_8s_AC4R (const Npp8s * pSrc, int nSrcStep, Npp8s * pDst, int nDstStep, NppiSize oSizeROI)

Four-channel 8-bit image copy, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.89 NppStatus nppiCopy_8s_C1R (const Npp8s * pSrc, int nSrcStep, Npp8s * pDst, int nDstStep, NppiSize oSizeROI)

8-bit image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.90 NppStatus nppiCopy_8s_C2R (const Npp8s * pSrc, int nSrcStep, Npp8s * pDst, int nDstStep, NppiSize oSizeROI)

Two-channel 8-bit image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.91 NppStatus nppiCopy_8s_C3R (const Npp8s * pSrc, int nSrcStep, Npp8s * pDst, int nDstStep, NppiSize oSizeROI)

Three-channel 8-bit image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.92 NppStatus nppiCopy_8s_C4R (const Npp8s * pSrc, int nSrcStep, Npp8s * pDst, int nDstStep, NppiSize oSizeROI)

Four-channel 8-bit image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.93 NppStatus nppiCopy_8u_AC4MR (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)

[Masked Operation](#) four channel 8-bit unsigned image copy, ignoring alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.94 NppStatus nppiCopy_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 8-bit unsigned image copy, not affecting Alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.95 NppStatus nppiCopy_8u_C1C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Single-channel to three-channel 8-bit unsigned image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Select-Channel Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.96 NppStatus nppiCopy_8u_C1C4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Single-channel to four-channel 8-bit unsigned image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Select-Channel Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.97 `NppStatus nppiCopy_8u_C1MR (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)`

Masked Operation 8-bit unsigned image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.98 `NppStatus nppiCopy_8u_C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

8-bit unsigned image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.99 `NppStatus nppiCopy_8u_C3C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Three-channel to single-channel 8-bit unsigned image copy.

Parameters:

pSrc Select-Channel Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.100 NppStatus nppiCopy_8u_C3CR (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Select-channel 8-bit unsigned image copy for three-channel images.

Parameters:

pSrc Select-Channel Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Select-Channel Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.101 NppStatus nppiCopy_8u_C3MR (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)

Masked Operation three channel 8-bit unsigned image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.102 NppStatus nppiCopy_8u_C3P3R (const Npp8u * pSrc, int nSrcStep, Npp8u * const aDst[3], int nDstStep, NppiSize oSizeROI)

Three-channel 8-bit unsigned packed to planar image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
aDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.103 NppStatus nppiCopy_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Three channel 8-bit unsigned image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.104 NppStatus nppiCopy_8u_C4C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Four-channel to single-channel 8-bit unsigned image copy.

Parameters:

pSrc Select-Channel Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.105 NppStatus nppiCopy_8u_C4CR (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Select-channel 8-bit unsigned image copy for four-channel images.

Parameters:

pSrc Select-Channel Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Select-Channel Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.106 `NppStatus nppiCopy_8u_C4MR (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)`

[Masked Operation](#) four channel 8-bit unsigned image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.107 `NppStatus nppiCopy_8u_C4P4R (const Npp8u * pSrc, int nSrcStep, Npp8u *const aDst[4], int nDstStep, NppiSize oSizeROI)`

Four-channel 8-bit unsigned packed to planar image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
aDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.108 `NppStatus nppiCopy_8u_C4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

4 channel 8-bit unsigned image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.55.1.109 `NppStatus nppiCopy_8u_P3C3R (const Npp8u *const aSrc[3], int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Three-channel 8-bit unsigned planar to packed image copy.

Parameters:

aSrc Planar Source-Image Pointer.
nSrcStep Source-Planar-Image Pointer Array.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.55.1.110 `NppStatus nppiCopy_8u_P4C4R (const Npp8u *const aSrc[4], int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four-channel 8-bit unsigned planar to packed image copy.

Parameters:

aSrc Planar Source-Planar-Image Pointer Array.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56 Convert

Convert to Increase Bit-Depth

The integer conversion methods do not involve any scaling.

Also, even when increasing the bit-depth loss of information may occur:

- When converting integers (e.g. `Npp32u`) to float (e.g. `Npp32f`) integervalue not accurately representable by the float are rounded to the closest floating-point value.
- When converting signed integers to unsigned integers all negative values are lost (saturated to 0).
- `NppStatus nppiConvert_8u16u_C1R` (const `Npp8u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Single channel 8-bit unsigned to 16-bit unsigned conversion.
- `NppStatus nppiConvert_8u16u_C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three channel 8-bit unsigned to 16-bit unsigned conversion.
- `NppStatus nppiConvert_8u16u_C4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four channel 8-bit unsigned to 16-bit unsigned conversion.
- `NppStatus nppiConvert_8u16u_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four channel 8-bit unsigned to 16-bit unsigned conversion, not affecting Alpha.
- `NppStatus nppiConvert_8u16s_C1R` (const `Npp8u` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Single channel 8-bit unsigned to 16-bit signed conversion.
- `NppStatus nppiConvert_8u16s_C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three channel 8-bit unsigned to 16-bit signed conversion.
- `NppStatus nppiConvert_8u16s_C4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four channel 8-bit unsigned to 16-bit signed conversion.
- `NppStatus nppiConvert_8u16s_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four channel 8-bit unsigned to 16-bit signed conversion, not affecting Alpha.
- `NppStatus nppiConvert_8u32s_C1R` (const `Npp8u` *pSrc, int nSrcStep, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Single channel 8-bit unsigned to 32-bit signed conversion.
- `NppStatus nppiConvert_8u32s_C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)

Three channel 8-bit unsigned to 32-bit signed conversion.

- `NppStatus nppiConvert_8u32s_C4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)

Four channel 8-bit unsigned to 32-bit signed conversion.

- `NppStatus nppiConvert_8u32s_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)

Four channel 8-bit unsigned to 32-bit signed conversion, not affecting Alpha.

- `NppStatus nppiConvert_8u32f_C1R` (const `Npp8u` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)

Single channel 8-bit unsigned to 32-bit floating-point conversion.

- `NppStatus nppiConvert_8u32f_C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)

Three channel 8-bit unsigned to 32-bit floating-point conversion.

- `NppStatus nppiConvert_8u32f_C4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)

Four channel 8-bit unsigned to 32-bit floating-point conversion.

- `NppStatus nppiConvert_8u32f_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)

Four channel 8-bit unsigned to 32-bit floating-point conversion, not affecting Alpha.

- `NppStatus nppiConvert_8s32s_C1R` (const `Npp8s` *pSrc, int nSrcStep, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)

Single channel 8-bit signed to 32-bit signed conversion.

- `NppStatus nppiConvert_8s32s_C3R` (const `Npp8s` *pSrc, int nSrcStep, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)

Three channel 8-bit signed to 32-bit signed conversion.

- `NppStatus nppiConvert_8s32s_C4R` (const `Npp8s` *pSrc, int nSrcStep, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)

Four channel 8-bit signed to 32-bit signed conversion.

- `NppStatus nppiConvert_8s32s_AC4R` (const `Npp8s` *pSrc, int nSrcStep, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)

Four channel 8-bit signed to 32-bit signed conversion, not affecting Alpha.

- `NppStatus nppiConvert_8s32f_C1R` (const `Npp8s` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)

Single channel 8-bit signed to 32-bit floating-point conversion.

- `NppStatus nppiConvert_8s32f_C3R` (const `Npp8s` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)

Three channel 8-bit signed to 32-bit floating-point conversion.

- [NppStatus nppiConvert_8s32f_C4R](#) (const [Npp8s](#) *pSrc, int nSrcStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Four channel 8-bit signed to 32-bit floating-point conversion.
- [NppStatus nppiConvert_8s32f_AC4R](#) (const [Npp8s](#) *pSrc, int nSrcStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Four channel 8-bit signed to 32-bit floating-point conversion, not affecting Alpha.
- [NppStatus nppiConvert_16u32s_C1R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Single channel 16-bit unsigned to 32-bit signed conversion.
- [NppStatus nppiConvert_16u32s_C3R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Three channel 16-bit unsigned to 32-bit signed conversion.
- [NppStatus nppiConvert_16u32s_C4R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Four channel 16-bit unsigned to 32-bit signed conversion.
- [NppStatus nppiConvert_16u32s_AC4R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Four channel 16-bit unsigned to 32-bit signed conversion, not affecting Alpha.
- [NppStatus nppiConvert_16u32f_C1R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Single channel 16-bit unsigned to 32-bit floating-point conversion.
- [NppStatus nppiConvert_16u32f_C3R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Three channel 16-bit unsigned to 32-bit floating-point conversion.
- [NppStatus nppiConvert_16u32f_C4R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Four channel 16-bit unsigned to 32-bit floating-point conversion.
- [NppStatus nppiConvert_16u32f_AC4R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Four channel 16-bit unsigned to 32-bit floating-point conversion, not affecting Alpha.
- [NppStatus nppiConvert_16s32s_C1R](#) (const [Npp16s](#) *pSrc, int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Single channel 16-bit signed to 32-bit signed conversion.
- [NppStatus nppiConvert_16s32s_C3R](#) (const [Npp16s](#) *pSrc, int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Three channel 16-bit signed to 32-bit signed conversion.
- [NppStatus nppiConvert_16s32s_C4R](#) (const [Npp16s](#) *pSrc, int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Four channel 16-bit signed to 32-bit signed conversion.

- **NppStatus nppiConvert_16s32s_AC4R** (const **Npp16s** *pSrc, int nSrcStep, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four channel 16-bit signed to 32-bit signed conversion, not affecting Alpha.
- **NppStatus nppiConvert_16s32f_C1R** (const **Npp16s** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
Single channel 16-bit signed to 32-bit floating-point conversion.
- **NppStatus nppiConvert_16s32f_C3R** (const **Npp16s** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three channel 16-bit signed to 32-bit floating-point conversion.
- **NppStatus nppiConvert_16s32f_C4R** (const **Npp16s** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four channel 16-bit signed to 32-bit floating-point conversion.
- **NppStatus nppiConvert_16s32f_AC4R** (const **Npp16s** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four channel 16-bit signed to 32-bit floating-point conversion, not affecting Alpha.
- **NppStatus nppiConvert_8s8u_C1Rs** (const **Npp8s** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Single channel 8-bit signed to 8-bit unsigned conversion with saturation.
- **NppStatus nppiConvert_8s16u_C1Rs** (const **Npp8s** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Single channel 8-bit signed to 16-bit unsigned conversion with saturation.
- **NppStatus nppiConvert_8s16s_C1R** (const **Npp8s** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI)
Single channel 8-bit signed to 16-bit signed conversion.
- **NppStatus nppiConvert_8s32u_C1Rs** (const **Npp8s** *pSrc, int nSrcStep, **Npp32u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Single channel 8-bit signed to 32-bit unsigned conversion with saturation.
- **NppStatus nppiConvert_16s16u_C1Rs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Single channel 16-bit signed to 16-bit unsigned conversion with saturation.
- **NppStatus nppiConvert_16s32u_C1Rs** (const **Npp16s** *pSrc, int nSrcStep, **Npp32u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Single channel 16-bit signed to 32-bit unsigned conversion with saturation.
- **NppStatus nppiConvert_16u32u_C1R** (const **Npp16u** *pSrc, int nSrcStep, **Npp32u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Single channel 16-bit unsigned to 32-bit unsigned conversion.
- **NppStatus nppiConvert_32s32u_C1Rs** (const **Npp32s** *pSrc, int nSrcStep, **Npp32u** *pDst, int nDstStep, **NppiSize** oSizeROI)

Single channel 32-bit signed to 32-bit unsigned conversion with saturation.

- `NppStatus nppiConvert_32s32f_C1R` (const `Npp32s` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)

Single channel 32-bit signed to 32-bit floating-point conversion.

- `NppStatus nppiConvert_32u32f_C1R` (const `Npp32u` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)

Single channel 32-bit unsigned to 32-bit floating-point conversion.

Convert to Decrease Bit-Depth

The integer conversion methods do not involve any scaling.

When converting floating-point values to integers the user may choose the most appropriate rounding-mode. Typically information is lost when converting to lower bit depth:

- All converted values are saturated to the destination type's range. E.g. any values larger than the largest value of the destination type are clamped to the destination's maximum.
- Converting floating-point values to integer also involves rounding, effectively losing all fractional value information in the process.

- `NppStatus nppiConvert_16u8u_C1R` (const `Npp16u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)

Single channel 16-bit unsigned to 8-bit unsigned conversion.

- `NppStatus nppiConvert_16u8u_C3R` (const `Npp16u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)

Three channel 16-bit unsigned to 8-bit unsigned conversion.

- `NppStatus nppiConvert_16u8u_C4R` (const `Npp16u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)

Four channel 16-bit unsigned to 8-bit unsigned conversion.

- `NppStatus nppiConvert_16u8u_AC4R` (const `Npp16u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)

Four channel 16-bit unsigned to 8-bit unsigned conversion, not affecting Alpha.

- `NppStatus nppiConvert_16s8u_C1R` (const `Npp16s` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)

Single channel 16-bit signed to 8-bit unsigned conversion.

- `NppStatus nppiConvert_16s8u_C3R` (const `Npp16s` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)

Three channel 16-bit signed to 8-bit unsigned conversion.

- `NppStatus nppiConvert_16s8u_C4R` (const `Npp16s` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)

Four channel 16-bit signed to 8-bit unsigned conversion.

- **NppStatus nppiConvert_16s8u_AC4R** (const **Npp16s** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four channel 16-bit signed to 8-bit unsigned conversion, not affecting Alpha.
- **NppStatus nppiConvert_32s8u_C1R** (const **Npp32s** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Single channel 32-bit signed to 8-bit unsigned conversion.
- **NppStatus nppiConvert_32s8u_C3R** (const **Npp32s** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three channel 32-bit signed to 8-bit unsigned conversion.
- **NppStatus nppiConvert_32s8u_C4R** (const **Npp32s** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four channel 32-bit signed to 8-bit unsigned conversion.
- **NppStatus nppiConvert_32s8u_AC4R** (const **Npp32s** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four channel 32-bit signed to 8-bit unsigned conversion, not affecting Alpha.
- **NppStatus nppiConvert_32s8s_C1R** (const **Npp32s** *pSrc, int nSrcStep, **Npp8s** *pDst, int nDstStep, **NppiSize** oSizeROI)
Single channel 32-bit signed to 8-bit signed conversion.
- **NppStatus nppiConvert_32s8s_C3R** (const **Npp32s** *pSrc, int nSrcStep, **Npp8s** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three channel 32-bit signed to 8-bit signed conversion.
- **NppStatus nppiConvert_32s8s_C4R** (const **Npp32s** *pSrc, int nSrcStep, **Npp8s** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four channel 32-bit signed to 8-bit signed conversion.
- **NppStatus nppiConvert_32s8s_AC4R** (const **Npp32s** *pSrc, int nSrcStep, **Npp8s** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four channel 32-bit signed to 8-bit signed conversion, not affecting Alpha.
- **NppStatus nppiConvert_8u8s_C1RSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8s** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** eRoundMode, int nScaleFactor)
Single channel 8-bit unsigned to 8-bit signed conversion.
- **NppStatus nppiConvert_16u8s_C1RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp8s** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** eRoundMode, int nScaleFactor)
Single channel 16-bit unsigned to 8-bit signed conversion.
- **NppStatus nppiConvert_16s8s_C1RSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp8s** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** eRoundMode, int nScaleFactor)
Single channel 16-bit signed to 8-bit signed conversion.
- **NppStatus nppiConvert_16u16s_C1RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** eRoundMode, int nScaleFactor)

Single channel 16-bit unsigned to 16-bit signed conversion.

- `NppStatus nppiConvert_32u8u_C1RSfs` (const `Npp32u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppRoundMode` eRoundMode, int nScaleFactor)

Single channel 32-bit unsigned to 8-bit unsigned conversion.

- `NppStatus nppiConvert_32u8s_C1RSfs` (const `Npp32u` *pSrc, int nSrcStep, `Npp8s` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppRoundMode` eRoundMode, int nScaleFactor)

Single channel 32-bit unsigned to 8-bit signed conversion.

- `NppStatus nppiConvert_32u16u_C1RSfs` (const `Npp32u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppRoundMode` eRoundMode, int nScaleFactor)

Single channel 32-bit unsigned to 16-bit unsigned conversion.

- `NppStatus nppiConvert_32u16s_C1RSfs` (const `Npp32u` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppRoundMode` eRoundMode, int nScaleFactor)

Single channel 32-bit unsigned to 16-bit signed conversion.

- `NppStatus nppiConvert_32u32s_C1RSfs` (const `Npp32u` *pSrc, int nSrcStep, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppRoundMode` eRoundMode, int nScaleFactor)

Single channel 32-bit unsigned to 32-bit signed conversion.

- `NppStatus nppiConvert_32s16u_C1RSfs` (const `Npp32s` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppRoundMode` eRoundMode, int nScaleFactor)

Single channel 32-bit unsigned to 16-bit unsigned conversion.

- `NppStatus nppiConvert_32s16s_C1RSfs` (const `Npp32s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppRoundMode` eRoundMode, int nScaleFactor)

Single channel 32-bit unsigned to 16-bit signed conversion.

- `NppStatus nppiConvert_32f8u_C1R` (const `Npp32f` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppRoundMode` eRoundMode)

Single channel 32-bit floating point to 8-bit unsigned conversion.

- `NppStatus nppiConvert_32f8u_C3R` (const `Npp32f` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppRoundMode` eRoundMode)

Three channel 32-bit floating point to 8-bit unsigned conversion.

- `NppStatus nppiConvert_32f8u_C4R` (const `Npp32f` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppRoundMode` eRoundMode)

Four channel 32-bit floating point to 8-bit unsigned conversion.

- `NppStatus nppiConvert_32f8u_AC4R` (const `Npp32f` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppRoundMode` eRoundMode)

Four channel 32-bit floating point to 8-bit unsigned conversion, not affecting Alpha.

- `NppStatus nppiConvert_32f8s_C1R` (const `Npp32f` *pSrc, int nSrcStep, `Npp8s` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppRoundMode` eRoundMode)

Single channel 32-bit floating point to 8-bit signed conversion.

- `NppStatus nppiConvert_32f8s_C3R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp8s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppRoundMode eRoundMode`)
Three channel 32-bit floating point to 8-bit signed conversion.
- `NppStatus nppiConvert_32f8s_C4R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp8s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppRoundMode eRoundMode`)
Four channel 32-bit floating point to 8-bit signed conversion.
- `NppStatus nppiConvert_32f8s_AC4R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp8s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppRoundMode eRoundMode`)
Four channel 32-bit floating point to 8-bit signed conversion, not affecting Alpha.
- `NppStatus nppiConvert_32f16u_C1R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppRoundMode eRoundMode`)
Single channel 32-bit floating point to 16-bit unsigned conversion.
- `NppStatus nppiConvert_32f16u_C3R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppRoundMode eRoundMode`)
Three channel 32-bit floating point to 16-bit unsigned conversion.
- `NppStatus nppiConvert_32f16u_C4R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppRoundMode eRoundMode`)
Four channel 32-bit floating point to 16-bit unsigned conversion.
- `NppStatus nppiConvert_32f16u_AC4R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppRoundMode eRoundMode`)
Four channel 32-bit floating point to 16-bit unsigned conversion, not affecting Alpha.
- `NppStatus nppiConvert_32f16s_C1R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppRoundMode eRoundMode`)
Single channel 32-bit floating point to 16-bit signed conversion.
- `NppStatus nppiConvert_32f16s_C3R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppRoundMode eRoundMode`)
Three channel 32-bit floating point to 16-bit signed conversion.
- `NppStatus nppiConvert_32f16s_C4R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppRoundMode eRoundMode`)
Four channel 32-bit floating point to 16-bit signed conversion.
- `NppStatus nppiConvert_32f16s_AC4R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppRoundMode eRoundMode`)
Four channel 32-bit floating point to 16-bit signed conversion.
- `NppStatus nppiConvert_32f8u_C1RSfs` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppRoundMode eRoundMode`, int `nScaleFactor`)
Single channel 32-bit floating point to 8-bit unsigned conversion.
- `NppStatus nppiConvert_32f8s_C1RSfs` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp8s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppRoundMode eRoundMode`, int `nScaleFactor`)
Single channel 32-bit floating point to 8-bit signed conversion.

- `NppStatus nppiConvert_32f16u_C1RSfs` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppRoundMode eRoundMode`, int `nScaleFactor`)
Single channel 32-bit floating point to 16-bit unsigned conversion.
- `NppStatus nppiConvert_32f16s_C1RSfs` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppRoundMode eRoundMode`, int `nScaleFactor`)
Single channel 32-bit floating point to 16-bit signed conversion.
- `NppStatus nppiConvert_32f32u_C1RSfs` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppRoundMode eRoundMode`, int `nScaleFactor`)
Single channel 32-bit floating point to 32-bit unsigned conversion.
- `NppStatus nppiConvert_32f32s_C1RSfs` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppRoundMode eRoundMode`, int `nScaleFactor`)
Single channel 32-bit floating point to 32-bit signed conversion.

7.56.1 Function Documentation

7.56.1.1 `NppStatus nppiConvert_16s16u_C1Rs` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Single channel 16-bit signed to 16-bit unsigned conversion with saturation.

Parameters:

- `pSrc` Source-Image Pointer.
- `nSrcStep` Source-Image Line Step.
- `pDst` Destination-Image Pointer.
- `nDstStep` Destination-Image Line Step.
- `oSizeROI` Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.2 `NppStatus nppiConvert_16s32f_AC4R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Four channel 16-bit signed to 32-bit floating-point conversion, not affecting Alpha.

Parameters:

- `pSrc` Source-Image Pointer.
- `nSrcStep` Source-Image Line Step.
- `pDst` Destination-Image Pointer.
- `nDstStep` Destination-Image Line Step.
- `oSizeROI` Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.3 NppStatus nppiConvert_16s32f_C1R (const Npp16s * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Single channel 16-bit signed to 32-bit floating-point conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.4 NppStatus nppiConvert_16s32f_C3R (const Npp16s * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Three channel 16-bit signed to 32-bit floating-point conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.5 NppStatus nppiConvert_16s32f_C4R (const Npp16s * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four channel 16-bit signed to 32-bit floating-point conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.6 NppStatus nppiConvert_16s32s_AC4R (const Npp16s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Four channel 16-bit signed to 32-bit signed conversion, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.7 NppStatus nppiConvert_16s32s_C1R (const Npp16s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Single channel 16-bit signed to 32-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.8 NppStatus nppiConvert_16s32s_C3R (const Npp16s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Three channel 16-bit signed to 32-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.9 NppStatus nppiConvert_16s32s_C4R (const Npp16s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Four channel 16-bit signed to 32-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.10 NppStatus nppiConvert_16s32u_C1Rs (const Npp16s * pSrc, int nSrcStep, Npp32u * pDst, int nDstStep, NppiSize oSizeROI)

Single channel 16-bit signed to 32-bit unsigned conversion with saturation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.11 NppStatus nppiConvert_16s8s_C1RSfs (const Npp16s * pSrc, int nSrcStep, Npp8s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode, int nScaleFactor)

Single channel 16-bit signed to 8-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eRoundMode Rounding Mode Parameter.
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.12 NppStatus nppiConvert_16s8u_AC4R (const Npp16s * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Four channel 16-bit signed to 8-bit unsigned conversion, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.13 NppStatus nppiConvert_16s8u_C1R (const Npp16s * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Single channel 16-bit signed to 8-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.14 NppStatus nppiConvert_16s8u_C3R (const Npp16s * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Three channel 16-bit signed to 8-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.15 NppStatus nppiConvert_16s8u_C4R (const Npp16s * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Four channel 16-bit signed to 8-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.16 NppStatus nppiConvert_16u16s_C1RSfs (const Npp16u * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode, int nScaleFactor)

Single channel 16-bit unsigned to 16-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eRoundMode Rounding Mode Parameter.
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.17 NppStatus nppiConvert_16u32f_AC4R (const Npp16u * *pSrc*, int *nSrcStep*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

Four channel 16-bit unsigned to 32-bit floating-point conversion, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.18 NppStatus nppiConvert_16u32f_C1R (const Npp16u * *pSrc*, int *nSrcStep*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

Single channel 16-bit unsigned to 32-bit floating-point conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.19 NppStatus nppiConvert_16u32f_C3R (const Npp16u * *pSrc*, int *nSrcStep*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

Three channel 16-bit unsigned to 32-bit floating-point conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.20 NppStatus nppiConvert_16u32f_C4R (const Npp16u * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four channel 16-bit unsigned to 32-bit floating-point conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.21 NppStatus nppiConvert_16u32s_AC4R (const Npp16u * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Four channel 16-bit unsigned to 32-bit signed conversion, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.22 NppStatus nppiConvert_16u32s_C1R (const Npp16u * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Single channel 16-bit unsigned to 32-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.23 NppStatus nppiConvert_16u32s_C3R (const Npp16u * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Three channel 16-bit unsigned to 32-bit signed conversion.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.24 NppStatus nppiConvert_16u32s_C4R (const Npp16u * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Four channel 16-bit unsigned to 32-bit signed conversion.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.25 NppStatus nppiConvert_16u32u_C1R (const Npp16u * pSrc, int nSrcStep, Npp32u * pDst, int nDstStep, NppiSize oSizeROI)

Single channel 16-bit unsigned to 32-bit unsigned conversion.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.26 `NppStatus nppiConvert_16u8s_C1RSfs (const Npp16u * pSrc, int nSrcStep, Npp8s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode, int nScaleFactor)`

Single channel 16-bit unsigned to 8-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eRoundMode Rounding Mode Parameter.
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.27 `NppStatus nppiConvert_16u8u_AC4R (const Npp16u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four channel 16-bit unsigned to 8-bit unsigned conversion, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.28 `NppStatus nppiConvert_16u8u_C1R (const Npp16u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Single channel 16-bit unsigned to 8-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.29 NppStatus nppiConvert_16u8u_C3R (const Npp16u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Three channel 16-bit unsigned to 8-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.30 NppStatus nppiConvert_16u8u_C4R (const Npp16u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Four channel 16-bit unsigned to 8-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.31 NppStatus nppiConvert_32f16s_AC4R (const Npp32f * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode)

Four channel 32-bit floating point to 16-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eRoundMode Flag specifying how fractional float values are rounded to integer values.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.32 `NppStatus nppiConvert_32f16s_C1R (const Npp32f * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode)`

Single channel 32-bit floating point to 16-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Flag specifying how fractional float values are rounded to integer values.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.33 `NppStatus nppiConvert_32f16s_C1RSfs (const Npp32f * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode, int nScaleFactor)`

Single channel 32-bit floating point to 16-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Flag specifying how fractional float values are rounded to integer values.

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.34 `NppStatus nppiConvert_32f16s_C3R (const Npp32f * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode)`

Three channel 32-bit floating point to 16-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Flag specifying how fractional float values are rounded to integer values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.35 `NppStatus nppiConvert_32f16s_C4R (const Npp32f * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode)`

Four channel 32-bit floating point to 16-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Flag specifying how fractional float values are rounded to integer values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.36 `NppStatus nppiConvert_32f16u_AC4R (const Npp32f * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode)`

Four channel 32-bit floating point to 16-bit unsigned conversion, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Flag specifying how fractional float values are rounded to integer values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.37 `NppStatus nppiConvert_32f16u_C1R (const Npp32f * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode)`

Single channel 32-bit floating point to 16-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Flag specifying how fractional float values are rounded to integer values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.38 `NppStatus nppiConvert_32f16u_C1RSfs (const Npp32f * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode, int nScaleFactor)`

Single channel 32-bit floating point to 16-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Flag specifying how fractional float values are rounded to integer values.

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.39 `NppStatus nppiConvert_32f16u_C3R (const Npp32f * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode)`

Three channel 32-bit floating point to 16-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Flag specifying how fractional float values are rounded to integer values.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.40 `NppStatus nppiConvert_32f16u_C4R (const Npp32f * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode)`

Four channel 32-bit floating point to 16-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Flag specifying how fractional float values are rounded to integer values.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.41 `NppStatus nppiConvert_32f32s_C1RSfs (const Npp32f * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode, int nScaleFactor)`

Single channel 32-bit floating point to 32-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Flag specifying how fractional float values are rounded to integer values.

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.42 `NppStatus nppiConvert_32f32u_C1RSfs (const Npp32f * pSrc, int nSrcStep, Npp32u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode, int nScaleFactor)`

Single channel 32-bit floating point to 32-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Flag specifying how fractional float values are rounded to integer values.

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.43 `NppStatus nppiConvert_32f8s_AC4R (const Npp32f * pSrc, int nSrcStep, Npp8s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode)`

Four channel 32-bit floating point to 8-bit signed conversion, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Flag specifying how fractional float values are rounded to integer values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.44 `NppStatus nppiConvert_32f8s_C1R (const Npp32f * pSrc, int nSrcStep, Npp8s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode)`

Single channel 32-bit floating point to 8-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Flag specifying how fractional float values are rounded to integer values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.45 NppStatus nppiConvert_32f8s_C1RSfs (const Npp32f * pSrc, int nSrcStep, Npp8s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode, int nScaleFactor)

Single channel 32-bit floating point to 8-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Flag specifying how fractional float values are rounded to integer values.

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.46 NppStatus nppiConvert_32f8s_C3R (const Npp32f * pSrc, int nSrcStep, Npp8s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode)

Three channel 32-bit floating point to 8-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Flag specifying how fractional float values are rounded to integer values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.47 NppStatus nppiConvert_32f8s_C4R (const Npp32f * pSrc, int nSrcStep, Npp8s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode)

Four channel 32-bit floating point to 8-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Flag specifying how fractional float values are rounded to integer values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.48 NppStatus nppiConvert_32f8u_AC4R (const Npp32f * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode)

Four channel 32-bit floating point to 8-bit unsigned conversion, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Flag specifying how fractional float values are rounded to integer values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.49 NppStatus nppiConvert_32f8u_C1R (const Npp32f * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode)

Single channel 32-bit floating point to 8-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Flag specifying how fractional float values are rounded to integer values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.50 `NppStatus nppiConvert_32f8u_C1RSfs (const Npp32f * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode, int nScaleFactor)`

Single channel 32-bit floating point to 8-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Flag specifying how fractional float values are rounded to integer values.

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.51 `NppStatus nppiConvert_32f8u_C3R (const Npp32f * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode)`

Three channel 32-bit floating point to 8-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Flag specifying how fractional float values are rounded to integer values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.52 `NppStatus nppiConvert_32f8u_C4R (const Npp32f * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode)`

Four channel 32-bit floating point to 8-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Flag specifying how fractional float values are rounded to integer values.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.53 `NppStatus nppiConvert_32s16s_C1RSfs (const Npp32s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode, int nScaleFactor)`

Single channel 32-bit unsigned to 16-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Rounding Mode Parameter.

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.54 `NppStatus nppiConvert_32s16u_C1RSfs (const Npp32s * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode, int nScaleFactor)`

Single channel 32-bit unsigned to 16-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Rounding Mode Parameter.

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.55 `NppStatus nppiConvert_32s32f_C1R (const Npp32s * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Single channel 32-bit signed to 32-bit floating-point conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.56 `NppStatus nppiConvert_32s32u_C1Rs (const Npp32s * pSrc, int nSrcStep, Npp32u * pDst, int nDstStep, NppiSize oSizeROI)`

Single channel 32-bit signed to 32-bit unsigned conversion with saturation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.57 `NppStatus nppiConvert_32s8s_AC4R (const Npp32s * pSrc, int nSrcStep, Npp8s * pDst, int nDstStep, NppiSize oSizeROI)`

Four channel 32-bit signed to 8-bit signed conversion, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.58 NppStatus nppiConvert_32s8s_C1R (const Npp32s * pSrc, int nSrcStep, Npp8s * pDst, int nDstStep, NppiSize oSizeROI)

Single channel 32-bit signed to 8-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.59 NppStatus nppiConvert_32s8s_C3R (const Npp32s * pSrc, int nSrcStep, Npp8s * pDst, int nDstStep, NppiSize oSizeROI)

Three channel 32-bit signed to 8-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.60 NppStatus nppiConvert_32s8s_C4R (const Npp32s * pSrc, int nSrcStep, Npp8s * pDst, int nDstStep, NppiSize oSizeROI)

Four channel 32-bit signed to 8-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.61 `NppStatus nppiConvert_32s8u_AC4R (const Npp32s * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four channel 32-bit signed to 8-bit unsigned conversion, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.62 `NppStatus nppiConvert_32s8u_C1R (const Npp32s * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Single channel 32-bit signed to 8-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.63 `NppStatus nppiConvert_32s8u_C3R (const Npp32s * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Three channel 32-bit signed to 8-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.64 `NppStatus nppiConvert_32s8u_C4R (const Npp32s * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four channel 32-bit signed to 8-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.65 `NppStatus nppiConvert_32u16s_C1RSfs (const Npp32u * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode, int nScaleFactor)`

Single channel 32-bit unsigned to 16-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eRoundMode Rounding Mode Parameter.
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.66 `NppStatus nppiConvert_32u16u_C1RSfs (const Npp32u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode, int nScaleFactor)`

Single channel 32-bit unsigned to 16-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).
eRoundMode Rounding Mode Parameter.
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.67 NppStatus nppiConvert_32u32f_C1R (const Npp32u * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Single channel 32-bit unsigned to 32-bit floating-point conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.68 NppStatus nppiConvert_32u32s_C1RSfs (const Npp32u * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode, int nScaleFactor)

Single channel 32-bit unsigned to 32-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eRoundMode Rounding Mode Parameter.
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.69 `NppStatus nppiConvert_32u8s_C1RSfs (const Npp32u * pSrc, int nSrcStep, Npp8s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode, int nScaleFactor)`

Single channel 32-bit unsigned to 8-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eRoundMode Rounding Mode Parameter.
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.70 `NppStatus nppiConvert_32u8u_C1RSfs (const Npp32u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode, int nScaleFactor)`

Single channel 32-bit unsigned to 8-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eRoundMode Rounding Mode Parameter.
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.71 `NppStatus nppiConvert_8s16s_C1R (const Npp8s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)`

Single channel 8-bit signed to 16-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.72 NppStatus nppiConvert_8s16u_C1Rs (const Npp8s * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Single channel 8-bit signed to 16-bit unsigned conversion with saturation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.73 NppStatus nppiConvert_8s32f_AC4R (const Npp8s * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four channel 8-bit signed to 32-bit floating-point conversion, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.74 NppStatus nppiConvert_8s32f_C1R (const Npp8s * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Single channel 8-bit signed to 32-bit floating-point conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.75 `NppStatus nppiConvert_8s32f_C3R (const Npp8s * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Three channel 8-bit signed to 32-bit floating-point conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.76 `NppStatus nppiConvert_8s32f_C4R (const Npp8s * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Four channel 8-bit signed to 32-bit floating-point conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.77 NppStatus nppiConvert_8s32s_AC4R (const Npp8s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Four channel 8-bit signed to 32-bit signed conversion, not affecting Alpha.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.78 NppStatus nppiConvert_8s32s_C1R (const Npp8s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Single channel 8-bit signed to 32-bit signed conversion.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.79 NppStatus nppiConvert_8s32s_C3R (const Npp8s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Three channel 8-bit signed to 32-bit signed conversion.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.80 `NppStatus nppiConvert_8s32s_C4R (const Npp8s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Four channel 8-bit signed to 32-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.81 `NppStatus nppiConvert_8s32u_C1Rs (const Npp8s * pSrc, int nSrcStep, Npp32u * pDst, int nDstStep, NppiSize oSizeROI)`

Single channel 8-bit signed to 32-bit unsigned conversion with saturation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.82 `NppStatus nppiConvert_8s8u_C1Rs (const Npp8s * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Single channel 8-bit signed to 8-bit unsigned conversion with saturation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.83 NppStatus nppiConvert_8u16s_AC4R (const Npp8u * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

Four channel 8-bit unsigned to 16-bit signed conversion, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.84 NppStatus nppiConvert_8u16s_C1R (const Npp8u * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

Single channel 8-bit unsigned to 16-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.85 NppStatus nppiConvert_8u16s_C3R (const Npp8u * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

Three channel 8-bit unsigned to 16-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.86 NppStatus nppiConvert_8u16s_C4R (const Npp8u * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

Four channel 8-bit unsigned to 16-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.87 NppStatus nppiConvert_8u16u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four channel 8-bit unsigned to 16-bit unsigned conversion, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.88 NppStatus nppiConvert_8u16u_C1R (const Npp8u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Single channel 8-bit unsigned to 16-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.89 NppStatus nppiConvert_8u16u_C3R (const Npp8u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Three channel 8-bit unsigned to 16-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.90 NppStatus nppiConvert_8u16u_C4R (const Npp8u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four channel 8-bit unsigned to 16-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.91 NppStatus nppiConvert_8u32f_AC4R (const Npp8u * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four channel 8-bit unsigned to 32-bit floating-point conversion, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.92 `NppStatus nppiConvert_8u32f_C1R (const Npp8u * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Single channel 8-bit unsigned to 32-bit floating-point conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.93 `NppStatus nppiConvert_8u32f_C3R (const Npp8u * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Three channel 8-bit unsigned to 32-bit floating-point conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.94 `NppStatus nppiConvert_8u32f_C4R (const Npp8u * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Four channel 8-bit unsigned to 32-bit floating-point conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.56.1.95 `NppStatus nppiConvert_8u32s_AC4R (const Npp8u * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Four channel 8-bit unsigned to 32-bit signed conversion, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.96 `NppStatus nppiConvert_8u32s_C1R (const Npp8u * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Single channel 8-bit unsigned to 32-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.97 `NppStatus nppiConvert_8u32s_C3R (const Npp8u * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Three channel 8-bit unsigned to 32-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.98 `NppStatus nppiConvert_8u32s_C4R (const Npp8u * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Four channel 8-bit unsigned to 32-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.56.1.99 `NppStatus nppiConvert_8u8s_C1RSfs (const Npp8u * pSrc, int nSrcStep, Npp8s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode, int nScaleFactor)`

Single channel 8-bit unsigned to 8-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eRoundMode Rounding Mode Parameter.
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.57 Scale

Scaled Bit-Depth Conversion

Scale bit-depth up and down.

To map source pixel `srcPixelValue` to destination pixel `dstPixelValue` the following equation is used:

$$\text{dstPixelValue} = \text{dstMinRangeValue} + \text{scaleFactor} * (\text{srcPixelValue} - \text{srcMinRangeValue})$$

where $\text{scaleFactor} = (\text{dstMaxRangeValue} - \text{dstMinRangeValue}) / (\text{srcMaxRangeValue} - \text{srcMinRangeValue})$.

For conversions between integer data types, the entire integer numeric range of the input data type is mapped onto the entire integer numeric range of the output data type.

For conversions to floating point data types the floating point data range is defined by the user supplied floating point values of `nMax` and `nMin` which are used as the `dstMaxRangeValue` and `dstMinRangeValue` respectively in the `scaleFactor` and `dstPixelValue` calculations and also as the saturation values to which output data is clamped.

When converting from floating-point values to integer values, `nMax` and `nMin` are used as the `srcMaxRangeValue` and `srcMinRangeValue` respectively in the `scaleFactor` and `dstPixelValue` calculations. Output values are saturated and clamped to the full output integer pixel value range.

- `NppStatus nppiScale_8u16u_C1R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Single channel 8-bit unsigned to 16-bit unsigned conversion.
- `NppStatus nppiScale_8u16u_C3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Three channel 8-bit unsigned to 16-bit unsigned conversion.
- `NppStatus nppiScale_8u16u_C4R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four channel 8-bit unsigned to 16-bit unsigned conversion.
- `NppStatus nppiScale_8u16u_AC4R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four channel 8-bit unsigned to 16-bit unsigned conversion, not affecting Alpha.
- `NppStatus nppiScale_8u16s_C1R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Single channel 8-bit unsigned to 16-bit signed conversion.
- `NppStatus nppiScale_8u16s_C3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Three channel 8-bit unsigned to 16-bit signed conversion.
- `NppStatus nppiScale_8u16s_C4R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four channel 8-bit unsigned to 16-bit signed conversion.
- `NppStatus nppiScale_8u16s_AC4R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Four channel 8-bit unsigned to 16-bit signed conversion, not affecting Alpha.

- `NppStatus nppiScale_8u32s_C1R` (const `Npp8u` *pSrc, int nSrcStep, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)

Single channel 8-bit unsigned to 32-bit signed conversion.

- `NppStatus nppiScale_8u32s_C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)

Three channel 8-bit unsigned to 32-bit signed conversion.

- `NppStatus nppiScale_8u32s_C4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)

Four channel 8-bit unsigned to 32-bit signed conversion.

- `NppStatus nppiScale_8u32s_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)

Four channel 8-bit unsigned to 32-bit signed conversion, not affecting Alpha.

- `NppStatus nppiScale_8u32f_C1R` (const `Npp8u` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI, `Npp32f` nMin, `Npp32f` nMax)

Single channel 8-bit unsigned to 32-bit floating-point conversion.

- `NppStatus nppiScale_8u32f_C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI, `Npp32f` nMin, `Npp32f` nMax)

Three channel 8-bit unsigned to 32-bit floating-point conversion.

- `NppStatus nppiScale_8u32f_C4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI, `Npp32f` nMin, `Npp32f` nMax)

Four channel 8-bit unsigned to 32-bit floating-point conversion.

- `NppStatus nppiScale_8u32f_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI, `Npp32f` nMin, `Npp32f` nMax)

Four channel 8-bit unsigned to 32-bit floating-point conversion, not affecting Alpha.

- `NppStatus nppiScale_16u8u_C1R` (const `Npp16u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppHintAlgorithm` hint)

Single channel 16-bit unsigned to 8-bit unsigned conversion.

- `NppStatus nppiScale_16u8u_C3R` (const `Npp16u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppHintAlgorithm` hint)

Three channel 16-bit unsigned to 8-bit unsigned conversion.

- `NppStatus nppiScale_16u8u_C4R` (const `Npp16u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppHintAlgorithm` hint)

Four channel 16-bit unsigned to 8-bit unsigned conversion.

- `NppStatus nppiScale_16u8u_AC4R` (const `Npp16u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppHintAlgorithm` hint)

Four channel 16-bit unsigned to 8-bit unsigned conversion, not affecting Alpha.

- `NppStatus nppiScale_16s8u_C1R` (const `Npp16s` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppHintAlgorithm` hint)
Single channel 16-bit signed to 8-bit unsigned conversion.
- `NppStatus nppiScale_16s8u_C3R` (const `Npp16s` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppHintAlgorithm` hint)
Three channel 16-bit signed to 8-bit unsigned conversion.
- `NppStatus nppiScale_16s8u_C4R` (const `Npp16s` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppHintAlgorithm` hint)
Four channel 16-bit signed to 8-bit unsigned conversion.
- `NppStatus nppiScale_16s8u_AC4R` (const `Npp16s` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppHintAlgorithm` hint)
Four channel 16-bit signed to 8-bit unsigned conversion, not affecting Alpha.
- `NppStatus nppiScale_32s8u_C1R` (const `Npp32s` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppHintAlgorithm` hint)
Single channel 32-bit signed to 8-bit unsigned conversion.
- `NppStatus nppiScale_32s8u_C3R` (const `Npp32s` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppHintAlgorithm` hint)
Three channel 32-bit signed to 8-bit unsigned conversion.
- `NppStatus nppiScale_32s8u_C4R` (const `Npp32s` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppHintAlgorithm` hint)
Four channel 32-bit signed to 8-bit unsigned conversion.
- `NppStatus nppiScale_32s8u_AC4R` (const `Npp32s` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppHintAlgorithm` hint)
Four channel 32-bit signed to 8-bit unsigned conversion, not affecting Alpha.
- `NppStatus nppiScale_32f8u_C1R` (const `Npp32f` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `Npp32f` nMin, `Npp32f` nMax)
Single channel 32-bit floating point to 8-bit unsigned conversion.
- `NppStatus nppiScale_32f8u_C3R` (const `Npp32f` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `Npp32f` nMin, `Npp32f` nMax)
Three channel 32-bit floating point to 8-bit unsigned conversion.
- `NppStatus nppiScale_32f8u_C4R` (const `Npp32f` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `Npp32f` nMin, `Npp32f` nMax)
Four channel 32-bit floating point to 8-bit unsigned conversion.
- `NppStatus nppiScale_32f8u_AC4R` (const `Npp32f` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `Npp32f` nMin, `Npp32f` nMax)
Four channel 32-bit floating point to 8-bit unsigned conversion, not affecting Alpha.

7.57.1 Function Documentation

7.57.1.1 `NppStatus nppiScale_16s8u_AC4R (const Npp16s * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppHintAlgorithm hint)`

Four channel 16-bit signed to 8-bit unsigned conversion, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

hint algorithm performance or accuracy selector, currently ignored

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.57.1.2 `NppStatus nppiScale_16s8u_C1R (const Npp16s * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppHintAlgorithm hint)`

Single channel 16-bit signed to 8-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

hint algorithm performance or accuracy selector, currently ignored

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.57.1.3 `NppStatus nppiScale_16s8u_C3R (const Npp16s * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppHintAlgorithm hint)`

Three channel 16-bit signed to 8-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

hint algorithm performance or accuracy selector, currently ignored

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.57.1.4 NppStatus nppiScale_16s8u_C4R (const Npp16s * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppHintAlgorithm hint)

Four channel 16-bit signed to 8-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

hint algorithm performance or accuracy selector, currently ignored

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.57.1.5 NppStatus nppiScale_16u8u_AC4R (const Npp16u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppHintAlgorithm hint)

Four channel 16-bit unsigned to 8-bit unsigned conversion, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

hint algorithm performance or accuracy selector, currently ignored

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.57.1.6 NppStatus nppiScale_16u8u_C1R (const Npp16u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppHintAlgorithm hint)

Single channel 16-bit unsigned to 8-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

hint algorithm performance or accuracy selector, currently ignored

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.57.1.7 NppStatus nppiScale_16u8u_C3R (const Npp16u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppHintAlgorithm hint)

Three channel 16-bit unsigned to 8-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

hint algorithm performance or accuracy selector, currently ignored

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.57.1.8 NppStatus nppiScale_16u8u_C4R (const Npp16u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppHintAlgorithm hint)

Four channel 16-bit unsigned to 8-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

hint algorithm performance or accuracy selector, currently ignored

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.57.1.9 NppStatus nppiScale_32f8u_AC4R (const Npp32f * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, Npp32f nMin, Npp32f nMax)

Four channel 32-bit floating point to 8-bit unsigned conversion, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nMin specifies the minimum saturation value to which every output value will be clamped.

nMax specifies the maximum saturation value to which every output value will be clamped.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, `NPP_SCALE_RANGE_ERROR` indicates an error condition if $nMax \leq nMin$.

7.57.1.10 NppStatus nppiScale_32f8u_C1R (const Npp32f * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, Npp32f nMin, Npp32f nMax)

Single channel 32-bit floating point to 8-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nMin specifies the minimum saturation value to which every output value will be clamped.

nMax specifies the maximum saturation value to which every output value will be clamped.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, `NPP_SCALE_RANGE_ERROR` indicates an error condition if $nMax \leq nMin$.

7.57.1.11 NppStatus nppiScale_32f8u_C3R (const Npp32f * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, Npp32f nMin, Npp32f nMax)

Three channel 32-bit floating point to 8-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nMin specifies the minimum saturation value to which every output value will be clamped.

nMax specifies the maximum saturation value to which every output value will be clamped.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, `NPP_SCALE_RANGE_ERROR` indicates an error condition if $nMax \leq nMin$.

7.57.1.12 `NppStatus nppiScale_32f8u_C4R (const Npp32f * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, Npp32f nMin, Npp32f nMax)`

Four channel 32-bit floating point to 8-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nMin specifies the minimum saturation value to which every output value will be clamped.

nMax specifies the maximum saturation value to which every output value will be clamped.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, `NPP_SCALE_RANGE_ERROR` indicates an error condition if $nMax \leq nMin$.

7.57.1.13 `NppStatus nppiScale_32s8u_AC4R (const Npp32s * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppHintAlgorithm hint)`

Four channel 32-bit signed to 8-bit unsigned conversion, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

hint algorithm performance or accuracy selector, currently ignored

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.57.1.14 `NppStatus nppiScale_32s8u_C1R (const Npp32s * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppHintAlgorithm hint)`

Single channel 32-bit signed to 8-bit unsigned conversion.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- hint* algorithm performance or accuracy selector, currently ignored

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.57.1.15 `NppStatus nppiScale_32s8u_C3R (const Npp32s * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppHintAlgorithm hint)`

Three channel 32-bit signed to 8-bit unsigned conversion.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- hint* algorithm performance or accuracy selector, currently ignored

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.57.1.16 `NppStatus nppiScale_32s8u_C4R (const Npp32s * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppHintAlgorithm hint)`

Four channel 32-bit signed to 8-bit unsigned conversion.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- hint* algorithm performance or accuracy selector, currently ignored

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.57.1.17 NppStatus nppiScale_8u16s_AC4R (const Npp8u * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

Four channel 8-bit unsigned to 16-bit signed conversion, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.57.1.18 NppStatus nppiScale_8u16s_C1R (const Npp8u * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

Single channel 8-bit unsigned to 16-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.57.1.19 NppStatus nppiScale_8u16s_C3R (const Npp8u * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

Three channel 8-bit unsigned to 16-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.57.1.20 NppStatus nppiScale_8u16s_C4R (const Npp8u * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

Four channel 8-bit unsigned to 16-bit signed conversion.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.57.1.21 NppStatus nppiScale_8u16u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four channel 8-bit unsigned to 16-bit unsigned conversion, not affecting Alpha.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.57.1.22 NppStatus nppiScale_8u16u_C1R (const Npp8u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Single channel 8-bit unsigned to 16-bit unsigned conversion.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.57.1.23 NppStatus nppiScale_8u16u_C3R (const Npp8u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Three channel 8-bit unsigned to 16-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.57.1.24 NppStatus nppiScale_8u16u_C4R (const Npp8u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four channel 8-bit unsigned to 16-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.57.1.25 NppStatus nppiScale_8u32f_AC4R (const Npp8u * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, Npp32f nMin, Npp32f nMax)

Four channel 8-bit unsigned to 32-bit floating-point conversion, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nMin specifies the minimum saturation value to which every output value will be clamped.
nMax specifies the maximum saturation value to which every output value will be clamped.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, `NPP_SCALE_RANGE_ERROR` indicates an error condition if $nMax \leq nMin$.

7.57.1.26 `NppStatus nppiScale_8u32f_C1R (const Npp8u * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, Npp32f nMin, Npp32f nMax)`

Single channel 8-bit unsigned to 32-bit floating-point conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nMin specifies the minimum saturation value to which every output value will be clamped.

nMax specifies the maximum saturation value to which every output value will be clamped.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, `NPP_SCALE_RANGE_ERROR` indicates an error condition if $nMax \leq nMin$.

7.57.1.27 `NppStatus nppiScale_8u32f_C3R (const Npp8u * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, Npp32f nMin, Npp32f nMax)`

Three channel 8-bit unsigned to 32-bit floating-point conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nMin specifies the minimum saturation value to which every output value will be clamped.

nMax specifies the maximum saturation value to which every output value will be clamped.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, `NPP_SCALE_RANGE_ERROR` indicates an error condition if $nMax \leq nMin$.

7.57.1.28 `NppStatus nppiScale_8u32f_C4R (const Npp8u * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, Npp32f nMin, Npp32f nMax)`

Four channel 8-bit unsigned to 32-bit floating-point conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nMin specifies the minimum saturation value to which every output value will be clamped.

nMax specifies the maximum saturation value to which every output value will be clamped.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, `NPP_SCALE_RANGE_ERROR` indicates an error condition if $nMax \leq nMin$.

7.57.1.29 `NppStatus nppiScale_8u32s_AC4R (const Npp8u * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Four channel 8-bit unsigned to 32-bit signed conversion, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.57.1.30 `NppStatus nppiScale_8u32s_C1R (const Npp8u * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Single channel 8-bit unsigned to 32-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.57.1.31 `NppStatus nppiScale_8u32s_C3R (const Npp8u * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Three channel 8-bit unsigned to 32-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.57.1.32 `NppStatus nppiScale_8u32s_C4R (const Npp8u * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Four channel 8-bit unsigned to 32-bit signed conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.58 Copy Constant Border

CopyConstBorder

Methods for copying images and padding borders with a constant, user-specifiable color.

- `NppStatus nppiCopyConstBorder_8u_C1R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcSizeROI`, `Npp8u *pDst`, int `nDstStep`, `NppiSize` `oDstSizeROI`, int `nTopBorderHeight`, int `nLeftBorderWidth`, `Npp8u` `nValue`)
1 channel 8-bit unsigned integer image copy with constant border color.
- `NppStatus nppiCopyConstBorder_8u_C3R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcSizeROI`, `Npp8u *pDst`, int `nDstStep`, `NppiSize` `oDstSizeROI`, int `nTopBorderHeight`, int `nLeftBorderWidth`, const `Npp8u` `aValue[3]`)
3 channel 8-bit unsigned integer image copy with constant border color.
- `NppStatus nppiCopyConstBorder_8u_C4R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcSizeROI`, `Npp8u *pDst`, int `nDstStep`, `NppiSize` `oDstSizeROI`, int `nTopBorderHeight`, int `nLeftBorderWidth`, const `Npp8u` `aValue[4]`)
4 channel 8-bit unsigned integer image copy with constant border color.
- `NppStatus nppiCopyConstBorder_8u_AC4R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcSizeROI`, `Npp8u *pDst`, int `nDstStep`, `NppiSize` `oDstSizeROI`, int `nTopBorderHeight`, int `nLeftBorderWidth`, const `Npp8u` `aValue[3]`)
4 channel 8-bit unsigned integer image copy with constant border color with alpha channel unaffected.
- `NppStatus nppiCopyConstBorder_16u_C1R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcSizeROI`, `Npp16u *pDst`, int `nDstStep`, `NppiSize` `oDstSizeROI`, int `nTopBorderHeight`, int `nLeftBorderWidth`, `Npp16u` `nValue`)
1 channel 16-bit unsigned integer image copy with constant border color.
- `NppStatus nppiCopyConstBorder_16u_C3R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcSizeROI`, `Npp16u *pDst`, int `nDstStep`, `NppiSize` `oDstSizeROI`, int `nTopBorderHeight`, int `nLeftBorderWidth`, const `Npp16u` `aValue[3]`)
3 channel 16-bit unsigned integer image copy with constant border color.
- `NppStatus nppiCopyConstBorder_16u_C4R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcSizeROI`, `Npp16u *pDst`, int `nDstStep`, `NppiSize` `oDstSizeROI`, int `nTopBorderHeight`, int `nLeftBorderWidth`, const `Npp16u` `aValue[4]`)
4 channel 16-bit unsigned integer image copy with constant border color.
- `NppStatus nppiCopyConstBorder_16u_AC4R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcSizeROI`, `Npp16u *pDst`, int `nDstStep`, `NppiSize` `oDstSizeROI`, int `nTopBorderHeight`, int `nLeftBorderWidth`, const `Npp16u` `aValue[3]`)
4 channel 16-bit unsigned integer image copy with constant border color with alpha channel unaffected.
- `NppStatus nppiCopyConstBorder_16s_C1R` (const `Npp16s *pSrc`, int `nSrcStep`, `NppiSize` `oSrcSizeROI`, `Npp16s *pDst`, int `nDstStep`, `NppiSize` `oDstSizeROI`, int `nTopBorderHeight`, int `nLeftBorderWidth`, `Npp16s` `nValue`)
1 channel 16-bit signed integer image copy with constant border color.

- **NppStatus nppiCopyConstBorder_16s_C3R** (const **Npp16s** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp16s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const **Npp16s** aValue[3])

3 channel 16-bit signed integer image copy with constant border color.
- **NppStatus nppiCopyConstBorder_16s_C4R** (const **Npp16s** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp16s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const **Npp16s** aValue[4])

4 channel 16-bit signed integer image copy with constant border color.
- **NppStatus nppiCopyConstBorder_16s_AC4R** (const **Npp16s** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp16s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const **Npp16s** aValue[3])

4 channel 16-bit signed integer image copy with constant border color with alpha channel unaffected.
- **NppStatus nppiCopyConstBorder_32s_C1R** (const **Npp32s** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp32s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, **Npp32s** nValue)

1 channel 32-bit signed integer image copy with constant border color.
- **NppStatus nppiCopyConstBorder_32s_C3R** (const **Npp32s** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp32s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const **Npp32s** aValue[3])

3 channel 32-bit signed integer image copy with constant border color.
- **NppStatus nppiCopyConstBorder_32s_C4R** (const **Npp32s** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp32s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const **Npp32s** aValue[4])

4 channel 32-bit signed integer image copy with constant border color.
- **NppStatus nppiCopyConstBorder_32s_AC4R** (const **Npp32s** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp32s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const **Npp32s** aValue[3])

4 channel 32-bit signed integer image copy with constant border color with alpha channel unaffected.
- **NppStatus nppiCopyConstBorder_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp32f** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, **Npp32f** nValue)

1 channel 32-bit floating point image copy with constant border color.
- **NppStatus nppiCopyConstBorder_32f_C3R** (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp32f** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const **Npp32f** aValue[3])

3 channel 32-bit floating point image copy with constant border color.
- **NppStatus nppiCopyConstBorder_32f_C4R** (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp32f** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const **Npp32f** aValue[4])

4 channel 32-bit floating point image copy with constant border color.

- `NppStatus nppiCopyConstBorder_32f_AC4R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize` `oSrcSizeROI`, `Npp32f *pDst`, int `nDstStep`, `NppiSize` `oDstSizeROI`, int `nTopBorderHeight`, int `nLeftBorderWidth`, const `Npp32f aValue[3]`)

4 channel 32-bit floating point image copy with constant border color with alpha channel unaffected.

7.58.1 Function Documentation

- 7.58.1.1** `NppStatus nppiCopyConstBorder_16s_AC4R` (const `Npp16s *pSrc`, int `nSrcStep`, `NppiSize` `oSrcSizeROI`, `Npp16s *pDst`, int `nDstStep`, `NppiSize` `oDstSizeROI`, int `nTopBorderHeight`, int `nLeftBorderWidth`, const `Npp16s aValue[3]`)

4 channel 16-bit signed integer image copy with constant border color with alpha channel unaffected.

See `nppiCopyConstBorder_16s_C1R()` for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region-of-interest.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

aValue Vector of the RGB values of the border pixels. Because this method does not affect the destination image's alpha channel, only three components of the border color are needed.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- 7.58.1.2** `NppStatus nppiCopyConstBorder_16s_C1R` (const `Npp16s *pSrc`, int `nSrcStep`, `NppiSize` `oSrcSizeROI`, `Npp16s *pDst`, int `nDstStep`, `NppiSize` `oDstSizeROI`, int `nTopBorderHeight`, int `nLeftBorderWidth`, `Npp16s nValue`)

1 channel 16-bit signed integer image copy with constant border color.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region of pixels.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image (inner part) and constant border color (outer part).

nTopBorderHeight Height (in pixels) of the top border. The number of pixel rows at the top of the destination ROI that will be filled with the constant border color. $nBottomBorderHeight = oDstSizeROI.height - nTopBorderHeight - oSrcSizeROI.height$.

nLeftBorderWidth Width (in pixels) of the left border. The width of the border at the right side of the destination ROI is implicitly defined by the size of the source ROI: $nRightBorderWidth = oDstSizeROI.width - nLeftBorderWidth - oSrcSizeROI.width$.

nValue The pixel value to be set for border pixels.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.58.1.3 `NppStatus nppiCopyConstBorder_16s_C3R (const Npp16s * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp16s * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const Npp16s aValue[3])`

3 channel 16-bit signed integer image copy with constant border color.

See [nppiCopyConstBorder_16s_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region-of-interest.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

aValue Vector of the RGBA values of the border pixels to be set.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.58.1.4 `NppStatus nppiCopyConstBorder_16s_C4R (const Npp16s * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp16s * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const Npp16s aValue[4])`

4 channel 16-bit signed integer image copy with constant border color.

See [nppiCopyConstBorder_16s_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region-of-interest.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

aValue Vector of the RGBA values of the border pixels to be set.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.58.1.5 NppStatus nppiCopyConstBorder_16u_AC4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const Npp16u aValue[3])

4 channel 16-bit unsigned integer image copy with constant border color with alpha channel unaffected.

See [nppiCopyConstBorder_16u_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region-of-interest.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

aValue Vector of the RGB values of the border pixels. Because this method does not affect the destination image's alpha channel, only three components of the border color are needed.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.58.1.6 NppStatus nppiCopyConstBorder_16u_C1R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, Npp16u nValue)

1 channel 16-bit unsigned integer image copy with constant border color.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region of pixels.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image (inner part) and constant border color (outer part).

nTopBorderHeight Height (in pixels) of the top border. The number of pixel rows at the top of the destination ROI that will be filled with the constant border color. $nBottomBorderHeight = oDstSizeROI.height - nTopBorderHeight - oSrcSizeROI.height$.

nLeftBorderWidth Width (in pixels) of the left border. The width of the border at the right side of the destination ROI is implicitly defined by the size of the source ROI: $nRightBorderWidth = oDstSizeROI.width - nLeftBorderWidth - oSrcSizeROI.width$.

nValue The pixel value to be set for border pixels.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.58.1.7 NppStatus nppiCopyConstBorder_16u_C3R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const Npp16u aValue[3])

3 channel 16-bit unsigned integer image copy with constant border color.

See [nppiCopyConstBorder_16u_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSizeROI Size of the source region-of-interest.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

aValue Vector of the RGBA values of the border pixels to be set.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.58.1.8 NppStatus nppiCopyConstBorder_16u_C4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const Npp16u aValue[4])

4 channel 16-bit unsigned integer image copy with constant border color.

See [nppiCopyConstBorder_16u_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSizeROI Size of the source region-of-interest.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstSizeROI Size of the destination region-of-interest.
nTopBorderHeight Height of top border.
nLeftBorderWidth Width of left border.
aValue Vector of the RGBA values of the border pixels to be set.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.58.1.9 NppStatus nppiCopyConstBorder_32f_AC4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp32f * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const Npp32f aValue[3])

4 channel 32-bit floating point image copy with constant border color with alpha channel unaffected.

See [nppiCopyConstBorder_32f_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSizeROI Size of the source region-of-interest.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstSizeROI Size of the destination region-of-interest.
nTopBorderHeight Height of top border.
nLeftBorderWidth Width of left border.
aValue Vector of the RGB values of the border pixels. Because this method does not affect the destination image's alpha channel, only three components of the border color are needed.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.58.1.10 NppStatus nppiCopyConstBorder_32f_C1R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp32f * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, Npp32f nValue)

1 channel 32-bit floating point image copy with constant border color.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSizeROI Size of the source region of pixels.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image (inner part) and constant border color (outer part).

nTopBorderHeight Height (in pixels) of the top border. The number of pixel rows at the top of the destination ROI that will be filled with the constant border color. $nBottomBorderHeight = oDstSizeROI.height - nTopBorderHeight - oSrcSizeROI.height$.

nLeftBorderWidth Width (in pixels) of the left border. The width of the border at the right side of the destination ROI is implicitly defined by the size of the source ROI: $nRightBorderWidth = oDstSizeROI.width - nLeftBorderWidth - oSrcSizeROI.width$.

nValue The pixel value to be set for border pixels.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.58.1.11 `NppStatus nppiCopyConstBorder_32f_C3R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp32f * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const Npp32f aValue[3])`

3 channel 32-bit floating point image copy with constant border color.

See [nppiCopyConstBorder_32f_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region-of-interest.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

aValue Vector of the RGBA values of the border pixels to be set.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.58.1.12 `NppStatus nppiCopyConstBorder_32f_C4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp32f * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const Npp32f aValue[4])`

4 channel 32-bit floating point image copy with constant border color.

See [nppiCopyConstBorder_32f_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
oSrcSizeROI Size of the source region-of-interest.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstSizeROI Size of the destination region-of-interest.
nTopBorderHeight Height of top border.
nLeftBorderWidth Width of left border.
aValue Vector of the RGBA values of the border pixels to be set.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.58.1.13 `NppStatus nppiCopyConstBorder_32s_AC4R (const Npp32s * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp32s * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const Npp32s aValue[3])`

4 channel 32-bit signed integer image copy with constant border color with alpha channel unaffected.

See `nppiCopyConstBorder_32s_C1R()` for detailed documentation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSizeROI Size of the source region-of-interest.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstSizeROI Size of the destination region-of-interest.
nTopBorderHeight Height of top border.
nLeftBorderWidth Width of left border.
aValue Vector of the RGB values of the border pixels. Because this method does not affect the destination image's alpha channel, only three components of the border color are needed.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.58.1.14 `NppStatus nppiCopyConstBorder_32s_C1R (const Npp32s * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp32s * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, Npp32s nValue)`

1 channel 32-bit signed integer image copy with constant border color.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region of pixels.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image (inner part) and constant border color (outer part).

nTopBorderHeight Height (in pixels) of the top border. The number of pixel rows at the top of the destination ROI that will be filled with the constant border color. $nBottomBorderHeight = oDstSizeROI.height - nTopBorderHeight - oSrcSizeROI.height$.

nLeftBorderWidth Width (in pixels) of the left border. The width of the border at the right side of the destination ROI is implicitly defined by the size of the source ROI: $nRightBorderWidth = oDstSizeROI.width - nLeftBorderWidth - oSrcSizeROI.width$.

nValue The pixel value to be set for border pixels.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.58.1.15 `NppStatus nppiCopyConstBorder_32s_C3R (const Npp32s * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp32s * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const Npp32s aValue[3])`

3 channel 32-bit signed integer image copy with constant border color.

See [nppiCopyConstBorder_32s_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region-of-interest.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

aValue Vector of the RGBA values of the border pixels to be set.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.58.1.16 `NppStatus nppiCopyConstBorder_32s_C4R (const Npp32s * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp32s * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const Npp32s aValue[4])`

4 channel 32-bit signed integer image copy with constant border color.

See [nppiCopyConstBorder_32s_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSizeROI Size of the source region-of-interest.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstSizeROI Size of the destination region-of-interest.
nTopBorderHeight Height of top border.
nLeftBorderWidth Width of left border.
aValue Vector of the RGBA values of the border pixels to be set.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.58.1.17 `NppStatus nppiCopyConstBorder_8u_AC4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const Npp8u aValue[3])`

4 channel 8-bit unsigned integer image copy with constant border color with alpha channel unaffected.

See [nppiCopyConstBorder_8u_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSizeROI Size of the source region-of-interest.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstSizeROI Size of the destination region-of-interest.
nTopBorderHeight Height of top border.
nLeftBorderWidth Width of left border.
aValue Vector of the RGB values of the border pixels. Because this method does not affect the destination image's alpha channel, only three components of the border color are needed.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.58.1.18 `NppStatus nppiCopyConstBorder_8u_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, Npp8u nValue)`

1 channel 8-bit unsigned integer image copy with constant border color.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region of pixels.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image (inner part) and constant border color (outer part).

nTopBorderHeight Height (in pixels) of the top border. The number of pixel rows at the top of the destination ROI that will be filled with the constant border color. $nBottomBorderHeight = oDstSizeROI.height - nTopBorderHeight - oSrcSizeROI.height$.

nLeftBorderWidth Width (in pixels) of the left border. The width of the border at the right side of the destination ROI is implicitly defined by the size of the source ROI: $nRightBorderWidth = oDstSizeROI.width - nLeftBorderWidth - oSrcSizeROI.width$.

nValue The pixel value to be set for border pixels.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.58.1.19 `NppStatus nppiCopyConstBorder_8u_C3R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const Npp8u aValue[3])`

3 channel 8-bit unsigned integer image copy with constant border color.

See [nppiCopyConstBorder_8u_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region-of-interest.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

aValue Vector of the RGBA values of the border pixels to be set.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.58.1.20 `NppStatus nppiCopyConstBorder_8u_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const Npp8u aValue[4])`

4 channel 8-bit unsigned integer image copy with constant border color.

See [nppiCopyConstBorder_8u_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region-of-interest.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

aValue Vector of the RGBA values of the border pixels to be set.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.59 Copy Replicate Border

CopyReplicateBorder

Methods for copying images and padding borders with a replicates of the nearest source image pixel color.

- `NppStatus nppiCopyReplicateBorder_8u_C1R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcSizeROI, `Npp8u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

1 channel 8-bit unsigned integer image copy with nearest source image pixel color.
- `NppStatus nppiCopyReplicateBorder_8u_C3R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcSizeROI, `Npp8u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

3 channel 8-bit unsigned integer image copy with nearest source image pixel color.
- `NppStatus nppiCopyReplicateBorder_8u_C4R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcSizeROI, `Npp8u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 8-bit unsigned integer image copy with nearest source image pixel color.
- `NppStatus nppiCopyReplicateBorder_8u_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcSizeROI, `Npp8u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 8-bit unsigned integer image copy with nearest source image pixel color with alpha channel unaffected.
- `NppStatus nppiCopyReplicateBorder_16u_C1R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcSizeROI, `Npp16u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

1 channel 16-bit unsigned integer image copy with nearest source image pixel color.
- `NppStatus nppiCopyReplicateBorder_16u_C3R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcSizeROI, `Npp16u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

3 channel 16-bit unsigned integer image copy with nearest source image pixel color.
- `NppStatus nppiCopyReplicateBorder_16u_C4R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcSizeROI, `Npp16u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 16-bit unsigned integer image copy with nearest source image pixel color.
- `NppStatus nppiCopyReplicateBorder_16u_AC4R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcSizeROI, `Npp16u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 16-bit unsigned image copy with nearest source image pixel color with alpha channel unaffected.
- `NppStatus nppiCopyReplicateBorder_16s_C1R` (const `Npp16s` *pSrc, int nSrcStep, `NppiSize` oSrcSizeROI, `Npp16s` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

1 channel 16-bit signed integer image copy with nearest source image pixel color.

- **NppStatus nppiCopyReplicateBorder_16s_C3R** (const **Npp16s** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp16s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

3 channel 16-bit signed integer image copy with nearest source image pixel color.
- **NppStatus nppiCopyReplicateBorder_16s_C4R** (const **Npp16s** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp16s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 16-bit signed integer image copy with nearest source image pixel color.
- **NppStatus nppiCopyReplicateBorder_16s_AC4R** (const **Npp16s** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp16s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 16-bit signed integer image copy with nearest source image pixel color with alpha channel unaffected.
- **NppStatus nppiCopyReplicateBorder_32s_C1R** (const **Npp32s** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp32s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

1 channel 32-bit signed integer image copy with nearest source image pixel color.
- **NppStatus nppiCopyReplicateBorder_32s_C3R** (const **Npp32s** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp32s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

3 channel 32-bit signed image copy with nearest source image pixel color.
- **NppStatus nppiCopyReplicateBorder_32s_C4R** (const **Npp32s** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp32s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 32-bit signed integer image copy with nearest source image pixel color.
- **NppStatus nppiCopyReplicateBorder_32s_AC4R** (const **Npp32s** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp32s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 32-bit signed integer image copy with nearest source image pixel color with alpha channel unaffected.
- **NppStatus nppiCopyReplicateBorder_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp32f** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

1 channel 32-bit floating point image copy with nearest source image pixel color.
- **NppStatus nppiCopyReplicateBorder_32f_C3R** (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp32f** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

3 channel 32-bit floating point image copy with nearest source image pixel color.
- **NppStatus nppiCopyReplicateBorder_32f_C4R** (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp32f** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 32-bit floating point image copy with nearest source image pixel color.

- [NppStatus nppiCopyReplicateBorder_32f_AC4R](#) (const [Npp32f](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcSizeROI, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 32-bit floating point image copy with nearest source image pixel color with alpha channel unaffected.

7.59.1 Function Documentation

7.59.1.1 [NppStatus nppiCopyReplicateBorder_16s_AC4R](#) (const [Npp16s](#) * pSrc, int nSrcStep, [NppiSize](#) oSrcSizeROI, [Npp16s](#) * pDst, int nDstStep, [NppiSize](#) oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 16-bit signed integer image copy with nearest source image pixel color with alpha channel unaffected.

See [nppiCopyReplicateBorder_16s_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSrcSizeROI Size of the source region-of-interest.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oDstSizeROI Size of the destination region-of-interest.
nTopBorderHeight Height of top border.
nLeftBorderWidth Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.59.1.2 [NppStatus nppiCopyReplicateBorder_16s_C1R](#) (const [Npp16s](#) * pSrc, int nSrcStep, [NppiSize](#) oSrcSizeROI, [Npp16s](#) * pDst, int nDstStep, [NppiSize](#) oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

1 channel 16-bit signed integer image copy with nearest source image pixel color.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSrcSizeROI Size of the source region of pixels.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oDstSizeROI Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image (inner part) and nearest source image pixel color (outer part).

nTopBorderHeight Height (in pixels) of the top border. The number of pixel rows at the top of the destination ROI that will be filled with the nearest source image pixel color. $nBottomBorderHeight = oDstSizeROI.height - nTopBorderHeight - oSrcSizeROI.height$.

nLeftBorderWidth Width (in pixels) of the left border. The width of the border at the right side of the destination ROI is implicitly defined by the size of the source ROI: $nRightBorderWidth = oDstSizeROI.width - nLeftBorderWidth - oSrcSizeROI.width$.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.59.1.3 NppStatus nppiCopyReplicateBorder_16s_C3R (const Npp16s * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp16s * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

3 channel 16-bit signed integer image copy with nearest source image pixel color.

See [nppiCopyReplicateBorder_16s_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region-of-interest.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.59.1.4 NppStatus nppiCopyReplicateBorder_16s_C4R (const Npp16s * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp16s * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 16-bit signed integer image copy with nearest source image pixel color.

See [nppiCopyReplicateBorder_16s_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region-of-interest.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.59.1.5 NppStatus nppiCopyReplicateBorder_16u_AC4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 16-bit unsigned image copy with nearest source image pixel color with alpha channel unaffected.

See [nppiCopyReplicateBorder_16u_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSizeROI Size of the source region-of-interest.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.59.1.6 NppStatus nppiCopyReplicateBorder_16u_C1R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

1 channel 16-bit unsigned integer image copy with nearest source image pixel color.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSizeROI Size of the source region of pixels.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image (inner part) and nearest source image pixel color (outer part).

nTopBorderHeight Height (in pixels) of the top border. The number of pixel rows at the top of the destination ROI that will be filled with the nearest source image pixel color. $nBottomBorderHeight = oDstSizeROI.height - nTopBorderHeight - oSrcSizeROI.height$.

nLeftBorderWidth Width (in pixels) of the left border. The width of the border at the right side of the destination ROI is implicitly defined by the size of the source ROI: $nRightBorderWidth = oDstSizeROI.width - nLeftBorderWidth - oSrcSizeROI.width$.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.59.1.7 NppStatus nppiCopyReplicateBorder_16u_C3R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

3 channel 16-bit unsigned integer image copy with nearest source image pixel color.

See [nppiCopyReplicateBorder_16u_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSizeROI Size of the source region-of-interest.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.59.1.8 NppStatus nppiCopyReplicateBorder_16u_C4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 16-bit unsigned integer image copy with nearest source image pixel color.

See [nppiCopyReplicateBorder_16u_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSizeROI Size of the source region-of-interest.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.59.1.9 NppStatus nppiCopyReplicateBorder_32f_AC4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp32f * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 32-bit floating point image copy with nearest source image pixel color with alpha channel unaffected.

See [nppiCopyReplicateBorder_32f_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSizeROI Size of the source region-of-interest.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstSizeROI Size of the destination region-of-interest.
nTopBorderHeight Height of top border.
nLeftBorderWidth Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.59.1.10 NppStatus nppiCopyReplicateBorder_32f_C1R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp32f * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

1 channel 32-bit floating point image copy with nearest source image pixel color.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSizeROI Size of the source region of pixels.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstSizeROI Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image (inner part) and nearest source image pixel color (outer part).
nTopBorderHeight Height (in pixels) of the top border. The number of pixel rows at the top of the destination ROI that will be filled with the nearest source image pixel color. $nBottomBorderHeight = oDstSizeROI.height - nTopBorderHeight - oSrcSizeROI.height$.
nLeftBorderWidth Width (in pixels) of the left border. The width of the border at the right side of the destination ROI is implicitly defined by the size of the source ROI: $nRightBorderWidth = oDstSizeROI.width - nLeftBorderWidth - oSrcSizeROI.width$.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.59.1.11 `NppStatus nppiCopyReplicateBorder_32f_C3R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp32f * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)`

3 channel 32-bit floating point image copy with nearest source image pixel color.

See [nppiCopyReplicateBorder_32f_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region-of-interest.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.59.1.12 `NppStatus nppiCopyReplicateBorder_32f_C4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp32f * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)`

4 channel 32-bit floating point image copy with nearest source image pixel color.

See [nppiCopyReplicateBorder_32f_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region-of-interest.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.59.1.13 `NppStatus nppiCopyReplicateBorder_32s_AC4R (const Npp32s * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp32s * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)`

4 channel 32-bit signed integer image copy with nearest source image pixel color with alpha channel unaffected.

See [nppiCopyReplicateBorder_32s_C1R\(\)](#) for detailed documentation.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- oSrcSizeROI* Size of the source region-of-interest.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oDstSizeROI* Size of the destination region-of-interest.
- nTopBorderHeight* Height of top border.
- nLeftBorderWidth* Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.59.1.14 `NppStatus nppiCopyReplicateBorder_32s_C1R (const Npp32s * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp32s * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)`

1 channel 32-bit signed integer image copy with nearest source image pixel color.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- oSrcSizeROI* Size of the source region of pixels.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oDstSizeROI* Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image (inner part) and nearest source image pixel color (outer part).
- nTopBorderHeight* Height (in pixels) of the top border. The number of pixel rows at the top of the destination ROI that will be filled with the nearest source image pixel color. $nBottomBorderHeight = oDstSizeROI.height - nTopBorderHeight - oSrcSizeROI.height$.
- nLeftBorderWidth* Width (in pixels) of the left border. The width of the border at the right side of the destination ROI is implicitly defined by the size of the source ROI: $nRightBorderWidth = oDstSizeROI.width - nLeftBorderWidth - oSrcSizeROI.width$.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.59.1.15 `NppStatus nppiCopyReplicateBorder_32s_C3R (const Npp32s * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp32s * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)`

3 channel 32-bit signed image copy with nearest source image pixel color.

See [nppiCopyReplicateBorder_32s_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region-of-interest.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.59.1.16 `NppStatus nppiCopyReplicateBorder_32s_C4R (const Npp32s * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp32s * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)`

4 channel 32-bit signed integer image copy with nearest source image pixel color.

See [nppiCopyReplicateBorder_32s_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region-of-interest.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.59.1.17 `NppStatus nppiCopyReplicateBorder_8u_AC4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)`

4 channel 8-bit unsigned integer image copy with nearest source image pixel color with alpha channel unaffected.

See [nppiCopyReplicateBorder_8u_C1R\(\)](#) for detailed documentation.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- oSrcSizeROI* Size of the source region-of-interest.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oDstSizeROI* Size of the destination region-of-interest.
- nTopBorderHeight* Height of top border.
- nLeftBorderWidth* Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.59.1.18 `NppStatus nppiCopyReplicateBorder_8u_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)`

1 channel 8-bit unsigned integer image copy with nearest source image pixel color.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- oSrcSizeROI* Size of the source region of pixels.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oDstSizeROI* Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image (inner part) and nearest source image pixel color (outer part).
- nTopBorderHeight* Height (in pixels) of the top border. The number of pixel rows at the top of the destination ROI that will be filled with the nearest source image pixel color. $nBottomBorderHeight = oDstSizeROI.height - nTopBorderHeight - oSrcSizeROI.height$.
- nLeftBorderWidth* Width (in pixels) of the left border. The width of the border at the right side of the destination ROI is implicitly defined by the size of the source ROI: $nRightBorderWidth = oDstSizeROI.width - nLeftBorderWidth - oSrcSizeROI.width$.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.59.1.19 `NppStatus nppiCopyReplicateBorder_8u_C3R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)`

3 channel 8-bit unsigned integer image copy with nearest source image pixel color.

See [nppiCopyReplicateBorder_8u_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSizeROI Size of the source region-of-interest.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstSizeROI Size of the destination region-of-interest.
nTopBorderHeight Height of top border.
nLeftBorderWidth Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.59.1.20 `NppStatus nppiCopyReplicateBorder_8u_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)`

4 channel 8-bit unsigned integer image copy with nearest source image pixel color.

See [nppiCopyReplicateBorder_8u_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSizeROI Size of the source region-of-interest.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstSizeROI Size of the destination region-of-interest.
nTopBorderHeight Height of top border.
nLeftBorderWidth Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.60 Copy Wrap Border

CopyWrapBorder

Methods for copying images and padding borders with wrapped replications of the source image pixel colors.

- `NppStatus nppiCopyWrapBorder_8u_C1R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcSizeROI, `Npp8u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

1 channel 8-bit unsigned integer image copy with the borders wrapped by replication of source image pixel colors.
- `NppStatus nppiCopyWrapBorder_8u_C3R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcSizeROI, `Npp8u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

3 channel 8-bit unsigned integer image copy with the borders wrapped by replication of source image pixel colors.
- `NppStatus nppiCopyWrapBorder_8u_C4R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcSizeROI, `Npp8u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 8-bit unsigned integer image copy with the borders wrapped by replication of source image pixel colors.
- `NppStatus nppiCopyWrapBorder_8u_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcSizeROI, `Npp8u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 8-bit unsigned integer image copy with the borders wrapped by replication of source image pixel colors with alpha channel unaffected.
- `NppStatus nppiCopyWrapBorder_16u_C1R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcSizeROI, `Npp16u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

1 channel 16-bit unsigned integer image copy with the borders wrapped by replication of source image pixel colors.
- `NppStatus nppiCopyWrapBorder_16u_C3R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcSizeROI, `Npp16u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

3 channel 16-bit unsigned integer image copy with the borders wrapped by replication of source image pixel colors.
- `NppStatus nppiCopyWrapBorder_16u_C4R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcSizeROI, `Npp16u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 16-bit unsigned integer image copy with the borders wrapped by replication of source image pixel colors.
- `NppStatus nppiCopyWrapBorder_16u_AC4R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcSizeROI, `Npp16u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 16-bit unsigned integer image copy with the borders wrapped by replication of source image pixel colors with alpha channel unaffected.

- **NppStatus nppiCopyWrapBorder_16s_C1R** (const **Npp16s** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp16s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

1 channel 16-bit signed integer image copy with the borders wrapped by replication of source image pixel colors.

- **NppStatus nppiCopyWrapBorder_16s_C3R** (const **Npp16s** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp16s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

3 channel 16-bit signed integer image copy with the borders wrapped by replication of source image pixel colors.

- **NppStatus nppiCopyWrapBorder_16s_C4R** (const **Npp16s** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp16s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 16-bit signed integer image copy with the borders wrapped by replication of source image pixel colors.

- **NppStatus nppiCopyWrapBorder_16s_AC4R** (const **Npp16s** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp16s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 16-bit signed integer image copy with the borders wrapped by replication of source image pixel colors with alpha channel unaffected.

- **NppStatus nppiCopyWrapBorder_32s_C1R** (const **Npp32s** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp32s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

1 channel 32-bit signed integer image copy with the borders wrapped by replication of source image pixel colors.

- **NppStatus nppiCopyWrapBorder_32s_C3R** (const **Npp32s** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp32s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

3 channel 32-bit signed integer image copy with the borders wrapped by replication of source image pixel colors.

- **NppStatus nppiCopyWrapBorder_32s_C4R** (const **Npp32s** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp32s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 32-bit signed integer image copy with the borders wrapped by replication of source image pixel colors.

- **NppStatus nppiCopyWrapBorder_32s_AC4R** (const **Npp32s** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp32s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 32-bit signed integer image copy with the borders wrapped by replication of source image pixel colors with alpha channel unaffected.

- **NppStatus nppiCopyWrapBorder_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp32f** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)
1 channel 32-bit floating point image copy with the borders wrapped by replication of source image pixel colors.
- **NppStatus nppiCopyWrapBorder_32f_C3R** (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp32f** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)
3 channel 32-bit floating point image copy with the borders wrapped by replication of source image pixel colors.
- **NppStatus nppiCopyWrapBorder_32f_C4R** (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp32f** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)
4 channel 32-bit floating point image copy with the borders wrapped by replication of source image pixel colors.
- **NppStatus nppiCopyWrapBorder_32f_AC4R** (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp32f** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)
1 channel 32-bit floating point image copy with the borders wrapped by replication of source image pixel colors with alpha channel unaffected.

7.60.1 Function Documentation

7.60.1.1 **NppStatus nppiCopyWrapBorder_16s_AC4R** (const **Npp16s** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp16s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 16-bit signed integer image copy with the borders wrapped by replication of source image pixel colors with alpha channel unaffected.

See [nppiCopyWrapBorder_16s_C1R\(\)](#) for detailed documentation.

Parameters:

- pSrc** Source-Image Pointer.
- nSrcStep** Source-Image Line Step.
- oSrcSizeROI** Size of the source region-of-interest.
- pDst** Destination-Image Pointer.
- nDstStep** Destination-Image Line Step.
- oDstSizeROI** Size of the destination region-of-interest.
- nTopBorderHeight** Height of top border.
- nLeftBorderWidth** Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.60.1.2 NppStatus nppiCopyWrapBorder_16s_C1R (const Npp16s * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp16s * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

1 channel 16-bit signed integer image copy with the borders wrapped by replication of source image pixel colors.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region of pixels.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image (inner part) and a border consisting of wrapped replication of the source image pixel colors (outer part).

nTopBorderHeight Height (in pixels) of the top border. The number of pixel rows at the top of the destination ROI that will be filled with the wrapped replication of the corresponding column of source image pixels colors. $nBottomBorderHeight = oDstSizeROI.height - nTopBorderHeight - oSrcSizeROI.height$.

nLeftBorderWidth Width (in pixels) of the left border. The width of the border at the right side of the destination ROI is implicitly defined by the size of the source ROI: $nRightBorderWidth = oDstSizeROI.width - nLeftBorderWidth - oSrcSizeROI.width$.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.60.1.3 NppStatus nppiCopyWrapBorder_16s_C3R (const Npp16s * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp16s * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

3 channel 16-bit signed integer image copy with the borders wrapped by replication of source image pixel colors.

See [nppiCopyWrapBorder_16s_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region-of-interest.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.60.1.4 NppStatus nppiCopyWrapBorder_16s_C4R (const Npp16s * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp16s * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 16-bit signed integer image copy with the borders wrapped by replication of source image pixel colors.

See [nppiCopyWrapBorder_16s_C1R\(\)](#) for detailed documentation.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- oSrcSizeROI* Size of the source region-of-interest.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oDstSizeROI* Size of the destination region-of-interest.
- nTopBorderHeight* Height of top border.
- nLeftBorderWidth* Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.60.1.5 NppStatus nppiCopyWrapBorder_16u_AC4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 16-bit unsigned integer image copy with the borders wrapped by replication of source image pixel colors with alpha channel unaffected.

See [nppiCopyWrapBorder_16u_C1R\(\)](#) for detailed documentation.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- oSrcSizeROI* Size of the source region-of-interest.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oDstSizeROI* Size of the destination region-of-interest.
- nTopBorderHeight* Height of top border.
- nLeftBorderWidth* Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.60.1.6 NppStatus nppiCopyWrapBorder_16u_C1R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

1 channel 16-bit unsigned integer image copy with the borders wrapped by replication of source image pixel colors.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region of pixels.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image (inner part) and a border consisting of wrapped replication of the source image pixel colors (outer part).

nTopBorderHeight Height (in pixels) of the top border. The number of pixel rows at the top of the destination ROI that will be filled with the wrapped replication of the corresponding column of source image pixels colors. $nBottomBorderHeight = oDstSizeROI.height - nTopBorderHeight - oSrcSizeROI.height$.

nLeftBorderWidth Width (in pixels) of the left border. The width of the border at the right side of the destination ROI is implicitly defined by the size of the source ROI: $nRightBorderWidth = oDstSizeROI.width - nLeftBorderWidth - oSrcSizeROI.width$.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.60.1.7 NppStatus nppiCopyWrapBorder_16u_C3R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

3 channel 16-bit unsigned integer image copy with the borders wrapped by replication of source image pixel colors.

See [nppiCopyWrapBorder_16u_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region-of-interest.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.60.1.8 NppStatus nppiCopyWrapBorder_16u_C4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 16-bit unsigned integer image copy with the borders wrapped by replication of source image pixel colors.

See [nppiCopyWrapBorder_16u_C1R\(\)](#) for detailed documentation.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- oSrcSizeROI* Size of the source region-of-interest.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oDstSizeROI* Size of the destination region-of-interest.
- nTopBorderHeight* Height of top border.
- nLeftBorderWidth* Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.60.1.9 NppStatus nppiCopyWrapBorder_32f_AC4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp32f * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

1 channel 32-bit floating point image copy with the borders wrapped by replication of source image pixel colors with alpha channel unaffected.

See [nppiCopyWrapBorder_32f_C1R\(\)](#) for detailed documentation.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- oSrcSizeROI* Size of the source region-of-interest.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oDstSizeROI* Size of the destination region-of-interest.
- nTopBorderHeight* Height of top border.
- nLeftBorderWidth* Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.60.1.10 `NppStatus nppiCopyWrapBorder_32f_C1R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp32f * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)`

1 channel 32-bit floating point image copy with the borders wrapped by replication of source image pixel colors.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region of pixels.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image (inner part) and a border consisting of wrapped replication of the source image pixel colors (outer part).

nTopBorderHeight Height (in pixels) of the top border. The number of pixel rows at the top of the destination ROI that will be filled with the wrapped replication of the corresponding column of source image pixels colors. $nBottomBorderHeight = oDstSizeROI.height - nTopBorderHeight - oSrcSizeROI.height$.

nLeftBorderWidth Width (in pixels) of the left border. The width of the border at the right side of the destination ROI is implicitly defined by the size of the source ROI: $nRightBorderWidth = oDstSizeROI.width - nLeftBorderWidth - oSrcSizeROI.width$.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.60.1.11 `NppStatus nppiCopyWrapBorder_32f_C3R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp32f * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)`

3 channel 32-bit floating point image copy with the borders wrapped by replication of source image pixel colors.

See `nppiCopyWrapBorder_32f_C1R()` for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region-of-interest.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.60.1.12 NppStatus nppiCopyWrapBorder_32f_C4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp32f * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 32-bit floating point image copy with the borders wrapped by replication of source image pixel colors.

See [nppiCopyWrapBorder_32f_C1R\(\)](#) for detailed documentation.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- oSrcSizeROI* Size of the source region-of-interest.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oDstSizeROI* Size of the destination region-of-interest.
- nTopBorderHeight* Height of top border.
- nLeftBorderWidth* Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.60.1.13 NppStatus nppiCopyWrapBorder_32s_AC4R (const Npp32s * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp32s * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 32-bit signed integer image copy with the borders wrapped by replication of source image pixel colors with alpha channel unaffected.

See [nppiCopyWrapBorder_32s_C1R\(\)](#) for detailed documentation.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- oSrcSizeROI* Size of the source region-of-interest.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oDstSizeROI* Size of the destination region-of-interest.
- nTopBorderHeight* Height of top border.
- nLeftBorderWidth* Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.60.1.14 `NppStatus nppiCopyWrapBorder_32s_C1R (const Npp32s * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp32s * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)`

1 channel 32-bit signed integer image copy with the borders wrapped by replication of source image pixel colors.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region of pixels.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image (inner part) and a border consisting of wrapped replication of the source image pixel colors (outer part).

nTopBorderHeight Height (in pixels) of the top border. The number of pixel rows at the top of the destination ROI that will be filled with the wrapped replication of the corresponding column of source image pixels colors. $nBottomBorderHeight = oDstSizeROI.height - nTopBorderHeight - oSrcSizeROI.height$.

nLeftBorderWidth Width (in pixels) of the left border. The width of the border at the right side of the destination ROI is implicitly defined by the size of the source ROI: $nRightBorderWidth = oDstSizeROI.width - nLeftBorderWidth - oSrcSizeROI.width$.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.60.1.15 `NppStatus nppiCopyWrapBorder_32s_C3R (const Npp32s * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp32s * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)`

3 channel 32-bit signed integer image copy with the borders wrapped by replication of source image pixel colors.

See `nppiCopyWrapBorder_32s_C1R()` for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region-of-interest.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.60.1.16 NppStatus nppiCopyWrapBorder_32s_C4R (const Npp32s * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp32s * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 32-bit signed integer image copy with the borders wrapped by replication of source image pixel colors.

See [nppiCopyWrapBorder_32s_C1R\(\)](#) for detailed documentation.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- oSrcSizeROI* Size of the source region-of-interest.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oDstSizeROI* Size of the destination region-of-interest.
- nTopBorderHeight* Height of top border.
- nLeftBorderWidth* Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.60.1.17 NppStatus nppiCopyWrapBorder_8u_AC4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

4 channel 8-bit unsigned integer image copy with the borders wrapped by replication of source image pixel colors with alpha channel unaffected.

See [nppiCopyWrapBorder_8u_C1R\(\)](#) for detailed documentation.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- oSrcSizeROI* Size of the source region-of-interest.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oDstSizeROI* Size of the destination region-of-interest.
- nTopBorderHeight* Height of top border.
- nLeftBorderWidth* Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.60.1.18 NppStatus nppiCopyWrapBorder_8u_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

1 channel 8-bit unsigned integer image copy with the borders wrapped by replication of source image pixel colors.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region of pixels.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image (inner part) and a border consisting of wrapped replication of the source image pixel colors (outer part).

nTopBorderHeight Height (in pixels) of the top border. The number of pixel rows at the top of the destination ROI that will be filled with the wrapped replication of the corresponding column of source image pixels colors. $nBottomBorderHeight = oDstSizeROI.height - nTopBorderHeight - oSrcSizeROI.height$.

nLeftBorderWidth Width (in pixels) of the left border. The width of the border at the right side of the destination ROI is implicitly defined by the size of the source ROI: $nRightBorderWidth = oDstSizeROI.width - nLeftBorderWidth - oSrcSizeROI.width$.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.60.1.19 NppStatus nppiCopyWrapBorder_8u_C3R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)

3 channel 8-bit unsigned integer image copy with the borders wrapped by replication of source image pixel colors.

See [nppiCopyWrapBorder_8u_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region-of-interest.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.60.1.20 `NppStatus nppiCopyWrapBorder_8u_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth)`

4 channel 8-bit unsigned integer image copy with the borders wrapped by replication of source image pixel colors.

See [nppiCopyWrapBorder_8u_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSizeROI Size of the source region-of-interest.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.61 Copy Sub-Pixel

CopySubpix

Functions for copying linearly interpolated images using source image subpixel coordinates

- **NppStatus nppiCopySubpix_8u_C1R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oDstSizeROI, **Npp32f** nDx, **Npp32f** nDy)
1 channel 8-bit unsigned integer linearly interpolated source image subpixel coordinate color copy.
- **NppStatus nppiCopySubpix_8u_C3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oDstSizeROI, **Npp32f** nDx, **Npp32f** nDy)
3 channel 8-bit unsigned integer linearly interpolated source image subpixel coordinate color copy.
- **NppStatus nppiCopySubpix_8u_C4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oDstSizeROI, **Npp32f** nDx, **Npp32f** nDy)
4 channel 8-bit unsigned integer linearly interpolated source image subpixel coordinate color copy.
- **NppStatus nppiCopySubpix_8u_AC4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oDstSizeROI, **Npp32f** nDx, **Npp32f** nDy)
4 channel 8-bit unsigned integer linearly interpolated source image subpixel coordinate color copy with alpha channel unaffected.
- **NppStatus nppiCopySubpix_16u_C1R** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oDstSizeROI, **Npp32f** nDx, **Npp32f** nDy)
1 channel 16-bit unsigned integer linearly interpolated source image subpixel coordinate color copy.
- **NppStatus nppiCopySubpix_16u_C3R** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oDstSizeROI, **Npp32f** nDx, **Npp32f** nDy)
3 channel 16-bit unsigned integer linearly interpolated source image subpixel coordinate color copy.
- **NppStatus nppiCopySubpix_16u_C4R** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oDstSizeROI, **Npp32f** nDx, **Npp32f** nDy)
4 channel 16-bit unsigned integer linearly interpolated source image subpixel coordinate color copy.
- **NppStatus nppiCopySubpix_16u_AC4R** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oDstSizeROI, **Npp32f** nDx, **Npp32f** nDy)
4 channel 16-bit unsigned linearly interpolated source image subpixel coordinate color copy with alpha channel unaffected.
- **NppStatus nppiCopySubpix_16s_C1R** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, **Npp32f** nDx, **Npp32f** nDy)
1 channel 16-bit signed integer linearly interpolated source image subpixel coordinate color copy.
- **NppStatus nppiCopySubpix_16s_C3R** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, **Npp32f** nDx, **Npp32f** nDy)
3 channel 16-bit signed integer linearly interpolated source image subpixel coordinate color copy.
- **NppStatus nppiCopySubpix_16s_C4R** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, **Npp32f** nDx, **Npp32f** nDy)
4 channel 16-bit signed integer linearly interpolated source image subpixel coordinate color copy.

- [NppStatus nppiCopySubpix_16s_AC4R](#) (const [Npp16s](#) *pSrc, int nSrcStep, [Npp16s](#) *pDst, int nDstStep, [NppiSize](#) oDstSizeROI, [Npp32f](#) nDx, [Npp32f](#) nDy)
4 channel 16-bit signed integer linearly interpolated source image subpixel coordinate color copy with alpha channel unaffected.
- [NppStatus nppiCopySubpix_32s_C1R](#) (const [Npp32s](#) *pSrc, int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oDstSizeROI, [Npp32f](#) nDx, [Npp32f](#) nDy)
1 channel 32-bit signed integer linearly interpolated source image subpixel coordinate color copy.
- [NppStatus nppiCopySubpix_32s_C3R](#) (const [Npp32s](#) *pSrc, int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oDstSizeROI, [Npp32f](#) nDx, [Npp32f](#) nDy)
3 channel 32-bit signed linearly interpolated source image subpixel coordinate color copy.
- [NppStatus nppiCopySubpix_32s_C4R](#) (const [Npp32s](#) *pSrc, int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oDstSizeROI, [Npp32f](#) nDx, [Npp32f](#) nDy)
4 channel 32-bit signed integer linearly interpolated source image subpixel coordinate color copy.
- [NppStatus nppiCopySubpix_32s_AC4R](#) (const [Npp32s](#) *pSrc, int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oDstSizeROI, [Npp32f](#) nDx, [Npp32f](#) nDy)
4 channel 32-bit signed integer linearly interpolated source image subpixel coordinate color copy with alpha channel unaffected.
- [NppStatus nppiCopySubpix_32f_C1R](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oDstSizeROI, [Npp32f](#) nDx, [Npp32f](#) nDy)
1 channel 32-bit floating point linearly interpolated source image subpixel coordinate color copy.
- [NppStatus nppiCopySubpix_32f_C3R](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oDstSizeROI, [Npp32f](#) nDx, [Npp32f](#) nDy)
3 channel 32-bit floating point linearly interpolated source image subpixel coordinate color copy.
- [NppStatus nppiCopySubpix_32f_C4R](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oDstSizeROI, [Npp32f](#) nDx, [Npp32f](#) nDy)
4 channel 32-bit floating point linearly interpolated source image subpixel coordinate color copy.
- [NppStatus nppiCopySubpix_32f_AC4R](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oDstSizeROI, [Npp32f](#) nDx, [Npp32f](#) nDy)
4 channel 32-bit floating point linearly interpolated source image subpixel coordinate color copy with alpha channel unaffected.

7.61.1 Function Documentation

7.61.1.1 [NppStatus nppiCopySubpix_16s_AC4R](#) (const [Npp16s](#) *pSrc, int nSrcStep, [Npp16s](#) *pDst, int nDstStep, [NppiSize](#) oDstSizeROI, [Npp32f](#) nDx, [Npp32f](#) nDy)

4 channel 16-bit signed integer linearly interpolated source image subpixel coordinate color copy with alpha channel unaffected.

See [nppiCopySubpix_16s_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstSizeROI Size of the destination region-of-interest.
nDx Fractional part of source image X coordinate.
nDy Fractional part of source image Y coordinate.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.61.1.2 `NppStatus nppiCopySubpix_16s_C1R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oDstSizeROI, Npp32f nDx, Npp32f nDy)`

1 channel 16-bit signed integer linearly interpolated source image subpixel coordinate color copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstSizeROI Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image, source image ROI is assumed to be same as destination image ROI.
nDx Fractional part of source image X coordinate.
nDy Fractional part of source image Y coordinate.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.61.1.3 `NppStatus nppiCopySubpix_16s_C3R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oDstSizeROI, Npp32f nDx, Npp32f nDy)`

3 channel 16-bit signed integer linearly interpolated source image subpixel coordinate color copy.

See [nppiCopySubpix_16s_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstSizeROI Size of the destination region-of-interest.

nDx Fractional part of source image X coordinate.

nDy Fractional part of source image Y coordinate.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.61.1.4 NppStatus nppiCopySubpix_16s_C4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oDstSizeROI, Npp32f nDx, Npp32f nDy)

4 channel 16-bit signed integer linearly interpolated source image subpixel coordinate color copy.

See [nppiCopySubpix_16s_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nDx Fractional part of source image X coordinate.

nDy Fractional part of source image Y coordinate.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.61.1.5 NppStatus nppiCopySubpix_16u_AC4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI, Npp32f nDx, Npp32f nDy)

4 channel 16-bit unsigned linearly interpolated source image subpixel coordinate color copy with alpha channel unaffected.

See [nppiCopySubpix_16u_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nDx Fractional part of source image X coordinate.

nDy Fractional part of source image Y coordinate.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.61.1.6 NppStatus nppiCopySubpix_16u_C1R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI, Npp32f nDx, Npp32f nDy)

1 channel 16-bit unsigned integer linearly interpolated source image subpixel coordinate color copy.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image, source image ROI is assumed to be same as destination image ROI.

nDx Fractional part of source image X coordinate.

nDy Fractional part of source image Y coordinate.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.61.1.7 NppStatus nppiCopySubpix_16u_C3R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI, Npp32f nDx, Npp32f nDy)

3 channel 16-bit unsigned integer linearly interpolated source image subpixel coordinate color copy.

See [nppiCopySubpix_16u_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nDx Fractional part of source image X coordinate.

nDy Fractional part of source image Y coordinate.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.61.1.8 NppStatus nppiCopySubpix_16u_C4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI, Npp32f nDx, Npp32f nDy)

4 channel 16-bit unsigned integer linearly interpolated source image subpixel coordinate color copy.

See [nppiCopySubpix_16u_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstSizeROI Size of the destination region-of-interest.
nDx Fractional part of source image X coordinate.
nDy Fractional part of source image Y coordinate.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.61.1.9 **NppStatus nppiCopySubpix_32f_AC4R** (const Npp32f * *pSrc*, int *nSrcStep*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oDstSizeROI*, Npp32f *nDx*, Npp32f *nDy*)

4 channel 32-bit floating point linearly interpolated source image subpixel coordinate color copy with alpha channel unaffected.

See [nppiCopySubpix_32f_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstSizeROI Size of the destination region-of-interest.
nDx Fractional part of source image X coordinate.
nDy Fractional part of source image Y coordinate.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.61.1.10 **NppStatus nppiCopySubpix_32f_C1R** (const Npp32f * *pSrc*, int *nSrcStep*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oDstSizeROI*, Npp32f *nDx*, Npp32f *nDy*)

1 channel 32-bit floating point linearly interpolated source image subpixel coordinate color copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstSizeROI Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image, source image ROI is assumed to be same as destination image ROI.
nDx Fractional part of source image X coordinate.
nDy Fractional part of source image Y coordinate.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.61.1.11 NppStatus nppiCopySubpix_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oDstSizeROI, Npp32f nDx, Npp32f nDy)

3 channel 32-bit floating point linearly interpolated source image subpixel coordinate color copy.

See [nppiCopySubpix_32f_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nDx Fractional part of source image X coordinate.

nDy Fractional part of source image Y coordinate.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.61.1.12 NppStatus nppiCopySubpix_32f_C4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oDstSizeROI, Npp32f nDx, Npp32f nDy)

4 channel 32-bit floating point linearly interpolated source image subpixel coordinate color copy.

See [nppiCopySubpix_32f_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nDx Fractional part of source image X coordinate.

nDy Fractional part of source image Y coordinate.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.61.1.13 NppStatus nppiCopySubpix_32s_AC4R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oDstSizeROI, Npp32f nDx, Npp32f nDy)

4 channel 32-bit signed integer linearly interpolated source image subpixel coordinate color copy with alpha channel unaffected.

See [nppiCopySubpix_32s_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstSizeROI Size of the destination region-of-interest.
nDx Fractional part of source image X coordinate.
nDy Fractional part of source image Y coordinate.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.61.1.14 `NppStatus nppiCopySubpix_32s_C1R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oDstSizeROI, Npp32f nDx, Npp32f nDy)`

1 channel 32-bit signed integer linearly interpolated source image subpixel coordinate color copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstSizeROI Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image, source image ROI is assumed to be same as destination image ROI.
nDx Fractional part of source image X coordinate.
nDy Fractional part of source image Y coordinate.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.61.1.15 `NppStatus nppiCopySubpix_32s_C3R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oDstSizeROI, Npp32f nDx, Npp32f nDy)`

3 channel 32-bit signed integer linearly interpolated source image subpixel coordinate color copy.

See [nppiCopySubpix_32s_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstSizeROI Size of the destination region-of-interest.

nDx Fractional part of source image X coordinate.

nDy Fractional part of source image Y coordinate.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.61.1.16 `NppStatus nppiCopySubpix_32s_C4R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oDstSizeROI, Npp32f nDx, Npp32f nDy)`

4 channel 32-bit signed integer linearly interpolated source image subpixel coordinate color copy.

See [nppiCopySubpix_32s_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nDx Fractional part of source image X coordinate.

nDy Fractional part of source image Y coordinate.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.61.1.17 `NppStatus nppiCopySubpix_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, Npp32f nDx, Npp32f nDy)`

4 channel 8-bit unsigned integer linearly interpolated source image subpixel coordinate color copy with alpha channel unaffected.

See [nppiCopySubpix_8u_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nDx Fractional part of source image X coordinate.

nDy Fractional part of source image Y coordinate.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.61.1.18 `NppStatus nppiCopySubpix_8u_C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, Npp32f nDx, Npp32f nDy)`

1 channel 8-bit unsigned integer linearly interpolated source image subpixel coordinate color copy.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image, source image ROI is assumed to be same as destination image ROI.

nDx Fractional part of source image X coordinate.

nDy Fractional part of source image Y coordinate.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.61.1.19 `NppStatus nppiCopySubpix_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, Npp32f nDx, Npp32f nDy)`

3 channel 8-bit unsigned integer linearly interpolated source image subpixel coordinate color copy.

See `nppiCopySubpix_8u_C1R()` for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nDx Fractional part of source image X coordinate.

nDy Fractional part of source image Y coordinate.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.61.1.20 `NppStatus nppiCopySubpix_8u_C4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, Npp32f nDx, Npp32f nDy)`

4 channel 8-bit unsigned integer linearly interpolated source image subpixel coordinate color copy.

See `nppiCopySubpix_8u_C1R()` for detailed documentation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nDx Fractional part of source image X coordinate.

nDy Fractional part of source image Y coordinate.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.62 Duplicate Channel

Dup

Functions for duplicating a single channel image in a multiple channel image.

- `NppStatus nppiDup_8u_C1C3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oDstSizeROI`)
1 channel 8-bit unsigned integer source image duplicated in all 3 channels of destination image.
- `NppStatus nppiDup_8u_C1C4R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oDstSizeROI`)
1 channel 8-bit unsigned integer source image duplicated in all 4 channels of destination image.
- `NppStatus nppiDup_8u_C1AC4R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oDstSizeROI`)
1 channel 8-bit unsigned integer source image duplicated in 3 channels of 4 channel destination image with alpha channel unaffected.
- `NppStatus nppiDup_16u_C1C3R` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oDstSizeROI`)
1 channel 16-bit unsigned integer source image duplicated in all 3 channels of destination image.
- `NppStatus nppiDup_16u_C1C4R` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oDstSizeROI`)
1 channel 16-bit unsigned integer source image duplicated in all 4 channels of destination image.
- `NppStatus nppiDup_16u_C1AC4R` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oDstSizeROI`)
1 channel 16-bit unsigned integer source image duplicated in 3 channels of 4 channel destination image with alpha channel unaffected.
- `NppStatus nppiDup_16s_C1C3R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oDstSizeROI`)
1 channel 16-bit signed integer source image duplicated in all 3 channels of destination image.
- `NppStatus nppiDup_16s_C1C4R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oDstSizeROI`)
1 channel 16-bit signed integer source image duplicated in all 4 channels of destination image.
- `NppStatus nppiDup_16s_C1AC4R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oDstSizeROI`)
1 channel 16-bit signed integer source image duplicated in 3 channels of 4 channel destination image with alpha channel unaffected.
- `NppStatus nppiDup_32s_C1C3R` (const `Npp32s *pSrc`, int `nSrcStep`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oDstSizeROI`)
1 channel 32-bit signed integer source image duplicated in all 3 channels of destination image.
- `NppStatus nppiDup_32s_C1C4R` (const `Npp32s *pSrc`, int `nSrcStep`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oDstSizeROI`)

1 channel 32-bit signed integer source image duplicated in all 4 channels of destination image.

- **NppStatus nppiDup_32s_C1AC4R** (const **Npp32s** *pSrc, int nSrcStep, **Npp32s** *pDst, int nDstStep, **NppiSize** oDstSizeROI)

1 channel 32-bit signed integer source image duplicated in 3 channels of 4 channel destination image with alpha channel unaffected.

- **NppStatus nppiDup_32f_C1C3R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oDstSizeROI)

1 channel 32-bit floating point source image duplicated in all 3 channels of destination image.

- **NppStatus nppiDup_32f_C1C4R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oDstSizeROI)

1 channel 32-bit floating point source image duplicated in all 4 channels of destination image.

- **NppStatus nppiDup_32f_C1AC4R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oDstSizeROI)

1 channel 32-bit floating point source image duplicated in 3 channels of 4 channel destination image with alpha channel unaffected.

7.62.1 Function Documentation

7.62.1.1 NppStatus nppiDup_16s_C1AC4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oDstSizeROI)

1 channel 16-bit signed integer source image duplicated in 3 channels of 4 channel destination image with alpha channel unaffected.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.62.1.2 NppStatus nppiDup_16s_C1C3R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oDstSizeROI)

1 channel 16-bit signed integer source image duplicated in all 3 channels of destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image, source image ROI is assumed to be same as destination image ROI.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.62.1.3 NppStatus nppiDup_16s_C1C4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oDstSizeROI)

1 channel 16-bit signed integer source image duplicated in all 4 channels of destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.62.1.4 NppStatus nppiDup_16u_C1AC4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI)

1 channel 16-bit unsigned integer source image duplicated in 3 channels of 4 channel destination image with alpha channel unaffected.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.62.1.5 NppStatus nppiDup_16u_C1C3R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI)

1 channel 16-bit unsigned integer source image duplicated in all 3 channels of destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image, source image ROI is assumed to be same as destination image ROI.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.62.1.6 NppStatus nppiDup_16u_C1C4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI)

1 channel 16-bit unsigned integer source image duplicated in all 4 channels of destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.62.1.7 NppStatus nppiDup_32f_C1AC4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oDstSizeROI)

1 channel 32-bit floating point source image duplicated in 3 channels of 4 channel destination image with alpha channel unaffected.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.62.1.8 NppStatus nppiDup_32f_C1C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oDstSizeROI)

1 channel 32-bit floating point source image duplicated in all 3 channels of destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image, source image ROI is assumed to be same as destination image ROI.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.62.1.9 NppStatus nppiDup_32f_C1C4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oDstSizeROI)

1 channel 32-bit floating point source image duplicated in all 4 channels of destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.62.1.10 NppStatus nppiDup_32s_C1AC4R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oDstSizeROI)

1 channel 32-bit signed integer source image duplicated in 3 channels of 4 channel destination image with alpha channel unaffected.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.62.1.11 NppStatus nppiDup_32s_C1C3R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oDstSizeROI)

1 channel 32-bit signed integer source image duplicated in all 3 channels of destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image, source image ROI is assumed to be same as destination image ROI.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.62.1.12 NppStatus nppiDup_32s_C1C4R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oDstSizeROI)

1 channel 32-bit signed integer source image duplicated in all 4 channels of destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.62.1.13 NppStatus nppiDup_8u_C1AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI)

1 channel 8-bit unsigned integer source image duplicated in 3 channels of 4 channel destination image with alpha channel unaffected.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.62.1.14 `NppStatus nppiDup_8u_C1C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI)`

1 channel 8-bit unsigned integer source image duplicated in all 3 channels of destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image, source image ROI is assumed to be same as destination image ROI.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.62.1.15 `NppStatus nppiDup_8u_C1C4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI)`

1 channel 8-bit unsigned integer source image duplicated in all 4 channels of destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.63 Transpose

Transpose

Methods for transposing images of various types.

Like matrix transpose, image transpose is a mirror along the image's diagonal (upper-left to lower-right corner).

- `NppStatus nppiTranspose_8u_C1R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSrcROI)
1 channel 8-bit unsigned int image transpose.
- `NppStatus nppiTranspose_8u_C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSrcROI)
3 channel 8-bit unsigned int image transpose.
- `NppStatus nppiTranspose_8u_C4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSrcROI)
4 channel 8-bit unsigned int image transpose.
- `NppStatus nppiTranspose_16u_C1R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSrcROI)
1 channel 16-bit unsigned int image transpose.
- `NppStatus nppiTranspose_16u_C3R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSrcROI)
3 channel 16-bit unsigned int image transpose.
- `NppStatus nppiTranspose_16u_C4R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSrcROI)
4 channel 16-bit unsigned int image transpose.
- `NppStatus nppiTranspose_16s_C1R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSrcROI)
1 channel 16-bit signed int image transpose.
- `NppStatus nppiTranspose_16s_C3R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSrcROI)
3 channel 16-bit signed int image transpose.
- `NppStatus nppiTranspose_16s_C4R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSrcROI)
4 channel 16-bit signed int image transpose.
- `NppStatus nppiTranspose_32s_C1R` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pDst, int nDstStep, `NppiSize` oSrcROI)
1 channel 32-bit signed int image transpose.
- `NppStatus nppiTranspose_32s_C3R` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pDst, int nDstStep, `NppiSize` oSrcROI)

3 channel 32-bit signed int image transpose.

- `NppStatus nppiTranspose_32s_C4R` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pDst, int nDstStep, `NppiSize` oSrcROI)

4 channel 32-bit signed int image transpose.

- `NppStatus nppiTranspose_32f_C1R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSrcROI)

1 channel 32-bit floating point image transpose.

- `NppStatus nppiTranspose_32f_C3R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSrcROI)

3 channel 32-bit floating point image transpose.

- `NppStatus nppiTranspose_32f_C4R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSrcROI)

4 channel 32-bit floating point image transpose.

7.63.1 Function Documentation

7.63.1.1 `NppStatus nppiTranspose_16s_C1R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSrcROI)

1 channel 16-bit signed int image transpose.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Pointer to the destination ROI.
- nDstStep* Destination-Image Line Step.
- oSrcROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.63.1.2 `NppStatus nppiTranspose_16s_C3R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSrcROI)

3 channel 16-bit signed int image transpose.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Pointer to the destination ROI.
- nDstStep* Destination-Image Line Step.

oSrcROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.63.1.3 NppStatus nppiTranspose_16s_C4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSrcROI)

4 channel 16-bit signed int image transpose.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Pointer to the destination ROI.

nDstStep Destination-Image Line Step.

oSrcROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.63.1.4 NppStatus nppiTranspose_16u_C1R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSrcROI)

1 channel 16-bit unsigned int image transpose.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Pointer to the destination ROI.

nDstStep Destination-Image Line Step.

oSrcROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.63.1.5 NppStatus nppiTranspose_16u_C3R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSrcROI)

3 channel 16-bit unsigned int image transpose.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Pointer to the destination ROI.
nDstStep Destination-Image Line Step.
oSrcROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.63.1.6 NppStatus nppiTranspose_16u_C4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSrcROI)

4 channel 16-bit unsigned int image transpose.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Pointer to the destination ROI.
nDstStep Destination-Image Line Step.
oSrcROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.63.1.7 NppStatus nppiTranspose_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSrcROI)

1 channel 32-bit floating point image transpose.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Pointer to the destination ROI.
nDstStep Destination-Image Line Step.
oSrcROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.63.1.8 NppStatus nppiTranspose_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSrcROI)

3 channel 32-bit floating point image transpose.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Pointer to the destination ROI.

nDstStep Destination-Image Line Step.

oSrcROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.63.1.9 `NppStatus nppiTranspose_32f_C4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSrcROI)`

4 channel 32-bit floating point image transpose.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Pointer to the destination ROI.

nDstStep Destination-Image Line Step.

oSrcROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.63.1.10 `NppStatus nppiTranspose_32s_C1R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSrcROI)`

1 channel 32-bit signed int image transpose.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Pointer to the destination ROI.

nDstStep Destination-Image Line Step.

oSrcROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.63.1.11 NppStatus nppiTranspose_32s_C3R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSrcROI)

3 channel 32-bit signed int image transpose.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Pointer to the destination ROI.
nDstStep Destination-Image Line Step.
oSrcROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.63.1.12 NppStatus nppiTranspose_32s_C4R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSrcROI)

4 channel 32-bit signed int image transpose.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Pointer to the destination ROI.
nDstStep Destination-Image Line Step.
oSrcROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.63.1.13 NppStatus nppiTranspose_8u_C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSrcROI)

1 channel 8-bit unsigned int image transpose.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Pointer to the destination ROI.
nDstStep Destination-Image Line Step.
oSrcROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.63.1.14 NppStatus nppiTranspose_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSrcROI)

3 channel 8-bit unsigned int image transpose.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Pointer to the destination ROI.
nDstStep Destination-Image Line Step.
oSrcROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.63.1.15 NppStatus nppiTranspose_8u_C4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSrcROI)

4 channel 8-bit unsigned int image transpose.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Pointer to the destination ROI.
nDstStep Destination-Image Line Step.
oSrcROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.64 Swap Channels

SwapChannels

Functions for swapping and duplicating channels in multiple channel images.

The methods support arbitrary permutations of the original channels, including replication and setting one or more channels to a constant value.

- `NppStatus nppiSwapChannels_8u_C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const int aDstOrder[3])
3 channel 8-bit unsigned integer source image to 3 channel destination image.
- `NppStatus nppiSwapChannels_8u_C3IR` (`Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const int aDstOrder[3])
3 channel 8-bit unsigned integer in place image.
- `NppStatus nppiSwapChannels_8u_C4C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const int aDstOrder[3])
4 channel 8-bit unsigned integer source image to 3 channel destination image.
- `NppStatus nppiSwapChannels_8u_C4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const int aDstOrder[4])
4 channel 8-bit unsigned integer source image to 4 channel destination image.
- `NppStatus nppiSwapChannels_8u_C4IR` (`Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const int aDstOrder[4])
4 channel 8-bit unsigned integer in place image.
- `NppStatus nppiSwapChannels_8u_C3C4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const int aDstOrder[4], const `Npp8u` nValue)
3 channel 8-bit unsigned integer source image to 4 channel destination image.
- `NppStatus nppiSwapChannels_8u_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const int aDstOrder[3])
4 channel 8-bit unsigned integer source image to 4 channel destination image with destination alpha channel unaffected.
- `NppStatus nppiSwapChannels_16u_C3R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const int aDstOrder[3])
3 channel 16-bit unsigned integer source image to 3 channel destination image.
- `NppStatus nppiSwapChannels_16u_C3IR` (`Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const int aDstOrder[3])
3 channel 16-bit unsigned integer in place image.
- `NppStatus nppiSwapChannels_16u_C4C3R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const int aDstOrder[3])
4 channel 16-bit unsigned integer source image to 3 channel destination image.
- `NppStatus nppiSwapChannels_16u_C4R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const int aDstOrder[4])

4 channel 16-bit unsigned integer source image to 4 channel destination image.

- `NppStatus nppiSwapChannels_16u_C4IR` (`Npp16u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const int aDstOrder[4]`)

4 channel 16-bit unsigned integer in place image.

- `NppStatus nppiSwapChannels_16u_C3C4R` (`const Npp16u *pSrc`, `int nSrcStep`, `Npp16u *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const int aDstOrder[4]`, `const Npp16u nValue`)

3 channel 16-bit unsigned integer source image to 4 channel destination image.

- `NppStatus nppiSwapChannels_16u_AC4R` (`const Npp16u *pSrc`, `int nSrcStep`, `Npp16u *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const int aDstOrder[3]`)

4 channel 16-bit unsigned integer source image to 4 channel destination image with destination alpha channel unaffected.

- `NppStatus nppiSwapChannels_16s_C3R` (`const Npp16s *pSrc`, `int nSrcStep`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const int aDstOrder[3]`)

3 channel 16-bit signed integer source image to 3 channel destination image.

- `NppStatus nppiSwapChannels_16s_C3IR` (`Npp16s *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const int aDstOrder[3]`)

3 channel 16-bit signed integer in place image.

- `NppStatus nppiSwapChannels_16s_C4C3R` (`const Npp16s *pSrc`, `int nSrcStep`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const int aDstOrder[3]`)

4 channel 16-bit signed integer source image to 3 channel destination image.

- `NppStatus nppiSwapChannels_16s_C4R` (`const Npp16s *pSrc`, `int nSrcStep`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const int aDstOrder[4]`)

4 channel 16-bit signed integer source image to 4 channel destination image.

- `NppStatus nppiSwapChannels_16s_C4IR` (`Npp16s *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const int aDstOrder[4]`)

4 channel 16-bit signed integer in place image.

- `NppStatus nppiSwapChannels_16s_C3C4R` (`const Npp16s *pSrc`, `int nSrcStep`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const int aDstOrder[4]`, `const Npp16s nValue`)

3 channel 16-bit signed integer source image to 4 channel destination image.

- `NppStatus nppiSwapChannels_16s_AC4R` (`const Npp16s *pSrc`, `int nSrcStep`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const int aDstOrder[3]`)

4 channel 16-bit signed integer source image to 4 channel destination image with destination alpha channel unaffected.

- `NppStatus nppiSwapChannels_32s_C3R` (`const Npp32s *pSrc`, `int nSrcStep`, `Npp32s *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const int aDstOrder[3]`)

3 channel 32-bit signed integer source image to 3 channel destination image.

- `NppStatus nppiSwapChannels_32s_C3IR` (`Npp32s *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const int aDstOrder[3]`)

3 channel 32-bit signed integer in place image.

- [NppStatus nppiSwapChannels_32s_C4C3R](#) (const [Npp32s](#) *pSrc, int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const int aDstOrder[3])
4 channel 32-bit signed integer source image to 3 channel destination image.
- [NppStatus nppiSwapChannels_32s_C4R](#) (const [Npp32s](#) *pSrc, int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const int aDstOrder[4])
4 channel 32-bit signed integer source image to 4 channel destination image.
- [NppStatus nppiSwapChannels_32s_C4IR](#) ([Npp32s](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI, const int aDstOrder[4])
4 channel 32-bit signed integer in place image.
- [NppStatus nppiSwapChannels_32s_C3C4R](#) (const [Npp32s](#) *pSrc, int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const int aDstOrder[4], const [Npp32s](#) nValue)
3 channel 32-bit signed integer source image to 4 channel destination image.
- [NppStatus nppiSwapChannels_32s_AC4R](#) (const [Npp32s](#) *pSrc, int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const int aDstOrder[3])
4 channel 32-bit signed integer source image to 4 channel destination image with destination alpha channel unaffected.
- [NppStatus nppiSwapChannels_32f_C3R](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const int aDstOrder[3])
3 channel 32-bit floating point source image to 3 channel destination image.
- [NppStatus nppiSwapChannels_32f_C3IR](#) ([Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI, const int aDstOrder[3])
3 channel 32-bit floating point in place image.
- [NppStatus nppiSwapChannels_32f_C4C3R](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const int aDstOrder[3])
4 channel 32-bit floating point source image to 3 channel destination image.
- [NppStatus nppiSwapChannels_32f_C4R](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const int aDstOrder[4])
4 channel 32-bit floating point source image to 4 channel destination image.
- [NppStatus nppiSwapChannels_32f_C4IR](#) ([Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI, const int aDstOrder[4])
4 channel 32-bit floating point in place image.
- [NppStatus nppiSwapChannels_32f_C3C4R](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const int aDstOrder[4], const [Npp32f](#) nValue)
3 channel 32-bit floating point source image to 4 channel destination image.
- [NppStatus nppiSwapChannels_32f_AC4R](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const int aDstOrder[3])
4 channel 32-bit floating point source image to 4 channel destination image with destination alpha channel unaffected.

7.64.1 Function Documentation

7.64.1.1 `NppStatus nppiSwapChannels_16s_AC4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const int aDstOrder[3])`

4 channel 16-bit signed integer source image to 4 channel destination image with destination alpha channel unaffected.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGBA image, `aDstOrder = [2,1,0]` converts this to BGRA channel order. In the AC4R case, the alpha channel is always assumed to be channel 3.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.2 `NppStatus nppiSwapChannels_16s_C3C4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const int aDstOrder[4], const Npp16s nValue)`

3 channel 16-bit signed integer source image to 4 channel destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGB image, `aDstOrder = [3,2,1,0]` converts this to VBGR channel order.

nValue (V) Single channel constant value that can be replicated in one or more of the 4 destination channels. `nValue` is either written or not written to a particular channel depending on the `aDstOrder` entry for that destination channel. An `aDstOrder` value of 3 will output `nValue` to that channel, an `aDstOrder` value greater than 3 will leave that particular destination channel value unmodified.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.3 NppStatus nppiSwapChannels_16s_C3IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const int aDstOrder[3])

3 channel 16-bit signed integer in place image.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGB image, aDstOrder = [2,1,0] converts this to BGR channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.4 NppStatus nppiSwapChannels_16s_C3R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const int aDstOrder[3])

3 channel 16-bit signed integer source image to 3 channel destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGB image, aDstOrder = [2,1,0] converts this to BGR channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.5 NppStatus nppiSwapChannels_16s_C4C3R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const int aDstOrder[3])

4 channel 16-bit signed integer source image to 3 channel destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI [Region-of-Interest \(ROI\)](#).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGBA image, *aDstOrder* = [2,1,0] converts this to a 3 channel BGR channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.6 NppStatus nppiSwapChannels_16s_C4IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const int aDstOrder[4])

4 channel 16-bit signed integer in place image.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an ARGB image, *aDstOrder* = [3,2,1,0] converts this to BGRA channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.7 NppStatus nppiSwapChannels_16s_C4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const int aDstOrder[4])

4 channel 16-bit signed integer source image to 4 channel destination image.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an ARGB image, *aDstOrder* = [3,2,1,0] converts this to BGRA channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.8 `NppStatus nppiSwapChannels_16u_AC4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const int aDstOrder[3])`

4 channel 16-bit unsigned integer source image to 4 channel destination image with destination alpha channel unaffected.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGBA image, `aDstOrder = [2,1,0]` converts this to BGRA channel order. In the AC4R case, the alpha channel is always assumed to be channel 3.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.9 `NppStatus nppiSwapChannels_16u_C3C4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const int aDstOrder[4], const Npp16u nValue)`

3 channel 16-bit unsigned integer source image to 4 channel destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGB image, `aDstOrder = [3,2,1,0]` converts this to VBGR channel order.

nValue (V) Single channel constant value that can be replicated in one or more of the 4 destination channels. `nValue` is either written or not written to a particular channel depending on the `aDstOrder` entry for that destination channel. An `aDstOrder` value of 3 will output `nValue` to that channel, an `aDstOrder` value greater than 3 will leave that particular destination channel value unmodified.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.10 NppStatus nppiSwapChannels_16u_C3IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const int aDstOrder[3])

3 channel 16-bit unsigned integer in place image.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGB image, aDstOrder = [2,1,0] converts this to BGR channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.11 NppStatus nppiSwapChannels_16u_C3R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const int aDstOrder[3])

3 channel 16-bit unsigned integer source image to 3 channel destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGB image, aDstOrder = [2,1,0] converts this to BGR channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.12 NppStatus nppiSwapChannels_16u_C4C3R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const int aDstOrder[3])

4 channel 16-bit unsigned integer source image to 3 channel destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI [Region-of-Interest \(ROI\)](#).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGBA image, *aDstOrder* = [2,1,0] converts this to a 3 channel BGR channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.13 `NppStatus nppiSwapChannels_16u_C4IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const int aDstOrder[4])`

4 channel 16-bit unsigned integer in place image.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an ARGB image, *aDstOrder* = [3,2,1,0] converts this to BGRA channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.14 `NppStatus nppiSwapChannels_16u_C4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const int aDstOrder[4])`

4 channel 16-bit unsigned integer source image to 4 channel destination image.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an ARGB image, *aDstOrder* = [3,2,1,0] converts this to BGRA channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.15 NppStatus nppiSwapChannels_32f_AC4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const int aDstOrder[3])

4 channel 32-bit floating point source image to 4 channel destination image with destination alpha channel unaffected.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGBA image, *aDstOrder* = [2,1,0] converts this to BGRA channel order. In the AC4R case, the alpha channel is always assumed to be channel 3.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.16 NppStatus nppiSwapChannels_32f_C3C4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const int aDstOrder[4], const Npp32f nValue)

3 channel 32-bit floating point source image to 4 channel destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGB image, *aDstOrder* = [3,2,1,0] converts this to VBGR channel order.

nValue (V) Single channel constant value that can be replicated in one or more of the 4 destination channels. *nValue* is either written or not written to a particular channel depending on the *aDstOrder* entry for that destination channel. An *aDstOrder* value of 3 will output *nValue* to that channel, an *aDstOrder* value greater than 3 will leave that particular destination channel value unmodified.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.17 NppStatus nppiSwapChannels_32f_C3IR (Npp32f * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, const int *aDstOrder*[3])

3 channel 32-bit floating point in place image.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI oSizeROI Region-of-Interest (ROI).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGB image, *aDstOrder* = [2,1,0] converts this to BGR channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.18 NppStatus nppiSwapChannels_32f_C3R (const Npp32f * *pSrc*, int *nSrcStep*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, const int *aDstOrder*[3])

3 channel 32-bit floating point source image to 3 channel destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGB image, *aDstOrder* = [2,1,0] converts this to BGR channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.19 NppStatus nppiSwapChannels_32f_C4C3R (const Npp32f * *pSrc*, int *nSrcStep*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, const int *aDstOrder*[3])

4 channel 32-bit floating point source image to 3 channel destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI [Region-of-Interest \(ROI\)](#).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGBA image, *aDstOrder* = [2,1,0] converts this to a 3 channel BGR channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.20 `NppStatus nppiSwapChannels_32f_C4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const int aDstOrder[4])`

4 channel 32-bit floating point in place image.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an ARGB image, *aDstOrder* = [3,2,1,0] converts this to BGRA channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.21 `NppStatus nppiSwapChannels_32f_C4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const int aDstOrder[4])`

4 channel 32-bit floating point source image to 4 channel destination image.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an ARGB image, *aDstOrder* = [3,2,1,0] converts this to BGRA channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.22 `NppStatus nppiSwapChannels_32s_AC4R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, const int aDstOrder[3])`

4 channel 32-bit signed integer source image to 4 channel destination image with destination alpha channel unaffected.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGBA image, `aDstOrder = [2,1,0]` converts this to BGRA channel order. In the AC4R case, the alpha channel is always assumed to be channel 3.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.23 `NppStatus nppiSwapChannels_32s_C3C4R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, const int aDstOrder[4], const Npp32s nValue)`

3 channel 32-bit signed integer source image to 4 channel destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGB image, `aDstOrder = [3,2,1,0]` converts this to VBGR channel order.

nValue (V) Single channel constant value that can be replicated in one or more of the 4 destination channels. `nValue` is either written or not written to a particular channel depending on the `aDstOrder` entry for that destination channel. An `aDstOrder` value of 3 will output `nValue` to that channel, an `aDstOrder` value greater than 3 will leave that particular destination channel value unmodified.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.24 NppStatus nppiSwapChannels_32s_C3IR (Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const int aDstOrder[3])

3 channel 32-bit signed integer in place image.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGB image, aDstOrder = [2,1,0] converts this to BGR channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.25 NppStatus nppiSwapChannels_32s_C3R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, const int aDstOrder[3])

3 channel 32-bit signed integer source image to 3 channel destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGB image, aDstOrder = [2,1,0] converts this to BGR channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.26 NppStatus nppiSwapChannels_32s_C4C3R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, const int aDstOrder[3])

4 channel 32-bit signed integer source image to 3 channel destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI [Region-of-Interest \(ROI\)](#).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGBA image, *aDstOrder* = [2,1,0] converts this to a 3 channel BGR channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.27 NppStatus nppiSwapChannels_32s_C4IR (Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const int aDstOrder[4])

4 channel 32-bit signed integer in place image.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an ARGB image, *aDstOrder* = [3,2,1,0] converts this to BGRA channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.28 NppStatus nppiSwapChannels_32s_C4R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, const int aDstOrder[4])

4 channel 32-bit signed integer source image to 4 channel destination image.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an ARGB image, *aDstOrder* = [3,2,1,0] converts this to BGRA channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.29 NppStatus nppiSwapChannels_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const int aDstOrder[3])

4 channel 8-bit unsigned integer source image to 4 channel destination image with destination alpha channel unaffected.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGB image, *aDstOrder* = [3,2,1,0] converts this to VBGR channel order. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGBA image, *aDstOrder* = [2,1,0] converts this to BGRA channel order. In the AC4R case, the alpha channel is always assumed to be channel 3.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.30 NppStatus nppiSwapChannels_8u_C3C4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const int aDstOrder[4], const Npp8u nValue)

3 channel 8-bit unsigned integer source image to 4 channel destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGB image, *aDstOrder* = [3,2,1,0] converts this to VBGR channel order.

nValue (V) Single channel constant value that can be replicated in one or more of the 4 destination channels. *nValue* is either written or not written to a particular channel depending on the *aDstOrder* entry for that destination channel. An *aDstOrder* value of 3 will output *nValue* to that channel, an *aDstOrder* value greater than 3 will leave that particular destination channel value unmodified.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.31 `NppStatus nppiSwapChannels_8u_C3IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const int aDstOrder[3])`

3 channel 8-bit unsigned integer in place image.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGB image, *aDstOrder* = [2,1,0] converts this to BGR channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.32 `NppStatus nppiSwapChannels_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const int aDstOrder[3])`

3 channel 8-bit unsigned integer source image to 3 channel destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGB image, *aDstOrder* = [2,1,0] converts this to BGR channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.33 `NppStatus nppiSwapChannels_8u_C4C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const int aDstOrder[3])`

4 channel 8-bit unsigned integer source image to 3 channel destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI [Region-of-Interest \(ROI\)](#).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGBA image, *aDstOrder* = [2,1,0] converts this to a 3 channel BGR channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.34 `NppStatus nppiSwapChannels_8u_C4IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const int aDstOrder[4])`

4 channel 8-bit unsigned integer in place image.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an ARGB image, *aDstOrder* = [3,2,1,0] converts this to BGRA channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.64.1.35 `NppStatus nppiSwapChannels_8u_C4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const int aDstOrder[4])`

4 channel 8-bit unsigned integer source image to 4 channel destination image.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aDstOrder Host memory integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an ARGB image, *aDstOrder* = [3,2,1,0] converts this to BGRA channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.65 Filtering Functions

Linear and non-linear image filtering functions.

Modules

- [1D Linear Filter](#)

7.65.1 Detailed Description

Linear and non-linear image filtering functions.

Filtering functions are classified as [Neighborhood Operations](#). It is the user's responsibility to avoid [Sampling Beyond Image Boundaries](#).

7.66 1D Linear Filter

Modules

- [1D Window Sum](#)
- [Convolution](#)
- [2D Fixed Linear Filters](#)
- [Rank Filters](#)
- [Fixed Filters](#)

Fixed filters perform linear filtering operations (i.e.

FilterColumn

Apply convolution filter with user specified 1D column of weights.

Result pixel is equal to the sum of the products between the kernel coefficients (pKernel array) and corresponding neighboring column pixel values in the source image defined by nKernelDim and nAnchorY, divided by nDivisor.

- `NppStatus nppiFilterColumn_8u_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32s *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)

8-bit unsigned single-channel 1D column convolution.

- `NppStatus nppiFilterColumn_8u_C3R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32s *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)

8-bit unsigned three-channel 1D column convolution.

- `NppStatus nppiFilterColumn_8u_C4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32s *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)

8-bit unsigned four-channel 1D column convolution.

- `NppStatus nppiFilterColumn_8u_AC4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32s *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)

8-bit unsigned four-channel 1D column convolution ignoring alpha-channel.

- `NppStatus nppiFilterColumn_16u_C1R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32s *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)

16-bit unsigned single-channel 1D column convolution.

- `NppStatus nppiFilterColumn_16u_C3R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32s *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)

16-bit unsigned three-channel 1D column convolution.

- `NppStatus nppiFilterColumn_16u_C4R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32s *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)
16-bit unsigned four-channel 1D column convolution.
- `NppStatus nppiFilterColumn_16u_AC4R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32s *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)
16-bit unsigned four-channel 1D column convolution ignoring alpha-channel.
- `NppStatus nppiFilterColumn_16s_C1R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32s *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)
16-bit single-channel 1D column convolution.
- `NppStatus nppiFilterColumn_16s_C3R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32s *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)
16-bit three-channel 1D column convolution.
- `NppStatus nppiFilterColumn_16s_C4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32s *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)
16-bit four-channel 1D column convolution.
- `NppStatus nppiFilterColumn_16s_AC4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32s *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)
16-bit four-channel 1D column convolution ignoring alpha-channel.
- `NppStatus nppiFilterColumn_32f_C1R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)
32-bit float single-channel 1D column convolution.
- `NppStatus nppiFilterColumn_32f_C3R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)
32-bit float three-channel 1D column convolution.
- `NppStatus nppiFilterColumn_32f_C4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)
32-bit float four-channel 1D column convolution.
- `NppStatus nppiFilterColumn_32f_AC4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)
32-bit float four-channel 1D column convolution ignoring alpha-channel.
- `NppStatus nppiFilterColumn_64f_C1R` (const `Npp64f *pSrc`, `Npp32s nSrcStep`, `Npp64f *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp64f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)
64-bit float single-channel 1D column convolution.

FilterColumn32f

FilterColumn using floating-point weights.

- `NppStatus nppiFilterColumn32f_8u_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)
8-bit unsigned single-channel 1D column convolution.
- `NppStatus nppiFilterColumn32f_8u_C3R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)
8-bit unsigned three-channel 1D column convolution.
- `NppStatus nppiFilterColumn32f_8u_C4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)
8-bit unsigned four-channel 1D column convolution.
- `NppStatus nppiFilterColumn32f_8u_AC4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)
8-bit unsigned four-channel 1D column convolution ignoring alpha-channel.
- `NppStatus nppiFilterColumn32f_16u_C1R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)
16-bit unsigned single-channel 1D column convolution.
- `NppStatus nppiFilterColumn32f_16u_C3R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)
16-bit unsigned three-channel 1D column convolution.
- `NppStatus nppiFilterColumn32f_16u_C4R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)
16-bit unsigned four-channel 1D column convolution.
- `NppStatus nppiFilterColumn32f_16u_AC4R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)
16-bit unsigned four-channel 1D column convolution ignoring alpha-channel.
- `NppStatus nppiFilterColumn32f_16s_C1R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)
16-bit single-channel 1D column convolution.
- `NppStatus nppiFilterColumn32f_16s_C3R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)
16-bit three-channel 1D column convolution.
- `NppStatus nppiFilterColumn32f_16s_C4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)
16-bit four-channel 1D column convolution.
- `NppStatus nppiFilterColumn32f_16s_AC4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)
16-bit four-channel 1D column convolution ignoring alpha-channel.

16-bit four-channel 1D column convolution ignoring alpha-channel.

FilterRow

Apply convolution filter with user specified 1D row of weights.

Result pixel is equal to the sum of the products between the kernel coefficients (pKernel array) and corresponding neighboring row pixel values in the source image defined by nKernelDim and nAnchorX, divided by nDivisor.

- `NppStatus nppiFilterRow_8u_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32s *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)
8-bit unsigned single-channel 1D row convolution.
- `NppStatus nppiFilterRow_8u_C3R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32s *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)
8-bit unsigned three-channel 1D row convolution.
- `NppStatus nppiFilterRow_8u_C4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32s *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)
8-bit unsigned four-channel 1D row convolution.
- `NppStatus nppiFilterRow_8u_AC4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32s *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)
8-bit unsigned four-channel 1D row convolution ignoring alpha-channel.
- `NppStatus nppiFilterRow_16u_C1R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32s *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)
16-bit unsigned single-channel 1D row convolution.
- `NppStatus nppiFilterRow_16u_C3R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32s *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)
16-bit unsigned three-channel 1D row convolution.
- `NppStatus nppiFilterRow_16u_C4R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32s *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)
16-bit unsigned four-channel 1D row convolution.
- `NppStatus nppiFilterRow_16u_AC4R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32s *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)
16-bit unsigned four-channel 1D row convolution ignoring alpha-channel.

- `NppStatus nppiFilterRow_16s_C1R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32s *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)
16-bit single-channel 1D row convolution.
- `NppStatus nppiFilterRow_16s_C3R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32s *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)
16-bit three-channel 1D row convolution.
- `NppStatus nppiFilterRow_16s_C4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32s *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)
16-bit four-channel 1D row convolution.
- `NppStatus nppiFilterRow_16s_AC4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32s *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)
16-bit four-channel 1D row convolution ignoring alpha-channel.
- `NppStatus nppiFilterRow_32f_C1R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)
32-bit float single-channel 1D row convolution.
- `NppStatus nppiFilterRow_32f_C3R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)
32-bit float three-channel 1D row convolution.
- `NppStatus nppiFilterRow_32f_C4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)
32-bit float four-channel 1D row convolution.
- `NppStatus nppiFilterRow_32f_AC4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)
32-bit float four-channel 1D row convolution ignoring alpha-channel.
- `NppStatus nppiFilterRow_64f_C1R` (const `Npp64f *pSrc`, `Npp32s nSrcStep`, `Npp64f *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp64f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)
64-bit float single-channel 1D row convolution.

FilterRow32f

FilterRow using floating-point weights.

- `NppStatus nppiFilterRow32f_8u_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)
8-bit unsigned single-channel 1D row convolution.
- `NppStatus nppiFilterRow32f_8u_C3R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)

8-bit unsigned three-channel 1D row convolution.

- `NppStatus nppiFilterRow32f_8u_C4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)

8-bit unsigned four-channel 1D row convolution.

- `NppStatus nppiFilterRow32f_8u_AC4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)

8-bit unsigned four-channel 1D row convolution ignoring alpha-channel.

- `NppStatus nppiFilterRow32f_16u_C1R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)

16-bit unsigned single-channel 1D row convolution.

- `NppStatus nppiFilterRow32f_16u_C3R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)

16-bit unsigned three-channel 1D row convolution.

- `NppStatus nppiFilterRow32f_16u_C4R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)

16-bit unsigned four-channel 1D row convolution.

- `NppStatus nppiFilterRow32f_16u_AC4R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)

16-bit unsigned four-channel 1D row convolution ignoring alpha-channel.

- `NppStatus nppiFilterRow32f_16s_C1R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)

16-bit single-channel 1D row convolution.

- `NppStatus nppiFilterRow32f_16s_C3R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)

16-bit three-channel 1D row convolution.

- `NppStatus nppiFilterRow32f_16s_C4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)

16-bit four-channel 1D row convolution.

- `NppStatus nppiFilterRow32f_16s_AC4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)

16-bit four-channel 1D row convolution ignoring alpha-channel.

FilterSobelVertSecond

Filters the image using a second derivative, vertical Sobel filter kernel:

$$\begin{pmatrix} 1 & -2 & 1 \\ 2 & -4 & 2 \\ 1 & -2 & 1 \end{pmatrix} \begin{pmatrix} 1 & 0 & -2 & 0 & 1 \\ 4 & 0 & -8 & 0 & 4 \\ 6 & 0 & -12 & 0 & 6 \\ 4 & 0 & -8 & 0 & 4 \\ 1 & 0 & -2 & 0 & 1 \end{pmatrix}$$

- `NppStatus nppiFilterSobelVertSecond_8u16s_C1R` (const `Npp8u` *pSrc, `Npp32s` nSrcStep, `Npp16s` *pDst, `Npp32s` nDstStep, `NppiSize` oSizeROI, `NppiMaskSize` eMaskSize)
Single channel 8-bit unsigned to 16-bit signed second derivative, vertical Sobel filter.
- `NppStatus nppiFilterSobelVertSecond_8s16s_C1R` (const `Npp8s` *pSrc, `Npp32s` nSrcStep, `Npp16s` *pDst, `Npp32s` nDstStep, `NppiSize` oSizeROI, `NppiMaskSize` eMaskSize)
Single channel 8-bit signed to 16-bit signed second derivative, vertical Sobel filter.
- `NppStatus nppiFilterSobelVertSecond_32f_C1R` (const `Npp32f` *pSrc, `Npp32s` nSrcStep, `Npp32f` *pDst, `Npp32s` nDstStep, `NppiSize` oSizeROI, `NppiMaskSize` eMaskSize)
Single channel 32-bit floating-point second derivative, vertical Sobel filter.

FilterSobelCross

Filters the image using a second cross derivative Sobel filter kernel:

$$\begin{pmatrix} -1 & 0 & 1 \\ 0 & 0 & 0 \\ 1 & 0 & -1 \end{pmatrix} \begin{pmatrix} -1 & -2 & 0 & 2 & 1 \\ -2 & -4 & 0 & 4 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 2 & 4 & 0 & -4 & -2 \\ 1 & 2 & 0 & -2 & -1 \end{pmatrix}$$

- `NppStatus nppiFilterSobelCross_8u16s_C1R` (const `Npp8u` *pSrc, `Npp32s` nSrcStep, `Npp16s` *pDst, `Npp32s` nDstStep, `NppiSize` oSizeROI, `NppiMaskSize` eMaskSize)
Single channel 8-bit unsigned to 16-bit signed second cross derivative Sobel filter.
- `NppStatus nppiFilterSobelCross_8s16s_C1R` (const `Npp8s` *pSrc, `Npp32s` nSrcStep, `Npp16s` *pDst, `Npp32s` nDstStep, `NppiSize` oSizeROI, `NppiMaskSize` eMaskSize)
Single channel 8-bit signed to 16-bit signed second cross derivative Sobel filter.
- `NppStatus nppiFilterSobelCross_32f_C1R` (const `Npp32f` *pSrc, `Npp32s` nSrcStep, `Npp32f` *pDst, `Npp32s` nDstStep, `NppiSize` oSizeROI, `NppiMaskSize` eMaskSize)
Single channel 32-bit floating-point second cross derivative Sobel filter.

FilterRobertsDown

Filters the image using a horizontal Roberts filter kernel:

$$\begin{pmatrix} 0 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & -1 \end{pmatrix}$$

- `NppStatus nppiFilterRobertsDown_8u_C1R` (const `Npp8u` *pSrc, `Npp32s` nSrcStep, `Npp8u` *pDst, `Npp32s` nDstStep, `NppiSize` oSizeROI)
Single channel 8-bit unsigned horizontal Roberts filter.
- `NppStatus nppiFilterRobertsDown_8u_C3R` (const `Npp8u` *pSrc, `Npp32s` nSrcStep, `Npp8u` *pDst, `Npp32s` nDstStep, `NppiSize` oSizeROI)

Three channel 8-bit unsigned horizontal Roberts filter.

- `NppStatus nppiFilterRobertsDown_8u_C4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Four channel 8-bit unsigned horizontal Roberts filter.

- `NppStatus nppiFilterRobertsDown_8u_AC4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Four channel 8-bit unsigned horizontal Roberts filter, ignoring alpha-channel.

- `NppStatus nppiFilterRobertsDown_16s_C1R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Single channel 16-bit signed horizontal Roberts filter.

- `NppStatus nppiFilterRobertsDown_16s_C3R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Three channel 16-bit signed horizontal Roberts filter.

- `NppStatus nppiFilterRobertsDown_16s_C4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Four channel 16-bit signed horizontal Roberts filter.

- `NppStatus nppiFilterRobertsDown_16s_AC4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Four channel 16-bit signed horizontal Roberts filter, ignoring alpha-channel.

- `NppStatus nppiFilterRobertsDown_32f_C1R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Single channel 32-bit floating-point horizontal Roberts filter.

- `NppStatus nppiFilterRobertsDown_32f_C3R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Three channel 32-bit floating-point horizontal Roberts filter.

- `NppStatus nppiFilterRobertsDown_32f_C4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Four channel 32-bit floating-point horizontal Roberts filter.

- `NppStatus nppiFilterRobertsDown_32f_AC4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Four channel 32-bit floating-point horizontal Roberts filter, ignoring alpha-channel.

FilterRobertsUp

Filters the image using a vertical Roberts filter kernel:

$$\begin{pmatrix} 0 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & -1 \end{pmatrix}$$

- `NppStatus nppiFilterRobertsUp_8u_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Single channel 8-bit unsigned vertical Roberts filter.
- `NppStatus nppiFilterRobertsUp_8u_C3R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Three channel 8-bit unsigned vertical Roberts filter.
- `NppStatus nppiFilterRobertsUp_8u_C4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Four channel 8-bit unsigned vertical Roberts filter.
- `NppStatus nppiFilterRobertsUp_8u_AC4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Four channel 8-bit unsigned vertical Roberts filter, ignoring alpha-channel.
- `NppStatus nppiFilterRobertsUp_16s_C1R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Single channel 16-bit signed vertical Roberts filter.
- `NppStatus nppiFilterRobertsUp_16s_C3R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Three channel 16-bit signed vertical Roberts filter.
- `NppStatus nppiFilterRobertsUp_16s_C4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Four channel 16-bit signed vertical Roberts filter.
- `NppStatus nppiFilterRobertsUp_16s_AC4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Four channel 16-bit signed vertical Roberts filter, ignoring alpha-channel.
- `NppStatus nppiFilterRobertsUp_32f_C1R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Single channel 32-bit floating-point vertical Roberts filter.
- `NppStatus nppiFilterRobertsUp_32f_C3R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Three channel 32-bit floating-point vertical Roberts filter.
- `NppStatus nppiFilterRobertsUp_32f_C4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Four channel 32-bit floating-point vertical Roberts filter.
- `NppStatus nppiFilterRobertsUp_32f_AC4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Four channel 32-bit floating-point vertical Roberts filter, ignoring alpha-channel.

FilterLaplace

Filters the image using a Laplacian filter kernel:

$$\begin{pmatrix} -1 & -1 & -1 \\ -1 & 8 & -1 \\ -1 & -1 & -1 \end{pmatrix} \begin{pmatrix} -1 & -3 & -4 & -3 & -1 \\ -3 & 0 & 6 & 0 & -3 \\ -4 & 6 & 20 & 6 & -4 \\ -3 & 0 & 6 & 0 & -3 \\ -1 & -3 & -4 & -3 & -1 \end{pmatrix}$$

- `NppStatus nppiFilterLaplace_8u_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Single channel 8-bit unsigned Laplace filter.
- `NppStatus nppiFilterLaplace_8u_C3R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Three channel 8-bit unsigned Laplace filter.
- `NppStatus nppiFilterLaplace_8u_C4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Four channel 8-bit unsigned Laplace filter.
- `NppStatus nppiFilterLaplace_8u_AC4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Four channel 8-bit unsigned Laplace filter, ignoring alpha channel.
- `NppStatus nppiFilterLaplace_16s_C1R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Single channel 16-bit signed Laplace filter.
- `NppStatus nppiFilterLaplace_16s_C3R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Three channel 16-bit signed Laplace filter.
- `NppStatus nppiFilterLaplace_16s_C4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Four channel 16-bit signed Laplace filter.
- `NppStatus nppiFilterLaplace_16s_AC4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Four channel 16-bit signed Laplace filter, ignoring alpha channel.
- `NppStatus nppiFilterLaplace_32f_C1R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Single channel 32-bit floating-point Laplace filter.
- `NppStatus nppiFilterLaplace_32f_C3R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Three channel 32-bit floating-point Laplace filter.

- `NppStatus nppiFilterLaplace_32f_C4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Four channel 32-bit floating-point Laplace filter.
- `NppStatus nppiFilterLaplace_32f_AC4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Four channel 32-bit floating-point Laplace filter, ignoring alpha channel.
- `NppStatus nppiFilterLaplace_8u16s_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Single channel 8-bit unsigned to 16-bit signed Laplace filter.
- `NppStatus nppiFilterLaplace_8s16s_C1R` (const `Npp8s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Single channel 8-bit signed to 16-bit signed Laplace filter.

FilterGauss

Filters the image using a Gaussian filter kernel:

$$\begin{pmatrix} 1/16 & 2/16 & 1/16 \\ 2/16 & 4/16 & 2/16 \\ 1/16 & 2/16 & 1/16 \end{pmatrix} \begin{pmatrix} 2/571 & 7/571 & 12/571 & 7/571 & 2/571 \\ 7/571 & 31/571 & 52/571 & 31/571 & 7/571 \\ 12/571 & 52/571 & 127/571 & 52/571 & 12/571 \\ 7/571 & 31/571 & 52/571 & 31/571 & 7/571 \\ 2/571 & 7/571 & 12/571 & 7/571 & 2/571 \end{pmatrix}$$

- `NppStatus nppiFilterGauss_8u_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Single channel 8-bit unsigned Gauss filter.
- `NppStatus nppiFilterGauss_8u_C3R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Three channel 8-bit unsigned Gauss filter.
- `NppStatus nppiFilterGauss_8u_C4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Four channel 8-bit unsigned Gauss filter.
- `NppStatus nppiFilterGauss_8u_AC4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Four channel 8-bit unsigned Gauss filter, ignoring alpha channel.
- `NppStatus nppiFilterGauss_16u_C1R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Single channel 16-bit unsigned Gauss filter.
- `NppStatus nppiFilterGauss_16u_C3R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Three channel 16-bit unsigned Gauss filter.

- `NppStatus nppiFilterGauss_16u_C4R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Four channel 16-bit unsigned Gauss filter.
- `NppStatus nppiFilterGauss_16u_AC4R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Four channel 16-bit unsigned Gauss filter, ignoring alpha channel.
- `NppStatus nppiFilterGauss_16s_C1R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Single channel 16-bit signed Gauss filter.
- `NppStatus nppiFilterGauss_16s_C3R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Three channel 16-bit signed Gauss filter.
- `NppStatus nppiFilterGauss_16s_C4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Four channel 16-bit signed Gauss filter.
- `NppStatus nppiFilterGauss_16s_AC4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Four channel 16-bit signed Gauss filter, ignoring alpha channel.
- `NppStatus nppiFilterGauss_32f_C1R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Single channel 32-bit floating-point Gauss filter.
- `NppStatus nppiFilterGauss_32f_C3R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Three channel 32-bit floating-point Gauss filter.
- `NppStatus nppiFilterGauss_32f_C4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Four channel 32-bit floating-point Gauss filter.
- `NppStatus nppiFilterGauss_32f_AC4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Four channel 32-bit floating-point Gauss filter, ignoring alpha channel.

FilterHighPass

Filters the image using a high-pass filter kernel:

$$\begin{pmatrix} -1 & -1 & -1 \\ -1 & 8 & -1 \\ -1 & -1 & -1 \end{pmatrix} \begin{pmatrix} -1 & -1 & -1 & -1 & -1 \\ -1 & -1 & -1 & -1 & -1 \\ -1 & -1 & 24 & -1 & -1 \\ -1 & -1 & -1 & -1 & -1 \\ -1 & -1 & -1 & -1 & -1 \end{pmatrix}$$

- `NppStatus nppiFilterHighPass_8u_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Single channel 8-bit unsigned high-pass filter.
- `NppStatus nppiFilterHighPass_8u_C3R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Three channel 8-bit unsigned high-pass filter.
- `NppStatus nppiFilterHighPass_8u_C4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Four channel 8-bit unsigned high-pass filter.
- `NppStatus nppiFilterHighPass_8u_AC4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Four channel 8-bit unsigned high-pass filter, ignoring alpha channel.
- `NppStatus nppiFilterHighPass_16u_C1R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Single channel 16-bit unsigned high-pass filter.
- `NppStatus nppiFilterHighPass_16u_C3R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Three channel 16-bit unsigned high-pass filter.
- `NppStatus nppiFilterHighPass_16u_C4R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Four channel 16-bit unsigned high-pass filter.
- `NppStatus nppiFilterHighPass_16u_AC4R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Four channel 16-bit unsigned high-pass filter, ignoring alpha channel.
- `NppStatus nppiFilterHighPass_16s_C1R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Single channel 16-bit signed high-pass filter.
- `NppStatus nppiFilterHighPass_16s_C3R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Three channel 16-bit signed high-pass filter.
- `NppStatus nppiFilterHighPass_16s_C4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Four channel 16-bit signed high-pass filter.
- `NppStatus nppiFilterHighPass_16s_AC4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Four channel 16-bit signed high-pass filter, ignoring alpha channel.
- `NppStatus nppiFilterHighPass_32f_C1R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Single channel 32-bit floating-point high-pass filter.

- `NppStatus nppiFilterHighPass_32f_C3R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Three channel 32-bit floating-point high-pass filter.
- `NppStatus nppiFilterHighPass_32f_C4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Four channel 32-bit floating-point high-pass filter.
- `NppStatus nppiFilterHighPass_32f_AC4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Four channel 32-bit floating-point high-pass filter, ignoring alpha channel.

FilterLowPass

Filters the image using a low-pass filter kernel:

$$\begin{pmatrix} 1/9 & 1/9 & 1/9 \\ 1/9 & 1/9 & 1/9 \\ 1/9 & 1/9 & 1/9 \end{pmatrix} \begin{pmatrix} 1/25 & 1/25 & 1/25 & 1/25 & 1/25 \\ 1/25 & 1/25 & 1/25 & 1/25 & 1/25 \\ 1/25 & 1/25 & 1/25 & 1/25 & 1/25 \\ 1/25 & 1/25 & 1/25 & 1/25 & 1/25 \\ 1/25 & 1/25 & 1/25 & 1/25 & 1/25 \end{pmatrix}$$

- `NppStatus nppiFilterLowPass_8u_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Single channel 8-bit unsigned low-pass filter.
- `NppStatus nppiFilterLowPass_8u_C3R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Three channel 8-bit unsigned low-pass filter.
- `NppStatus nppiFilterLowPass_8u_C4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Four channel 8-bit unsigned low-pass filter.
- `NppStatus nppiFilterLowPass_8u_AC4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Four channel 8-bit unsigned low-pass filter, ignoring alpha channel.
- `NppStatus nppiFilterLowPass_16u_C1R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Single channel 16-bit unsigned low-pass filter.
- `NppStatus nppiFilterLowPass_16u_C3R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)
Three channel 16-bit unsigned low-pass filter.
- `NppStatus nppiFilterLowPass_16u_C4R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)

Four channel 16-bit unsigned low-pass filter.

- `NppStatus nppiFilterLowPass_16u_AC4R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)

Four channel 16-bit unsigned low-pass filter, ignoring alpha channel.

- `NppStatus nppiFilterLowPass_16s_C1R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)

Single channel 16-bit signed low-pass filter.

- `NppStatus nppiFilterLowPass_16s_C3R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)

Three channel 16-bit signed low-pass filter.

- `NppStatus nppiFilterLowPass_16s_C4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)

Four channel 16-bit signed low-pass filter.

- `NppStatus nppiFilterLowPass_16s_AC4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)

Four channel 16-bit signed low-pass filter, ignoring alpha channel.

- `NppStatus nppiFilterLowPass_32f_C1R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)

Single channel 32-bit floating-point low-pass filter.

- `NppStatus nppiFilterLowPass_32f_C3R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)

Three channel 32-bit floating-point low-pass filter.

- `NppStatus nppiFilterLowPass_32f_C4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)

Four channel 32-bit floating-point low-pass filter.

- `NppStatus nppiFilterLowPass_32f_AC4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)

Four channel 32-bit floating-point high-pass filter, ignoring alpha channel.

FilterSharpen

Filters the image using a sharpening filter kernel:

$$\begin{pmatrix} -1/8 & -1/8 & -1/8 \\ -1/8 & 16/8 & -1/8 \\ -1/8 & -1/8 & -1/8 \end{pmatrix}$$

- `NppStatus nppiFilterSharpen_8u_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Single channel 8-bit unsigned sharpening filter.

- `NppStatus nppiFilterSharpen_8u_C3R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Three channel 8-bit unsigned sharpening filter.
- `NppStatus nppiFilterSharpen_8u_C4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Four channel 8-bit unsigned sharpening filter.
- `NppStatus nppiFilterSharpen_8u_AC4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Four channel 8-bit unsigned sharpening filter; ignoring alpha channel.
- `NppStatus nppiFilterSharpen_16u_C1R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Single channel 16-bit unsigned sharpening filter.
- `NppStatus nppiFilterSharpen_16u_C3R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Three channel 16-bit unsigned sharpening filter.
- `NppStatus nppiFilterSharpen_16u_C4R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Four channel 16-bit unsigned sharpening filter.
- `NppStatus nppiFilterSharpen_16u_AC4R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Four channel 16-bit unsigned sharpening filter; ignoring alpha channel.
- `NppStatus nppiFilterSharpen_16s_C1R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Single channel 16-bit signed sharpening filter.
- `NppStatus nppiFilterSharpen_16s_C3R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Three channel 16-bit signed sharpening filter.
- `NppStatus nppiFilterSharpen_16s_C4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Four channel 16-bit signed sharpening filter.
- `NppStatus nppiFilterSharpen_16s_AC4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Four channel 16-bit signed sharpening filter; ignoring alpha channel.
- `NppStatus nppiFilterSharpen_32f_C1R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Single channel 32-bit floating-point sharpening filter.
- `NppStatus nppiFilterSharpen_32f_C3R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Three channel 32-bit floating-point sharpening filter.

- `NppStatus nppiFilterSharpen_32f_C4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Four channel 32-bit floating-point sharpening filter.

- `NppStatus nppiFilterSharpen_32f_AC4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Four channel 32-bit floating-point sharpening filter, ignoring alpha channel.

7.66.1 Function Documentation

- 7.66.1.1 `NppStatus nppiFilterColumn32f_16s_AC4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)**

16-bit four-channel 1D column convolution ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- 7.66.1.2 `NppStatus nppiFilterColumn32f_16s_C1R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, const `Npp32f *pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)**

16-bit single-channel 1D column convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.3 NppStatus nppiFilterColumn32f_16s_C3R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)

16-bit three-channel 1D column convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.4 NppStatus nppiFilterColumn32f_16s_C4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)

16-bit four-channel 1D column convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.5 `NppStatus nppiFilterColumn32f_16u_AC4R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)`

16-bit unsigned four-channel 1D column convolution ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.6 `NppStatus nppiFilterColumn32f_16u_C1R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)`

16-bit unsigned single-channel 1D column convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.7 NppStatus nppiFilterColumn32f_16u_C3R (const Npp16u * *pSrc*, Npp32s *nSrcStep*, Npp16u * *pDst*, Npp32s *nDstStep*, NppiSize *oROI*, const Npp32f * *pKernel*, Npp32s *nMaskSize*, Npp32s *nAnchor*)

16-bit unsigned three-channel 1D column convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.8 NppStatus nppiFilterColumn32f_16u_C4R (const Npp16u * *pSrc*, Npp32s *nSrcStep*, Npp16u * *pDst*, Npp32s *nDstStep*, NppiSize *oROI*, const Npp32f * *pKernel*, Npp32s *nMaskSize*, Npp32s *nAnchor*)

16-bit unsigned four-channel 1D column convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.9 NppStatus nppiFilterColumn32f_8u_AC4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)

8-bit unsigned four-channel 1D column convolution ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.10 NppStatus nppiFilterColumn32f_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)

8-bit unsigned single-channel 1D column convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.11 NppStatus nppiFilterColumn32f_8u_C3R (const Npp8u * *pSrc*, Npp32s *nSrcStep*, Npp8u * *pDst*, Npp32s *nDstStep*, NppiSize *oROI*, const Npp32f * *pKernel*, Npp32s *nMaskSize*, Npp32s *nAnchor*)

8-bit unsigned three-channel 1D column convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.12 NppStatus nppiFilterColumn32f_8u_C4R (const Npp8u * *pSrc*, Npp32s *nSrcStep*, Npp8u * *pDst*, Npp32s *nDstStep*, NppiSize *oROI*, const Npp32f * *pKernel*, Npp32s *nMaskSize*, Npp32s *nAnchor*)

8-bit unsigned four-channel 1D column convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.13 NppStatus nppiFilterColumn_16s_AC4R (const Npp16s * *pSrc*, Npp32s *nSrcStep*, Npp16s * *pDst*, Npp32s *nDstStep*, NppiSize *oROI*, const Npp32s * *pKernel*, Npp32s *nMaskSize*, Npp32s *nAnchor*, Npp32s *nDivisor*)

16-bit four-channel 1D column convolution ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.14 NppStatus nppiFilterColumn_16s_C1R (const Npp16s * *pSrc*, Npp32s *nSrcStep*, Npp16s * *pDst*, Npp32s *nDstStep*, NppiSize *oROI*, const Npp32s * *pKernel*, Npp32s *nMaskSize*, Npp32s *nAnchor*, Npp32s *nDivisor*)

16-bit single-channel 1D column convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.15 NppStatus nppiFilterColumn_16s_C3R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32s * pKernel, Npp32s nMaskSize, Npp32s nAnchor, Npp32s nDivisor)

16-bit three-channel 1D column convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.16 NppStatus nppiFilterColumn_16s_C4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32s * pKernel, Npp32s nMaskSize, Npp32s nAnchor, Npp32s nDivisor)

16-bit four-channel 1D column convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.17 `NppStatus nppiFilterColumn_16u_AC4R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32s * pKernel, Npp32s nMaskSize, Npp32s nAnchor, Npp32s nDivisor)`

16-bit unsigned four-channel 1D column convolution ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.18 `NppStatus nppiFilterColumn_16u_C1R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32s * pKernel, Npp32s nMaskSize, Npp32s nAnchor, Npp32s nDivisor)`

16-bit unsigned single-channel 1D column convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.19 NppStatus nppiFilterColumn_16u_C3R (const Npp16u * *pSrc*, Npp32s *nSrcStep*, Npp16u * *pDst*, Npp32s *nDstStep*, NppiSize *oROI*, const Npp32s * *pKernel*, Npp32s *nMaskSize*, Npp32s *nAnchor*, Npp32s *nDivisor*)

16-bit unsigned three-channel 1D column convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.20 NppStatus nppiFilterColumn_16u_C4R (const Npp16u * *pSrc*, Npp32s *nSrcStep*, Npp16u * *pDst*, Npp32s *nDstStep*, NppiSize *oROI*, const Npp32s * *pKernel*, Npp32s *nMaskSize*, Npp32s *nAnchor*, Npp32s *nDivisor*)

16-bit unsigned four-channel 1D column convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.21 `NppStatus nppiFilterColumn_32f_AC4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)`

32-bit float four-channel 1D column convolution ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.22 `NppStatus nppiFilterColumn_32f_C1R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)`

32-bit float single-channel 1D column convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.23 `NppStatus nppiFilterColumn_32f_C3R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)`

32-bit float three-channel 1D column convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.24 `NppStatus nppiFilterColumn_32f_C4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)`

32-bit float four-channel 1D column convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.25 `NppStatus nppiFilterColumn_64f_C1R` (`const Npp64f * pSrc`, `Npp32s nSrcStep`, `Npp64f * pDst`, `Npp32s nDstStep`, `NppiSize oROI`, `const Npp64f * pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`)

64-bit float single-channel 1D column convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.26 `NppStatus nppiFilterColumn_8u_AC4R` (`const Npp8u * pSrc`, `Npp32s nSrcStep`, `Npp8u * pDst`, `Npp32s nDstStep`, `NppiSize oROI`, `const Npp32s * pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)

8-bit unsigned four-channel 1D column convolution ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.27 `NppStatus nppiFilterColumn_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32s * pKernel, Npp32s nMaskSize, Npp32s nAnchor, Npp32s nDivisor)`

8-bit unsigned single-channel 1D column convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.28 `NppStatus nppiFilterColumn_8u_C3R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32s * pKernel, Npp32s nMaskSize, Npp32s nAnchor, Npp32s nDivisor)`

8-bit unsigned three-channel 1D column convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.29 `NppStatus nppiFilterColumn_8u_C4R` (`const Npp8u * pSrc`, `Npp32s nSrcStep`, `Npp8u * pDst`, `Npp32s nDstStep`, `NppiSize oROI`, `const Npp32s * pKernel`, `Npp32s nMaskSize`, `Npp32s nAnchor`, `Npp32s nDivisor`)

8-bit unsigned four-channel 1D column convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.30 `NppStatus nppiFilterGauss_16s_AC4R` (`const Npp16s * pSrc`, `Npp32s nSrcStep`, `Npp16s * pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)

Four channel 16-bit signed Gauss filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eMaskSize Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.31 `NppStatus nppiFilterGauss_16s_C1R` (`const Npp16s * pSrc`, `Npp32s nSrcStep`, `Npp16s * pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)

Single channel 16-bit signed Gauss filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eMaskSize Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.32 `NppStatus nppiFilterGauss_16s_C3R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Three channel 16-bit signed Gauss filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eMaskSize Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.33 `NppStatus nppiFilterGauss_16s_C4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Four channel 16-bit signed Gauss filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eMaskSize Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.34 NppStatus nppiFilterGauss_16u_AC4R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)

Four channel 16-bit unsigned Gauss filter, ignoring alpha channel.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.35 NppStatus nppiFilterGauss_16u_C1R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)

Single channel 16-bit unsigned Gauss filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.36 NppStatus nppiFilterGauss_16u_C3R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)

Three channel 16-bit unsigned Gauss filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.37 `NppStatus nppiFilterGauss_16u_C4R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Four channel 16-bit unsigned Gauss filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.38 `NppStatus nppiFilterGauss_32f_AC4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Four channel 32-bit floating-point Gauss filter, ignoring alpha channel.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.39 `NppStatus nppiFilterGauss_32f_C1R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Single channel 32-bit floating-point Gauss filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.40 `NppStatus nppiFilterGauss_32f_C3R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Three channel 32-bit floating-point Gauss filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.41 `NppStatus nppiFilterGauss_32f_C4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Four channel 32-bit floating-point Gauss filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.42 `NppStatus nppiFilterGauss_8u_AC4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Four channel 8-bit unsigned Gauss filter, ignoring alpha channel.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.43 `NppStatus nppiFilterGauss_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Single channel 8-bit unsigned Gauss filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.44 `NppStatus nppiFilterGauss_8u_C3R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Three channel 8-bit unsigned Gauss filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.45 `NppStatus nppiFilterGauss_8u_C4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Four channel 8-bit unsigned Gauss filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.46 NppStatus nppiFilterHighPass_16s_AC4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)

Four channel 16-bit signed high-pass filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eMaskSize Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.47 NppStatus nppiFilterHighPass_16s_C1R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)

Single channel 16-bit signed high-pass filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eMaskSize Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.48 NppStatus nppiFilterHighPass_16s_C3R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)

Three channel 16-bit signed high-pass filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eMaskSize Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.49 NppStatus nppiFilterHighPass_16s_C4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)

Four channel 16-bit signed high-pass filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.50 NppStatus nppiFilterHighPass_16u_AC4R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)

Four channel 16-bit unsigned high-pass filter, ignoring alpha channel.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.51 NppStatus nppiFilterHighPass_16u_C1R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)

Single channel 16-bit unsigned high-pass filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.52 NppStatus nppiFilterHighPass_16u_C3R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)

Three channel 16-bit unsigned high-pass filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.53 NppStatus nppiFilterHighPass_16u_C4R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)

Four channel 16-bit unsigned high-pass filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.54 NppStatus nppiFilterHighPass_32f_AC4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)

Four channel 32-bit floating-point high-pass filter, ignoring alpha channel.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.55 NppStatus nppiFilterHighPass_32f_C1R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)

Single channel 32-bit floating-point high-pass filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.56 NppStatus nppiFilterHighPass_32f_C3R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)

Three channel 32-bit floating-point high-pass filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.57 NppStatus nppiFilterHighPass_32f_C4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)

Four channel 32-bit floating-point high-pass filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.58 `NppStatus nppiFilterHighPass_8u_AC4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Four channel 8-bit unsigned high-pass filter, ignoring alpha channel.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.59 `NppStatus nppiFilterHighPass_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Single channel 8-bit unsigned high-pass filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.60 `NppStatus nppiFilterHighPass_8u_C3R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Three channel 8-bit unsigned high-pass filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.61 `NppStatus nppiFilterHighPass_8u_C4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Four channel 8-bit unsigned high-pass filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.62 `NppStatus nppiFilterLaplace_16s_AC4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Four channel 16-bit signed Laplace filter, ignoring alpha channel.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.63 `NppStatus nppiFilterLaplace_16s_C1R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Single channel 16-bit signed Laplace filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.64 NppStatus nppiFilterLaplace_16s_C3R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)

Three channel 16-bit signed Laplace filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.65 NppStatus nppiFilterLaplace_16s_C4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)

Four channel 16-bit signed Laplace filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.66 NppStatus nppiFilterLaplace_32f_AC4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)

Four channel 32-bit floating-point Laplace filter, ignoring alpha channel.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.67 `NppStatus nppiFilterLaplace_32f_C1R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Single channel 32-bit floating-point Laplace filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eMaskSize Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.68 `NppStatus nppiFilterLaplace_32f_C3R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Three channel 32-bit floating-point Laplace filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eMaskSize Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.69 `NppStatus nppiFilterLaplace_32f_C4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Four channel 32-bit floating-point Laplace filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eMaskSize Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.70 `NppStatus nppiFilterLaplace_8s16s_C1R (const Npp8s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Single channel 8-bit signed to 16-bit signed Laplace filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.71 `NppStatus nppiFilterLaplace_8u16s_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Single channel 8-bit unsigned to 16-bit signed Laplace filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.72 `NppStatus nppiFilterLaplace_8u_AC4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Four channel 8-bit unsigned Laplace filter, ignoring alpha channel.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.73 `NppStatus nppiFilterLaplace_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Single channel 8-bit unsigned Laplace filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.74 `NppStatus nppiFilterLaplace_8u_C3R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Three channel 8-bit unsigned Laplace filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.75 `NppStatus nppiFilterLaplace_8u_C4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Four channel 8-bit unsigned Laplace filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.76 NppStatus nppiFilterLowPass_16s_AC4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)

Four channel 16-bit signed low-pass filter, ignoring alpha channel.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.77 NppStatus nppiFilterLowPass_16s_C1R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)

Single channel 16-bit signed low-pass filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.78 NppStatus nppiFilterLowPass_16s_C3R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)

Three channel 16-bit signed low-pass filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.79 NppStatus nppiFilterLowPass_16s_C4R (const Npp16s * *pSrc*, Npp32s *nSrcStep*, Npp16s * *pDst*, Npp32s *nDstStep*, NppiSize *oSizeROI*, NppiMaskSize *eMaskSize*)

Four channel 16-bit signed low-pass filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.80 NppStatus nppiFilterLowPass_16u_AC4R (const Npp16u * *pSrc*, Npp32s *nSrcStep*, Npp16u * *pDst*, Npp32s *nDstStep*, NppiSize *oSizeROI*, NppiMaskSize *eMaskSize*)

Four channel 16-bit unsigned low-pass filter, ignoring alpha channel.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.81 NppStatus nppiFilterLowPass_16u_C1R (const Npp16u * *pSrc*, Npp32s *nSrcStep*, Npp16u * *pDst*, Npp32s *nDstStep*, NppiSize *oSizeROI*, NppiMaskSize *eMaskSize*)

Single channel 16-bit unsigned low-pass filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.82 `NppStatus nppiFilterLowPass_16u_C3R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Three channel 16-bit unsigned low-pass filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.83 `NppStatus nppiFilterLowPass_16u_C4R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Four channel 16-bit unsigned low-pass filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.84 `NppStatus nppiFilterLowPass_32f_AC4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Four channel 32-bit floating-point high-pass filter, ignoring alpha channel.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.85 NppStatus nppiFilterLowPass_32f_C1R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)

Single channel 32-bit floating-point low-pass filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.86 NppStatus nppiFilterLowPass_32f_C3R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)

Three channel 32-bit floating-point low-pass filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.87 NppStatus nppiFilterLowPass_32f_C4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)

Four channel 32-bit floating-point low-pass filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.88 `NppStatus nppiFilterLowPass_8u_AC4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Four channel 8-bit unsigned low-pass filter, ignoring alpha channel.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.89 `NppStatus nppiFilterLowPass_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Single channel 8-bit unsigned low-pass filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.90 `NppStatus nppiFilterLowPass_8u_C3R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Three channel 8-bit unsigned low-pass filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.91 `NppStatus nppiFilterLowPass_8u_C4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Four channel 8-bit unsigned low-pass filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eMaskSize Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.92 `NppStatus nppiFilterRobertsDown_16s_AC4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)`

Four channel 16-bit signed horizontal Roberts filter, ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.93 `NppStatus nppiFilterRobertsDown_16s_C1R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)`

Single channel 16-bit signed horizontal Roberts filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.94 NppStatus nppiFilterRobertsDown_16s_C3R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Three channel 16-bit signed horizontal Roberts filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.66.1.95 NppStatus nppiFilterRobertsDown_16s_C4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 16-bit signed horizontal Roberts filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.66.1.96 NppStatus nppiFilterRobertsDown_32f_AC4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 32-bit floating-point horizontal Roberts filter, ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.66.1.97 NppStatus nppiFilterRobertsDown_32f_C1R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single channel 32-bit floating-point horizontal Roberts filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.98 NppStatus nppiFilterRobertsDown_32f_C3R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Three channel 32-bit floating-point horizontal Roberts filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.99 NppStatus nppiFilterRobertsDown_32f_C4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 32-bit floating-point horizontal Roberts filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.100 NppStatus nppiFilterRobertsDown_8u_AC4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 8-bit unsigned horizontal Roberts filter, ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.66.1.101 NppStatus nppiFilterRobertsDown_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single channel 8-bit unsigned horizontal Roberts filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.66.1.102 NppStatus nppiFilterRobertsDown_8u_C3R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Three channel 8-bit unsigned horizontal Roberts filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.66.1.103 NppStatus nppiFilterRobertsDown_8u_C4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 8-bit unsigned horizontal Roberts filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.104 NppStatus nppiFilterRobertsUp_16s_AC4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 16-bit signed vertical Roberts filter, ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.105 NppStatus nppiFilterRobertsUp_16s_C1R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single channel 16-bit signed vertical Roberts filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.106 NppStatus nppiFilterRobertsUp_16s_C3R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Three channel 16-bit signed vertical Roberts filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.107 NppStatus nppiFilterRobertsUp_16s_C4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 16-bit signed vertical Roberts filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.108 NppStatus nppiFilterRobertsUp_32f_AC4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 32-bit floating-point vertical Roberts filter, ignoring alpha-channel.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.109 NppStatus nppiFilterRobertsUp_32f_C1R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single channel 32-bit floating-point vertical Roberts filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.110 NppStatus nppiFilterRobertsUp_32f_C3R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Three channel 32-bit floating-point vertical Roberts filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.111 NppStatus nppiFilterRobertsUp_32f_C4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 32-bit floating-point vertical Roberts filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.112 NppStatus nppiFilterRobertsUp_8u_AC4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 8-bit unsigned vertical Roberts filter, ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.66.1.113 NppStatus nppiFilterRobertsUp_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single channel 8-bit unsigned vertical Roberts filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.66.1.114 NppStatus nppiFilterRobertsUp_8u_C3R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Three channel 8-bit unsigned vertical Roberts filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.66.1.115 `NppStatus nppiFilterRobertsUp_8u_C4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)`

Four channel 8-bit unsigned vertical Roberts filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.116 `NppStatus nppiFilterRow32f_16s_AC4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)`

16-bit four-channel 1D row convolution ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oROI Region-of-Interest (ROI).
pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.
nMaskSize Length of the linear kernel array.
nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.117 `NppStatus nppiFilterRow32f_16s_C1R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)`

16-bit single-channel 1D row convolution.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.118 `NppStatus nppiFilterRow32f_16s_C3R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)`

16-bit three-channel 1D row convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.119 `NppStatus nppiFilterRow32f_16s_C4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)`

16-bit four-channel 1D row convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.120 `NppStatus nppiFilterRow32f_16u_AC4R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)`

16-bit unsigned four-channel 1D row convolution ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.121 `NppStatus nppiFilterRow32f_16u_C1R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)`

16-bit unsigned single-channel 1D row convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.122 `NppStatus nppiFilterRow32f_16u_C3R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)`

16-bit unsigned three-channel 1D row convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.123 `NppStatus nppiFilterRow32f_16u_C4R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)`

16-bit unsigned four-channel 1D row convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.124 `NppStatus nppiFilterRow32f_8u_AC4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)`

8-bit unsigned four-channel 1D row convolution ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.125 `NppStatus nppiFilterRow32f_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)`

8-bit unsigned single-channel 1D row convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.126 `NppStatus nppiFilterRow32f_8u_C3R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)`

8-bit unsigned three-channel 1D row convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.127 `NppStatus nppiFilterRow32f_8u_C4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)`

8-bit unsigned four-channel 1D row convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.128 NppStatus nppiFilterRow_16s_AC4R (const Npp16s * *pSrc*, Npp32s *nSrcStep*, Npp16s * *pDst*, Npp32s *nDstStep*, NppiSize *oROI*, const Npp32s * *pKernel*, Npp32s *nMaskSize*, Npp32s *nAnchor*, Npp32s *nDivisor*)

16-bit four-channel 1D row convolution ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.129 NppStatus nppiFilterRow_16s_C1R (const Npp16s * *pSrc*, Npp32s *nSrcStep*, Npp16s * *pDst*, Npp32s *nDstStep*, NppiSize *oROI*, const Npp32s * *pKernel*, Npp32s *nMaskSize*, Npp32s *nAnchor*, Npp32s *nDivisor*)

16-bit single-channel 1D row convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.130 `NppStatus nppiFilterRow_16s_C3R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32s * pKernel, Npp32s nMaskSize, Npp32s nAnchor, Npp32s nDivisor)`

16-bit three-channel 1D row convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.131 `NppStatus nppiFilterRow_16s_C4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32s * pKernel, Npp32s nMaskSize, Npp32s nAnchor, Npp32s nDivisor)`

16-bit four-channel 1D row convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.132 NppStatus nppiFilterRow_16u_AC4R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32s * pKernel, Npp32s nMaskSize, Npp32s nAnchor, Npp32s nDivisor)

16-bit unsigned four-channel 1D row convolution ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.133 NppStatus nppiFilterRow_16u_C1R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32s * pKernel, Npp32s nMaskSize, Npp32s nAnchor, Npp32s nDivisor)

16-bit unsigned single-channel 1D row convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.134 NppStatus nppiFilterRow_16u_C3R (const Npp16u * *pSrc*, Npp32s *nSrcStep*, Npp16u * *pDst*, Npp32s *nDstStep*, NppiSize *oROI*, const Npp32s * *pKernel*, Npp32s *nMaskSize*, Npp32s *nAnchor*, Npp32s *nDivisor*)

16-bit unsigned three-channel 1D row convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.135 NppStatus nppiFilterRow_16u_C4R (const Npp16u * *pSrc*, Npp32s *nSrcStep*, Npp16u * *pDst*, Npp32s *nDstStep*, NppiSize *oROI*, const Npp32s * *pKernel*, Npp32s *nMaskSize*, Npp32s *nAnchor*, Npp32s *nDivisor*)

16-bit unsigned four-channel 1D row convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.136 `NppStatus nppiFilterRow_32f_AC4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)`

32-bit float four-channel 1D row convolution ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.137 `NppStatus nppiFilterRow_32f_C1R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)`

32-bit float single-channel 1D row convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.138 `NppStatus nppiFilterRow_32f_C3R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)`

32-bit float three-channel 1D row convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.139 `NppStatus nppiFilterRow_32f_C4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)`

32-bit float four-channel 1D row convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.140 `NppStatus nppiFilterRow_64f_C1R (const Npp64f * pSrc, Npp32s nSrcStep, Npp64f * pDst, Npp32s nDstStep, NppiSize oROI, const Npp64f * pKernel, Npp32s nMaskSize, Npp32s nAnchor)`

64-bit float single-channel 1D row convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.141 `NppStatus nppiFilterRow_8u_AC4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32s * pKernel, Npp32s nMaskSize, Npp32s nAnchor, Npp32s nDivisor)`

8-bit unsigned four-channel 1D row convolution ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.142 NppStatus nppiFilterRow_8u_C1R (const Npp8u * *pSrc*, Npp32s *nSrcStep*, Npp8u * *pDst*, Npp32s *nDstStep*, NppiSize *oROI*, const Npp32s * *pKernel*, Npp32s *nMaskSize*, Npp32s *nAnchor*, Npp32s *nDivisor*)

8-bit unsigned single-channel 1D row convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.143 NppStatus nppiFilterRow_8u_C3R (const Npp8u * *pSrc*, Npp32s *nSrcStep*, Npp8u * *pDst*, Npp32s *nDstStep*, NppiSize *oROI*, const Npp32s * *pKernel*, Npp32s *nMaskSize*, Npp32s *nAnchor*, Npp32s *nDivisor*)

8-bit unsigned three-channel 1D row convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.144 NppStatus nppiFilterRow_8u_C4R (const Npp8u * *pSrc*, Npp32s *nSrcStep*, Npp8u * *pDst*, Npp32s *nDstStep*, NppiSize *oROI*, const Npp32s * *pKernel*, Npp32s *nMaskSize*, Npp32s *nAnchor*, Npp32s *nDivisor*)

8-bit unsigned four-channel 1D row convolution.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.145 NppStatus nppiFilterSharpen_16s_AC4R (const Npp16s * *pSrc*, Npp32s *nSrcStep*, Npp16s * *pDst*, Npp32s *nDstStep*, NppiSize *oSizeROI*)

Four channel 16-bit signed sharpening filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.146 NppStatus nppiFilterSharpen_16s_C1R (const Npp16s * *pSrc*, Npp32s *nSrcStep*, Npp16s * *pDst*, Npp32s *nDstStep*, NppiSize *oSizeROI*)

Single channel 16-bit signed sharpening filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.66.1.147 NppStatus nppiFilterSharpen_16s_C3R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Three channel 16-bit signed sharpening filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.66.1.148 NppStatus nppiFilterSharpen_16s_C4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 16-bit signed sharpening filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.66.1.149 NppStatus nppiFilterSharpen_16u_AC4R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 16-bit unsigned sharpening filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.66.1.150 NppStatus nppiFilterSharpen_16u_C1R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single channel 16-bit unsigned sharpening filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.66.1.151 NppStatus nppiFilterSharpen_16u_C3R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Three channel 16-bit unsigned sharpening filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.66.1.152 NppStatus nppiFilterSharpen_16u_C4R (const Npp16u * *pSrc*, Npp32s *nSrcStep*, Npp16u * *pDst*, Npp32s *nDstStep*, NppiSize *oSizeROI*)

Four channel 16-bit unsigned sharpening filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.66.1.153 NppStatus nppiFilterSharpen_32f_AC4R (const Npp32f * *pSrc*, Npp32s *nSrcStep*, Npp32f * *pDst*, Npp32s *nDstStep*, NppiSize *oSizeROI*)

Four channel 32-bit floating-point sharpening filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.66.1.154 NppStatus nppiFilterSharpen_32f_C1R (const Npp32f * *pSrc*, Npp32s *nSrcStep*, Npp32f * *pDst*, Npp32s *nDstStep*, NppiSize *oSizeROI*)

Single channel 32-bit floating-point sharpening filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.66.1.155 NppStatus nppiFilterSharpen_32f_C3R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Three channel 32-bit floating-point sharpening filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.156 NppStatus nppiFilterSharpen_32f_C4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 32-bit floating-point sharpening filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.157 NppStatus nppiFilterSharpen_8u_AC4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 8-bit unsigned sharpening filter, ignoring alpha channel.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.158 `NppStatus nppiFilterSharpen_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)`

Single channel 8-bit unsigned sharpening filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.66.1.159 `NppStatus nppiFilterSharpen_8u_C3R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)`

Three channel 8-bit unsigned sharpening filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.66.1.160 `NppStatus nppiFilterSharpen_8u_C4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)`

Four channel 8-bit unsigned sharpening filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.66.1.161 NppStatus nppiFilterSobelCross_32f_C1R (const Npp32f * *pSrc*, Npp32s *nSrcStep*, Npp32f * *pDst*, Npp32s *nDstStep*, NppiSize *oSizeROI*, NppiMaskSize *eMaskSize*)

Single channel 32-bit floating-point second cross derivative Sobel filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.162 NppStatus nppiFilterSobelCross_8s16s_C1R (const Npp8s * *pSrc*, Npp32s *nSrcStep*, Npp16s * *pDst*, Npp32s *nDstStep*, NppiSize *oSizeROI*, NppiMaskSize *eMaskSize*)

Single channel 8-bit signed to 16-bit signed second cross derivative Sobel filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.163 NppStatus nppiFilterSobelCross_8u16s_C1R (const Npp8u * *pSrc*, Npp32s *nSrcStep*, Npp16s * *pDst*, Npp32s *nDstStep*, NppiSize *oSizeROI*, NppiMaskSize *eMaskSize*)

Single channel 8-bit unsigned to 16-bit signed second cross derivative Sobel filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eMaskSize* Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.164 `NppStatus nppiFilterSobelVertSecond_32f_C1R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Single channel 32-bit floating-point second derivative, vertical Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eMaskSize Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.165 `NppStatus nppiFilterSobelVertSecond_8s16s_C1R (const Npp8s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Single channel 8-bit signed to 16-bit signed second derivative, vertical Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eMaskSize Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.66.1.166 `NppStatus nppiFilterSobelVertSecond_8u16s_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Single channel 8-bit unsigned to 16-bit signed second derivative, vertical Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eMaskSize Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.67 1D Window Sum

1D Window Sum

1D mask Window Sum for 8 bit images.

- `NppStatus nppiSumWindowColumn_8u32f_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, `Npp32s nMaskSize`, `Npp32s nAnchor`)
8-bit unsigned 1D (column) sum to 32f.
- `NppStatus nppiSumWindowRow_8u32f_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, `Npp32s nMaskSize`, `Npp32s nAnchor`)
8-bit unsigned 1D (row) sum to 32f.

7.67.1 Function Documentation

7.67.1.1 `NppStatus nppiSumWindowColumn_8u32f_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, `Npp32s nMaskSize`, `Npp32s nAnchor`)

8-bit unsigned 1D (column) sum to 32f.

Apply Column Window Summation filter over a 1D mask region around each source pixel for 1-channel 8 bit/pixel input images with 32-bit floating point output. Result 32-bit floating point pixel is equal to the sum of the corresponding and neighboring column pixel values in a mask region of the source image defined by `nMaskSize` and `nAnchor`.

Parameters:

- `pSrc` Source-Image Pointer.
- `nSrcStep` Source-Image Line Step.
- `pDst` Destination-Image Pointer.
- `nDstStep` Destination-Image Line Step.
- `oROI` Region-of-Interest (ROI).
- `nMaskSize` Length of the linear kernel array.
- `nAnchor` Y offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.67.1.2 `NppStatus nppiSumWindowRow_8u32f_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oROI`, `Npp32s nMaskSize`, `Npp32s nAnchor`)

8-bit unsigned 1D (row) sum to 32f.

Apply Row Window Summation filter over a 1D mask region around each source pixel for 1-channel 8-bit pixel input images with 32-bit floating point output. Result 32-bit floating point pixel is equal to the sum of the corresponding and neighboring row pixel values in a mask region of the source image defined by `iKernelDim` and `iAnchorX`.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68 Convolution

Filter

General purpose 2D convolution filter.

Pixels under the mask are multiplied by the respective weights in the mask and the results are summed. Before writing the result pixel the sum is scaled back via division by nDivisor.

- `NppStatus nppiFilter_8u_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, const `Npp32s *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`, `Npp32s nDivisor`)

Single channel 8-bit unsigned convolution filter.

- `NppStatus nppiFilter_8u_C3R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, const `Npp32s *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`, `Npp32s nDivisor`)

Three channel 8-bit unsigned convolution filter.

- `NppStatus nppiFilter_8u_C4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, const `Npp32s *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`, `Npp32s nDivisor`)

Four channel channel 8-bit unsigned convolution filter.

- `NppStatus nppiFilter_8u_AC4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, const `Npp32s *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`, `Npp32s nDivisor`)

Four channel 8-bit unsigned convolution filter, ignoring alpha channel.

- `NppStatus nppiFilter_16u_C1R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, const `Npp32s *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`, `Npp32s nDivisor`)

Single channel 16-bit unsigned convolution filter.

- `NppStatus nppiFilter_16u_C3R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, const `Npp32s *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`, `Npp32s nDivisor`)

Three channel 16-bit unsigned convolution filter.

- `NppStatus nppiFilter_16u_C4R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, const `Npp32s *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`, `Npp32s nDivisor`)

Four channel channel 16-bit unsigned convolution filter.

- `NppStatus nppiFilter_16u_AC4R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, const `Npp32s *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`, `Npp32s nDivisor`)

Four channel 16-bit unsigned convolution filter, ignoring alpha channel.

- `NppStatus nppiFilter_16s_C1R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, const `Npp32s *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`, `Npp32s nDivisor`)

Single channel 16-bit convolution filter.

- `NppStatus nppiFilter_16s_C3R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, const `Npp32s *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`, `Npp32s nDivisor`)

Three channel 16-bit convolution filter.

- `NppStatus nppiFilter_16s_C4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, const `Npp32s *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`, `Npp32s nDivisor`)

Four channel channel 16-bit convolution filter.

- `NppStatus nppiFilter_16s_AC4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, const `Npp32s *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`, `Npp32s nDivisor`)

Four channel 16-bit convolution filter, ignoring alpha channel.

- `NppStatus nppiFilter_32f_C1R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`)

Single channel 32-bit float convolution filter.

- `NppStatus nppiFilter_32f_C3R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`)

Three channel 32-bit float convolution filter.

- `NppStatus nppiFilter_32f_C4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`)

Four channel 32-bit float convolution filter.

- `NppStatus nppiFilter_32f_AC4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`)

Four channel 32-bit float convolution filter, ignoring alpha channel.

- `NppStatus nppiFilter_64f_C1R` (const `Npp64f *pSrc`, `Npp32s nSrcStep`, `Npp64f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, const `Npp64f *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`)

Single channel 64-bit float convolution filter.

Filter32f

General purpose 2D convolution filter using floating-point weights.

Pixels under the mask are multiplied by the respective weights in the mask and the results are summed. Before writing the result pixel the sum is scaled back via division by `nDivisor`.

- `NppStatus nppiFilter32f_8u_C1R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`)

Single channel 8-bit unsigned convolution filter.

- `NppStatus nppiFilter32f_8u_C3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`)

Three channel 8-bit unsigned convolution filter.

- `NppStatus nppiFilter32f_8u_C4R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`)

Four channel 8-bit unsigned convolution filter.

- `NppStatus nppiFilter32f_8u_AC4R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`)

Four channel 8-bit unsigned convolution filter, ignorint alpha channel.

- `NppStatus nppiFilter32f_8s_C1R` (const `Npp8s *pSrc`, int `nSrcStep`, `Npp8s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`)

Single channel 8-bit signed convolution filter.

- `NppStatus nppiFilter32f_8s_C3R` (const `Npp8s *pSrc`, int `nSrcStep`, `Npp8s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`)

Three channel 8-bit signed convolution filter.

- `NppStatus nppiFilter32f_8s_C4R` (const `Npp8s *pSrc`, int `nSrcStep`, `Npp8s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`)

Four channel 8-bit signed convolution filter.

- `NppStatus nppiFilter32f_8s_AC4R` (const `Npp8s *pSrc`, int `nSrcStep`, `Npp8s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`)

Four channel 8-bit signed convolution filter, ignoring alpha channel.

- `NppStatus nppiFilter32f_16u_C1R` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`)

Single channel 16-bit unsigned convolution filter.

- `NppStatus nppiFilter32f_16u_C3R` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`)

Three channel 16-bit unsigned convolution filter.

- `NppStatus nppiFilter32f_16u_C4R` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`)

Four channel 16-bit unsigned convolution filter.

- `NppStatus nppiFilter32f_16u_AC4R` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`)

Four channel 16-bit unsigned convolution filter, ignoring alpha channel.

- `NppStatus nppiFilter32f_16s_C1R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`)

Single channel 16-bit convolution filter.

- `NppStatus nppiFilter32f_16s_C3R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`)

Three channel 16-bit convolution filter.

- [NppStatus nppiFilter32f_16s_C4R](#) (const [Npp16s](#) *pSrc, int nSrcStep, [Npp16s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp32f](#) *pKernel, [NppiSize](#) oKernelSize, [NppiPoint](#) oAnchor)
Four channel 16-bit convolution filter.
- [NppStatus nppiFilter32f_16s_AC4R](#) (const [Npp16s](#) *pSrc, int nSrcStep, [Npp16s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp32f](#) *pKernel, [NppiSize](#) oKernelSize, [NppiPoint](#) oAnchor)
Four channel 16-bit convolution filter, ignoring alpha channel.
- [NppStatus nppiFilter32f_32s_C1R](#) (const [Npp32s](#) *pSrc, int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp32f](#) *pKernel, [NppiSize](#) oKernelSize, [NppiPoint](#) oAnchor)
Single channel 32-bit convolution filter.
- [NppStatus nppiFilter32f_32s_C3R](#) (const [Npp32s](#) *pSrc, int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp32f](#) *pKernel, [NppiSize](#) oKernelSize, [NppiPoint](#) oAnchor)
Three channel 32-bit convolution filter.
- [NppStatus nppiFilter32f_32s_C4R](#) (const [Npp32s](#) *pSrc, int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp32f](#) *pKernel, [NppiSize](#) oKernelSize, [NppiPoint](#) oAnchor)
Four channel 32-bit convolution filter.
- [NppStatus nppiFilter32f_32s_AC4R](#) (const [Npp32s](#) *pSrc, int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp32f](#) *pKernel, [NppiSize](#) oKernelSize, [NppiPoint](#) oAnchor)
Four channel 32-bit convolution filter, ignoring alpha channel.
- [NppStatus nppiFilter32f_8u16s_C1R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [Npp16s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp32f](#) *pKernel, [NppiSize](#) oKernelSize, [NppiPoint](#) oAnchor)
Single channel 8-bit unsigned to 16-bit signed convolution filter.
- [NppStatus nppiFilter32f_8u16s_C3R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [Npp16s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp32f](#) *pKernel, [NppiSize](#) oKernelSize, [NppiPoint](#) oAnchor)
Three channel 8-bit unsigned to 16-bit signed convolution filter.
- [NppStatus nppiFilter32f_8u16s_C4R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [Npp16s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp32f](#) *pKernel, [NppiSize](#) oKernelSize, [NppiPoint](#) oAnchor)
Four channel 8-bit unsigned to 16-bit signed convolution filter.
- [NppStatus nppiFilter32f_8u16s_AC4R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [Npp16s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp32f](#) *pKernel, [NppiSize](#) oKernelSize, [NppiPoint](#) oAnchor)
Four channel 8-bit unsigned to 16-bit signed convolution filter, ignoring alpha channel.
- [NppStatus nppiFilter32f_8s16s_C1R](#) (const [Npp8s](#) *pSrc, int nSrcStep, [Npp16s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp32f](#) *pKernel, [NppiSize](#) oKernelSize, [NppiPoint](#) oAnchor)
Single channel 8-bit to 16-bit signed convolution filter.
- [NppStatus nppiFilter32f_8s16s_C3R](#) (const [Npp8s](#) *pSrc, int nSrcStep, [Npp16s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp32f](#) *pKernel, [NppiSize](#) oKernelSize, [NppiPoint](#) oAnchor)
Three channel 8-bit to 16-bit signed convolution filter.
- [NppStatus nppiFilter32f_8s16s_C4R](#) (const [Npp8s](#) *pSrc, int nSrcStep, [Npp16s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp32f](#) *pKernel, [NppiSize](#) oKernelSize, [NppiPoint](#) oAnchor)
Four channel 8-bit to 16-bit signed convolution filter.

- `NppStatus nppiFilter32f_8s16s_AC4R` (const `Npp8s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`)
Four channel 8-bit to 16-bit signed convolution filter, ignoring alpha channel.

7.68.1 Function Documentation

7.68.1.1 `NppStatus nppiFilter32f_16s_AC4R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`)

Four channel 16-bit convolution filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.2 `NppStatus nppiFilter32f_16s_C1R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f *pKernel`, `NppiSize oKernelSize`, `NppiPoint oAnchor`)

Single channel 16-bit convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.3 NppStatus nppiFilter32f_16s_C3R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)

Three channel 16-bit convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.4 NppStatus nppiFilter32f_16s_C4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)

Four channel 16-bit convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.5 NppStatus nppiFilter32f_16u_AC4R (const Npp16u * *pSrc*, int *nSrcStep*, Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, const Npp32f * *pKernel*, NppiSize *oKernelSize*, NppiPoint *oAnchor*)

Four channel 16-bit unsigned convolution filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.6 NppStatus nppiFilter32f_16u_C1R (const Npp16u * *pSrc*, int *nSrcStep*, Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, const Npp32f * *pKernel*, NppiSize *oKernelSize*, NppiPoint *oAnchor*)

Single channel 16-bit unsigned convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.7 NppStatus nppiFilter32f_16u_C3R (const Npp16u * *pSrc*, int *nSrcStep*, Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, const Npp32f * *pKernel*, NppiSize *oKernelSize*, NppiPoint *oAnchor*)

Three channel 16-bit unsigned convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.8 NppStatus nppiFilter32f_16u_C4R (const Npp16u * *pSrc*, int *nSrcStep*, Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, const Npp32f * *pKernel*, NppiSize *oKernelSize*, NppiPoint *oAnchor*)

Four channel 16-bit unsigned convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.9 NppStatus nppiFilter32f_32s_AC4R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)

Four channel 32-bit convolution filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.10 NppStatus nppiFilter32f_32s_C1R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)

Single channel 32-bit convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.11 `NppStatus nppiFilter32f_32s_C3R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)`

Three channel 32-bit convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.12 `NppStatus nppiFilter32f_32s_C4R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)`

Four channel 32-bit convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.13 `NppStatus nppiFilter32f_8s16s_AC4R (const Npp8s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)`

Four channel 8-bit to 16-bit signed convolution filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.14 `NppStatus nppiFilter32f_8s16s_C1R (const Npp8s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)`

Single channel 8-bit to 16-bit signed convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.15 `NppStatus nppiFilter32f_8s16s_C3R (const Npp8s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)`

Three channel 8-bit to 16-bit signed convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.16 `NppStatus nppiFilter32f_8s16s_C4R (const Npp8s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)`

Four channel 8-bit to 16-bit signed convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.17 `NppStatus nppiFilter32f_8s_AC4R (const Npp8s * pSrc, int nSrcStep, Npp8s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)`

Four channel 8-bit signed convolution filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.18 `NppStatus nppiFilter32f_8s_C1R (const Npp8s * pSrc, int nSrcStep, Npp8s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)`

Single channel 8-bit signed convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.19 `NppStatus nppiFilter32f_8s_C3R (const Npp8s * pSrc, int nSrcStep, Npp8s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)`

Three channel 8-bit signed convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.20 `NppStatus nppiFilter32f_8s_C4R (const Npp8s * pSrc, int nSrcStep, Npp8s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)`

Four channel 8-bit signed convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.21 `NppStatus nppiFilter32f_8u16s_AC4R (const Npp8u * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)`

Four channel 8-bit unsigned to 16-bit signed convolution filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.22 `NppStatus nppiFilter32f_8u16s_C1R (const Npp8u * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)`

Single channel 8-bit unsigned to 16-bit signed convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.23 `NppStatus nppiFilter32f_8u16s_C3R (const Npp8u * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)`

Three channel 8-bit unsigned to 16-bit signed convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.24 `NppStatus nppiFilter32f_8u16s_C4R (const Npp8u * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)`

Four channel 8-bit unsigned to 16-bit signed convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.25 `NppStatus nppiFilter32f_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)`

Four channel 8-bit unsigned convolution filter, ignorint alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.26 `NppStatus nppiFilter32f_8u_C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)`

Single channel 8-bit unsigned convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.27 `NppStatus nppiFilter32f_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)`

Three channel 8-bit unsigned convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.28 `NppStatus nppiFilter32f_8u_C4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)`

Four channel 8-bit unsigned convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.29 `NppStatus nppiFilter_16s_AC4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp32s * pKernel, NppiSize oKernelSize, NppiPoint oAnchor, Npp32s nDivisor)`

Four channel 16-bit convolution filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.30 `NppStatus nppiFilter_16s_C1R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp32s * pKernel, NppiSize oKernelSize, NppiPoint oAnchor, Npp32s nDivisor)`

Single channel 16-bit convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.31 `NppStatus nppiFilter_16s_C3R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp32s * pKernel, NppiSize oKernelSize, NppiPoint oAnchor, Npp32s nDivisor)`

Three channel 16-bit convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.32 `NppStatus nppiFilter_16s_C4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp32s * pKernel, NppiSize oKernelSize, NppiPoint oAnchor, Npp32s nDivisor)`

Four channel channel 16-bit convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.33 `NppStatus nppiFilter_16u_AC4R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp32s * pKernel, NppiSize oKernelSize, NppiPoint oAnchor, Npp32s nDivisor)`

Four channel 16-bit unsigned convolution filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.34 `NppStatus nppiFilter_16u_C1R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp32s * pKernel, NppiSize oKernelSize, NppiPoint oAnchor, Npp32s nDivisor)`

Single channel 16-bit unsigned convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.35 `NppStatus nppiFilter_16u_C3R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp32s * pKernel, NppiSize oKernelSize, NppiPoint oAnchor, Npp32s nDivisor)`

Three channel 16-bit unsigned convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.36 `NppStatus nppiFilter_16u_C4R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp32s * pKernel, NppiSize oKernelSize, NppiPoint oAnchor, Npp32s nDivisor)`

Four channel channel 16-bit unsigned convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.37 `NppStatus nppiFilter_32f_AC4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)`

Four channel 32-bit float convolution filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.38 `NppStatus nppiFilter_32f_C1R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)`

Single channel 32-bit float convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.39 `NppStatus nppiFilter_32f_C3R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)`

Three channel 32-bit float convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.40 `NppStatus nppiFilter_32f_C4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp32f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)`

Four channel 32-bit float convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.41 `NppStatus nppiFilter_64f_C1R (const Npp64f * pSrc, Npp32s nSrcStep, Npp64f * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp64f * pKernel, NppiSize oKernelSize, NppiPoint oAnchor)`

Single channel 64-bit float convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.42 `NppStatus nppiFilter_8u_AC4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp32s * pKernel, NppiSize oKernelSize, NppiPoint oAnchor, Npp32s nDivisor)`

Four channel 8-bit unsigned convolution filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.43 `NppStatus nppiFilter_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp32s * pKernel, NppiSize oKernelSize, NppiPoint oAnchor, Npp32s nDivisor)`

Single channel 8-bit unsigned convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.44 `NppStatus nppiFilter_8u_C3R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp32s * pKernel, NppiSize oKernelSize, NppiPoint oAnchor, Npp32s nDivisor)`

Three channel 8-bit unsigned convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.68.1.45 `NppStatus nppiFilter_8u_C4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp32s * pKernel, NppiSize oKernelSize, NppiPoint oAnchor, Npp32s nDivisor)`

Four channel channel 8-bit unsigned convolution filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.69 2D Fixed Linear Filters

FilterBox

Computes the average pixel values of the pixels under a rectangular mask.

- `NppStatus nppiFilterBox_8u_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Single channel 8-bit unsigned box filter.
- `NppStatus nppiFilterBox_8u_C3R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Three channel 8-bit unsigned box filter.
- `NppStatus nppiFilterBox_8u_C4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Four channel 8-bit unsigned box filter.
- `NppStatus nppiFilterBox_8u_AC4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Four channel 8-bit unsigned box filter, ignoring alpha channel.
- `NppStatus nppiFilterBox_16u_C1R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Single channel 16-bit unsigned box filter.
- `NppStatus nppiFilterBox_16u_C3R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Three channel 16-bit unsigned box filter.
- `NppStatus nppiFilterBox_16u_C4R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Four channel 16-bit unsigned box filter.
- `NppStatus nppiFilterBox_16u_AC4R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Four channel 16-bit unsigned box filter, ignoring alpha channel.
- `NppStatus nppiFilterBox_16s_C1R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Single channel 16-bit box filter.
- `NppStatus nppiFilterBox_16s_C3R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Three channel 16-bit box filter.
- `NppStatus nppiFilterBox_16s_C4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Four channel 16-bit box filter.

- `NppStatus nppiFilterBox_16s_AC4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)

Four channel 16-bit box filter, ignoring alpha channel.

- `NppStatus nppiFilterBox_32f_C1R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)

Single channel 32-bit floating-point box filter.

- `NppStatus nppiFilterBox_32f_C3R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)

Three channel 32-bit floating-point box filter.

- `NppStatus nppiFilterBox_32f_C4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)

Four channel 32-bit floating-point box filter.

- `NppStatus nppiFilterBox_32f_AC4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)

Four channel 32-bit floating-point box filter, ignoring alpha channel.

- `NppStatus nppiFilterBox_64f_C1R` (const `Npp64f *pSrc`, `Npp32s nSrcStep`, `Npp64f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)

Single channel 64-bit floating-point box filter.

7.69.1 Function Documentation

7.69.1.1 `NppStatus nppiFilterBox_16s_AC4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)

Four channel 16-bit box filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Avg operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.69.1.2 `NppStatus nppiFilterBox_16s_C1R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Single channel 16-bit box filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Avg operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.69.1.3 `NppStatus nppiFilterBox_16s_C3R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Three channel 16-bit box filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Avg operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.69.1.4 `NppStatus nppiFilterBox_16s_C4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Four channel 16-bit box filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Avg operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.69.1.5 NppStatus nppiFilterBox_16u_AC4R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)

Four channel 16-bit unsigned box filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Avg operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.69.1.6 NppStatus nppiFilterBox_16u_C1R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)

Single channel 16-bit unsigned box filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Avg operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.69.1.7 NppStatus nppiFilterBox_16u_C3R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)

Three channel 16-bit unsigned box filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Avg operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.69.1.8 NppStatus nppiFilterBox_16u_C4R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)

Four channel 16-bit unsigned box filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Avg operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.69.1.9 NppStatus nppiFilterBox_32f_AC4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)

Four channel 32-bit floating-point box filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Avg operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.69.1.10 `NppStatus nppiFilterBox_32f_C1R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Single channel 32-bit floating-point box filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Avg operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.69.1.11 `NppStatus nppiFilterBox_32f_C3R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Three channel 32-bit floating-point box filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Avg operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.69.1.12 `NppStatus nppiFilterBox_32f_C4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Four channel 32-bit floating-point box filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Avg operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.69.1.13 `NppStatus nppiFilterBox_64f_C1R (const Npp64f * pSrc, Npp32s nSrcStep, Npp64f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Single channel 64-bit floating-point box filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Avg operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.69.1.14 `NppStatus nppiFilterBox_8u_AC4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Four channel 8-bit unsigned box filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Avg operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.69.1.15 `NppStatus nppiFilterBox_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Single channel 8-bit unsigned box filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Avg operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.69.1.16 `NppStatus nppiFilterBox_8u_C3R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Three channel 8-bit unsigned box filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Avg operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.69.1.17 `NppStatus nppiFilterBox_8u_C4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Four channel 8-bit unsigned box filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Avg operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.70 Rank Filters

ImageMax Filter

Result pixel value is the maximum of pixel values under the rectangular mask region.

- `NppStatus nppiFilterMax_8u_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Single channel 8-bit unsigned maximum filter.
- `NppStatus nppiFilterMax_8u_C3R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Three channel 8-bit unsigned maximum filter.
- `NppStatus nppiFilterMax_8u_C4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Four channel 8-bit unsigned maximum filter.
- `NppStatus nppiFilterMax_8u_AC4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Four channel 8-bit unsigned maximum filter, ignoring alpha channel.
- `NppStatus nppiFilterMax_16u_C1R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Single channel 16-bit unsigned maximum filter.
- `NppStatus nppiFilterMax_16u_C3R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Three channel 16-bit unsigned maximum filter.
- `NppStatus nppiFilterMax_16u_C4R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Four channel 16-bit unsigned maximum filter.
- `NppStatus nppiFilterMax_16u_AC4R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Four channel 16-bit unsigned maximum filter, ignoring alpha channel.
- `NppStatus nppiFilterMax_16s_C1R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Single channel 16-bit signed maximum filter.
- `NppStatus nppiFilterMax_16s_C3R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Three channel 16-bit signed maximum filter.
- `NppStatus nppiFilterMax_16s_C4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Four channel 16-bit signed maximum filter.

- `NppStatus nppiFilterMax_16s_AC4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Four channel 16-bit signed maximum filter, ignoring alpha channel.
- `NppStatus nppiFilterMax_32f_C1R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Single channel 32-bit floating-point maximum filter.
- `NppStatus nppiFilterMax_32f_C3R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Three channel 32-bit floating-point maximum filter.
- `NppStatus nppiFilterMax_32f_C4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Four channel 32-bit floating-point maximum filter.
- `NppStatus nppiFilterMax_32f_AC4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Four channel 32-bit floating-point maximum filter, ignoring alpha channel.

ImageMin Filter

Result pixel value is the minimum of pixel values under the rectangular mask region.

- `NppStatus nppiFilterMin_8u_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Single channel 8-bit unsigned minimum filter.
- `NppStatus nppiFilterMin_8u_C3R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Three channel 8-bit unsigned minimum filter.
- `NppStatus nppiFilterMin_8u_C4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Four channel 8-bit unsigned minimum filter.
- `NppStatus nppiFilterMin_8u_AC4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Four channel 8-bit unsigned minimum filter, ignoring alpha channel.
- `NppStatus nppiFilterMin_16u_C1R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Single channel 16-bit unsigned minimum filter.
- `NppStatus nppiFilterMin_16u_C3R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)
Three channel 16-bit unsigned minimum filter.
- `NppStatus nppiFilterMin_16u_C4R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)

Four channel 16-bit unsigned minimum filter.

- `NppStatus nppiFilterMin_16u_AC4R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)

Four channel 16-bit unsigned minimum filter, ignoring alpha channel.

- `NppStatus nppiFilterMin_16s_C1R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)

Single channel 16-bit signed minimum filter.

- `NppStatus nppiFilterMin_16s_C3R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)

Three channel 16-bit signed minimum filter.

- `NppStatus nppiFilterMin_16s_C4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)

Four channel 16-bit signed minimum filter.

- `NppStatus nppiFilterMin_16s_AC4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)

Four channel 16-bit signed minimum filter, ignoring alpha channel.

- `NppStatus nppiFilterMin_32f_C1R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)

Single channel 32-bit floating-point minimum filter.

- `NppStatus nppiFilterMin_32f_C3R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)

Three channel 32-bit floating-point minimum filter.

- `NppStatus nppiFilterMin_32f_C4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)

Four channel 32-bit floating-point minimum filter.

- `NppStatus nppiFilterMin_32f_AC4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)

Four channel 32-bit floating-point minimum filter, ignoring alpha channel.

7.70.1 Function Documentation

7.70.1.1 `NppStatus nppiFilterMax_16s_AC4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)

Four channel 16-bit signed maximum filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.70.1.2 `NppStatus nppiFilterMax_16s_C1R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Single channel 16-bit signed maximum filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.70.1.3 `NppStatus nppiFilterMax_16s_C3R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Three channel 16-bit signed maximum filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.70.1.4 NppStatus nppiFilterMax_16s_C4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)

Four channel 16-bit signed maximum filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.70.1.5 NppStatus nppiFilterMax_16u_AC4R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)

Four channel 16-bit unsigned maximum filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.70.1.6 NppStatus nppiFilterMax_16u_C1R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)

Single channel 16-bit unsigned maximum filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.70.1.7 `NppStatus nppiFilterMax_16u_C3R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Three channel 16-bit unsigned maximum filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.70.1.8 `NppStatus nppiFilterMax_16u_C4R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Four channel 16-bit unsigned maximum filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.70.1.9 NppStatus nppiFilterMax_32f_AC4R (const Npp32f * *pSrc*, Npp32s *nSrcStep*, Npp32f * *pDst*, Npp32s *nDstStep*, NppiSize *oSizeROI*, NppiSize *oMaskSize*, NppiPoint *oAnchor*)

Four channel 32-bit floating-point maximum filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.70.1.10 NppStatus nppiFilterMax_32f_C1R (const Npp32f * *pSrc*, Npp32s *nSrcStep*, Npp32f * *pDst*, Npp32s *nDstStep*, NppiSize *oSizeROI*, NppiSize *oMaskSize*, NppiPoint *oAnchor*)

Single channel 32-bit floating-point maximum filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.70.1.11 NppStatus nppiFilterMax_32f_C3R (const Npp32f * *pSrc*, Npp32s *nSrcStep*, Npp32f * *pDst*, Npp32s *nDstStep*, NppiSize *oSizeROI*, NppiSize *oMaskSize*, NppiPoint *oAnchor*)

Three channel 32-bit floating-point maximum filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.70.1.12 `NppStatus nppiFilterMax_32f_C4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Four channel 32-bit floating-point maximum filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.70.1.13 `NppStatus nppiFilterMax_8u_AC4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Four channel 8-bit unsigned maximum filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.70.1.14 `NppStatus nppiFilterMax_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Single channel 8-bit unsigned maximum filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.70.1.15 `NppStatus nppiFilterMax_8u_C3R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Three channel 8-bit unsigned maximum filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.70.1.16 `NppStatus nppiFilterMax_8u_C4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Four channel 8-bit unsigned maximum filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.70.1.17 `NppStatus nppiFilterMin_16s_AC4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Four channel 16-bit signed minimum filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.70.1.18 `NppStatus nppiFilterMin_16s_C1R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Single channel 16-bit signed minimum filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.70.1.19 NppStatus nppiFilterMin_16s_C3R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)

Three channel 16-bit signed minimum filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.70.1.20 NppStatus nppiFilterMin_16s_C4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)

Four channel 16-bit signed minimum filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.70.1.21 NppStatus nppiFilterMin_16u_AC4R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)

Four channel 16-bit unsigned minimum filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.70.1.22 `NppStatus nppiFilterMin_16u_C1R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Single channel 16-bit unsigned minimum filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.70.1.23 `NppStatus nppiFilterMin_16u_C3R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Three channel 16-bit unsigned minimum filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.70.1.24 NppStatus nppiFilterMin_16u_C4R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)

Four channel 16-bit unsigned minimum filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.70.1.25 NppStatus nppiFilterMin_32f_AC4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)

Four channel 32-bit floating-point minimum filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.70.1.26 NppStatus nppiFilterMin_32f_C1R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)

Single channel 32-bit floating-point minimum filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.70.1.27 `NppStatus nppiFilterMin_32f_C3R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Three channel 32-bit floating-point minimum filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.70.1.28 `NppStatus nppiFilterMin_32f_C4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Four channel 32-bit floating-point minimum filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.70.1.29 `NppStatus nppiFilterMin_8u_AC4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Four channel 8-bit unsigned minimum filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.70.1.30 `NppStatus nppiFilterMin_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Single channel 8-bit unsigned minimum filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.70.1.31 `NppStatus nppiFilterMin_8u_C3R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Three channel 8-bit unsigned minimum filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.70.1.32 `NppStatus nppiFilterMin_8u_C4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

Four channel 8-bit unsigned minimum filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference relative to the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71 Fixed Filters

Fixed filters perform linear filtering operations (i.e.

FilterPrewittHoriz

Filters the image using a horizontal Prewitt filter kernel:

$$\begin{pmatrix} 1 & 1 & 1 \\ 0 & 0 & 0 \\ -1 & -1 & -1 \end{pmatrix}$$

- `NppStatus nppiFilterPrewittHoriz_8u_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Single channel 8-bit unsigned horizontal Prewitt filter.
- `NppStatus nppiFilterPrewittHoriz_8u_C3R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Three channel 8-bit unsigned horizontal Prewitt filter.
- `NppStatus nppiFilterPrewittHoriz_8u_C4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Four channel 8-bit unsigned horizontal Prewitt filter.
- `NppStatus nppiFilterPrewittHoriz_8u_AC4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Four channel 8-bit unsigned horizontal Prewitt filter; ignoring alpha channel.
- `NppStatus nppiFilterPrewittHoriz_16s_C1R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Single channel 16-bit signed horizontal Prewitt filter.
- `NppStatus nppiFilterPrewittHoriz_16s_C3R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Three channel 16-bit signed horizontal Prewitt filter.
- `NppStatus nppiFilterPrewittHoriz_16s_C4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Four channel 16-bit signed horizontal Prewitt filter.
- `NppStatus nppiFilterPrewittHoriz_16s_AC4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Four channel 16-bit signed horizontal Prewitt filter; ignoring alpha channel.
- `NppStatus nppiFilterPrewittHoriz_32f_C1R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Single channel 32-bit floating-point horizontal Prewitt filter.
- `NppStatus nppiFilterPrewittHoriz_32f_C3R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Three channel 32-bit floating-point horizontal Prewitt filter.

- `NppStatus nppiFilterPrewittHoriz_32f_C4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Four channel 32-bit floating-point horizontal Prewitt filter.

- `NppStatus nppiFilterPrewittHoriz_32f_AC4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Four channel 32-bit floating-point horizontal Prewitt filter, ignoring alpha channel.

FilterPrewittVert

Filters the image using a vertical Prewitt filter kernel:

$$\begin{pmatrix} -1 & 0 & 1 \\ -1 & 0 & 1 \\ -1 & 0 & 1 \end{pmatrix}$$

- `NppStatus nppiFilterPrewittVert_8u_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Single channel 8-bit unsigned vertical Prewitt filter.

- `NppStatus nppiFilterPrewittVert_8u_C3R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Three channel 8-bit unsigned vertical Prewitt filter.

- `NppStatus nppiFilterPrewittVert_8u_C4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Four channel 8-bit unsigned vertical Prewitt filter.

- `NppStatus nppiFilterPrewittVert_8u_AC4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Four channel 8-bit unsigned vertical Prewitt filter, ignoring alpha channel.

- `NppStatus nppiFilterPrewittVert_16s_C1R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Single channel 16-bit signed vertical Prewitt filter.

- `NppStatus nppiFilterPrewittVert_16s_C3R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Three channel 16-bit signed vertical Prewitt filter.

- `NppStatus nppiFilterPrewittVert_16s_C4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Four channel 16-bit signed vertical Prewitt filter.

- `NppStatus nppiFilterPrewittVert_16s_AC4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Four channel 16-bit signed vertical Prewitt filter, ignoring alpha channel.

- `NppStatus nppiFilterPrewittVert_32f_C1R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Single channel 32-bit floating-point vertical Prewitt filter.
- `NppStatus nppiFilterPrewittVert_32f_C3R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Three channel 32-bit floating-point vertical Prewitt filter.
- `NppStatus nppiFilterPrewittVert_32f_C4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Four channel 32-bit floating-point vertical Prewitt filter.
- `NppStatus nppiFilterPrewittVert_32f_AC4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Four channel 32-bit floating-point vertical Prewitt filter, ignoring alpha channel.

FilterScharrHoriz

Filters the image using a horizontal Scharr filter kernel:

$$\begin{pmatrix} 3 & 10 & 3 \\ 0 & 0 & 0 \\ -3 & -10 & -3 \end{pmatrix}$$

- `NppStatus nppiFilterScharrHoriz_8u16s_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Single channel 8-bit unsigned to 16-bit signed horizontal Scharr filter.
- `NppStatus nppiFilterScharrHoriz_8s16s_C1R` (const `Npp8s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Single channel 8-bit signed to 16-bit signed horizontal Scharr filter.
- `NppStatus nppiFilterScharrHoriz_32f_C1R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Single channel 32-bit floating-point horizontal Scharr filter.

FilterScharrVert

Filters the image using a vertical Scharr filter kernel:

$$\begin{pmatrix} 3 & 10 & 3 \\ 0 & 0 & 0 \\ -3 & -10 & -3 \end{pmatrix}$$

- `NppStatus nppiFilterScharrVert_8u16s_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Single channel 8-bit unsigned to 16-bit signed vertical Scharr filter.

- `NppStatus nppiFilterScharrVert_8s16s_C1R` (const `Npp8s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Single channel 8-bit signed to 16-bit signed vertical Scharr filter.
- `NppStatus nppiFilterScharrVert_32f_C1R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Single channel 32-bit floating-point vertical Scharr filter.

FilterSobelHoriz

Filters the image using a horizontal Sobel filter kernel:

$$\begin{pmatrix} 1 & 2 & 1 \\ 0 & 0 & 0 \\ -1 & -2 & -2 \end{pmatrix} \begin{pmatrix} 1 & 4 & 6 & 4 & 1 \\ 2 & 8 & 12 & 8 & 2 \\ 0 & 0 & 0 & 0 & 0 \\ -2 & -8 & -12 & -8 & -2 \\ -1 & -4 & -6 & -4 & -1 \end{pmatrix}$$

- `NppStatus nppiFilterSobelHoriz_8u_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Single channel 8-bit unsigned horizontal Sobel filter.
- `NppStatus nppiFilterSobelHoriz_8u_C3R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Three channel 8-bit unsigned horizontal Sobel filter.
- `NppStatus nppiFilterSobelHoriz_8u_C4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Four channel 8-bit unsigned horizontal Sobel filter.
- `NppStatus nppiFilterSobelHoriz_8u_AC4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Four channel 16-bit signed horizontal Sobel filter, ignoring alpha channel.
- `NppStatus nppiFilterSobelHoriz_16s_C1R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Single channel 16-bit signed horizontal Sobel filter.
- `NppStatus nppiFilterSobelHoriz_16s_C3R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Three channel 16-bit signed horizontal Sobel filter.
- `NppStatus nppiFilterSobelHoriz_16s_C4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Four channel 16-bit signed horizontal Sobel filter.
- `NppStatus nppiFilterSobelHoriz_16s_AC4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Four channel 8-bit unsigned horizontal Sobel filter, ignoring alpha channel.

- `NppStatus nppiFilterSobelHoriz_32f_C1R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Single channel 32-bit floating-point horizontal Sobel filter.

- `NppStatus nppiFilterSobelHoriz_32f_C3R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Three channel 32-bit floating-point horizontal Sobel filter.

- `NppStatus nppiFilterSobelHoriz_32f_C4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Four channel 32-bit floating-point horizontal Sobel filter.

- `NppStatus nppiFilterSobelHoriz_32f_AC4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Four channel 32-bit floating-point horizontal Sobel filter, ignoring alpha channel.

- `NppStatus nppiFilterSobelHoriz_8u16s_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)

Single channel 8-bit unsigned to 16-bit signed horizontal Sobel filter.

- `NppStatus nppiFilterSobelHoriz_8s16s_C1R` (const `Npp8s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)

Single channel 8-bit signed to 16-bit signed horizontal Sobel filter.

- `NppStatus nppiFilterSobelHorizMask_32f_C1R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)

Single channel 32-bit floating-point horizontal Sobel filter.

FilterSobelVert

Filters the image using a vertical Sobel filter kernel:

$$\begin{pmatrix} -1 & 0 & 1 \\ -2 & 0 & 2 \\ -1 & 0 & 1 \end{pmatrix} \begin{pmatrix} -1 & -2 & 0 & 2 & 1 \\ -4 & -8 & 0 & 8 & 4 \\ -6 & -12 & 0 & 12 & 6 \\ -4 & -8 & 0 & 8 & 4 \\ -1 & -2 & 0 & 2 & 1 \end{pmatrix}$$

- `NppStatus nppiFilterSobelVert_8u_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Single channel 8-bit unsigned vertical Sobel filter.

- `NppStatus nppiFilterSobelVert_8u_C3R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Three channel 8-bit unsigned vertical Sobel filter.

- `NppStatus nppiFilterSobelVert_8u_C4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Four channel 8-bit unsigned vertical Sobel filter.

- `NppStatus nppiFilterSobelVert_8u_AC4R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp8u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Four channel 16-bit signed vertical Sobel filter, ignoring alpha channel.

- `NppStatus nppiFilterSobelVert_16s_C1R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Single channel 16-bit signed vertical Sobel filter.

- `NppStatus nppiFilterSobelVert_16s_C3R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Three channel 16-bit signed vertical Sobel filter.

- `NppStatus nppiFilterSobelVert_16s_C4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Four channel 16-bit signed vertical Sobel filter.

- `NppStatus nppiFilterSobelVert_16s_AC4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Four channel 8-bit unsigned vertical Sobel filter, ignoring alpha channel.

- `NppStatus nppiFilterSobelVert_32f_C1R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Single channel 32-bit floating-point vertical Sobel filter.

- `NppStatus nppiFilterSobelVert_32f_C3R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Three channel 32-bit floating-point vertical Sobel filter.

- `NppStatus nppiFilterSobelVert_32f_C4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Four channel 32-bit floating-point vertical Sobel filter.

- `NppStatus nppiFilterSobelVert_32f_AC4R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Four channel 32-bit floating-point vertical Sobel filter, ignoring alpha channel.

- `NppStatus nppiFilterSobelVert_8u16s_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)

Single channel 8-bit unsigned to 16-bit signed vertical Sobel filter.

- `NppStatus nppiFilterSobelVert_8s16s_C1R` (const `Npp8s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)

Single channel 8-bit signed to 16-bit signed vertical Sobel filter.

- `NppStatus nppiFilterSobelVertMask_32f_C1R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)

Single channel 32-bit floating-point vertical Sobel filter.

FilterSobelHorizSecond

Filters the image using a second derivative, horizontal Sobel filter kernel:

$$\begin{pmatrix} 1 & 2 & 1 \\ -2 & -4 & -2 \\ 1 & 2 & 1 \end{pmatrix} \begin{pmatrix} 1 & 4 & 6 & 4 & 1 \\ 0 & 0 & 0 & 0 & 0 \\ -2 & -8 & -12 & -8 & -2 \\ 0 & 0 & 0 & 0 & 0 \\ 1 & 4 & 6 & 4 & 1 \end{pmatrix}$$

- `NppStatus nppiFilterSobelHorizSecond_8u16s_C1R` (const `Npp8u *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)

Single channel 8-bit unsigned to 16-bit signed second derivative, horizontal Sobel filter.

- `NppStatus nppiFilterSobelHorizSecond_8s16s_C1R` (const `Npp8s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)

Single channel 8-bit signed to 16-bit signed second derivative, horizontal Sobel filter.

- `NppStatus nppiFilterSobelHorizSecond_32f_C1R` (const `Npp32f *pSrc`, `Npp32s nSrcStep`, `Npp32f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, `NppiMaskSize eMaskSize`)

Single channel 32-bit floating-point second derivative, horizontal Sobel filter.

7.71.1 Detailed Description

Fixed filters perform linear filtering operations (i.e. convolutions) with predefined kernels of fixed sizes.

7.71.2 Function Documentation

7.71.2.1 `NppStatus nppiFilterPrewittHoriz_16s_AC4R` (const `Npp16s *pSrc`, `Npp32s nSrcStep`, `Npp16s *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Four channel 16-bit signed horizontal Prewitt filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.2 NppStatus nppiFilterPrewittHoriz_16s_C1R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single channel 16-bit signed horizontal Prewitt filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.3 NppStatus nppiFilterPrewittHoriz_16s_C3R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Three channel 16-bit signed horizontal Prewitt filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.4 NppStatus nppiFilterPrewittHoriz_16s_C4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 16-bit signed horizontal Prewitt filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.5 NppStatus nppiFilterPrewittHoriz_32f_AC4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 32-bit floating-point horizontal Prewitt filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.6 NppStatus nppiFilterPrewittHoriz_32f_C1R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single channel 32-bit floating-point horizontal Prewitt filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.7 NppStatus nppiFilterPrewittHoriz_32f_C3R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Three channel 32-bit floating-point horizontal Prewitt filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.8 NppStatus nppiFilterPrewittHoriz_32f_C4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 32-bit floating-point horizontal Prewitt filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.9 NppStatus nppiFilterPrewittHoriz_8u_AC4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 8-bit unsigned horizontal Prewitt filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.10 NppStatus nppiFilterPrewittHoriz_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single channel 8-bit unsigned horizontal Prewitt filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.11 NppStatus nppiFilterPrewittHoriz_8u_C3R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Three channel 8-bit unsigned horizontal Prewitt filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.12 NppStatus nppiFilterPrewittHoriz_8u_C4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 8-bit unsigned horizontal Prewitt filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.13 NppStatus nppiFilterPrewittVert_16s_AC4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 16-bit signed vertical Prewitt filter, ignoring alpha channel.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.14 NppStatus nppiFilterPrewittVert_16s_C1R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single channel 16-bit signed vertical Prewitt filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.15 NppStatus nppiFilterPrewittVert_16s_C3R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Three channel 16-bit signed vertical Prewitt filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.16 NppStatus nppiFilterPrewittVert_16s_C4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 16-bit signed vertical Prewitt filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.17 NppStatus nppiFilterPrewittVert_32f_AC4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 32-bit floating-point vertical Prewitt filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.18 NppStatus nppiFilterPrewittVert_32f_C1R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single channel 32-bit floating-point vertical Prewitt filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.19 NppStatus nppiFilterPrewittVert_32f_C3R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Three channel 32-bit floating-point vertical Prewitt filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.20 NppStatus nppiFilterPrewittVert_32f_C4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 32-bit floating-point vertical Prewitt filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.21 NppStatus nppiFilterPrewittVert_8u_AC4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 8-bit unsigned vertical Prewitt filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.22 NppStatus nppiFilterPrewittVert_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single channel 8-bit unsigned vertical Prewitt filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.23 NppStatus nppiFilterPrewittVert_8u_C3R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Three channel 8-bit unsigned vertical Prewitt filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.24 NppStatus nppiFilterPrewittVert_8u_C4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 8-bit unsigned vertical Prewitt filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.25 NppStatus nppiFilterScharHoriz_32f_C1R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single channel 32-bit floating-point horizontal Schar filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.26 NppStatus nppiFilterScharrHoriz_8s16s_C1R (const Npp8s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single channel 8-bit signed to 16-bit signed horizontal Scharr filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.27 NppStatus nppiFilterScharrHoriz_8u16s_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single channel 8-bit unsigned to 16-bit signed horizontal Scharr filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.28 NppStatus nppiFilterScharrVert_32f_C1R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single channel 32-bit floating-point vertical Scharr filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.29 NppStatus nppiFilterScharrVert_8s16s_C1R (const Npp8s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single channel 8-bit signed to 16-bit signed vertical Scharr filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.30 NppStatus nppiFilterScharrVert_8u16s_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single channel 8-bit unsigned to 16-bit signed vertical Scharr filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.31 NppStatus nppiFilterSobelHoriz_16s_AC4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 8-bit unsigned horizontal Sobel filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.32 NppStatus nppiFilterSobelHoriz_16s_C1R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single channel 16-bit signed horizontal Sobel filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.33 NppStatus nppiFilterSobelHoriz_16s_C3R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Three channel 16-bit signed horizontal Sobel filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.34 NppStatus nppiFilterSobelHoriz_16s_C4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 16-bit signed horizontal Sobel filter.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.35 NppStatus nppiFilterSobelHoriz_32f_AC4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 32-bit floating-point horizontal Sobel filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.36 NppStatus nppiFilterSobelHoriz_32f_C1R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single channel 32-bit floating-point horizontal Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.37 NppStatus nppiFilterSobelHoriz_32f_C3R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Three channel 32-bit floating-point horizontal Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.38 `NppStatus nppiFilterSobelHoriz_32f_C4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)`

Four channel 32-bit floating-point horizontal Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.39 `NppStatus nppiFilterSobelHoriz_8s16s_C1R (const Npp8s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Single channel 8-bit signed to 16-bit signed horizontal Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eMaskSize Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.40 `NppStatus nppiFilterSobelHoriz_8u16s_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Single channel 8-bit unsigned to 16-bit signed horizontal Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eMaskSize Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.41 NppStatus nppiFilterSobelHoriz_8u_AC4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 16-bit signed horizontal Sobel filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.42 NppStatus nppiFilterSobelHoriz_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single channel 8-bit unsigned horizontal Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.43 NppStatus nppiFilterSobelHoriz_8u_C3R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Three channel 8-bit unsigned horizontal Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.44 `NppStatus nppiFilterSobelHoriz_8u_C4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)`

Four channel 8-bit unsigned horizontal Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.45 `NppStatus nppiFilterSobelHorizMask_32f_C1R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Single channel 32-bit floating-point horizontal Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eMaskSize Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.46 `NppStatus nppiFilterSobelHorizSecond_32f_C1R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Single channel 32-bit floating-point second derivative, horizontal Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eMaskSize Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.47 `NppStatus nppiFilterSobelHorizSecond_8s16s_C1R (const Npp8s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Single channel 8-bit signed to 16-bit signed second derivative, horizontal Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eMaskSize Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.48 `NppStatus nppiFilterSobelHorizSecond_8u16s_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Single channel 8-bit unsigned to 16-bit signed second derivative, horizontal Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eMaskSize Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.49 `NppStatus nppiFilterSobelVert_16s_AC4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)`

Four channel 8-bit unsigned vertical Sobel filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.50 `NppStatus nppiFilterSobelVert_16s_C1R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)`

Single channel 16-bit signed vertical Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.51 `NppStatus nppiFilterSobelVert_16s_C3R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)`

Three channel 16-bit signed vertical Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.52 `NppStatus nppiFilterSobelVert_16s_C4R (const Npp16s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI)`

Four channel 16-bit signed vertical Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.53 NppStatus nppiFilterSobelVert_32f_AC4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Four channel 32-bit floating-point vertical Sobel filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.54 NppStatus nppiFilterSobelVert_32f_C1R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single channel 32-bit floating-point vertical Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.55 NppStatus nppiFilterSobelVert_32f_C3R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Three channel 32-bit floating-point vertical Sobel filter.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.56 `NppStatus nppiFilterSobelVert_32f_C4R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)`

Four channel 32-bit floating-point vertical Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.57 `NppStatus nppiFilterSobelVert_8s16s_C1R (const Npp8s * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Single channel 8-bit signed to 16-bit signed vertical Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eMaskSize Enumeration value specifying the mask size.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.58 `NppStatus nppiFilterSobelVert_8u16s_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp16s * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Single channel 8-bit unsigned to 16-bit signed vertical Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eMaskSize Enumeration value specifying the mask size.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.59 `NppStatus nppiFilterSobelVert_8u_AC4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)`

Four channel 16-bit signed vertical Sobel filter, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.60 `NppStatus nppiFilterSobelVert_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)`

Single channel 8-bit unsigned vertical Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.71.2.61 `NppStatus nppiFilterSobelVert_8u_C3R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)`

Three channel 8-bit unsigned vertical Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.62 `NppStatus nppiFilterSobelVert_8u_C4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)`

Four channel 8-bit unsigned vertical Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.71.2.63 `NppStatus nppiFilterSobelVertMask_32f_C1R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiMaskSize eMaskSize)`

Single channel 32-bit floating-point vertical Sobel filter.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eMaskSize Enumeration value specifying the mask size.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.72 Geometry Transforms

Routines manipulating an image's geometry.

Modules

- [ResizeSqrPixel](#)

ResizeSqrPixel supports the following interpolation modes:.

- [Resize](#)

This function has been deprecated.

- [Remap](#)

Remap supports the following interpolation modes:.

- [Rotate](#)

Rotates an image around the origin (0,0) and then shifts it.

- [Mirror](#)

- [Affine Transforms](#)

- [Perspective Transform](#)

7.72.1 Detailed Description

Routines manipulating an image's geometry.

7.72.2 Geometric Transform API Specifics

This section covers some of the unique API features common to the geometric transform primitives.

7.72.2.1 Geometric Transforms and ROIs

Geometric transforms operate on source and destination ROIs. The way these ROIs affect the processing of pixels differs from other (non geometric) image-processing primitives: Only pixels in the intersection of the destination ROI and the transformed source ROI are being processed.

The typical processing proceeds as follows:

1. Transform the rectangular source ROI (given in source image coordinates) into the destination image space. This yields a quadrilateral.
2. Write only pixels in the intersection of the transformed source ROI and the destination ROI.

7.72.2.2 Pixel Interpolation

The majority of image geometry transform operation need to perform a resampling of the source image as source and destination pixels are not coincident.

NPP supports the following pixel interpolation modes (in order from fastest to slowest and lowest to highest quality):

- nearest neighbor
- linear interpolation
- cubic convolution
- supersampling
- interpolation using Lanczos window function

7.73 ResizeSqrPixel

ResizeSqrPixel supports the following interpolation modes:.

GetResizeRect

Returns [NppiRect](#) which represents the offset and size of the destination rectangle that would be generated by resizing the source [NppiRect](#) by the requested scale factors and shifts.

- [NppStatus](#) [nppiGetResizeRect](#) ([NppiRect](#) oSrcROI, [NppiRect](#) *pDstRect, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)

ResizeSqrPixel

Resizes images.

- [NppStatus](#) [nppiResizeSqrPixel_8u_C1R](#) (const [Npp8u](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, [Npp8u](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
1 channel 8-bit unsigned image resize.
- [NppStatus](#) [nppiResizeSqrPixel_8u_C3R](#) (const [Npp8u](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, [Npp8u](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
3 channel 8-bit unsigned image resize.
- [NppStatus](#) [nppiResizeSqrPixel_8u_C4R](#) (const [Npp8u](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, [Npp8u](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 8-bit unsigned image resize.
- [NppStatus](#) [nppiResizeSqrPixel_8u_AC4R](#) (const [Npp8u](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, [Npp8u](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 8-bit unsigned image resize not affecting alpha.
- [NppStatus](#) [nppiResizeSqrPixel_8u_P3R](#) (const [Npp8u](#) *const pSrc[3], [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, [Npp8u](#) *pDst[3], int nDstStep, [NppiRect](#) oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
3 channel 8-bit unsigned planar image resize.
- [NppStatus](#) [nppiResizeSqrPixel_8u_P4R](#) (const [Npp8u](#) *const pSrc[4], [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, [Npp8u](#) *pDst[4], int nDstStep, [NppiRect](#) oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 8-bit unsigned planar image resize.
- [NppStatus](#) [nppiResizeSqrPixel_16u_C1R](#) (const [Npp16u](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, [Npp16u](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
1 channel 16-bit unsigned image resize.

- `NppStatus nppiResizeSqrPixel_16u_C3R` (const `Npp16u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
3 channel 16-bit unsigned image resize.
- `NppStatus nppiResizeSqrPixel_16u_C4R` (const `Npp16u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 16-bit unsigned image resize.
- `NppStatus nppiResizeSqrPixel_16u_AC4R` (const `Npp16u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 16-bit unsigned image resize not affecting alpha.
- `NppStatus nppiResizeSqrPixel_16u_P3R` (const `Npp16u` *const pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst[3], int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
3 channel 16-bit unsigned planar image resize.
- `NppStatus nppiResizeSqrPixel_16u_P4R` (const `Npp16u` *const pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst[4], int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 16-bit unsigned planar image resize.
- `NppStatus nppiResizeSqrPixel_16s_C1R` (const `Npp16s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16s` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
1 channel 16-bit signed image resize.
- `NppStatus nppiResizeSqrPixel_16s_C3R` (const `Npp16s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16s` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
3 channel 16-bit signed image resize.
- `NppStatus nppiResizeSqrPixel_16s_C4R` (const `Npp16s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16s` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 16-bit signed image resize.
- `NppStatus nppiResizeSqrPixel_16s_AC4R` (const `Npp16s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16s` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 16-bit signed image resize not affecting alpha.
- `NppStatus nppiResizeSqrPixel_16s_P3R` (const `Npp16s` *const pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16s` *pDst[3], int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
3 channel 16-bit signed planar image resize.

- `NppStatus nppiResizeSqrPixel_16s_P4R` (const `Npp16s` *const pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16s` *pDst[4], int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 16-bit signed planar image resize.
- `NppStatus nppiResizeSqrPixel_32f_C1R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
1 channel 32-bit floating point image resize.
- `NppStatus nppiResizeSqrPixel_32f_C3R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
3 channel 32-bit floating point image resize.
- `NppStatus nppiResizeSqrPixel_32f_C4R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 32-bit floating point image resize.
- `NppStatus nppiResizeSqrPixel_32f_AC4R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 32-bit floating point image resize not affecting alpha.
- `NppStatus nppiResizeSqrPixel_32f_P3R` (const `Npp32f` *const pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst[3], int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
3 channel 32-bit floating point planar image resize.
- `NppStatus nppiResizeSqrPixel_32f_P4R` (const `Npp32f` *const pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst[4], int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 32-bit floating point planar image resize.
- `NppStatus nppiResizeSqrPixel_64f_C1R` (const `Npp64f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp64f` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
1 channel 64-bit floating point image resize.
- `NppStatus nppiResizeSqrPixel_64f_C3R` (const `Npp64f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp64f` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
3 channel 64-bit floating point image resize.
- `NppStatus nppiResizeSqrPixel_64f_C4R` (const `Npp64f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp64f` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 64-bit floating point image resize.

- `NppStatus nppiResizeSqrPixel_64f_AC4R` (const `Npp64f *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp64f *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, double `nXFactor`, double `nYFactor`, double `nXShift`, double `nYShift`, int `eInterpolation`)
4 channel 64-bit floating point image resize not affecting alpha.
- `NppStatus nppiResizeSqrPixel_64f_P3R` (const `Npp64f *const pSrc[3]`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp64f *pDst[3]`, int `nDstStep`, `NppiRect` `oDstROI`, double `nXFactor`, double `nYFactor`, double `nXShift`, double `nYShift`, int `eInterpolation`)
3 channel 64-bit floating point planar image resize.
- `NppStatus nppiResizeSqrPixel_64f_P4R` (const `Npp64f *const pSrc[4]`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp64f *pDst[4]`, int `nDstStep`, `NppiRect` `oDstROI`, double `nXFactor`, double `nYFactor`, double `nXShift`, double `nYShift`, int `eInterpolation`)
4 channel 64-bit floating point planar image resize.

7.73.1 Detailed Description

`ResizeSqrPixel` supports the following interpolation modes:

```
NPPI_INTER_NN
NPPI_INTER_LINEAR
NPPI_INTER_CUBIC
NPPI_INTER_CUBIC2P_BSPLINE
NPPI_INTER_CUBIC2P_CATMULLROM
NPPI_INTER_CUBIC2P_B05C03
NPPI_INTER_SUPER
NPPI_INTER_LANCZOS
```

`ResizeSqrPixel` attempts to choose source pixels that would approximately represent the center of the destination pixels. It does so by using the following scaling formula to select source pixels for interpolation:

```
nAdjustedXFactor = 1.0 / nXFactor;
nAdjustedYFactor = 1.0 / nYFactor;
nAdjustedXShift = nXShift * nAdjustedXFactor + ((1.0 - nAdjustedXFactor) * 0.5);
nAdjustedYShift = nYShift * nAdjustedYFactor + ((1.0 - nAdjustedYFactor) * 0.5);
nSrcX = nAdjustedXFactor * nDstX - nAdjustedXShift;
nSrcY = nAdjustedYFactor * nDstY - nAdjustedYShift;
```

In the `ResizeSqrPixel` functions below source image clip checking is handled as follows:

If the source pixel fractional `x` and `y` coordinates are greater than or equal to `oSizeROI.x` and less than `oSizeROI.x + oSizeROI.width` and greater than or equal to `oSizeROI.y` and less than `oSizeROI.y + oSizeROI.height` then the source pixel is considered to be within the source image clip rectangle and the source image is sampled. Otherwise the source image is not sampled and a destination pixel is not written to the destination image.

7.73.2 Error Codes

The resize primitives return the following error codes:

- `NPP_WRONG_INTERSECTION_ROI_ERROR` indicates an error condition if `srcROIRect` has no intersection with the source image.

- [NPP_RESIZE_NO_OPERATION_ERROR](#) if either destination ROI width or height is less than 1 pixel.
- [NPP_RESIZE_FACTOR_ERROR](#) Indicates an error condition if either `nXFactor` or `nYFactor` is less than or equal to zero.
- [NPP_INTERPOLATION_ERROR](#) if `eInterpolation` has an illegal value.

7.73.3 Function Documentation

7.73.3.1 `NppStatus nppiGetResizeRect (NppiRect oSrcROI, NppiRect * pDstRect, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

Parameters:

- oSrcROI* Region of interest in the source image.
- pDstRect* User supplied host memory pointer to an [NppiRect](#) structure that will be filled in by this function with the region of interest in the destination image.
- nXFactor* Factor by which x dimension is changed.
- nYFactor* Factor by which y dimension is changed.
- nXShift* Source pixel shift in x-direction.
- nYShift* Source pixel shift in y-direction.
- eInterpolation* The type of `eInterpolation` to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.2 `NppStatus nppiResizeSqrPixel_16s_AC4R (const Npp16s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16s * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

4 channel 16-bit signed image resize not affecting alpha.

Parameters:

- pSrc* [Source-Image Pointer](#).
- nSrcStep* [Source-Image Line Step](#).
- oSrcSize* Size in pixels of the source image.
- oSrcROI* Region of interest in the source image.
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oDstROI* Region of interest in the destination image.
- nXFactor* Factor by which x dimension is changed.
- nYFactor* Factor by which y dimension is changed.
- nXShift* Source pixel shift in x-direction.
- nYShift* Source pixel shift in y-direction.
- eInterpolation* The type of interpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.3 NppStatus nppiResizeSqrPixel_16s_C1R (const Npp16s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16s * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)

1 channel 16-bit signed image resize.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.4 NppStatus nppiResizeSqrPixel_16s_C3R (const Npp16s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16s * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)

3 channel 16-bit signed image resize.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.5 NppStatus nppiResizeSqrPixel_16s_C4R (const Npp16s * *pSrc*, NppiSize *oSrcSize*, int *nSrcStep*, NppiRect *oSrcROI*, Npp16s * *pDst*, int *nDstStep*, NppiRect *oDstROI*, double *nXFactor*, double *nYFactor*, double *nXShift*, double *nYShift*, int *eInterpolation*)

4 channel 16-bit signed image resize.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of [eInterpolation](#) to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.6 NppStatus nppiResizeSqrPixel_16s_P3R (const Npp16s *const *pSrc*[3], NppiSize *oSrcSize*, int *nSrcStep*, NppiRect *oSrcROI*, Npp16s * *pDst*[3], int *nDstStep*, NppiRect *oDstROI*, double *nXFactor*, double *nYFactor*, double *nXShift*, double *nYShift*, int *eInterpolation*)

3 channel 16-bit signed planar image resize.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.7 `NppStatus nppiResizeSqrPixel_16s_P4R (const Npp16s *const pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16s *pDst[4], int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

4 channel 16-bit signed planar image resize.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.8 `NppStatus nppiResizeSqrPixel_16u_AC4R (const Npp16u *pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u *pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

4 channel 16-bit unsigned image resize not affecting alpha.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep Destination-Image Line Step.
oDstROI Region of interest in the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
nXShift Source pixel shift in x-direction.
nYShift Source pixel shift in y-direction.
eInterpolation The type of interpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.9 `NppStatus nppiResizeSqrPixel_16u_C1R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

1 channel 16-bit unsigned image resize.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSize Size in pixels of the source image.
oSrcROI Region of interest in the source image.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstROI Region of interest in the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
nXShift Source pixel shift in x-direction.
nYShift Source pixel shift in y-direction.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.10 `NppStatus nppiResizeSqrPixel_16u_C3R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

3 channel 16-bit unsigned image resize.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.11 `NppStatus nppiResizeSqrPixel_16u_C4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

4 channel 16-bit unsigned image resize.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.12 NppStatus nppiResizeSqrPixel_16u_P3R (const Npp16u *const *pSrc*[3], NppiSize *oSrcSize*, int *nSrcStep*, NppiRect *oSrcROI*, Npp16u **pDst*[3], int *nDstStep*, NppiRect *oDstROI*, double *nXFactor*, double *nYFactor*, double *nXShift*, double *nYShift*, int *eInterpolation*)

3 channel 16-bit unsigned planar image resize.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of *eInterpolation* to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.13 NppStatus nppiResizeSqrPixel_16u_P4R (const Npp16u *const *pSrc*[4], NppiSize *oSrcSize*, int *nSrcStep*, NppiRect *oSrcROI*, Npp16u **pDst*[4], int *nDstStep*, NppiRect *oDstROI*, double *nXFactor*, double *nYFactor*, double *nXShift*, double *nYShift*, int *eInterpolation*)

4 channel 16-bit unsigned planar image resize.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.
nXShift Source pixel shift in x-direction.
nYShift Source pixel shift in y-direction.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.14 `NppStatus nppiResizeSqrPixel_32f_AC4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

4 channel 32-bit floating point image resize not affecting alpha.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image.
oSrcROI Region of interest in the source image.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oDstROI Region of interest in the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
nXShift Source pixel shift in x-direction.
nYShift Source pixel shift in y-direction.
eInterpolation The type of interpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.15 `NppStatus nppiResizeSqrPixel_32f_C1R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

1 channel 32-bit floating point image resize.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image.
oSrcROI Region of interest in the source image.
pDst [Destination-Image Pointer](#).

nDstStep Destination-Image Line Step.
oDstROI Region of interest in the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
nXShift Source pixel shift in x-direction.
nYShift Source pixel shift in y-direction.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.16 `NppStatus nppiResizeSqrPixel_32f_C3R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

3 channel 32-bit floating point image resize.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSize Size in pixels of the source image.
oSrcROI Region of interest in the source image.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstROI Region of interest in the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
nXShift Source pixel shift in x-direction.
nYShift Source pixel shift in y-direction.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.17 `NppStatus nppiResizeSqrPixel_32f_C4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

4 channel 32-bit floating point image resize.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.

oSrcSize Size in pixels of the source image.
oSrcROI Region of interest in the source image.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oDstROI Region of interest in the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
nXShift Source pixel shift in x-direction.
nYShift Source pixel shift in y-direction.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.18 `NppStatus nppiResizeSqrPixel_32f_P3R (const Npp32f *const pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f *pDst[3], int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

3 channel 32-bit floating point planar image resize.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image.
oSrcROI Region of interest in the source image.
pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).
nDstStep [Destination-Image Line Step](#).
oDstROI Region of interest in the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
nXShift Source pixel shift in x-direction.
nYShift Source pixel shift in y-direction.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.19 `NppStatus nppiResizeSqrPixel_32f_P4R (const Npp32f *const pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f *pDst[4], int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

4 channel 32-bit floating point planar image resize.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.20 `NppStatus nppiResizeSqrPixel_64f_AC4R (const Npp64f *pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp64f *pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

4 channel 64-bit floating point image resize not affecting alpha.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of interpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.21 `NppStatus nppiResizeSqrPixel_64f_C1R (const Npp64f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp64f * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

1 channel 64-bit floating point image resize.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.22 `NppStatus nppiResizeSqrPixel_64f_C3R (const Npp64f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp64f * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

3 channel 64-bit floating point image resize.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.
nXShift Source pixel shift in x-direction.
nYShift Source pixel shift in y-direction.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.23 `NppStatus nppiResizeSqrPixel_64f_C4R (const Npp64f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp64f * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

4 channel 64-bit floating point image resize.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image.
oSrcROI Region of interest in the source image.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oDstROI Region of interest in the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
nXShift Source pixel shift in x-direction.
nYShift Source pixel shift in y-direction.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.24 `NppStatus nppiResizeSqrPixel_64f_P3R (const Npp64f *const pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp64f * pDst[3], int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

3 channel 64-bit floating point planar image resize.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.25 `NppStatus nppiResizeSqrPixel_64f_P4R (const Npp64f *const pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp64f *pDst[4], int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

4 channel 64-bit floating point planar image resize.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.26 `NppStatus nppiResizeSqrPixel_8u_AC4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

4 channel 8-bit unsigned image resize not affecting alpha.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of interpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.27 `NppStatus nppiResizeSqrPixel_8u_C1R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

1 channel 8-bit unsigned image resize.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.28 `NppStatus nppiResizeSqrPixel_8u_C3R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

3 channel 8-bit unsigned image resize.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.3.29 `NppStatus nppiResizeSqrPixel_8u_C4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

4 channel 8-bit unsigned image resize.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.330 `NppStatus nppiResizeSqrPixel_8u_P3R (const Npp8u *const pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u *pDst[3], int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

3 channel 8-bit unsigned planar image resize.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.73.331 `NppStatus nppiResizeSqrPixel_8u_P4R (const Npp8u *const pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u *pDst[4], int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

4 channel 8-bit unsigned planar image resize.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.74 Resize

This function has been deprecated.

Resize

Resizes images.

- `NppStatus nppiResize_8u_C1R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp8u` *pDst, int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)
1 channel 8-bit unsigned image resize.
- `NppStatus nppiResize_8u_C3R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp8u` *pDst, int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)
3 channel 8-bit unsigned image resize.
- `NppStatus nppiResize_8u_C4R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp8u` *pDst, int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)
4 channel 8-bit unsigned image resize.
- `NppStatus nppiResize_8u_AC4R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp8u` *pDst, int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)
4 channel 8-bit unsigned image resize not affecting alpha.
- `NppStatus nppiResize_8u_P3R` (const `Npp8u` *const pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp8u` *pDst[3], int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)
3 channel 8-bit unsigned planar image resize.
- `NppStatus nppiResize_8u_P4R` (const `Npp8u` *const pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp8u` *pDst[4], int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)
4 channel 8-bit unsigned planar image resize.
- `NppStatus nppiResize_16u_C1R` (const `Npp16u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst, int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)
1 channel 16-bit unsigned image resize.
- `NppStatus nppiResize_16u_C3R` (const `Npp16u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst, int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)
3 channel 16-bit unsigned image resize.
- `NppStatus nppiResize_16u_C4R` (const `Npp16u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst, int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)

4 channel 16-bit unsigned image resize.

- `NppStatus nppiResize_16u_AC4R` (const `Npp16u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst, int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)

4 channel 16-bit unsigned image resize not affecting alpha.

- `NppStatus nppiResize_16u_P3R` (const `Npp16u` *const pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst[3], int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)

3 channel 16-bit unsigned planar image resize.

- `NppStatus nppiResize_16u_P4R` (const `Npp16u` *const pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst[4], int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)

4 channel 16-bit unsigned planar image resize.

- `NppStatus nppiResize_32f_C1R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)

1 channel 32-bit floating point image resize.

- `NppStatus nppiResize_32f_C3R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)

3 channel 32-bit floating point image resize.

- `NppStatus nppiResize_32f_C4R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)

4 channel 32-bit floating point image resize.

- `NppStatus nppiResize_32f_AC4R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)

4 channel 32-bit floating point image resize not affecting alpha.

- `NppStatus nppiResize_32f_P3R` (const `Npp32f` *const pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst[3], int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)

3 channel 32-bit floating point planar image resize.

- `NppStatus nppiResize_32f_P4R` (const `Npp32f` *const pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst[4], int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)

4 channel 32-bit floating point planar image resize.

7.74.1 Detailed Description

This function has been deprecated.

ResizeSqrPixel provides the same functionality and more.

Resize supports the following interpolation modes:

```
NPPI_INTER_NN
NPPI_INTER_LINEAR
NPPI_INTER_CUBIC
NPPI_INTER_SUPER
NPPI_INTER_LANCZOS
```

Resize uses the following scaling formula to select source pixels for interpolation:

```
scaledSrcSize.width = nXFactor * srcRectROI.width;
scaledSrcSize.height = nYFactor * srcRectROI.height;
nAdjustedXFactor = (srcRectROI.width - 1) / (scaledSrcSize.width - 1);
nAdjustedYFactor = (srcRectROI.height - 1) / (scaledSrcSize.height - 1);
nSrcX = nAdjustedXFactor * nDstX;
nSrcY = nAdjustedYFactor * nDstY;
```

In the Resize functions below source image clip checking is handled as follows:

If the source pixel fractional x and y coordinates are greater than or equal to $oSizeROI.x$ and less than $oSizeROI.x + oSizeROI.width$ and greater than or equal to $oSizeROI.y$ and less than $oSizeROI.y + oSizeROI.height$ then the source pixel is considered to be within the source image clip rectangle and the source image is sampled. Otherwise the source image is not sampled and a destination pixel is not written to the destination image.

7.74.2 Error Codes

The resize primitives return the following error codes:

- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) indicates an error condition if `srcROIRect` has no intersection with the source image.
- [NPP_RESIZE_NO_OPERATION_ERROR](#) if either destination ROI width or height is less than 1 pixel.
- [NPP_RESIZE_FACTOR_ERROR](#) Indicates an error condition if either `nXFactor` or `nYFactor` is less than or equal to zero.
- [NPP_INTERPOLATION_ERROR](#) if `eInterpolation` has an illegal value.

7.74.3 Function Documentation

7.74.3.1 NppStatus nppiResize_16u_AC4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)

4 channel 16-bit unsigned image resize not affecting alpha.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- oSrcSize* Size in pixels of the source image

oSrcROI Region of interest in the source image.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of interpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.74.3.2 NppStatus nppiResize_16u_C1R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)

1 channel 16-bit unsigned image resize.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.74.3.3 NppStatus nppiResize_16u_C3R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)

3 channel 16-bit unsigned image resize.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.

pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, Error Codes

7.74.3.4 `NppStatus nppiResize_16u_C4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)`

4 channel 16-bit unsigned image resize.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, Error Codes

7.74.3.5 `NppStatus nppiResize_16u_P3R (const Npp16u *const pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst[3], int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)`

3 channel 16-bit unsigned planar image resize.

Parameters:

pSrc Source-Planar-Image Pointer Array (host memory array containing device memory image plane pointers).
nSrcStep Source-Image Line Step.
oSrcSize Size in pixels of the source image.
oSrcROI Region of interest in the source image.

pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nDstStep [Destination-Image Line Step](#).

dstROISize Size in pixels of the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.74.3.6 `NppStatus nppiResize_16u_P4R (const Npp16u *const pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst[4], int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)`

4 channel 16-bit unsigned planar image resize.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nDstStep [Destination-Image Line Step](#).

dstROISize Size in pixels of the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.74.3.7 `NppStatus nppiResize_32f_AC4R (const Npp32f *pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)`

4 channel 32-bit floating point image resize not affecting alpha.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of interpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.74.3.8 `NppStatus nppiResize_32f_C1R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)`

1 channel 32-bit floating point image resize.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.74.3.9 `NppStatus nppiResize_32f_C3R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)`

3 channel 32-bit floating point image resize.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSize Size in pixels of the source image

oSrcROI Region of interest in the source image.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.74.3.10 **NppStatus nppiResize_32f_C4R** (const Npp32f * *pSrc*, NppiSize *oSrcSize*, int *nSrcStep*, NppiRect *oSrcROI*, Npp32f * *pDst*, int *nDstStep*, NppiSize *dstROISize*, double *nXFactor*, double *nYFactor*, int *eInterpolation*)

4 channel 32-bit floating point image resize.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.74.3.11 **NppStatus nppiResize_32f_P3R** (const Npp32f *const *pSrc*[3], NppiSize *oSrcSize*, int *nSrcStep*, NppiRect *oSrcROI*, Npp32f * *pDst*[3], int *nDstStep*, NppiSize *dstROISize*, double *nXFactor*, double *nYFactor*, int *eInterpolation*)

3 channel 32-bit floating point planar image resize.

Parameters:

pSrc Source-Planar-Image Pointer Array (host memory array containing device memory image plane pointers).
nSrcStep Source-Image Line Step.
oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nDstStep [Destination-Image Line Step](#).

dstROISize Size in pixels of the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.74.3.12 `NppStatus nppiResize_32f_P4R (const Npp32f *const pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f *pDst[4], int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)`

4 channel 32-bit floating point planar image resize.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nDstStep [Destination-Image Line Step](#).

dstROISize Size in pixels of the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.74.3.13 `NppStatus nppiResize_8u_AC4R (const Npp8u *pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u *pDst, int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)`

4 channel 8-bit unsigned image resize not affecting alpha.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of interpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.74.3.14 `NppStatus nppiResize_8u_C1R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)`

1 channel 8-bit unsigned image resize.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.74.3.15 `NppStatus nppiResize_8u_C3R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)`

3 channel 8-bit unsigned image resize.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.74.3.16 `NppStatus nppiResize_8u_C4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)`

4 channel 8-bit unsigned image resize.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.74.3.17 `NppStatus nppiResize_8u_P3R (const Npp8u *const pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst[3], int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)`

3 channel 8-bit unsigned planar image resize.

Parameters:

pSrc Source-Planar-Image Pointer Array (host memory array containing device memory image plane pointers).
nSrcStep Source-Image Line Step.

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nDstStep [Destination-Image Line Step](#).

dstROISize Size in pixels of the destination image

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.74.3.18 NppStatus nppiResize_8u_P4R (const Npp8u *const pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst[4], int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)

4 channel 8-bit unsigned planar image resize.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nDstStep [Destination-Image Line Step](#).

dstROISize Size in pixels of the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75 Remap

Remap supports the following interpolation modes:

Remap

Remaps images.

- `NppStatus nppiRemap_8u_C1R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)
1 channel 8-bit unsigned image remap.
- `NppStatus nppiRemap_8u_C3R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)
3 channel 8-bit unsigned image remap.
- `NppStatus nppiRemap_8u_C4R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)
4 channel 8-bit unsigned image remap.
- `NppStatus nppiRemap_8u_AC4R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)
4 channel 8-bit unsigned image remap not affecting alpha.
- `NppStatus nppiRemap_8u_P3R` (const `Npp8u` *const pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp8u` *pDst[3], int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)
3 channel 8-bit unsigned planar image remap.
- `NppStatus nppiRemap_8u_P4R` (const `Npp8u` *const pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp8u` *pDst[4], int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)
4 channel 8-bit unsigned planar image remap.
- `NppStatus nppiRemap_16u_C1R` (const `Npp16u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)
1 channel 16-bit unsigned image remap.
- `NppStatus nppiRemap_16u_C3R` (const `Npp16u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)
3 channel 16-bit unsigned image remap.
- `NppStatus nppiRemap_16u_C4R` (const `Npp16u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)

4 channel 16-bit unsigned image remap.

- `NppStatus nppiRemap_16u_AC4R` (const `Npp16u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)

4 channel 16-bit unsigned image remap not affecting alpha.

- `NppStatus nppiRemap_16u_P3R` (const `Npp16u` *const pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp16u` *pDst[3], int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)

3 channel 16-bit unsigned planar image remap.

- `NppStatus nppiRemap_16u_P4R` (const `Npp16u` *const pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp16u` *pDst[4], int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)

4 channel 16-bit unsigned planar image remap.

- `NppStatus nppiRemap_16s_C1R` (const `Npp16s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)

1 channel 16-bit signed image remap.

- `NppStatus nppiRemap_16s_C3R` (const `Npp16s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)

3 channel 16-bit signed image remap.

- `NppStatus nppiRemap_16s_C4R` (const `Npp16s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)

4 channel 16-bit signed image remap.

- `NppStatus nppiRemap_16s_AC4R` (const `Npp16s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)

4 channel 16-bit signed image remap not affecting alpha.

- `NppStatus nppiRemap_16s_P3R` (const `Npp16s` *const pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp16s` *pDst[3], int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)

3 channel 16-bit signed planar image remap.

- `NppStatus nppiRemap_16s_P4R` (const `Npp16s` *const pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp16s` *pDst[4], int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)

4 channel 16-bit signed planar image remap.

- `NppStatus nppiRemap_32f_C1R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)

1 channel 32-bit floating point image remap.

- **NppStatus nppiRemap_32f_C3R** (const **Npp32f** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, const **Npp32f** *pXMap, int nXMapStep, const **Npp32f** *pYMap, int nYMapStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int eInterpolation)
3 channel 32-bit floating point image remap.
- **NppStatus nppiRemap_32f_C4R** (const **Npp32f** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, const **Npp32f** *pXMap, int nXMapStep, const **Npp32f** *pYMap, int nYMapStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int eInterpolation)
4 channel 32-bit floating point image remap.
- **NppStatus nppiRemap_32f_AC4R** (const **Npp32f** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, const **Npp32f** *pXMap, int nXMapStep, const **Npp32f** *pYMap, int nYMapStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int eInterpolation)
4 channel 32-bit floating point image remap not affecting alpha.
- **NppStatus nppiRemap_32f_P3R** (const **Npp32f** *const pSrc[3], **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, const **Npp32f** *pXMap, int nXMapStep, const **Npp32f** *pYMap, int nYMapStep, **Npp32f** *pDst[3], int nDstStep, **NppiSize** oDstSizeROI, int eInterpolation)
3 channel 32-bit floating point planar image remap.
- **NppStatus nppiRemap_32f_P4R** (const **Npp32f** *const pSrc[4], **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, const **Npp32f** *pXMap, int nXMapStep, const **Npp32f** *pYMap, int nYMapStep, **Npp32f** *pDst[4], int nDstStep, **NppiSize** oDstSizeROI, int eInterpolation)
4 channel 32-bit floating point planar image remap.
- **NppStatus nppiRemap_64f_C1R** (const **Npp64f** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, const **Npp64f** *pXMap, int nXMapStep, const **Npp64f** *pYMap, int nYMapStep, **Npp64f** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int eInterpolation)
1 channel 64-bit floating point image remap.
- **NppStatus nppiRemap_64f_C3R** (const **Npp64f** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, const **Npp64f** *pXMap, int nXMapStep, const **Npp64f** *pYMap, int nYMapStep, **Npp64f** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int eInterpolation)
3 channel 64-bit floating point image remap.
- **NppStatus nppiRemap_64f_C4R** (const **Npp64f** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, const **Npp64f** *pXMap, int nXMapStep, const **Npp64f** *pYMap, int nYMapStep, **Npp64f** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int eInterpolation)
4 channel 64-bit floating point image remap.
- **NppStatus nppiRemap_64f_AC4R** (const **Npp64f** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, const **Npp64f** *pXMap, int nXMapStep, const **Npp64f** *pYMap, int nYMapStep, **Npp64f** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int eInterpolation)
4 channel 64-bit floating point image remap not affecting alpha.
- **NppStatus nppiRemap_64f_P3R** (const **Npp64f** *const pSrc[3], **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, const **Npp64f** *pXMap, int nXMapStep, const **Npp64f** *pYMap, int nYMapStep, **Npp64f** *pDst[3], int nDstStep, **NppiSize** oDstSizeROI, int eInterpolation)
3 channel 64-bit floating point planar image remap.

- `NppStatus nppiRemap_64f_P4R` (const `Npp64f *const pSrc[4]`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, const `Npp64f *pXMap`, int `nXMapStep`, const `Npp64f *pYMap`, int `nYMapStep`, `Npp64f *pDst[4]`, int `nDstStep`, `NppiSize oDstSizeROI`, int `eInterpolation`)

4 channel 64-bit floating point planar image remap.

7.75.1 Detailed Description

Remap supports the following interpolation modes:

NPPI_INTER_NN NPPI_INTER_LINEAR NPPI_INTER_CUBIC NPPI_INTER_CUBIC2P_BSPLINE
NPPI_INTER_CUBIC2P_CATMULLROM NPPI_INTER_CUBIC2P_B05C03 NPPI_INTER_-
LANCZOS

Remap chooses source pixels using pixel coordinates explicitly supplied in two 2D device memory image arrays pointed to by the `pXMap` and `pYMap` pointers. The `pXMap` array contains the X coordinated and the `pYMap` array contains the Y coordinate of the corresponding source image pixel to use as input. These coordinates are in floating point format so fraction pixel positions can be used. The coordinates of the source pixel to sample are determined as follows:

$$nSrcX = pxMap[nDstX, nDstY] \quad nSrcY = pyMap[nDstX, nDstY]$$

In the Remap functions below source image clip checking is handled as follows:

If the source pixel fractional `x` and `y` coordinates are greater than or equal to `oSizeROI.x` and less than `oSizeROI.x + oSizeROI.width` and greater than or equal to `oSizeROI.y` and less than `oSizeROI.y + oSizeROI.height` then the source pixel is considered to be within the source image clip rectangle and the source image is sampled. Otherwise the source image is not sampled and a destination pixel is not written to the destination image.

7.75.2 Error Codes

The remap primitives return the following error codes:

- `NPP_WRONG_INTERSECTION_ROI_ERROR` indicates an error condition if `srcROIrect` has no intersection with the source image.
- `NPP_RESIZE_NO_OPERATION_ERROR` if either destination ROI width or height is less than 1 pixel.
- `NPP_RESIZE_FACTOR_ERROR` Indicates an error condition if either `nXFactor` or `nYFactor` is less than or equal to zero.
- `NPP_INTERPOLATION_ERROR` if `eInterpolation` has an illegal value.

7.75.3 Function Documentation

7.75.3.1 `NppStatus nppiRemap_16s_AC4R` (const `Npp16s *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, const `Npp32f *pXMap`, int `nXMapStep`, const `Npp32f *pYMap`, int `nYMapStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oDstSizeROI`, int `eInterpolation`)

4 channel 16-bit signed image remap not affecting alpha.

Parameters:

- pSrc* [Source-Image Pointer](#).
- nSrcStep* [Source-Image Line Step](#).
- oSrcSize* Size in pixels of the source image.
- oSrcROI* Region of interest in the source image.
- pXMap* Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.
- nXMapStep* pXMap image array line step in bytes.
- pYMap* Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.
- nYMapStep* pYMap image array line step in bytes.
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oDstSizeROI* Region of interest size in the destination image.
- eInterpolation* The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.2 `NppStatus nppiRemap_16s_C1R (const Npp16s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp16s * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

1 channel 16-bit signed image remap.

Parameters:

- pSrc* [Source-Image Pointer](#).
- nSrcStep* [Source-Image Line Step](#).
- oSrcSize* Size in pixels of the source image.
- oSrcROI* Region of interest in the source image.
- pXMap* Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.
- nXMapStep* pXMap image array line step in bytes.
- pYMap* Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.
- nYMapStep* pYMap image array line step in bytes.
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oDstSizeROI* Region of interest size in the destination image.
- eInterpolation* The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.3 NppStatus nppiRemap_16s_C3R (const Npp16s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp16s * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)

3 channel 16-bit signed image remap.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.4 NppStatus nppiRemap_16s_C4R (const Npp16s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp16s * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)

4 channel 16-bit signed image remap.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.5 `NppStatus nppiRemap_16s_P3R (const Npp16s *const pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f *pXMap, int nXMapStep, const Npp32f *pYMap, int nYMapStep, Npp16s *pDst[3], int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

3 channel 16-bit signed planar image remap.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Planar-Image Pointer Array](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.6 `NppStatus nppiRemap_16s_P4R (const Npp16s *const pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f *pXMap, int nXMapStep, const Npp32f *pYMap, int nYMapStep, Npp16s *pDst[4], int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

4 channel 16-bit signed planar image remap.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst Destination-Planar-Image Pointer Array.

nDstStep Destination-Image Line Step.

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.7 NppStatus nppiRemap_16u_AC4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)

4 channel 16-bit unsigned image remap not affecting alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of interpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.8 `NppStatus nppiRemap_16u_C1R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

1 channel 16-bit unsigned image remap.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep *pXMap* image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep *pYMap* image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of *eInterpolation* to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.9 `NppStatus nppiRemap_16u_C3R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

3 channel 16-bit unsigned image remap.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep *pXMap* image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep *pYMap* image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.10 `NppStatus nppiRemap_16u_C4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

4 channel 16-bit unsigned image remap.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.11 `NppStatus nppiRemap_16u_P3R (const Npp16u *const pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp16u * pDst[3], int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

3 channel 16-bit unsigned planar image remap.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst Destination-Planar-Image Pointer Array.

nDstStep Destination-Image Line Step.

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.12 `NppStatus nppiRemap_16u_P4R (const Npp16u *const pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f *pXMap, int nXMapStep, const Npp32f *pYMap, int nYMapStep, Npp16u *pDst[4], int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

4 channel 16-bit unsigned planar image remap.

Parameters:

pSrc Source-Planar-Image Pointer Array.

nSrcStep Source-Image Line Step.

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst Destination-Planar-Image Pointer Array.

nDstStep Destination-Image Line Step.

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.13 `NppStatus nppiRemap_32f_AC4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp32f * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

4 channel 32-bit floating point image remap not affecting alpha.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.14 `NppStatus nppiRemap_32f_C1R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp32f * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

1 channel 32-bit floating point image remap.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep Destination-Image Line Step.

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling

Returns:

Image Data Related Error Codes, ROI Related Error Codes, Error Codes

7.75.3.15 `NppStatus nppiRemap_32f_C3R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp32f * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

3 channel 32-bit floating point image remap.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling

Returns:

Image Data Related Error Codes, ROI Related Error Codes, Error Codes

7.75.3.16 `NppStatus nppiRemap_32f_C4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp32f * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

4 channel 32-bit floating point image remap.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.17 `NppStatus nppiRemap_32f_P3R (const Npp32f *const pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f *pXMap, int nXMapStep, const Npp32f *pYMap, int nYMapStep, Npp32f *pDst[3], int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

3 channel 32-bit floating point planar image remap.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Planar-Image Pointer Array](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.18 `NppStatus nppiRemap_32f_P4R (const Npp32f *const pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f *pXMap, int nXMapStep, const Npp32f *pYMap, int nYMapStep, Npp32f *pDst[4], int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

4 channel 32-bit floating point planar image remap.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep *pXMap* image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep *pYMap* image array line step in bytes.

pDst [Destination-Planar-Image Pointer Array](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of *eInterpolation* to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.19 `NppStatus nppiRemap_64f_AC4R (const Npp64f *pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp64f *pXMap, int nXMapStep, const Npp64f *pYMap, int nYMapStep, Npp64f *pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

4 channel 64-bit floating point image remap not affecting alpha.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep *pXMap* image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep *pYMap* image array line step in bytes.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.20 `NppStatus nppiRemap_64f_C1R (const Npp64f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp64f * pXMap, int nXMapStep, const Npp64f * pYMap, int nYMapStep, Npp64f * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

1 channel 64-bit floating point image remap.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.21 `NppStatus nppiRemap_64f_C3R (const Npp64f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp64f * pXMap, int nXMapStep, const Npp64f * pYMap, int nYMapStep, Npp64f * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

3 channel 64-bit floating point image remap.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.22 NppStatus nppiRemap_64f_C4R (const Npp64f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp64f * pXMap, int nXMapStep, const Npp64f * pYMap, int nYMapStep, Npp64f * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)

4 channel 64-bit floating point image remap.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.23 NppStatus nppiRemap_64f_P3R (**const Npp64f *const pSrc[3]**, **NppiSize oSrcSize**, **int nSrcStep**, **NppiRect oSrcROI**, **const Npp64f *pXMap**, **int nXMapStep**, **const Npp64f *pYMap**, **int nYMapStep**, **Npp64f *pDst[3]**, **int nDstStep**, **NppiSize oDstSizeROI**, **int eInterpolation**)

3 channel 64-bit floating point planar image remap.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep *pXMap* image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep *pYMap* image array line step in bytes.

pDst [Destination-Planar-Image Pointer Array](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of *eInterpolation* to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.24 NppStatus nppiRemap_64f_P4R (**const Npp64f *const pSrc[4]**, **NppiSize oSrcSize**, **int nSrcStep**, **NppiRect oSrcROI**, **const Npp64f *pXMap**, **int nXMapStep**, **const Npp64f *pYMap**, **int nYMapStep**, **Npp64f *pDst[4]**, **int nDstStep**, **NppiSize oDstSizeROI**, **int eInterpolation**)

4 channel 64-bit floating point planar image remap.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep *pXMap* image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep *pYMap* image array line step in bytes.

pDst Destination-Planar-Image Pointer Array.
nDstStep Destination-Image Line Step.
oDstSizeROI Region of interest size in the destination image.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.25 `NppStatus nppiRemap_8u_AC4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

4 channel 8-bit unsigned image remap not affecting alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSize Size in pixels of the source image.
oSrcROI Region of interest in the source image.
pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.
nXMapStep pXMap image array line step in bytes.
pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.
nYMapStep pYMap image array line step in bytes.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstSizeROI Region of interest size in the destination image.
eInterpolation The type of interpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.26 `NppStatus nppiRemap_8u_C1R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

1 channel 8-bit unsigned image remap.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.27 `NppStatus nppiRemap_8u_C3R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

3 channel 8-bit unsigned image remap.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.28 `NppStatus nppiRemap_8u_C4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

4 channel 8-bit unsigned image remap.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep *pXMap* image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep *pYMap* image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of *eInterpolation* to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.29 `NppStatus nppiRemap_8u_P3R (const Npp8u *const pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp8u * pDst[3], int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

3 channel 8-bit unsigned planar image remap.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep *pXMap* image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep *pYMap* image array line step in bytes.

pDst [Destination-Planar-Image Pointer Array](#).

nDstStep Destination-Image Line Step.

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.75.3.30 `NppStatus nppiRemap_8u_P4R (const Npp8u *const pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp8u * pDst[4], int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

4 channel 8-bit unsigned planar image remap.

Parameters:

pSrc Source-Planar-Image Pointer Array.

nSrcStep Source-Image Line Step.

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst Destination-Planar-Image Pointer Array.

nDstStep Destination-Image Line Step.

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.76 Rotate

Rotates an image around the origin (0,0) and then shifts it.

Utility Functions

- **NppStatus nppiGetRotateQuad** (**NppiRect** oSrcROI, double aQuad[4][2], double nAngle, double nShiftX, double nShiftY)
Compute shape of rotated image.
- **NppStatus nppiGetRotateBound** (**NppiRect** oSrcROI, double aBoundingBox[2][2], double nAngle, double nShiftX, double nShiftY)
Compute bounding-box of rotated image.

Rotate

- **NppStatus nppiRotate_8u_C1R** (const **Npp8u** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp8u** *pDst, int nDstStep, **NppiRect** oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)
8-bit unsigned image rotate.
- **NppStatus nppiRotate_8u_C3R** (const **Npp8u** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp8u** *pDst, int nDstStep, **NppiRect** oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)
3 channel 8-bit unsigned image rotate.
- **NppStatus nppiRotate_8u_C4R** (const **Npp8u** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp8u** *pDst, int nDstStep, **NppiRect** oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)
4 channel 8-bit unsigned image rotate.
- **NppStatus nppiRotate_8u_AC4R** (const **Npp8u** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp8u** *pDst, int nDstStep, **NppiRect** oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)
4 channel 8-bit unsigned image rotate ignoring alpha channel.
- **NppStatus nppiRotate_16u_C1R** (const **Npp16u** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp16u** *pDst, int nDstStep, **NppiRect** oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)
16-bit unsigned image rotate.
- **NppStatus nppiRotate_16u_C3R** (const **Npp16u** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp16u** *pDst, int nDstStep, **NppiRect** oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)
3 channel 16-bit unsigned image rotate.
- **NppStatus nppiRotate_16u_C4R** (const **Npp16u** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp16u** *pDst, int nDstStep, **NppiRect** oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)

4 channel 16-bit unsigned image rotate.

- `NppStatus nppiRotate_16u_AC4R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp16u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, double `nAngle`, double `nShiftX`, double `nShiftY`, int `eInterpolation`)

4 channel 16-bit unsigned image rotate ignoring alpha channel.

- `NppStatus nppiRotate_32f_C1R` (const `Npp32f *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32f *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, double `nAngle`, double `nShiftX`, double `nShiftY`, int `eInterpolation`)

32-bit float image rotate.

- `NppStatus nppiRotate_32f_C3R` (const `Npp32f *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32f *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, double `nAngle`, double `nShiftX`, double `nShiftY`, int `eInterpolation`)

3 channel 32-bit float image rotate.

- `NppStatus nppiRotate_32f_C4R` (const `Npp32f *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32f *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, double `nAngle`, double `nShiftX`, double `nShiftY`, int `eInterpolation`)

4 channel 32-bit float image rotate.

- `NppStatus nppiRotate_32f_AC4R` (const `Npp32f *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32f *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, double `nAngle`, double `nShiftX`, double `nShiftY`, int `eInterpolation`)

4 channel 32-bit float image rotate ignoring alpha channel.

7.76.1 Detailed Description

Rotates an image around the origin (0,0) and then shifts it.

7.76.2 Rotate Error Codes

- `NPP_INTERPOLATION_ERROR` if `eInterpolation` has an illegal value.
- `NPP_RECT_ERROR` Indicates an error condition if width or height of the intersection of the `oSrcROI` and source image is less than or equal to 1.
- `NPP_WRONG_INTERSECTION_ROI_ERROR` indicates an error condition if `srcROIrect` has no intersection with the source image.
- `NPP_WRONG_INTERSECTION_QUAD_WARNING` indicates a warning that no operation is performed if the transformed source ROI does not intersect the destination ROI.

7.76.3 Function Documentation

7.76.3.1 `NppStatus nppiGetRotateBound` (`NppiRect` `oSrcROI`, `double` `aBoundingBox[2][2]`, `double` `nAngle`, `double` `nShiftX`, `double` `nShiftY`)

Compute bounding-box of rotated image.

Parameters:

oSrcROI Region-of-interest of the source image.

aBoundingBox Two 2D points representing the bounding-box of the rotated image. All four points from `nppiGetRotateQuad` are contained inside the axis-aligned rectangle spanned by the two points of this bounding box.

nAngle The rotation angle.

nShiftX Post-rotation shift in x-direction.

nShiftY Post-rotation shift in y-direction.

Returns:

[ROI Related Error Codes.](#)

7.76.3.2 `NppStatus nppiGetRotateQuad (NppiRect oSrcROI, double aQuad[4][2], double nAngle, double nShiftX, double nShiftY)`

Compute shape of rotated image.

Parameters:

oSrcROI Region-of-interest of the source image.

aQuad Array of 2D points. These points are the locations of the corners of the rotated ROI.

nAngle The rotation `nAngle`.

nShiftX Post-rotation shift in x-direction

nShiftY Post-rotation shift in y-direction

Returns:

[ROI Related Error Codes.](#)

7.76.3.3 `NppStatus nppiRotate_16u_AC4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)`

4 channel 16-bit unsigned image rotate ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer.](#)

nSrcStep [Source-Image Line Step.](#)

oSrcSize Size in pixels of the source image

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer.](#)

nDstStep [Destination-Image Line Step.](#)

oDstROI Region of interest in the destination image.

nAngle The angle of rotation in degrees.

nShiftX Shift along horizontal axis

nShiftY Shift along vertical axis

eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Rotate Error Codes](#)

7.76.3.4 NppStatus nppiRotate_16u_C1R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)

16-bit unsigned image rotate.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nAngle The angle of rotation in degrees.

nShiftX Shift along horizontal axis

nShiftY Shift along vertical axis

eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Rotate Error Codes](#)

7.76.3.5 NppStatus nppiRotate_16u_C3R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)

3 channel 16-bit unsigned image rotate.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nAngle The angle of rotation in degrees.

nShiftX Shift along horizontal axis

nShiftY Shift along vertical axis

eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Rotate Error Codes](#)

7.76.3.6 `NppStatus nppiRotate_16u_C4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)`

4 channel 16-bit unsigned image rotate.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nAngle The angle of rotation in degrees.

nShiftX Shift along horizontal axis

nShiftY Shift along vertical axis

eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Rotate Error Codes](#)

7.76.3.7 `NppStatus nppiRotate_32f_AC4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)`

4 channel 32-bit float image rotate ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nAngle The angle of rotation in degrees.
nShiftX Shift along horizontal axis
nShiftY Shift along vertical axis
eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Rotate Error Codes](#)

7.76.3.8 `NppStatus nppiRotate_32f_C1R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)`

32-bit float image rotate.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oDstROI Region of interest in the destination image.
nAngle The angle of rotation in degrees.
nShiftX Shift along horizontal axis
nShiftY Shift along vertical axis
eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Rotate Error Codes](#)

7.76.3.9 `NppStatus nppiRotate_32f_C3R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)`

3 channel 32-bit float image rotate.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.
nAngle The angle of rotation in degrees.
nShiftX Shift along horizontal axis
nShiftY Shift along vertical axis
eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Rotate Error Codes](#)

7.76.3.10 `NppStatus nppiRotate_32f_C4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)`

4 channel 32-bit float image rotate.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oDstROI Region of interest in the destination image.
nAngle The angle of rotation in degrees.
nShiftX Shift along horizontal axis
nShiftY Shift along vertical axis
eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Rotate Error Codes](#)

7.76.3.11 `NppStatus nppiRotate_8u_AC4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)`

4 channel 8-bit unsigned image rotate ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst [Destination-Image Pointer](#).

nDstStep Destination-Image Line Step.
oDstROI Region of interest in the destination image.
nAngle The angle of rotation in degrees.
nShiftX Shift along horizontal axis
nShiftY Shift along vertical axis
eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Rotate Error Codes](#)

7.76.3.12 `NppStatus nppiRotate_8u_C1R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)`

8-bit unsigned image rotate.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstROI Region of interest in the destination image.
nAngle The angle of rotation in degrees.
nShiftX Shift along horizontal axis
nShiftY Shift along vertical axis
eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Rotate Error Codes](#)

7.76.3.13 `NppStatus nppiRotate_8u_C3R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)`

3 channel 8-bit unsigned image rotate.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.

pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstROI Region of interest in the destination image.
nAngle The angle of rotation in degrees.
nShiftX Shift along horizontal axis
nShiftY Shift along vertical axis
eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Rotate Error Codes](#)

7.76.3.14 `NppStatus nppiRotate_8u_C4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)`

4 channel 8-bit unsigned image rotate.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstROI Region of interest in the destination image.
nAngle The angle of rotation in degrees.
nShiftX Shift along horizontal axis
nShiftY Shift along vertical axis
eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Rotate Error Codes](#)

7.77 Mirror

Mirror

Mirrors images horizontally, vertically and diagonally.

- `NppStatus nppiMirror_8u_C1R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize` `oROI`, `NppiAxis` `flip`)
1 channel 8-bit unsigned image mirror.
- `NppStatus nppiMirror_8u_C1IR` (`Npp8u *pSrcDst`, int `nSrcDstStep`, `NppiSize` `oROI`, `NppiAxis` `flip`)
1 channel 8-bit unsigned in place image mirror.
- `NppStatus nppiMirror_8u_C3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize` `oROI`, `NppiAxis` `flip`)
3 channel 8-bit unsigned image mirror.
- `NppStatus nppiMirror_8u_C3IR` (`Npp8u *pSrcDst`, int `nSrcDstStep`, `NppiSize` `oROI`, `NppiAxis` `flip`)
3 channel 8-bit unsigned in place image mirror.
- `NppStatus nppiMirror_8u_C4R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize` `oROI`, `NppiAxis` `flip`)
4 channel 8-bit unsigned image mirror.
- `NppStatus nppiMirror_8u_C4IR` (`Npp8u *pSrcDst`, int `nSrcDstStep`, `NppiSize` `oROI`, `NppiAxis` `flip`)
4 channel 8-bit unsigned in place image mirror.
- `NppStatus nppiMirror_8u_AC4R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize` `oROI`, `NppiAxis` `flip`)
4 channel 8-bit unsigned image mirror not affecting alpha.
- `NppStatus nppiMirror_8u_AC4IR` (`Npp8u *pSrcDst`, int `nSrcDstStep`, `NppiSize` `oROI`, `NppiAxis` `flip`)
4 channel 8-bit unsigned in place image mirror not affecting alpha.
- `NppStatus nppiMirror_16u_C1R` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize` `oROI`, `NppiAxis` `flip`)
1 channel 16-bit unsigned image mirror.
- `NppStatus nppiMirror_16u_C1IR` (`Npp16u *pSrcDst`, int `nSrcDstStep`, `NppiSize` `oROI`, `NppiAxis` `flip`)
1 channel 16-bit unsigned in place image mirror.
- `NppStatus nppiMirror_16u_C3R` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize` `oROI`, `NppiAxis` `flip`)
3 channel 16-bit unsigned image mirror.

- **NppStatus nppiMirror_16u_C3IR** (**Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oROI, **NppiAxis** flip)
3 channel 16-bit unsigned in place image mirror.
- **NppStatus nppiMirror_16u_C4R** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oROI, **NppiAxis** flip)
4 channel 16-bit unsigned image mirror.
- **NppStatus nppiMirror_16u_C4IR** (**Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oROI, **NppiAxis** flip)
4 channel 16-bit unsigned in place image mirror.
- **NppStatus nppiMirror_16u_AC4R** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oROI, **NppiAxis** flip)
4 channel 16-bit unsigned image mirror not affecting alpha.
- **NppStatus nppiMirror_16u_AC4IR** (**Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oROI, **NppiAxis** flip)
4 channel 16-bit unsigned in place image mirror not affecting alpha.
- **NppStatus nppiMirror_16s_C1R** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oROI, **NppiAxis** flip)
1 channel 16-bit signed image mirror.
- **NppStatus nppiMirror_16s_C1IR** (**Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oROI, **NppiAxis** flip)
1 channel 16-bit signed in place image mirror.
- **NppStatus nppiMirror_16s_C3R** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oROI, **NppiAxis** flip)
3 channel 16-bit signed image mirror.
- **NppStatus nppiMirror_16s_C3IR** (**Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oROI, **NppiAxis** flip)
3 channel 16-bit signed in place image mirror.
- **NppStatus nppiMirror_16s_C4R** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oROI, **NppiAxis** flip)
4 channel 16-bit signed image mirror.
- **NppStatus nppiMirror_16s_C4IR** (**Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oROI, **NppiAxis** flip)
4 channel 16-bit signed in place image mirror.
- **NppStatus nppiMirror_16s_AC4R** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oROI, **NppiAxis** flip)
4 channel 16-bit signed image mirror not affecting alpha.
- **NppStatus nppiMirror_16s_AC4IR** (**Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oROI, **NppiAxis** flip)
4 channel 16-bit signed in place image mirror not affecting alpha.

- [NppStatus nppiMirror_32s_C1R](#) (const [Npp32s](#) *pSrc, int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oROI, [NppiAxis](#) flip)
1 channel 32-bit image mirror.
- [NppStatus nppiMirror_32s_C1IR](#) ([Npp32s](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oROI, [NppiAxis](#) flip)
1 channel 32-bit signed in place image mirror.
- [NppStatus nppiMirror_32s_C3R](#) (const [Npp32s](#) *pSrc, int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oROI, [NppiAxis](#) flip)
3 channel 32-bit image mirror.
- [NppStatus nppiMirror_32s_C3IR](#) ([Npp32s](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oROI, [NppiAxis](#) flip)
3 channel 32-bit signed in place image mirror.
- [NppStatus nppiMirror_32s_C4R](#) (const [Npp32s](#) *pSrc, int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oROI, [NppiAxis](#) flip)
4 channel 32-bit image mirror.
- [NppStatus nppiMirror_32s_C4IR](#) ([Npp32s](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oROI, [NppiAxis](#) flip)
4 channel 32-bit signed in place image mirror.
- [NppStatus nppiMirror_32s_AC4R](#) (const [Npp32s](#) *pSrc, int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oROI, [NppiAxis](#) flip)
4 channel 32-bit image mirror not affecting alpha.
- [NppStatus nppiMirror_32s_AC4IR](#) ([Npp32s](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oROI, [NppiAxis](#) flip)
4 channel 32-bit signed in place image mirror not affecting alpha.
- [NppStatus nppiMirror_32f_C1R](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oROI, [NppiAxis](#) flip)
1 channel 32-bit float image mirror.
- [NppStatus nppiMirror_32f_C1IR](#) ([Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oROI, [NppiAxis](#) flip)
1 channel 32-bit float in place image mirror.
- [NppStatus nppiMirror_32f_C3R](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oROI, [NppiAxis](#) flip)
3 channel 32-bit float image mirror.
- [NppStatus nppiMirror_32f_C3IR](#) ([Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oROI, [NppiAxis](#) flip)
3 channel 32-bit float in place image mirror.
- [NppStatus nppiMirror_32f_C4R](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oROI, [NppiAxis](#) flip)

4 channel 32-bit float image mirror.

- `NppStatus nppiMirror_32f_C4IR` (`Npp32f *pSrcDst`, `int nSrcDstStep`, `NppiSize oROI`, `NppiAxis flip`)

4 channel 32-bit float in place image mirror.

- `NppStatus nppiMirror_32f_AC4R` (`const Npp32f *pSrc`, `int nSrcStep`, `Npp32f *pDst`, `int nDstStep`, `NppiSize oROI`, `NppiAxis flip`)

4 channel 32-bit float image mirror not affecting alpha.

- `NppStatus nppiMirror_32f_AC4IR` (`Npp32f *pSrcDst`, `int nSrcDstStep`, `NppiSize oROI`, `NppiAxis flip`)

4 channel 32-bit float in place image mirror not affecting alpha.

7.77.1 Detailed Description

7.77.2 Mirror Error Codes

- `NPP_MIRROR_FLIP_ERR` if flip has an illegal value.

7.77.3 Function Documentation

7.77.3.1 `NppStatus nppiMirror_16s_AC4IR` (`Npp16s *pSrcDst`, `int nSrcDstStep`, `NppiSize oROI`, `NppiAxis flip`)

4 channel 16-bit signed in place image mirror not affecting alpha.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, Mirror Error Codes

7.77.3.2 `NppStatus nppiMirror_16s_AC4R` (`const Npp16s *pSrc`, `int nSrcStep`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oROI`, `NppiAxis flip`)

4 channel 16-bit signed image mirror not affecting alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Distance in bytes between starts of consecutive lines of the destination image.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.3 NppStatus nppiMirror_16s_C1IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

1 channel 16-bit signed in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.4 NppStatus nppiMirror_16s_C1R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

1 channel 16-bit signed image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.5 NppStatus nppiMirror_16s_C3IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

3 channel 16-bit signed in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.6 NppStatus nppiMirror_16s_C3R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

3 channel 16-bit signed image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.7 NppStatus nppiMirror_16s_C4IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

4 channel 16-bit signed in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.8 NppStatus nppiMirror_16s_C4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

4 channel 16-bit signed image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Distance in bytes between starts of consecutive lines of the destination image.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.9 NppStatus nppiMirror_16u_AC4IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

4 channel 16-bit unsigned in place image mirror not affecting alpha.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.10 NppStatus nppiMirror_16u_AC4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

4 channel 16-bit unsigned image mirror not affecting alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Distance in bytes between starts of consecutive lines of the destination image.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.11 NppStatus nppiMirror_16u_C1IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

1 channel 16-bit unsigned in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.12 NppStatus nppiMirror_16u_C1R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

1 channel 16-bit unsigned image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.13 NppStatus nppiMirror_16u_C3IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

3 channel 16-bit unsigned in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.14 NppStatus nppiMirror_16u_C3R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

3 channel 16-bit unsigned image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.15 NppStatus nppiMirror_16u_C4IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

4 channel 16-bit unsigned in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.16 NppStatus nppiMirror_16u_C4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

4 channel 16-bit unsigned image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Distance in bytes between starts of consecutive lines of the destination image.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.17 NppStatus nppiMirror_32f_AC4IR (Npp32f * *pSrcDst*, int *nSrcDstStep*, NppiSize *oROI*, NppiAxis *flip*)

4 channel 32-bit float in place image mirror not affecting alpha.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.18 NppStatus nppiMirror_32f_AC4R (const Npp32f * *pSrc*, int *nSrcStep*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oROI*, NppiAxis *flip*)

4 channel 32-bit float image mirror not affecting alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Distance in bytes between starts of consecutive lines of the destination image.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.19 NppStatus nppiMirror_32f_C1IR (Npp32f * *pSrcDst*, int *nSrcDstStep*, NppiSize *oROI*, NppiAxis *flip*)

1 channel 32-bit float in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.20 `NppStatus nppiMirror_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)`

1 channel 32-bit float image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.21 `NppStatus nppiMirror_32f_C3IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)`

3 channel 32-bit float in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.22 `NppStatus nppiMirror_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)`

3 channel 32-bit float image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.23 NppStatus nppiMirror_32f_C4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

4 channel 32-bit float in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.24 NppStatus nppiMirror_32f_C4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

4 channel 32-bit float image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Distance in bytes between starts of consecutive lines of the destination image.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.25 NppStatus nppiMirror_32s_AC4IR (Npp32s * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

4 channel 32-bit signed in place image mirror not affecting alpha.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.26 `NppStatus nppiMirror_32s_AC4R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)`

4 channel 32-bit image mirror not affecting alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Distance in bytes between starts of consecutive lines of the destination image.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.27 `NppStatus nppiMirror_32s_C11R (Npp32s * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)`

1 channel 32-bit signed in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.28 `NppStatus nppiMirror_32s_C1R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)`

1 channel 32-bit image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.29 NppStatus nppiMirror_32s_C3IR (Npp32s * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

3 channel 32-bit signed in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.30 NppStatus nppiMirror_32s_C3R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

3 channel 32-bit image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.31 NppStatus nppiMirror_32s_C4IR (Npp32s * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

4 channel 32-bit signed in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.32 NppStatus nppiMirror_32s_C4R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

4 channel 32-bit image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Distance in bytes between starts of consecutive lines of the destination image.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.33 NppStatus nppiMirror_8u_AC4IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

4 channel 8-bit unsigned in place image mirror not affecting alpha.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.34 NppStatus nppiMirror_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

4 channel 8-bit unsigned image mirror not affecting alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Distance in bytes between starts of consecutive lines of the destination image.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.35 NppStatus nppiMirror_8u_C1IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

1 channel 8-bit unsigned in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.36 NppStatus nppiMirror_8u_C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

1 channel 8-bit unsigned image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.37 NppStatus nppiMirror_8u_C3IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

3 channel 8-bit unsigned in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.38 NppStatus nppiMirror_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

3 channel 8-bit unsigned image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.39 NppStatus nppiMirror_8u_C4IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

4 channel 8-bit unsigned in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.77.3.40 NppStatus nppiMirror_8u_C4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

4 channel 8-bit unsigned image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Distance in bytes between starts of consecutive lines of the destination image.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.78 Affine Transforms

Utility Functions

- **NppStatus** `nppiGetAffineTransform` (**NppiRect** oSrcROI, const double aQuad[4][2], double aCoeffs[2][3])
Computes affine transform coefficients based on source ROI and destination quadrilateral.
- **NppStatus** `nppiGetAffineQuad` (**NppiRect** oSrcROI, double aQuad[4][2], const double aCoeffs[2][3])
Compute shape of transformed image.
- **NppStatus** `nppiGetAffineBound` (**NppiRect** oSrcROI, double aBound[2][2], const double aCoeffs[2][3])
Compute bounding-box of transformed image.

Affine Transform

Transforms (warps) an image based on an affine transform.

The affine transform is given as a 2×3 matrix C . A pixel location (x, y) in the source image is mapped to the location (x', y') in the destination image. The destination image coordinates are computed as follows:

$$x' = c_{00} * x + c_{01} * y + c_{02} \quad y' = c_{10} * x + c_{11} * y + c_{12} \quad C = \begin{bmatrix} c_{00} & c_{01} & c_{02} \\ c_{10} & c_{11} & c_{12} \end{bmatrix}$$

Affine transforms can be understood as a linear transformation (traditional matrix multiplication) and a shift operation. The 2×2 matrix

$$L = \begin{bmatrix} c_{00} & c_{01} \\ c_{10} & c_{11} \end{bmatrix}$$

represents the linear transform portion of the affine transformation. The vector

$$v = \begin{pmatrix} c_{02} \\ c_{12} \end{pmatrix}$$

represents the post-transform shift, i.e. after the pixel location is transformed by L it is translated by v .

- **NppStatus** `nppiWarpAffine_8u_C1R` (const **Npp8u** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp8u** *pDst, int nDstStep, **NppiRect** oDstROI, const double aCoeffs[2][3], int eInterpolation)
Single-channel 8-bit unsigned affine warp.
- **NppStatus** `nppiWarpAffine_8u_C3R` (const **Npp8u** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp8u** *pDst, int nDstStep, **NppiRect** oDstROI, const double aCoeffs[2][3], int eInterpolation)
Three-channel 8-bit unsigned affine warp.
- **NppStatus** `nppiWarpAffine_8u_C4R` (const **Npp8u** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp8u** *pDst, int nDstStep, **NppiRect** oDstROI, const double aCoeffs[2][3], int eInterpolation)
Four-channel 8-bit unsigned affine warp.

- `NppStatus nppiWarpAffine_8u_AC4R` (const `Npp8u *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp8u *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Four-channel 8-bit unsigned affine warp, ignoring alpha channel.
- `NppStatus nppiWarpAffine_8u_P3R` (const `Npp8u *pSrc[3]`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp8u *pDst[3]`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Three-channel planar 8-bit unsigned affine warp.
- `NppStatus nppiWarpAffine_8u_P4R` (const `Npp8u *pSrc[4]`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp8u *pDst[4]`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Four-channel planar 8-bit unsigned affine warp.
- `NppStatus nppiWarpAffine_16u_C1R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp16u *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Single-channel 16-bit unsigned affine warp.
- `NppStatus nppiWarpAffine_16u_C3R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp16u *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Three-channel 16-bit unsigned affine warp.
- `NppStatus nppiWarpAffine_16u_C4R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp16u *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Four-channel 16-bit unsigned affine warp.
- `NppStatus nppiWarpAffine_16u_AC4R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp16u *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Four-channel 16-bit unsigned affine warp, ignoring alpha channel.
- `NppStatus nppiWarpAffine_16u_P3R` (const `Npp16u *pSrc[3]`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp16u *pDst[3]`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Three-channel planar 16-bit unsigned affine warp.
- `NppStatus nppiWarpAffine_16u_P4R` (const `Npp16u *pSrc[4]`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp16u *pDst[4]`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Four-channel planar 16-bit unsigned affine warp.
- `NppStatus nppiWarpAffine_32s_C1R` (const `Npp32s *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32s *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Single-channel 32-bit signed affine warp.

- `NppStatus nppiWarpAffine_32s_C3R` (const `Npp32s *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32s *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)
Three-channel 32-bit signed affine warp.
- `NppStatus nppiWarpAffine_32s_C4R` (const `Npp32s *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32s *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)
Four-channel 32-bit signed affine warp.
- `NppStatus nppiWarpAffine_32s_AC4R` (const `Npp32s *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32s *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)
Four-channel 32-bit signed affine warp, ignoring alpha channel.
- `NppStatus nppiWarpAffine_32s_P3R` (const `Npp32s *pSrc[3]`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32s *pDst[3]`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)
Three-channel planar 32-bit signed affine warp.
- `NppStatus nppiWarpAffine_32s_P4R` (const `Npp32s *pSrc[4]`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32s *pDst[4]`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)
Four-channel planar 32-bit signed affine warp.
- `NppStatus nppiWarpAffine_32f_C1R` (const `Npp32f *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32f *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)
Single-channel 32-bit floating-point affine warp.
- `NppStatus nppiWarpAffine_32f_C3R` (const `Npp32f *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32f *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)
Three-channel 32-bit floating-point affine warp.
- `NppStatus nppiWarpAffine_32f_C4R` (const `Npp32f *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32f *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)
Four-channel 32-bit floating-point affine warp.
- `NppStatus nppiWarpAffine_32f_AC4R` (const `Npp32f *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32f *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)
Four-channel 32-bit floating-point affine warp, ignoring alpha channel.
- `NppStatus nppiWarpAffine_32f_P3R` (const `Npp32f *pSrc[3]`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32f *pDst[3]`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)
Three-channel planar 32-bit floating-point affine warp.

- `NppStatus nppiWarpAffine_32f_P4R` (const `Npp32f *pSrc[4]`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f *pDst[4]`, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)
Four-channel planar 32-bit floating-point affine warp.
- `NppStatus nppiWarpAffine_64f_C1R` (const `Npp64f *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp64f *pDst`, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)
Single-channel 64-bit floating-point affine warp.
- `NppStatus nppiWarpAffine_64f_C3R` (const `Npp64f *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp64f *pDst`, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)
Three-channel 64-bit floating-point affine warp.
- `NppStatus nppiWarpAffine_64f_C4R` (const `Npp64f *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp64f *pDst`, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)
Four-channel 64-bit floating-point affine warp.
- `NppStatus nppiWarpAffine_64f_AC4R` (const `Npp64f *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp64f *pDst`, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)
Four-channel 64-bit floating-point affine warp, ignoring alpha channel.
- `NppStatus nppiWarpAffine_64f_P3R` (const `Npp64f *aSrc[3]`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp64f *aDst[3]`, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)
Three-channel planar 64-bit floating-point affine warp.
- `NppStatus nppiWarpAffine_64f_P4R` (const `Npp64f *aSrc[4]`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp64f *aDst[4]`, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)
Four-channel planar 64-bit floating-point affine warp.

Backwards Affine Transform

Transforms (warps) an image based on an affine transform.

The affine transform is given as a 2×3 matrix C . A pixel location (x, y) in the source image is mapped to the location (x', y') in the destination image. The destination image coordinates fulfill the following properties:

$$x = c_{00} * x' + c_{01} * y' + c_{02} \quad y = c_{10} * x' + c_{11} * y' + c_{12} \quad C = \begin{bmatrix} c_{00} & c_{01} & c_{02} \\ c_{10} & c_{11} & c_{12} \end{bmatrix}$$

In other words, given matrix C the source image's shape is transformed to the destination image using the inverse matrix C^{-1} :

$$M = C^{-1} = \begin{bmatrix} m_{00} & m_{01} & m_{02} \\ m_{10} & m_{11} & m_{12} \end{bmatrix} \quad x' = m_{00} * x + m_{01} * y + m_{02} \quad y' = m_{10} * x + m_{11} * y + m_{12}$$

- `NppStatus nppiWarpAffineBack_8u_C1R` (const `Npp8u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp8u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, int `eInterpolation`)

Single-channel 8-bit unsigned integer backwards affine warp.
- `NppStatus nppiWarpAffineBack_8u_C3R` (const `Npp8u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp8u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, int `eInterpolation`)

Three-channel 8-bit unsigned integer backwards affine warp.
- `NppStatus nppiWarpAffineBack_8u_C4R` (const `Npp8u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp8u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, int `eInterpolation`)

Four-channel 8-bit unsigned integer backwards affine warp.
- `NppStatus nppiWarpAffineBack_8u_AC4R` (const `Npp8u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp8u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, int `eInterpolation`)

Four-channel 8-bit unsigned integer backwards affine warp, ignoring alpha channel.
- `NppStatus nppiWarpAffineBack_8u_P3R` (const `Npp8u *pSrc[3]`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp8u *pDst[3]`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, int `eInterpolation`)

Three-channel planar 8-bit unsigned integer backwards affine warp.
- `NppStatus nppiWarpAffineBack_8u_P4R` (const `Npp8u *pSrc[4]`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp8u *pDst[4]`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, int `eInterpolation`)

Four-channel planar 8-bit unsigned integer backwards affine warp.
- `NppStatus nppiWarpAffineBack_16u_C1R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp16u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, int `eInterpolation`)

Single-channel 16-bit unsigned integer backwards affine warp.
- `NppStatus nppiWarpAffineBack_16u_C3R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp16u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, int `eInterpolation`)

Three-channel 16-bit unsigned integer backwards affine warp.
- `NppStatus nppiWarpAffineBack_16u_C4R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp16u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, int `eInterpolation`)

Four-channel 16-bit unsigned integer backwards affine warp.
- `NppStatus nppiWarpAffineBack_16u_AC4R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp16u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, int `eInterpolation`)

Four-channel 16-bit unsigned integer backwards affine warp, ignoring alpha channel.

- [NppStatus nppiWarpAffineBack_16u_P3R](#) (const [Npp16u](#) *pSrc[3], [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, [Npp16u](#) *pDst[3], int nDstStep, [NppiRect](#) oDstROI, const double aCoeffs[2][3], int eInterpolation)

Three-channel planar 16-bit unsigned integer backwards affine warp.
- [NppStatus nppiWarpAffineBack_16u_P4R](#) (const [Npp16u](#) *pSrc[4], [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, [Npp16u](#) *pDst[4], int nDstStep, [NppiRect](#) oDstROI, const double aCoeffs[2][3], int eInterpolation)

Four-channel planar 16-bit unsigned integer backwards affine warp.
- [NppStatus nppiWarpAffineBack_32s_C1R](#) (const [Npp32s](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, [Npp32s](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, const double aCoeffs[2][3], int eInterpolation)

Single-channel 32-bit signed integer backwards affine warp.
- [NppStatus nppiWarpAffineBack_32s_C3R](#) (const [Npp32s](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, [Npp32s](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, const double aCoeffs[2][3], int eInterpolation)

Three-channel 32-bit signed integer backwards affine warp.
- [NppStatus nppiWarpAffineBack_32s_C4R](#) (const [Npp32s](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, [Npp32s](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, const double aCoeffs[2][3], int eInterpolation)

Four-channel 32-bit signed integer backwards affine warp.
- [NppStatus nppiWarpAffineBack_32s_AC4R](#) (const [Npp32s](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, [Npp32s](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, const double aCoeffs[2][3], int eInterpolation)

Four-channel 32-bit signed integer backwards affine warp, ignoring alpha channel.
- [NppStatus nppiWarpAffineBack_32s_P3R](#) (const [Npp32s](#) *pSrc[3], [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, [Npp32s](#) *pDst[3], int nDstStep, [NppiRect](#) oDstROI, const double aCoeffs[2][3], int eInterpolation)

Three-channel planar 32-bit signed integer backwards affine warp.
- [NppStatus nppiWarpAffineBack_32s_P4R](#) (const [Npp32s](#) *pSrc[4], [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, [Npp32s](#) *pDst[4], int nDstStep, [NppiRect](#) oDstROI, const double aCoeffs[2][3], int eInterpolation)

Four-channel planar 32-bit signed integer backwards affine warp.
- [NppStatus nppiWarpAffineBack_32f_C1R](#) (const [Npp32f](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, [Npp32f](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, const double aCoeffs[2][3], int eInterpolation)

Single-channel 32-bit floating-point backwards affine warp.
- [NppStatus nppiWarpAffineBack_32f_C3R](#) (const [Npp32f](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, [Npp32f](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, const double aCoeffs[2][3], int eInterpolation)

Three-channel 32-bit floating-point backwards affine warp.

- `NppStatus nppiWarpAffineBack_32f_C4R` (const `Npp32f *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f *pDst`, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)
Four-channel 32-bit floating-point backwards affine warp.
- `NppStatus nppiWarpAffineBack_32f_AC4R` (const `Npp32f *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f *pDst`, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)
Four-channel 32-bit floating-point backwards affine warp, ignoring alpha channel.
- `NppStatus nppiWarpAffineBack_32f_P3R` (const `Npp32f *pSrc[3]`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f *pDst[3]`, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)
Three-channel planar 32-bit floating-point backwards affine warp.
- `NppStatus nppiWarpAffineBack_32f_P4R` (const `Npp32f *pSrc[4]`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f *pDst[4]`, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)
Four-channel planar 32-bit floating-point backwards affine warp.

Quad-Based Affine Transform

Transforms (warps) an image based on an affine transform.

The affine transform is computed such that it maps a quadrilateral in source image space to a quadrilateral in destination image space.

An affine transform is fully determined by the mapping of 3 discrete points. The following primitives compute an affine transformation matrix that maps the first three corners of the source quad are mapped to the first three vertices of the destination image quad. If the fourth vertices do not match the transform, an `NPP_AFFINE_QUAD_INCORRECT_WARNING` is returned by the primitive.

- `NppStatus nppiWarpAffineQuad_8u_C1R` (const `Npp8u *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp8u *pDst`, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Single-channel 32-bit floating-point quad-based affine warp.
- `NppStatus nppiWarpAffineQuad_8u_C3R` (const `Npp8u *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp8u *pDst`, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Three-channel 8-bit unsigned integer quad-based affine warp.
- `NppStatus nppiWarpAffineQuad_8u_C4R` (const `Npp8u *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp8u *pDst`, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Four-channel 8-bit unsigned integer quad-based affine warp.
- `NppStatus nppiWarpAffineQuad_8u_AC4R` (const `Npp8u *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp8u *pDst`, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Four-channel 8-bit unsigned integer quad-based affine warp, ignoring alpha channel.

- [NppStatus nppiWarpAffineQuad_8u_P3R](#) (const [Npp8u](#) *pSrc[3], [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const double aSrcQuad[4][2], [Npp8u](#) *pDst[3], int nDstStep, [NppiRect](#) oDstROI, const double aDstQuad[4][2], int eInterpolation)

Three-channel planar 8-bit unsigned integer quad-based affine warp.
- [NppStatus nppiWarpAffineQuad_8u_P4R](#) (const [Npp8u](#) *pSrc[4], [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const double aSrcQuad[4][2], [Npp8u](#) *pDst[4], int nDstStep, [NppiRect](#) oDstROI, const double aDstQuad[4][2], int eInterpolation)

Four-channel planar 8-bit unsigned integer quad-based affine warp.
- [NppStatus nppiWarpAffineQuad_16u_C1R](#) (const [Npp16u](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const double aSrcQuad[4][2], [Npp16u](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, const double aDstQuad[4][2], int eInterpolation)

Single-channel 16-bit unsigned integer quad-based affine warp.
- [NppStatus nppiWarpAffineQuad_16u_C3R](#) (const [Npp16u](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const double aSrcQuad[4][2], [Npp16u](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, const double aDstQuad[4][2], int eInterpolation)

Three-channel 16-bit unsigned integer quad-based affine warp.
- [NppStatus nppiWarpAffineQuad_16u_C4R](#) (const [Npp16u](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const double aSrcQuad[4][2], [Npp16u](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, const double aDstQuad[4][2], int eInterpolation)

Four-channel 16-bit unsigned integer quad-based affine warp.
- [NppStatus nppiWarpAffineQuad_16u_AC4R](#) (const [Npp16u](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const double aSrcQuad[4][2], [Npp16u](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, const double aDstQuad[4][2], int eInterpolation)

Four-channel 16-bit unsigned integer quad-based affine warp, ignoring alpha channel.
- [NppStatus nppiWarpAffineQuad_16u_P3R](#) (const [Npp16u](#) *pSrc[3], [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const double aSrcQuad[4][2], [Npp16u](#) *pDst[3], int nDstStep, [NppiRect](#) oDstROI, const double aDstQuad[4][2], int eInterpolation)

Three-channel planar 16-bit unsigned integer quad-based affine warp.
- [NppStatus nppiWarpAffineQuad_16u_P4R](#) (const [Npp16u](#) *pSrc[4], [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const double aSrcQuad[4][2], [Npp16u](#) *pDst[4], int nDstStep, [NppiRect](#) oDstROI, const double aDstQuad[4][2], int eInterpolation)

Four-channel planar 16-bit unsigned integer quad-based affine warp.
- [NppStatus nppiWarpAffineQuad_32s_C1R](#) (const [Npp32s](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const double aSrcQuad[4][2], [Npp32s](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, const double aDstQuad[4][2], int eInterpolation)

Single-channel 32-bit signed integer quad-based affine warp.
- [NppStatus nppiWarpAffineQuad_32s_C3R](#) (const [Npp32s](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const double aSrcQuad[4][2], [Npp32s](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, const double aDstQuad[4][2], int eInterpolation)

Three-channel 32-bit signed integer quad-based affine warp.

- `NppStatus nppiWarpAffineQuad_32s_C4R` (const `Npp32s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32s` *pDst, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)

Four-channel 32-bit signed integer quad-based affine warp.

- `NppStatus nppiWarpAffineQuad_32s_AC4R` (const `Npp32s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32s` *pDst, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)

Four-channel 32-bit signed integer quad-based affine warp, ignoring alpha channel.

- `NppStatus nppiWarpAffineQuad_32s_P3R` (const `Npp32s` *pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32s` *pDst[3], int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)

Three-channel planar 32-bit signed integer quad-based affine warp.

- `NppStatus nppiWarpAffineQuad_32s_P4R` (const `Npp32s` *pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32s` *pDst[4], int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)

Four-channel planar 32-bit signed integer quad-based affine warp.

- `NppStatus nppiWarpAffineQuad_32f_C1R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)

Single-channel 32-bit floating-point quad-based affine warp.

- `NppStatus nppiWarpAffineQuad_32f_C3R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)

Three-channel 32-bit floating-point quad-based affine warp.

- `NppStatus nppiWarpAffineQuad_32f_C4R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)

Four-channel 32-bit floating-point quad-based affine warp.

- `NppStatus nppiWarpAffineQuad_32f_AC4R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)

Four-channel 32-bit floating-point quad-based affine warp, ignoring alpha channel.

- `NppStatus nppiWarpAffineQuad_32f_P3R` (const `Npp32f` *pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32f` *pDst[3], int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)

Three-channel planar 32-bit floating-point quad-based affine warp.

- `NppStatus nppiWarpAffineQuad_32f_P4R` (const `Npp32f` *pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32f` *pDst[4], int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)

Four-channel planar 32-bit floating-point quad-based affine warp.

7.78.1 Detailed Description

7.78.2 Affine Transform Error Codes

- `NPP_RECT_ERROR` Indicates an error condition if width or height of the intersection of the `oSrcROI` and source image is less than or equal to 1
- `NPP_WRONG_INTERSECTION_ROI_ERROR` Indicates an error condition if `oSrcROI` has no intersection with the source image
- `NPP_INTERPOLATION_ERROR` Indicates an error condition if interpolation has an illegal value
- `NPP_COEFF_ERROR` Indicates an error condition if coefficient values are invalid
- `NPP_WRONG_INTERSECTION_QUAD_WARNING` Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI

7.78.3 Function Documentation

7.78.3.1 `NppStatus nppiGetAffineBound (NppiRect oSrcROI, double aBound[2][2], const double aCoeffs[2][3])`

Compute bounding-box of transformed image.

The method effectively computes the bounding box (axis aligned rectangle) of the transformed source ROI (see [nppiGetAffineQuad\(\)](#)).

Parameters:

- oSrcROI* The source ROI.
- aBound* The resulting bounding box.
- aCoeffs* The affine transform coefficients.

Returns:

Error codes:

- `NPP_SIZE_ERROR` Indicates an error condition if any image dimension has zero or negative value
- `NPP_RECT_ERROR` Indicates an error condition if width or height of the intersection of the `oSrcROI` and source image is less than or equal to 1
- `NPP_COEFF_ERROR` Indicates an error condition if coefficient values are invalid

7.78.3.2 `NppStatus nppiGetAffineQuad (NppiRect oSrcROI, double aQuad[4][2], const double aCoeffs[2][3])`

Compute shape of transformed image.

This method computes the quadrilateral in the destination image that the source ROI is transformed into by the affine transformation expressed by the coefficients array (`aCoeffs`).

Parameters:

- oSrcROI* The source ROI.

aQuad The resulting destination quadrangle.

aCoeffs The affine transform coefficients.

Returns:

Error codes:

- [NPP_SIZE_ERROR](#) Indicates an error condition if any image dimension has zero or negative value
- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *oSrcROI* and source image is less than or equal to 1
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid

7.78.3.3 NppStatus nppiGetAffineTransform (NppiRect *oSrcROI*, const double *aQuad*[4][2], double *aCoeffs*[2][3])

Computes affine transform coefficients based on source ROI and destination quadrilateral.

The function computes the coefficients of an affine transformation that maps the given source ROI (axis aligned rectangle with integer coordinates) to a quadrilateral in the destination image.

An affine transform in 2D is fully determined by the mapping of just three vertices. This function's API allows for passing a complete quadrilateral effectively making the problem overdetermined. What this means in practice is, that for certain quadrilaterals it is not possible to find an affine transform that would map all four corners of the source ROI to the four vertices of that quadrilateral.

The function circumvents this problem by only looking at the first three vertices of the destination image quadrilateral to determine the affine transformation's coefficients. If the destination quadrilateral is indeed one that cannot be mapped using an affine transformation the function informs the user of this situation by returning a [NPP_AFFINE_QUAD_INCORRECT_WARNING](#).

Parameters:

oSrcROI The source ROI. This rectangle needs to be at least one pixel wide and high. If either width or height are less than one an [NPP_RECT_ERROR](#) is returned.

aQuad The destination quadrilateral.

aCoeffs The resulting affine transform coefficients.

Returns:

Error codes:

- [NPP_SIZE_ERROR](#) Indicates an error condition if any image dimension has zero or negative value
- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *oSrcROI* and source image is less than or equal to 1
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid
- [NPP_AFFINE_QUAD_INCORRECT_WARNING](#) Indicates a warning when quad does not conform to the transform properties. Fourth vertex is ignored, internally computed coordinates are used instead

7.78.3.4 NppStatus nppiWarpAffine_16u_AC4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)

Four-channel 16-bit unsigned affine warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.5 NppStatus nppiWarpAffine_16u_C1R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)

Single-channel 16-bit unsigned affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.6 `NppStatus nppiWarpAffine_16u_C3R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel 16-bit unsigned affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.7 `NppStatus nppiWarpAffine_16u_C4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel 16-bit unsigned affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.8 `NppStatus nppiWarpAffine_16u_P3R (const Npp16u * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel planar 16-bit unsigned affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.9 `NppStatus nppiWarpAffine_16u_P4R (const Npp16u * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel planar 16-bit unsigned affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.10 `NppStatus nppiWarpAffine_32f_AC4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel 32-bit floating-point affine warp, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.11 `NppStatus nppiWarpAffine_32f_C1R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Single-channel 32-bit floating-point affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.12 `NppStatus nppiWarpAffine_32f_C3R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel 32-bit floating-point affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.13 `NppStatus nppiWarpAffine_32f_C4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel 32-bit floating-point affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.14 `NppStatus nppiWarpAffine_32f_P3R (const Npp32f * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel planar 32-bit floating-point affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.15 `NppStatus nppiWarpAffine_32f_P4R (const Npp32f * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel planar 32-bit floating-point affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.16 `NppStatus nppiWarpAffine_32s_AC4R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel 32-bit signed affine warp, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.17 `NppStatus nppiWarpAffine_32s_C1R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Single-channel 32-bit signed affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.18 `NppStatus nppiWarpAffine_32s_C3R` (`const Npp32s * pSrc`, `NppiSize oSrcSize`, `int nSrcStep`, `NppiRect oSrcROI`, `Npp32s * pDst`, `int nDstStep`, `NppiRect oDstROI`, `const double aCoeffs[2][3]`, `int eInterpolation`)

Three-channel 32-bit signed affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be `NPPI_INTER_NN`, `NPPI_INTER_LINEAR` or `NPPI_INTER_CUBIC`

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.19 `NppStatus nppiWarpAffine_32s_C4R` (`const Npp32s * pSrc`, `NppiSize oSrcSize`, `int nSrcStep`, `NppiRect oSrcROI`, `Npp32s * pDst`, `int nDstStep`, `NppiRect oDstROI`, `const double aCoeffs[2][3]`, `int eInterpolation`)

Four-channel 32-bit signed affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be `NPPI_INTER_NN`, `NPPI_INTER_LINEAR` or `NPPI_INTER_CUBIC`

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.20 `NppStatus nppiWarpAffine_32s_P3R (const Npp32s * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel planar 32-bit signed affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.21 `NppStatus nppiWarpAffine_32s_P4R (const Npp32s * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel planar 32-bit signed affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.22 `NppStatus nppiWarpAffine_64f_AC4R (const Npp64f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp64f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel 64-bit floating-point affine warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.23 `NppStatus nppiWarpAffine_64f_C1R (const Npp64f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp64f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Single-channel 64-bit floating-point affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.24 NppStatus nppiWarpAffine_64f_C3R (const Npp64f * *pSrc*, NppiSize *oSrcSize*, int *nSrcStep*, NppiRect *oSrcROI*, Npp64f * *pDst*, int *nDstStep*, NppiRect *oDstROI*, const double *aCoeffs*[2][3], int *eInterpolation*)

Three-channel 64-bit floating-point affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.25 NppStatus nppiWarpAffine_64f_C4R (const Npp64f * *pSrc*, NppiSize *oSrcSize*, int *nSrcStep*, NppiRect *oSrcROI*, Npp64f * *pDst*, int *nDstStep*, NppiRect *oDstROI*, const double *aCoeffs*[2][3], int *eInterpolation*)

Four-channel 64-bit floating-point affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.26 `NppStatus nppiWarpAffine_64f_P3R (const Npp64f * aSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp64f * aDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel planar 64-bit floating-point affine warp.

Parameters:

aSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.27 `NppStatus nppiWarpAffine_64f_P4R (const Npp64f * aSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp64f * aDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel planar 64-bit floating-point affine warp.

Parameters:

aSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.28 `NppStatus nppiWarpAffine_8u_AC4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel 8-bit unsigned affine warp, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.29 `NppStatus nppiWarpAffine_8u_C1R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Single-channel 8-bit unsigned affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.30 `NppStatus nppiWarpAffine_8u_C3R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel 8-bit unsigned affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.31 `NppStatus nppiWarpAffine_8u_C4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel 8-bit unsigned affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.32 `NppStatus nppiWarpAffine_8u_P3R (const Npp8u * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel planar 8-bit unsigned affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.33 `NppStatus nppiWarpAffine_8u_P4R (const Npp8u * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel planar 8-bit unsigned affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.34 `NppStatus nppiWarpAffineBack_16u_AC4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel 16-bit unsigned integer backwards affine warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.35 `NppStatus nppiWarpAffineBack_16u_C1R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Single-channel 16-bit unsigned integer backwards affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.36 `NppStatus nppiWarpAffineBack_16u_C3R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel 16-bit unsigned integer backwards affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.37 `NppStatus nppiWarpAffineBack_16u_C4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel 16-bit unsigned integer backwards affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.38 `NppStatus nppiWarpAffineBack_16u_P3R (const Npp16u * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel planar 16-bit unsigned integer backwards affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.39 `NppStatus nppiWarpAffineBack_16u_P4R (const Npp16u * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel planar 16-bit unsigned integer backwards affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.40 `NppStatus nppiWarpAffineBack_32f_AC4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel 32-bit floating-point backwards affine warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.41 `NppStatus nppiWarpAffineBack_32f_C1R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Single-channel 32-bit floating-point backwards affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.42 `NppStatus nppiWarpAffineBack_32f_C3R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel 32-bit floating-point backwards affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.43 `NppStatus nppiWarpAffineBack_32f_C4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel 32-bit floating-point backwards affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.44 `NppStatus nppiWarpAffineBack_32f_P3R (const Npp32f * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel planar 32-bit floating-point backwards affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.45 `NppStatus nppiWarpAffineBack_32f_P4R (const Npp32f * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel planar 32-bit floating-point backwards affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.46 `NppStatus nppiWarpAffineBack_32s_AC4R` (`const Npp32s * pSrc`, `NppiSize oSrcSize`, `int nSrcStep`, `NppiRect oSrcROI`, `Npp32s * pDst`, `int nDstStep`, `NppiRect oDstROI`, `const double aCoeffs[2][3]`, `int eInterpolation`)

Four-channel 32-bit signed integer backwards affine warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.47 `NppStatus nppiWarpAffineBack_32s_C1R` (`const Npp32s * pSrc`, `NppiSize oSrcSize`, `int nSrcStep`, `NppiRect oSrcROI`, `Npp32s * pDst`, `int nDstStep`, `NppiRect oDstROI`, `const double aCoeffs[2][3]`, `int eInterpolation`)

Single-channel 32-bit signed integer backwards affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.48 `NppStatus nppiWarpAffineBack_32s_C3R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel 32-bit signed integer backwards affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.49 `NppStatus nppiWarpAffineBack_32s_C4R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel 32-bit signed integer backwards affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.50 `NppStatus nppiWarpAffineBack_32s_P3R (const Npp32s * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel planar 32-bit signed integer backwards affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.51 `NppStatus nppiWarpAffineBack_32s_P4R (const Npp32s * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel planar 32-bit signed integer backwards affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.52 `NppStatus nppiWarpAffineBack_8u_AC4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel 8-bit unsigned integer backwards affine warp, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.53 `NppStatus nppiWarpAffineBack_8u_C1R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Single-channel 8-bit unsigned integer backwards affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.54 `NppStatus nppiWarpAffineBack_8u_C3R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel 8-bit unsigned integer backwards affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.55 `NppStatus nppiWarpAffineBack_8u_C4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel 8-bit unsigned integer backwards affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.56 `NppStatus nppiWarpAffineBack_8u_P3R (const Npp8u * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel planar 8-bit unsigned integer backwards affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.57 `NppStatus nppiWarpAffineBack_8u_P4R (const Npp8u * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel planar 8-bit unsigned integer backwards affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.58 `NppStatus nppiWarpAffineQuad_16u_AC4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 16-bit unsigned integer quad-based affine warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.59 `NppStatus nppiWarpAffineQuad_16u_C1R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Single-channel 16-bit unsigned integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.60 `NppStatus nppiWarpAffineQuad_16u_C3R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel 16-bit unsigned integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.61 `NppStatus nppiWarpAffineQuad_16u_C4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 16-bit unsigned integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.62 `NppStatus nppiWarpAffineQuad_16u_P3R (const Npp16u * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp16u * pDst[3], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel planar 16-bit unsigned integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.63 `NppStatus nppiWarpAffineQuad_16u_P4R (const Npp16u * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp16u * pDst[4], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel planar 16-bit unsigned integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.64 `NppStatus nppiWarpAffineQuad_32f_AC4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 32-bit floating-point quad-based affine warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.65 `NppStatus nppiWarpAffineQuad_32f_C1R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Single-channel 32-bit floating-point quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.66 `NppStatus nppiWarpAffineQuad_32f_C3R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel 32-bit floating-point quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.67 `NppStatus nppiWarpAffineQuad_32f_C4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 32-bit floating-point quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.68 `NppStatus nppiWarpAffineQuad_32f_P3R (const Npp32f * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32f * pDst[3], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel planar 32-bit floating-point quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.69 `NppStatus nppiWarpAffineQuad_32f_P4R (const Npp32f * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32f * pDst[4], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel planar 32-bit floating-point quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.70 `NppStatus nppiWarpAffineQuad_32s_AC4R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 32-bit signed integer quad-based affine warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.71 `NppStatus nppiWarpAffineQuad_32s_C1R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Single-channel 32-bit signed integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.72 `NppStatus nppiWarpAffineQuad_32s_C3R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel 32-bit signed integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.73 `NppStatus nppiWarpAffineQuad_32s_C4R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 32-bit signed integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.74 `NppStatus nppiWarpAffineQuad_32s_P3R (const Npp32s * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32s * pDst[3], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel planar 32-bit signed integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.75 `NppStatus nppiWarpAffineQuad_32s_P4R (const Npp32s * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32s * pDst[4], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel planar 32-bit signed integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.76 `NppStatus nppiWarpAffineQuad_8u_AC4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 8-bit unsigned integer quad-based affine warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.77 `NppStatus nppiWarpAffineQuad_8u_C1R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Single-channel 32-bit floating-point quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.78 `NppStatus nppiWarpAffineQuad_8u_C3R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel 8-bit unsigned integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.79 `NppStatus nppiWarpAffineQuad_8u_C4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 8-bit unsigned integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.80 `NppStatus nppiWarpAffineQuad_8u_P3R (const Npp8u * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp8u * pDst[3], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel planar 8-bit unsigned integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.78.3.81 `NppStatus nppiWarpAffineQuad_8u_P4R (const Npp8u * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp8u * pDst[4], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel planar 8-bit unsigned integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.79 Perspective Transform

Utility Functions

- `NppStatus nppiGetPerspectiveTransform` (`NppiRect` oSrcROI, `const double quad[4][2]`, `double aCoeffs[3][3]`)
Calculates perspective transform coefficients given source rectangular ROI and its destination quadrangle projection.
- `NppStatus nppiGetPerspectiveQuad` (`NppiRect` oSrcROI, `double quad[4][2]`, `const double aCoeffs[3][3]`)
Calculates perspective transform projection of given source rectangular ROI.
- `NppStatus nppiGetPerspectiveBound` (`NppiRect` oSrcROI, `double bound[2][2]`, `const double aCoeffs[3][3]`)
Calculates bounding box of the perspective transform projection of the given source rectangular ROI.

Perspective Transform

Transforms (warps) an image based on a perspective transform.

The perspective transform is given as a 3×3 matrix C . A pixel location (x, y) in the source image is mapped to the location (x', y') in the destination image. The destination image coordinates are computed as follows:

$$x' = \frac{c_{00} * x + c_{01} * y + c_{02}}{c_{20} * x + c_{21} * y + c_{22}} \quad y' = \frac{c_{10} * x + c_{11} * y + c_{12}}{c_{20} * x + c_{21} * y + c_{22}}$$

$$C = \begin{bmatrix} c_{00} & c_{01} & c_{02} \\ c_{10} & c_{11} & c_{12} \\ c_{20} & c_{21} & c_{22} \end{bmatrix}$$

- `NppStatus nppiWarpPerspective_8u_C1R` (`const Npp8u *pSrc`, `NppiSize` oSrcSize, `int nSrcStep`, `NppiRect` oSrcROI, `Npp8u *pDst`, `int nDstStep`, `NppiRect` oDstROI, `const double aCoeffs[3][3]`, `int eInterpolation`)
Single-channel 8-bit unsigned integer perspective warp.
- `NppStatus nppiWarpPerspective_8u_C3R` (`const Npp8u *pSrc`, `NppiSize` oSrcSize, `int nSrcStep`, `NppiRect` oSrcROI, `Npp8u *pDst`, `int nDstStep`, `NppiRect` oDstROI, `const double aCoeffs[3][3]`, `int eInterpolation`)
Three-channel 8-bit unsigned integer perspective warp.
- `NppStatus nppiWarpPerspective_8u_C4R` (`const Npp8u *pSrc`, `NppiSize` oSrcSize, `int nSrcStep`, `NppiRect` oSrcROI, `Npp8u *pDst`, `int nDstStep`, `NppiRect` oDstROI, `const double aCoeffs[3][3]`, `int eInterpolation`)
Four-channel 8-bit unsigned integer perspective warp.
- `NppStatus nppiWarpPerspective_8u_AC4R` (`const Npp8u *pSrc`, `NppiSize` oSrcSize, `int nSrcStep`, `NppiRect` oSrcROI, `Npp8u *pDst`, `int nDstStep`, `NppiRect` oDstROI, `const double aCoeffs[3][3]`, `int eInterpolation`)
Four-channel 8-bit unsigned integer perspective warp, ignoring alpha channel.

- **NppStatus nppiWarpPerspective_8u_P3R** (const **Npp8u** *pSrc[3], **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp8u** *pDst[3], int nDstStep, **NppiRect** oDstROI, const double aCoeffs[3][3], int eInterpolation)
Three-channel planar 8-bit unsigned integer perspective warp.
- **NppStatus nppiWarpPerspective_8u_P4R** (const **Npp8u** *pSrc[4], **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp8u** *pDst[4], int nDstStep, **NppiRect** oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel planar 8-bit unsigned integer perspective warp.
- **NppStatus nppiWarpPerspective_16u_C1R** (const **Npp16u** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp16u** *pDst, int nDstStep, **NppiRect** oDstROI, const double aCoeffs[3][3], int eInterpolation)
Single-channel 16-bit unsigned integer perspective warp.
- **NppStatus nppiWarpPerspective_16u_C3R** (const **Npp16u** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp16u** *pDst, int nDstStep, **NppiRect** oDstROI, const double aCoeffs[3][3], int eInterpolation)
Three-channel 16-bit unsigned integer perspective warp.
- **NppStatus nppiWarpPerspective_16u_C4R** (const **Npp16u** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp16u** *pDst, int nDstStep, **NppiRect** oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel 16-bit unsigned integer perspective warp.
- **NppStatus nppiWarpPerspective_16u_AC4R** (const **Npp16u** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp16u** *pDst, int nDstStep, **NppiRect** oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel 16-bit unsigned integer perspective warp, ignoring alpha channel.
- **NppStatus nppiWarpPerspective_16u_P3R** (const **Npp16u** *pSrc[3], **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp16u** *pDst[3], int nDstStep, **NppiRect** oDstROI, const double aCoeffs[3][3], int eInterpolation)
Three-channel planar 16-bit unsigned integer perspective warp.
- **NppStatus nppiWarpPerspective_16u_P4R** (const **Npp16u** *pSrc[4], **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp16u** *pDst[4], int nDstStep, **NppiRect** oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel planar 16-bit unsigned integer perspective warp.
- **NppStatus nppiWarpPerspective_32s_C1R** (const **Npp32s** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp32s** *pDst, int nDstStep, **NppiRect** oDstROI, const double aCoeffs[3][3], int eInterpolation)
Single-channel 32-bit signed integer perspective warp.
- **NppStatus nppiWarpPerspective_32s_C3R** (const **Npp32s** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp32s** *pDst, int nDstStep, **NppiRect** oDstROI, const double aCoeffs[3][3], int eInterpolation)
Three-channel 32-bit signed integer perspective warp.

- `NppStatus nppiWarpPerspective_32s_C4R` (const `Npp32s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32s` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel 32-bit signed integer perspective warp.
- `NppStatus nppiWarpPerspective_32s_AC4R` (const `Npp32s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32s` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel 32-bit signed integer perspective warp, ignoring alpha channel.
- `NppStatus nppiWarpPerspective_32s_P3R` (const `Npp32s` *pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32s` *pDst[3], int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Three-channel planar 32-bit signed integer perspective warp.
- `NppStatus nppiWarpPerspective_32s_P4R` (const `Npp32s` *pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32s` *pDst[4], int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel planar 32-bit signed integer perspective warp.
- `NppStatus nppiWarpPerspective_32f_C1R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Single-channel 32-bit floating-point perspective warp.
- `NppStatus nppiWarpPerspective_32f_C3R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Three-channel 32-bit floating-point perspective warp.
- `NppStatus nppiWarpPerspective_32f_C4R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel 32-bit floating-point perspective warp.
- `NppStatus nppiWarpPerspective_32f_AC4R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel 32-bit floating-point perspective warp, ignoring alpha channel.
- `NppStatus nppiWarpPerspective_32f_P3R` (const `Npp32f` *pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst[3], int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Three-channel planar 32-bit floating-point perspective warp.
- `NppStatus nppiWarpPerspective_32f_P4R` (const `Npp32f` *pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst[4], int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel planar 32-bit floating-point perspective warp.

Backwards Perspective Transform

Transforms (warps) an image based on a perspective transform.

The perspective transform is given as a 3×3 matrix C . A pixel location (x, y) in the source image is mapped to the location (x', y') in the destination image. The destination image coordinates fulfill the following properties:

$$x = \frac{c_{00} * x' + c_{01} * y' + c_{02}}{c_{20} * x' + c_{21} * y' + c_{22}} \quad y = \frac{c_{10} * x' + c_{11} * y' + c_{12}}{c_{20} * x' + c_{21} * y' + c_{22}}$$

$$C = \begin{bmatrix} c_{00} & c_{01} & c_{02} \\ c_{10} & c_{11} & c_{12} \\ c_{20} & c_{21} & c_{22} \end{bmatrix}$$

In other words, given matrix C the source image's shape is transformed to the destination image using the inverse matrix C^{-1} :

$$M = C^{-1} = \begin{bmatrix} m_{00} & m_{01} & m_{02} \\ m_{10} & m_{11} & m_{12} \\ m_{20} & m_{21} & m_{22} \end{bmatrix} \quad x' = \frac{c_{00} * x + c_{01} * y + c_{02}}{c_{20} * x + c_{21} * y + c_{22}} \quad y' = \frac{c_{10} * x + c_{11} * y + c_{12}}{c_{20} * x + c_{21} * y + c_{22}}$$

- `NppStatus nppiWarpPerspectiveBack_8u_C1R` (const `Npp8u *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp8u *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)
Single-channel 8-bit unsigned integer backwards perspective warp.
- `NppStatus nppiWarpPerspectiveBack_8u_C3R` (const `Npp8u *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp8u *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)
Three-channel 8-bit unsigned integer backwards perspective warp.
- `NppStatus nppiWarpPerspectiveBack_8u_C4R` (const `Npp8u *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp8u *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)
Four-channel 8-bit unsigned integer backwards perspective warp.
- `NppStatus nppiWarpPerspectiveBack_8u_AC4R` (const `Npp8u *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp8u *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)
Four-channel 8-bit unsigned integer backwards perspective warp, ignoring alpha channel.
- `NppStatus nppiWarpPerspectiveBack_8u_P3R` (const `Npp8u *pSrc[3]`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp8u *pDst[3]`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)
Three-channel planar 8-bit unsigned integer backwards perspective warp.
- `NppStatus nppiWarpPerspectiveBack_8u_P4R` (const `Npp8u *pSrc[4]`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp8u *pDst[4]`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)
Four-channel planar 8-bit unsigned integer backwards perspective warp.
- `NppStatus nppiWarpPerspectiveBack_16u_C1R` (const `Npp16u *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp16u *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Single-channel 16-bit unsigned integer backwards perspective warp.

- `NppStatus nppiWarpPerspectiveBack_16u_C3R` (const `Npp16u *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp16u *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Three-channel 16-bit unsigned integer backwards perspective warp.

- `NppStatus nppiWarpPerspectiveBack_16u_C4R` (const `Npp16u *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp16u *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Four-channel 16-bit unsigned integer backwards perspective warp.

- `NppStatus nppiWarpPerspectiveBack_16u_AC4R` (const `Npp16u *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp16u *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Four-channel 16-bit unsigned integer backwards perspective warp, ignoring alpha channel.

- `NppStatus nppiWarpPerspectiveBack_16u_P3R` (const `Npp16u *pSrc[3]`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp16u *pDst[3]`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Four-channel planar 16-bit unsigned integer backwards perspective warp.

- `NppStatus nppiWarpPerspectiveBack_16u_P4R` (const `Npp16u *pSrc[4]`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp16u *pDst[4]`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Four-channel planar 16-bit unsigned integer backwards perspective warp.

- `NppStatus nppiWarpPerspectiveBack_32s_C1R` (const `Npp32s *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp32s *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Single-channel 32-bit signed integer backwards perspective warp.

- `NppStatus nppiWarpPerspectiveBack_32s_C3R` (const `Npp32s *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp32s *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Three-channel 32-bit signed integer backwards perspective warp.

- `NppStatus nppiWarpPerspectiveBack_32s_C4R` (const `Npp32s *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp32s *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Four-channel 32-bit signed integer backwards perspective warp.

- `NppStatus nppiWarpPerspectiveBack_32s_AC4R` (const `Npp32s *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp32s *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Four-channel 32-bit signed integer backwards perspective warp, ignoring alpha channel.

- `NppStatus nppiWarpPerspectiveBack_32s_P3R` (const `Npp32s *pSrc[3]`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp32s *pDst[3]`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Three-channel planar 32-bit signed integer backwards perspective warp.

- `NppStatus nppiWarpPerspectiveBack_32s_P4R` (const `Npp32s *pSrc[4]`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp32s *pDst[4]`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)
Four-channel planar 32-bit signed integer backwards perspective warp.
- `NppStatus nppiWarpPerspectiveBack_32f_C1R` (const `Npp32f *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp32f *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)
Single-channel 32-bit floating-point backwards perspective warp.
- `NppStatus nppiWarpPerspectiveBack_32f_C3R` (const `Npp32f *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp32f *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)
Three-channel 32-bit floating-point backwards perspective warp.
- `NppStatus nppiWarpPerspectiveBack_32f_C4R` (const `Npp32f *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp32f *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)
Four-channel 32-bit floating-point backwards perspective warp.
- `NppStatus nppiWarpPerspectiveBack_32f_AC4R` (const `Npp32f *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp32f *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)
Four-channel 32-bit floating-point backwards perspective warp, ignoring alpha channel.
- `NppStatus nppiWarpPerspectiveBack_32f_P3R` (const `Npp32f *pSrc[3]`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp32f *pDst[3]`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)
Three-channel planar 32-bit floating-point backwards perspective warp.
- `NppStatus nppiWarpPerspectiveBack_32f_P4R` (const `Npp32f *pSrc[4]`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp32f *pDst[4]`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)
Four-channel planar 32-bit floating-point backwards perspective warp.

Quad-Based Perspective Transform

Transforms (warps) an image based on an perspective transform.

The perspective transform is computed such that it maps a quadrilateral in source image space to a quadrilateral in destination image space.

- `NppStatus nppiWarpPerspectiveQuad_8u_C1R` (const `Npp8u *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, const double `aSrcQuad[4][2]`, `Npp8u *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)
Single-channel 8-bit unsigned integer quad-based perspective warp.
- `NppStatus nppiWarpPerspectiveQuad_8u_C3R` (const `Npp8u *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, const double `aSrcQuad[4][2]`, `Npp8u *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Three-channel 8-bit unsigned integer quad-based perspective warp.

- `NppStatus nppiWarpPerspectiveQuad_8u_C4R` (const `Npp8u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp8u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Four-channel 8-bit unsigned integer quad-based perspective warp.

- `NppStatus nppiWarpPerspectiveQuad_8u_AC4R` (const `Npp8u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp8u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Four-channel 8-bit unsigned integer quad-based perspective warp, ignoring alpha channel.

- `NppStatus nppiWarpPerspectiveQuad_8u_P3R` (const `Npp8u *pSrc[3]`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp8u *pDst[3]`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Three-channel planar 8-bit unsigned integer quad-based perspective warp.

- `NppStatus nppiWarpPerspectiveQuad_8u_P4R` (const `Npp8u *pSrc[4]`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp8u *pDst[4]`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Four-channel planar 8-bit unsigned integer quad-based perspective warp.

- `NppStatus nppiWarpPerspectiveQuad_16u_C1R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp16u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Single-channel 16-bit unsigned integer quad-based perspective warp.

- `NppStatus nppiWarpPerspectiveQuad_16u_C3R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp16u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Three-channel 16-bit unsigned integer quad-based perspective warp.

- `NppStatus nppiWarpPerspectiveQuad_16u_C4R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp16u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Four-channel 16-bit unsigned integer quad-based perspective warp.

- `NppStatus nppiWarpPerspectiveQuad_16u_AC4R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp16u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Four-channel 16-bit unsigned integer quad-based perspective warp, ignoring alpha channel.

- `NppStatus nppiWarpPerspectiveQuad_16u_P3R` (const `Npp16u *pSrc[3]`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp16u *pDst[3]`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Three-channel planar 16-bit unsigned integer quad-based perspective warp.

- `NppStatus nppiWarpPerspectiveQuad_16u_P4R` (const `Npp16u *pSrc[4]`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp16u *pDst[4]`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Four-channel planar 16-bit unsigned integer quad-based perspective warp.

- [NppStatus nppiWarpPerspectiveQuad_32s_C1R](#) (const [Npp32s](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const double aSrcQuad[4][2], [Npp32s](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, const double aDstQuad[4][2], int eInterpolation)
Single-channel 32-bit signed integer quad-based perspective warp.
- [NppStatus nppiWarpPerspectiveQuad_32s_C3R](#) (const [Npp32s](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const double aSrcQuad[4][2], [Npp32s](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, const double aDstQuad[4][2], int eInterpolation)
Three-channel 32-bit signed integer quad-based perspective warp.
- [NppStatus nppiWarpPerspectiveQuad_32s_C4R](#) (const [Npp32s](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const double aSrcQuad[4][2], [Npp32s](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, const double aDstQuad[4][2], int eInterpolation)
Four-channel 32-bit signed integer quad-based perspective warp.
- [NppStatus nppiWarpPerspectiveQuad_32s_AC4R](#) (const [Npp32s](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const double aSrcQuad[4][2], [Npp32s](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, const double aDstQuad[4][2], int eInterpolation)
Four-channel 32-bit signed integer quad-based perspective warp, ignoring alpha channel.
- [NppStatus nppiWarpPerspectiveQuad_32s_P3R](#) (const [Npp32s](#) *pSrc[3], [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const double aSrcQuad[4][2], [Npp32s](#) *pDst[3], int nDstStep, [NppiRect](#) oDstROI, const double aDstQuad[4][2], int eInterpolation)
Three-channel planar 32-bit signed integer quad-based perspective warp.
- [NppStatus nppiWarpPerspectiveQuad_32s_P4R](#) (const [Npp32s](#) *pSrc[4], [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const double aSrcQuad[4][2], [Npp32s](#) *pDst[4], int nDstStep, [NppiRect](#) oDstROI, const double aDstQuad[4][2], int eInterpolation)
Four-channel planar 32-bit signed integer quad-based perspective warp.
- [NppStatus nppiWarpPerspectiveQuad_32f_C1R](#) (const [Npp32f](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const double aSrcQuad[4][2], [Npp32f](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, const double aDstQuad[4][2], int eInterpolation)
Single-channel 32-bit floating-point quad-based perspective warp.
- [NppStatus nppiWarpPerspectiveQuad_32f_C3R](#) (const [Npp32f](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const double aSrcQuad[4][2], [Npp32f](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, const double aDstQuad[4][2], int eInterpolation)
Three-channel 32-bit floating-point quad-based perspective warp.
- [NppStatus nppiWarpPerspectiveQuad_32f_C4R](#) (const [Npp32f](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const double aSrcQuad[4][2], [Npp32f](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, const double aDstQuad[4][2], int eInterpolation)
Four-channel 32-bit floating-point quad-based perspective warp.
- [NppStatus nppiWarpPerspectiveQuad_32f_AC4R](#) (const [Npp32f](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const double aSrcQuad[4][2], [Npp32f](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, const double aDstQuad[4][2], int eInterpolation)
Four-channel 32-bit floating-point quad-based perspective warp, ignoring alpha channel.

- `NppStatus nppiWarpPerspectiveQuad_32f_P3R` (const `Npp32f *pSrc[3]`, `NppiSize oSrcSize`, `int nSrcStep`, `NppiRect oSrcROI`, const double `aSrcQuad[4][2]`, `Npp32f *pDst[3]`, `int nDstStep`, `NppiRect oDstROI`, const double `aDstQuad[4][2]`, `int eInterpolation`)

Three-channel planar 32-bit floating-point quad-based perspective warp.

- `NppStatus nppiWarpPerspectiveQuad_32f_P4R` (const `Npp32f *pSrc[4]`, `NppiSize oSrcSize`, `int nSrcStep`, `NppiRect oSrcROI`, const double `aSrcQuad[4][2]`, `Npp32f *pDst[4]`, `int nDstStep`, `NppiRect oDstROI`, const double `aDstQuad[4][2]`, `int eInterpolation`)

Four-channel planar 32-bit floating-point quad-based perspective warp.

7.79.1 Detailed Description

7.79.2 Perspective Transform Error Codes

- `NPP_RECT_ERROR` Indicates an error condition if width or height of the intersection of the `oSrcROI` and source image is less than or equal to 1
- `NPP_WRONG_INTERSECTION_ROI_ERROR` Indicates an error condition if `oSrcROI` has no intersection with the source image
- `NPP_INTERPOLATION_ERROR` Indicates an error condition if interpolation has an illegal value
- `NPP_COEFF_ERROR` Indicates an error condition if coefficient values are invalid
- `NPP_WRONG_INTERSECTION_QUAD_WARNING` Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI

7.79.3 Function Documentation

7.79.3.1 `NppStatus nppiGetPerspectiveBound` (`NppiRect oSrcROI`, double `bound[2][2]`, const double `aCoeffs[3][3]`)

Calculates bounding box of the perspective transform projection of the given source rectangular ROI.

Parameters:

`oSrcROI` Source ROI

`bound` Bounding box of the transformed source ROI

`aCoeffs` Perspective transform coefficients

Returns:

Error codes:

- `NPP_SIZE_ERROR` Indicates an error condition if any image dimension has zero or negative value
- `NPP_RECT_ERROR` Indicates an error condition if width or height of the intersection of the `oSrcROI` and source image is less than or equal to 1
- `NPP_COEFF_ERROR` Indicates an error condition if coefficient values are invalid

7.79.3.2 NppStatus nppiGetPerspectiveQuad (NppiRect *oSrcROI*, double *quad*[4][2], const double *aCoeffs*[3][3])

Calculates perspective transform projection of given source rectangular ROI.

Parameters:

oSrcROI Source ROI
quad Destination quadrangle
aCoeffs Perspective transform coefficients

Returns:

Error codes:

- [NPP_SIZE_ERROR](#) Indicates an error condition if any image dimension has zero or negative value
- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *oSrcROI* and source image is less than or equal to 1
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid

7.79.3.3 NppStatus nppiGetPerspectiveTransform (NppiRect *oSrcROI*, const double *quad*[4][2], double *aCoeffs*[3][3])

Calculates perspective transform coefficients given source rectangular ROI and its destination quadrangle projection.

Parameters:

oSrcROI Source ROI
quad Destination quadrangle
aCoeffs Perspective transform coefficients

Returns:

Error codes:

- [NPP_SIZE_ERROR](#) Indicates an error condition if any image dimension has zero or negative value
- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *oSrcROI* and source image is less than or equal to 1
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid

7.79.3.4 NppStatus nppiWarpPerspective_16u_AC4R (const Npp16u * *pSrc*, NppiSize *oSrcSize*, int *nSrcStep*, NppiRect *oSrcROI*, Npp16u * *pDst*, int *nDstStep*, NppiRect *oDstROI*, const double *aCoeffs*[3][3], int *eInterpolation*)

Four-channel 16-bit unsigned integer perspective warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels
nSrcStep [Source-Image Line Step](#).
oSrcROI Source ROI
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oDstROI Destination ROI
aCoeffs Perspective transform coefficients
eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.5 NppStatus nppiWarpPerspective_16u_C1R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)

Single-channel 16-bit unsigned integer perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).
oSrcSize Size of source image in pixels
nSrcStep [Source-Image Line Step](#).
oSrcROI Source ROI
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oDstROI Destination ROI
aCoeffs Perspective transform coefficients
eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.6 NppStatus nppiWarpPerspective_16u_C3R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)

Three-channel 16-bit unsigned integer perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).
oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.
oSrcROI Source ROI
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstROI Destination ROI
aCoeffs Perspective transform coefficients
eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

Image Data Related Error Codes, ROI Related Error Codes, Perspective Transform Error Codes

7.79.3.7 `NppStatus nppiWarpPerspective_16u_C4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel 16-bit unsigned integer perspective warp.

Parameters:

pSrc Source-Image Pointer.
oSrcSize Size of source image in pixels
nSrcStep Source-Image Line Step.
oSrcROI Source ROI
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstROI Destination ROI
aCoeffs Perspective transform coefficients
eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

Image Data Related Error Codes, ROI Related Error Codes, Perspective Transform Error Codes

7.79.3.8 `NppStatus nppiWarpPerspective_16u_P3R (const Npp16u * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Three-channel planar 16-bit unsigned integer perspective warp.

Parameters:

pSrc Source-Image Pointer.
oSrcSize Size of source image in pixels
nSrcStep Source-Image Line Step.

oSrcROI Source ROI
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstROI Destination ROI
aCoeffs Perspective transform coefficients
eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.9 `NppStatus nppiWarpPerspective_16u_P4R (const Npp16u * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel planar 16-bit unsigned integer perspective warp.

Parameters:

pSrc Source-Image Pointer.
oSrcSize Size of source image in pixels
nSrcStep Source-Image Line Step.
oSrcROI Source ROI
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstROI Destination ROI
aCoeffs Perspective transform coefficients
eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.10 `NppStatus nppiWarpPerspective_32f_AC4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel 32-bit floating-point perspective warp, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
oSrcSize Size of source image in pixels
nSrcStep Source-Image Line Step.
oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.11 `NppStatus nppiWarpPerspective_32f_C1R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Single-channel 32-bit floating-point perspective warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.12 `NppStatus nppiWarpPerspective_32f_C3R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Three-channel 32-bit floating-point perspective warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.13 `NppStatus nppiWarpPerspective_32f_C4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel 32-bit floating-point perspective warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.14 `NppStatus nppiWarpPerspective_32f_P3R (const Npp32f * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Three-channel planar 32-bit floating-point perspective warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.15 `NppStatus nppiWarpPerspective_32f_P4R (const Npp32f * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel planar 32-bit floating-point perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.16 `NppStatus nppiWarpPerspective_32s_AC4R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel 32-bit signed integer perspective warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.17 `NppStatus nppiWarpPerspective_32s_C1R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Single-channel 32-bit signed integer perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.18 `NppStatus nppiWarpPerspective_32s_C3R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Three-channel 32-bit signed integer perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.19 `NppStatus nppiWarpPerspective_32s_C4R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel 32-bit signed integer perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.20 `NppStatus nppiWarpPerspective_32s_P3R (const Npp32s * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Three-channel planar 32-bit signed integer perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.21 `NppStatus nppiWarpPerspective_32s_P4R (const Npp32s * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel planar 32-bit signed integer perspective warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.22 `NppStatus nppiWarpPerspective_8u_AC4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel 8-bit unsigned integer perspective warp, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.23 `NppStatus nppiWarpPerspective_8u_C1R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Single-channel 8-bit unsigned integer perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.24 `NppStatus nppiWarpPerspective_8u_C3R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Three-channel 8-bit unsigned integer perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.25 `NppStatus nppiWarpPerspective_8u_C4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel 8-bit unsigned integer perspective warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.26 `NppStatus nppiWarpPerspective_8u_P3R (const Npp8u * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Three-channel planar 8-bit unsigned integer perspective warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.27 `NppStatus nppiWarpPerspective_8u_P4R (const Npp8u * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel planar 8-bit unsigned integer perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.28 `NppStatus nppiWarpPerspectiveBack_16u_AC4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel 16-bit unsigned integer backwards perspective warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.29 `NppStatus nppiWarpPerspectiveBack_16u_C1R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Single-channel 16-bit unsigned integer backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.30 `NppStatus nppiWarpPerspectiveBack_16u_C3R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Three-channel 16-bit unsigned integer backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.31 `NppStatus nppiWarpPerspectiveBack_16u_C4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel 16-bit unsigned integer backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.32 `NppStatus nppiWarpPerspectiveBack_16u_P3R (const Npp16u * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel planar 16-bit unsigned integer backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.33 `NppStatus nppiWarpPerspectiveBack_16u_P4R (const Npp16u * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel planar 16-bit unsigned integer backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.34 `NppStatus nppiWarpPerspectiveBack_32f_AC4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel 32-bit floating-point backwards perspective warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.35 `NppStatus nppiWarpPerspectiveBack_32f_C1R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Single-channel 32-bit floating-point backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.36 `NppStatus nppiWarpPerspectiveBack_32f_C3R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Three-channel 32-bit floating-point backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.37 `NppStatus nppiWarpPerspectiveBack_32f_C4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel 32-bit floating-point backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.38 `NppStatus nppiWarpPerspectiveBack_32f_P3R (const Npp32f * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Three-channel planar 32-bit floating-point backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.39 `NppStatus nppiWarpPerspectiveBack_32f_P4R (const Npp32f * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel planar 32-bit floating-point backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.40 `NppStatus nppiWarpPerspectiveBack_32s_AC4R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel 32-bit signed integer backwards perspective warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.41 `NppStatus nppiWarpPerspectiveBack_32s_C1R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Single-channel 32-bit signed integer backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.42 `NppStatus nppiWarpPerspectiveBack_32s_C3R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Three-channel 32-bit signed integer backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.43 NppStatus nppiWarpPerspectiveBack_32s_C4R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)

Four-channel 32-bit signed integer backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.44 NppStatus nppiWarpPerspectiveBack_32s_P3R (const Npp32s * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)

Three-channel planar 32-bit signed integer backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.45 `NppStatus nppiWarpPerspectiveBack_32s_P4R (const Npp32s * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel planar 32-bit signed integer backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.46 `NppStatus nppiWarpPerspectiveBack_8u_AC4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel 8-bit unsigned integer backwards perspective warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.47 `NppStatus nppiWarpPerspectiveBack_8u_C1R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Single-channel 8-bit unsigned integer backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.48 `NppStatus nppiWarpPerspectiveBack_8u_C3R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Three-channel 8-bit unsigned integer backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.49 `NppStatus nppiWarpPerspectiveBack_8u_C4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel 8-bit unsigned integer backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.50 `NppStatus nppiWarpPerspectiveBack_8u_P3R (const Npp8u * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Three-channel planar 8-bit unsigned integer backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.51 `NppStatus nppiWarpPerspectiveBack_8u_P4R (const Npp8u * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel planar 8-bit unsigned integer backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.52 `NppStatus nppiWarpPerspectiveQuad_16u_AC4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 16-bit unsigned integer quad-based perspective warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.53 `NppStatus nppiWarpPerspectiveQuad_16u_C1R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Single-channel 16-bit unsigned integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.54 `NppStatus nppiWarpPerspectiveQuad_16u_C3R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel 16-bit unsigned integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.55 `NppStatus nppiWarpPerspectiveQuad_16u_C4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 16-bit unsigned integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.56 `NppStatus nppiWarpPerspectiveQuad_16u_P3R (const Npp16u * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp16u * pDst[3], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel planar 16-bit unsigned integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.57 `NppStatus nppiWarpPerspectiveQuad_16u_P4R (const Npp16u * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp16u * pDst[4], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel planar 16-bit unsigned integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.58 `NppStatus nppiWarpPerspectiveQuad_32f_AC4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 32-bit floating-point quad-based perspective warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.59 `NppStatus nppiWarpPerspectiveQuad_32f_C1R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Single-channel 32-bit floating-point quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.60 `NppStatus nppiWarpPerspectiveQuad_32f_C3R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel 32-bit floating-point quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.61 `NppStatus nppiWarpPerspectiveQuad_32f_C4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 32-bit floating-point quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.62 `NppStatus nppiWarpPerspectiveQuad_32f_P3R (const Npp32f * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32f * pDst[3], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel planar 32-bit floating-point quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.63 `NppStatus nppiWarpPerspectiveQuad_32f_P4R (const Npp32f * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32f * pDst[4], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel planar 32-bit floating-point quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.64 `NppStatus nppiWarpPerspectiveQuad_32s_AC4R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 32-bit signed integer quad-based perspective warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.65 `NppStatus nppiWarpPerspectiveQuad_32s_C1R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Single-channel 32-bit signed integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.66 `NppStatus nppiWarpPerspectiveQuad_32s_C3R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel 32-bit signed integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.67 `NppStatus nppiWarpPerspectiveQuad_32s_C4R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 32-bit signed integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.68 `NppStatus nppiWarpPerspectiveQuad_32s_P3R (const Npp32s * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32s * pDst[3], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel planar 32-bit signed integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.69 `NppStatus nppiWarpPerspectiveQuad_32s_P4R (const Npp32s * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32s * pDst[4], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel planar 32-bit signed integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.70 `NppStatus nppiWarpPerspectiveQuad_8u_AC4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 8-bit unsigned integer quad-based perspective warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.71 `NppStatus nppiWarpPerspectiveQuad_8u_C1R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Single-channel 8-bit unsigned integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.72 `NppStatus nppiWarpPerspectiveQuad_8u_C3R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel 8-bit unsigned integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.73 `NppStatus nppiWarpPerspectiveQuad_8u_C4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 8-bit unsigned integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.74 `NppStatus nppiWarpPerspectiveQuad_8u_P3R (const Npp8u * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp8u * pDst[3], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel planar 8-bit unsigned integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.79.3.75 `NppStatus nppiWarpPerspectiveQuad_8u_P4R (const Npp8u * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp8u * pDst[4], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel planar 8-bit unsigned integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.80 Linear Transforms

Linear image transformations.

Modules

- [Fourier Transforms](#)

7.80.1 Detailed Description

Linear image transformations.

7.81 Fourier Transforms

Functions

- `NppStatus nppiMagnitude_32fc32f_C1R` (const `Npp32fc *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
32-bit floating point complex to 32-bit floating point magnitude.
- `NppStatus nppiMagnitudeSqr_32fc32f_C1R` (const `Npp32fc *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
32-bit floating point complex to 32-bit floating point squared magnitude.

7.81.1 Function Documentation

7.81.1.1 `NppStatus nppiMagnitude_32fc32f_C1R` (const `Npp32fc *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

32-bit floating point complex to 32-bit floating point magnitude.

Converts complex-number pixel image to single channel image computing the result pixels as the magnitude of the complex values.

Parameters:

- `pSrc` Source-Image Pointer.
- `nSrcStep` Source-Image Line Step.
- `pDst` Destination-Image Pointer.
- `nDstStep` Destination-Image Line Step.
- `oSizeROI` Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.81.1.2 `NppStatus nppiMagnitudeSqr_32fc32f_C1R` (const `Npp32fc *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

32-bit floating point complex to 32-bit floating point squared magnitude.

Converts complex-number pixel image to single channel image computing the result pixels as the squared magnitude of the complex values.

The squared magnitude is an intermediate result of magnitude computation and can thus be computed faster than actual magnitude. If magnitudes are required for sorting/comparing only, using this function instead of `nppiMagnitude_32fc32f_C1R` can be a worthwhile performance optimization.

Parameters:

- `pSrc` Source-Image Pointer.
- `nSrcStep` Source-Image Line Step.
- `pDst` Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.82 Morphological Operations

Morphological image operations.

Modules

- [Dilation](#)

Dilation computes the output pixel as the maximum pixel value of the pixels under the mask.

- [Erode](#)

Erosion computes the output pixel as the minimum pixel value of the pixels under the mask.

- [Dilate3x3](#)

Dilation using a 3x3 mask with the anchor at its center pixel.

- [Erode3x3](#)

Erosion using a 3x3 mask with the anchor at its center pixel.

7.82.1 Detailed Description

Morphological image operations.

Morphological operations are classified as [Neighborhood Operations](#). It is the user's responsibility to avoid [Sampling Beyond Image Boundaries](#).

7.83 Dilation

Dilation computes the output pixel as the maximum pixel value of the pixels under the mask.

Functions

- `NppStatus nppiDilate_8u_C1R` (const `Npp8u` *pSrc, `Npp32s` nSrcStep, `Npp8u` *pDst, `Npp32s` nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, `NppiSize` oMaskSize, `NppiPoint` oAnchor)
Single-channel 8-bit unsigned integer dilation.
- `NppStatus nppiDilate_8u_C3R` (const `Npp8u` *pSrc, `Npp32s` nSrcStep, `Npp8u` *pDst, `Npp32s` nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, `NppiSize` oMaskSize, `NppiPoint` oAnchor)
Three-channel 8-bit unsigned integer dilation.
- `NppStatus nppiDilate_8u_C4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, `NppiSize` oMaskSize, `NppiPoint` oAnchor)
Four-channel 8-bit unsigned integer dilation.
- `NppStatus nppiDilate_8u_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, `NppiSize` oMaskSize, `NppiPoint` oAnchor)
Four-channel 8-bit unsigned integer dilation, ignoring alpha-channel.
- `NppStatus nppiDilate_16u_C1R` (const `Npp16u` *pSrc, `Npp32s` nSrcStep, `Npp16u` *pDst, `Npp32s` nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, `NppiSize` oMaskSize, `NppiPoint` oAnchor)
Single-channel 16-bit unsigned integer dilation.
- `NppStatus nppiDilate_16u_C3R` (const `Npp16u` *pSrc, `Npp32s` nSrcStep, `Npp16u` *pDst, `Npp32s` nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, `NppiSize` oMaskSize, `NppiPoint` oAnchor)
Three-channel 16-bit unsigned integer dilation.
- `NppStatus nppiDilate_16u_C4R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, `NppiSize` oMaskSize, `NppiPoint` oAnchor)
Four-channel 16-bit unsigned integer dilation.
- `NppStatus nppiDilate_16u_AC4R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, `NppiSize` oMaskSize, `NppiPoint` oAnchor)
Four-channel 16-bit unsigned integer dilation, ignoring alpha-channel.
- `NppStatus nppiDilate_32f_C1R` (const `Npp32f` *pSrc, `Npp32s` nSrcStep, `Npp32f` *pDst, `Npp32s` nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, `NppiSize` oMaskSize, `NppiPoint` oAnchor)
Single-channel 32-bit floating-point dilation.
- `NppStatus nppiDilate_32f_C3R` (const `Npp32f` *pSrc, `Npp32s` nSrcStep, `Npp32f` *pDst, `Npp32s` nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, `NppiSize` oMaskSize, `NppiPoint` oAnchor)
Three-channel 32-bit floating-point dilation.
- `NppStatus nppiDilate_32f_C4R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, `NppiSize` oMaskSize, `NppiPoint` oAnchor)
Four-channel 32-bit floating-point dilation.

- `NppStatus nppiDilate_32f_AC4R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp8u *pMask`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)

Four-channel 32-bit floating-point dilation, ignoring alpha-channel.

7.83.1 Detailed Description

Dilation computes the output pixel as the maximum pixel value of the pixels under the mask.

Pixels whose corresponding mask values are zero do not participate in the maximum search.

7.83.2 Function Documentation

- 7.83.2.1 `NppStatus nppiDilate_16u_AC4R` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp8u *pMask`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)

Four-channel 16-bit unsigned integer dilation, ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Pointer to the start address of the mask array

oMaskSize Width and Height mask array.

oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- 7.83.2.2 `NppStatus nppiDilate_16u_C1R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, const `Npp8u *pMask`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)

Single-channel 16-bit unsigned integer dilation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Pointer to the start address of the mask array

oMaskSize Width and Height mask array.

oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.83.2.3 `NppStatus nppiDilate_16u_C3R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp8u * pMask, NppiSize oMaskSize, NppiPoint oAnchor)`

Three-channel 16-bit unsigned integer dilation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Pointer to the start address of the mask array

oMaskSize Width and Height mask array.

oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.83.2.4 `NppStatus nppiDilate_16u_C4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, NppiSize oMaskSize, NppiPoint oAnchor)`

Four-channel 16-bit unsigned integer dilation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Pointer to the start address of the mask array

oMaskSize Width and Height mask array.

oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.83.2.5 `NppStatus nppiDilate_32f_AC4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, NppiSize oMaskSize, NppiPoint oAnchor)`

Four-channel 32-bit floating-point dilation, ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Pointer to the start address of the mask array

oMaskSize Width and Height mask array.

oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.83.2.6 `NppStatus nppiDilate_32f_C1R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp8u * pMask, NppiSize oMaskSize, NppiPoint oAnchor)`

Single-channel 32-bit floating-point dilation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Pointer to the start address of the mask array

oMaskSize Width and Height mask array.

oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.83.2.7 `NppStatus nppiDilate_32f_C3R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp8u * pMask, NppiSize oMaskSize, NppiPoint oAnchor)`

Three-channel 32-bit floating-point dilation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
pMask Pointer to the start address of the mask array
oMaskSize Width and Height mask array.
oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.83.2.8 `NppStatus nppiDilate_32f_C4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, NppiSize oMaskSize, NppiPoint oAnchor)`

Four-channel 32-bit floating-point dilation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
pMask Pointer to the start address of the mask array
oMaskSize Width and Height mask array.
oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.83.2.9 `NppStatus nppiDilate_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, NppiSize oMaskSize, NppiPoint oAnchor)`

Four-channel 8-bit unsigned integer dilation, ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

oSizeROI [Region-of-Interest \(ROI\)](#).

pMask Pointer to the start address of the mask array

oMaskSize Width and Height mask array.

oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.83.2.10 `NppStatus nppiDilate_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp8u * pMask, NppiSize oMaskSize, NppiPoint oAnchor)`

Single-channel 8-bit unsigned integer dilation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pMask Pointer to the start address of the mask array

oMaskSize Width and Height mask array.

oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.83.2.11 `NppStatus nppiDilate_8u_C3R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp8u * pMask, NppiSize oMaskSize, NppiPoint oAnchor)`

Three-channel 8-bit unsigned integer dilation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pMask Pointer to the start address of the mask array

oMaskSize Width and Height mask array.

oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.83.2.12 `NppStatus nppiDilate_8u_C4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, NppiSize oMaskSize, NppiPoint oAnchor)`

Four-channel 8-bit unsigned integer dilation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Pointer to the start address of the mask array

oMaskSize Width and Height mask array.

oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.84 Erode

Erosion computes the output pixel as the minimum pixel value of the pixels under the mask.

Functions

- [NppStatus nppiErode_8u_C1R](#) (const [Npp8u](#) *pSrc, [Npp32s](#) nSrcStep, [Npp8u](#) *pDst, [Npp32s](#) nDstStep, [NppiSize](#) oSizeROI, const [Npp8u](#) *pMask, [NppiSize](#) oMaskSize, [NppiPoint](#) oAnchor)
Single-channel 8-bit unsigned integer erosion.
- [NppStatus nppiErode_8u_C3R](#) (const [Npp8u](#) *pSrc, [Npp32s](#) nSrcStep, [Npp8u](#) *pDst, [Npp32s](#) nDstStep, [NppiSize](#) oSizeROI, const [Npp8u](#) *pMask, [NppiSize](#) oMaskSize, [NppiPoint](#) oAnchor)
Three-channel 8-bit unsigned integer erosion.
- [NppStatus nppiErode_8u_C4R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [Npp8u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp8u](#) *pMask, [NppiSize](#) oMaskSize, [NppiPoint](#) oAnchor)
Four-channel 8-bit unsigned integer erosion.
- [NppStatus nppiErode_8u_AC4R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [Npp8u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp8u](#) *pMask, [NppiSize](#) oMaskSize, [NppiPoint](#) oAnchor)
Four-channel 8-bit unsigned integer erosion, ignoring alpha-channel.
- [NppStatus nppiErode_16u_C1R](#) (const [Npp16u](#) *pSrc, [Npp32s](#) nSrcStep, [Npp16u](#) *pDst, [Npp32s](#) nDstStep, [NppiSize](#) oSizeROI, const [Npp8u](#) *pMask, [NppiSize](#) oMaskSize, [NppiPoint](#) oAnchor)
Single-channel 16-bit unsigned integer erosion.
- [NppStatus nppiErode_16u_C3R](#) (const [Npp16u](#) *pSrc, [Npp32s](#) nSrcStep, [Npp16u](#) *pDst, [Npp32s](#) nDstStep, [NppiSize](#) oSizeROI, const [Npp8u](#) *pMask, [NppiSize](#) oMaskSize, [NppiPoint](#) oAnchor)
Three-channel 16-bit unsigned integer erosion.
- [NppStatus nppiErode_16u_C4R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [Npp16u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp8u](#) *pMask, [NppiSize](#) oMaskSize, [NppiPoint](#) oAnchor)
Four-channel 16-bit unsigned integer erosion.
- [NppStatus nppiErode_16u_AC4R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [Npp16u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp8u](#) *pMask, [NppiSize](#) oMaskSize, [NppiPoint](#) oAnchor)
Four-channel 16-bit unsigned integer erosion, ignoring alpha-channel.
- [NppStatus nppiErode_32f_C1R](#) (const [Npp32f](#) *pSrc, [Npp32s](#) nSrcStep, [Npp32f](#) *pDst, [Npp32s](#) nDstStep, [NppiSize](#) oSizeROI, const [Npp8u](#) *pMask, [NppiSize](#) oMaskSize, [NppiPoint](#) oAnchor)
Single-channel 32-bit floating-point erosion.
- [NppStatus nppiErode_32f_C3R](#) (const [Npp32f](#) *pSrc, [Npp32s](#) nSrcStep, [Npp32f](#) *pDst, [Npp32s](#) nDstStep, [NppiSize](#) oSizeROI, const [Npp8u](#) *pMask, [NppiSize](#) oMaskSize, [NppiPoint](#) oAnchor)
Three-channel 32-bit floating-point erosion.
- [NppStatus nppiErode_32f_C4R](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, const [Npp8u](#) *pMask, [NppiSize](#) oMaskSize, [NppiPoint](#) oAnchor)
Four-channel 32-bit floating-point erosion.

- `NppStatus nppiErode_32f_AC4R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp8u *pMask`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)

Four-channel 32-bit floating-point erosion, ignoring alpha-channel.

7.84.1 Detailed Description

Erosion computes the output pixel as the minimum pixel value of the pixels under the mask.

Pixels whose corresponding mask values are zero do not participate in the maximum search.

7.84.2 Function Documentation

- 7.84.2.1 `NppStatus nppiErode_16u_AC4R` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp8u *pMask`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)

Four-channel 16-bit unsigned integer erosion, ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Pointer to the start address of the mask array

oMaskSize Width and Height mask array.

oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- 7.84.2.2 `NppStatus nppiErode_16u_C1R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`, const `Npp8u *pMask`, `NppiSize oMaskSize`, `NppiPoint oAnchor`)

Single-channel 16-bit unsigned integer erosion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Pointer to the start address of the mask array

oMaskSize Width and Height mask array.

oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.84.2.3 `NppStatus nppiErode_16u_C3R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp8u * pMask, NppiSize oMaskSize, NppiPoint oAnchor)`

Three-channel 16-bit unsigned integer erosion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Pointer to the start address of the mask array

oMaskSize Width and Height mask array.

oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.84.2.4 `NppStatus nppiErode_16u_C4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, NppiSize oMaskSize, NppiPoint oAnchor)`

Four-channel 16-bit unsigned integer erosion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Pointer to the start address of the mask array

oMaskSize Width and Height mask array.

oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.84.2.5 `NppStatus nppiErode_32f_AC4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, NppiSize oMaskSize, NppiPoint oAnchor)`

Four-channel 32-bit floating-point erosion, ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Pointer to the start address of the mask array

oMaskSize Width and Height mask array.

oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.84.2.6 `NppStatus nppiErode_32f_C1R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp8u * pMask, NppiSize oMaskSize, NppiPoint oAnchor)`

Single-channel 32-bit floating-point erosion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Pointer to the start address of the mask array

oMaskSize Width and Height mask array.

oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.84.2.7 `NppStatus nppiErode_32f_C3R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp8u * pMask, NppiSize oMaskSize, NppiPoint oAnchor)`

Three-channel 32-bit floating-point erosion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
pMask Pointer to the start address of the mask array
oMaskSize Width and Height mask array.
oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.84.2.8 `NppStatus nppiErode_32f_C4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, NppiSize oMaskSize, NppiPoint oAnchor)`

Four-channel 32-bit floating-point erosion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
pMask Pointer to the start address of the mask array
oMaskSize Width and Height mask array.
oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.84.2.9 `NppStatus nppiErode_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, NppiSize oMaskSize, NppiPoint oAnchor)`

Four-channel 8-bit unsigned integer erosion, ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

oSizeROI [Region-of-Interest \(ROI\)](#).

pMask Pointer to the start address of the mask array

oMaskSize Width and Height mask array.

oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.84.2.10 `NppStatus nppiErode_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp8u * pMask, NppiSize oMaskSize, NppiPoint oAnchor)`

Single-channel 8-bit unsigned integer erosion.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pMask Pointer to the start address of the mask array

oMaskSize Width and Height mask array.

oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.84.2.11 `NppStatus nppiErode_8u_C3R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp8u * pMask, NppiSize oMaskSize, NppiPoint oAnchor)`

Three-channel 8-bit unsigned integer erosion.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pMask Pointer to the start address of the mask array

oMaskSize Width and Height mask array.

oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.84.2.12 `NppStatus nppiErode_8u_C4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, NppiSize oMaskSize, NppiPoint oAnchor)`

Four-channel 8-bit unsigned integer erosion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Pointer to the start address of the mask array

oMaskSize Width and Height mask array.

oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.85 Dilate3x3

Dilation using a 3x3 mask with the anchor at its center pixel.

Functions

- **NppStatus nppiDilate3x3_8u_C1R** (const **Npp8u** *pSrc, **Npp32s** nSrcStep, **Npp8u** *pDst, **Npp32s** nDstStep, **NppiSize** oSizeROI)
Single-channel 8-bit unsigned integer 3x3 dilation.
- **NppStatus nppiDilate3x3_8u_C3R** (const **Npp8u** *pSrc, **Npp32s** nSrcStep, **Npp8u** *pDst, **Npp32s** nDstStep, **NppiSize** oSizeROI)
Three-channel 8-bit unsigned integer 3x3 dilation.
- **NppStatus nppiDilate3x3_8u_C4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four-channel 8-bit unsigned integer 3x3 dilation.
- **NppStatus nppiDilate3x3_8u_AC4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four-channel 8-bit unsigned integer 3x3 dilation, ignoring alpha-channel.
- **NppStatus nppiDilate3x3_16u_C1R** (const **Npp16u** *pSrc, **Npp32s** nSrcStep, **Npp16u** *pDst, **Npp32s** nDstStep, **NppiSize** oSizeROI)
Single-channel 16-bit unsigned integer 3x3 dilation.
- **NppStatus nppiDilate3x3_16u_C3R** (const **Npp16u** *pSrc, **Npp32s** nSrcStep, **Npp16u** *pDst, **Npp32s** nDstStep, **NppiSize** oSizeROI)
Three-channel 16-bit unsigned integer 3x3 dilation.
- **NppStatus nppiDilate3x3_16u_C4R** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four-channel 16-bit unsigned integer 3x3 dilation.
- **NppStatus nppiDilate3x3_16u_AC4R** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four-channel 16-bit unsigned integer 3x3 dilation, ignoring alpha-channel.
- **NppStatus nppiDilate3x3_32f_C1R** (const **Npp32f** *pSrc, **Npp32s** nSrcStep, **Npp32f** *pDst, **Npp32s** nDstStep, **NppiSize** oSizeROI)
Single-channel 32-bit floating-point 3x3 dilation.
- **NppStatus nppiDilate3x3_32f_C3R** (const **Npp32f** *pSrc, **Npp32s** nSrcStep, **Npp32f** *pDst, **Npp32s** nDstStep, **NppiSize** oSizeROI)
Three-channel 32-bit floating-point 3x3 dilation.
- **NppStatus nppiDilate3x3_32f_C4R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four-channel 32-bit floating-point 3x3 dilation.

- `NppStatus nppiDilate3x3_32f_AC4R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four-channel 32-bit floating-point 3x3 dilation, ignoring alpha-channel.
- `NppStatus nppiDilate3x3_64f_C1R` (const `Npp64f *pSrc`, `Npp32s nSrcStep`, `Npp64f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Single-channel 64-bit floating-point 3x3 dilation.

7.85.1 Detailed Description

Dilation using a 3x3 mask with the anchor at its center pixel.

7.85.2 Function Documentation

7.85.2.1 `NppStatus nppiDilate3x3_16u_AC4R` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Four-channel 16-bit unsigned integer 3x3 dilation, ignoring alpha-channel.

Parameters:

- `pSrc` Source-Image Pointer.
- `nSrcStep` Source-Image Line Step.
- `pDst` Destination-Image Pointer.
- `nDstStep` Destination-Image Line Step.
- `oSizeROI` Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.85.2.2 `NppStatus nppiDilate3x3_16u_C1R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Single-channel 16-bit unsigned integer 3x3 dilation.

Parameters:

- `pSrc` Source-Image Pointer.
- `nSrcStep` Source-Image Line Step.
- `pDst` Destination-Image Pointer.
- `nDstStep` Destination-Image Line Step.
- `oSizeROI` Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.85.2.3 NppStatus nppiDilate3x3_16u_C3R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Three-channel 16-bit unsigned integer 3x3 dilation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.85.2.4 NppStatus nppiDilate3x3_16u_C4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four-channel 16-bit unsigned integer 3x3 dilation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.85.2.5 NppStatus nppiDilate3x3_32f_AC4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four-channel 32-bit floating-point 3x3 dilation, ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.85.2.6 NppStatus nppiDilate3x3_32f_C1R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single-channel 32-bit floating-point 3x3 dilation.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.85.2.7 NppStatus nppiDilate3x3_32f_C3R (const Npp32f * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Three-channel 32-bit floating-point 3x3 dilation.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.85.2.8 NppStatus nppiDilate3x3_32f_C4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four-channel 32-bit floating-point 3x3 dilation.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.85.2.9 NppStatus nppiDilate3x3_64f_C1R (const Npp64f * pSrc, Npp32s nSrcStep, Npp64f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single-channel 64-bit floating-point 3x3 dilation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.85.2.10 NppStatus nppiDilate3x3_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Four-channel 8-bit unsigned integer 3x3 dilation, ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.85.2.11 NppStatus nppiDilate3x3_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single-channel 8-bit unsigned integer 3x3 dilation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.85.2.12 `NppStatus nppiDilate3x3_8u_C3R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)`

Three-channel 8-bit unsigned integer 3x3 dilation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.85.2.13 `NppStatus nppiDilate3x3_8u_C4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four-channel 8-bit unsigned integer 3x3 dilation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.86 Erode3x3

Erosion using a 3x3 mask with the anchor at its center pixel.

Functions

- **NppStatus nppiErode3x3_8u_C1R** (const **Npp8u** *pSrc, **Npp32s** nSrcStep, **Npp8u** *pDst, **Npp32s** nDstStep, **NppiSize** oSizeROI)
Single-channel 8-bit unsigned integer 3x3 erosion.
- **NppStatus nppiErode3x3_8u_C3R** (const **Npp8u** *pSrc, **Npp32s** nSrcStep, **Npp8u** *pDst, **Npp32s** nDstStep, **NppiSize** oSizeROI)
Three-channel 8-bit unsigned integer 3x3 erosion.
- **NppStatus nppiErode3x3_8u_C4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four-channel 8-bit unsigned integer 3x3 erosion.
- **NppStatus nppiErode3x3_8u_AC4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four-channel 8-bit unsigned integer 3x3 erosion, ignoring alpha-channel.
- **NppStatus nppiErode3x3_16u_C1R** (const **Npp16u** *pSrc, **Npp32s** nSrcStep, **Npp16u** *pDst, **Npp32s** nDstStep, **NppiSize** oSizeROI)
Single-channel 16-bit unsigned integer 3x3 erosion.
- **NppStatus nppiErode3x3_16u_C3R** (const **Npp16u** *pSrc, **Npp32s** nSrcStep, **Npp16u** *pDst, **Npp32s** nDstStep, **NppiSize** oSizeROI)
Three-channel 16-bit unsigned integer 3x3 erosion.
- **NppStatus nppiErode3x3_16u_C4R** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four-channel 16-bit unsigned integer 3x3 erosion.
- **NppStatus nppiErode3x3_16u_AC4R** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four-channel 16-bit unsigned integer 3x3 erosion, ignoring alpha-channel.
- **NppStatus nppiErode3x3_32f_C1R** (const **Npp32f** *pSrc, **Npp32s** nSrcStep, **Npp32f** *pDst, **Npp32s** nDstStep, **NppiSize** oSizeROI)
Single-channel 32-bit floating-point 3x3 erosion.
- **NppStatus nppiErode3x3_32f_C3R** (const **Npp32f** *pSrc, **Npp32s** nSrcStep, **Npp32f** *pDst, **Npp32s** nDstStep, **NppiSize** oSizeROI)
Three-channel 32-bit floating-point 3x3 erosion.
- **NppStatus nppiErode3x3_32f_C4R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four-channel 32-bit floating-point 3x3 erosion.

- `NppStatus nppiErode3x3_32f_AC4R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four-channel 32-bit floating-point 3x3 erosion, ignoring alpha-channel.
- `NppStatus nppiErode3x3_64f_C1R` (const `Npp64f *pSrc`, `Npp32s nSrcStep`, `Npp64f *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)
Single-channel 64-bit floating-point 3x3 erosion.

7.86.1 Detailed Description

Erosion using a 3x3 mask with the anchor at its center pixel.

7.86.2 Function Documentation

7.86.2.1 `NppStatus nppiErode3x3_16u_AC4R` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Four-channel 16-bit unsigned integer 3x3 erosion, ignoring alpha-channel.

Parameters:

- `pSrc` Source-Image Pointer.
- `nSrcStep` Source-Image Line Step.
- `pDst` Destination-Image Pointer.
- `nDstStep` Destination-Image Line Step.
- `oSizeROI` Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.86.2.2 `NppStatus nppiErode3x3_16u_C1R` (const `Npp16u *pSrc`, `Npp32s nSrcStep`, `Npp16u *pDst`, `Npp32s nDstStep`, `NppiSize oSizeROI`)

Single-channel 16-bit unsigned integer 3x3 erosion.

Parameters:

- `pSrc` Source-Image Pointer.
- `nSrcStep` Source-Image Line Step.
- `pDst` Destination-Image Pointer.
- `nDstStep` Destination-Image Line Step.
- `oSizeROI` Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.86.2.3 NppStatus nppiErode3x3_16u_C3R (const Npp16u * pSrc, Npp32s nSrcStep, Npp16u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Three-channel 16-bit unsigned integer 3x3 erosion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.86.2.4 NppStatus nppiErode3x3_16u_C4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four-channel 16-bit unsigned integer 3x3 erosion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.86.2.5 NppStatus nppiErode3x3_32f_AC4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four-channel 32-bit floating-point 3x3 erosion, ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.86.2.6 NppStatus nppiErode3x3_32f_C1R (const Npp32f * *pSrc*, Npp32s *nSrcStep*, Npp32f * *pDst*, Npp32s *nDstStep*, NppiSize *oSizeROI*)

Single-channel 32-bit floating-point 3x3 erosion.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.86.2.7 NppStatus nppiErode3x3_32f_C3R (const Npp32f * *pSrc*, Npp32s *nSrcStep*, Npp32f * *pDst*, Npp32s *nDstStep*, NppiSize *oSizeROI*)

Three-channel 32-bit floating-point 3x3 erosion.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.86.2.8 NppStatus nppiErode3x3_32f_C4R (const Npp32f * *pSrc*, int *nSrcStep*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

Four-channel 32-bit floating-point 3x3 erosion.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.86.2.9 NppStatus nppiErode3x3_64f_C1R (const Npp64f * pSrc, Npp32s nSrcStep, Npp64f * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single-channel 64-bit floating-point 3x3 erosion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.86.2.10 NppStatus nppiErode3x3_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Four-channel 8-bit unsigned integer 3x3 erosion, ignoring alpha-channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.86.2.11 NppStatus nppiErode3x3_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)

Single-channel 8-bit unsigned integer 3x3 erosion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.86.2.12 `NppStatus nppiErode3x3_8u_C3R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI)`

Three-channel 8-bit unsigned integer 3x3 erosion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.86.2.13 `NppStatus nppiErode3x3_8u_C4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four-channel 8-bit unsigned integer 3x3 erosion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.87 Statistical Operations

Primitives for computing the statistical properties of an image.

Modules

- [Sum](#)

Primitives for computing the sum of all the pixel values in an image.

- [Min](#)

Primitives for computing the minimal pixel value of an image.

- [MinIndx](#)

Primitives for computing the minimal value and its indices (X and Y coordinates) of an image.

- [Max](#)

Primitives for computing the maximal pixel value of an image.

- [MaxIndx](#)

Primitives for computing the maximal value and its indices (X and Y coordinates) of an image.

- [MinMax](#)

Primitives for computing both the minimal and the maximal values of an image.

- [MinMaxIndx](#)

Primitives for computing the minimal and the maximal values with their indices (X and Y coordinates) of an image.

- [Mean](#)

Primitives for computing the arithmetic mean of all the pixel values in an image.

- [Mean_StdDev](#)

Primitives for computing both the arithmetic mean and the standard deviation of an image.

- [Image Norms](#)

Primitives for computing the norms of an image, the norms of difference, and the relative errors of two images.

- [DotProd](#)

Primitives for computing the dot product of two images.

- [CountInRange.](#)

Primitives for computing the amount of pixels that fall into the specified intensity range.

- [MaxEvery](#)

Primitives for computing the maximal value of the pixel pair from two images.

- [MinEvery](#)

Primitives for computing the minimal value of the pixel pair from two images.

- [Integral](#)
Primitives for computing the integral image of a given image.
- [SqrIntegral](#)
Primitives for computing both the integral and the squared integral images of a given image.
- [RectStdDev](#)
Primitives for computing the standard deviation of the integral images.
- [HistogramEven](#)
Primitives for computing the histogram of an image with evenly distributed bins.
- [HistogramRange](#)
Primitives for computing the histogram of an image within specified ranges.
- [Image Proximity](#)
Primitives for computing the proximity measure between a source image and a template image.
- [Image Quality Index](#)
Primitives for computing the image quality index of two images.

7.87.1 Detailed Description

Primitives for computing the statistical properties of an image.

Some statistical primitives also require scratch buffer during the computation. For details, please refer to [Scratch Buffer and Host Pointer](#).

7.88 Sum

Primitives for computing the sum of all the pixel values in an image.

Sum

Given an image $pSrc$ with width W and height H , the sum will be computed as

$$Sum = \sum_{j=0}^{H-1} \sum_{i=0}^{W-1} pSrc(j, i)$$

All the results are stored in a 64-bit double precision format, except for two primitives `nppiSum_8u64s_C1R` and `nppiSum_8u64s_C4R`.

The sum functions require additional scratch buffer for computations.

- `NppStatus nppiSum_8u_C1R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` *pSum)
One-channel 8-bit unsigned image sum.
- `NppStatus nppiSum_8u64s_C1R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64s` *pSum)
One-channel 8-bit unsigned image sum.
- `NppStatus nppiSum_16u_C1R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` *pSum)
One-channel 16-bit unsigned image sum.
- `NppStatus nppiSum_16s_C1R` (const `Npp16s` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` *pSum)
One-channel 16-bit signed image sum.
- `NppStatus nppiSum_32f_C1R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` *pSum)
One-channel 32-bit floating point image sum.
- `NppStatus nppiSum_8u_C3R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` aSum[3])
Three-channel 8-bit unsigned image sum.
- `NppStatus nppiSum_16u_C3R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` aSum[3])
Three-channel 16-bit unsigned image sum.
- `NppStatus nppiSum_16s_C3R` (const `Npp16s` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` aSum[3])
Three-channel 16-bit signed image sum.
- `NppStatus nppiSum_32f_C3R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` aSum[3])
Three-channel 32-bit floating point image sum.

- `NppStatus nppiSum_8u_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` aSum[3])
Four-channel 8-bit unsigned image sum ignoring alpha channel.
- `NppStatus nppiSum_16u_AC4R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` aSum[3])
Four-channel 16-bit unsigned image sum ignoring alpha channel.
- `NppStatus nppiSum_16s_AC4R` (const `Npp16s` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` aSum[3])
Four-channel 16-bit signed image sum ignoring alpha channel.
- `NppStatus nppiSum_32f_AC4R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` aSum[3])
Four-channel 32-bit floating point image sum ignoring alpha channel.
- `NppStatus nppiSum_8u_C4R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` aSum[4])
Four-channel 8-bit unsigned image sum.
- `NppStatus nppiSum_8u64s_C4R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64s` aSum[4])
Four-channel 8-bit unsigned image sum.
- `NppStatus nppiSum_16u_C4R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` aSum[4])
Four-channel 16-bit unsigned image sum.
- `NppStatus nppiSum_16s_C4R` (const `Npp16s` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` aSum[4])
Four-channel 16-bit signed image sum.
- `NppStatus nppiSum_32f_C4R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` aSum[4])
Four-channel 32-bit floating point image sum.

SumGetBufferHostSize

Companion primitives for computing the device buffer size (in bytes) required by the sum primitives.

- `NppStatus nppiSumGetBufferHostSize_8u_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiSum_8u_C1R`.
- `NppStatus nppiSumGetBufferHostSize_8u64s_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiSum_8u64s_C1R`.
- `NppStatus nppiSumGetBufferHostSize_16u_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiSum_16u_C1R`.

- `NppStatus nppiSumGetBufferHostSize_16s_C1R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiSum_16s_C1R`.
- `NppStatus nppiSumGetBufferHostSize_32f_C1R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiSum_32f_C1R`.
- `NppStatus nppiSumGetBufferHostSize_8u_C3R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiSum_8u_C3R`.
- `NppStatus nppiSumGetBufferHostSize_16u_C3R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiSum_16u_C3R`.
- `NppStatus nppiSumGetBufferHostSize_16s_C3R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiSum_16s_C3R`.
- `NppStatus nppiSumGetBufferHostSize_32f_C3R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiSum_32f_C3R`.
- `NppStatus nppiSumGetBufferHostSize_8u_AC4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiSum_8u_AC4R`.
- `NppStatus nppiSumGetBufferHostSize_16u_AC4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiSum_16u_AC4R`.
- `NppStatus nppiSumGetBufferHostSize_16s_AC4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiSum_16s_AC4R`.
- `NppStatus nppiSumGetBufferHostSize_32f_AC4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiSum_32f_AC4R`.
- `NppStatus nppiSumGetBufferHostSize_8u64s_C4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiSum_8u64s_C4R`.
- `NppStatus nppiSumGetBufferHostSize_8u_C4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiSum_8u_C4R`.
- `NppStatus nppiSumGetBufferHostSize_16u_C4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiSum_16u_C4R`.
- `NppStatus nppiSumGetBufferHostSize_16s_C4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiSum_16s_C4R`.
- `NppStatus nppiSumGetBufferHostSize_32f_C4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiSum_32f_C4R`.

7.88.1 Detailed Description

Primitives for computing the sum of all the pixel values in an image.

7.88.2 Function Documentation

7.88.2.1 `NppStatus nppiSum_16s_AC4R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f aSum[3])`

Four-channel 16-bit signed image sum ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiSumGetBufferHostSize_16s_AC4R](#) to determine the minimum number of bytes required.

aSum Array that contains computed sum for each channel (alpha channel is not computed).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.88.2.2 `NppStatus nppiSum_16s_C1R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f * pSum)`

One-channel 16-bit signed image sum.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiSumGetBufferHostSize_16s_C1R](#) to determine the minimum number of bytes required.

pSum Pointer to the computed sum.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.88.2.3 `NppStatus nppiSum_16s_C3R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f aSum[3])`

Three-channel 16-bit signed image sum.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiSumGetBufferHostSize_16s_C3R](#) to determine the minimum number of bytes required.

aSum Array that contains computed sum for each channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.88.2.4 NppStatus nppiSum_16s_C4R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f aSum[4])

Four-channel 16-bit signed image sum.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiSumGetBufferHostSize_16s_C4R](#) to determine the minium number of bytes required.

aSum Array that contains computed sum for each channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.88.2.5 NppStatus nppiSum_16u_AC4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f aSum[3])

Four-channel 16-bit unsigned image sum ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#). Use [nppiSumGetBufferHostSize_16u_AC4R](#) to determine the minium number of bytes required.

aSum Array that contains computed sum for each channel (alpha channel is not computed).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.88.2.6 NppStatus nppiSum_16u_C1R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f * pSum)

One-channel 16-bit unsigned image sum.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiSumGetBufferHostSize_16u_C1R](#) to determine the minimum number of bytes required.

pSum Pointer to the computed sum.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.88.2.7 NppStatus nppiSum_16u_C3R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f aSum[3])

Three-channel 16-bit unsigned image sum.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiSumGetBufferHostSize_16u_C3R](#) to determine the minimum number of bytes required.

aSum Array that contains computed sum for each channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.88.2.8 NppStatus nppiSum_16u_C4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f aSum[4])

Four-channel 16-bit unsigned image sum.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use
[nppiSumGetBufferHostSize_16u_C4R](#) to determine the minimum number of bytes required.

aSum Array that contains computed sum for each channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.88.2.9 NppStatus nppiSum_32f_AC4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f aSum[3])

Four-channel 32-bit floating point image sum ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiSumGetBufferHostSize_32f_AC4R](#) to determine the minium number of bytes required.

aSum Array that contains computed sum for each channel (alpha channel is not computed).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.88.2.10 NppStatus nppiSum_32f_C1R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f * pSum)

One-channel 32-bit floating point image sum.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiSumGetBufferHostSize_32f_C1R](#) to determine the minium number of bytes required.

pSum Pointer to the computed sum.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.88.2.11 NppStatus nppiSum_32f_C3R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f aSum[3])

Three-channel 32-bit floating point image sum.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#). Use [nppiSumGetBufferHostSize_32f_C3R](#) to determine the minium number of bytes required.

aSum Array that contains computed sum for each channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.88.2.12 `NppStatus nppiSum_32f_C4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f aSum[4])`

Four-channel 32-bit floating point image sum.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use `nppiSumGetBufferHostSize_32f_C4R` to determine the minium number of bytes required.

aSum Array that contains computed sum for each channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.88.2.13 `NppStatus nppiSum_8u64s_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64s * pSum)`

One-channel 8-bit unsigned image sum.

The result is 64-bit long long integer.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#). Use `nppiSumGetBufferHostSize_8u64s_C1R` to determine the minium number of bytes required.

pSum Pointer to the computed sum.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.88.2.14 `NppStatus nppiSum_8u64s_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64s aSum[4])`

Four-channel 8-bit unsigned image sum.

The result is 64-bit long long integer.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiSumGetBufferHostSize_8u64s_C4R](#) to determine the minimum number of bytes required.

aSum Array that contains computed sum for each channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.88.2.15 `NppStatus nppiSum_8u_AC4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f aSum[3])`

Four-channel 8-bit unsigned image sum ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#). Use [nppiSumGetBufferHostSize_8u_AC4R](#) to determine the minimum number of bytes required.

aSum Array that contains computed sum for each channel (alpha channel is not computed).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.88.2.16 `NppStatus nppiSum_8u_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f * pSum)`

One-channel 8-bit unsigned image sum.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#). Use [nppiSumGetBufferHostSize_8u_C1R](#) to determine the minimum number of bytes required.

pSum Pointer to the computed sum.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.88.2.17 `NppStatus nppiSum_8u_C3R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f aSum[3])`

Three-channel 8-bit unsigned image sum.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).

Use `nppiSumGetBufferHostSize_8u_C3R` to determine the minimum number of bytes required.

aSum Array that contains computed sum for each channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.88.2.18 `NppStatus nppiSum_8u_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f aSum[4])`

Four-channel 8-bit unsigned image sum.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use

`nppiSumGetBufferHostSize_8u_C4R` to determine the minimum number of bytes required.

aSum Array that contains computed sum for each channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.88.2.19 `NppStatus nppiSumGetBufferHostSize_16s_AC4R (NppiSize oSizeROI, int * hpBufferSize)`

Buffer size for `nppiSum_16s_AC4R`.

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.88.2.20 NppStatus nppiSumGetBufferHostSize_16s_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiSum_16s_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.88.2.21 NppStatus nppiSumGetBufferHostSize_16s_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiSum_16s_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.88.2.22 NppStatus nppiSumGetBufferHostSize_16s_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiSum_16s_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.88.2.23 NppStatus nppiSumGetBufferHostSize_16u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiSum_16u_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.88.2.24 NppStatus nppiSumGetBufferHostSize_16u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiSum_16u_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.88.2.25 NppStatus nppiSumGetBufferHostSize_16u_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiSum_16u_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.88.2.26 NppStatus nppiSumGetBufferHostSize_16u_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiSum_16u_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.88.2.27 NppStatus nppiSumGetBufferHostSize_32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiSum_32f_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.88.2.28 NppStatus nppiSumGetBufferHostSize_32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiSum_32f_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.88.2.29 NppStatus nppiSumGetBufferHostSize_32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiSum_32f_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.88.2.30 NppStatus nppiSumGetBufferHostSize_32f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiSum_32f_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.88.2.31 NppStatus nppiSumGetBufferHostSize_8u64s_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiSum_8u64s_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.88.2.32 NppStatus nppiSumGetBufferHostSize_8u64s_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiSum_8u64s_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.88.2.33 NppStatus nppiSumGetBufferHostSize_8u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiSum_8u_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.88.2.34 NppStatus nppiSumGetBufferHostSize_8u_C1R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size for [nppiSum_8u_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.88.2.35 NppStatus nppiSumGetBufferHostSize_8u_C3R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size for [nppiSum_8u_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.88.2.36 NppStatus nppiSumGetBufferHostSize_8u_C4R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size for [nppiSum_8u_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.89 Min

Primitives for computing the minimal pixel value of an image.

Min

The scratch buffer is required by the min functions.

- `NppStatus nppiMin_8u_C1R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp8u *pMin`)
One-channel 8-bit unsigned image min.
- `NppStatus nppiMin_16u_C1R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp16u *pMin`)
One-channel 16-bit unsigned image min.
- `NppStatus nppiMin_16s_C1R` (const `Npp16s *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp16s *pMin`)
One-channel 16-bit signed image min.
- `NppStatus nppiMin_32f_C1R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp32f *pMin`)
One-channel 32-bit floating point image min.
- `NppStatus nppiMin_8u_C3R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp8u aMin[3]`)
Three-channel 8-bit unsigned image min.
- `NppStatus nppiMin_16u_C3R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp16u aMin[3]`)
Three-channel 16-bit unsigned image min.
- `NppStatus nppiMin_16s_C3R` (const `Npp16s *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp16s aMin[3]`)
Three-channel 16-bit signed image min.
- `NppStatus nppiMin_32f_C3R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp32f aMin[3]`)
Three-channel 32-bit floating point image min.
- `NppStatus nppiMin_8u_C4R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp8u aMin[4]`)
Four-channel 8-bit unsigned image min.
- `NppStatus nppiMin_16u_C4R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp16u aMin[4]`)
Four-channel 16-bit unsigned image min.
- `NppStatus nppiMin_16s_C4R` (const `Npp16s *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp16s aMin[4]`)

Four-channel 16-bit signed image min.

- `NppStatus nppiMin_32f_C4R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp32f aMin[4]`)

Four-channel 32-bit floating point image min.

- `NppStatus nppiMin_8u_AC4R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp8u aMin[3]`)

Four-channel 8-bit unsigned image min ignoring alpha channel.

- `NppStatus nppiMin_16u_AC4R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp16u aMin[3]`)

Four-channel 16-bit unsigned image min ignoring alpha channel.

- `NppStatus nppiMin_16s_AC4R` (const `Npp16s *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp16s aMin[3]`)

Four-channel 16-bit signed image min ignoring alpha channel.

- `NppStatus nppiMin_32f_AC4R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp32f aMin[3]`)

Four-channel 32-bit floating point image min ignoring alpha channel.

MinGetBufferHostSize

Companion primitives for computing the device buffer size (in bytes) required by the min primitives.

- `NppStatus nppiMinGetBufferHostSize_8u_C1R` (`NppiSize oSizeROI`, int `*hpBufferSize`)
Buffer size for `nppiMin_8u_C1R`.
- `NppStatus nppiMinGetBufferHostSize_16u_C1R` (`NppiSize oSizeROI`, int `*hpBufferSize`)
Buffer size for `nppiMin_16u_C1R`.
- `NppStatus nppiMinGetBufferHostSize_16s_C1R` (`NppiSize oSizeROI`, int `*hpBufferSize`)
Buffer size for `nppiMin_16s_C1R`.
- `NppStatus nppiMinGetBufferHostSize_32f_C1R` (`NppiSize oSizeROI`, int `*hpBufferSize`)
Buffer size for `nppiMin_32f_C1R`.
- `NppStatus nppiMinGetBufferHostSize_8u_C3R` (`NppiSize oSizeROI`, int `*hpBufferSize`)
Buffer size for `nppiMin_8u_C3R`.
- `NppStatus nppiMinGetBufferHostSize_16u_C3R` (`NppiSize oSizeROI`, int `*hpBufferSize`)
Buffer size for `nppiMin_16u_C3R`.
- `NppStatus nppiMinGetBufferHostSize_16s_C3R` (`NppiSize oSizeROI`, int `*hpBufferSize`)
Buffer size for `nppiMin_16s_C3R`.
- `NppStatus nppiMinGetBufferHostSize_32f_C3R` (`NppiSize oSizeROI`, int `*hpBufferSize`)
Buffer size for `nppiMin_32f_C3R`.

- `NppStatus nppiMinGetBufferHostSize_8u_C4R` (`NppiSize oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiMin_8u_C4R`.
- `NppStatus nppiMinGetBufferHostSize_16u_C4R` (`NppiSize oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiMin_16u_C4R`.
- `NppStatus nppiMinGetBufferHostSize_16s_C4R` (`NppiSize oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiMin_16s_C4R`.
- `NppStatus nppiMinGetBufferHostSize_32f_C4R` (`NppiSize oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiMin_32f_C4R`.
- `NppStatus nppiMinGetBufferHostSize_8u_AC4R` (`NppiSize oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiMin_8u_AC4R`.
- `NppStatus nppiMinGetBufferHostSize_16u_AC4R` (`NppiSize oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiMin_16u_AC4R`.
- `NppStatus nppiMinGetBufferHostSize_16s_AC4R` (`NppiSize oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiMin_16s_AC4R`.
- `NppStatus nppiMinGetBufferHostSize_32f_AC4R` (`NppiSize oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiMin_32f_AC4R`.

7.89.1 Detailed Description

Primitives for computing the minimal pixel value of an image.

7.89.2 Function Documentation

7.89.2.1 `NppStatus nppiMin_16s_AC4R` (`const Npp16s *pSrc`, `int nSrcStep`, `NppiSize oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp16s aMin[3]`)

Four-channel 16-bit signed image min ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use `nppiMinGetBufferHostSize_16s_AC4R` to determine the minimum number of bytes required.

aMin Array that contains the computed minimum results for each channel (alpha channel is not processed).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.89.2.2 NppStatus nppiMin_16s_C1R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16s * pMin)

One-channel 16-bit signed image min.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinGetBufferHostSize_16s_C1R](#) to determine the minimum number of bytes required.

pMin Pointer to the computed minimum result.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.89.2.3 NppStatus nppiMin_16s_C3R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16s aMin[3])

Three-channel 16-bit signed image min.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinGetBufferHostSize_16s_C3R](#) to determine the minimum number of bytes required.

aMin Array that contains the computed minimum results for each channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.89.2.4 NppStatus nppiMin_16s_C4R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16s aMin[4])

Four-channel 16-bit signed image min.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinGetBufferHostSize_16s_C4R](#) to determine the minimum number of bytes required.

aMin Array that contains the computed minimum results for each channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.89.2.5 NppStatus nppiMin_16u_AC4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16u aMin[3])

Four-channel 16-bit unsigned image min ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinGetBufferHostSize_16u_AC4R](#) to determine the minimum number of bytes required.

aMin Array that contains the computed minimum results for each channel (alpha channel is not processed).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.89.2.6 NppStatus nppiMin_16u_C1R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16u * pMin)

One-channel 16-bit unsigned image min.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinGetBufferHostSize_16u_C1R](#) to determine the minimum number of bytes required.

pMin Pointer to the computed minimum result.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.89.2.7 NppStatus nppiMin_16u_C3R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16u aMin[3])

Three-channel 16-bit unsigned image min.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinGetBufferHostSize_16u_C3R](#) to determine the minimum number of bytes required.

aMin Array that contains the computed minimum results for each channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.89.2.8 NppStatus nppiMin_16u_C4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16u aMin[4])

Four-channel 16-bit unsigned image min.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinGetBufferHostSize_16u_C4R](#) to determine the minimum number of bytes required.

aMin Array that contains the computed minimum results for each channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.89.2.9 NppStatus nppiMin_32f_AC4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp32f aMin[3])

Four-channel 32-bit floating point image min ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinGetBufferHostSize_32f_AC4R](#) to determine the minimum number of bytes required.

aMin Array that contains the computed minimum results for each channel (alpha channel is not processed).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.89.2.10 NppStatus nppiMin_32f_C1R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp32f * pMin)

One-channel 32-bit floating point image min.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinGetBufferHostSize_32f_C1R](#) to determine the minimum number of bytes required.

pMin Pointer to the computed minimum result.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.89.2.11 `NppStatus nppiMin_32f_C3R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp32f aMin[3])`

Three-channel 32-bit floating point image min.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinGetBufferHostSize_32f_C3R](#) to determine the minimum number of bytes required.

aMin Array that contains the computed minimum results for each channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.89.2.12 `NppStatus nppiMin_32f_C4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp32f aMin[4])`

Four-channel 32-bit floating point image min.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinGetBufferHostSize_32f_C4R](#) to determine the minimum number of bytes required.

aMin Array that contains the computed minimum results for each channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.89.2.13 `NppStatus nppiMin_8u_AC4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp8u aMin[3])`

Four-channel 8-bit unsigned image min ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use `nppiMinGetBufferHostSize_8u_AC4R` to determine the minimum number of bytes required.

aMin Array that contains the computed minimum results for each channel (alpha channel is not processed).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.89.2.14 `NppStatus nppiMin_8u_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp8u * pMin)`

One-channel 8-bit unsigned image min.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use `nppiMinGetBufferHostSize_8u_C1R` to determine the minimum number of bytes required.

pMin Pointer to the computed minimum result.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.89.2.15 `NppStatus nppiMin_8u_C3R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp8u aMin[3])`

Three-channel 8-bit unsigned image min.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use `nppiMinGetBufferHostSize_8u_C3R` to determine the minimum number of bytes required.

aMin Array that contains the computed minimum results for each channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.89.2.16 NppStatus nppiMin_8u_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp8u aMin[4])

Four-channel 8-bit unsigned image min.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinGetBufferHostSize_8u_C4R](#) to determine the minimum number of bytes required.

aMin Array that contains the computed minimum results for each channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.89.2.17 NppStatus nppiMinGetBufferHostSize_16s_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMin_16s_AC4R](#).

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.89.2.18 NppStatus nppiMinGetBufferHostSize_16s_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMin_16s_C1R](#).

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.89.2.19 NppStatus nppiMinGetBufferHostSize_16s_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMin_16s_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.89.2.20 NppStatus nppiMinGetBufferHostSize_16s_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMin_16s_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.89.2.21 NppStatus nppiMinGetBufferHostSize_16u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMin_16u_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.89.2.22 NppStatus nppiMinGetBufferHostSize_16u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMin_16u_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.89.2.23 NppStatus nppiMinGetBufferHostSize_16u_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMin_16u_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.89.2.24 NppStatus nppiMinGetBufferHostSize_16u_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMin_16u_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.89.2.25 NppStatus nppiMinGetBufferHostSize_32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMin_32f_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.89.2.26 NppStatus nppiMinGetBufferHostSize_32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMin_32f_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.89.2.27 NppStatus nppiMinGetBufferHostSize_32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMin_32f_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.89.2.28 NppStatus nppiMinGetBufferHostSize_32f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMin_32f_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.89.2.29 NppStatus nppiMinGetBufferHostSize_8u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMin_8u_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.89.2.30 NppStatus nppiMinGetBufferHostSize_8u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMin_8u_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.89.2.31 NppStatus nppiMinGetBufferHostSize_8u_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMin_8u_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.89.2.32 NppStatus nppiMinGetBufferHostSize_8u_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMin_8u_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.90 MinIndx

Primitives for computing the minimal value and its indices (X and Y coordinates) of an image.

MinIndx

If there are several minima in the selected ROI, the function returns one on the top leftmost position.

The scratch buffer is required by the functions.

- **NppStatus nppiMinIndx_8u_C1R** (const **Npp8u** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp8u** *pDeviceBuffer, **Npp8u** *pMin, int *pIndexX, int *pIndexY)
One-channel 8-bit unsigned image MinIndx.
- **NppStatus nppiMinIndx_16u_C1R** (const **Npp16u** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp8u** *pDeviceBuffer, **Npp16u** *pMin, int *pIndexX, int *pIndexY)
One-channel 16-bit unsigned image MinIndx.
- **NppStatus nppiMinIndx_16s_C1R** (const **Npp16s** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp8u** *pDeviceBuffer, **Npp16s** *pMin, int *pIndexX, int *pIndexY)
One-channel 16-bit signed image MinIndx.
- **NppStatus nppiMinIndx_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp8u** *pDeviceBuffer, **Npp32f** *pMin, int *pIndexX, int *pIndexY)
One-channel 32-bit floating point image MinIndx.
- **NppStatus nppiMinIndx_8u_C3R** (const **Npp8u** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp8u** *pDeviceBuffer, **Npp8u** aMin[3], int aIndexX[3], int aIndexY[3])
Three-channel 8-bit unsigned image MinIndx.
- **NppStatus nppiMinIndx_16u_C3R** (const **Npp16u** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp8u** *pDeviceBuffer, **Npp16u** aMin[3], int aIndexX[3], int aIndexY[3])
Three-channel 16-bit unsigned image MinIndx.
- **NppStatus nppiMinIndx_16s_C3R** (const **Npp16s** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp8u** *pDeviceBuffer, **Npp16s** aMin[3], int aIndexX[3], int aIndexY[3])
Three-channel 16-bit signed image MinIndx.
- **NppStatus nppiMinIndx_32f_C3R** (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp8u** *pDeviceBuffer, **Npp32f** aMin[3], int aIndexX[3], int aIndexY[3])
Three-channel 32-bit floating point image MinIndx.
- **NppStatus nppiMinIndx_8u_C4R** (const **Npp8u** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp8u** *pDeviceBuffer, **Npp8u** aMin[4], int aIndexX[4], int aIndexY[4])
Four-channel 8-bit unsigned image MinIndx.
- **NppStatus nppiMinIndx_16u_C4R** (const **Npp16u** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp8u** *pDeviceBuffer, **Npp16u** aMin[4], int aIndexX[4], int aIndexY[4])
Four-channel 16-bit unsigned image MinIndx.

- `NppStatus nppiMinIndx_16s_C4R` (const `Npp16s` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp16s` aMin[4], int aIndexX[4], int aIndexY[4])
Four-channel 16-bit signed image MinIndx.
- `NppStatus nppiMinIndx_32f_C4R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp32f` aMin[4], int aIndexX[4], int aIndexY[4])
Four-channel 32-bit floating point image MinIndx.
- `NppStatus nppiMinIndx_8u_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp8u` aMin[3], int aIndexX[3], int aIndexY[3])
Four-channel 8-bit unsigned image MinIndx ignoring alpha channel.
- `NppStatus nppiMinIndx_16u_AC4R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp16u` aMin[3], int aIndexX[3], int aIndexY[3])
Four-channel 16-bit unsigned image MinIndx ignoring alpha channel.
- `NppStatus nppiMinIndx_16s_AC4R` (const `Npp16s` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp16s` aMin[3], int aIndexX[3], int aIndexY[3])
Four-channel 16-bit signed image MinIndx ignoring alpha channel.
- `NppStatus nppiMinIndx_32f_AC4R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp32f` aMin[3], int aIndexX[3], int aIndexY[3])
Four-channel 32-bit floating point image MinIndx ignoring alpha channel.

MinIndxGetBufferHostSize

Companion primitives for computing the device buffer size (in bytes) required by the MinIndx primitives.

- `NppStatus nppiMinIndxGetBufferHostSize_8u_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMinIndx_8u_C1R.
- `NppStatus nppiMinIndxGetBufferHostSize_16u_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMinIndx_16u_C1R.
- `NppStatus nppiMinIndxGetBufferHostSize_16s_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMinIndx_16s_C1R.
- `NppStatus nppiMinIndxGetBufferHostSize_32f_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMinIndx_32f_C1R.
- `NppStatus nppiMinIndxGetBufferHostSize_8u_C3R` (`NppiSize` oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMinIndx_8u_C3R.
- `NppStatus nppiMinIndxGetBufferHostSize_16u_C3R` (`NppiSize` oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMinIndx_16u_C3R.
- `NppStatus nppiMinIndxGetBufferHostSize_16s_C3R` (`NppiSize` oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMinIndx_16s_C3R.

- [NppStatus nppiMinIndxGetBufferHostSize_32f_C3R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMinIndx_32f_C3R.
- [NppStatus nppiMinIndxGetBufferHostSize_8u_C4R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMinIndx_8u_C4R.
- [NppStatus nppiMinIndxGetBufferHostSize_16u_C4R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMinIndx_16u_C4R.
- [NppStatus nppiMinIndxGetBufferHostSize_16s_C4R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMinIndx_16s_C4R.
- [NppStatus nppiMinIndxGetBufferHostSize_32f_C4R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMinIndx_32f_C4R.
- [NppStatus nppiMinIndxGetBufferHostSize_8u_AC4R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMinIndx_8u_AC4R.
- [NppStatus nppiMinIndxGetBufferHostSize_16u_AC4R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMinIndx_16u_AC4R.
- [NppStatus nppiMinIndxGetBufferHostSize_16s_AC4R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMinIndx_16s_AC4R.
- [NppStatus nppiMinIndxGetBufferHostSize_32f_AC4R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMinIndx_32f_AC4R.

7.90.1 Detailed Description

Primitives for computing the minimal value and its indices (X and Y coordinates) of an image.

7.90.2 Function Documentation

7.90.2.1 [NppStatus nppiMinIndx_16s_AC4R](#) (const [Npp16s](#) * pSrc, int nSrcStep, [NppiSize](#) oSizeROI, [Npp8u](#) * pDeviceBuffer, [Npp16s](#) aMin[3], int aIndexX[3], int aIndexY[3])

Four-channel 16-bit signed image MinIndx ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinIndxGetBufferHostSize_16s_AC4R](#) to determine the minimum number of bytes required.

aMin Array that contains the min values.

aIndexX Array that contains the X coordinates of the image min values.

aIndexY Array that contains the Y coordinates of the image min values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.90.2.2 NppStatus nppiMinIndx_16s_C1R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16s * pMin, int * pIndexX, int * pIndexY)

One-channel 16-bit signed image MinIndx.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinIndxGetBufferHostSize_16s_C1R](#) to determine the minium number of bytes required.

pMin Pointer to the computed min result.

pIndexX Pointer to the X coordinate of the image min value.

pIndexY Pointer to the Y coordinate of the image min value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.90.2.3 NppStatus nppiMinIndx_16s_C3R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16s aMin[3], int aIndexX[3], int aIndexY[3])

Three-channel 16-bit signed image MinIndx.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinIndxGetBufferHostSize_16s_C3R](#) to determine the minium number of bytes required.

aMin Array that contains the min values.

aIndexX Array that contains the X coordinates of the image min values.

aIndexY Array that contains the Y coordinates of the image min values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.90.2.4 NppStatus nppiMinIndx_16s_C4R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16s aMin[4], int aIndexX[4], int aIndexY[4])

Four-channel 16-bit signed image MinIndx.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinIndxGetBufferHostSize_16s_C4R](#) to determine the minium number of bytes required.

aMin Array that contains the min values.

aIndexX Array that contains the X coordinates of the image min values.

aIndexY Array that contains the Y coordinates of the image min values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.90.2.5 NppStatus nppiMinIndx_16u_AC4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16u aMin[3], int aIndexX[3], int aIndexY[3])

Four-channel 16-bit unsigned image MinIndx ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinIndxGetBufferHostSize_16u_AC4R](#) to determine the minium number of bytes required.

aMin Array that contains the min values.

aIndexX Array that contains the X coordinates of the image min values.

aIndexY Array that contains the Y coordinates of the image min values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.90.2.6 NppStatus nppiMinIndx_16u_C1R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16u * pMin, int * pIndexX, int * pIndexY)

One-channel 16-bit unsigned image MinIndx.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI [Region-of-Interest \(ROI\)](#).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinIdxGetBufferHostSize_16u_C1R](#) to determine the minimum number of bytes required.

pMin Pointer to the computed min result.

pIndexX Pointer to the X coordinate of the image min value.

pIndexY Pointer to the Y coordinate of the image min value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.90.2.7 NppStatus nppiMinIdx_16u_C3R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16u aMin[3], int aIndexX[3], int aIndexY[3])

Three-channel 16-bit unsigned image MinIdx.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinIdxGetBufferHostSize_16u_C3R](#) to determine the minimum number of bytes required.

aMin Array that contains the min values.

aIndexX Array that contains the X coordinates of the image min values.

aIndexY Array that contains the Y coordinates of the image min values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.90.2.8 NppStatus nppiMinIdx_16u_C4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16u aMin[4], int aIndexX[4], int aIndexY[4])

Four-channel 16-bit unsigned image MinIdx.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinIdxGetBufferHostSize_16u_C4R](#) to determine the minimum number of bytes required.

aMin Array that contains the min values.

aIndexX Array that contains the X coordinates of the image min values.

aIndexY Array that contains the Y coordinates of the image min values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.90.2.9 NppStatus nppiMinIndx_32f_AC4R (const Npp32f * *pSrc*, int *nSrcStep*, NppiSize *oSizeROI*, Npp8u * *pDeviceBuffer*, Npp32f *aMin*[3], int *aIndexX*[3], int *aIndexY*[3])

Four-channel 32-bit floating point image MinIndx ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinIndxGetBufferHostSize_32f_AC4R](#) to determine the minium number of bytes required.

aMin Array that contains the min values.

aIndexX Array that contains the X coordinates of the image min values.

aIndexY Array that contains the Y coordinates of the image min values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.90.2.10 NppStatus nppiMinIndx_32f_C1R (const Npp32f * *pSrc*, int *nSrcStep*, NppiSize *oSizeROI*, Npp8u * *pDeviceBuffer*, Npp32f * *pMin*, int * *pIndexX*, int * *pIndexY*)

One-channel 32-bit floating point image MinIndx.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinIndxGetBufferHostSize_32f_C1R](#) to determine the minium number of bytes required.

pMin Pointer to the computed min result.

pIndexX Pointer to the X coordinate of the image min value.

pIndexY Pointer to the Y coordinate of the image min value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.90.2.11 NppStatus nppiMinIndx_32f_C3R (const Npp32f * *pSrc*, int *nSrcStep*, NppiSize *oSizeROI*, Npp8u * *pDeviceBuffer*, Npp32f *aMin*[3], int *aIndexX*[3], int *aIndexY*[3])

Three-channel 32-bit floating point image MinIndx.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI [Region-of-Interest \(ROI\)](#).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinIdxGetBufferHostSize_32f_C3R](#) to determine the minium number of bytes required.

aMin Array that contains the min values.

aIndexX Array that contains the X coordinates of the image min values.

aIndexY Array that contains the Y coordinates of the image min values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.90.2.12 NppStatus nppiMinIdx_32f_C4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp32f aMin[4], int aIndexX[4], int aIndexY[4])

Four-channel 32-bit floating point image MinIdx.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinIdxGetBufferHostSize_32f_C4R](#) to determine the minium number of bytes required.

aMin Array that contains the min values.

aIndexX Array that contains the X coordinates of the image min values.

aIndexY Array that contains the Y coordinates of the image min values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.90.2.13 NppStatus nppiMinIdx_8u_AC4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp8u aMin[3], int aIndexX[3], int aIndexY[3])

Four-channel 8-bit unsigned image MinIdx ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinIdxGetBufferHostSize_8u_AC4R](#) to determine the minium number of bytes required.

aMin Array that contains the min values.

aIndexX Array that contains the X coordinates of the image min values.

aIndexY Array that contains the Y coordinates of the image min values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.90.2.14 `NppStatus nppiMinIndx_8u_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp8u * pMin, int * pIndexX, int * pIndexY)`

One-channel 8-bit unsigned image MinIndx.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinIndxGetBufferHostSize_8u_C1R](#) to determine the minium number of bytes required.

pMin Pointer to the computed min result.

pIndexX Pointer to the X coordinate of the image min value.

pIndexY Ppointer to the Y coordinate of the image min value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.90.2.15 `NppStatus nppiMinIndx_8u_C3R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp8u aMin[3], int aIndexX[3], int aIndexY[3])`

Three-channel 8-bit unsigned image MinIndx.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinIndxGetBufferHostSize_8u_C3R](#) to determine the minium number of bytes required.

aMin Array that contains the min values.

aIndexX Array that contains the X coordinates of the image min values.

aIndexY Array that contains the Y coordinates of the image min values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.90.2.16 `NppStatus nppiMinIndx_8u_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp8u aMin[4], int aIndexX[4], int aIndexY[4])`

Four-channel 8-bit unsigned image MinIndx.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI [Region-of-Interest \(ROI\)](#).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMinIdxGetBufferHostSize_8u_C4R](#) to determine the minium number of bytes required.

aMin Array that contains the min values.

aIndexX Array that contains the X coordinates of the image min values.

aIndexY Array that contains the Y coordinates of the image min values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.90.2.17 NppStatus nppiMinIdxGetBufferHostSize_16s_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the dvice scratch buffer size (in bytes) for nppiMinIdx_16u_AC4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if hpBufferSize is 0 (NULL), [ROI Related Error Codes](#).

7.90.2.18 NppStatus nppiMinIdxGetBufferHostSize_16s_C1R (NppiSize oSizeROI, int * hpBufferSize)

Computes the dvice scratch buffer size (in bytes) for nppiMinIdx_16s_C1R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if hpBufferSize is 0 (NULL), [ROI Related Error Codes](#).

7.90.2.19 NppStatus nppiMinIdxGetBufferHostSize_16s_C3R (NppiSize oSizeROI, int * hpBufferSize)

Computes the dvice scratch buffer size (in bytes) for nppiMinIdx_16s_C3R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.90.2.20 NppStatus nppiMinIndxGetBufferHostSize_16s_C4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiMinIndx_16s_C4R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.90.2.21 NppStatus nppiMinIndxGetBufferHostSize_16u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiMinIndx_8u_AC4R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.90.2.22 NppStatus nppiMinIndxGetBufferHostSize_16u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiMinIndx_16u_C1R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.90.2.23 NppStatus nppiMinIdxGetBufferHostSize_16u_C3R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Computes the device scratch buffer size (in bytes) for nppiMinIdx_16u_C3R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.90.2.24 NppStatus nppiMinIdxGetBufferHostSize_16u_C4R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Computes the device scratch buffer size (in bytes) for nppiMinIdx_16u_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.90.2.25 NppStatus nppiMinIdxGetBufferHostSize_32f_AC4R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Computes the device scratch buffer size (in bytes) for nppiMinIdx_32f_AC4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.90.2.26 NppStatus nppiMinIdxGetBufferHostSize_32f_C1R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Computes the device scratch buffer size (in bytes) for nppiMinIdx_32f_C1R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.90.2.27 NppStatus nppiMinIndxGetBufferHostSize_32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiMinIndx_32f_C3R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.90.2.28 NppStatus nppiMinIndxGetBufferHostSize_32f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiMinIndx_32f_C4R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.90.2.29 NppStatus nppiMinIndxGetBufferHostSize_8u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiMinIndx_8u_AC4R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

**7.90.2.30 NppStatus nppiMinIdxGetBufferHostSize_8u_C1R (NppiSize *oSizeROI*, int *
hpBufferSize)**

Computes the device scratch buffer size (in bytes) for nppiMinIdx_8u_C1R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

**7.90.2.31 NppStatus nppiMinIdxGetBufferHostSize_8u_C3R (NppiSize *oSizeROI*, int *
hpBufferSize)**

Computes the device scratch buffer size (in bytes) for nppiMinIdx_8u_C3R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

**7.90.2.32 NppStatus nppiMinIdxGetBufferHostSize_8u_C4R (NppiSize *oSizeROI*, int *
hpBufferSize)**

Computes the device scratch buffer size (in bytes) for nppiMinIdx_8u_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.91 Max

Primitives for computing the maximal pixel value of an image.

Max

The scratch buffer is required by the functions.

- `NppStatus nppiMax_8u_C1R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp8u *pMax`)
One-channel 8-bit unsigned image Max.
- `NppStatus nppiMax_16u_C1R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp16u *pMax`)
One-channel 16-bit unsigned image Max.
- `NppStatus nppiMax_16s_C1R` (const `Npp16s *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp16s *pMax`)
One-channel 16-bit signed image Max.
- `NppStatus nppiMax_32f_C1R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp32f *pMax`)
One-channel 32-bit floating point image Max.
- `NppStatus nppiMax_8u_C3R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp8u aMax[3]`)
Three-channel 8-bit unsigned image Max.
- `NppStatus nppiMax_16u_C3R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp16u aMax[3]`)
Three-channel 16-bit unsigned image Max.
- `NppStatus nppiMax_16s_C3R` (const `Npp16s *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp16s aMax[3]`)
Three-channel 16-bit signed image Max.
- `NppStatus nppiMax_32f_C3R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp32f aMax[3]`)
Three-channel 32-bit floating point image Max.
- `NppStatus nppiMax_8u_C4R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp8u aMax[4]`)
Four-channel 8-bit unsigned image Max.
- `NppStatus nppiMax_16u_C4R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp16u aMax[4]`)
Four-channel 16-bit unsigned image Max.
- `NppStatus nppiMax_16s_C4R` (const `Npp16s *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp16s aMax[4]`)

Four-channel 16-bit signed image Max.

- `NppStatus nppiMax_32f_C4R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp32f` aMax[4])

Four-channel 32-bit floating point image Max.

- `NppStatus nppiMax_8u_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp8u` aMax[3])

Four-channel 8-bit unsigned image Max ignoring alpha channel.

- `NppStatus nppiMax_16u_AC4R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp16u` aMax[3])

Four-channel 16-bit unsigned image Max ignoring alpha channel.

- `NppStatus nppiMax_16s_AC4R` (const `Npp16s` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp16s` aMax[3])

Four-channel 16-bit signed image Max ignoring alpha channel.

- `NppStatus nppiMax_32f_AC4R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp32f` aMax[3])

Four-channel 32-bit floating point image Max ignoring alpha channel.

MaxGetBufferHostSize

Companion primitives for computing the device buffer size (in bytes) required by the Max primitives.

- `NppStatus nppiMaxGetBufferHostSize_8u_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiMax_8u_C1R`.
- `NppStatus nppiMaxGetBufferHostSize_16u_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiMax_16u_C1R`.
- `NppStatus nppiMaxGetBufferHostSize_16s_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiMax_16s_C1R`.
- `NppStatus nppiMaxGetBufferHostSize_32f_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiMax_32f_C1R`.
- `NppStatus nppiMaxGetBufferHostSize_8u_C3R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiMax_8u_C3R`.
- `NppStatus nppiMaxGetBufferHostSize_16u_C3R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiMax_16u_C3R`.
- `NppStatus nppiMaxGetBufferHostSize_16s_C3R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiMax_16s_C3R`.
- `NppStatus nppiMaxGetBufferHostSize_32f_C3R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiMax_32f_C3R`.

- `NppStatus nppiMaxGetBufferHostSize_8u_C4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiMax_8u_C4R`.
- `NppStatus nppiMaxGetBufferHostSize_16u_C4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiMax_16u_C4R`.
- `NppStatus nppiMaxGetBufferHostSize_16s_C4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiMax_16s_C4R`.
- `NppStatus nppiMaxGetBufferHostSize_32f_C4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiMax_32f_C4R`.
- `NppStatus nppiMaxGetBufferHostSize_8u_AC4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiMax_8u_AC4R`.
- `NppStatus nppiMaxGetBufferHostSize_16u_AC4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiMax_16u_AC4R`.
- `NppStatus nppiMaxGetBufferHostSize_16s_AC4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiMax_16s_AC4R`.
- `NppStatus nppiMaxGetBufferHostSize_32f_AC4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiMax_32f_AC4R`.

7.91.1 Detailed Description

Primitives for computing the maximal pixel value of an image.

7.91.2 Function Documentation

7.91.2.1 `NppStatus nppiMax_16s_AC4R` (`const Npp16s *pSrc`, `int nSrcStep`, `NppiSize oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp16s aMax[3]`)

Four-channel 16-bit signed image Max ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use `nppiMaxGetBufferHostSize_16s_AC4R` to determine the maximum number of bytes required.

aMax Array that contains the computed maximum results for each channel (alpha channel is not processed).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.91.2.2 NppStatus nppiMax_16s_C1R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16s * pMax)

One-channel 16-bit signed image Max.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxGetBufferHostSize_16s_C1R](#) to determine the maximum number of bytes required.

pMax Pointer to the computed maximum result.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.91.2.3 NppStatus nppiMax_16s_C3R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16s aMax[3])

Three-channel 16-bit signed image Max.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxGetBufferHostSize_16s_C3R](#) to determine the maximum number of bytes required.

aMax Array that contains the computed maximum results for each channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.91.2.4 NppStatus nppiMax_16s_C4R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16s aMax[4])

Four-channel 16-bit signed image Max.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxGetBufferHostSize_16s_C4R](#) to determine the maximum number of bytes required.

aMax Array that contains the computed maximum results for each channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.91.2.5 NppStatus nppiMax_16u_AC4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16u aMax[3])

Four-channel 16-bit unsigned image Max ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxGetBufferHostSize_16u_AC4R](#) to determine the maximum number of bytes required.

aMax Array that contains the computed maximum results for each channel (alpha channel is not processed).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.91.2.6 NppStatus nppiMax_16u_C1R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16u * pMax)

One-channel 16-bit unsigned image Max.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxGetBufferHostSize_16u_C1R](#) to determine the maximum number of bytes required.

pMax Pointer to the computed maximum result.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.91.2.7 NppStatus nppiMax_16u_C3R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16u aMax[3])

Three-channel 16-bit unsigned image Max.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxGetBufferHostSize_16u_C3R](#) to determine the maximum number of bytes required.

aMax Array that contains the computed maximum results for each channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.91.2.8 NppStatus nppiMax_16u_C4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16u aMax[4])

Four-channel 16-bit unsigned image Max.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxGetBufferHostSize_16u_C4R](#) to determine the maximum number of bytes required.

aMax Array that contains the computed maximum results for each channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.91.2.9 NppStatus nppiMax_32f_AC4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp32f aMax[3])

Four-channel 32-bit floating point image Max ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxGetBufferHostSize_32f_AC4R](#) to determine the maximum number of bytes required.

aMax Array that contains the computed maximum results for each channel (alpha channel is not processed).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.91.2.10 NppStatus nppiMax_32f_C1R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp32f * pMax)

One-channel 32-bit floating point image Max.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxGetBufferHostSize_32f_C1R](#) to determine the maximum number of bytes required.

pMax Pointer to the computed maximum result.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.91.2.11 `NppStatus nppiMax_32f_C3R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp32f aMax[3])`

Three-channel 32-bit floating point image Max.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxGetBufferHostSize_32f_C3R](#) to determine the maximum number of bytes required.

aMax Array that contains the computed maximum results for each channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.91.2.12 `NppStatus nppiMax_32f_C4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp32f aMax[4])`

Four-channel 32-bit floating point image Max.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxGetBufferHostSize_32f_C4R](#) to determine the maximum number of bytes required.

aMax Array that contains the computed maximum results for each channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.91.2.13 `NppStatus nppiMax_8u_AC4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp8u aMax[3])`

Four-channel 8-bit unsigned image Max ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use `nppiMaxGetBufferHostSize_8u_AC4R` to determine the maximum number of bytes required.

aMax Array that contains the computed maximum results for each channel (alpha channel is not processed).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.91.2.14 `NppStatus nppiMax_8u_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp8u * pMax)`

One-channel 8-bit unsigned image Max.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use `nppiMaxGetBufferHostSize_8u_C1R` to determine the maximum number of bytes required.

pMax Pointer to the computed maximum result.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.91.2.15 `NppStatus nppiMax_8u_C3R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp8u aMax[3])`

Three-channel 8-bit unsigned image Max.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use `nppiMaxGetBufferHostSize_8u_C3R` to determine the maximum number of bytes required.

aMax Array that contains the computed maximum results for each channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.91.2.16 NppStatus nppiMax_8u_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp8u aMax[4])

Four-channel 8-bit unsigned image Max.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxGetBufferHostSize_8u_C4R](#) to determine the maximum number of bytes required.

aMax Array that contains the computed maximum results for each channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.91.2.17 NppStatus nppiMaxGetBufferHostSize_16s_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMax_16s_AC4R](#).

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.91.2.18 NppStatus nppiMaxGetBufferHostSize_16s_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMax_16s_C1R](#).

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.91.2.19 NppStatus nppiMaxGetBufferHostSize_16s_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMax_16s_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.91.2.20 NppStatus nppiMaxGetBufferHostSize_16s_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMax_16s_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.91.2.21 NppStatus nppiMaxGetBufferHostSize_16u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMax_16u_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.91.2.22 NppStatus nppiMaxGetBufferHostSize_16u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMax_16u_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.91.2.23 NppStatus nppiMaxGetBufferHostSize_16u_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMax_16u_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.91.2.24 NppStatus nppiMaxGetBufferHostSize_16u_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMax_16u_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.91.2.25 NppStatus nppiMaxGetBufferHostSize_32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMax_32f_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.91.2.26 NppStatus nppiMaxGetBufferHostSize_32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMax_32f_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.91.2.27 NppStatus nppiMaxGetBufferHostSize_32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMax_32f_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.91.2.28 NppStatus nppiMaxGetBufferHostSize_32f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMax_32f_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.91.2.29 NppStatus nppiMaxGetBufferHostSize_8u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMax_8u_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.91.2.30 NppStatus nppiMaxGetBufferHostSize_8u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMax_8u_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.91.2.31 NppStatus nppiMaxGetBufferHostSize_8u_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMax_8u_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.91.2.32 NppStatus nppiMaxGetBufferHostSize_8u_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMax_8u_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.92 MaxIndx

Primitives for computing the maximal value and its indices (X and Y coordinates) of an image.

MaxIndx

If there are several maxima in the selected region of interest, the function returns one on the top leftmost position.

The scratch buffer is required by the functions.

- `NppStatus nppiMaxIndx_8u_C1R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp8u` *pMax, int *pIndexX, int *pIndexY)
One-channel 8-bit unsigned image MaxIndx.
- `NppStatus nppiMaxIndx_16u_C1R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp16u` *pMax, int *pIndexX, int *pIndexY)
One-channel 16-bit unsigned image MaxIndx.
- `NppStatus nppiMaxIndx_16s_C1R` (const `Npp16s` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp16s` *pMax, int *pIndexX, int *pIndexY)
One-channel 16-bit signed image MaxIndx.
- `NppStatus nppiMaxIndx_32f_C1R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp32f` *pMax, int *pIndexX, int *pIndexY)
One-channel 32-bit floating point image MaxIndx.
- `NppStatus nppiMaxIndx_8u_C3R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp8u` aMax[3], int aIndexX[3], int aIndexY[3])
Three-channel 8-bit unsigned image MaxIndx.
- `NppStatus nppiMaxIndx_16u_C3R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp16u` aMax[3], int aIndexX[3], int aIndexY[3])
Three-channel 16-bit unsigned image MaxIndx.
- `NppStatus nppiMaxIndx_16s_C3R` (const `Npp16s` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp16s` aMax[3], int aIndexX[3], int aIndexY[3])
Three-channel 16-bit signed image MaxIndx.
- `NppStatus nppiMaxIndx_32f_C3R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp32f` aMax[3], int aIndexX[3], int aIndexY[3])
Three-channel 32-bit floating point image MaxIndx.
- `NppStatus nppiMaxIndx_8u_C4R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp8u` aMax[4], int aIndexX[4], int aIndexY[4])
Four-channel 8-bit unsigned image MaxIndx.
- `NppStatus nppiMaxIndx_16u_C4R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp16u` aMax[4], int aIndexX[4], int aIndexY[4])
Four-channel 16-bit unsigned image MaxIndx.

- **NppStatus nppiMaxIndx_16s_C4R** (const **Npp16s** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp8u** *pDeviceBuffer, **Npp16s** aMax[4], int aIndexX[4], int aIndexY[4])
Four-channel 16-bit signed image MaxIndx.
- **NppStatus nppiMaxIndx_32f_C4R** (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp8u** *pDeviceBuffer, **Npp32f** aMax[4], int aIndexX[4], int aIndexY[4])
Four-channel 32-bit floating point image MaxIndx.
- **NppStatus nppiMaxIndx_8u_AC4R** (const **Npp8u** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp8u** *pDeviceBuffer, **Npp8u** aMax[3], int aIndexX[3], int aIndexY[3])
Four-channel 8-bit unsigned image MaxIndx ignoring alpha channel.
- **NppStatus nppiMaxIndx_16u_AC4R** (const **Npp16u** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp8u** *pDeviceBuffer, **Npp16u** aMax[3], int aIndexX[3], int aIndexY[3])
Four-channel 16-bit unsigned image MaxIndx ignoring alpha channel.
- **NppStatus nppiMaxIndx_16s_AC4R** (const **Npp16s** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp8u** *pDeviceBuffer, **Npp16s** aMax[3], int aIndexX[3], int aIndexY[3])
Four-channel 16-bit signed image MaxIndx ignoring alpha channel.
- **NppStatus nppiMaxIndx_32f_AC4R** (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp8u** *pDeviceBuffer, **Npp32f** aMax[3], int aIndexX[3], int aIndexY[3])
Four-channel 32-bit floating point image MaxIndx ignoring alpha channel.

MaxIndxGetBufferHostSize

Companion primitives for computing the device buffer size (in bytes) required by the MaxIndx primitives.

- **NppStatus nppiMaxIndxGetBufferHostSize_8u_C1R** (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMaxIndx_8u_C1R.
- **NppStatus nppiMaxIndxGetBufferHostSize_16u_C1R** (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMaxIndx_16u_C1R.
- **NppStatus nppiMaxIndxGetBufferHostSize_16s_C1R** (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMaxIndx_16s_C1R.
- **NppStatus nppiMaxIndxGetBufferHostSize_32f_C1R** (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMaxIndx_32f_C1R.
- **NppStatus nppiMaxIndxGetBufferHostSize_8u_C3R** (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMaxIndx_8u_C3R.
- **NppStatus nppiMaxIndxGetBufferHostSize_16u_C3R** (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMaxIndx_16u_C3R.
- **NppStatus nppiMaxIndxGetBufferHostSize_16s_C3R** (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMaxIndx_16s_C3R.

- [NppStatus nppiMaxIdxGetBufferHostSize_32f_C3R](#) (NppiSize oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMaxIdx_32f_C3R.
- [NppStatus nppiMaxIdxGetBufferHostSize_8u_C4R](#) (NppiSize oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMaxIdx_8u_C4R.
- [NppStatus nppiMaxIdxGetBufferHostSize_16u_C4R](#) (NppiSize oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMaxIdx_16u_C4R.
- [NppStatus nppiMaxIdxGetBufferHostSize_16s_C4R](#) (NppiSize oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMaxIdx_16s_C4R.
- [NppStatus nppiMaxIdxGetBufferHostSize_32f_C4R](#) (NppiSize oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMaxIdx_32f_C4R.
- [NppStatus nppiMaxIdxGetBufferHostSize_8u_AC4R](#) (NppiSize oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMaxIdx_8u_AC4R.
- [NppStatus nppiMaxIdxGetBufferHostSize_16u_AC4R](#) (NppiSize oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMaxIdx_16u_AC4R.
- [NppStatus nppiMaxIdxGetBufferHostSize_16s_AC4R](#) (NppiSize oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMaxIdx_16s_AC4R.
- [NppStatus nppiMaxIdxGetBufferHostSize_32f_AC4R](#) (NppiSize oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiMaxIdx_32f_AC4R.

7.92.1 Detailed Description

Primitives for computing the maximal value and its indices (X and Y coordinates) of an image.

7.92.2 Function Documentation

7.92.2.1 NppStatus nppiMaxIdx_16s_AC4R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16s aMax[3], int aIndexX[3], int aIndexY[3])

Four-channel 16-bit signed image MaxIdx ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#)
Use [nppiMaxIdxGetBufferHostSize_16s_AC4R](#) to determine the maximum number of bytes required.

aMax Array that contains the max values.

aIndexX Array that contains the X coordinates of the image max values.

aIndexY Array that contains the Y coordinates of the image max values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.92.2.2 NppStatus nppiMaxIndx_16s_C1R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16s * pMax, int * pIndexX, int * pIndexY)

One-channel 16-bit signed image MaxIndx.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxIndxGetBufferHostSize_16s_C1R](#) to determine the maximum number of bytes required.

pMax Pointer to the computed max result.

pIndexX Pointer to the X coordinate of the image max value.

pIndexY Pointer to the Y coordinate of the image max value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.92.2.3 NppStatus nppiMaxIndx_16s_C3R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16s aMax[3], int aIndexX[3], int aIndexY[3])

Three-channel 16-bit signed image MaxIndx.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxIndxGetBufferHostSize_16s_C3R](#) to determine the maximum number of bytes required.

aMax Array that contains the max values.

aIndexX Array that contains the X coordinates of the image max values.

aIndexY Array that contains the Y coordinates of the image max values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.92.2.4 NppStatus nppiMaxIndx_16s_C4R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16s aMax[4], int aIndexX[4], int aIndexY[4])

Four-channel 16-bit signed image MaxIndx.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxIndxGetBufferHostSize_16s_C4R](#) to determine the maximum number of bytes required.

aMax Array that contains the max values.

aIndexX Array that contains the X coordinates of the image max values.

aIndexY Array that contains the Y coordinates of the image max values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.92.2.5 NppStatus nppiMaxIndx_16u_AC4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16u aMax[3], int aIndexX[3], int aIndexY[3])

Four-channel 16-bit unsigned image MaxIndx ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxIndxGetBufferHostSize_16u_AC4R](#) to determine the maximum number of bytes required.

aMax Array that contains the max values.

aIndexX Array that contains the X coordinates of the image max values.

aIndexY Array that contains the Y coordinates of the image max values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.92.2.6 NppStatus nppiMaxIndx_16u_C1R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16u * pMax, int * pIndexX, int * pIndexY)

One-channel 16-bit unsigned image MaxIndx.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxIdxGetBufferHostSize_16u_C1R](#) to determine the maximum number of bytes required.

pMax Pointer to the computed max result.

pIndexX Pointer to the X coordinate of the image max value.

pIndexY Pointer to the Y coordinate of the image max value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.92.2.7 `NppStatus nppiMaxIdx_16u_C3R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16u aMax[3], int aIndexX[3], int aIndexY[3])`

Three-channel 16-bit unsigned image MaxIdx.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxIdxGetBufferHostSize_16u_C3R](#) to determine the maximum number of bytes required.

aMax Array that contains the max values.

aIndexX Array that contains the X coordinates of the image max values.

aIndexY Array that contains the Y coordinates of the image max values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.92.2.8 `NppStatus nppiMaxIdx_16u_C4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp16u aMax[4], int aIndexX[4], int aIndexY[4])`

Four-channel 16-bit unsigned image MaxIdx.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxIdxGetBufferHostSize_16u_C4R](#) to determine the maximum number of bytes required.

aMax Array that contains the max values.

aIndexX Array that contains the X coordinates of the image max values.

aIndexY Array that contains the Y coordinates of the image max values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.92.2.9 NppStatus nppiMaxIndx_32f_AC4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp32f aMax[3], int aIndexX[3], int aIndexY[3])

Four-channel 32-bit floating point image MaxIndx ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxIndxGetBufferHostSize_32f_AC4R](#) to determine the maximum number of bytes required.

aMax Array that contains the max values.

aIndexX Array that contains the X coordinates of the image max values.

aIndexY Array that contains the Y coordinates of the image max values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.92.2.10 NppStatus nppiMaxIndx_32f_C1R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp32f * pMax, int * pIndexX, int * pIndexY)

One-channel 32-bit floating point image MaxIndx.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxIndxGetBufferHostSize_32f_C1R](#) to determine the maximum number of bytes required.

pMax Pointer to the computed max result.

pIndexX Pointer to the X coordinate of the image max value.

pIndexY Pointer to the Y coordinate of the image max value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.92.2.11 NppStatus nppiMaxIndx_32f_C3R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp32f aMax[3], int aIndexX[3], int aIndexY[3])

Three-channel 32-bit floating point image MaxIndx.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI [Region-of-Interest \(ROI\)](#).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxIndxGetBufferHostSize_32f_C3R](#) to determine the maximum number of bytes required.

aMax Array that contains the max values.

aIndexX Array that contains the X coordinates of the image max values.

aIndexY Array that contains the Y coordinates of the image max values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.92.2.12 NppStatus nppiMaxIndx_32f_C4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp32f aMax[4], int aIndexX[4], int aIndexY[4])

Four-channel 32-bit floating point image MaxIndx.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxIndxGetBufferHostSize_32f_C4R](#) to determine the maximum number of bytes required.

aMax Array that contains the max values.

aIndexX Array that contains the X coordinates of the image max values.

aIndexY Array that contains the Y coordinates of the image max values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.92.2.13 NppStatus nppiMaxIndx_8u_AC4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp8u aMax[3], int aIndexX[3], int aIndexY[3])

Four-channel 8-bit unsigned image MaxIndx ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxIndxGetBufferHostSize_8u_AC4R](#) to determine the maximum number of bytes required.

aMax Array that contains the max values.

aIndexX Array that contains the X coordinates of the image max values.

aIndexY Array that contains the Y coordinates of the image max values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.92.2.14 `NppStatus nppiMaxIdx_8u_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp8u * pMax, int * pIndexX, int * pIndexY)`

One-channel 8-bit unsigned image MaxIdx.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxIdxGetBufferHostSize_8u_C1R](#) to determine the maximum number of bytes required.

pMax Pointer to the computed max result.

pIndexX Pointer to the X coordinate of the image max value.

pIndexY Pointer to the Y coordinate of the image max value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.92.2.15 `NppStatus nppiMaxIdx_8u_C3R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp8u aMax[3], int aIndexX[3], int aIndexY[3])`

Three-channel 8-bit unsigned image MaxIdx.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxIdxGetBufferHostSize_8u_C3R](#) to determine the maximum number of bytes required.

aMax Array that contains the max values.

aIndexX Array that contains the X coordinates of the image max values.

aIndexY Array that contains the Y coordinates of the image max values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.92.2.16 `NppStatus nppiMaxIdx_8u_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp8u aMax[4], int aIndexX[4], int aIndexY[4])`

Four-channel 8-bit unsigned image MaxIdx.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI [Region-of-Interest \(ROI\)](#).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMaxIndxGetBufferHostSize_8u_C4R](#) to determine the maximum number of bytes required.

aMax Array that contains the max values.

aIndexX Array that contains the X coordinates of the image max values.

aIndexY Array that contains the Y coordinates of the image max values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.92.2.17 NppStatus nppiMaxIndxGetBufferHostSize_16s_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for [nppiMaxIndx_16u_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

[NPP_NULL_POINTER_ERROR](#) if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.92.2.18 NppStatus nppiMaxIndxGetBufferHostSize_16s_C1R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for [nppiMaxIndx_16s_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

[NPP_NULL_POINTER_ERROR](#) if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.92.2.19 NppStatus nppiMaxIndxGetBufferHostSize_16s_C3R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for [nppiMaxIndx_16s_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.92.2.20 NppStatus nppiMaxIndxGetBufferHostSize_16s_C4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiMaxIndx_16s_C4R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.92.2.21 NppStatus nppiMaxIndxGetBufferHostSize_16u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiMaxIndx_8u_AC4R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.92.2.22 NppStatus nppiMaxIndxGetBufferHostSize_16u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiMaxIndx_16u_C1R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.92.2.23 NppStatus nppiMaxIndxGetBufferHostSize_16u_C3R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Computes the device scratch buffer size (in bytes) for nppiMaxIndx_16u_C3R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.92.2.24 NppStatus nppiMaxIndxGetBufferHostSize_16u_C4R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Computes the device scratch buffer size (in bytes) for nppiMaxIndx_16u_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.92.2.25 NppStatus nppiMaxIndxGetBufferHostSize_32f_AC4R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Computes the device scratch buffer size (in bytes) for nppiMaxIndx_32f_AC4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.92.2.26 NppStatus nppiMaxIndxGetBufferHostSize_32f_C1R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Computes the device scratch buffer size (in bytes) for nppiMaxIndx_32f_C1R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.92.2.27 NppStatus nppiMaxIndxGetBufferHostSize_32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiMaxIndx_32f_C3R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.92.2.28 NppStatus nppiMaxIndxGetBufferHostSize_32f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiMaxIndx_32f_C4R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.92.2.29 NppStatus nppiMaxIndxGetBufferHostSize_8u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiMaxIndx_8u_AC4R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.92.2.30 NppStatus nppiMaxIndxGetBufferHostSize_8u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiMaxIndx_8u_C1R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.92.2.31 NppStatus nppiMaxIndxGetBufferHostSize_8u_C3R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiMaxIndx_8u_C3R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.92.2.32 NppStatus nppiMaxIndxGetBufferHostSize_8u_C4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiMaxIndx_8u_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.93 MinMax

Primitives for computing both the minimal and the maximal values of an image.

MinMax

The functions require the device scratch buffer.

- `NppStatus nppiMinMax_8u_C1R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp8u *pMin`, `Npp8u *pMax`, `Npp8u *pDeviceBuffer`)
One-channel 8-bit unsigned image MinMax.
- `NppStatus nppiMinMax_16u_C1R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp16u *pMin`, `Npp16u *pMax`, `Npp8u *pDeviceBuffer`)
One-channel 16-bit unsigned image MinMax.
- `NppStatus nppiMinMax_16s_C1R` (const `Npp16s *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp16s *pMin`, `Npp16s *pMax`, `Npp8u *pDeviceBuffer`)
One-channel 16-bit signed image MinMax.
- `NppStatus nppiMinMax_32f_C1R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp32f *pMin`, `Npp32f *pMax`, `Npp8u *pDeviceBuffer`)
One-channel 32-bit floating point image MinMax.
- `NppStatus nppiMinMax_8u_C3R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp8u aMin[3]`, `Npp8u aMax[3]`, `Npp8u *pDeviceBuffer`)
Three-channel 8-bit unsigned image MinMax.
- `NppStatus nppiMinMax_16u_C3R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp16u aMin[3]`, `Npp16u aMax[3]`, `Npp8u *pDeviceBuffer`)
Three-channel 16-bit unsigned image MinMax.
- `NppStatus nppiMinMax_16s_C3R` (const `Npp16s *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp16s aMin[3]`, `Npp16s aMax[3]`, `Npp8u *pDeviceBuffer`)
Three-channel 16-bit signed image MinMax.
- `NppStatus nppiMinMax_32f_C3R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp32f aMin[3]`, `Npp32f aMax[3]`, `Npp8u *pDeviceBuffer`)
Three-channel 32-bit floating point image MinMax.
- `NppStatus nppiMinMax_8u_AC4R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp8u aMin[3]`, `Npp8u aMax[3]`, `Npp8u *pDeviceBuffer`)
Four-channel 8-bit unsigned image MinMax ignoring alpha channel.
- `NppStatus nppiMinMax_16u_AC4R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp16u aMin[3]`, `Npp16u aMax[3]`, `Npp8u *pDeviceBuffer`)
Four-channel 16-bit unsigned image MinMax ignoring alpha channel.
- `NppStatus nppiMinMax_16s_AC4R` (const `Npp16s *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp16s aMin[3]`, `Npp16s aMax[3]`, `Npp8u *pDeviceBuffer`)

Four-channel 16-bit signed image MinMax ignoring alpha channel.

- `NppStatus nppiMinMax_32f_AC4R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp32f aMin[3]`, `Npp32f aMax[3]`, `Npp8u *pDeviceBuffer`)

Four-channel 32-bit floating point image MinMax ignoring alpha channel.

- `NppStatus nppiMinMax_8u_C4R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp8u aMin[4]`, `Npp8u aMax[4]`, `Npp8u *pDeviceBuffer`)

Four-channel 8-bit unsigned image MinMax.

- `NppStatus nppiMinMax_16u_C4R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp16u aMin[4]`, `Npp16u aMax[4]`, `Npp8u *pDeviceBuffer`)

Four-channel 16-bit unsigned image MinMax.

- `NppStatus nppiMinMax_16s_C4R` (const `Npp16s *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp16s aMin[4]`, `Npp16s aMax[4]`, `Npp8u *pDeviceBuffer`)

Four-channel 16-bit signed image MinMax.

- `NppStatus nppiMinMax_32f_C4R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp32f aMin[4]`, `Npp32f aMax[4]`, `Npp8u *pDeviceBuffer`)

Four-channel 32-bit floating point image MinMax.

MinMaxGetBufferHostSize

Companion primitives for computing the device buffer size (in bytes) required by the MinMax primitives.

- `NppStatus nppiMinMaxGetBufferHostSize_8u_C1R` (`NppiSize oSizeROI`, int `*hpBufferSize`)
Buffer size for `nppiMinMax_8u_C1R`.

- `NppStatus nppiMinMaxGetBufferHostSize_16u_C1R` (`NppiSize oSizeROI`, int `*hpBufferSize`)
Buffer size for `nppiMinMax_16u_C1R`.

- `NppStatus nppiMinMaxGetBufferHostSize_16s_C1R` (`NppiSize oSizeROI`, int `*hpBufferSize`)
Buffer size for `nppiMinMax_16s_C1R`.

- `NppStatus nppiMinMaxGetBufferHostSize_32f_C1R` (`NppiSize oSizeROI`, int `*hpBufferSize`)
Buffer size for `nppiMinMax_32f_C1R`.

- `NppStatus nppiMinMaxGetBufferHostSize_8u_C3R` (`NppiSize oSizeROI`, int `*hpBufferSize`)
Buffer size for `nppiMinMax_8u_C3R`.

- `NppStatus nppiMinMaxGetBufferHostSize_16u_C3R` (`NppiSize oSizeROI`, int `*hpBufferSize`)
Buffer size for `nppiMinMax_16u_C3R`.

- `NppStatus nppiMinMaxGetBufferHostSize_16s_C3R` (`NppiSize oSizeROI`, int `*hpBufferSize`)
Buffer size for `nppiMinMax_16s_C3R`.

- `NppStatus nppiMinMaxGetBufferHostSize_32f_C3R` (`NppiSize oSizeROI`, int `*hpBufferSize`)
Buffer size for `nppiMinMax_32f_C3R`.

- [NppStatus nppiMinMaxGetBufferHostSize_8u_AC4R](#) ([NppiSize](#) [oSizeROI](#), int *hpBufferSize)
Buffer size for [nppiMinMax_8u_AC4R](#).
- [NppStatus nppiMinMaxGetBufferHostSize_16u_AC4R](#) ([NppiSize](#) [oSizeROI](#), int *hpBufferSize)
Buffer size for [nppiMinMax_16u_AC4R](#).
- [NppStatus nppiMinMaxGetBufferHostSize_16s_AC4R](#) ([NppiSize](#) [oSizeROI](#), int *hpBufferSize)
Buffer size for [nppiMinMax_16s_AC4R](#).
- [NppStatus nppiMinMaxGetBufferHostSize_32f_AC4R](#) ([NppiSize](#) [oSizeROI](#), int *hpBufferSize)
Buffer size for [nppiMinMax_32f_AC4R](#).
- [NppStatus nppiMinMaxGetBufferHostSize_8u_C4R](#) ([NppiSize](#) [oSizeROI](#), int *hpBufferSize)
Buffer size for [nppiMinMax_8u_C4R](#).
- [NppStatus nppiMinMaxGetBufferHostSize_16u_C4R](#) ([NppiSize](#) [oSizeROI](#), int *hpBufferSize)
Buffer size for [nppiMinMax_16u_C4R](#).
- [NppStatus nppiMinMaxGetBufferHostSize_16s_C4R](#) ([NppiSize](#) [oSizeROI](#), int *hpBufferSize)
Buffer size for [nppiMinMax_16s_C4R](#).
- [NppStatus nppiMinMaxGetBufferHostSize_32f_C4R](#) ([NppiSize](#) [oSizeROI](#), int *hpBufferSize)
Buffer size for [nppiMinMax_32f_C4R](#).

7.93.1 Detailed Description

Primitives for computing both the minimal and the maximal values of an image.

7.93.2 Function Documentation

7.93.2.1 [NppStatus nppiMinMax_16s_AC4R](#) (const [Npp16s](#) * *pSrc*, int *nSrcStep*, [NppiSize](#) *oSizeROI*, [Npp16s](#) *aMin*[3], [Npp16s](#) *aMax*[3], [Npp8u](#) * *pDeviceBuffer*)

Four-channel 16-bit signed image MinMax ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aMin Array that contains the minima.

aMax Array that contains the maxima.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxGetBufferHostSize_16s_AC4R](#) to determine the minimum number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.93.2.2 NppStatus nppiMinMax_16s_C1R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp16s * pMin, Npp16s * pMax, Npp8u * pDeviceBuffer)

One-channel 16-bit signed image MinMax.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMin Pointer to the computed minimal result.

pMax Pointer to the computed maximal result.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxGetBufferHostSize_16s_C1R](#) to determine the minium number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.93.2.3 NppStatus nppiMinMax_16s_C3R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp16s aMin[3], Npp16s aMax[3], Npp8u * pDeviceBuffer)

Three-channel 16-bit signed image MinMax.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aMin Array that contains the minima.

aMax Array that contains the maxima.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxGetBufferHostSize_16s_C3R](#) to determine the minium number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.93.2.4 NppStatus nppiMinMax_16s_C4R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp16s aMin[4], Npp16s aMax[4], Npp8u * pDeviceBuffer)

Four-channel 16-bit signed image MinMax.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aMin Array that contains the minima.

aMax Array that contains the maxima.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxGetBufferHostSize_16s_C4R](#) to determine the minimum number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.93.2.5 NppStatus nppiMinMax_16u_AC4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp16u aMin[3], Npp16u aMax[3], Npp8u * pDeviceBuffer)

Four-channel 16-bit unsigned image MinMax ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aMin Array that contains the minima.

aMax Array that contains the maxima.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxGetBufferHostSize_16u_AC4R](#) to determine the minimum number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.93.2.6 NppStatus nppiMinMax_16u_C1R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp16u * pMin, Npp16u * pMax, Npp8u * pDeviceBuffer)

One-channel 16-bit unsigned image MinMax.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pMin Pointer to the computed minimal result.

pMax Pointer to the computed maximal result.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxGetBufferHostSize_16u_C1R](#) to determine the minimum number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.93.2.7 NppStatus nppiMinMax_16u_C3R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp16u aMin[3], Npp16u aMax[3], Npp8u * pDeviceBuffer)

Three-channel 16-bit unsigned image MinMax.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aMin Array that contains the minima.

aMax Array that contains the maxima.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxGetBufferHostSize_16u_C3R](#) to determine the minimum number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.93.2.8 NppStatus nppiMinMax_16u_C4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp16u aMin[4], Npp16u aMax[4], Npp8u * pDeviceBuffer)

Four-channel 16-bit unsigned image MinMax.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aMin Array that contains the minima.

aMax Array that contains the maxima.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxGetBufferHostSize_16u_C4R](#) to determine the minimum number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.93.2.9 NppStatus nppiMinMax_32f_AC4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32f aMin[3], Npp32f aMax[3], Npp8u * pDeviceBuffer)

Four-channel 32-bit floating point image MinMax ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aMin Array that contains the minima.

aMax Array that contains the maxima.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxGetBufferHostSize_32f_AC4R](#) to determine the minimum number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.93.2.10 NppStatus nppiMinMax_32f_C1R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32f * pMin, Npp32f * pMax, Npp8u * pDeviceBuffer)

One-channel 32-bit floating point image MinMax.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMin Pointer to the computed minimal result.

pMax Pointer to the computed maximal result.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxGetBufferHostSize_32f_C1R](#) to determine the minimum number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.93.2.11 NppStatus nppiMinMax_32f_C3R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32f aMin[3], Npp32f aMax[3], Npp8u * pDeviceBuffer)

Three-channel 32-bit floating point image MinMax.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aMin Array that contains the minima.

aMax Array that contains the maxima.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxGetBufferHostSize_32f_C3R](#) to determine the minimum number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.93.2.12 NppStatus nppiMinMax_32f_C4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32f aMin[4], Npp32f aMax[4], Npp8u * pDeviceBuffer)

Four-channel 32-bit floating point image MinMax.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aMin Array that contains the minima.

aMax Array that contains the maxima.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxGetBufferHostSize_32f_C4R](#) to determine the minimum number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.93.2.13 NppStatus nppiMinMax_8u_AC4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u aMin[3], Npp8u aMax[3], Npp8u * pDeviceBuffer)

Four-channel 8-bit unsigned image MinMax ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aMin Array that contains the minima.

aMax Array that contains the maxima.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxGetBufferHostSize_8u_AC4R](#) to determine the minimum number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.93.2.14 NppStatus nppiMinMax_8u_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pMin, Npp8u * pMax, Npp8u * pDeviceBuffer)

One-channel 8-bit unsigned image MinMax.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMin Pointer to the computed minimal result.

pMax Pointer to the computed maximal result.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxGetBufferHostSize_8u_C1R](#) to determine the minimum number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.93.2.15 NppStatus nppiMinMax_8u_C3R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u aMin[3], Npp8u aMax[3], Npp8u * pDeviceBuffer)

Three-channel 8-bit unsigned image MinMax.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aMin Array that contains the minima.

aMax Array that contains the maxima.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxGetBufferHostSize_8u_C3R](#) to determine the minimum number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.93.2.16 NppStatus nppiMinMax_8u_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u aMin[4], Npp8u aMax[4], Npp8u * pDeviceBuffer)

Four-channel 8-bit unsigned image MinMax.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aMin Array that contains the minima.

aMax Array that contains the maxima.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxGetBufferHostSize_8u_C4R](#) to determine the minimum number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.93.2.17 NppStatus nppiMinMaxGetBufferHostSize_16s_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMinMax_16s_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.93.2.18 NppStatus nppiMinMaxGetBufferHostSize_16s_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMinMax_16s_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.93.2.19 NppStatus nppiMinMaxGetBufferHostSize_16s_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMinMax_16s_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.93.2.20 NppStatus nppiMinMaxGetBufferHostSize_16s_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMinMax_16s_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.93.2.21 NppStatus nppiMinMaxGetBufferHostSize_16u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMinMax_16u_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.93.2.22 NppStatus nppiMinMaxGetBufferHostSize_16u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMinMax_16u_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.93.2.23 NppStatus nppiMinMaxGetBufferHostSize_16u_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMinMax_16u_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.93.2.24 NppStatus nppiMinMaxGetBufferHostSize_16u_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMinMax_16u_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.93.2.25 NppStatus nppiMinMaxGetBufferHostSize_32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMinMax_32f_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.93.2.26 NppStatus nppiMinMaxGetBufferHostSize_32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMinMax_32f_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.93.2.27 NppStatus nppiMinMaxGetBufferHostSize_32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMinMax_32f_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.93.2.28 NppStatus nppiMinMaxGetBufferHostSize_32f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMinMax_32f_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.93.2.29 NppStatus nppiMinMaxGetBufferHostSize_8u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMinMax_8u_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.93.2.30 NppStatus nppiMinMaxGetBufferHostSize_8u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMinMax_8u_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

**7.93.2.31 NppStatus nppiMinMaxGetBufferHostSize_8u_C3R (NppiSize *oSizeROI*, int *
hpBufferSize)**

Buffer size for [nppiMinMax_8u_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

**7.93.2.32 NppStatus nppiMinMaxGetBufferHostSize_8u_C4R (NppiSize *oSizeROI*, int *
hpBufferSize)**

Buffer size for [nppiMinMax_8u_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.94 MinMaxIndx

Primitives for computing the minimal and the maximal values with their indices (X and Y coordinates) of an image.

MinMaxIndx

If there are several minima and maxima in the selected region of interest, the function returns ones on the top leftmost position.

The scratch buffer is required by the functions.

- `NppStatus nppiMinMaxIndx_8u_C1R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pMinValue, `Npp8u` *pMaxValue, `NppiPoint` *pMinIndex, `NppiPoint` *pMaxIndex, `Npp8u` *pDeviceBuffer)
Computes the minimal and the maximal pixel values with their X and Y coordinates of 1-channel 8-bit unsigned char image.
- `NppStatus nppiMinMaxIndx_8s_C1R` (const `Npp8s` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8s` *pMinValue, `Npp8s` *pMaxValue, `NppiPoint` *pMinIndex, `NppiPoint` *pMaxIndex, `Npp8u` *pDeviceBuffer)
Computes the minimal and the maximal pixel values with their X and Y coordinates of 1-channel 8-bit signed char image.
- `NppStatus nppiMinMaxIndx_16u_C1R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp16u` *pMinValue, `Npp16u` *pMaxValue, `NppiPoint` *pMinIndex, `NppiPoint` *pMaxIndex, `Npp8u` *pDeviceBuffer)
Computes the minimal and the maximal pixel values with their X and Y coordinates of 1-channel 16-bit unsigned short image.
- `NppStatus nppiMinMaxIndx_32f_C1R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp32f` *pMinValue, `Npp32f` *pMaxValue, `NppiPoint` *pMinIndex, `NppiPoint` *pMaxIndex, `Npp8u` *pDeviceBuffer)
Computes the minimal and the maximal pixel values with their X and Y coordinates of 1-channel 32-bit floating point image.

Masked MinMaxIndx

See [Masked Operation](#).

- `NppStatus nppiMinMaxIndx_8u_C1MR` (const `Npp8u` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, `Npp8u` *pMinValue, `Npp8u` *pMaxValue, `NppiPoint` *pMinIndex, `NppiPoint` *pMaxIndex, `Npp8u` *pDeviceBuffer)
Masked one-channel 8-bit unsigned image MinMaxIndx.
- `NppStatus nppiMinMaxIndx_8s_C1MR` (const `Npp8s` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, `Npp8s` *pMinValue, `Npp8s` *pMaxValue, `NppiPoint` *pMinIndex, `NppiPoint` *pMaxIndex, `Npp8u` *pDeviceBuffer)
Masked one-channel 8-bit signed image MinMaxIndx.

- `NppStatus nppiMinMaxIndx_16u_C1MR` (const `Npp16u` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, `Npp16u` *pMinValue, `Npp16u` *pMaxValue, `NppiPoint` *pMinIndex, `NppiPoint` *pMaxIndex, `Npp8u` *pDeviceBuffer)
Masked one-channel 16-bit unsigned image MinMaxIndx.
- `NppStatus nppiMinMaxIndx_32f_C1MR` (const `Npp32f` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, `Npp32f` *pMinValue, `Npp32f` *pMaxValue, `NppiPoint` *pMinIndex, `NppiPoint` *pMaxIndex, `Npp8u` *pDeviceBuffer)
Masked one-channel 32-bit floating point image MinMaxIndx.

Channel MinMaxIndx

See [Channel-of-Interest API](#).

- `NppStatus nppiMinMaxIndx_8u_C3CR` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, int nCOI, `Npp8u` *pMinValue, `Npp8u` *pMaxValue, `NppiPoint` *pMinIndex, `NppiPoint` *pMaxIndex, `Npp8u` *pDeviceBuffer)
Three-channel 8-bit unsigned image MinMaxIndx affecting only single channel.
- `NppStatus nppiMinMaxIndx_8s_C3CR` (const `Npp8s` *pSrc, int nSrcStep, `NppiSize` oSizeROI, int nCOI, `Npp8s` *pMinValue, `Npp8s` *pMaxValue, `NppiPoint` *pMinIndex, `NppiPoint` *pMaxIndex, `Npp8u` *pDeviceBuffer)
Three-channel 8-bit signed image MinMaxIndx affecting only single channel.
- `NppStatus nppiMinMaxIndx_16u_C3CR` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, int nCOI, `Npp16u` *pMinValue, `Npp16u` *pMaxValue, `NppiPoint` *pMinIndex, `NppiPoint` *pMaxIndex, `Npp8u` *pDeviceBuffer)
Three-channel 16-bit unsigned image MinMaxIndx affecting only single channel.
- `NppStatus nppiMinMaxIndx_32f_C3CR` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSizeROI, int nCOI, `Npp32f` *pMinValue, `Npp32f` *pMaxValue, `NppiPoint` *pMinIndex, `NppiPoint` *pMaxIndex, `Npp8u` *pDeviceBuffer)
Three-channel 32-bit floating point image MinMaxIndx affecting only single channel.

Masked Channel MinMaxIndx

See [Masked Operation](#) and [Channel-of-Interest API](#).

- `NppStatus nppiMinMaxIndx_8u_C3CMR` (const `Npp8u` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, int nCOI, `Npp8u` *pMinValue, `Npp8u` *pMaxValue, `NppiPoint` *pMinIndex, `NppiPoint` *pMaxIndex, `Npp8u` *pDeviceBuffer)
Masked three-channel 8-bit unsigned image MinMaxIndx affecting only single channel.
- `NppStatus nppiMinMaxIndx_8s_C3CMR` (const `Npp8s` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, int nCOI, `Npp8s` *pMinValue, `Npp8s` *pMaxValue, `NppiPoint` *pMinIndex, `NppiPoint` *pMaxIndex, `Npp8u` *pDeviceBuffer)
Masked three-channel 8-bit signed image MinMaxIndx affecting only single channel.

- `NppStatus nppiMinMaxIndx_16u_C3CMR` (const `Npp16u *pSrc`, int `nSrcStep`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, int `nCOI`, `Npp16u *pMinValue`, `Npp16u *pMaxValue`, `NppiPoint *pMinIndex`, `NppiPoint *pMaxIndex`, `Npp8u *pDeviceBuffer`)
Masked three-channel 16-bit unsigned image MinMaxIndx affecting only single channel.
- `NppStatus nppiMinMaxIndx_32f_C3CMR` (const `Npp32f *pSrc`, int `nSrcStep`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, int `nCOI`, `Npp32f *pMinValue`, `Npp32f *pMaxValue`, `NppiPoint *pMinIndex`, `NppiPoint *pMaxIndex`, `Npp8u *pDeviceBuffer`)
Masked three-channel 32-bit floating point image MinMaxIndx affecting only single channel.

MinMaxIndxGetBufferHostSize

Companion primitives for computing the device buffer size (in bytes) required by the `MinMaxIndx` primitives.

- `NppStatus nppiMinMaxIndxGetBufferHostSize_8u_C1R` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size for `nppiMinMaxIndx_8u_C1R`.
- `NppStatus nppiMinMaxIndxGetBufferHostSize_8s_C1R` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size for `nppiMinMaxIndx_8s_C1R`.
- `NppStatus nppiMinMaxIndxGetBufferHostSize_16u_C1R` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size for `nppiMinMaxIndx_16u_C1R`.
- `NppStatus nppiMinMaxIndxGetBufferHostSize_32f_C1R` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size for `nppiMinMaxIndx_32f_C1R`.
- `NppStatus nppiMinMaxIndxGetBufferHostSize_8u_C1MR` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size for `nppiMinMaxIndx_8u_C1MR`.
- `NppStatus nppiMinMaxIndxGetBufferHostSize_8s_C1MR` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size for `nppiMinMaxIndx_8s_C1MR`.
- `NppStatus nppiMinMaxIndxGetBufferHostSize_16u_C1MR` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size for `nppiMinMaxIndx_16u_C1MR`.
- `NppStatus nppiMinMaxIndxGetBufferHostSize_32f_C1MR` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size for `nppiMinMaxIndx_32f_C1MR`.
- `NppStatus nppiMinMaxIndxGetBufferHostSize_8u_C3CR` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size for `nppiMinMaxIndx_8u_C3CR`.

- **NppStatus** `nppiMinMaxIndxGetBufferHostSize_8s_C3CR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Buffer size for `nppiMinMaxIndx_8s_C3CR`.
- **NppStatus** `nppiMinMaxIndxGetBufferHostSize_16u_C3CR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Buffer size for `nppiMinMaxIndx_16u_C3CR`.
- **NppStatus** `nppiMinMaxIndxGetBufferHostSize_32f_C3CR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Buffer size for `nppiMinMaxIndx_32f_C3CR`.
- **NppStatus** `nppiMinMaxIndxGetBufferHostSize_8u_C3CMR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Buffer size for `nppiMinMaxIndx_8u_C3CMR`.
- **NppStatus** `nppiMinMaxIndxGetBufferHostSize_8s_C3CMR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Buffer size for `nppiMinMaxIndx_8s_C3CMR`.
- **NppStatus** `nppiMinMaxIndxGetBufferHostSize_16u_C3CMR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Buffer size for `nppiMinMaxIndx_16u_C3CMR`.
- **NppStatus** `nppiMinMaxIndxGetBufferHostSize_32f_C3CMR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Buffer size for `nppiMinMaxIndx_32f_C3CMR`.

7.94.1 Detailed Description

Primitives for computing the minimal and the maximal values with their indices (X and Y coordinates) of an image.

7.94.2 Function Documentation

7.94.2.1 **NppStatus** `nppiMinMaxIndx_16u_C1MR` (**const** **Npp16u** `*pSrc`, **int** `nSrcStep`, **const** **Npp8u** `*pMask`, **int** `nMaskStep`, **NppiSize** `oSizeROI`, **Npp16u** `*pMinValue`, **Npp16u** `*pMaxValue`, **NppiPoint** `*pMinIndex`, **NppiPoint** `*pMaxIndex`, **Npp8u** `*pDeviceBuffer`)

Masked one-channel 16-bit unsigned image MinMaxIndx.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pMask* Mask-Image Pointer.
- nMaskStep* Mask-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

pMinValue Pointer to the minimum value.

pMaxValue Pointer to the maximum value.

pMinIndex Pointer to the indicies (X and Y coordinates) of the minimum value.

pMaxIndex Pointer to the indicies (X and Y coordinates) of the maximum value.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxIndxGetBufferHostSize_16u_C1MR](#) to determine the minium number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#). If the mask is filled with zeros, then all the returned values are zeros, i.e., $pMinIndex = \{0, 0\}$, $pMaxIndex = \{0, 0\}$, $pMinValue = 0$, $pMaxValue = 0$. If any of $pMinValue$, $pMaxValue$, $pMinIndex$, or $pMaxIndex$ is not needed, zero pointer must be passed correspondingly.

7.94.2.2 NppStatus nppiMinMaxIndx_16u_C1R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp16u * pMinValue, Npp16u * pMaxValue, NppiPoint * pMinIndex, NppiPoint * pMaxIndex, Npp8u * pDeviceBuffer)

Computes the minimal and the maximal pixel values with their X and Y coordinates of 1-channel 16-bit unsigned short image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMinValue Pointer to the minimum value.

pMaxValue Pointer to the maximum value.

pMinIndex Pointer to the indicies (X and Y coordinates) of the minimum value.

pMaxIndex Pointer to the indicies (X and Y coordinates) of the maximum value.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxIndxGetBufferHostSize_16u_C1R](#) to determine the minium number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#). If any of $pMinValue$, $pMaxValue$, $pMinIndex$, or $pMaxIndex$ is not needed, zero pointer must be passed correspondingly.

7.94.2.3 NppStatus nppiMinMaxIndx_16u_C3CMR (const Npp16u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp16u * pMinValue, Npp16u * pMaxValue, NppiPoint * pMinIndex, NppiPoint * pMaxIndex, Npp8u * pDeviceBuffer)

Masked three-channel 16-bit unsigned image MinMaxIndx affecting only single channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pMinValue Pointer to the minimum value.

pMaxValue Pointer to the maximum value.

pMinIndex Pointer to the indicies (X and Y coordinates) of the minimum value.

pMaxIndex Pointer to the indicies (X and Y coordinates) of the maximum value.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxIndxGetBufferHostSize_16u_C3CMR](#) to determine the minium number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified. If the mask is filled with zeros, then all the returned values are zeros, i.e., `pMinIndex = {0, 0}`, `pMaxIndex = {0, 0}`, `pMinValue = 0`, `pMaxValue = 0`. If any of `pMinValue`, `pMaxValue`, `pMinIndex`, or `pMaxIndex` is not needed, zero pointer must be passed correspondingly.

7.94.2.4 NppStatus nppiMinMaxIndx_16u_C3CR (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, int nCOI, Npp16u * pMinValue, Npp16u * pMaxValue, NppiPoint * pMinIndex, NppiPoint * pMaxIndex, Npp8u * pDeviceBuffer)

Three-channel 16-bit unsigned image MinMaxIndx affecting only single channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pMinValue Pointer to the minimum value.

pMaxValue Pointer to the maximum value.

pMinIndex Pointer to the indicies (X and Y coordinates) of the minimum value.

pMaxIndex Pointer to the indicies (X and Y coordinates) of the maximum value.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxIndxGetBufferHostSize_16u_C3CR](#) to determine the minium number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified. If any of `pMinValue`, `pMaxValue`, `pMinIndex`, or `pMaxIndex` is not needed, zero pointer must be passed correspondingly.

7.94.2.5 NppStatus nppiMinMaxIdx_32f_C1MR (const Npp32f * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp32f * pMinValue, Npp32f * pMaxValue, NppiPoint * pMinIndex, NppiPoint * pMaxIndex, Npp8u * pDeviceBuffer)

Masked one-channel 32-bit floating point image MinMaxIdx.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMinValue Pointer to the minimum value.

pMaxValue Pointer to the maximum value.

pMinIndex Pointer to the indicies (X and Y coordinates) of the minimum value.

pMaxIndex Pointer to the indicies (X and Y coordinates) of the maximum value.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxIdxGetBufferHostSize_32f_C1MR](#) to determine the minium number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified. If the mask is filled with zeros, then all the returned values are zeros, i.e., `pMinIndex = {0, 0}`, `pMaxIndex = {0, 0}`, `pMinValue = 0`, `pMaxValue = 0`. If any of `pMinValue`, `pMaxValue`, `pMinIndex`, or `pMaxIndex` is not needed, zero pointer must be passed correspondingly.

7.94.2.6 NppStatus nppiMinMaxIdx_32f_C1R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32f * pMinValue, Npp32f * pMaxValue, NppiPoint * pMinIndex, NppiPoint * pMaxIndex, Npp8u * pDeviceBuffer)

Computes the minimal and the maximal pixel values with their X and Y coordinates of 1-channel 32-bit floating point image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMinValue Pointer to the minimum value.

pMaxValue Pointer to the maximum value.

pMinIndex Pointer to the indicies (X and Y coordinates) of the minimum value.

pMaxIndex Pointer to the indicies (X and Y coordinates) of the maximum value.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxIdxGetBufferHostSize_32f_C1R](#) to determine the minium number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified. If any of `pMinValue`, `pMaxValue`, `pMinIndex`, or `pMaxIndex` is not needed, zero pointer must be passed correspondingly.

7.94.2.7 NppStatus nppiMinMaxIndx_32f_C3CMR (**const Npp32f * pSrc**, **int nSrcStep**, **const Npp8u * pMask**, **int nMaskStep**, **NppiSize oSizeROI**, **int nCOI**, **Npp32f * pMinValue**, **Npp32f * pMaxValue**, **NppiPoint * pMinIndex**, **NppiPoint * pMaxIndex**, **Npp8u * pDeviceBuffer**)

Masked three-channel 32-bit floating point image MinMaxIndx affecting only single channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pMinValue Pointer to the minimum value.

pMaxValue Pointer to the maximum value.

pMinIndex Pointer to the indicies (X and Y coordinates) of the minimum value.

pMaxIndex Pointer to the indicies (X and Y coordinates) of the maximum value.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxIndxGetBufferHostSize_32f_C3CMR](#) to determine the minium number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified, or `NPP_COI_ERROR` if an invalid channel of interest is specified. If the mask is filled with zeros, then all the returned values are zeros, i.e., `pMinIndex = {0, 0}`, `pMaxIndex = {0, 0}`, `pMinValue = 0`, `pMaxValue = 0`. If any of `pMinValue`, `pMaxValue`, `pMinIndex`, or `pMaxIndex` is not needed, zero pointer must be passed correspondingly.

7.94.2.8 NppStatus nppiMinMaxIndx_32f_C3CR (**const Npp32f * pSrc**, **int nSrcStep**, **NppiSize oSizeROI**, **int nCOI**, **Npp32f * pMinValue**, **Npp32f * pMaxValue**, **NppiPoint * pMinIndex**, **NppiPoint * pMaxIndex**, **Npp8u * pDeviceBuffer**)

Three-channel 32-bit floating point image MinMaxIndx affecting only single channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pMinValue Pointer to the minimum value.

pMaxValue Pointer to the maximum value.

pMinIndex Pointer to the indicies (X and Y coordinates) of the minimum value.

pMaxIndex Pointer to the indicies (X and Y coordinates) of the maximum value.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxIndxGetBufferHostSize_32f_C3CR](#) to determine the minium number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), NPP_NOT_EVEN_STEP_ERROR if an invalid floating-point image is specified, or NPP_COI_ERROR if an invalid channel of interest is specified. If any of pMinValue, pMaxValue, pMinIndex, or pMaxIndex is not needed, zero pointer must be passed correspondingly.

7.94.2.9 `NppStatus nppiMinMaxIdx_8s_C1MR (const Npp8s * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp8s * pMinValue, Npp8s * pMaxValue, NppiPoint * pMinIndex, NppiPoint * pMaxIndex, Npp8u * pDeviceBuffer)`

Masked one-channel 8-bit signed image MinMaxIdx.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pMask [Mask-Image Pointer](#).

nMaskStep [Mask-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pMinValue Pointer to the minimum value.

pMaxValue Pointer to the maximum value.

pMinIndex Pointer to the indicies (X and Y coordinates) of the minimum value.

pMaxIndex Pointer to the indicies (X and Y coordinates) of the maximum value.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxIdxGetBufferHostSize_8s_C1MR](#) to determine the minium number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#). If the mask is filled with zeros, then all the returned values are zeros, i.e., pMinIndex = {0, 0}, pMaxIndex = {0, 0}, pMinValue = 0, pMaxValue = 0. If any of pMinValue, pMaxValue, pMinIndex, or pMaxIndex is not needed, zero pointer must be passed correspondingly.

7.94.2.10 `NppStatus nppiMinMaxIdx_8s_C1R (const Npp8s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8s * pMinValue, Npp8s * pMaxValue, NppiPoint * pMinIndex, NppiPoint * pMaxIndex, Npp8u * pDeviceBuffer)`

Computes the minimal and the maximal pixel values with their X and Y coordinates of 1-channel 8-bit signed char image.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pMinValue Pointer to the minimum value.

pMaxValue Pointer to the maximum value.

pMinIndex Pointer to the indices (X and Y coordinates) of the minimum value.

pMaxIndex Pointer to the indices (X and Y coordinates) of the maximum value.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxIndxGetBufferHostSize_8s_C1R](#) to determine the minimum number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#). If any of *pMinValue*, *pMaxValue*, *pMinIndex*, or *pMaxIndex* is not needed, zero pointer must be passed correspondingly.

7.94.2.11 `NppStatus nppiMinMaxIndx_8s_C3CMR (const Npp8s * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp8s * pMinValue, Npp8s * pMaxValue, NppiPoint * pMinIndex, NppiPoint * pMaxIndex, Npp8u * pDeviceBuffer)`

Masked three-channel 8-bit signed image MinMaxIndx affecting only single channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pMinValue Pointer to the minimum value.

pMaxValue Pointer to the maximum value.

pMinIndex Pointer to the indices (X and Y coordinates) of the minimum value.

pMaxIndex Pointer to the indices (X and Y coordinates) of the maximum value.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxIndxGetBufferHostSize_8s_C3CMR](#) to determine the minimum number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified. If the mask is filled with zeros, then all the returned values are zeros, i.e., *pMinIndex* = {0, 0}, *pMaxIndex* = {0, 0}, *pMinValue* = 0, *pMaxValue* = 0. If any of *pMinValue*, *pMaxValue*, *pMinIndex*, or *pMaxIndex* is not needed, zero pointer must be passed correspondingly.

7.94.2.12 `NppStatus nppiMinMaxIndx_8s_C3CR (const Npp8s * pSrc, int nSrcStep, NppiSize oSizeROI, int nCOI, Npp8s * pMinValue, Npp8s * pMaxValue, NppiPoint * pMinIndex, NppiPoint * pMaxIndex, Npp8u * pDeviceBuffer)`

Three-channel 8-bit signed image MinMaxIndx affecting only single channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

nCOI [Channel_of_Interest Number](#).

pMinValue Pointer to the minimum value.

pMaxValue Pointer to the maximum value.

pMinIndex Pointer to the indicies (X and Y coordinates) of the minimum value.

pMaxIndex Pointer to the indicies (X and Y coordinates) of the maximum value.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxIndxGetBufferHostSize_8s_C3CR](#) to determine the minium number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified. If any of *pMinValue*, *pMaxValue*, *pMinIndex*, or *pMaxIndex* is not needed, zero pointer must be passed correspondingly.

7.94.2.13 `NppStatus nppiMinMaxIndx_8u_C1MR (const Npp8u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp8u * pMinValue, Npp8u * pMaxValue, NppiPoint * pMinIndex, NppiPoint * pMaxIndex, Npp8u * pDeviceBuffer)`

Masked one-channel 8-bit unsigned image MinMaxIndx.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pMask [Mask-Image Pointer](#).

nMaskStep [Mask-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pMinValue Pointer to the minimum value.

pMaxValue Pointer to the maximum value.

pMinIndex Pointer to the indicies (X and Y coordinates) of the minimum value.

pMaxIndex Pointer to the indicies (X and Y coordinates) of the maximum value.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxIndxGetBufferHostSize_8u_C1MR](#) to determine the minium number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#). If the mask is filled with zeros, then all the returned values are zeros, i.e., *pMinIndex* = {0, 0}, *pMaxIndex* = {0, 0}, *pMinValue* = 0, *pMaxValue* = 0. If any of *pMinValue*, *pMaxValue*, *pMinIndex*, or *pMaxIndex* is not needed, zero pointer must be passed correspondingly.

7.94.2.14 `NppStatus nppiMinMaxIndx_8u_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pMinValue, Npp8u * pMaxValue, NppiPoint * pMinIndex, NppiPoint * pMaxIndex, Npp8u * pDeviceBuffer)`

Computes the minimal and the maximal pixel values with their X and Y coordinates of 1-channel 8-bit unsigned char image.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- pMinValue* Pointer to the minimum value.
- pMaxValue* Pointer to the maximum value.
- pMinIndex* Pointer to the indicies (X and Y coordinates) of the minimum value.
- pMaxIndex* Pointer to the indicies (X and Y coordinates) of the maximum value.
- pDeviceBuffer* Buffer to a scratch memory. Use `nppiMinMaxIndxGetBufferHostSize_8u_C1R` to determine the minium number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#). If any of *pMinValue*, *pMaxValue*, *pMinIndex*, or *pMaxIndex* is not needed, zero pointer must be passed correspondingly.

7.94.2.15 `NppStatus nppiMinMaxIndx_8u_C3CMR (const Npp8u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp8u * pMinValue, Npp8u * pMaxValue, NppiPoint * pMinIndex, NppiPoint * pMaxIndex, Npp8u * pDeviceBuffer)`

Masked three-channel 8-bit unsigned image MinMaxIndx affecting only single channel.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pMask* Mask-Image Pointer.
- nMaskStep* Mask-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nCOI* Channel_of_Interest Number.
- pMinValue* Pointer to the minimum value.
- pMaxValue* Pointer to the maximum value.
- pMinIndex* Pointer to the indicies (X and Y coordinates) of the minimum value.
- pMaxIndex* Pointer to the indicies (X and Y coordinates) of the maximum value.
- pDeviceBuffer* Buffer to a scratch memory. Use `nppiMinMaxIndxGetBufferHostSize_8u_C3CMR` to determine the minium number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified. If the mask is filled with zeros, then all the returned values are zeros, i.e., *pMinIndex* = {0, 0}, *pMaxIndex* = {0, 0}, *pMinValue* = 0, *pMaxValue* = 0. If any of *pMinValue*, *pMaxValue*, *pMinIndex*, or *pMaxIndex* is not needed, zero pointer must be passed correspondingly.

7.94.2.16 `NppStatus nppiMinMaxIndx_8u_C3CR (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, int nCOI, Npp8u * pMinValue, Npp8u * pMaxValue, NppiPoint * pMinIndex, NppiPoint * pMaxIndex, Npp8u * pDeviceBuffer)`

Three-channel 8-bit unsigned image MinMaxIndx affecting only single channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pMinValue Pointer to the minimum value.

pMaxValue Pointer to the maximum value.

pMinIndex Pointer to the indicies (X and Y coordinates) of the minimum value.

pMaxIndex Pointer to the indicies (X and Y coordinates) of the maximum value.

pDeviceBuffer Buffer to a scratch memory. Use `nppiMinMaxIndxGetBufferHostSize_8u_C3CR` to determine the minium number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified. If any of *pMinValue*, *pMaxValue*, *pMinIndex*, or *pMaxIndex* is not needed, zero pointer must be passed correspondingly.

7.94.2.17 `NppStatus nppiMinMaxIndxGetBufferHostSize_16u_C1MR (NppiSize oSizeROI, int * hpBufferSize)`

Buffer size for `nppiMinMaxIndx_16u_C1MR`.

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.94.2.18 `NppStatus nppiMinMaxIndxGetBufferHostSize_16u_C1R (NppiSize oSizeROI, int * hpBufferSize)`

Buffer size for `nppiMinMaxIndx_16u_C1R`.

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.94.2.19 NppStatus nppiMinMaxIndxGetBufferHostSize_16u_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMinMaxIndx_16u_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.94.2.20 NppStatus nppiMinMaxIndxGetBufferHostSize_16u_C3CR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMinMaxIndx_16u_C3CR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.94.2.21 NppStatus nppiMinMaxIndxGetBufferHostSize_32f_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMinMaxIndx_32f_C1MR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.94.2.22 NppStatus nppiMinMaxIndxGetBufferHostSize_32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMinMaxIndx_32f_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.94.2.23 NppStatus nppiMinMaxIndxGetBufferHostSize_32f_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMinMaxIndx_32f_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.94.2.24 NppStatus nppiMinMaxIndxGetBufferHostSize_32f_C3CR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMinMaxIndx_32f_C3CR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.94.2.25 NppStatus nppiMinMaxIndxGetBufferHostSize_8s_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMinMaxIndx_8s_C1MR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.94.2.26 NppStatus nppiMinMaxIndxGetBufferHostSize_8s_C1R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size for [nppiMinMaxIndx_8s_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.94.2.27 NppStatus nppiMinMaxIndxGetBufferHostSize_8s_C3CMR (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size for [nppiMinMaxIndx_8s_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.94.2.28 NppStatus nppiMinMaxIndxGetBufferHostSize_8s_C3CR (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size for [nppiMinMaxIndx_8s_C3CR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.94.2.29 NppStatus nppiMinMaxIndxGetBufferHostSize_8u_C1MR (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size for [nppiMinMaxIndx_8u_C1MR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.94.2.30 NppStatus nppiMinMaxIndxGetBufferHostSize_8u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMinMaxIndx_8u_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.94.2.31 NppStatus nppiMinMaxIndxGetBufferHostSize_8u_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMinMaxIndx_8u_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.94.2.32 NppStatus nppiMinMaxIndxGetBufferHostSize_8u_C3CR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMinMaxIndx_8u_C3CR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.95 Mean

Primitives for computing the arithmetic mean of all the pixel values in an image.

Mean

Given an image $pSrc$ with width W and height H , the arithmetic mean will be computed as

$$Mean = \frac{1}{W \cdot H} \sum_{j=0}^{H-1} \sum_{i=0}^{W-1} pSrc(j, i)$$

The mean functions require additional scratch buffer for computations.

- `NppStatus nppiMean_8u_C1R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` *pMean)
One-channel 8-bit unsigned image Mean.
- `NppStatus nppiMean_16u_C1R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` *pMean)
One-channel 16-bit unsigned image Mean.
- `NppStatus nppiMean_16s_C1R` (const `Npp16s` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` *pMean)
One-channel 16-bit signed image Mean.
- `NppStatus nppiMean_32f_C1R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` *pMean)
One-channel 32-bit floating point image Mean.
- `NppStatus nppiMean_8u_C3R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` aMean[3])
Three-channel 8-bit unsigned image Mean.
- `NppStatus nppiMean_16u_C3R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` aMean[3])
Three-channel 16-bit unsigned image Mean.
- `NppStatus nppiMean_16s_C3R` (const `Npp16s` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` aMean[3])
Three-channel 16-bit signed image Mean.
- `NppStatus nppiMean_32f_C3R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` aMean[3])
Three-channel 32-bit floating point image Mean.
- `NppStatus nppiMean_8u_C4R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` aMean[4])
Four-channel 8-bit unsigned image Mean.

- `NppStatus nppiMean_16u_C4R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` aMean[4])
Four-channel 16-bit unsigned image Mean.
- `NppStatus nppiMean_16s_C4R` (const `Npp16s` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` aMean[4])
Four-channel 16-bit signed image Mean.
- `NppStatus nppiMean_32f_C4R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` aMean[4])
Four-channel 32-bit floating point image Mean.
- `NppStatus nppiMean_8u_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` aMean[3])
Four-channel 8-bit unsigned image Mean ignoring alpha channel.
- `NppStatus nppiMean_16u_AC4R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` aMean[3])
Four-channel 16-bit unsigned image Mean ignoring alpha channel.
- `NppStatus nppiMean_16s_AC4R` (const `Npp16s` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` aMean[3])
Four-channel 16-bit signed image Mean ignoring alpha channel.
- `NppStatus nppiMean_32f_AC4R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` aMean[3])
Four-channel 32-bit floating point image Mean ignoring alpha channel.

Masked Mean

See [Masked Operation](#).

- `NppStatus nppiMean_8u_C1MR` (const `Npp8u` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` *pMean)
Masked one-channel 8-bit unsigned image Mean.
- `NppStatus nppiMean_8s_C1MR` (const `Npp8s` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` *pMean)
Masked one-channel 8-bit signed image Mean.
- `NppStatus nppiMean_16u_C1MR` (const `Npp16u` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` *pMean)
Masked one-channel 16-bit unsigned image Mean.
- `NppStatus nppiMean_32f_C1MR` (const `Npp32f` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` *pMean)
Masked one-channel 32-bit floating point image Mean.

Masked Channel Mean

See [Channel-of-Interest API](#) and [Masked Operation](#).

- [NppStatus nppiMean_8u_C3CMR](#) (const [Npp8u](#) *pSrc, int nSrcStep, const [Npp8u](#) *pMask, int nMaskStep, [NppiSize](#) oSizeROI, int nCOI, [Npp8u](#) *pDeviceBuffer, [Npp64f](#) *pMean)
Masked three-channel 8-bit unsigned image Mean affecting only single channel.
- [NppStatus nppiMean_8s_C3CMR](#) (const [Npp8s](#) *pSrc, int nSrcStep, const [Npp8u](#) *pMask, int nMaskStep, [NppiSize](#) oSizeROI, int nCOI, [Npp8u](#) *pDeviceBuffer, [Npp64f](#) *pMean)
Masked three-channel 8-bit signed image Mean affecting only single channel.
- [NppStatus nppiMean_16u_C3CMR](#) (const [Npp16u](#) *pSrc, int nSrcStep, const [Npp8u](#) *pMask, int nMaskStep, [NppiSize](#) oSizeROI, int nCOI, [Npp8u](#) *pDeviceBuffer, [Npp64f](#) *pMean)
Masked three-channel 16-bit unsigned image Mean affecting only single channel.
- [NppStatus nppiMean_32f_C3CMR](#) (const [Npp32f](#) *pSrc, int nSrcStep, const [Npp8u](#) *pMask, int nMaskStep, [NppiSize](#) oSizeROI, int nCOI, [Npp8u](#) *pDeviceBuffer, [Npp64f](#) *pMean)
Masked three-channel 32-bit floating point image Mean affecting only single channel.

MeanGetBufferHostSize

Companion primitives for computing the device buffer size (in bytes) required by the Mean primitives.

- [NppStatus nppiMeanGetBufferHostSize_8u_C1R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Buffer size for [nppiMean_8u_C1R](#).
- [NppStatus nppiMeanGetBufferHostSize_16u_C1R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Buffer size for [nppiMean_16u_C1R](#).
- [NppStatus nppiMeanGetBufferHostSize_16s_C1R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Buffer size for [nppiMean_16s_C1R](#).
- [NppStatus nppiMeanGetBufferHostSize_32f_C1R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Buffer size for [nppiMean_32f_C1R](#).
- [NppStatus nppiMeanGetBufferHostSize_8u_C3R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Buffer size for [nppiMean_8u_C3R](#).
- [NppStatus nppiMeanGetBufferHostSize_16u_C3R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Buffer size for [nppiMean_16u_C3R](#).
- [NppStatus nppiMeanGetBufferHostSize_16s_C3R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Buffer size for [nppiMean_16s_C3R](#).
- [NppStatus nppiMeanGetBufferHostSize_32f_C3R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Buffer size for [nppiMean_32f_C3R](#).
- [NppStatus nppiMeanGetBufferHostSize_8u_AC4R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)

Buffer size for nppiMean_8u_AC4R.

- `NppStatus nppiMeanGetBufferHostSize_16u_AC4R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_16u_AC4R.
- `NppStatus nppiMeanGetBufferHostSize_16s_AC4R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_16s_AC4R.
- `NppStatus nppiMeanGetBufferHostSize_32f_AC4R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_32f_AC4R.
- `NppStatus nppiMeanGetBufferHostSize_8u_C4R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_8u_C4R.
- `NppStatus nppiMeanGetBufferHostSize_16u_C4R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_16u_C4R.
- `NppStatus nppiMeanGetBufferHostSize_16s_C4R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_16s_C4R.
- `NppStatus nppiMeanGetBufferHostSize_32f_C4R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_32f_C4R.
- `NppStatus nppiMeanGetBufferHostSize_8u_C1MR` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_8u_C1MR.
- `NppStatus nppiMeanGetBufferHostSize_8s_C1MR` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_8s_C1MR.
- `NppStatus nppiMeanGetBufferHostSize_16u_C1MR` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_16u_C1MR.
- `NppStatus nppiMeanGetBufferHostSize_32f_C1MR` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_32f_C1MR.
- `NppStatus nppiMeanGetBufferHostSize_8u_C3CMR` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_8u_C3CMR.
- `NppStatus nppiMeanGetBufferHostSize_8s_C3CMR` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_8s_C3CMR.
- `NppStatus nppiMeanGetBufferHostSize_16u_C3CMR` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_16u_C3CMR.
- `NppStatus nppiMeanGetBufferHostSize_32f_C3CMR` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_32f_C3CMR.

7.95.1 Detailed Description

Primitives for computing the arithmetic mean of all the pixel values in an image.

7.95.2 Function Documentation

7.95.2.1 `NppStatus nppiMean_16s_AC4R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f aMean[3])`

Four-channel 16-bit signed image Mean ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanGetBufferHostSize_16s_AC4R](#) to determine the minium number of bytes required.

aMean Array that contains the computed mean results.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.95.2.2 `NppStatus nppiMean_16s_C1R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f * pMean)`

One-channel 16-bit signed image Mean.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanGetBufferHostSize_16s_C1R](#) to determine the minium number of bytes required.

pMean Pointer to the computed mean result.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.95.2.3 `NppStatus nppiMean_16s_C3R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f aMean[3])`

Three-channel 16-bit signed image Mean.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanGetBufferHostSize_16s_C3R](#) to determine the minium number of bytes required.

aMean Array that contains the computed mean results.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.95.2.4 NppStatus nppiMean_16s_C4R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f aMean[4])

Four-channel 16-bit signed image Mean.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanGetBufferHostSize_16s_C4R](#) to determine the minium number of bytes required.

aMean Array that contains the computed mean results.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.95.2.5 NppStatus nppiMean_16u_AC4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f aMean[3])

Four-channel 16-bit unsigned image Mean ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanGetBufferHostSize_16u_AC4R](#) to determine the minium number of bytes required.

aMean Array that contains the computed mean results.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.95.2.6 NppStatus nppiMean_16u_C1MR (const Npp16u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f * pMean)

Masked one-channel 16-bit unsigned image Mean.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep Source-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
oSizeROI Region-of-Interest (ROI).
pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanGetBufferHostSize_16u_C1MR](#) to determine the minium number of bytes required.
pMean Pointer to the computed mean result.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.95.2.7 NppStatus nppiMean_16u_C1R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f * pMean)

One-channel 16-bit unsigned image Mean.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).
pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanGetBufferHostSize_16u_C1R](#) to determine the minium number of bytes required.
pMean Pointer to the computed mean result.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.95.2.8 NppStatus nppiMean_16u_C3CMR (const Npp16u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp8u * pDeviceBuffer, Npp64f * pMean)

Masked three-channel 16-bit unsigned image Mean affecting only single channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nCOI Channel_of_Interest Number.
pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanGetBufferHostSize_16u_C3CMR](#) to determine the minium number of bytes required.
pMean Pointer to the computed mean result.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or [NPP_COI_ERROR](#) if an invalid channel of interest is specified.

7.95.2.9 NppStatus nppiMean_16u_C3R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f aMean[3])

Three-channel 16-bit unsigned image Mean.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanGetBufferHostSize_16u_C3R](#) to determine the minium number of bytes required.

aMean Array that contains the computed mean results.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.95.2.10 NppStatus nppiMean_16u_C4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f aMean[4])

Four-channel 16-bit unsigned image Mean.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanGetBufferHostSize_16u_C4R](#) to determine the minium number of bytes required.

aMean Array that contains the computed mean results.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.95.2.11 NppStatus nppiMean_32f_AC4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f aMean[3])

Four-channel 32-bit floating point image Mean ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanGetBufferHostSize_32f_AC4R](#) to determine the minium number of bytes required.

aMean Array that contains the computed mean results.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified.

7.95.2.12 `NppStatus nppiMean_32f_C1MR (const Npp32f * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f * pMean)`

Masked one-channel 32-bit floating point image Mean.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanGetBufferHostSize_32f_C1MR](#) to determine the minimum number of bytes required.

pMean Pointer to the computed mean result.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified.

7.95.2.13 `NppStatus nppiMean_32f_C1R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f * pMean)`

One-channel 32-bit floating point image Mean.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanGetBufferHostSize_32f_C1R](#) to determine the minimum number of bytes required.

pMean Pointer to the computed mean result.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified.

7.95.2.14 `NppStatus nppiMean_32f_C3CMR (const Npp32f * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp8u * pDeviceBuffer, Npp64f * pMean)`

Masked three-channel 32-bit floating point image Mean affecting only single channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanGetBufferHostSize_32f_C3CMR](#) to determine the minium number of bytes required.

pMean Pointer to the computed mean result.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [NPP_NOT_EVEN_STEP_ERROR](#) if an invalid floating-point image is specified, or [NPP_COI_ERROR](#) if an invalid channel of interest is specified.

7.95.2.15 `NppStatus nppiMean_32f_C3R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f aMean[3])`

Three-channel 32-bit floating point image Mean.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanGetBufferHostSize_32f_C3R](#) to determine the minium number of bytes required.

aMean Array that contains the computed mean results.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [NPP_NOT_EVEN_STEP_ERROR](#) if an invalid floating-point image is specified.

7.95.2.16 `NppStatus nppiMean_32f_C4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f aMean[4])`

Four-channel 32-bit floating point image Mean.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanGetBufferHostSize_32f_C4R](#) to determine the minium number of bytes required.

aMean Array that contains the computed mean results.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), NPP_NOT_EVEN_STEP_ERROR if an invalid floating-point image is specified.

7.95.2.17 `NppStatus nppiMean_8s_C1MR (const Npp8s * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f * pMean)`

Masked one-channel 8-bit signed image Mean.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanGetBufferHostSize_8s_C1MR](#) to determine the minium number of bytes required.

pMean Pointer to the computed mean result.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.95.2.18 `NppStatus nppiMean_8s_C3CMR (const Npp8s * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp8u * pDeviceBuffer, Npp64f * pMean)`

Masked three-channel 8-bit signed image Mean affecting only single channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanGetBufferHostSize_8s_C3CMR](#) to determine the minimum number of bytes required.

pMean Pointer to the computed mean result.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or NPP_COI_ERROR if an invalid channel of interest is specified.

7.95.2.19 NppStatus nppiMean_8u_AC4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f aMean[3])

Four-channel 8-bit unsigned image Mean ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanGetBufferHostSize_8u_AC4R](#) to determine the minimum number of bytes required.

aMean Array that contains the computed mean results.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.95.2.20 NppStatus nppiMean_8u_C1MR (const Npp8u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f * pMean)

Masked one-channel 8-bit unsigned image Mean.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanGetBufferHostSize_8u_C1MR](#) to determine the minimum number of bytes required.

pMean Pointer to the computed mean result.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.95.2.21 `NppStatus nppiMean_8u_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f * pMean)`

One-channel 8-bit unsigned image Mean.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanGetBufferHostSize_8u_C1R](#) to determine the minium number of bytes required.

pMean Pointer to the computed mean result.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.95.2.22 `NppStatus nppiMean_8u_C3CMR (const Npp8u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp8u * pDeviceBuffer, Npp64f * pMean)`

Masked three-channel 8-bit unsigned image Mean affecting only single channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanGetBufferHostSize_8u_C3CMR](#) to determine the minium number of bytes required.

pMean Pointer to the computed mean result.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.95.2.23 `NppStatus nppiMean_8u_C3R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f aMean[3])`

Three-channel 8-bit unsigned image Mean.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanGetBufferHostSize_8u_C3R](#) to determine the minium number of bytes required.

aMean Array that contains the computed mean results.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.95.2.24 `NppStatus nppiMean_8u_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f aMean[4])`

Four-channel 8-bit unsigned image Mean.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanGetBufferHostSize_8u_C4R](#) to determine the minium number of bytes required.

aMean Array that contains the computed mean results.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.95.2.25 `NppStatus nppiMeanGetBufferHostSize_16s_AC4R (NppiSize oSizeROI, int * hpBufferSize)`

Buffer size for [nppiMean_16s_AC4R](#).

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.95.2.26 `NppStatus nppiMeanGetBufferHostSize_16s_C1R (NppiSize oSizeROI, int * hpBufferSize)`

Buffer size for [nppiMean_16s_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.95.2.27 NppStatus nppiMeanGetBufferHostSize_16s_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_16s_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.95.2.28 NppStatus nppiMeanGetBufferHostSize_16s_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_16s_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.95.2.29 NppStatus nppiMeanGetBufferHostSize_16u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_16u_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.95.2.30 NppStatus nppiMeanGetBufferHostSize_16u_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_16u_C1MR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.95.2.31 NppStatus nppiMeanGetBufferHostSize_16u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_16u_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.95.2.32 NppStatus nppiMeanGetBufferHostSize_16u_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_16u_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.95.2.33 NppStatus nppiMeanGetBufferHostSize_16u_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_16u_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.95.2.34 NppStatus nppiMeanGetBufferHostSize_16u_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_16u_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.95.2.35 NppStatus nppiMeanGetBufferHostSize_32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_32f_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.95.2.36 NppStatus nppiMeanGetBufferHostSize_32f_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_32f_C1MR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.95.2.37 NppStatus nppiMeanGetBufferHostSize_32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_32f_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.95.2.38 NppStatus nppiMeanGetBufferHostSize_32f_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_32f_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.95.2.39 NppStatus nppiMeanGetBufferHostSize_32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_32f_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.95.2.40 NppStatus nppiMeanGetBufferHostSize_32f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_32f_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.95.2.41 NppStatus nppiMeanGetBufferHostSize_8s_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_8s_C1MR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.95.2.42 NppStatus nppiMeanGetBufferHostSize_8s_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_8s_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.95.2.43 NppStatus nppiMeanGetBufferHostSize_8u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_8u_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.95.2.44 NppStatus nppiMeanGetBufferHostSize_8u_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_8u_C1MR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.95.2.45 NppStatus nppiMeanGetBufferHostSize_8u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_8u_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.95.2.46 NppStatus nppiMeanGetBufferHostSize_8u_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_8u_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.95.2.47 NppStatus nppiMeanGetBufferHostSize_8u_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_8u_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.95.2.48 NppStatus nppiMeanGetBufferHostSize_8u_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_8u_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.96 Mean_StdDev

Primitives for computing both the arithmetic mean and the standard deviation of an image.

Mean_StdDev

Given an image $pSrc$ with width W and height H , the mean and the standard deviation will be computed as

$$Mean = \frac{1}{W \cdot H} \sum_{j=0}^{H-1} \sum_{i=0}^{W-1} pSrc(j, i)$$

$$StdDev = \sqrt{\frac{1}{W \cdot H} \sum_{j=0}^{H-1} \sum_{i=0}^{W-1} (pSrc(j, i) - Mean)^2}$$

The Mean_StdDev primitives require additional scratch buffer for computations.

- `NppStatus nppiMean_StdDev_8u_C1R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` *pMean, `Npp64f` *pStdDev)
One-channel 8-bit unsigned image Mean_StdDev.
- `NppStatus nppiMean_StdDev_8s_C1R` (const `Npp8s` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` *pMean, `Npp64f` *pStdDev)
One-channel 8-bit signed image Mean_StdDev.
- `NppStatus nppiMean_StdDev_16u_C1R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` *pMean, `Npp64f` *pStdDev)
One-channel 16-bit unsigned image Mean_StdDev.
- `NppStatus nppiMean_StdDev_32f_C1R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` *pMean, `Npp64f` *pStdDev)
One-channel 32-bit floating point image Mean_StdDev.

Masked Mean_StdDev

See [Masked Operation](#).

- `NppStatus nppiMean_StdDev_8u_C1MR` (const `Npp8u` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` *pMean, `Npp64f` *pStdDev)
Masked one-channel 8-bit unsigned image Mean_StdDev.
- `NppStatus nppiMean_StdDev_8s_C1MR` (const `Npp8s` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` *pMean, `Npp64f` *pStdDev)
Masked one-channel 8-bit signed image Mean_StdDev.
- `NppStatus nppiMean_StdDev_16u_C1MR` (const `Npp16u` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, `Npp8u` *pDeviceBuffer, `Npp64f` *pMean, `Npp64f` *pStdDev)
Masked one-channel 16-bit unsigned image Mean_StdDev.

- `NppStatus nppiMean_StdDev_32f_C1MR` (const `Npp32f *pSrc`, int `nSrcStep`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, `Npp8u *pDeviceBuffer`, `Npp64f *pMean`, `Npp64f *pStdDev`)
Masked one-channel 32-bit floating point image Mean_StdDev.

Channel Mean_StdDev

See [Channel-of-Interest API](#).

- `NppStatus nppiMean_StdDev_8u_C3CR` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, int `nCOI`, `Npp8u *pDeviceBuffer`, `Npp64f *pMean`, `Npp64f *pStdDev`)
Three-channel 8-bit unsigned image Mean_StdDev affecting only single channel.
- `NppStatus nppiMean_StdDev_8s_C3CR` (const `Npp8s *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, int `nCOI`, `Npp8u *pDeviceBuffer`, `Npp64f *pMean`, `Npp64f *pStdDev`)
Three-channel 8-bit signed image Mean_StdDev affecting only single channel.
- `NppStatus nppiMean_StdDev_16u_C3CR` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, int `nCOI`, `Npp8u *pDeviceBuffer`, `Npp64f *pMean`, `Npp64f *pStdDev`)
Three-channel 16-bit unsigned image Mean_StdDev affecting only single channel.
- `NppStatus nppiMean_StdDev_32f_C3CR` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, int `nCOI`, `Npp8u *pDeviceBuffer`, `Npp64f *pMean`, `Npp64f *pStdDev`)
Three-channel 32-bit floating point image Mean_StdDev affecting only single channel.

Masked Channel Mean_StdDev

See [Masked Operation](#) and [Channel-of-Interest API](#).

- `NppStatus nppiMean_StdDev_8u_C3CMR` (const `Npp8u *pSrc`, int `nSrcStep`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, int `nCOI`, `Npp8u *pDeviceBuffer`, `Npp64f *pMean`, `Npp64f *pStdDev`)
Masked three-channel 8-bit unsigned image Mean_StdDev.
- `NppStatus nppiMean_StdDev_8s_C3CMR` (const `Npp8s *pSrc`, int `nSrcStep`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, int `nCOI`, `Npp8u *pDeviceBuffer`, `Npp64f *pMean`, `Npp64f *pStdDev`)
Masked three-channel 8-bit signed image Mean_StdDev.
- `NppStatus nppiMean_StdDev_16u_C3CMR` (const `Npp16u *pSrc`, int `nSrcStep`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, int `nCOI`, `Npp8u *pDeviceBuffer`, `Npp64f *pMean`, `Npp64f *pStdDev`)
Masked three-channel 16-bit unsigned image Mean_StdDev.
- `NppStatus nppiMean_StdDev_32f_C3CMR` (const `Npp32f *pSrc`, int `nSrcStep`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, int `nCOI`, `Npp8u *pDeviceBuffer`, `Npp64f *pMean`, `Npp64f *pStdDev`)
Masked three-channel 32-bit floating point image Mean_StdDev.

MeanStdDevGetBufferHostSize

Companion primitives for computing the device buffer size (in bytes) required by the Mean_StdDev primitives.

- [NppStatus nppiMeanStdDevGetBufferHostSize_8u_C1R](#) (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_StdDev_8u_C1R.
- [NppStatus nppiMeanStdDevGetBufferHostSize_8s_C1R](#) (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_StdDev_8s_C1R.
- [NppStatus nppiMeanStdDevGetBufferHostSize_16u_C1R](#) (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_StdDev_16u_C1R.
- [NppStatus nppiMeanStdDevGetBufferHostSize_32f_C1R](#) (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_StdDev_32f_C1R.
- [NppStatus nppiMeanStdDevGetBufferHostSize_8u_C1MR](#) (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_StdDev_8u_C1MR.
- [NppStatus nppiMeanStdDevGetBufferHostSize_8s_C1MR](#) (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_StdDev_8s_C1MR.
- [NppStatus nppiMeanStdDevGetBufferHostSize_16u_C1MR](#) (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_StdDev_16u_C1MR.
- [NppStatus nppiMeanStdDevGetBufferHostSize_32f_C1MR](#) (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_StdDev_32f_C1MR.
- [NppStatus nppiMeanStdDevGetBufferHostSize_8u_C3CR](#) (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_StdDev_8u_C3CR.
- [NppStatus nppiMeanStdDevGetBufferHostSize_8s_C3CR](#) (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_StdDev_8s_C3CR.
- [NppStatus nppiMeanStdDevGetBufferHostSize_16u_C3CR](#) (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_StdDev_16u_C3CR.
- [NppStatus nppiMeanStdDevGetBufferHostSize_32f_C3CR](#) (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiMean_StdDev_32f_C3CR.

- **NppStatus** `nppiMeanStdDevGetBufferHostSize_8u_C3CMR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Buffer size for `nppiMean_StdDev_8u_C3CMR`.
- **NppStatus** `nppiMeanStdDevGetBufferHostSize_8s_C3CMR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Buffer size for `nppiMean_StdDev_8s_C3CMR`.
- **NppStatus** `nppiMeanStdDevGetBufferHostSize_16u_C3CMR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Buffer size for `nppiMean_StdDev_16u_C3CMR`.
- **NppStatus** `nppiMeanStdDevGetBufferHostSize_32f_C3CMR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Buffer size for `nppiMean_StdDev_32f_C3CMR`.

7.96.1 Detailed Description

Primitives for computing both the arithmetic mean and the standard deviation of an image.

7.96.2 Function Documentation

7.96.2.1 **NppStatus** `nppiMean_StdDev_16u_C1MR` (**const** **Npp16u** `*pSrc`, **int** `nSrcStep`, **const** **Npp8u** `*pMask`, **int** `nMaskStep`, **NppiSize** `oSizeROI`, **Npp8u** `*pDeviceBuffer`, **Npp64f** `*pMean`, **Npp64f** `*pStdDev`)

Masked one-channel 16-bit unsigned image Mean_StdDev.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#)
 Use `nppiMeanStdDevGetBufferHostSize_16u_C1MR` to determine the minimum number of bytes required.

pMean Pointer to the computed mean.

pStdDev Pointer to the computed standard deviation.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.96.2.2 NppStatus nppiMean_StdDev_16u_C1R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f * pMean, Npp64f * pStdDev)

One-channel 16-bit unsigned image Mean_StdDev.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanStdDevGetBufferHostSize_16u_C1R](#) to determine the minium number of bytes required.

pMean Pointer to the computed mean.

pStdDev Pointer to the computed standard deviation.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.96.2.3 NppStatus nppiMean_StdDev_16u_C3CMR (const Npp16u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp8u * pDeviceBuffer, Npp64f * pMean, Npp64f * pStdDev)

Masked three-channel 16-bit unsigned image Mean_StdDev.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanStdDevGetBufferHostSize_16u_C3CMR](#) to determine the minium number of bytes required.

pMean Pointer to the computed mean.

pStdDev Pointer to the computed standard deviation.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.96.2.4 NppStatus nppiMean_StdDev_16u_C3CR (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, int nCOI, Npp8u * pDeviceBuffer, Npp64f * pMean, Npp64f * pStdDev)

Three-channel 16-bit unsigned image Mean_StdDev affecting only single channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#)
Use [nppiMeanStdDevGetBufferHostSize_16u_C3CR](#) to determine the minium number of bytes required.

pMean Pointer to the computed mean.

pStdDev Pointer to the computed standard deviation.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.96.2.5 NppStatus nppiMean_StdDev_32f_C1MR (const Npp32f * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f * pMean, Npp64f * pStdDev)

Masked one-channel 32-bit floating point image Mean_StdDev.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#)
Use [nppiMeanStdDevGetBufferHostSize_32f_C1MR](#) to determine the minium number of bytes required.

pMean Pointer to the computed mean.

pStdDev Pointer to the computed standard deviation.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified.

7.96.2.6 NppStatus nppiMean_StdDev_32f_C1R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f * pMean, Npp64f * pStdDev)

One-channel 32-bit floating point image Mean_StdDev.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanStdDevGetBufferHostSize_32f_C1R](#) to determine the minimum number of bytes required.

pMean Pointer to the computed mean.

pStdDev Pointer to the computed standard deviation.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified.

7.96.2.7 NppStatus nppiMean_StdDev_32f_C3CMR (const Npp32f * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp8u * pDeviceBuffer, Npp64f * pMean, Npp64f * pStdDev)

Masked three-channel 32-bit floating point image Mean_StdDev.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#) Use [nppiMeanStdDevGetBufferHostSize_32f_C3CMR](#) to determine the minimum number of bytes required.

pMean Pointer to the computed mean.

pStdDev Pointer to the computed standard deviation.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified, or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.96.2.8 NppStatus nppiMean_StdDev_32f_C3CR (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, int nCOI, Npp8u * pDeviceBuffer, Npp64f * pMean, Npp64f * pStdDev)

Three-channel 32-bit floating point image Mean_StdDev affecting only single channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#)
Use [nppiMeanStdDevGetBufferHostSize_32f_C3CR](#) to determine the minium number of bytes required.

pMean Pointer to the computed mean.

pStdDev Pointer to the computed standard deviation.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), NPP_NOT_EVEN_STEP_ERROR if an invalid floating-point image is specified, or NPP_COI_ERROR if an invalid channel of interest is specified.

7.96.2.9 NppStatus nppiMean_StdDev_8s_C1MR (const Npp8s * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f * pMean, Npp64f * pStdDev)

Masked one-channel 8-bit signed image Mean_StdDev.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#)
Use [nppiMeanStdDevGetBufferHostSize_8s_C1MR](#) to determine the minium number of bytes required.

pMean Pointer to the computed mean.

pStdDev Pointer to the computed standard deviation.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.96.2.10 `NppStatus nppiMean_StdDev_8s_C1R (const Npp8s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f * pMean, Npp64f * pStdDev)`

One-channel 8-bit signed image Mean_StdDev.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#)
Use [nppiMeanStdDevGetBufferHostSize_8s_C1R](#) to determine the minium number of bytes required.

pMean Pointer to the computed mean.

pStdDev Pointer to the computed standard deviation.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.96.2.11 `NppStatus nppiMean_StdDev_8s_C3CMR (const Npp8s * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp8u * pDeviceBuffer, Npp64f * pMean, Npp64f * pStdDev)`

Masked three-channel 8-bit signed image Mean_StdDev.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#)
Use [nppiMeanStdDevGetBufferHostSize_8s_C3CMR](#) to determine the minium number of bytes required.

pMean Pointer to the computed mean.

pStdDev Pointer to the computed standard deviation.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.96.2.12 `NppStatus nppiMean_StdDev_8s_C3CR (const Npp8s * pSrc, int nSrcStep, NppiSize oSizeROI, int nCOI, Npp8u * pDeviceBuffer, Npp64f * pMean, Npp64f * pStdDev)`

Three-channel 8-bit signed image Mean_StdDev affecting only single channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#)
Use [nppiMeanStdDevGetBufferHostSize_8s_C3CR](#) to determine the minium number of bytes required.

pMean Pointer to the computed mean.

pStdDev Pointer to the computed standard deviation.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.96.2.13 `NppStatus nppiMean_StdDev_8u_C1MR (const Npp8u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f * pMean, Npp64f * pStdDev)`

Masked one-channel 8-bit unsigned image Mean_StdDev.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#)
Use [nppiMeanStdDevGetBufferHostSize_8u_C1MR](#) to determine the minium number of bytes required.

pMean Pointer to the computed mean.

pStdDev Pointer to the computed standard deviation.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.96.2.14 `NppStatus nppiMean_StdDev_8u_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f * pMean, Npp64f * pStdDev)`

One-channel 8-bit unsigned image Mean_StdDev.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#)
Use [nppiMeanStdDevGetBufferHostSize_8u_C1R](#) to determine the minium number of bytes required.

pMean Pointer to the computed mean.

pStdDev Pointer to the computed standard deviation.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.96.2.15 `NppStatus nppiMean_StdDev_8u_C3CMR (const Npp8u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp8u * pDeviceBuffer, Npp64f * pMean, Npp64f * pStdDev)`

Masked three-channel 8-bit unsigned image Mean_StdDev.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#)
Use [nppiMeanStdDevGetBufferHostSize_8u_C3CMR](#) to determine the minium number of bytes required.

pMean Pointer to the computed mean.

pStdDev Pointer to the computed standard deviation.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.96.2.16 `NppStatus nppiMean_StdDev_8u_C3CR (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, int nCOI, Npp8u * pDeviceBuffer, Npp64f * pMean, Npp64f * pStdDev)`

Three-channel 8-bit unsigned image Mean_StdDev affecting only single channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#)
Use `nppiMeanStdDevGetBufferHostSize_8u_C3CR` to determine the minium number of bytes required.

pMean Pointer to the computed mean.

pStdDev Pointer to the computed standard deviation.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.96.2.17 `NppStatus nppiMeanStdDevGetBufferHostSize_16u_C1MR (NppiSize oSizeROI, int * hpBufferSize)`

Buffer size for `nppiMean_StdDev_16u_C1MR`.

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.96.2.18 `NppStatus nppiMeanStdDevGetBufferHostSize_16u_C1R (NppiSize oSizeROI, int * hpBufferSize)`

Buffer size for `nppiMean_StdDev_16u_C1R`.

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.96.2.19 NppStatus nppiMeanStdDevGetBufferHostSize_16u_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_StdDev_16u_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.96.2.20 NppStatus nppiMeanStdDevGetBufferHostSize_16u_C3CR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_StdDev_16u_C3CR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.96.2.21 NppStatus nppiMeanStdDevGetBufferHostSize_32f_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_StdDev_32f_C1MR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.96.2.22 NppStatus nppiMeanStdDevGetBufferHostSize_32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_StdDev_32f_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.96.2.23 NppStatus nppiMeanStdDevGetBufferHostSize_32f_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_StdDev_32f_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.96.2.24 NppStatus nppiMeanStdDevGetBufferHostSize_32f_C3CR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_StdDev_32f_C3CR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.96.2.25 NppStatus nppiMeanStdDevGetBufferHostSize_8s_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_StdDev_8s_C1MR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.96.2.26 NppStatus nppiMeanStdDevGetBufferHostSize_8s_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_StdDev_8s_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.96.2.27 NppStatus nppiMeanStdDevGetBufferHostSize_8s_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_StdDev_8s_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.96.2.28 NppStatus nppiMeanStdDevGetBufferHostSize_8s_C3CR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_StdDev_8s_C3CR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.96.2.29 NppStatus nppiMeanStdDevGetBufferHostSize_8u_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_StdDev_8u_C1MR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.96.2.30 NppStatus nppiMeanStdDevGetBufferHostSize_8u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_StdDev_8u_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.96.2.31 NppStatus nppiMeanStdDevGetBufferHostSize_8u_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_StdDev_8u_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.96.2.32 NppStatus nppiMeanStdDevGetBufferHostSize_8u_C3CR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiMean_StdDev_8u_C3CR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.97 Image Norms

Primitives for computing the norms of an image, the norms of difference, and the relative errors of two images.

Modules

- [Norm_Inf](#)
Primitives for computing the infinity norm of an image.
- [Norm_L1](#)
Primitives for computing the L1 norm of an image.
- [Norm_L2](#)
Primitives for computing the L2 norm of an image.
- [NormDiff_Inf](#)
Primitives for computing the infinity norm of difference of pixels between two images.
- [NormDiff_L1](#)
Primitives for computing the L1 norm of difference of pixels between two images.
- [NormDiff_L2](#)
Primitives for computing the L2 norm of difference of pixels between two images.
- [NormRel_Inf](#)
Primitives for computing the relative error of infinity norm between two images.
- [NormRel_L1](#)
Primitives for computing the relative error of L1 norm between two images.
- [NormRel_L2](#)
Primitives for computing the relative error of L2 norm between two images.

7.97.1 Detailed Description

Primitives for computing the norms of an image, the norms of difference, and the relative errors of two images.

Given an image $pSrc$ with width W and height H ,

1. The infinity norm (`Norm_Inf`) is defined as the largest absolute pixel value of the image.
2. The L1 norm (`Norm_L1`) is defined as the sum of the absolute pixel value of the image, i.e.,

$$Norm_L1 = \sum_{j=0}^{H-1} \sum_{i=0}^{W-1} |pSrc(j, i)|$$

3. The L2 norm (Norm_L2) is defined as the square root of the sum of the squared absolute pixel value of the image, i.e.,

$$Norm_L2 = \sqrt{\sum_{j=0}^{H-1} \sum_{i=0}^{W-1} |pSrc(j, i)|^2}$$

Given two images $pSrc1$ and $pSrc2$ both with width W and height H ,

1. The infinity norm of difference (NormDiff_Inf) is defined as the largest absolute difference between pixels of two images.
2. The L1 norm of difference (NormDiff_L1) is defined as the sum of the absolute difference between pixels of two images, i.e.,

$$NormDiff_L1 = \sum_{j=0}^{H-1} \sum_{i=0}^{W-1} |pSrc1(j, i) - pSrc2(j, i)|$$

3. The L2 norm of difference (NormDiff_L2) is defined as the squared root of the sum of the squared absolute difference between pixels of two images, i.e.,

$$NormDiff_L2 = \sqrt{\sum_{j=0}^{H-1} \sum_{i=0}^{W-1} |pSrc1(j, i) - pSrc2(j, i)|^2}$$

Given two images $pSrc1$ and $pSrc2$ both with width W and height H ,

1. The relative error for the infinity norm of difference (NormRel_Inf) is defined as NormDiff_Inf divided by the infinity norm of the second image, i.e.,

$$NormRel_Inf = \frac{NormDiff_Inf}{Norm_Inf_{src2}}$$

2. The relative error for the L1 norm of difference (NormRel_L1) is defined as NormDiff_L1 divided by the L1 norm of the second image, i.e.,

$$NormRel_L1 = \frac{NormDiff_L1}{Norm_L1_{src2}}$$

3. The relative error for the L2 norm of difference (NormRel_L2) is defined as NormDiff_L2 divided by the L2 norm of the second image, i.e.,

$$NormRel_L2 = \frac{NormDiff_L2}{Norm_L2_{src2}}$$

The norm functions require the addition device scratch buffer for the computations.

7.98 Norm_Inf

Primitives for computing the infinity norm of an image.

Basic Norm_Inf

- **NppStatus nppiNorm_Inf_8u_C1R** (const **Npp8u** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp64f** *pNorm, **Npp8u** *pDeviceBuffer)
One-channel 8-bit unsigned image Norm_Inf.
- **NppStatus nppiNorm_Inf_16u_C1R** (const **Npp16u** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp64f** *pNorm, **Npp8u** *pDeviceBuffer)
One-channel 16-bit unsigned image Norm_Inf.
- **NppStatus nppiNorm_Inf_16s_C1R** (const **Npp16s** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp64f** *pNorm, **Npp8u** *pDeviceBuffer)
One-channel 16-bit signed image Norm_Inf.
- **NppStatus nppiNorm_Inf_32s_C1R** (const **Npp32s** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp64f** *pNorm, **Npp8u** *pDeviceBuffer)
One-channel 32-bit signed image Norm_Inf.
- **NppStatus nppiNorm_Inf_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp64f** *pNorm, **Npp8u** *pDeviceBuffer)
One-channel 32-bit floating point image Norm_Inf.
- **NppStatus nppiNorm_Inf_8u_C3R** (const **Npp8u** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp64f** aNorm[3], **Npp8u** *pDeviceBuffer)
Three-channel 8-bit unsigned image Norm_Inf.
- **NppStatus nppiNorm_Inf_16u_C3R** (const **Npp16u** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp64f** aNorm[3], **Npp8u** *pDeviceBuffer)
Three-channel 16-bit unsigned image Norm_Inf.
- **NppStatus nppiNorm_Inf_16s_C3R** (const **Npp16s** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp64f** aNorm[3], **Npp8u** *pDeviceBuffer)
Three-channel 16-bit signed image Norm_Inf.
- **NppStatus nppiNorm_Inf_32f_C3R** (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp64f** aNorm[3], **Npp8u** *pDeviceBuffer)
Three-channel 32-bit floating point image Norm_Inf.
- **NppStatus nppiNorm_Inf_8u_AC4R** (const **Npp8u** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp64f** aNorm[3], **Npp8u** *pDeviceBuffer)
Four-channel 8-bit unsigned image Norm_Inf ignoring alpha channel.
- **NppStatus nppiNorm_Inf_16u_AC4R** (const **Npp16u** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp64f** aNorm[3], **Npp8u** *pDeviceBuffer)
Four-channel 16-bit unsigned image Norm_Inf ignoring alpha channel.

- `NppStatus nppiNorm_Inf_16s_AC4R` (const `Npp16s` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp64f` aNorm[3], `Npp8u` *pDeviceBuffer)
Four-channel 16-bit signed image Norm_Inf ignoring alpha channel.
- `NppStatus nppiNorm_Inf_32f_AC4R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp64f` aNorm[3], `Npp8u` *pDeviceBuffer)
Four-channel 32-bit floating point image Norm_Inf ignoring alpha channel.
- `NppStatus nppiNorm_Inf_8u_C4R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp64f` aNorm[4], `Npp8u` *pDeviceBuffer)
Four-channel 8-bit unsigned image Norm_Inf.
- `NppStatus nppiNorm_Inf_16u_C4R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp64f` aNorm[4], `Npp8u` *pDeviceBuffer)
Four-channel 16-bit unsigned image Norm_Inf.
- `NppStatus nppiNorm_Inf_16s_C4R` (const `Npp16s` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp64f` aNorm[4], `Npp8u` *pDeviceBuffer)
Four-channel 16-bit signed image Norm_Inf.
- `NppStatus nppiNorm_Inf_32f_C4R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSizeROI, `Npp64f` aNorm[4], `Npp8u` *pDeviceBuffer)
Four-channel 32-bit floating point image Norm_Inf.

Masked Norm_Inf

See [Masked Operation](#).

- `NppStatus nppiNorm_Inf_8u_C1MR` (const `Npp8u` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, `Npp64f` *pNorm, `Npp8u` *pDeviceBuffer)
Masked one-channel 8-bit unsigned image Norm_Inf.
- `NppStatus nppiNorm_Inf_8s_C1MR` (const `Npp8s` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, `Npp64f` *pNorm, `Npp8u` *pDeviceBuffer)
Masked one-channel 8-bit signed image Norm_Inf.
- `NppStatus nppiNorm_Inf_16u_C1MR` (const `Npp16u` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, `Npp64f` *pNorm, `Npp8u` *pDeviceBuffer)
Masked one-channel 16-bit unsigned image Norm_Inf.
- `NppStatus nppiNorm_Inf_32f_C1MR` (const `Npp32f` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, `Npp64f` *pNorm, `Npp8u` *pDeviceBuffer)
Masked one-channel 32-bit floating point image Norm_Inf.

Masked Channel Norm_Inf

See [Channel-of-Interest API](#) and [Masked Operation](#).

- `NppStatus nppiNorm_Inf_8u_C3CMR` (const `Npp8u` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, int nCOI, `Npp64f` *pNorm, `Npp8u` *pDeviceBuffer)
Masked three-channel 8-bit unsigned image Norm_Inf affecting only single channel.
- `NppStatus nppiNorm_Inf_8s_C3CMR` (const `Npp8s` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, int nCOI, `Npp64f` *pNorm, `Npp8u` *pDeviceBuffer)
Masked three-channel 8-bit signed image Norm_Inf affecting only single channel.
- `NppStatus nppiNorm_Inf_16u_C3CMR` (const `Npp16u` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, int nCOI, `Npp64f` *pNorm, `Npp8u` *pDeviceBuffer)
Masked three-channel 16-bit unsigned image Norm_Inf affecting only single channel.
- `NppStatus nppiNorm_Inf_32f_C3CMR` (const `Npp32f` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, int nCOI, `Npp64f` *pNorm, `Npp8u` *pDeviceBuffer)
Masked three-channel 32-bit floating point image Norm_Inf affecting only single channel.

NormInfGetBufferHostSize

Companion primitives for computing the device buffer size (in bytes) required by the Norm_Inf primitives.

- `NppStatus nppiNormInfGetBufferHostSize_8u_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiNorm_Inf_8u_C1R`.
- `NppStatus nppiNormInfGetBufferHostSize_16u_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiNorm_Inf_16u_C1R`.
- `NppStatus nppiNormInfGetBufferHostSize_16s_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiNorm_Inf_16s_C1R`.
- `NppStatus nppiNormInfGetBufferHostSize_32s_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiNorm_Inf_32s_C1R`.
- `NppStatus nppiNormInfGetBufferHostSize_32f_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiNorm_Inf_32f_C1R`.
- `NppStatus nppiNormInfGetBufferHostSize_8u_C1MR` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiNorm_Inf_8u_C1MR`.
- `NppStatus nppiNormInfGetBufferHostSize_8s_C1MR` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiNorm_Inf_8s_C1MR`.
- `NppStatus nppiNormInfGetBufferHostSize_16u_C1MR` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiNorm_Inf_16u_C1MR`.
- `NppStatus nppiNormInfGetBufferHostSize_32f_C1MR` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiNorm_Inf_32f_C1MR`.
- `NppStatus nppiNormInfGetBufferHostSize_8u_C3R` (`NppiSize` oSizeROI, int *hpBufferSize)

Buffer size for nppiNorm_Inf_8u_C3R.

- **NppStatus nppiNormInfGetBufferHostSize_16u_C3R** (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_Inf_16u_C3R.
- **NppStatus nppiNormInfGetBufferHostSize_16s_C3R** (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_Inf_16s_C3R.
- **NppStatus nppiNormInfGetBufferHostSize_32f_C3R** (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_Inf_32f_C3R.
- **NppStatus nppiNormInfGetBufferHostSize_8u_AC4R** (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_Inf_8u_AC4R.
- **NppStatus nppiNormInfGetBufferHostSize_16u_AC4R** (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_Inf_16u_AC4R.
- **NppStatus nppiNormInfGetBufferHostSize_16s_AC4R** (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_Inf_16s_AC4R.
- **NppStatus nppiNormInfGetBufferHostSize_32f_AC4R** (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_Inf_32f_AC4R.
- **NppStatus nppiNormInfGetBufferHostSize_8u_C4R** (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_Inf_8u_C4R.
- **NppStatus nppiNormInfGetBufferHostSize_16u_C4R** (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_Inf_16u_C4R.
- **NppStatus nppiNormInfGetBufferHostSize_16s_C4R** (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_Inf_16s_C4R.
- **NppStatus nppiNormInfGetBufferHostSize_32f_C4R** (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_Inf_32f_C4R.
- **NppStatus nppiNormInfGetBufferHostSize_8u_C3CMR** (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_Inf_8u_C3CMR.
- **NppStatus nppiNormInfGetBufferHostSize_8s_C3CMR** (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_Inf_8s_C3CMR.
- **NppStatus nppiNormInfGetBufferHostSize_16u_C3CMR** (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_Inf_16u_C3CMR.
- **NppStatus nppiNormInfGetBufferHostSize_32f_C3CMR** (NppiSize oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_Inf_32f_C3CMR.

7.98.1 Detailed Description

Primitives for computing the infinity norm of an image.

7.98.2 Function Documentation

7.98.2.1 `NppStatus nppiNorm_Inf_16s_AC4R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[3], Npp8u * pDeviceBuffer)`

Four-channel 16-bit signed image Norm_Inf ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Three-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormInfGetBufferHostSize_16s_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.98.2.2 `NppStatus nppiNorm_Inf_16s_C1R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

One-channel 16-bit signed image Norm_Inf.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormInfGetBufferHostSize_16s_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.98.2.3 `NppStatus nppiNorm_Inf_16s_C3R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[3], Npp8u * pDeviceBuffer)`

Three-channel 16-bit signed image Norm_Inf.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Three-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormInfGetBufferHostSize_16s_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.98.2.4 NppStatus nppiNorm_Inf_16s_C4R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[4], Npp8u * pDeviceBuffer)

Four-channel 16-bit signed image Norm_Inf.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Four-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormInfGetBufferHostSize_16s_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.98.2.5 NppStatus nppiNorm_Inf_16u_AC4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[3], Npp8u * pDeviceBuffer)

Four-channel 16-bit unsigned image Norm_Inf ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Three-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormInfGetBufferHostSize_16u_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.98.2.6 `NppStatus nppiNorm_Inf_16u_C1MR (const Npp16u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

Masked one-channel 16-bit unsigned image Norm_Inf.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormInfGetBufferHostSize_16u_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.98.2.7 `NppStatus nppiNorm_Inf_16u_C1R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

One-channel 16-bit unsigned image Norm_Inf.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormInfGetBufferHostSize_16u_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.98.2.8 `NppStatus nppiNorm_Inf_16u_C3CMR (const Npp16u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

Masked three-channel 16-bit unsigned image Norm_Inf affecting only single channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormInfGetBufferHostSize_16u_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.98.2.9 NppStatus nppiNorm_Inf_16u_C3R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[3], Npp8u * pDeviceBuffer)

Three-channel 16-bit unsigned image Norm_Inf.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Three-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormInfGetBufferHostSize_16u_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.98.2.10 NppStatus nppiNorm_Inf_16u_C4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[4], Npp8u * pDeviceBuffer)

Four-channel 16-bit unsigned image Norm_Inf.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Four-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormInfGetBufferHostSize_16u_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.98.2.11 `NppStatus nppiNorm_Inf_32f_AC4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[3], Npp8u * pDeviceBuffer)`

Four-channel 32-bit floating point image Norm_Inf ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Three-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormInfGetBufferHostSize_32f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.98.2.12 `NppStatus nppiNorm_Inf_32f_C1MR (const Npp32f * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

Masked one-channel 32-bit floating point image Norm_Inf.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormInfGetBufferHostSize_32f_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.98.2.13 `NppStatus nppiNorm_Inf_32f_C1R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

One-channel 32-bit floating point image Norm_Inf.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormInfGetBufferHostSize_32f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.98.2.14 `NppStatus nppiNorm_Inf_32f_C3CMR (const Npp32f * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

Masked three-channel 32-bit floating point image Norm_Inf affecting only single channel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pMask [Mask-Image Pointer](#).

nMaskStep [Mask-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

nCOI [Channel_of_Interest Number](#).

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormInfGetBufferHostSize_32f_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified, or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.98.2.15 `NppStatus nppiNorm_Inf_32f_C3R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[3], Npp8u * pDeviceBuffer)`

Three-channel 32-bit floating point image Norm_Inf.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aNorm Array that contains the norm values of Three-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormInfGetBufferHostSize_32f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.98.2.16 `NppStatus nppiNorm_Inf_32f_C4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[4], Npp8u * pDeviceBuffer)`

Four-channel 32-bit floating point image Norm_Inf.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Four-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormInfGetBufferHostSize_32f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.98.2.17 `NppStatus nppiNorm_Inf_32s_C1R (const Npp32s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

One-channel 32-bit signed image Norm_Inf.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormInfGetBufferHostSize_32s_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.98.2.18 `NppStatus nppiNorm_Inf_8s_C1MR (const Npp8s * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

Masked one-channel 8-bit signed image Norm_Inf.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormInfGetBufferSize_8s_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.98.2.19 `NppStatus nppiNorm_Inf_8s_C3CMR (const Npp8s * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

Masked three-channel 8-bit signed image Norm_Inf affecting only single channel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pMask [Mask-Image Pointer](#).

nMaskStep [Mask-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

nCOI [Channel_of_Interest Number](#).

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormInfGetBufferSize_8s_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.98.2.20 `NppStatus nppiNorm_Inf_8u_AC4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[3], Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image Norm_Inf ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aNorm Array that contains the norm values of Three-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormInfGetBufferSize_8u_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.98.2.21 `NppStatus nppiNorm_Inf_8u_C1MR (const Npp8u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

Masked one-channel 8-bit unsigned image Norm_Inf.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormInfGetBufferHostSize_8u_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.98.2.22 `NppStatus nppiNorm_Inf_8u_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

One-channel 8-bit unsigned image Norm_Inf.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormInfGetBufferHostSize_8u_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.98.2.23 `NppStatus nppiNorm_Inf_8u_C3CMR (const Npp8u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

Masked three-channel 8-bit unsigned image Norm_Inf affecting only single channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormInfGetBufferHostSize_8u_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.98.2.24 NppStatus nppiNorm_Inf_8u_C3R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[3], Npp8u * pDeviceBuffer)

Three-channel 8-bit unsigned image Norm_Inf.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Three-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormInfGetBufferHostSize_8u_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.98.2.25 NppStatus nppiNorm_Inf_8u_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[4], Npp8u * pDeviceBuffer)

Four-channel 8-bit unsigned image Norm_Inf.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Four-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormInfGetBufferHostSize_8u_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.98.2.26 NppStatus nppiNormInfGetBufferHostSize_16s_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_Inf_16s_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.98.2.27 NppStatus nppiNormInfGetBufferHostSize_16s_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_Inf_16s_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.98.2.28 NppStatus nppiNormInfGetBufferHostSize_16s_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_Inf_16s_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.98.2.29 NppStatus nppiNormInfGetBufferHostSize_16s_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_Inf_16s_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.98.2.30 NppStatus nppiNormInfGetBufferHostSize_16u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_Inf_16u_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.98.2.31 NppStatus nppiNormInfGetBufferHostSize_16u_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_Inf_16u_C1MR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.98.2.32 NppStatus nppiNormInfGetBufferHostSize_16u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_Inf_16u_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.98.2.33 NppStatus nppiNormInfGetBufferHostSize_16u_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_Inf_16u_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.98.2.34 NppStatus nppiNormInfGetBufferHostSize_16u_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_Inf_16u_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.98.2.35 NppStatus nppiNormInfGetBufferHostSize_16u_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_Inf_16u_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.98.2.36 NppStatus nppiNormInfGetBufferHostSize_32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_Inf_32f_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.98.2.37 NppStatus nppiNormInfGetBufferHostSize_32f_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_Inf_32f_C1MR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.98.2.38 NppStatus nppiNormInfGetBufferHostSize_32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_Inf_32f_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.98.2.39 NppStatus nppiNormInfGetBufferHostSize_32f_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_Inf_32f_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.98.2.40 `NppStatus nppiNormInfGetBufferHostSize_32f_C3R` (`NppiSize oSizeROI`, `int * hpBufferSize`)

Buffer size for `nppiNorm_Inf_32f_C3R`.

Parameters:

`oSizeROI` [Region-of-Interest \(ROI\)](#).

`hpBufferSize` Required buffer size. Important: `hpBufferSize` is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if `hpBufferSize` is 0 (NULL), [ROI Related Error Codes](#).

7.98.2.41 `NppStatus nppiNormInfGetBufferHostSize_32f_C4R` (`NppiSize oSizeROI`, `int * hpBufferSize`)

Buffer size for `nppiNorm_Inf_32f_C4R`.

Parameters:

`oSizeROI` [Region-of-Interest \(ROI\)](#).

`hpBufferSize` Required buffer size. Important: `hpBufferSize` is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if `hpBufferSize` is 0 (NULL), [ROI Related Error Codes](#).

7.98.2.42 `NppStatus nppiNormInfGetBufferHostSize_32s_C1R` (`NppiSize oSizeROI`, `int * hpBufferSize`)

Buffer size for `nppiNorm_Inf_32s_C1R`.

Parameters:

`oSizeROI` [Region-of-Interest \(ROI\)](#).

`hpBufferSize` Required buffer size. Important: `hpBufferSize` is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if `hpBufferSize` is 0 (NULL), [ROI Related Error Codes](#).

7.98.2.43 `NppStatus nppiNormInfGetBufferHostSize_8s_C1MR` (`NppiSize oSizeROI`, `int * hpBufferSize`)

Buffer size for `nppiNorm_Inf_8s_C1MR`.

Parameters:

`oSizeROI` [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.98.2.44 NppStatus nppiNormInfGetBufferHostSize_8s_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_Inf_8s_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.98.2.45 NppStatus nppiNormInfGetBufferHostSize_8u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_Inf_8u_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.98.2.46 NppStatus nppiNormInfGetBufferHostSize_8u_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_Inf_8u_C1MR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.98.2.47 `NppStatus nppiNormInfGetBufferHostSize_8u_C1R (NppiSize oSizeROI, int * hpBufferSize)`

Buffer size for `nppiNorm_Inf_8u_C1R`.

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.98.2.48 `NppStatus nppiNormInfGetBufferHostSize_8u_C3CMR (NppiSize oSizeROI, int * hpBufferSize)`

Buffer size for `nppiNorm_Inf_8u_C3CMR`.

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.98.2.49 `NppStatus nppiNormInfGetBufferHostSize_8u_C3R (NppiSize oSizeROI, int * hpBufferSize)`

Buffer size for `nppiNorm_Inf_8u_C3R`.

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.98.2.50 `NppStatus nppiNormInfGetBufferHostSize_8u_C4R (NppiSize oSizeROI, int * hpBufferSize)`

Buffer size for `nppiNorm_Inf_8u_C4R`.

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.99 Norm_L1

Primitives for computing the L1 norm of an image.

Basic Norm_L1

- **NppStatus nppiNorm_L1_8u_C1R** (const **Npp8u** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp64f** *pNorm, **Npp8u** *pDeviceBuffer)
One-channel 8-bit unsigned image Norm_L1.
- **NppStatus nppiNorm_L1_16u_C1R** (const **Npp16u** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp64f** *pNorm, **Npp8u** *pDeviceBuffer)
One-channel 16-bit unsigned image Norm_L1.
- **NppStatus nppiNorm_L1_16s_C1R** (const **Npp16s** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp64f** *pNorm, **Npp8u** *pDeviceBuffer)
One-channel 16-bit signed image Norm_L1.
- **NppStatus nppiNorm_L1_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp64f** *pNorm, **Npp8u** *pDeviceBuffer)
One-channel 32-bit floating point image Norm_L1.
- **NppStatus nppiNorm_L1_8u_C3R** (const **Npp8u** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp64f** aNorm[3], **Npp8u** *pDeviceBuffer)
Three-channel 8-bit unsigned image Norm_L1.
- **NppStatus nppiNorm_L1_16u_C3R** (const **Npp16u** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp64f** aNorm[3], **Npp8u** *pDeviceBuffer)
Three-channel 16-bit unsigned image Norm_L1.
- **NppStatus nppiNorm_L1_16s_C3R** (const **Npp16s** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp64f** aNorm[3], **Npp8u** *pDeviceBuffer)
Three-channel 16-bit signed image Norm_L1.
- **NppStatus nppiNorm_L1_32f_C3R** (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp64f** aNorm[3], **Npp8u** *pDeviceBuffer)
Three-channel 32-bit floating point image Norm_L1.
- **NppStatus nppiNorm_L1_8u_AC4R** (const **Npp8u** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp64f** aNorm[3], **Npp8u** *pDeviceBuffer)
Four-channel 8-bit unsigned image Norm_L1 ignoring alpha channel.
- **NppStatus nppiNorm_L1_16u_AC4R** (const **Npp16u** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp64f** aNorm[3], **Npp8u** *pDeviceBuffer)
Four-channel 16-bit unsigned image Norm_L1 ignoring alpha channel.
- **NppStatus nppiNorm_L1_16s_AC4R** (const **Npp16s** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp64f** aNorm[3], **Npp8u** *pDeviceBuffer)
Four-channel 16-bit signed image Norm_L1 ignoring alpha channel.

- `NppStatus nppiNorm_L1_32f_AC4R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp64f aNorm[3]`, `Npp8u *pDeviceBuffer`)
Four-channel 32-bit floating point image Norm_L1 ignoring alpha channel.
- `NppStatus nppiNorm_L1_8u_C4R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp64f aNorm[4]`, `Npp8u *pDeviceBuffer`)
Four-channel 8-bit unsigned image Norm_L1.
- `NppStatus nppiNorm_L1_16u_C4R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp64f aNorm[4]`, `Npp8u *pDeviceBuffer`)
Four-channel 16-bit unsigned image Norm_L1.
- `NppStatus nppiNorm_L1_16s_C4R` (const `Npp16s *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp64f aNorm[4]`, `Npp8u *pDeviceBuffer`)
Four-channel 16-bit signed image Norm_L1.
- `NppStatus nppiNorm_L1_32f_C4R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp64f aNorm[4]`, `Npp8u *pDeviceBuffer`)
Four-channel 32-bit floating point image Norm_L1.

Masked Norm_L1

See [Masked Operation](#).

- `NppStatus nppiNorm_L1_8u_C1MR` (const `Npp8u *pSrc`, int `nSrcStep`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize oSizeROI`, `Npp64f *pNorm`, `Npp8u *pDeviceBuffer`)
Masked one-channel 8-bit unsigned image Norm_L1.
- `NppStatus nppiNorm_L1_8s_C1MR` (const `Npp8s *pSrc`, int `nSrcStep`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize oSizeROI`, `Npp64f *pNorm`, `Npp8u *pDeviceBuffer`)
Masked one-channel 8-bit signed image Norm_L1.
- `NppStatus nppiNorm_L1_16u_C1MR` (const `Npp16u *pSrc`, int `nSrcStep`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize oSizeROI`, `Npp64f *pNorm`, `Npp8u *pDeviceBuffer`)
Masked one-channel 16-bit unsigned image Norm_L1.
- `NppStatus nppiNorm_L1_32f_C1MR` (const `Npp32f *pSrc`, int `nSrcStep`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize oSizeROI`, `Npp64f *pNorm`, `Npp8u *pDeviceBuffer`)
Masked one-channel 32-bit floating point image Norm_L1.

Masked Channel Norm_L1

See [Channel-of-Interest API](#) and [Masked Operation](#).

- `NppStatus nppiNorm_L1_8u_C3CMR` (const `Npp8u *pSrc`, int `nSrcStep`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize oSizeROI`, int `nCOI`, `Npp64f *pNorm`, `Npp8u *pDeviceBuffer`)
Masked three-channel 8-bit unsigned image Norm_L1 affecting only single channel.

- `NppStatus nppiNorm_L1_8s_C3CMR` (const `Npp8s` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, int nCOI, `Npp64f` *pNorm, `Npp8u` *pDeviceBuffer)
Masked three-channel 8-bit signed image Norm_L1 affecting only single channel.
- `NppStatus nppiNorm_L1_16u_C3CMR` (const `Npp16u` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, int nCOI, `Npp64f` *pNorm, `Npp8u` *pDeviceBuffer)
Masked three-channel 16-bit unsigned image Norm_L1 affecting only single channel.
- `NppStatus nppiNorm_L1_32f_C3CMR` (const `Npp32f` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, int nCOI, `Npp64f` *pNorm, `Npp8u` *pDeviceBuffer)
Masked three-channel 32-bit floating point image Norm_L1 affecting only single channel.

NormL1GetBufferHostSize

Companion primitives for computing the device buffer size (in bytes) required by the Norm_L1 primitives.

- `NppStatus nppiNormL1GetBufferHostSize_8u_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_L1_8u_C1R.
- `NppStatus nppiNormL1GetBufferHostSize_16u_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_L1_16u_C1R.
- `NppStatus nppiNormL1GetBufferHostSize_16s_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_L1_16s_C1R.
- `NppStatus nppiNormL1GetBufferHostSize_32f_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_L1_32f_C1R.
- `NppStatus nppiNormL1GetBufferHostSize_8u_C1MR` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_L1_8u_C1MR.
- `NppStatus nppiNormL1GetBufferHostSize_8s_C1MR` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_L1_8s_C1MR.
- `NppStatus nppiNormL1GetBufferHostSize_16u_C1MR` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_L1_16u_C1MR.
- `NppStatus nppiNormL1GetBufferHostSize_32f_C1MR` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_L1_32f_C1MR.
- `NppStatus nppiNormL1GetBufferHostSize_8u_C3R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_L1_8u_C3R.
- `NppStatus nppiNormL1GetBufferHostSize_16u_C3R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_L1_16u_C3R.
- `NppStatus nppiNormL1GetBufferHostSize_16s_C3R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_L1_16s_C3R.

- `NppStatus nppiNormL1GetBufferHostSize_32f_C3R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L1_32f_C3R`.
- `NppStatus nppiNormL1GetBufferHostSize_8u_AC4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L1_8u_AC4R`.
- `NppStatus nppiNormL1GetBufferHostSize_16u_AC4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L1_16u_AC4R`.
- `NppStatus nppiNormL1GetBufferHostSize_16s_AC4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L1_16s_AC4R`.
- `NppStatus nppiNormL1GetBufferHostSize_32f_AC4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L1_32f_AC4R`.
- `NppStatus nppiNormL1GetBufferHostSize_8u_C4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L1_8u_C4R`.
- `NppStatus nppiNormL1GetBufferHostSize_16u_C4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L1_16u_C4R`.
- `NppStatus nppiNormL1GetBufferHostSize_16s_C4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L1_16s_C4R`.
- `NppStatus nppiNormL1GetBufferHostSize_32f_C4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L1_32f_C4R`.
- `NppStatus nppiNormL1GetBufferHostSize_8u_C3CMR` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L1_8u_C3CMR`.
- `NppStatus nppiNormL1GetBufferHostSize_8s_C3CMR` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L1_8s_C3CMR`.
- `NppStatus nppiNormL1GetBufferHostSize_16u_C3CMR` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L1_16u_C3CMR`.
- `NppStatus nppiNormL1GetBufferHostSize_32f_C3CMR` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L1_32f_C3CMR`.

7.99.1 Detailed Description

Primitives for computing the L1 norm of an image.

7.99.2 Function Documentation

7.99.2.1 `NppStatus nppiNorm_L1_16s_AC4R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[3], Npp8u * pDeviceBuffer)`

Four-channel 16-bit signed image Norm_L1 ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Three-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).

Use [nppiNormL1GetBufferHostSize_16s_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.99.2.2 `NppStatus nppiNorm_L1_16s_C1R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

One-channel 16-bit signed image Norm_L1.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).

Use [nppiNormL1GetBufferHostSize_16s_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.99.2.3 `NppStatus nppiNorm_L1_16s_C3R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[3], Npp8u * pDeviceBuffer)`

Three-channel 16-bit signed image Norm_L1.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Three-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL1GetBufferHostSize_16s_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.99.2.4 NppStatus nppiNorm_L1_16s_C4R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[4], Npp8u * pDeviceBuffer)

Four-channel 16-bit signed image Norm_L1.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Four-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL1GetBufferHostSize_16s_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.99.2.5 NppStatus nppiNorm_L1_16u_AC4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[3], Npp8u * pDeviceBuffer)

Four-channel 16-bit unsigned image Norm_L1 ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Three-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL1GetBufferHostSize_16u_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.99.2.6 NppStatus nppiNorm_L1_16u_C1MR (const Npp16u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNorm, Npp8u * pDeviceBuffer)

Masked one-channel 16-bit unsigned image Norm_L1.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
oSizeROI Region-of-Interest (ROI).
pNorm Pointer to the norm value.
pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
 Use [nppiNormL1GetBufferHostSize_16u_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.99.2.7 NppStatus nppiNorm_L1_16u_C1R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f * pNorm, Npp8u * pDeviceBuffer)

One-channel 16-bit unsigned image Norm_L1.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).
pNorm Pointer to the norm value.
pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
 Use [nppiNormL1GetBufferHostSize_16u_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.99.2.8 NppStatus nppiNorm_L1_16u_C3CMR (const Npp16u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNorm, Npp8u * pDeviceBuffer)

Masked three-channel 16-bit unsigned image Norm_L1 affecting only single channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nCOI Channel_of_Interest Number.
pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL1GetBufferHostSize_16u_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.99.2.9 NppStatus nppiNorm_L1_16u_C3R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[3], Npp8u * pDeviceBuffer)

Three-channel 16-bit unsigned image Norm_L1.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Three-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL1GetBufferHostSize_16u_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.99.2.10 NppStatus nppiNorm_L1_16u_C4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[4], Npp8u * pDeviceBuffer)

Four-channel 16-bit unsigned image Norm_L1.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Four-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL1GetBufferHostSize_16u_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.99.2.11 NppStatus nppiNorm_L1_32f_AC4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[3], Npp8u * pDeviceBuffer)

Four-channel 32-bit floating point image Norm_L1 ignoring alpha channel.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- aNorm* Array that contains the norm values of Three-channels.
- pDeviceBuffer* Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL1GetBufferHostSize_32f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.99.2.12 NppStatus nppiNorm_L1_32f_C1MR (const Npp32f * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNorm, Npp8u * pDeviceBuffer)

Masked one-channel 32-bit floating point image Norm_L1.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pMask* Mask-Image Pointer.
- nMaskStep* Mask-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- pNorm* Pointer to the norm value.
- pDeviceBuffer* Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL1GetBufferHostSize_32f_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.99.2.13 NppStatus nppiNorm_L1_32f_C1R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f * pNorm, Npp8u * pDeviceBuffer)

One-channel 32-bit floating point image Norm_L1.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- pNorm* Pointer to the norm value.
- pDeviceBuffer* Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL1GetBufferHostSize_32f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.99.2.14 `NppStatus nppiNorm_L1_32f_C3CMR (const Npp32f * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

Masked three-channel 32-bit floating point image Norm_L1 affecting only single channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL1GetBufferHostSize_32f_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), `NPP_NOT_EVEN_STEP_ERROR` if the step of the source image cannot be divided by 4, or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.99.2.15 `NppStatus nppiNorm_L1_32f_C3R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[3], Npp8u * pDeviceBuffer)`

Three-channel 32-bit floating point image Norm_L1.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Three-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL1GetBufferHostSize_32f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.99.2.16 `NppStatus nppiNorm_L1_32f_C4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[4], Npp8u * pDeviceBuffer)`

Four-channel 32-bit floating point image Norm_L1.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Four-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL1GetBufferHostSize_32f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.99.2.17 `NppStatus nppiNorm_L1_8s_C1MR (const Npp8s * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

Masked one-channel 8-bit signed image Norm_L1.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL1GetBufferHostSize_8s_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.99.2.18 `NppStatus nppiNorm_L1_8s_C3CMR (const Npp8s * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

Masked three-channel 8-bit signed image Norm_L1 affecting only single channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL1GetBufferHostSize_8s_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.99.2.19 `NppStatus nppiNorm_L1_8u_AC4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[3], Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image Norm_L1 ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Three-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL1GetBufferHostSize_8u_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.99.2.20 `NppStatus nppiNorm_L1_8u_C1MR (const Npp8u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

Masked one-channel 8-bit unsigned image Norm_L1.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL1GetBufferHostSize_8u_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.99.2.21 `NppStatus nppiNorm_L1_8u_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

One-channel 8-bit unsigned image Norm_L1.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL1GetBufferHostSize_8u_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.99.2.22 `NppStatus nppiNorm_L1_8u_C3CMR (const Npp8u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

Masked three-channel 8-bit unsigned image Norm_L1 affecting only single channel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pMask [Mask-Image Pointer](#).

nMaskStep [Mask-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

nCOI [Channel_of_Interest Number](#).

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL1GetBufferHostSize_8u_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.99.2.23 `NppStatus nppiNorm_L1_8u_C3R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[3], Npp8u * pDeviceBuffer)`

Three-channel 8-bit unsigned image Norm_L1.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aNorm Array that contains the norm values of Three-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL1GetBufferHostSize_8u_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.99.2.24 `NppStatus nppiNorm_L1_8u_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[4], Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image Norm_L1.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Four-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL1GetBufferHostSize_8u_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.99.2.25 `NppStatus nppiNormL1GetBufferHostSize_16s_AC4R (NppiSize oSizeROI, int * hpBufferSize)`

Buffer size for [nppiNorm_L1_16s_AC4R](#).

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.99.2.26 `NppStatus nppiNormL1GetBufferHostSize_16s_C1R (NppiSize oSizeROI, int * hpBufferSize)`

Buffer size for [nppiNorm_L1_16s_C1R](#).

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.99.2.27 NppStatus nppiNormL1GetBufferHostSize_16s_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L1_16s_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.99.2.28 NppStatus nppiNormL1GetBufferHostSize_16s_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L1_16s_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.99.2.29 NppStatus nppiNormL1GetBufferHostSize_16u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L1_16u_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.99.2.30 NppStatus nppiNormL1GetBufferHostSize_16u_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L1_16u_C1MR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.99.2.31 NppStatus nppiNormL1GetBufferHostSize_16u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L1_16u_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.99.2.32 NppStatus nppiNormL1GetBufferHostSize_16u_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L1_16u_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.99.2.33 NppStatus nppiNormL1GetBufferHostSize_16u_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L1_16u_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.99.2.34 `NppStatus nppiNormL1GetBufferHostSize_16u_C4R` (`NppiSize oSizeROI`, `int * hpBufferSize`)

Buffer size for `nppiNorm_L1_16u_C4R`.

Parameters:

`oSizeROI` Region-of-Interest (ROI).

`hpBufferSize` Required buffer size. Important: `hpBufferSize` is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if `hpBufferSize` is 0 (NULL), [ROI Related Error Codes](#).

7.99.2.35 `NppStatus nppiNormL1GetBufferHostSize_32f_AC4R` (`NppiSize oSizeROI`, `int * hpBufferSize`)

Buffer size for `nppiNorm_L1_32f_AC4R`.

Parameters:

`oSizeROI` Region-of-Interest (ROI).

`hpBufferSize` Required buffer size. Important: `hpBufferSize` is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if `hpBufferSize` is 0 (NULL), [ROI Related Error Codes](#).

7.99.2.36 `NppStatus nppiNormL1GetBufferHostSize_32f_C1MR` (`NppiSize oSizeROI`, `int * hpBufferSize`)

Buffer size for `nppiNorm_L1_32f_C1MR`.

Parameters:

`oSizeROI` Region-of-Interest (ROI).

`hpBufferSize` Required buffer size. Important: `hpBufferSize` is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if `hpBufferSize` is 0 (NULL), [ROI Related Error Codes](#).

7.99.2.37 `NppStatus nppiNormL1GetBufferHostSize_32f_C1R` (`NppiSize oSizeROI`, `int * hpBufferSize`)

Buffer size for `nppiNorm_L1_32f_C1R`.

Parameters:

`oSizeROI` Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.99.2.38 NppStatus nppiNormL1GetBufferHostSize_32f_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L1_32f_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.99.2.39 NppStatus nppiNormL1GetBufferHostSize_32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L1_32f_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.99.2.40 NppStatus nppiNormL1GetBufferHostSize_32f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L1_32f_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.99.2.41 NppStatus nppiNormL1GetBufferHostSize_8s_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L1_8s_C1MR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.99.2.42 NppStatus nppiNormL1GetBufferHostSize_8s_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L1_8s_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.99.2.43 NppStatus nppiNormL1GetBufferHostSize_8u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L1_8u_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.99.2.44 NppStatus nppiNormL1GetBufferHostSize_8u_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L1_8u_C1MR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.99.2.45 NppStatus nppiNormL1GetBufferHostSize_8u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L1_8u_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.99.2.46 NppStatus nppiNormL1GetBufferHostSize_8u_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L1_8u_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.99.2.47 NppStatus nppiNormL1GetBufferHostSize_8u_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L1_8u_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.99.2.48 `NppStatus nppiNormL1GetBufferHostSize_8u_C4R` (`NppiSize oSizeROI`, `int * hpBufferSize`)

Buffer size for [nppiNorm_L1_8u_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.100 Norm_L2

Primitives for computing the L2 norm of an image.

Basic Norm_L2

Computes the L2 norm of an image.

- `NppStatus nppiNorm_L2_8u_C1R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp64f *pNorm`, `Npp8u *pDeviceBuffer`)
One-channel 8-bit unsigned image Norm_L2.
- `NppStatus nppiNorm_L2_16u_C1R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp64f *pNorm`, `Npp8u *pDeviceBuffer`)
One-channel 16-bit unsigned image Norm_L2.
- `NppStatus nppiNorm_L2_16s_C1R` (const `Npp16s *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp64f *pNorm`, `Npp8u *pDeviceBuffer`)
One-channel 16-bit signed image Norm_L2.
- `NppStatus nppiNorm_L2_32f_C1R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp64f *pNorm`, `Npp8u *pDeviceBuffer`)
One-channel 32-bit floating point image Norm_L2.
- `NppStatus nppiNorm_L2_8u_C3R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp64f aNorm[3]`, `Npp8u *pDeviceBuffer`)
Three-channel 8-bit unsigned image Norm_L2.
- `NppStatus nppiNorm_L2_16u_C3R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp64f aNorm[3]`, `Npp8u *pDeviceBuffer`)
Three-channel 16-bit unsigned image Norm_L2.
- `NppStatus nppiNorm_L2_16s_C3R` (const `Npp16s *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp64f aNorm[3]`, `Npp8u *pDeviceBuffer`)
Three-channel 16-bit signed image Norm_L2.
- `NppStatus nppiNorm_L2_32f_C3R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp64f aNorm[3]`, `Npp8u *pDeviceBuffer`)
Three-channel 32-bit floating point image Norm_L2.
- `NppStatus nppiNorm_L2_8u_AC4R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp64f aNorm[3]`, `Npp8u *pDeviceBuffer`)
Four-channel 8-bit unsigned image Norm_L2 ignoring alpha channel.
- `NppStatus nppiNorm_L2_16u_AC4R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp64f aNorm[3]`, `Npp8u *pDeviceBuffer`)
Four-channel 16-bit unsigned image Norm_L2 ignoring alpha channel.
- `NppStatus nppiNorm_L2_16s_AC4R` (const `Npp16s *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp64f aNorm[3]`, `Npp8u *pDeviceBuffer`)

Four-channel 16-bit signed image Norm_L2 ignoring alpha channel.

- `NppStatus nppiNorm_L2_32f_AC4R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp64f` `aNorm[3]`, `Npp8u *pDeviceBuffer`)

Four-channel 32-bit floating point image Norm_L2 ignoring alpha channel.

- `NppStatus nppiNorm_L2_8u_C4R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp64f` `aNorm[4]`, `Npp8u *pDeviceBuffer`)

Four-channel 8-bit unsigned image Norm_L2.

- `NppStatus nppiNorm_L2_16u_C4R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp64f` `aNorm[4]`, `Npp8u *pDeviceBuffer`)

Four-channel 16-bit unsigned image Norm_L2.

- `NppStatus nppiNorm_L2_16s_C4R` (const `Npp16s *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp64f` `aNorm[4]`, `Npp8u *pDeviceBuffer`)

Four-channel 16-bit signed image Norm_L2.

- `NppStatus nppiNorm_L2_32f_C4R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp64f` `aNorm[4]`, `Npp8u *pDeviceBuffer`)

Four-channel 32-bit floating point image Norm_L2.

Masked Norm_L2

See [Masked Operation](#).

- `NppStatus nppiNorm_L2_8u_C1MR` (const `Npp8u *pSrc`, int `nSrcStep`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, `Npp64f *pNorm`, `Npp8u *pDeviceBuffer`)

Masked one-channel 8-bit unsigned image Norm_L2.

- `NppStatus nppiNorm_L2_8s_C1MR` (const `Npp8s *pSrc`, int `nSrcStep`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, `Npp64f *pNorm`, `Npp8u *pDeviceBuffer`)

Masked one-channel 8-bit signed image Norm_L2.

- `NppStatus nppiNorm_L2_16u_C1MR` (const `Npp16u *pSrc`, int `nSrcStep`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, `Npp64f *pNorm`, `Npp8u *pDeviceBuffer`)

Masked one-channel 16-bit unsigned image Norm_L2.

- `NppStatus nppiNorm_L2_32f_C1MR` (const `Npp32f *pSrc`, int `nSrcStep`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, `Npp64f *pNorm`, `Npp8u *pDeviceBuffer`)

Masked one-channel 32-bit floating point image Norm_L2.

Masked Channel Norm_L2

See [Channel-of-Interest API](#) and [Masked Operation](#).

- `NppStatus nppiNorm_L2_8u_C3CMR` (const `Npp8u *pSrc`, int `nSrcStep`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, int `nCOI`, `Npp64f *pNorm`, `Npp8u *pDeviceBuffer`)

Masked three-channel 8-bit unsigned image Norm_L2.

- `NppStatus nppiNorm_L2_8s_C3CMR` (const `Npp8s` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, int nCOI, `Npp64f` *pNorm, `Npp8u` *pDeviceBuffer)

Masked three-channel 8-bit signed image Norm_L2.

- `NppStatus nppiNorm_L2_16u_C3CMR` (const `Npp16u` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, int nCOI, `Npp64f` *pNorm, `Npp8u` *pDeviceBuffer)

Masked three-channel 16-bit unsigned image Norm_L2.

- `NppStatus nppiNorm_L2_32f_C3CMR` (const `Npp32f` *pSrc, int nSrcStep, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, int nCOI, `Npp64f` *pNorm, `Npp8u` *pDeviceBuffer)

Masked three-channel 32-bit floating point image Norm_L2.

NormL2GetBufferHostSize

Companion primitives for computing the device buffer size (in bytes) required by the Norm_L2 primitives.

- `NppStatus nppiNormL2GetBufferHostSize_8u_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_L2_8u_C1R.
- `NppStatus nppiNormL2GetBufferHostSize_16u_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_L2_16u_C1R.
- `NppStatus nppiNormL2GetBufferHostSize_16s_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_L2_16s_C1R.
- `NppStatus nppiNormL2GetBufferHostSize_32f_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_L2_32f_C1R.
- `NppStatus nppiNormL2GetBufferHostSize_8u_C1MR` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_L2_8u_C1MR.
- `NppStatus nppiNormL2GetBufferHostSize_8s_C1MR` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_L2_8s_C1MR.
- `NppStatus nppiNormL2GetBufferHostSize_16u_C1MR` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_L2_16u_C1MR.
- `NppStatus nppiNormL2GetBufferHostSize_32f_C1MR` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_L2_32f_C1MR.
- `NppStatus nppiNormL2GetBufferHostSize_8u_C3R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_L2_8u_C3R.
- `NppStatus nppiNormL2GetBufferHostSize_16u_C3R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for nppiNorm_L2_16u_C3R.
- `NppStatus nppiNormL2GetBufferHostSize_16s_C3R` (`NppiSize` oSizeROI, int *hpBufferSize)

Buffer size for `nppiNorm_L2_16s_C3R`.

- `NppStatus nppiNormL2GetBufferHostSize_32f_C3R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L2_32f_C3R`.
- `NppStatus nppiNormL2GetBufferHostSize_8u_AC4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L2_8u_AC4R`.
- `NppStatus nppiNormL2GetBufferHostSize_16u_AC4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L2_16u_AC4R`.
- `NppStatus nppiNormL2GetBufferHostSize_16s_AC4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L2_16s_AC4R`.
- `NppStatus nppiNormL2GetBufferHostSize_32f_AC4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L2_32f_AC4R`.
- `NppStatus nppiNormL2GetBufferHostSize_8u_C4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L2_8u_C4R`.
- `NppStatus nppiNormL2GetBufferHostSize_16u_C4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L2_16u_C4R`.
- `NppStatus nppiNormL2GetBufferHostSize_16s_C4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L2_16s_C4R`.
- `NppStatus nppiNormL2GetBufferHostSize_32f_C4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L2_32f_C4R`.
- `NppStatus nppiNormL2GetBufferHostSize_8u_C3CMR` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L2_8u_C3CMR`.
- `NppStatus nppiNormL2GetBufferHostSize_8s_C3CMR` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L2_8s_C3CMR`.
- `NppStatus nppiNormL2GetBufferHostSize_16u_C3CMR` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L2_16u_C3CMR`.
- `NppStatus nppiNormL2GetBufferHostSize_32f_C3CMR` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size for `nppiNorm_L2_32f_C3CMR`.

7.100.1 Detailed Description

Primitives for computing the L2 norm of an image.

7.100.2 Function Documentation

7.100.2.1 `NppStatus nppiNorm_L2_16s_AC4R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[3], Npp8u * pDeviceBuffer)`

Four-channel 16-bit signed image Norm_L2 ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Three-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL2GetBufferHostSize_16s_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.100.2.2 `NppStatus nppiNorm_L2_16s_C1R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

One-channel 16-bit signed image Norm_L2.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL2GetBufferHostSize_16s_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.100.2.3 `NppStatus nppiNorm_L2_16s_C3R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[3], Npp8u * pDeviceBuffer)`

Three-channel 16-bit signed image Norm_L2.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Three-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL2GetBufferHostSize_16s_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.100.2.4 NppStatus nppiNorm_L2_16s_C4R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[4], Npp8u * pDeviceBuffer)

Four-channel 16-bit signed image Norm_L2.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Four-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL2GetBufferHostSize_16s_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.100.2.5 NppStatus nppiNorm_L2_16u_AC4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[3], Npp8u * pDeviceBuffer)

Four-channel 16-bit unsigned image Norm_L2 ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Three-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL2GetBufferHostSize_16u_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.100.2.6 NppStatus nppiNorm_L2_16u_C1MR (const Npp16u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNorm, Npp8u * pDeviceBuffer)

Masked one-channel 16-bit unsigned image Norm_L2.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL2GetBufferHostSize_16u_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.100.2.7 NppStatus nppiNorm_L2_16u_C1R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f * pNorm, Npp8u * pDeviceBuffer)

One-channel 16-bit unsigned image Norm_L2.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL2GetBufferHostSize_16u_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.100.2.8 NppStatus nppiNorm_L2_16u_C3CMR (const Npp16u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNorm, Npp8u * pDeviceBuffer)

Masked three-channel 16-bit unsigned image Norm_L2.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL2GetBufferHostSize_16u_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.100.2.9 NppStatus nppiNorm_L2_16u_C3R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[3], Npp8u * pDeviceBuffer)

Three-channel 16-bit unsigned image Norm_L2.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Three-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL2GetBufferHostSize_16u_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.100.2.10 NppStatus nppiNorm_L2_16u_C4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[4], Npp8u * pDeviceBuffer)

Four-channel 16-bit unsigned image Norm_L2.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Four-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL2GetBufferHostSize_16u_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.100.2.11 NppStatus nppiNorm_L2_32f_AC4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[3], Npp8u * pDeviceBuffer)

Four-channel 32-bit floating point image Norm_L2 ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Three-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL2GetBufferHostSize_32f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.100.2.12 `NppStatus nppiNorm_L2_32f_C1MR (const Npp32f * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

Masked one-channel 32-bit floating point image Norm_L2.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL2GetBufferHostSize_32f_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_EVEN_STEP_ERROR` if the step of the source image cannot be divided by 4.

7.100.2.13 `NppStatus nppiNorm_L2_32f_C1R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

One-channel 32-bit floating point image Norm_L2.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL2GetBufferHostSize_32f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.100.2.14 **NppStatus nppiNorm_L2_32f_C3CMR** (**const Npp32f * pSrc**, **int nSrcStep**, **const Npp8u * pMask**, **int nMaskStep**, **NppiSize oSizeROI**, **int nCOI**, **Npp64f * pNorm**, **Npp8u * pDeviceBuffer**)

Masked three-channel 32-bit floating point image Norm_L2.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL2GetBufferHostSize_32f_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), `NPP_NOT_EVEN_STEP_ERROR` if the step of the source image cannot be divided by 4, or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.100.2.15 **NppStatus nppiNorm_L2_32f_C3R** (**const Npp32f * pSrc**, **int nSrcStep**, **NppiSize oSizeROI**, **Npp64f aNorm[3]**, **Npp8u * pDeviceBuffer**)

Three-channel 32-bit floating point image Norm_L2.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Three-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL2GetBufferHostSize_32f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.100.2.16 **NppStatus nppiNorm_L2_32f_C4R** (**const Npp32f * pSrc**, **int nSrcStep**, **NppiSize oSizeROI**, **Npp64f aNorm[4]**, **Npp8u * pDeviceBuffer**)

Four-channel 32-bit floating point image Norm_L2.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Four-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL2GetBufferHostSize_32f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.100.2.17 `NppStatus nppiNorm_L2_8s_C1MR (const Npp8s * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

Masked one-channel 8-bit signed image Norm_L2.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL2GetBufferHostSize_8s_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.100.2.18 `NppStatus nppiNorm_L2_8s_C3CMR (const Npp8s * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

Masked three-channel 8-bit signed image Norm_L2.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL2GetBufferHostSize_8s_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.100.2.19 `NppStatus nppiNorm_L2_8u_AC4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[3], Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image Norm_L2 ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Three-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL2GetBufferHostSize_8u_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.100.2.20 `NppStatus nppiNorm_L2_8u_C1MR (const Npp8u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

Masked one-channel 8-bit unsigned image Norm_L2.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL2GetBufferHostSize_8u_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.100.2.21 `NppStatus nppiNorm_L2_8u_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

One-channel 8-bit unsigned image Norm_L2.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL2GetBufferSize_8u_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.100.2.22 `NppStatus nppiNorm_L2_8u_C3CMR (const Npp8u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

Masked three-channel 8-bit unsigned image Norm_L2.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pMask [Mask-Image Pointer](#).

nMaskStep [Mask-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

nCOI [Channel_of_Interest Number](#).

pNorm Pointer to the norm value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL2GetBufferSize_8u_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.100.2.23 `NppStatus nppiNorm_L2_8u_C3R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[3], Npp8u * pDeviceBuffer)`

Three-channel 8-bit unsigned image Norm_L2.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aNorm Array that contains the norm values of Three-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormL2GetBufferSize_8u_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.100.2.24 `NppStatus nppiNorm_L2_8u_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f aNorm[4], Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image Norm_L2.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNorm Array that contains the norm values of Four-channels.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use `nppiNormL2GetBufferHostSize_8u_C4R` to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.100.2.25 `NppStatus nppiNormL2GetBufferHostSize_16s_AC4R (NppiSize oSizeROI, int * hpBufferSize)`

Buffer size for `nppiNorm_L2_16s_AC4R`.

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.100.2.26 `NppStatus nppiNormL2GetBufferHostSize_16s_C1R (NppiSize oSizeROI, int * hpBufferSize)`

Buffer size for `nppiNorm_L2_16s_C1R`.

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.100.2.27 NppStatus nppiNormL2GetBufferHostSize_16s_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L2_16s_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.100.2.28 NppStatus nppiNormL2GetBufferHostSize_16s_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L2_16s_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.100.2.29 NppStatus nppiNormL2GetBufferHostSize_16u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L2_16u_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.100.2.30 NppStatus nppiNormL2GetBufferHostSize_16u_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L2_16u_C1MR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.100.2.31 NppStatus nppiNormL2GetBufferHostSize_16u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L2_16u_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.100.2.32 NppStatus nppiNormL2GetBufferHostSize_16u_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L2_16u_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.100.2.33 NppStatus nppiNormL2GetBufferHostSize_16u_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L2_16u_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.100.2.34 NppStatus nppiNormL2GetBufferHostSize_16u_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L2_16u_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.100.2.35 NppStatus nppiNormL2GetBufferHostSize_32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L2_32f_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.100.2.36 NppStatus nppiNormL2GetBufferHostSize_32f_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L2_32f_C1MR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.100.2.37 NppStatus nppiNormL2GetBufferHostSize_32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L2_32f_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.100.2.38 NppStatus nppiNormL2GetBufferHostSize_32f_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L2_32f_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.100.2.39 NppStatus nppiNormL2GetBufferHostSize_32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L2_32f_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.100.2.40 NppStatus nppiNormL2GetBufferHostSize_32f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L2_32f_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.100.2.41 NppStatus nppiNormL2GetBufferHostSize_8s_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L2_8s_C1MR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.100.2.42 NppStatus nppiNormL2GetBufferHostSize_8s_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L2_8s_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.100.2.43 NppStatus nppiNormL2GetBufferHostSize_8u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L2_8u_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.100.2.44 NppStatus nppiNormL2GetBufferHostSize_8u_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L2_8u_C1MR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.100.2.45 NppStatus nppiNormL2GetBufferHostSize_8u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L2_8u_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.100.2.46 NppStatus nppiNormL2GetBufferHostSize_8u_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L2_8u_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.100.2.47 NppStatus nppiNormL2GetBufferHostSize_8u_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNorm_L2_8u_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.100.2.48 NppStatus nppiNormL2GetBufferHostSize_8u_C4R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size for [nppiNorm_L2_8u_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.101 NormDiff_Inf

Primitives for computing the infinity norm of difference of pixels between two images.

Basic NormDiff_Inf

- `NppStatus nppiNormDiff_Inf_8u_C1R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` *pNormDiff, `Npp8u` *pDeviceBuffer)
One-channel 8-bit unsigned image NormDiff_Inf.
- `NppStatus nppiNormDiff_Inf_16u_C1R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` *pNormDiff, `Npp8u` *pDeviceBuffer)
One-channel 16-bit unsigned image NormDiff_Inf.
- `NppStatus nppiNormDiff_Inf_16s_C1R` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` *pNormDiff, `Npp8u` *pDeviceBuffer)
One-channel 16-bit signed image NormDiff_Inf.
- `NppStatus nppiNormDiff_Inf_32f_C1R` (const `Npp32f` *pSrc1, int nSrc1Step, const `Npp32f` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` *pNormDiff, `Npp8u` *pDeviceBuffer)
One-channel 32-bit floating point image NormDiff_Inf.
- `NppStatus nppiNormDiff_Inf_8u_C3R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` aNormDiff[3], `Npp8u` *pDeviceBuffer)
Three-channel 8-bit unsigned image NormDiff_Inf.
- `NppStatus nppiNormDiff_Inf_16u_C3R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` aNormDiff[3], `Npp8u` *pDeviceBuffer)
Three-channel 16-bit unsigned image NormDiff_Inf.
- `NppStatus nppiNormDiff_Inf_16s_C3R` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` aNormDiff[3], `Npp8u` *pDeviceBuffer)
Three-channel 16-bit signed image NormDiff_Inf.
- `NppStatus nppiNormDiff_Inf_32f_C3R` (const `Npp32f` *pSrc1, int nSrc1Step, const `Npp32f` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` aNormDiff[3], `Npp8u` *pDeviceBuffer)
Three-channel 32-bit floating point image NormDiff_Inf.
- `NppStatus nppiNormDiff_Inf_8u_AC4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` aNormDiff[3], `Npp8u` *pDeviceBuffer)
Four-channel 8-bit unsigned image NormDiff_Inf ignoring alpha channel.
- `NppStatus nppiNormDiff_Inf_16u_AC4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` aNormDiff[3], `Npp8u` *pDeviceBuffer)
Four-channel 16-bit unsigned image NormDiff_Inf ignoring alpha channel.
- `NppStatus nppiNormDiff_Inf_16s_AC4R` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` aNormDiff[3], `Npp8u` *pDeviceBuffer)
Four-channel 16-bit signed image NormDiff_Inf ignoring alpha channel.

- `NppStatus nppiNormDiff_Inf_32f_AC4R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f *pSrc2`, int `nSrc2Step`, `NppiSize` `oSizeROI`, `Npp64f` `aNormDiff[3]`, `Npp8u *pDeviceBuffer`)
Four-channel 32-bit floating point image NormDiff_Inf ignoring alpha channel.
- `NppStatus nppiNormDiff_Inf_8u_C4R` (const `Npp8u *pSrc1`, int `nSrc1Step`, const `Npp8u *pSrc2`, int `nSrc2Step`, `NppiSize` `oSizeROI`, `Npp64f` `aNormDiff[4]`, `Npp8u *pDeviceBuffer`)
Four-channel 8-bit unsigned image NormDiff_Inf.
- `NppStatus nppiNormDiff_Inf_16u_C4R` (const `Npp16u *pSrc1`, int `nSrc1Step`, const `Npp16u *pSrc2`, int `nSrc2Step`, `NppiSize` `oSizeROI`, `Npp64f` `aNormDiff[4]`, `Npp8u *pDeviceBuffer`)
Four-channel 16-bit unsigned image NormDiff_Inf.
- `NppStatus nppiNormDiff_Inf_16s_C4R` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp16s *pSrc2`, int `nSrc2Step`, `NppiSize` `oSizeROI`, `Npp64f` `aNormDiff[4]`, `Npp8u *pDeviceBuffer`)
Four-channel 16-bit signed image NormDiff_Inf.
- `NppStatus nppiNormDiff_Inf_32f_C4R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f *pSrc2`, int `nSrc2Step`, `NppiSize` `oSizeROI`, `Npp64f` `aNormDiff[4]`, `Npp8u *pDeviceBuffer`)
Four-channel 32-bit floating point image NormDiff_Inf.

Masked NormDiff_Inf

See [Masked Operation](#).

- `NppStatus nppiNormDiff_Inf_8u_C1MR` (const `Npp8u *pSrc1`, int `nSrc1Step`, const `Npp8u *pSrc2`, int `nSrc2Step`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, `Npp64f *pNormDiff`, `Npp8u *pDeviceBuffer`)
Masked one-channel 8-bit unsigned images NormDiff_Inf.
- `NppStatus nppiNormDiff_Inf_8s_C1MR` (const `Npp8s *pSrc1`, int `nSrc1Step`, const `Npp8s *pSrc2`, int `nSrc2Step`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, `Npp64f *pNormDiff`, `Npp8u *pDeviceBuffer`)
Masked one-channel 8-bit signed images NormDiff_Inf.
- `NppStatus nppiNormDiff_Inf_16u_C1MR` (const `Npp16u *pSrc1`, int `nSrc1Step`, const `Npp16u *pSrc2`, int `nSrc2Step`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, `Npp64f *pNormDiff`, `Npp8u *pDeviceBuffer`)
Masked one-channel 16-bit unsigned images NormDiff_Inf.
- `NppStatus nppiNormDiff_Inf_32f_C1MR` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f *pSrc2`, int `nSrc2Step`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, `Npp64f *pNormDiff`, `Npp8u *pDeviceBuffer`)
Masked one-channel 32-bit floating point images NormDiff_Inf.

Masked Channel Mean

See [Masked Operation](#) and [Channel-of-Interest API](#).

- `NppStatus nppiNormDiff_Inf_8u_C3CMR` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, int nCOI, `Npp64f` *pNormDiff, `Npp8u` *pDeviceBuffer)
Masked three-channel 8-bit unsigned image NormDiff_Inf affecting only single channel.
- `NppStatus nppiNormDiff_Inf_8s_C3CMR` (const `Npp8s` *pSrc1, int nSrc1Step, const `Npp8s` *pSrc2, int nSrc2Step, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, int nCOI, `Npp64f` *pNormDiff, `Npp8u` *pDeviceBuffer)
Masked three-channel 8-bit signed image NormDiff_Inf affecting only single channel.
- `NppStatus nppiNormDiff_Inf_16u_C3CMR` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, int nCOI, `Npp64f` *pNormDiff, `Npp8u` *pDeviceBuffer)
Masked three-channel 16-bit unsigned image NormDiff_Inf affecting only single channel.
- `NppStatus nppiNormDiff_Inf_32f_C3CMR` (const `Npp32f` *pSrc1, int nSrc1Step, const `Npp32f` *pSrc2, int nSrc2Step, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, int nCOI, `Npp64f` *pNormDiff, `Npp8u` *pDeviceBuffer)
Masked three-channel 32-bit floating point image NormDiff_Inf affecting only single channel.

NormDiffInfGetBufferHostSize

Companion primitives for computing the device buffer size (in bytes) required by the NormDiff_Inf primitives.

- `NppStatus nppiNormDiffInfGetBufferHostSize_8u_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiNormDiff_Inf_8u_C1R`.
- `NppStatus nppiNormDiffInfGetBufferHostSize_16u_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiNormDiff_Inf_16u_C1R`.
- `NppStatus nppiNormDiffInfGetBufferHostSize_16s_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiNormDiff_Inf_16s_C1R`.
- `NppStatus nppiNormDiffInfGetBufferHostSize_32f_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiNormDiff_Inf_32f_C1R`.
- `NppStatus nppiNormDiffInfGetBufferHostSize_8u_C1MR` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiNormDiff_Inf_8u_C1MR`.
- `NppStatus nppiNormDiffInfGetBufferHostSize_8s_C1MR` (`NppiSize` oSizeROI, int *hpBufferSize)
Buffer size for `nppiNormDiff_Inf_8s_C1MR`.
- `NppStatus nppiNormDiffInfGetBufferHostSize_16u_C1MR` (`NppiSize` oSizeROI, int *hpBufferSize)

Buffer size for nppiNormDiff_Inf_16u_C1MR.

- **NppStatus** nppiNormDiffInfGetBufferHostSize_32f_C1MR (NppiSize oSizeROI, int *hpBufferSize)

Buffer size for nppiNormDiff_Inf_32f_C1MR.

- **NppStatus** nppiNormDiffInfGetBufferHostSize_8u_C3R (NppiSize oSizeROI, int *hpBufferSize)

Buffer size for nppiNormDiff_Inf_8u_C3R.

- **NppStatus** nppiNormDiffInfGetBufferHostSize_16u_C3R (NppiSize oSizeROI, int *hpBufferSize)

Buffer size for nppiNormDiff_Inf_16u_C3R.

- **NppStatus** nppiNormDiffInfGetBufferHostSize_16s_C3R (NppiSize oSizeROI, int *hpBufferSize)

Buffer size for nppiNormDiff_Inf_16s_C3R.

- **NppStatus** nppiNormDiffInfGetBufferHostSize_32f_C3R (NppiSize oSizeROI, int *hpBufferSize)

Buffer size for nppiNormDiff_Inf_32f_C3R.

- **NppStatus** nppiNormDiffInfGetBufferHostSize_8u_C4R (NppiSize oSizeROI, int *hpBufferSize)

Buffer size for nppiNormDiff_Inf_8u_C4R.

- **NppStatus** nppiNormDiffInfGetBufferHostSize_16u_C4R (NppiSize oSizeROI, int *hpBufferSize)

Buffer size for nppiNormDiff_Inf_16u_C4R.

- **NppStatus** nppiNormDiffInfGetBufferHostSize_16s_C4R (NppiSize oSizeROI, int *hpBufferSize)

Buffer size for nppiNormDiff_Inf_16s_C4R.

- **NppStatus** nppiNormDiffInfGetBufferHostSize_32f_C4R (NppiSize oSizeROI, int *hpBufferSize)

Buffer size for nppiNormDiff_Inf_32f_C4R.

- **NppStatus** nppiNormDiffInfGetBufferHostSize_8u_AC4R (NppiSize oSizeROI, int *hpBufferSize)

Buffer size for nppiNormDiff_Inf_8u_AC4R.

- **NppStatus** nppiNormDiffInfGetBufferHostSize_16u_AC4R (NppiSize oSizeROI, int *hpBufferSize)

Buffer size for nppiNormDiff_Inf_16u_AC4R.

- **NppStatus** nppiNormDiffInfGetBufferHostSize_16s_AC4R (NppiSize oSizeROI, int *hpBufferSize)

Buffer size for nppiNormDiff_Inf_16s_AC4R.

- **NppStatus** nppiNormDiffInfGetBufferHostSize_32f_AC4R (NppiSize oSizeROI, int *hpBufferSize)

Buffer size for nppiNormDiff_Inf_32f_AC4R.

- [NppStatus nppiNormDiffInfGetBufferHostSize_8u_C3CMR](#) ([NppiSize](#) [oSizeROI](#), [int](#) *[hpBufferSize](#))
Buffer size for [nppiNormDiff_Inf_8u_C3CMR](#).
- [NppStatus nppiNormDiffInfGetBufferHostSize_8s_C3CMR](#) ([NppiSize](#) [oSizeROI](#), [int](#) *[hpBufferSize](#))
Buffer size for [nppiNormDiff_Inf_8s_C3CMR](#).
- [NppStatus nppiNormDiffInfGetBufferHostSize_16u_C3CMR](#) ([NppiSize](#) [oSizeROI](#), [int](#) *[hpBufferSize](#))
Buffer size for [nppiNormDiff_Inf_16u_C3CMR](#).
- [NppStatus nppiNormDiffInfGetBufferHostSize_32f_C3CMR](#) ([NppiSize](#) [oSizeROI](#), [int](#) *[hpBufferSize](#))
Buffer size for [nppiNormDiff_Inf_32f_C3CMR](#).

7.101.1 Detailed Description

Primitives for computing the infinity norm of difference of pixels between two images.

7.101.2 Function Documentation

7.101.2.1 [NppStatus nppiNormDiff_Inf_16s_AC4R](#) ([const Npp16s * pSrc1](#), [int nSrc1Step](#), [const Npp16s * pSrc2](#), [int nSrc2Step](#), [NppiSize oSizeROI](#), [Npp64f aNormDiff\[3\]](#), [Npp8u * pDeviceBuffer](#))

Four-channel 16-bit signed image NormDiff_Inf ignoring alpha channel.

Parameters:

pSrc1 [Source-Image Pointer](#).

nSrc1Step [Source-Image Line Step](#).

pSrc2 [Source-Image Pointer](#).

nSrc2Step [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer [Pointer to the required device memory allocation, Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffInfGetBufferHostSize_16s_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.101.2.2 `NppStatus nppiNormDiff_Inf_16s_C1R (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

One-channel 16-bit signed image NormDiff_Inf.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use `nppiNormDiffInfGetBufferHostSize_16s_C1R` to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.101.2.3 `NppStatus nppiNormDiff_Inf_16s_C3R (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[3], Npp8u * pDeviceBuffer)`

Three-channel 16-bit signed image NormDiff_Inf.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use `nppiNormDiffInfGetBufferHostSize_16s_C3R` to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.101.2.4 `NppStatus nppiNormDiff_Inf_16s_C4R (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[4], Npp8u * pDeviceBuffer)`

Four-channel 16-bit signed image NormDiff_Inf.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).
aNormDiff Array that contains computed Inf-norm of differences.
pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
 Use [nppiNormDiffInfGetBufferHostSize_16s_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.101.2.5 `NppStatus nppiNormDiff_Inf_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[3], Npp8u * pDeviceBuffer)`

Four-channel 16-bit unsigned image NormDiff_Inf ignoring alpha channel.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).
aNormDiff Array that contains computed Inf-norm of differences.
pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
 Use [nppiNormDiffInfGetBufferHostSize_16u_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.101.2.6 `NppStatus nppiNormDiff_Inf_16u_C1MR (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

Masked one-channel 16-bit unsigned images NormDiff_Inf.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffInfGetBufferHostSize_16u_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.101.2.7 `NppStatus nppiNormDiff_Inf_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

One-channel 16-bit unsigned image NormDiff_Inf.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffInfGetBufferHostSize_16u_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.101.2.8 `NppStatus nppiNormDiff_Inf_16u_C3CMR (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

Masked three-channel 16-bit unsigned image NormDiff_Inf affecting only single channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffInfGetBufferHostSize_16u_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.101.2.9 NppStatus nppiNormDiff_Inf_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[3], Npp8u * pDeviceBuffer)

Three-channel 16-bit unsigned image NormDiff_Inf.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffInfGetBufferHostSize_16u_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.101.2.10 NppStatus nppiNormDiff_Inf_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[4], Npp8u * pDeviceBuffer)

Four-channel 16-bit unsigned image NormDiff_Inf.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffInfGetBufferHostSize_16u_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.101.2.11 `NppStatus nppiNormDiff_Inf_32f_AC4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[3], Npp8u * pDeviceBuffer)`

Four-channel 32-bit floating point image NormDiff_Inf ignoring alpha channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffInfGetBufferHostSize_32f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified.

7.101.2.12 `NppStatus nppiNormDiff_Inf_32f_C1MR (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

Masked one-channel 32-bit floating point images NormDiff_Inf.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffInfGetBufferHostSize_32f_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified.

7.101.2.13 `NppStatus nppiNormDiff_Inf_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

One-channel 32-bit floating point image NormDiff_Inf.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffInfGetBufferHostSize_32f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified.

7.101.2.14 `NppStatus nppiNormDiff_Inf_32f_C3CMR (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

Masked three-channel 32-bit floating point image NormDiff_Inf affecting only single channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffInfGetBufferHostSize_32f_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified, or `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified.

7.101.2.15 `NppStatus nppiNormDiff_Inf_32f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[3], Npp8u * pDeviceBuffer)`

Three-channel 32-bit floating point image NormDiff_Inf.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).

Use [nppiNormDiffInfGetBufferHostSize_32f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified.

7.101.2.16 `NppStatus nppiNormDiff_Inf_32f_C4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[4], Npp8u * pDeviceBuffer)`

Four-channel 32-bit floating point image NormDiff_Inf.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).

Use [nppiNormDiffInfGetBufferHostSize_32f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified.

7.101.2.17 `NppStatus nppiNormDiff_Inf_8s_C1MR (const Npp8s * pSrc1, int nSrc1Step, const Npp8s * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

Masked one-channel 8-bit signed images NormDiff_Inf.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pMask* Mask-Image Pointer.
- nMaskStep* Mask-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- pNormDiff* Pointer to the computed Inf-norm of differences.
- pDeviceBuffer* Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffInfGetBufferHostSize_8s_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.101.2.18 `NppStatus nppiNormDiff_Inf_8s_C3CMR (const Npp8s * pSrc1, int nSrc1Step, const Npp8s * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

Masked three-channel 8-bit signed image NormDiff_Inf affecting only single channel.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pMask* Mask-Image Pointer.
- nMaskStep* Mask-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nCOI* Channel_of_Interest Number.
- pNormDiff* Pointer to the computed Inf-norm of differences.
- pDeviceBuffer* Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffInfGetBufferHostSize_8s_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.101.2.19 `NppStatus nppiNormDiff_Inf_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[3], Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image NormDiff_Inf ignoring alpha channel.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- aNormDiff* Array that contains computed Inf-norm of differences.
- pDeviceBuffer* Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffInfGetBufferHostSize_8u_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.101.2.20 `NppStatus nppiNormDiff_Inf_8u_C1MR (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

Masked one-channel 8-bit unsigned images NormDiff_Inf.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pMask* Mask-Image Pointer.
- nMaskStep* Mask-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- pNormDiff* Pointer to the computed Inf-norm of differences.
- pDeviceBuffer* Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffInfGetBufferHostSize_8u_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.101.2.21 `NppStatus nppiNormDiff_Inf_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

One-channel 8-bit unsigned image NormDiff_Inf.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffInfGetBufferHostSize_8u_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.101.2.22 `NppStatus nppiNormDiff_Inf_8u_C3CMR (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

Masked three-channel 8-bit unsigned image NormDiff_Inf affecting only single channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffInfGetBufferHostSize_8u_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.101.2.23 `NppStatus nppiNormDiff_Inf_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[3], Npp8u * pDeviceBuffer)`

Three-channel 8-bit unsigned image NormDiff_Inf.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffInfGetBufferHostSize_8u_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.101.2.24 `NppStatus nppiNormDiff_Inf_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[4], Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image NormDiff_Inf.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffInfGetBufferHostSize_8u_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.101.2.25 `NppStatus nppiNormDiffInfGetBufferHostSize_16s_AC4R (NppiSize oSizeROI, int * hpBufferSize)`

Buffer size for [nppiNormDiff_Inf_16s_AC4R](#).

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.101.2.26 NppStatus nppiNormDiffInfGetBufferHostSize_16s_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNormDiff_Inf_16s_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.101.2.27 NppStatus nppiNormDiffInfGetBufferHostSize_16s_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNormDiff_Inf_16s_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.101.2.28 NppStatus nppiNormDiffInfGetBufferHostSize_16s_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNormDiff_Inf_16s_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.101.2.29 NppStatus nppiNormDiffInfGetBufferHostSize_16u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNormDiff_Inf_16u_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.101.2.30 NppStatus nppiNormDiffInfGetBufferHostSize_16u_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNormDiff_Inf_16u_C1MR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.101.2.31 NppStatus nppiNormDiffInfGetBufferHostSize_16u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNormDiff_Inf_16u_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.101.2.32 NppStatus nppiNormDiffInfGetBufferHostSize_16u_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNormDiff_Inf_16u_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.101.2.33 NppStatus nppiNormDiffInfGetBufferHostSize_16u_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNormDiff_Inf_16u_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.101.2.34 NppStatus nppiNormDiffInfGetBufferHostSize_16u_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNormDiff_Inf_16u_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.101.2.35 NppStatus nppiNormDiffInfGetBufferHostSize_32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNormDiff_Inf_32f_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.101.2.36 NppStatus nppiNormDiffInfGetBufferHostSize_32f_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNormDiff_Inf_32f_C1MR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.101.2.37 NppStatus nppiNormDiffInfGetBufferHostSize_32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNormDiff_Inf_32f_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.101.2.38 NppStatus nppiNormDiffInfGetBufferHostSize_32f_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNormDiff_Inf_32f_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.101.2.39 NppStatus nppiNormDiffInfGetBufferHostSize_32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNormDiff_Inf_32f_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.101.2.40 NppStatus nppiNormDiffInfGetBufferHostSize_32f_C4R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size for [nppiNormDiff_Inf_32f_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.101.2.41 NppStatus nppiNormDiffInfGetBufferHostSize_8s_C1MR (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size for [nppiNormDiff_Inf_8s_C1MR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.101.2.42 NppStatus nppiNormDiffInfGetBufferHostSize_8s_C3CMR (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size for [nppiNormDiff_Inf_8s_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.101.2.43 NppStatus nppiNormDiffInfGetBufferHostSize_8u_AC4R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size for [nppiNormDiff_Inf_8u_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.101.2.44 NppStatus nppiNormDiffInfGetBufferHostSize_8u_C1MR (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size for [nppiNormDiff_Inf_8u_C1MR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.101.2.45 NppStatus nppiNormDiffInfGetBufferHostSize_8u_C1R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size for [nppiNormDiff_Inf_8u_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.101.2.46 NppStatus nppiNormDiffInfGetBufferHostSize_8u_C3CMR (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size for [nppiNormDiff_Inf_8u_C3CMR](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.101.2.47 NppStatus nppiNormDiffInfGetBufferHostSize_8u_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNormDiff_Inf_8u_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.101.2.48 NppStatus nppiNormDiffInfGetBufferHostSize_8u_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size for [nppiNormDiff_Inf_8u_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.102 NormDiff_L1

Primitives for computing the L1 norm of difference of pixels between two images.

Basic NormDiff_L1

- **NppStatus nppiNormDiff_L1_8u_C1R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pNormDiff, **Npp8u** *pDeviceBuffer)
One-channel 8-bit unsigned image NormDiff_L1.
- **NppStatus nppiNormDiff_L1_16u_C1R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pNormDiff, **Npp8u** *pDeviceBuffer)
One-channel 16-bit unsigned image NormDiff_L1.
- **NppStatus nppiNormDiff_L1_16s_C1R** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pNormDiff, **Npp8u** *pDeviceBuffer)
One-channel 16-bit signed image NormDiff_L1.
- **NppStatus nppiNormDiff_L1_32f_C1R** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pNormDiff, **Npp8u** *pDeviceBuffer)
One-channel 32-bit floating point image NormDiff_L1.
- **NppStatus nppiNormDiff_L1_8u_C3R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormDiff[3], **Npp8u** *pDeviceBuffer)
Three-channel 8-bit unsigned image NormDiff_L1.
- **NppStatus nppiNormDiff_L1_16u_C3R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormDiff[3], **Npp8u** *pDeviceBuffer)
Three-channel 16-bit unsigned image NormDiff_L1.
- **NppStatus nppiNormDiff_L1_16s_C3R** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormDiff[3], **Npp8u** *pDeviceBuffer)
Three-channel 16-bit signed image NormDiff_L1.
- **NppStatus nppiNormDiff_L1_32f_C3R** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormDiff[3], **Npp8u** *pDeviceBuffer)
Three-channel 32-bit floating point image NormDiff_L1.
- **NppStatus nppiNormDiff_L1_8u_AC4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormDiff[3], **Npp8u** *pDeviceBuffer)
Four-channel 8-bit unsigned image NormDiff_L1 ignoring alpha channel.
- **NppStatus nppiNormDiff_L1_16u_AC4R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormDiff[3], **Npp8u** *pDeviceBuffer)
Four-channel 16-bit unsigned image NormDiff_L1 ignoring alpha channel.
- **NppStatus nppiNormDiff_L1_16s_AC4R** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormDiff[3], **Npp8u** *pDeviceBuffer)
Four-channel 16-bit signed image NormDiff_L1 ignoring alpha channel.

- `NppStatus nppiNormDiff_L1_32f_AC4R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f *pSrc2`, int `nSrc2Step`, `NppiSize` `oSizeROI`, `Npp64f` `aNormDiff[3]`, `Npp8u *pDeviceBuffer`)
Four-channel 32-bit floating point image NormDiff_L1 ignoring alpha channel.
- `NppStatus nppiNormDiff_L1_8u_C4R` (const `Npp8u *pSrc1`, int `nSrc1Step`, const `Npp8u *pSrc2`, int `nSrc2Step`, `NppiSize` `oSizeROI`, `Npp64f` `aNormDiff[4]`, `Npp8u *pDeviceBuffer`)
Four-channel 8-bit unsigned image NormDiff_L1.
- `NppStatus nppiNormDiff_L1_16u_C4R` (const `Npp16u *pSrc1`, int `nSrc1Step`, const `Npp16u *pSrc2`, int `nSrc2Step`, `NppiSize` `oSizeROI`, `Npp64f` `aNormDiff[4]`, `Npp8u *pDeviceBuffer`)
Four-channel 16-bit unsigned image NormDiff_L1.
- `NppStatus nppiNormDiff_L1_16s_C4R` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp16s *pSrc2`, int `nSrc2Step`, `NppiSize` `oSizeROI`, `Npp64f` `aNormDiff[4]`, `Npp8u *pDeviceBuffer`)
Four-channel 16-bit signed image NormDiff_L1.
- `NppStatus nppiNormDiff_L1_32f_C4R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f *pSrc2`, int `nSrc2Step`, `NppiSize` `oSizeROI`, `Npp64f` `aNormDiff[4]`, `Npp8u *pDeviceBuffer`)
Four-channel 32-bit floating point image NormDiff_L1.

Masked NormDiff_L1

See [Masked Operation](#).

- `NppStatus nppiNormDiff_L1_8u_C1MR` (const `Npp8u *pSrc1`, int `nSrc1Step`, const `Npp8u *pSrc2`, int `nSrc2Step`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, `Npp64f *pNormDiff`, `Npp8u *pDeviceBuffer`)
Masked one-channel 8-bit unsigned image NormDiff_L1.
- `NppStatus nppiNormDiff_L1_8s_C1MR` (const `Npp8s *pSrc1`, int `nSrc1Step`, const `Npp8s *pSrc2`, int `nSrc2Step`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, `Npp64f *pNormDiff`, `Npp8u *pDeviceBuffer`)
Masked one-channel 8-bit signed image NormDiff_L1.
- `NppStatus nppiNormDiff_L1_16u_C1MR` (const `Npp16u *pSrc1`, int `nSrc1Step`, const `Npp16u *pSrc2`, int `nSrc2Step`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, `Npp64f *pNormDiff`, `Npp8u *pDeviceBuffer`)
Masked one-channel 16-bit unsigned image NormDiff_L1.
- `NppStatus nppiNormDiff_L1_32f_C1MR` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f *pSrc2`, int `nSrc2Step`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, `Npp64f *pNormDiff`, `Npp8u *pDeviceBuffer`)
Masked one-channel 32-bit floating point image NormDiff_L1.

Masked Channel NormDiff_L1

See [Masked Operation](#) and [Channel-of-Interest API](#).

- **NppStatus** `nppiNormDiff_L1_8u_C3CMR` (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, const **Npp8u** *pMask, int nMaskStep, **NppiSize** oSizeROI, int nCOI, **Npp64f** *pNormDiff, **Npp8u** *pDeviceBuffer)
Masked three-channel 8-bit unsigned image NormDiff_L1 affecting only single channel.
- **NppStatus** `nppiNormDiff_L1_8s_C3CMR` (const **Npp8s** *pSrc1, int nSrc1Step, const **Npp8s** *pSrc2, int nSrc2Step, const **Npp8u** *pMask, int nMaskStep, **NppiSize** oSizeROI, int nCOI, **Npp64f** *pNormDiff, **Npp8u** *pDeviceBuffer)
Masked three-channel 8-bit signed image NormDiff_L1 affecting only single channel.
- **NppStatus** `nppiNormDiff_L1_16u_C3CMR` (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, const **Npp8u** *pMask, int nMaskStep, **NppiSize** oSizeROI, int nCOI, **Npp64f** *pNormDiff, **Npp8u** *pDeviceBuffer)
Masked three-channel 16-bit unsigned image NormDiff_L1 affecting only single channel.
- **NppStatus** `nppiNormDiff_L1_32f_C3CMR` (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, const **Npp8u** *pMask, int nMaskStep, **NppiSize** oSizeROI, int nCOI, **Npp64f** *pNormDiff, **Npp8u** *pDeviceBuffer)
Masked three-channel 32-bit floating point image NormDiff_L1 affecting only single channel.

NormDiffL1GetBufferHostSize

Companion primitives for computing the device buffer size (in bytes) required by the NormDiff_L1 primitives.

- **NppStatus** `nppiNormDiffL1GetBufferHostSize_8u_C1R` (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_8u_C1R.
- **NppStatus** `nppiNormDiffL1GetBufferHostSize_16u_C1R` (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_16u_C1R.
- **NppStatus** `nppiNormDiffL1GetBufferHostSize_16s_C1R` (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_16s_C1R.
- **NppStatus** `nppiNormDiffL1GetBufferHostSize_32f_C1R` (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_32f_C1R.
- **NppStatus** `nppiNormDiffL1GetBufferHostSize_8u_C1MR` (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_8u_C1MR.
- **NppStatus** `nppiNormDiffL1GetBufferHostSize_8s_C1MR` (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_8s_C1MR.
- **NppStatus** `nppiNormDiffL1GetBufferHostSize_16u_C1MR` (**NppiSize** oSizeROI, int *hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_16u_C1MR.

- **NppStatus** `nppiNormDiffL1GetBufferHostSize_32f_C1MR` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_32f_C1MR.

- **NppStatus** `nppiNormDiffL1GetBufferHostSize_8u_C3R` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_8u_C3R.

- **NppStatus** `nppiNormDiffL1GetBufferHostSize_16u_C3R` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_16u_C3R.

- **NppStatus** `nppiNormDiffL1GetBufferHostSize_16s_C3R` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_16s_C3R.

- **NppStatus** `nppiNormDiffL1GetBufferHostSize_32f_C3R` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_32f_C3R.

- **NppStatus** `nppiNormDiffL1GetBufferHostSize_8u_C4R` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_8u_C4R.

- **NppStatus** `nppiNormDiffL1GetBufferHostSize_16u_C4R` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_16u_C4R.

- **NppStatus** `nppiNormDiffL1GetBufferHostSize_16s_C4R` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_16s_C4R.

- **NppStatus** `nppiNormDiffL1GetBufferHostSize_32f_C4R` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_32f_C4R.

- **NppStatus** `nppiNormDiffL1GetBufferHostSize_8u_AC4R` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_8u_AC4R.

- **NppStatus** `nppiNormDiffL1GetBufferHostSize_16u_AC4R` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_16u_AC4R.

- **NppStatus** `nppiNormDiffL1GetBufferHostSize_16s_AC4R` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_16s_AC4R.

- **NppStatus** `nppiNormDiffL1GetBufferHostSize_32f_AC4R` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_32f_AC4R.

- **NppStatus** `nppiNormDiffL1GetBufferHostSize_8u_C3CMR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Computes the device scratch buffer size (in bytes) for `nppiNormDiff_L1_8u_C3CMR`.
- **NppStatus** `nppiNormDiffL1GetBufferHostSize_8s_C3CMR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Computes the device scratch buffer size (in bytes) for `nppiNormDiff_L1_8s_C3CMR`.
- **NppStatus** `nppiNormDiffL1GetBufferHostSize_16u_C3CMR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Computes the device scratch buffer size (in bytes) for `nppiNormDiff_L1_16u_C3CMR`.
- **NppStatus** `nppiNormDiffL1GetBufferHostSize_32f_C3CMR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Computes the device scratch buffer size (in bytes) for `nppiNormDiff_L1_32f_C3CMR`.

7.102.1 Detailed Description

Primitives for computing the L1 norm of difference of pixels between two images.

7.102.2 Function Documentation

7.102.2.1 **NppStatus** `nppiNormDiff_L1_16s_AC4R` (**const** **Npp16s** `*pSrc1`, **int** `nSrc1Step`, **const** **Npp16s** `*pSrc2`, **int** `nSrc2Step`, **NppiSize** `oSizeROI`, **Npp64f** `aNormDiff[3]`, **Npp8u** `*pDeviceBuffer`)

Four-channel 16-bit signed image NormDiff_L1 ignoring alpha channel.

Parameters:

`pSrc1` [Source-Image Pointer](#).

`nSrc1Step` [Source-Image Line Step](#).

`pSrc2` [Source-Image Pointer](#).

`nSrc2Step` [Source-Image Line Step](#).

`oSizeROI` [Region-of-Interest \(ROI\)](#).

`aNormDiff` Array that contains computed Inf-norm of differences.

`pDeviceBuffer` Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
 Use `nppiNormDiffL1GetBufferHostSize_16s_AC4R` to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.102.2.2 **NppStatus** `nppiNormDiff_L1_16s_C1R` (**const** **Npp16s** `*pSrc1`, **int** `nSrc1Step`, **const** **Npp16s** `*pSrc2`, **int** `nSrc2Step`, **NppiSize** `oSizeROI`, **Npp64f** `*pNormDiff`, **Npp8u** `*pDeviceBuffer`)

One-channel 16-bit signed image NormDiff_L1.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- pNormDiff* Pointer to the computed Inf-norm of differences.
- pDeviceBuffer* Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL1GetBufferHostSize_16s_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.102.2.3 `NppStatus nppiNormDiff_L1_16s_C3R (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[3], Npp8u * pDeviceBuffer)`

Three-channel 16-bit signed image NormDiff_L1.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- aNormDiff* Array that contains computed Inf-norm of differences.
- pDeviceBuffer* Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL1GetBufferHostSize_16s_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.102.2.4 `NppStatus nppiNormDiff_L1_16s_C4R (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[4], Npp8u * pDeviceBuffer)`

Four-channel 16-bit signed image NormDiff_L1.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL1GetBufferHostSize_16s_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.102.2.5 `NppStatus nppiNormDiff_L1_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[3], Npp8u * pDeviceBuffer)`

Four-channel 16-bit unsigned image NormDiff_L1 ignoring alpha channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL1GetBufferHostSize_16u_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.102.2.6 `NppStatus nppiNormDiff_L1_16u_C1MR (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

Masked one-channel 16-bit unsigned image NormDiff_L1.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL1GetBufferHostSize_16u_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.102.2.7 `NppStatus nppiNormDiff_L1_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

One-channel 16-bit unsigned image NormDiff_L1.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL1GetBufferHostSize_16u_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.102.2.8 `NppStatus nppiNormDiff_L1_16u_C3CMR (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

Masked three-channel 16-bit unsigned image NormDiff_L1 affecting only single channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL1GetBufferHostSize_16u_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.102.2.9 `NppStatus nppiNormDiff_L1_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[3], Npp8u * pDeviceBuffer)`

Three-channel 16-bit unsigned image NormDiff_L1.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL1GetBufferHostSize_16u_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.102.2.10 `NppStatus nppiNormDiff_L1_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[4], Npp8u * pDeviceBuffer)`

Four-channel 16-bit unsigned image NormDiff_L1.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL1GetBufferHostSize_16u_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.102.2.11 `NppStatus nppiNormDiff_L1_32f_AC4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[3], Npp8u * pDeviceBuffer)`

Four-channel 32-bit floating point image NormDiff_L1 ignoring alpha channel.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- aNormDiff* Array that contains computed Inf-norm of differences.
- pDeviceBuffer* Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL1GetBufferHostSize_32f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified.

7.102.2.12 `NppStatus nppiNormDiff_L1_32f_C1MR (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

Masked one-channel 32-bit floating point image NormDiff_L1.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pMask* Mask-Image Pointer.
- nMaskStep* Mask-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- pNormDiff* Pointer to the computed Inf-norm of differences.
- pDeviceBuffer* Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL1GetBufferHostSize_32f_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified.

7.102.2.13 `NppStatus nppiNormDiff_L1_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

One-channel 32-bit floating point image NormDiff_L1.

Parameters:

- pSrc1* Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL1GetBufferHostSize_32f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified.

7.102.2.14 `NppStatus nppiNormDiff_L1_32f_C3CMR (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

Masked three-channel 32-bit floating point image NormDiff_L1 affecting only single channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL1GetBufferHostSize_32f_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified, or `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified.

7.102.2.15 `NppStatus nppiNormDiff_L1_32f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[3], Npp8u * pDeviceBuffer)`

Three-channel 32-bit floating point image NormDiff_L1.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL1GetBufferHostSize_32f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified.

7.102.2.16 `NppStatus nppiNormDiff_L1_32f_C4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[4], Npp8u * pDeviceBuffer)`

Four-channel 32-bit floating point image NormDiff_L1.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL1GetBufferHostSize_32f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified.

7.102.2.17 `NppStatus nppiNormDiff_L1_8s_C1MR (const Npp8s * pSrc1, int nSrc1Step, const Npp8s * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

Masked one-channel 8-bit signed image NormDiff_L1.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL1GetBufferHostSize_8s_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.102.2.18 `NppStatus nppiNormDiff_L1_8s_C3CMR (const Npp8s * pSrc1, int nSrc1Step, const Npp8s * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

Masked three-channel 8-bit signed image NormDiff_L1 affecting only single channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL1GetBufferHostSize_8s_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.102.2.19 `NppStatus nppiNormDiff_L1_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[3], Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image NormDiff_L1 ignoring alpha channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL1GetBufferHostSize_8u_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.102.2.20 `NppStatus nppiNormDiff_L1_8u_C1MR (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

Masked one-channel 8-bit unsigned image NormDiff_L1.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL1GetBufferHostSize_8u_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.102.2.21 `NppStatus nppiNormDiff_L1_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

One-channel 8-bit unsigned image NormDiff_L1.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL1GetBufferHostSize_8u_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.102.2.22 `NppStatus nppiNormDiff_L1_8u_C3CMR (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

Masked three-channel 8-bit unsigned image NormDiff_L1 affecting only single channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL1GetBufferHostSize_8u_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.102.2.23 `NppStatus nppiNormDiff_L1_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[3], Npp8u * pDeviceBuffer)`

Three-channel 8-bit unsigned image NormDiff_L1.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL1GetBufferHostSize_8u_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.102.2.24 `NppStatus nppiNormDiff_L1_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[4], Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image NormDiff_L1.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL1GetBufferHostSize_8u_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.102.2.25 `NppStatus nppiNormDiffL1GetBufferHostSize_16s_AC4R (NppiSize oSizeROI, int * hpBufferSize)`

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_16s_AC4R.

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if hpBufferSize is 0 (NULL), [ROI Related Error Codes](#).

7.102.2.26 `NppStatus nppiNormDiffL1GetBufferHostSize_16s_C1R (NppiSize oSizeROI, int * hpBufferSize)`

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_16s_C1R.

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if hpBufferSize is 0 (NULL), [ROI Related Error Codes](#).

7.102.2.27 NppStatus nppiNormDiffL1GetBufferHostSize_16s_C3R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_16s_C3R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.102.2.28 NppStatus nppiNormDiffL1GetBufferHostSize_16s_C4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_16s_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.102.2.29 NppStatus nppiNormDiffL1GetBufferHostSize_16u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_16u_AC4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.102.2.30 NppStatus nppiNormDiffL1GetBufferHostSize_16u_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_16u_C1MR.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.102.2.31 NppStatus nppiNormDiffL1GetBufferHostSize_16u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormDiff_L1_16u_C1R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.102.2.32 NppStatus nppiNormDiffL1GetBufferHostSize_16u_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormDiff_L1_16u_C3CMR*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.102.2.33 NppStatus nppiNormDiffL1GetBufferHostSize_16u_C3R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormDiff_L1_16u_C3R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.102.2.34 NppStatus nppiNormDiffL1GetBufferHostSize_16u_C4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_16u_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.102.2.35 NppStatus nppiNormDiffL1GetBufferHostSize_32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_32f_AC4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.102.2.36 NppStatus nppiNormDiffL1GetBufferHostSize_32f_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_32f_C1MR.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.102.2.37 NppStatus nppiNormDiffL1GetBufferHostSize_32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_32f_C1R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.102.2.38 NppStatus nppiNormDiffL1GetBufferHostSize_32f_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormDiff_L1_32f_C3CMR*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.102.2.39 NppStatus nppiNormDiffL1GetBufferHostSize_32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormDiff_L1_32f_C3R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.102.2.40 NppStatus nppiNormDiffL1GetBufferHostSize_32f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormDiff_L1_32f_C4R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.102.2.41 NppStatus nppiNormDiffL1GetBufferHostSize_8s_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_8s_C1MR.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.102.2.42 NppStatus nppiNormDiffL1GetBufferHostSize_8s_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_8s_C3CMR.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.102.2.43 NppStatus nppiNormDiffL1GetBufferHostSize_8u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_8u_AC4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.102.2.44 NppStatus nppiNormDiffL1GetBufferHostSize_8u_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_8u_C1MR.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.102.2.45 NppStatus nppiNormDiffL1GetBufferHostSize_8u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormDiff_L1_8u_C1R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.102.2.46 NppStatus nppiNormDiffL1GetBufferHostSize_8u_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormDiff_L1_8u_C3CMR*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.102.2.47 NppStatus nppiNormDiffL1GetBufferHostSize_8u_C3R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormDiff_L1_8u_C3R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.102.2.48 NppStatus nppiNormDiffL1GetBufferHostSize_8u_C4R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L1_8u_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.103 NormDiff_L2

Primitives for computing the L2 norm of difference of pixels between two images.

Basic NormDiff_L2

- **NppStatus nppiNormDiff_L2_8u_C1R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pNormDiff, **Npp8u** *pDeviceBuffer)
One-channel 8-bit unsigned image NormDiff_L2.
- **NppStatus nppiNormDiff_L2_16u_C1R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pNormDiff, **Npp8u** *pDeviceBuffer)
One-channel 16-bit unsigned image NormDiff_L2.
- **NppStatus nppiNormDiff_L2_16s_C1R** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pNormDiff, **Npp8u** *pDeviceBuffer)
One-channel 16-bit signed image NormDiff_L2.
- **NppStatus nppiNormDiff_L2_32f_C1R** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pNormDiff, **Npp8u** *pDeviceBuffer)
One-channel 32-bit floating point image NormDiff_L2.
- **NppStatus nppiNormDiff_L2_8u_C3R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormDiff[3], **Npp8u** *pDeviceBuffer)
Three-channel 8-bit unsigned image NormDiff_L2.
- **NppStatus nppiNormDiff_L2_16u_C3R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormDiff[3], **Npp8u** *pDeviceBuffer)
Three-channel 16-bit unsigned image NormDiff_L2.
- **NppStatus nppiNormDiff_L2_16s_C3R** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormDiff[3], **Npp8u** *pDeviceBuffer)
Three-channel 16-bit signed image NormDiff_L2.
- **NppStatus nppiNormDiff_L2_32f_C3R** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormDiff[3], **Npp8u** *pDeviceBuffer)
Three-channel 32-bit floating point image NormDiff_L2.
- **NppStatus nppiNormDiff_L2_8u_AC4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormDiff[3], **Npp8u** *pDeviceBuffer)
Four-channel 8-bit unsigned image NormDiff_L2 ignoring alpha channel.
- **NppStatus nppiNormDiff_L2_16u_AC4R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormDiff[3], **Npp8u** *pDeviceBuffer)
Four-channel 16-bit unsigned image NormDiff_L2 ignoring alpha channel.
- **NppStatus nppiNormDiff_L2_16s_AC4R** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormDiff[3], **Npp8u** *pDeviceBuffer)
Four-channel 16-bit signed image NormDiff_L2 ignoring alpha channel.

- [NppStatus nppiNormDiff_L2_32f_AC4R](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [NppiSize](#) oSizeROI, [Npp64f](#) aNormDiff[3], [Npp8u](#) *pDeviceBuffer)
Four-channel 32-bit floating point image NormDiff_L2 ignoring alpha channel.
- [NppStatus nppiNormDiff_L2_8u_C4R](#) (const [Npp8u](#) *pSrc1, int nSrc1Step, const [Npp8u](#) *pSrc2, int nSrc2Step, [NppiSize](#) oSizeROI, [Npp64f](#) aNormDiff[4], [Npp8u](#) *pDeviceBuffer)
Four-channel 8-bit unsigned image NormDiff_L2.
- [NppStatus nppiNormDiff_L2_16u_C4R](#) (const [Npp16u](#) *pSrc1, int nSrc1Step, const [Npp16u](#) *pSrc2, int nSrc2Step, [NppiSize](#) oSizeROI, [Npp64f](#) aNormDiff[4], [Npp8u](#) *pDeviceBuffer)
Four-channel 16-bit unsigned image NormDiff_L2.
- [NppStatus nppiNormDiff_L2_16s_C4R](#) (const [Npp16s](#) *pSrc1, int nSrc1Step, const [Npp16s](#) *pSrc2, int nSrc2Step, [NppiSize](#) oSizeROI, [Npp64f](#) aNormDiff[4], [Npp8u](#) *pDeviceBuffer)
Four-channel 16-bit signed image NormDiff_L2.
- [NppStatus nppiNormDiff_L2_32f_C4R](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [NppiSize](#) oSizeROI, [Npp64f](#) aNormDiff[4], [Npp8u](#) *pDeviceBuffer)
Four-channel 32-bit floating point image NormDiff_L2.

Masked NormDiff_L2

See [Masked Operation](#).

- [NppStatus nppiNormDiff_L2_8u_C1MR](#) (const [Npp8u](#) *pSrc1, int nSrc1Step, const [Npp8u](#) *pSrc2, int nSrc2Step, const [Npp8u](#) *pMask, int nMaskStep, [NppiSize](#) oSizeROI, [Npp64f](#) *pNormDiff, [Npp8u](#) *pDeviceBuffer)
Masked one-channel 8-bit unsigned image NormDiff_L2.
- [NppStatus nppiNormDiff_L2_8s_C1MR](#) (const [Npp8s](#) *pSrc1, int nSrc1Step, const [Npp8s](#) *pSrc2, int nSrc2Step, const [Npp8u](#) *pMask, int nMaskStep, [NppiSize](#) oSizeROI, [Npp64f](#) *pNormDiff, [Npp8u](#) *pDeviceBuffer)
Masked one-channel 8-bit signed image NormDiff_L2.
- [NppStatus nppiNormDiff_L2_16u_C1MR](#) (const [Npp16u](#) *pSrc1, int nSrc1Step, const [Npp16u](#) *pSrc2, int nSrc2Step, const [Npp8u](#) *pMask, int nMaskStep, [NppiSize](#) oSizeROI, [Npp64f](#) *pNormDiff, [Npp8u](#) *pDeviceBuffer)
Masked one-channel 16-bit unsigned image NormDiff_L2.
- [NppStatus nppiNormDiff_L2_32f_C1MR](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, const [Npp8u](#) *pMask, int nMaskStep, [NppiSize](#) oSizeROI, [Npp64f](#) *pNormDiff, [Npp8u](#) *pDeviceBuffer)
Masked one-channel 32-bit floating point image NormDiff_L2.

Masked Channel NormDiff_L2

See [Masked Operation](#) and [Channel-of-Interest API](#).

- `NppStatus nppiNormDiff_L2_8u_C3CMR` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, int nCOI, `Npp64f` *pNormDiff, `Npp8u` *pDeviceBuffer)
Masked three-channel 8-bit unsigned image NormDiff_L2 affecting only single channel.
- `NppStatus nppiNormDiff_L2_8s_C3CMR` (const `Npp8s` *pSrc1, int nSrc1Step, const `Npp8s` *pSrc2, int nSrc2Step, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, int nCOI, `Npp64f` *pNormDiff, `Npp8u` *pDeviceBuffer)
Masked three-channel 8-bit signed image NormDiff_L2 affecting only single channel.
- `NppStatus nppiNormDiff_L2_16u_C3CMR` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, int nCOI, `Npp64f` *pNormDiff, `Npp8u` *pDeviceBuffer)
Masked three-channel 16-bit unsigned image NormDiff_L2 affecting only single channel.
- `NppStatus nppiNormDiff_L2_32f_C3CMR` (const `Npp32f` *pSrc1, int nSrc1Step, const `Npp32f` *pSrc2, int nSrc2Step, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, int nCOI, `Npp64f` *pNormDiff, `Npp8u` *pDeviceBuffer)
Masked three-channel 32-bit floating point image NormDiff_L2 affecting only single channel.

NormDiffL2GetBufferHostSize

Companion primitives for computing the device buffer size (in bytes) required by the NormDiff_L2 primitives.

- `NppStatus nppiNormDiffL2GetBufferHostSize_8u_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_8u_C1R.
- `NppStatus nppiNormDiffL2GetBufferHostSize_16u_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_16u_C1R.
- `NppStatus nppiNormDiffL2GetBufferHostSize_16s_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_16s_C1R.
- `NppStatus nppiNormDiffL2GetBufferHostSize_32f_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_32f_C1R.
- `NppStatus nppiNormDiffL2GetBufferHostSize_8u_C1MR` (`NppiSize` oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_8u_C1MR.
- `NppStatus nppiNormDiffL2GetBufferHostSize_8s_C1MR` (`NppiSize` oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_8s_C1MR.
- `NppStatus nppiNormDiffL2GetBufferHostSize_16u_C1MR` (`NppiSize` oSizeROI, int *hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_16u_C1MR.

- **NppStatus** `nppiNormDiffL2GetBufferHostSize_32f_C1MR` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_32f_C1MR.

- **NppStatus** `nppiNormDiffL2GetBufferHostSize_8u_C3R` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_8u_C3R.

- **NppStatus** `nppiNormDiffL2GetBufferHostSize_16u_C3R` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_16u_C3R.

- **NppStatus** `nppiNormDiffL2GetBufferHostSize_16s_C3R` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_16s_C3R.

- **NppStatus** `nppiNormDiffL2GetBufferHostSize_32f_C3R` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_32f_C3R.

- **NppStatus** `nppiNormDiffL2GetBufferHostSize_8u_C4R` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_8u_C4R.

- **NppStatus** `nppiNormDiffL2GetBufferHostSize_16u_C4R` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_16u_C4R.

- **NppStatus** `nppiNormDiffL2GetBufferHostSize_16s_C4R` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_16s_C4R.

- **NppStatus** `nppiNormDiffL2GetBufferHostSize_32f_C4R` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_32f_C4R.

- **NppStatus** `nppiNormDiffL2GetBufferHostSize_8u_AC4R` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_8u_AC4R.

- **NppStatus** `nppiNormDiffL2GetBufferHostSize_16u_AC4R` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_16u_AC4R.

- **NppStatus** `nppiNormDiffL2GetBufferHostSize_16s_AC4R` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_16s_AC4R.

- **NppStatus** `nppiNormDiffL2GetBufferHostSize_32f_AC4R` (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_32f_AC4R.

- **NppStatus** `nppiNormDiffL2GetBufferHostSize_8u_C3CMR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Computes the device scratch buffer size (in bytes) for `nppiNormDiff_L2_8u_C3CMR`.
- **NppStatus** `nppiNormDiffL2GetBufferHostSize_8s_C3CMR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Computes the device scratch buffer size (in bytes) for `nppiNormDiff_L2_8s_C3CMR`.
- **NppStatus** `nppiNormDiffL2GetBufferHostSize_16u_C3CMR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Computes the device scratch buffer size (in bytes) for `nppiNormDiff_L2_16u_C3CMR`.
- **NppStatus** `nppiNormDiffL2GetBufferHostSize_32f_C3CMR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Computes the device scratch buffer size (in bytes) for `nppiNormDiff_L2_32f_C3CMR`.

7.103.1 Detailed Description

Primitives for computing the L2 norm of difference of pixels between two images.

7.103.2 Function Documentation

7.103.2.1 **NppStatus** `nppiNormDiff_L2_16s_AC4R` (**const** **Npp16s** `*pSrc1`, **int** `nSrc1Step`, **const** **Npp16s** `*pSrc2`, **int** `nSrc2Step`, **NppiSize** `oSizeROI`, **Npp64f** `aNormDiff[3]`, **Npp8u** `*pDeviceBuffer`)

Four-channel 16-bit signed image NormDiff_L2 ignoring alpha channel.

Parameters:

`pSrc1` [Source-Image Pointer](#).

`nSrc1Step` [Source-Image Line Step](#).

`pSrc2` [Source-Image Pointer](#).

`nSrc2Step` [Source-Image Line Step](#).

`oSizeROI` [Region-of-Interest \(ROI\)](#).

`aNormDiff` Array that contains computed Inf-norm of differences.

`pDeviceBuffer` Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
 Use `nppiNormDiffL2GetBufferHostSize_16s_AC4R` to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.103.2.2 **NppStatus** `nppiNormDiff_L2_16s_C1R` (**const** **Npp16s** `*pSrc1`, **int** `nSrc1Step`, **const** **Npp16s** `*pSrc2`, **int** `nSrc2Step`, **NppiSize** `oSizeROI`, **Npp64f** `*pNormDiff`, **Npp8u** `*pDeviceBuffer`)

One-channel 16-bit signed image NormDiff_L2.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- pNormDiff* Pointer to the computed Inf-norm of differences.
- pDeviceBuffer* Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL2GetBufferHostSize_16s_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.103.2.3 `NppStatus nppiNormDiff_L2_16s_C3R (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[3], Npp8u * pDeviceBuffer)`

Three-channel 16-bit signed image NormDiff_L2.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- aNormDiff* Array that contains computed Inf-norm of differences.
- pDeviceBuffer* Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL2GetBufferHostSize_16s_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.103.2.4 `NppStatus nppiNormDiff_L2_16s_C4R (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[4], Npp8u * pDeviceBuffer)`

Four-channel 16-bit signed image NormDiff_L2.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL2GetBufferHostSize_16s_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.103.2.5 `NppStatus nppiNormDiff_L2_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[3], Npp8u * pDeviceBuffer)`

Four-channel 16-bit unsigned image NormDiff_L2 ignoring alpha channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL2GetBufferHostSize_16u_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.103.2.6 `NppStatus nppiNormDiff_L2_16u_C1MR (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

Masked one-channel 16-bit unsigned image NormDiff_L2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL2GetBufferHostSize_16u_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.103.2.7 `NppStatus nppiNormDiff_L2_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

One-channel 16-bit unsigned image NormDiff_L2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL2GetBufferHostSize_16u_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.103.2.8 `NppStatus nppiNormDiff_L2_16u_C3CMR (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

Masked three-channel 16-bit unsigned image NormDiff_L2 affecting only single channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL2GetBufferHostSize_16u_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.103.2.9 `NppStatus nppiNormDiff_L2_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[3], Npp8u * pDeviceBuffer)`

Three-channel 16-bit unsigned image NormDiff_L2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use `nppiNormDiffL2GetBufferHostSize_16u_C3R` to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.103.2.10 `NppStatus nppiNormDiff_L2_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[4], Npp8u * pDeviceBuffer)`

Four-channel 16-bit unsigned image NormDiff_L2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use `nppiNormDiffL2GetBufferHostSize_16u_C4R` to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.103.2.11 `NppStatus nppiNormDiff_L2_32f_AC4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[3], Npp8u * pDeviceBuffer)`

Four-channel 32-bit floating point image NormDiff_L2 ignoring alpha channel.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- aNormDiff* Array that contains computed Inf-norm of differences.
- pDeviceBuffer* Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL2GetBufferHostSize_32f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified.

7.103.2.12 `NppStatus nppiNormDiff_L2_32f_C1MR (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

Masked one-channel 32-bit floating point image NormDiff_L2.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pMask* Mask-Image Pointer.
- nMaskStep* Mask-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- pNormDiff* Pointer to the computed Inf-norm of differences.
- pDeviceBuffer* Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL2GetBufferHostSize_32f_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified.

7.103.2.13 `NppStatus nppiNormDiff_L2_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

One-channel 32-bit floating point image NormDiff_L2.

Parameters:

- pSrc1* Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL2GetBufferHostSize_32f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified.

7.103.2.14 `NppStatus nppiNormDiff_L2_32f_C3CMR (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

Masked three-channel 32-bit floating point image NormDiff_L2 affecting only single channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL2GetBufferHostSize_32f_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified, or `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified.

7.103.2.15 `NppStatus nppiNormDiff_L2_32f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[3], Npp8u * pDeviceBuffer)`

Three-channel 32-bit floating point image NormDiff_L2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL2GetBufferHostSize_32f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified.

7.103.2.16 `NppStatus nppiNormDiff_L2_32f_C4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[4], Npp8u * pDeviceBuffer)`

Four-channel 32-bit floating point image NormDiff_L2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL2GetBufferHostSize_32f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified.

7.103.2.17 `NppStatus nppiNormDiff_L2_8s_C1MR (const Npp8s * pSrc1, int nSrc1Step, const Npp8s * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

Masked one-channel 8-bit signed image NormDiff_L2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL2GetBufferHostSize_8s_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.103.2.18 `NppStatus nppiNormDiff_L2_8s_C3CMR (const Npp8s * pSrc1, int nSrc1Step, const Npp8s * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

Masked three-channel 8-bit signed image NormDiff_L2 affecting only single channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL2GetBufferHostSize_8s_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.103.2.19 `NppStatus nppiNormDiff_L2_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[3], Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image NormDiff_L2 ignoring alpha channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL2GetBufferHostSize_8u_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.103.2.20 `NppStatus nppiNormDiff_L2_8u_C1MR (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

Masked one-channel 8-bit unsigned image NormDiff_L2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL2GetBufferHostSize_8u_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.103.2.21 `NppStatus nppiNormDiff_L2_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

One-channel 8-bit unsigned image NormDiff_L2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL2GetBufferHostSize_8u_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.103.2.22 `NppStatus nppiNormDiff_L2_8u_C3CMR (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNormDiff, Npp8u * pDeviceBuffer)`

Masked three-channel 8-bit unsigned image NormDiff_L2 affecting only single channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNormDiff Pointer to the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use `nppiNormDiffL2GetBufferHostSize_8u_C3CMR` to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified.

7.103.2.23 `NppStatus nppiNormDiff_L2_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[3], Npp8u * pDeviceBuffer)`

Three-channel 8-bit unsigned image NormDiff_L2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use `nppiNormDiffL2GetBufferHostSize_8u_C3R` to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.103.2.24 `NppStatus nppiNormDiff_L2_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormDiff[4], Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image NormDiff_L2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormDiff Array that contains computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormDiffL2GetBufferHostSize_8u_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.103.2.25 `NppStatus nppiNormDiffL2GetBufferHostSize_16s_AC4R (NppiSize oSizeROI, int * hpBufferSize)`

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_16s_AC4R.

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.103.2.26 `NppStatus nppiNormDiffL2GetBufferHostSize_16s_C1R (NppiSize oSizeROI, int * hpBufferSize)`

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_16s_C1R.

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.103.2.27 NppStatus nppiNormDiffL2GetBufferHostSize_16s_C3R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_16s_C3R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.103.2.28 NppStatus nppiNormDiffL2GetBufferHostSize_16s_C4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_16s_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.103.2.29 NppStatus nppiNormDiffL2GetBufferHostSize_16u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_16u_AC4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.103.2.30 NppStatus nppiNormDiffL2GetBufferHostSize_16u_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_16u_C1MR.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.103.2.31 NppStatus nppiNormDiffL2GetBufferHostSize_16u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormDiff_L2_16u_C1R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.103.2.32 NppStatus nppiNormDiffL2GetBufferHostSize_16u_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormDiff_L2_16u_C3CMR*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.103.2.33 NppStatus nppiNormDiffL2GetBufferHostSize_16u_C3R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormDiff_L2_16u_C3R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.103.2.34 NppStatus nppiNormDiffL2GetBufferHostSize_16u_C4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_16u_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.103.2.35 NppStatus nppiNormDiffL2GetBufferHostSize_32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_32f_AC4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.103.2.36 NppStatus nppiNormDiffL2GetBufferHostSize_32f_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_32f_C1MR.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.103.2.37 NppStatus nppiNormDiffL2GetBufferHostSize_32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_32f_C1R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.103.2.38 NppStatus nppiNormDiffL2GetBufferHostSize_32f_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormDiff_L2_32f_C3CMR*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.103.2.39 NppStatus nppiNormDiffL2GetBufferHostSize_32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormDiff_L2_32f_C3R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.103.2.40 NppStatus nppiNormDiffL2GetBufferHostSize_32f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormDiff_L2_32f_C4R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.103.2.41 NppStatus nppiNormDiffL2GetBufferHostSize_8s_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_8s_C1MR.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.103.2.42 NppStatus nppiNormDiffL2GetBufferHostSize_8s_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_8s_C3CMR.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.103.2.43 NppStatus nppiNormDiffL2GetBufferHostSize_8u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_8u_AC4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.103.2.44 NppStatus nppiNormDiffL2GetBufferHostSize_8u_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_8u_C1MR.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.103.2.45 NppStatus nppiNormDiffL2GetBufferHostSize_8u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormDiff_L2_8u_C1R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.103.2.46 NppStatus nppiNormDiffL2GetBufferHostSize_8u_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormDiff_L2_8u_C3CMR*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.103.2.47 NppStatus nppiNormDiffL2GetBufferHostSize_8u_C3R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormDiff_L2_8u_C3R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.103.2.48 NppStatus nppiNormDiffL2GetBufferHostSize_8u_C4R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Computes the device scratch buffer size (in bytes) for nppiNormDiff_L2_8u_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.104 NormRel_Inf

Primitives for computing the relative error of infinity norm between two images.

Basic NormRel_Inf

- **NppStatus nppiNormRel_Inf_8u_C1R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pNormRel, **Npp8u** *pDeviceBuffer)
One-channel 8-bit unsigned image NormRel_Inf.
- **NppStatus nppiNormRel_Inf_16u_C1R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pNormRel, **Npp8u** *pDeviceBuffer)
One-channel 16-bit unsigned image NormRel_Inf.
- **NppStatus nppiNormRel_Inf_16s_C1R** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pNormRel, **Npp8u** *pDeviceBuffer)
One-channel 16-bit signed image NormRel_Inf.
- **NppStatus nppiNormRel_Inf_32f_C1R** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pNormRel, **Npp8u** *pDeviceBuffer)
One-channel 32-bit floating point image NormRel_Inf.
- **NppStatus nppiNormRel_Inf_8u_C3R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormRel[3], **Npp8u** *pDeviceBuffer)
Three-channel 8-bit unsigned image NormRel_Inf.
- **NppStatus nppiNormRel_Inf_16u_C3R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormRel[3], **Npp8u** *pDeviceBuffer)
Three-channel 16-bit unsigned image NormRel_Inf.
- **NppStatus nppiNormRel_Inf_16s_C3R** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormRel[3], **Npp8u** *pDeviceBuffer)
Three-channel 16-bit signed image NormRel_Inf.
- **NppStatus nppiNormRel_Inf_32f_C3R** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormRel[3], **Npp8u** *pDeviceBuffer)
Three-channel 32-bit floating point image NormRel_Inf.
- **NppStatus nppiNormRel_Inf_8u_AC4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormRel[3], **Npp8u** *pDeviceBuffer)
Four-channel 8-bit unsigned image NormRel_Inf ignoring alpha channel.
- **NppStatus nppiNormRel_Inf_16u_AC4R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormRel[3], **Npp8u** *pDeviceBuffer)
Four-channel 16-bit unsigned image NormRel_Inf ignoring alpha channel.
- **NppStatus nppiNormRel_Inf_16s_AC4R** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormRel[3], **Npp8u** *pDeviceBuffer)
Four-channel 16-bit signed image NormRel_Inf ignoring alpha channel.

- [NppStatus nppiNormRel_Inf_32f_AC4R](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [NppiSize](#) oSizeROI, [Npp64f](#) aNormRel[3], [Npp8u](#) *pDeviceBuffer)
Four-channel 32-bit floating point image NormRel_Inf ignoring alpha channel.
- [NppStatus nppiNormRel_Inf_8u_C4R](#) (const [Npp8u](#) *pSrc1, int nSrc1Step, const [Npp8u](#) *pSrc2, int nSrc2Step, [NppiSize](#) oSizeROI, [Npp64f](#) aNormRel[4], [Npp8u](#) *pDeviceBuffer)
Four-channel 8-bit unsigned image NormRel_Inf.
- [NppStatus nppiNormRel_Inf_16u_C4R](#) (const [Npp16u](#) *pSrc1, int nSrc1Step, const [Npp16u](#) *pSrc2, int nSrc2Step, [NppiSize](#) oSizeROI, [Npp64f](#) aNormRel[4], [Npp8u](#) *pDeviceBuffer)
Four-channel 16-bit unsigned image NormRel_Inf.
- [NppStatus nppiNormRel_Inf_16s_C4R](#) (const [Npp16s](#) *pSrc1, int nSrc1Step, const [Npp16s](#) *pSrc2, int nSrc2Step, [NppiSize](#) oSizeROI, [Npp64f](#) aNormRel[4], [Npp8u](#) *pDeviceBuffer)
Four-channel 16-bit signed image NormRel_Inf.
- [NppStatus nppiNormRel_Inf_32f_C4R](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [NppiSize](#) oSizeROI, [Npp64f](#) aNormRel[4], [Npp8u](#) *pDeviceBuffer)
Four-channel 32-bit floating point image NormRel_Inf.

Masked NormRel_Inf

See [Masked Operation](#).

- [NppStatus nppiNormRel_Inf_8u_C1MR](#) (const [Npp8u](#) *pSrc1, int nSrc1Step, const [Npp8u](#) *pSrc2, int nSrc2Step, const [Npp8u](#) *pMask, int nMaskStep, [NppiSize](#) oSizeROI, [Npp64f](#) *pNormRel, [Npp8u](#) *pDeviceBuffer)
Masked one-channel 8-bit unsigned image NormRel_Inf.
- [NppStatus nppiNormRel_Inf_8s_C1MR](#) (const [Npp8s](#) *pSrc1, int nSrc1Step, const [Npp8s](#) *pSrc2, int nSrc2Step, const [Npp8u](#) *pMask, int nMaskStep, [NppiSize](#) oSizeROI, [Npp64f](#) *pNormRel, [Npp8u](#) *pDeviceBuffer)
Masked one-channel 8-bit signed image NormRel_Inf.
- [NppStatus nppiNormRel_Inf_16u_C1MR](#) (const [Npp16u](#) *pSrc1, int nSrc1Step, const [Npp16u](#) *pSrc2, int nSrc2Step, const [Npp8u](#) *pMask, int nMaskStep, [NppiSize](#) oSizeROI, [Npp64f](#) *pNormRel, [Npp8u](#) *pDeviceBuffer)
Masked one-channel 16-bit unsigned image NormRel_Inf.
- [NppStatus nppiNormRel_Inf_32f_C1MR](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, const [Npp8u](#) *pMask, int nMaskStep, [NppiSize](#) oSizeROI, [Npp64f](#) *pNormRel, [Npp8u](#) *pDeviceBuffer)
Masked one-channel 32-bit floating point image NormRel_Inf.

Masked Channel NormRel_Inf

See [Masked Operation](#) and [Channel-of-Interest API](#).

- **NppStatus** `nppiNormRel_Inf_8u_C3CMR` (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, const **Npp8u** *pMask, int nMaskStep, **NppiSize** oSizeROI, int nCOI, **Npp64f** *pNormRel, **Npp8u** *pDeviceBuffer)
Masked three-channel 8-bit unsigned image NormRel_Inf affecting only single channel.
- **NppStatus** `nppiNormRel_Inf_8s_C3CMR` (const **Npp8s** *pSrc1, int nSrc1Step, const **Npp8s** *pSrc2, int nSrc2Step, const **Npp8u** *pMask, int nMaskStep, **NppiSize** oSizeROI, int nCOI, **Npp64f** *pNormRel, **Npp8u** *pDeviceBuffer)
Masked three-channel 8-bit signed image NormRel_Inf affecting only single channel.
- **NppStatus** `nppiNormRel_Inf_16u_C3CMR` (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, const **Npp8u** *pMask, int nMaskStep, **NppiSize** oSizeROI, int nCOI, **Npp64f** *pNormRel, **Npp8u** *pDeviceBuffer)
Masked three-channel 16-bit unsigned image NormRel_Inf affecting only single channel.
- **NppStatus** `nppiNormRel_Inf_32f_C3CMR` (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, const **Npp8u** *pMask, int nMaskStep, **NppiSize** oSizeROI, int nCOI, **Npp64f** *pNormRel, **Npp8u** *pDeviceBuffer)
Masked three-channel 32-bit floating point image NormRel_Inf affecting only single channel.

NormRelInfGetBufferHostSize

Companion primitives for computing the device buffer size (in bytes) required by the NormRel_Inf primitives.

- **NppStatus** `nppiNormRelInfGetBufferHostSize_8u_C1R` (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_8u_C1R.
- **NppStatus** `nppiNormRelInfGetBufferHostSize_16u_C1R` (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_16u_C1R.
- **NppStatus** `nppiNormRelInfGetBufferHostSize_16s_C1R` (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_16s_C1R.
- **NppStatus** `nppiNormRelInfGetBufferHostSize_32s_C1R` (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_32s_C1R.
- **NppStatus** `nppiNormRelInfGetBufferHostSize_32f_C1R` (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_32f_C1R.
- **NppStatus** `nppiNormRelInfGetBufferHostSize_8u_C1MR` (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_8u_C1MR.
- **NppStatus** `nppiNormRelInfGetBufferHostSize_8s_C1MR` (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_8s_C1MR.
- **NppStatus** `nppiNormRelInfGetBufferHostSize_16u_C1MR` (**NppiSize** oSizeROI, int *hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_16u_C1MR.

- **NppStatus** [nppiNormRelInfGetBufferHostSize_32f_C1MR](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_32f_C1MR.

- **NppStatus** [nppiNormRelInfGetBufferHostSize_8u_C3R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_8u_C3R.

- **NppStatus** [nppiNormRelInfGetBufferHostSize_16u_C3R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_16u_C3R.

- **NppStatus** [nppiNormRelInfGetBufferHostSize_16s_C3R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_16s_C3R.

- **NppStatus** [nppiNormRelInfGetBufferHostSize_32f_C3R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_32f_C3R.

- **NppStatus** [nppiNormRelInfGetBufferHostSize_8u_C4R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_8u_C4R.

- **NppStatus** [nppiNormRelInfGetBufferHostSize_16u_C4R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_16u_C4R.

- **NppStatus** [nppiNormRelInfGetBufferHostSize_16s_C4R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_16s_C4R.

- **NppStatus** [nppiNormRelInfGetBufferHostSize_32f_C4R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_32f_C4R.

- **NppStatus** [nppiNormRelInfGetBufferHostSize_8u_AC4R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_8u_AC4R.

- **NppStatus** [nppiNormRelInfGetBufferHostSize_16u_AC4R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_16u_AC4R.

- **NppStatus** [nppiNormRelInfGetBufferHostSize_16s_AC4R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_16s_AC4R.

- **NppStatus** [nppiNormRelInfGetBufferHostSize_32f_AC4R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_32f_AC4R.

- **NppStatus** [nppiNormRelInfGetBufferHostSize_8u_C3CMR](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_8u_C3CMR.

- **NppStatus** `nppiNormRelInfGetBufferHostSize_8s_C3CMR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Computes the device scratch buffer size (in bytes) for `nppiNormRel_Inf_8s_C3CMR`.
- **NppStatus** `nppiNormRelInfGetBufferHostSize_16u_C3CMR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Computes the device scratch buffer size (in bytes) for `nppiNormRel_Inf_16u_C3CMR`.
- **NppStatus** `nppiNormRelInfGetBufferHostSize_32f_C3CMR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Computes the device scratch buffer size (in bytes) for `nppiNormRel_Inf_32f_C3CMR`.

7.104.1 Detailed Description

Primitives for computing the relative error of infinity norm between two images.

7.104.2 Function Documentation

7.104.2.1 **NppStatus** `nppiNormRel_Inf_16s_AC4R` (**const** **Npp16s** `*pSrc1`, **int** `nSrc1Step`, **const** **Npp16s** `*pSrc2`, **int** `nSrc2Step`, **NppiSize** `oSizeROI`, **Npp64f** `aNormRel[3]`, **Npp8u** `*pDeviceBuffer`)

Four-channel 16-bit signed image NormRel_Inf ignoring alpha channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the infinity norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use `nppiNormRelInfGetBufferHostSize_16s_AC4R` to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the infinity norm of the second image is zero.

7.104.2.2 **NppStatus** `nppiNormRel_Inf_16s_C1R` (**const** **Npp16s** `*pSrc1`, **int** `nSrc1Step`, **const** **Npp16s** `*pSrc2`, **int** `nSrc2Step`, **NppiSize** `oSizeROI`, **Npp64f** `*pNormRel`, **Npp8u** `*pDeviceBuffer`)

One-channel 16-bit signed image NormRel_Inf.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormRel Pointer to the computed relative error for the infinity norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelInfGetBufferHostSize_16s_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the infinity norm of the second image is zero.

7.104.2.3 `NppStatus nppiNormRel_Inf_16s_C3R (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[3], Npp8u * pDeviceBuffer)`

Three-channel 16-bit signed image NormRel_Inf.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the infinity norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelInfGetBufferHostSize_16s_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the infinity norm of the second image is zero.

7.104.2.4 `NppStatus nppiNormRel_Inf_16s_C4R (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[4], Npp8u * pDeviceBuffer)`

Four-channel 16-bit signed image NormRel_Inf.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the infinity norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).

Use [nppiNormRelInfGetBufferHostSize_16s_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or NPP_DIVISOR_ERROR if the infinity norm of the second image is zero.

7.104.2.5 NppStatus nppiNormRel_Inf_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[3], Npp8u * pDeviceBuffer)

Four-channel 16-bit unsigned image NormRel_Inf ignoring alpha channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the infinity norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).

Use [nppiNormRelInfGetBufferHostSize_16u_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or NPP_DIVISOR_ERROR if the infinity norm of the second image is zero.

7.104.2.6 NppStatus nppiNormRel_Inf_16u_C1MR (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)

Masked one-channel 16-bit unsigned image NormRel_Inf.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormRel Pointer to the computed relative error for the infinity norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelInfGetBufferHostSize_16u_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the infinity norm of the second image is zero.

7.104.2.7 `NppStatus nppiNormRel_Inf_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

One-channel 16-bit unsigned image NormRel_Inf.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormRel Pointer to the computed relative error for the infinity norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelInfGetBufferHostSize_16u_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the infinity norm of the second image is zero.

7.104.2.8 `NppStatus nppiNormRel_Inf_16u_C3CMR (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

Masked three-channel 16-bit unsigned image NormRel_Inf affecting only single channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNormRel Pointer to the computed relative error for the infinity norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelInfGetBufferHostSize_16u_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), NPP_COI_ERROR if an invalid channel of interest is specified, or NPP_DIVISOR_ERROR if the infinity norm of the second image is zero.

7.104.2.9 `NppStatus nppiNormRel_Inf_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[3], Npp8u * pDeviceBuffer)`

Three-channel 16-bit unsigned image NormRel_Inf.

Parameters:

pSrc1 [Source-Image Pointer](#).

nSrc1Step [Source-Image Line Step](#).

pSrc2 [Source-Image Pointer](#).

nSrc2Step [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aNormRel Array that contains the computed relative error for the infinity norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelInfGetBufferHostSize_16u_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or NPP_DIVISOR_ERROR if the infinity norm of the second image is zero.

7.104.2.10 `NppStatus nppiNormRel_Inf_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[4], Npp8u * pDeviceBuffer)`

Four-channel 16-bit unsigned image NormRel_Inf.

Parameters:

pSrc1 [Source-Image Pointer](#).

nSrc1Step [Source-Image Line Step](#).

pSrc2 [Source-Image Pointer](#).

nSrc2Step [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aNormRel Array that contains the computed relative error for the infinity norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelInfGetBufferHostSize_16u_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or NPP_DIVISOR_ERROR if the infinity norm of the second image is zero.

7.104.2.11 `NppStatus nppiNormRel_Inf_32f_AC4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[3], Npp8u * pDeviceBuffer)`

Four-channel 32-bit floating point image NormRel_Inf ignoring alpha channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the infinity norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelInfGetBufferHostSize_32f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified, or `NPP_DIVISOR_ERROR` if the infinity norm of the second image is zero.

7.104.2.12 `NppStatus nppiNormRel_Inf_32f_C1MR (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

Masked one-channel 32-bit floating point image NormRel_Inf.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormRel Pointer to the computed relative error for the infinity norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelInfGetBufferHostSize_32f_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified, or `NPP_DIVISOR_ERROR` if the infinity norm of the second image is zero.

7.104.2.13 `NppStatus nppiNormRel_Inf_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

One-channel 32-bit floating point image NormRel_Inf.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormRel Pointer to the computed relative error for the infinity norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelInfGetBufferHostSize_32f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified, or `NPP_DIVISOR_ERROR` if the infinity norm of the second image is zero.

7.104.2.14 `NppStatus nppiNormRel_Inf_32f_C3CMR (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

Masked three-channel 32-bit floating point image NormRel_Inf affecting only single channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNormRel Pointer to the computed relative error for the infinity norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelInfGetBufferHostSize_32f_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), `NPP_COI_ERROR` if an invalid channel of interest is specified, or `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified, or `NPP_DIVISOR_ERROR` if the infinity norm of the second image is zero.

7.104.2.15 `NppStatus nppiNormRel_Inf_32f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[3], Npp8u * pDeviceBuffer)`

Three-channel 32-bit floating point image NormRel_Inf.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the infinity norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelInfGetBufferHostSize_32f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified, or `NPP_DIVISOR_ERROR` if the infinity norm of the second image is zero.

7.104.2.16 `NppStatus nppiNormRel_Inf_32f_C4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[4], Npp8u * pDeviceBuffer)`

Four-channel 32-bit floating point image NormRel_Inf.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the infinity norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelInfGetBufferHostSize_32f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), `NPP_NOT_EVEN_STEP_ERROR` if an invalid floating-point image is specified, or `NPP_DIVISOR_ERROR` if the infinity norm of the second image is zero.

7.104.2.17 `NppStatus nppiNormRel_Inf_8s_C1MR (const Npp8s * pSrc1, int nSrc1Step, const Npp8s * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

Masked one-channel 8-bit signed image NormRel_Inf.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormRel Pointer to the computed relative error for the infinity norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelInfGetBufferHostSize_8s_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the infinity norm of the second image is zero.

7.104.2.18 `NppStatus nppiNormRel_Inf_8s_C3CMR (const Npp8s * pSrc1, int nSrc1Step, const Npp8s * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

Masked three-channel 8-bit signed image NormRel_Inf affecting only single channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNormRel Pointer to the computed relative error for the infinity norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelInfGetBufferHostSize_8s_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), `NPP_COI_ERROR` if an invalid channel of interest is specified, or `NPP_DIVISOR_ERROR` if the infinity norm of the second image is zero.

7.104.2.19 `NppStatus nppiNormRel_Inf_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[3], Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image NormRel_Inf ignoring alpha channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the infinity norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelInfGetBufferHostSize_8u_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the infinity norm of the second image is zero.

7.104.2.20 `NppStatus nppiNormRel_Inf_8u_C1MR (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

Masked one-channel 8-bit unsigned image NormRel_Inf.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormRel Pointer to the computed relative error for the infinity norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelInfGetBufferHostSize_8u_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the infinity norm of the second image is zero.

7.104.2.21 `NppStatus nppiNormRel_Inf_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

One-channel 8-bit unsigned image NormRel_Inf.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormRel Pointer to the computed relative error for the infinity norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelInfGetBufferHostSize_8u_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the infinity norm of the second image is zero.

7.104.2.22 `NppStatus nppiNormRel_Inf_8u_C3CMR (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

Masked three-channel 8-bit unsigned image NormRel_Inf affecting only single channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNormRel Pointer to the computed relative error for the infinity norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelInfGetBufferHostSize_8u_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), `NPP_COI_ERROR` if an invalid channel of interest is specified, or `NPP_DIVISOR_ERROR` if the infinity norm of the second image is zero.

7.104.2.23 `NppStatus nppiNormRel_Inf_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[3], Npp8u * pDeviceBuffer)`

Three-channel 8-bit unsigned image NormRel_Inf.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the infinity norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelInfGetBufferHostSize_8u_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the infinity norm of the second image is zero.

7.104.2.24 `NppStatus nppiNormRel_Inf_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[4], Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image NormRel_Inf.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the infinity norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelInfGetBufferHostSize_8u_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the infinity norm of the second image is zero.

7.104.2.25 `NppStatus nppiNormRelInfGetBufferHostSize_16s_AC4R (NppiSize oSizeROI, int * hpBufferSize)`

Computes the device scratch buffer size (in bytes) for `nppiNormRel_Inf_16s_AC4R`.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.104.2.26 NppStatus nppiNormRelInfGetBufferHostSize_16s_C1R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_Inf_16s_C1R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.104.2.27 NppStatus nppiNormRelInfGetBufferHostSize_16s_C3R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_Inf_16s_C3R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.104.2.28 NppStatus nppiNormRelInfGetBufferHostSize_16s_C4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_Inf_16s_C4R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.104.2.29 NppStatus nppiNormRelInfGetBufferHostSize_16u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_16u_AC4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.104.2.30 NppStatus nppiNormRelInfGetBufferHostSize_16u_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_16u_C1MR.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.104.2.31 NppStatus nppiNormRelInfGetBufferHostSize_16u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_16u_C1R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.104.2.32 NppStatus nppiNormRelInfGetBufferHostSize_16u_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_16u_C3CMR.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.104.2.33 NppStatus nppiNormRelInfGetBufferHostSize_16u_C3R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_Inf_16u_C3R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.104.2.34 NppStatus nppiNormRelInfGetBufferHostSize_16u_C4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_Inf_16u_C4R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.104.2.35 NppStatus nppiNormRelInfGetBufferHostSize_32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_Inf_32f_AC4R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.104.2.36 NppStatus nppiNormRelInfGetBufferHostSize_32f_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_32f_C1MR.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.104.2.37 NppStatus nppiNormRelInfGetBufferHostSize_32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_32f_C1R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.104.2.38 NppStatus nppiNormRelInfGetBufferHostSize_32f_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_32f_C3CMR.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.104.2.39 NppStatus nppiNormRelInfGetBufferHostSize_32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_32f_C3R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.104.2.40 NppStatus nppiNormRelInfGetBufferHostSize_32f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_Inf_32f_C4R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.104.2.41 NppStatus nppiNormRelInfGetBufferHostSize_32s_C1R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_Inf_32s_C1R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.104.2.42 NppStatus nppiNormRelInfGetBufferHostSize_8s_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_Inf_8s_C1MR*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.104.2.43 NppStatus nppiNormRelInfGetBufferHostSize_8s_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_8s_C3CMR.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.104.2.44 NppStatus nppiNormRelInfGetBufferHostSize_8u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_8u_AC4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.104.2.45 NppStatus nppiNormRelInfGetBufferHostSize_8u_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_8u_C1MR.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.104.2.46 NppStatus nppiNormRelInfGetBufferHostSize_8u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_Inf_8u_C1R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.104.2.47 NppStatus nppiNormRelInfGetBufferHostSize_8u_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_Inf_8u_C3CMR*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.104.2.48 NppStatus nppiNormRelInfGetBufferHostSize_8u_C3R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_Inf_8u_C3R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.104.2.49 NppStatus nppiNormRelInfGetBufferHostSize_8u_C4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_Inf_8u_C4R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.105 NormRel_L1

Primitives for computing the relative error of L1 norm between two images.

Basic NormRel_L1

- **NppStatus nppiNormRel_L1_8u_C1R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pNormRel, **Npp8u** *pDeviceBuffer)
One-channel 8-bit unsigned image NormRel_L1.
- **NppStatus nppiNormRel_L1_16u_C1R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pNormRel, **Npp8u** *pDeviceBuffer)
One-channel 16-bit unsigned image NormRel_L1.
- **NppStatus nppiNormRel_L1_16s_C1R** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pNormRel, **Npp8u** *pDeviceBuffer)
One-channel 16-bit signed image NormRel_L1.
- **NppStatus nppiNormRel_L1_32f_C1R** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pNormRel, **Npp8u** *pDeviceBuffer)
One-channel 32-bit floating point image NormRel_L1.
- **NppStatus nppiNormRel_L1_8u_C3R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormRel[3], **Npp8u** *pDeviceBuffer)
Three-channel 8-bit unsigned image NormRel_L1.
- **NppStatus nppiNormRel_L1_16u_C3R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormRel[3], **Npp8u** *pDeviceBuffer)
Three-channel 16-bit unsigned image NormRel_L1.
- **NppStatus nppiNormRel_L1_16s_C3R** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormRel[3], **Npp8u** *pDeviceBuffer)
Three-channel 16-bit signed image NormRel_L1.
- **NppStatus nppiNormRel_L1_32f_C3R** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormRel[3], **Npp8u** *pDeviceBuffer)
Three-channel 32-bit floating point image NormRel_L1.
- **NppStatus nppiNormRel_L1_8u_AC4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormRel[3], **Npp8u** *pDeviceBuffer)
Four-channel 8-bit signed image NormRel_L1 ignoring alpha channel.
- **NppStatus nppiNormRel_L1_16u_AC4R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormRel[3], **Npp8u** *pDeviceBuffer)
Four-channel 16-bit unsigned image NormRel_L1 ignoring alpha channel.
- **NppStatus nppiNormRel_L1_16s_AC4R** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormRel[3], **Npp8u** *pDeviceBuffer)
Four-channel 16-bit signed image NormRel_L1 ignoring alpha channel.

- `NppStatus nppiNormRel_L1_32f_AC4R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f *pSrc2`, int `nSrc2Step`, `NppiSize` `oSizeROI`, `Npp64f` `aNormRel[3]`, `Npp8u *pDeviceBuffer`)
Four-channel 32-bit floating point image NormRel_L1 ignoring alpha channel.
- `NppStatus nppiNormRel_L1_8u_C4R` (const `Npp8u *pSrc1`, int `nSrc1Step`, const `Npp8u *pSrc2`, int `nSrc2Step`, `NppiSize` `oSizeROI`, `Npp64f` `aNormRel[4]`, `Npp8u *pDeviceBuffer`)
Four-channel 8-bit unsigned image NormRel_L1.
- `NppStatus nppiNormRel_L1_16u_C4R` (const `Npp16u *pSrc1`, int `nSrc1Step`, const `Npp16u *pSrc2`, int `nSrc2Step`, `NppiSize` `oSizeROI`, `Npp64f` `aNormRel[4]`, `Npp8u *pDeviceBuffer`)
Four-channel 16-bit unsigned image NormRel_L1.
- `NppStatus nppiNormRel_L1_16s_C4R` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp16s *pSrc2`, int `nSrc2Step`, `NppiSize` `oSizeROI`, `Npp64f` `aNormRel[4]`, `Npp8u *pDeviceBuffer`)
Four-channel 16-bit signed image NormRel_L1.
- `NppStatus nppiNormRel_L1_32f_C4R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f *pSrc2`, int `nSrc2Step`, `NppiSize` `oSizeROI`, `Npp64f` `aNormRel[4]`, `Npp8u *pDeviceBuffer`)
Four-channel 32-bit floating point image NormRel_L1.

Masked NormRel_L1

See [Masked Operation](#).

- `NppStatus nppiNormRel_L1_8u_C1MR` (const `Npp8u *pSrc1`, int `nSrc1Step`, const `Npp8u *pSrc2`, int `nSrc2Step`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, `Npp64f *pNormRel`, `Npp8u *pDeviceBuffer`)
One-channel 8-bit unsigned image NormRel_L1.
- `NppStatus nppiNormRel_L1_8s_C1MR` (const `Npp8s *pSrc1`, int `nSrc1Step`, const `Npp8s *pSrc2`, int `nSrc2Step`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, `Npp64f *pNormRel`, `Npp8u *pDeviceBuffer`)
One-channel 8-bit signed image NormRel_L1.
- `NppStatus nppiNormRel_L1_16u_C1MR` (const `Npp16u *pSrc1`, int `nSrc1Step`, const `Npp16u *pSrc2`, int `nSrc2Step`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, `Npp64f *pNormRel`, `Npp8u *pDeviceBuffer`)
One-channel 16-bit unsigned image NormRel_L1.
- `NppStatus nppiNormRel_L1_32f_C1MR` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f *pSrc2`, int `nSrc2Step`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, `Npp64f *pNormRel`, `Npp8u *pDeviceBuffer`)
One-channel 32-bit floating point image NormRel_L1.

Masked Channel NormRel_L1

See [Masked Operation](#) and [Channel-of-Interest API](#).

- `NppStatus nppiNormRel_L1_8u_C3CMR` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, int nCOI, `Npp64f` *pNormRel, `Npp8u` *pDeviceBuffer)
Masked three-channel 8-bit unsigned image NormRel_L1 affecting only single channel.
- `NppStatus nppiNormRel_L1_8s_C3CMR` (const `Npp8s` *pSrc1, int nSrc1Step, const `Npp8s` *pSrc2, int nSrc2Step, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, int nCOI, `Npp64f` *pNormRel, `Npp8u` *pDeviceBuffer)
Masked three-channel 8-bit signed image NormRel_L1 affecting only single channel.
- `NppStatus nppiNormRel_L1_16u_C3CMR` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, int nCOI, `Npp64f` *pNormRel, `Npp8u` *pDeviceBuffer)
Masked three-channel 16-bit unsigned image NormRel_L1 affecting only single channel.
- `NppStatus nppiNormRel_L1_32f_C3CMR` (const `Npp32f` *pSrc1, int nSrc1Step, const `Npp32f` *pSrc2, int nSrc2Step, const `Npp8u` *pMask, int nMaskStep, `NppiSize` oSizeROI, int nCOI, `Npp64f` *pNormRel, `Npp8u` *pDeviceBuffer)
Masked three-channel 32-bit floating point image NormRel_L1 affecting only single channel.

NormRelL1GetBufferHostSize

Companion primitives for computing the device buffer size (in bytes) required by the NormRel_L1 primitives.

- `NppStatus nppiNormRelL1GetBufferHostSize_8u_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_8u_C1R.
- `NppStatus nppiNormRelL1GetBufferHostSize_16u_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_16u_C1R.
- `NppStatus nppiNormRelL1GetBufferHostSize_16s_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_16s_C1R.
- `NppStatus nppiNormRelL1GetBufferHostSize_32f_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_32f_C1R.
- `NppStatus nppiNormRelL1GetBufferHostSize_8u_C1MR` (`NppiSize` oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_8u_C1MR.
- `NppStatus nppiNormRelL1GetBufferHostSize_8s_C1MR` (`NppiSize` oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_8s_C1MR.
- `NppStatus nppiNormRelL1GetBufferHostSize_16u_C1MR` (`NppiSize` oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_16u_C1MR.

- **NppStatus** `nppiNormRelL1GetBufferHostSize_32f_C1MR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_32f_C1MR.
- **NppStatus** `nppiNormRelL1GetBufferHostSize_8u_C3R` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_8u_C3R.
- **NppStatus** `nppiNormRelL1GetBufferHostSize_16u_C3R` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_16u_C3R.
- **NppStatus** `nppiNormRelL1GetBufferHostSize_16s_C3R` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_16s_C3R.
- **NppStatus** `nppiNormRelL1GetBufferHostSize_32f_C3R` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_32f_C3R.
- **NppStatus** `nppiNormRelL1GetBufferHostSize_8u_C4R` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_8u_C4R.
- **NppStatus** `nppiNormRelL1GetBufferHostSize_16u_C4R` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_16u_C4R.
- **NppStatus** `nppiNormRelL1GetBufferHostSize_16s_C4R` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_16s_C4R.
- **NppStatus** `nppiNormRelL1GetBufferHostSize_32f_C4R` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_32f_C4R.
- **NppStatus** `nppiNormRelL1GetBufferHostSize_8u_AC4R` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_8u_AC4R.
- **NppStatus** `nppiNormRelL1GetBufferHostSize_16u_AC4R` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_16u_AC4R.
- **NppStatus** `nppiNormRelL1GetBufferHostSize_16s_AC4R` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_16s_AC4R.
- **NppStatus** `nppiNormRelL1GetBufferHostSize_32f_AC4R` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_32f_AC4R.
- **NppStatus** `nppiNormRelL1GetBufferHostSize_8u_C3CMR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_8u_C3CMR.
- **NppStatus** `nppiNormRelL1GetBufferHostSize_8s_C3CMR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)

Computes the device scratch buffer size (in bytes) for `nppiNormRel_L1_8s_C3CMR`.

- `NppStatus` `nppiNormRelL1GetBufferHostSize_16u_C3CMR` (`NppiSize` `oSizeROI`, `int` `*hpBufferSize`)

Computes the device scratch buffer size (in bytes) for `nppiNormRel_L1_16u_C3CMR`.

- `NppStatus` `nppiNormRelL1GetBufferHostSize_32f_C3CMR` (`NppiSize` `oSizeROI`, `int` `*hpBufferSize`)

Computes the device scratch buffer size (in bytes) for `nppiNormRel_L1_32f_C3CMR`.

7.105.1 Detailed Description

Primitives for computing the relative error of L1 norm between two images.

7.105.2 Function Documentation

7.105.2.1 `NppStatus nppiNormRel_L1_16s_AC4R` (`const Npp16s *pSrc1`, `int nSrc1Step`, `const Npp16s *pSrc2`, `int nSrc2Step`, `NppiSize oSizeROI`, `Npp64f aNormRel[3]`, `Npp8u *pDeviceBuffer`)

Four-channel 16-bit signed image NormRel_L1 ignoring alpha channel.

Parameters:

`pSrc1` Source-Image Pointer.

`nSrc1Step` Source-Image Line Step.

`pSrc2` Source-Image Pointer.

`nSrc2Step` Source-Image Line Step.

`oSizeROI` Region-of-Interest (ROI).

`aNormRel` Array that contains the computed relative error for the L1 norm of two images.

`pDeviceBuffer` Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use `nppiNormRelL1GetBufferHostSize_16s_AC4R` to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L1 norm of the second image is zero.

7.105.2.2 `NppStatus nppiNormRel_L1_16s_C1R` (`const Npp16s *pSrc1`, `int nSrc1Step`, `const Npp16s *pSrc2`, `int nSrc2Step`, `NppiSize oSizeROI`, `Npp64f *pNormRel`, `Npp8u *pDeviceBuffer`)

One-channel 16-bit signed image NormRel_L1.

Parameters:

`pSrc1` Source-Image Pointer.

`nSrc1Step` Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormRel Pointer to the computed relative error for the L1 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use `nppiNormRelL1GetBufferHostSize_16s_C1R` to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L1 norm of the second image is zero.

7.105.2.3 NppStatus nppiNormRel_L1_16s_C3R (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[3], Npp8u * pDeviceBuffer)

Three-channel 16-bit signed image NormRel_L1.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the L1 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use `nppiNormRelL1GetBufferHostSize_16s_C3R` to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L1 norm of the second image is zero.

7.105.2.4 NppStatus nppiNormRel_L1_16s_C4R (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[4], Npp8u * pDeviceBuffer)

Four-channel 16-bit signed image NormRel_L1.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the L1 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL1GetBufferHostSize_16s_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L1 norm of the second image is zero.

7.105.2.5 `NppStatus nppiNormRel_L1_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[3], Npp8u * pDeviceBuffer)`

Four-channel 16-bit unsigned image NormRel_L1 ignoring alpha channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the L1 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL1GetBufferHostSize_16u_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L1 norm of the second image is zero.

7.105.2.6 `NppStatus nppiNormRel_L1_16u_C1MR (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

One-channel 16-bit unsigned image NormRel_L1.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormRel Pointer to the computed relative error for the L1 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL1GetBufferHostSize_16u_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L1 norm of the second image is zero.

7.105.2.7 `NppStatus nppiNormRel_L1_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

One-channel 16-bit unsigned image NormRel_L1.

Parameters:

pSrc1 [Source-Image Pointer](#).

nSrc1Step [Source-Image Line Step](#).

pSrc2 [Source-Image Pointer](#).

nSrc2Step [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pNormRel [Pointer to the computed relative error for the L1 norm of two images](#).

pDeviceBuffer [Pointer to the required device memory allocation, Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL1GetBufferHostSize_16u_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L1 norm of the second image is zero.

7.105.2.8 `NppStatus nppiNormRel_L1_16u_C3CMR (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

Masked three-channel 16-bit unsigned image NormRel_L1 affecting only single channel.

Parameters:

pSrc1 [Source-Image Pointer](#).

nSrc1Step [Source-Image Line Step](#).

pSrc2 [Source-Image Pointer](#).

nSrc2Step [Source-Image Line Step](#).

pMask [Mask-Image Pointer](#).

nMaskStep [Mask-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

nCOI [Channel_of_Interest Number](#).

pNormRel [Pointer to the computed relative error for the L1 norm of two images](#).

pDeviceBuffer [Pointer to the required device memory allocation, Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL1GetBufferHostSize_16u_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified, or `NPP_DIVISOR_ERROR` if the L1 norm of the second image is zero.

7.105.2.9 NppStatus nppiNormRel_L1_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[3], Npp8u * pDeviceBuffer)

Three-channel 16-bit unsigned image NormRel_L1.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the L1 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL1GetBufferHostSize_16u_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L1 norm of the second image is zero.

7.105.2.10 NppStatus nppiNormRel_L1_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[4], Npp8u * pDeviceBuffer)

Four-channel 16-bit unsigned image NormRel_L1.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the L1 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL1GetBufferHostSize_16u_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L1 norm of the second image is zero.

7.105.2.11 NppStatus nppiNormRel_L1_32f_AC4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[3], Npp8u * pDeviceBuffer)

Four-channel 32-bit floating point image NormRel_L1 ignoring alpha channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the L1 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL1GetBufferHostSize_32f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), NPP_NOT_EVEN_STEP_ERROR if an invalid floating-point image is specified, or NPP_DIVISOR_ERROR if the L1 norm of the second image is zero.

7.105.2.12 NppStatus nppiNormRel_L1_32f_C1MR (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)

One-channel 32-bit floating point image NormRel_L1.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormRel Pointer to the computed relative error for the L1 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL1GetBufferHostSize_32f_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), NPP_NOT_EVEN_STEP_ERROR if an invalid floating-point image is specified, or NPP_DIVISOR_ERROR if the L1 norm of the second image is zero.

7.105.2.13 NppStatus nppiNormRel_L1_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)

One-channel 32-bit floating point image NormRel_L1.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- pNormRel* Pointer to the computed relative error for the L1 norm of two images.
- pDeviceBuffer* Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL1GetBufferHostSize_32f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), NPP_NOT_EVEN_STEP_ERROR if an invalid floating-point image is specified, or NPP_DIVISOR_ERROR if the L1 norm of the second image is zero.

7.105.2.14 NppStatus nppiNormRel_L1_32f_C3CMR (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)

Masked three-channel 32-bit floating point image NormRel_L1 affecting only single channel.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pMask* Mask-Image Pointer.
- nMaskStep* Mask-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nCOI* Channel_of_Interest Number.
- pNormRel* Pointer to the computed relative error for the L1 norm of two images.
- pDeviceBuffer* Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL1GetBufferHostSize_32f_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or NPP_COI_ERROR if an invalid channel of interest is specified, NPP_NOT_EVEN_STEP_ERROR if an invalid floating-point image is specified, or NPP_DIVISOR_ERROR if the L1 norm of the second image is zero.

7.105.2.15 NppStatus nppiNormRel_L1_32f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[3], Npp8u * pDeviceBuffer)

Three-channel 32-bit floating point image NormRel_L1.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the L1 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL1GetBufferHostSize_32f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), NPP_NOT_EVEN_STEP_ERROR if an invalid floating-point image is specified, or NPP_DIVISOR_ERROR if the L1 norm of the second image is zero.

7.105.2.16 NppStatus nppiNormRel_L1_32f_C4R (const Npp32f * *pSrc1*, int *nSrc1Step*, const Npp32f * *pSrc2*, int *nSrc2Step*, NppiSize *oSizeROI*, Npp64f *aNormRel*[4], Npp8u * *pDeviceBuffer*)

Four-channel 32-bit floating point image NormRel_L1.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the L1 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL1GetBufferHostSize_32f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), NPP_NOT_EVEN_STEP_ERROR if an invalid floating-point image is specified, or NPP_DIVISOR_ERROR if the L1 norm of the second image is zero.

7.105.2.17 NppStatus nppiNormRel_L1_8s_C1MR (const Npp8s * *pSrc1*, int *nSrc1Step*, const Npp8s * *pSrc2*, int *nSrc2Step*, const Npp8u * *pMask*, int *nMaskStep*, NppiSize *oSizeROI*, Npp64f * *pNormRel*, Npp8u * *pDeviceBuffer*)

One-channel 8-bit signed image NormRel_L1.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormRel Pointer to the computed relative error for the L1 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).

Use [nppiNormRelL1GetBufferHostSize_8s_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L1 norm of the second image is zero.

7.105.2.18 `NppStatus nppiNormRel_L1_8s_C3CMR (const Npp8s * pSrc1, int nSrc1Step, const Npp8s * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

Masked three-channel 8-bit signed image NormRel_L1 affecting only single channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNormRel Pointer to the computed relative error for the L1 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).

Use [nppiNormRelL1GetBufferHostSize_8s_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified, or `NPP_DIVISOR_ERROR` if the L1 norm of the second image is zero.

7.105.2.19 `NppStatus nppiNormRel_L1_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[3], Npp8u * pDeviceBuffer)`

Four-channel 8-bit signed image NormRel_L1 ignoring alpha channel.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- aNormRel* Array that contains the computed relative error for the L1 norm of two images.
- pDeviceBuffer* Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL1GetBufferHostSize_8u_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L1 norm of the second image is zero.

7.105.2.20 `NppStatus nppiNormRel_L1_8u_C1MR (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

One-channel 8-bit unsigned image NormRel_L1.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pMask* Mask-Image Pointer.
- nMaskStep* Mask-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- pNormRel* Pointer to the computed relative error for the L1 norm of two images.
- pDeviceBuffer* Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL1GetBufferHostSize_8u_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L1 norm of the second image is zero.

7.105.2.21 `NppStatus nppiNormRel_L1_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

One-channel 8-bit unsigned image NormRel_L1.

Parameters:

- pSrc1* Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormRel Pointer to the computed relative error for the norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL1GetBufferHostSize_8u_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L1 norm of the second image is zero.

7.105.2.22 `NppStatus nppiNormRel_L1_8u_C3CMR (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

Masked three-channel 8-bit unsigned image NormRel_L1 affecting only single channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNormRel Pointer to the computed relative error for the L1 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL1GetBufferHostSize_8u_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified, or `NPP_DIVISOR_ERROR` if the L1 norm of the second image is zero.

7.105.2.23 `NppStatus nppiNormRel_L1_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[3], Npp8u * pDeviceBuffer)`

Three-channel 8-bit unsigned image NormRel_L1.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the L1 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL1GetBufferHostSize_8u_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L1 norm of the second image is zero.

7.105.2.24 `NppStatus nppiNormRel_L1_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[4], Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image NormRel_L1.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the L1 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL1GetBufferHostSize_8u_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L1 norm of the second image is zero.

7.105.2.25 `NppStatus nppiNormRelL1GetBufferHostSize_16s_AC4R (NppiSize oSizeROI, int * hpBufferSize)`

Computes the device scratch buffer size (in bytes) for `nppiNormRel_L1_16s_AC4R`.

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.105.2.26 NppStatus nppiNormRelL1GetBufferHostSize_16s_C1R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_16s_C1R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.105.2.27 NppStatus nppiNormRelL1GetBufferHostSize_16s_C3R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_16s_C3R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.105.2.28 NppStatus nppiNormRelL1GetBufferHostSize_16s_C4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_16s_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.105.2.29 NppStatus nppiNormRelL1GetBufferHostSize_16u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_16u_AC4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.105.2.30 NppStatus nppiNormRelL1GetBufferHostSize_16u_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_L1_16u_C1MR*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.105.2.31 NppStatus nppiNormRelL1GetBufferHostSize_16u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_L1_16u_C1R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.105.2.32 NppStatus nppiNormRelL1GetBufferHostSize_16u_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_L1_16u_C3CMR*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.105.2.33 NppStatus nppiNormRelL1GetBufferHostSize_16u_C3R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_16u_C3R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.105.2.34 NppStatus nppiNormRelL1GetBufferHostSize_16u_C4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_16u_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.105.2.35 NppStatus nppiNormRelL1GetBufferHostSize_32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_32f_AC4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.105.2.36 NppStatus nppiNormRelL1GetBufferHostSize_32f_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_32f_C1MR.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.105.2.37 NppStatus nppiNormRelL1GetBufferHostSize_32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_L1_32f_C1R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.105.2.38 NppStatus nppiNormRelL1GetBufferHostSize_32f_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_L1_32f_C3CMR*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.105.2.39 NppStatus nppiNormRelL1GetBufferHostSize_32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_L1_32f_C3R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.105.2.40 NppStatus nppiNormRelL1GetBufferHostSize_32f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_32f_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.105.2.41 NppStatus nppiNormRelL1GetBufferHostSize_8s_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_8s_C1MR.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.105.2.42 NppStatus nppiNormRelL1GetBufferHostSize_8s_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_8s_C3CMR.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.105.2.43 NppStatus nppiNormRelL1GetBufferHostSize_8u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_8u_AC4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.105.2.44 NppStatus nppiNormRelL1GetBufferHostSize_8u_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_L1_8u_C1MR*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.105.2.45 NppStatus nppiNormRelL1GetBufferHostSize_8u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_L1_8u_C1R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.105.2.46 NppStatus nppiNormRelL1GetBufferHostSize_8u_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_L1_8u_C3CMR*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.105.2.47 NppStatus nppiNormRelL1GetBufferHostSize_8u_C3R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_8u_C3R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.105.2.48 NppStatus nppiNormRelL1GetBufferHostSize_8u_C4R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L1_8u_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.106 NormRel_L2

Primitives for computing the relative error of L2 norm between two images.

Basic NormRel_L2

- **NppStatus nppiNormRel_L2_8u_C1R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pNormRel, **Npp8u** *pDeviceBuffer)
One-channel 8-bit unsigned image NormRel_L2.
- **NppStatus nppiNormRel_L2_16u_C1R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pNormRel, **Npp8u** *pDeviceBuffer)
One-channel 16-bit unsigned image NormRel_L2.
- **NppStatus nppiNormRel_L2_16s_C1R** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pNormRel, **Npp8u** *pDeviceBuffer)
One-channel 16-bit signed image NormRel_L2.
- **NppStatus nppiNormRel_L2_32f_C1R** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pNormRel, **Npp8u** *pDeviceBuffer)
One-channel 32-bit floating point image NormRel_L2.
- **NppStatus nppiNormRel_L2_8u_C3R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormRel[3], **Npp8u** *pDeviceBuffer)
Three-channel 8-bit unsigned image NormRel_L2.
- **NppStatus nppiNormRel_L2_16u_C3R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormRel[3], **Npp8u** *pDeviceBuffer)
Three-channel 16-bit unsigned image NormRel_L2.
- **NppStatus nppiNormRel_L2_16s_C3R** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormRel[3], **Npp8u** *pDeviceBuffer)
Three-channel 16-bit signed image NormRel_L2.
- **NppStatus nppiNormRel_L2_32f_C3R** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormRel[3], **Npp8u** *pDeviceBuffer)
Three-channel 32-bit floating point image NormRel_L2.
- **NppStatus nppiNormRel_L2_8u_AC4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormRel[3], **Npp8u** *pDeviceBuffer)
Four-channel 8-bit unsigned image NormRel_L2 ignoring alpha channel.
- **NppStatus nppiNormRel_L2_16u_AC4R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormRel[3], **Npp8u** *pDeviceBuffer)
Four-channel 16-bit unsigned image NormRel_L2 ignoring alpha channel.
- **NppStatus nppiNormRel_L2_16s_AC4R** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aNormRel[3], **Npp8u** *pDeviceBuffer)
Four-channel 16-bit signed image NormRel_L2 ignoring alpha channel.

- `NppStatus nppiNormRel_L2_32f_AC4R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f *pSrc2`, int `nSrc2Step`, `NppiSize` `oSizeROI`, `Npp64f` `aNormRel[3]`, `Npp8u *pDeviceBuffer`)
Four-channel 32-bit floating point image NormRel_L2 ignoring alpha channel.
- `NppStatus nppiNormRel_L2_8u_C4R` (const `Npp8u *pSrc1`, int `nSrc1Step`, const `Npp8u *pSrc2`, int `nSrc2Step`, `NppiSize` `oSizeROI`, `Npp64f` `aNormRel[4]`, `Npp8u *pDeviceBuffer`)
Four-channel 8-bit unsigned image NormRel_L2.
- `NppStatus nppiNormRel_L2_16u_C4R` (const `Npp16u *pSrc1`, int `nSrc1Step`, const `Npp16u *pSrc2`, int `nSrc2Step`, `NppiSize` `oSizeROI`, `Npp64f` `aNormRel[4]`, `Npp8u *pDeviceBuffer`)
Four-channel 16-bit unsigned image NormRel_L2.
- `NppStatus nppiNormRel_L2_16s_C4R` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp16s *pSrc2`, int `nSrc2Step`, `NppiSize` `oSizeROI`, `Npp64f` `aNormRel[4]`, `Npp8u *pDeviceBuffer`)
Four-channel 16-bit signed image NormRel_L2.
- `NppStatus nppiNormRel_L2_32f_C4R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f *pSrc2`, int `nSrc2Step`, `NppiSize` `oSizeROI`, `Npp64f` `aNormRel[4]`, `Npp8u *pDeviceBuffer`)
Four-channel 32-bit floating point image NormRel_L2.

Masked NormRel_L2

See [Masked Operation](#).

- `NppStatus nppiNormRel_L2_8u_C1MR` (const `Npp8u *pSrc1`, int `nSrc1Step`, const `Npp8u *pSrc2`, int `nSrc2Step`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, `Npp64f *pNormRel`, `Npp8u *pDeviceBuffer`)
Masked one-channel 8-bit unsigned image NormRel_L2.
- `NppStatus nppiNormRel_L2_8s_C1MR` (const `Npp8s *pSrc1`, int `nSrc1Step`, const `Npp8s *pSrc2`, int `nSrc2Step`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, `Npp64f *pNormRel`, `Npp8u *pDeviceBuffer`)
Masked one-channel 8-bit signed image NormRel_L2.
- `NppStatus nppiNormRel_L2_16u_C1MR` (const `Npp16u *pSrc1`, int `nSrc1Step`, const `Npp16u *pSrc2`, int `nSrc2Step`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, `Npp64f *pNormRel`, `Npp8u *pDeviceBuffer`)
Masked one-channel 16-bit unsigned image NormRel_L2.
- `NppStatus nppiNormRel_L2_32f_C1MR` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f *pSrc2`, int `nSrc2Step`, const `Npp8u *pMask`, int `nMaskStep`, `NppiSize` `oSizeROI`, `Npp64f *pNormRel`, `Npp8u *pDeviceBuffer`)
Masked one-channel 32-bit floating point image NormRel_L2.

Masked Channel NormRel_L2

See [Masked Operation](#) and [Channel-of-Interest API](#).

- **NppStatus nppiNormRel_L2_8u_C3CMR** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, const **Npp8u** *pMask, int nMaskStep, **NppiSize** oSizeROI, int nCOI, **Npp64f** *pNormRel, **Npp8u** *pDeviceBuffer)
Masked three-channel 8-bit unsigned image NormRel_L2 affecting only single channel.
- **NppStatus nppiNormRel_L2_8s_C3CMR** (const **Npp8s** *pSrc1, int nSrc1Step, const **Npp8s** *pSrc2, int nSrc2Step, const **Npp8u** *pMask, int nMaskStep, **NppiSize** oSizeROI, int nCOI, **Npp64f** *pNormRel, **Npp8u** *pDeviceBuffer)
Masked three-channel 8-bit signed image NormRel_L2 affecting only single channel.
- **NppStatus nppiNormRel_L2_16u_C3CMR** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, const **Npp8u** *pMask, int nMaskStep, **NppiSize** oSizeROI, int nCOI, **Npp64f** *pNormRel, **Npp8u** *pDeviceBuffer)
Masked three-channel 16-bit unsigned image NormRel_L2 affecting only single channel.
- **NppStatus nppiNormRel_L2_32f_C3CMR** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, const **Npp8u** *pMask, int nMaskStep, **NppiSize** oSizeROI, int nCOI, **Npp64f** *pNormRel, **Npp8u** *pDeviceBuffer)
Masked three-channel 32-bit floating point image NormRel_L2 affecting only single channel.

NormRelL2GetBufferHostSize

Companion primitives for computing the device buffer size (in bytes) required by the NormRel_L2 primitives.

- **NppStatus nppiNormRelL2GetBufferHostSize_8u_C1R** (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_8u_C1R.
- **NppStatus nppiNormRelL2GetBufferHostSize_16u_C1R** (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_16u_C1R.
- **NppStatus nppiNormRelL2GetBufferHostSize_16s_C1R** (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_16s_C1R.
- **NppStatus nppiNormRelL2GetBufferHostSize_32f_C1R** (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_32f_C1R.
- **NppStatus nppiNormRelL2GetBufferHostSize_8u_C1MR** (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_8u_C1MR.
- **NppStatus nppiNormRelL2GetBufferHostSize_8s_C1MR** (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_8s_C1MR.
- **NppStatus nppiNormRelL2GetBufferHostSize_16u_C1MR** (**NppiSize** oSizeROI, int *hpBufferSize)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_16u_C1MR.

- **NppStatus** [nppiNormRelL2GetBufferHostSize_32f_C1MR](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_32f_C1MR.
- **NppStatus** [nppiNormRelL2GetBufferHostSize_8u_C3R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_8u_C3R.
- **NppStatus** [nppiNormRelL2GetBufferHostSize_16u_C3R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_16u_C3R.
- **NppStatus** [nppiNormRelL2GetBufferHostSize_16s_C3R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_16s_C3R.
- **NppStatus** [nppiNormRelL2GetBufferHostSize_32f_C3R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_32f_C3R.
- **NppStatus** [nppiNormRelL2GetBufferHostSize_8u_C4R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_8u_C4R.
- **NppStatus** [nppiNormRelL2GetBufferHostSize_16u_C4R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_16u_C4R.
- **NppStatus** [nppiNormRelL2GetBufferHostSize_16s_C4R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_16s_C4R.
- **NppStatus** [nppiNormRelL2GetBufferHostSize_32f_C4R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_32f_C4R.
- **NppStatus** [nppiNormRelL2GetBufferHostSize_8u_AC4R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_8u_AC4R.
- **NppStatus** [nppiNormRelL2GetBufferHostSize_16u_AC4R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_16u_AC4R.
- **NppStatus** [nppiNormRelL2GetBufferHostSize_16s_AC4R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_16s_AC4R.
- **NppStatus** [nppiNormRelL2GetBufferHostSize_32f_AC4R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_32f_AC4R.
- **NppStatus** [nppiNormRelL2GetBufferHostSize_8u_C3CMR](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)
Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_8u_C3CMR.
- **NppStatus** [nppiNormRelL2GetBufferHostSize_8s_C3CMR](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_8s_C3CMR.

- **NppStatus** `nppiNormRelL2GetBufferHostSize_16u_C3CMR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_16u_C3CMR.

- **NppStatus** `nppiNormRelL2GetBufferHostSize_32f_C3CMR` (**NppiSize** `oSizeROI`, **int** `*hpBufferSize`)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_32f_C3CMR.

7.106.1 Detailed Description

Primitives for computing the relative error of L2 norm between two images.

7.106.2 Function Documentation

7.106.2.1 **NppStatus** `nppiNormRel_L2_16s_AC4R` (**const** **Npp16s** `*pSrc1`, **int** `nSrc1Step`, **const** **Npp16s** `*pSrc2`, **int** `nSrc2Step`, **NppiSize** `oSizeROI`, **Npp64f** `aNormRel[3]`, **Npp8u** `*pDeviceBuffer`)

Four-channel 16-bit signed image NormRel_L2 ignoring alpha channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the L2 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use `nppiNormRelL2GetBufferHostSize_16s_AC4R` to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L2 norm of the second image is zero.

7.106.2.2 **NppStatus** `nppiNormRel_L2_16s_C1R` (**const** **Npp16s** `*pSrc1`, **int** `nSrc1Step`, **const** **Npp16s** `*pSrc2`, **int** `nSrc2Step`, **NppiSize** `oSizeROI`, **Npp64f** `*pNormRel`, **Npp8u** `*pDeviceBuffer`)

One-channel 16-bit signed image NormRel_L2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormRel Pointer to the computed relative error for the L2 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use `nppiNormRelL2GetBufferHostSize_16s_C1R` to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L2 norm of the second image is zero.

7.106.2.3 `NppStatus nppiNormRel_L2_16s_C3R (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[3], Npp8u * pDeviceBuffer)`

Three-channel 16-bit signed image NormRel_L2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the L2 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use `nppiNormRelL2GetBufferHostSize_16s_C3R` to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L2 norm of the second image is zero.

7.106.2.4 `NppStatus nppiNormRel_L2_16s_C4R (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[4], Npp8u * pDeviceBuffer)`

Four-channel 16-bit signed image NormRel_L2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the L2 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL2GetBufferHostSize_16s_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L2 norm of the second image is zero.

7.106.2.5 `NppStatus nppiNormRel_L2_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[3], Npp8u * pDeviceBuffer)`

Four-channel 16-bit unsigned image NormRel_L2 ignoring alpha channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the L2 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL2GetBufferHostSize_16u_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L2 norm of the second image is zero.

7.106.2.6 `NppStatus nppiNormRel_L2_16u_C1MR (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

Masked one-channel 16-bit unsigned image NormRel_L2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormRel Pointer to the computed relative error for the L2 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL2GetBufferHostSize_16u_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L2 norm of the second image is zero.

7.106.2.7 `NppStatus nppiNormRel_L2_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

One-channel 16-bit unsigned image NormRel_L2.

Parameters:

pSrc1 [Source-Image Pointer](#).

nSrc1Step [Source-Image Line Step](#).

pSrc2 [Source-Image Pointer](#).

nSrc2Step [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pNormRel Pointer to the computed relative error for the L2 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL2GetBufferHostSize_16u_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L2 norm of the second image is zero.

7.106.2.8 `NppStatus nppiNormRel_L2_16u_C3CMR (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

Masked three-channel 16-bit unsigned image NormRel_L2 affecting only single channel.

Parameters:

pSrc1 [Source-Image Pointer](#).

nSrc1Step [Source-Image Line Step](#).

pSrc2 [Source-Image Pointer](#).

nSrc2Step [Source-Image Line Step](#).

pMask [Mask-Image Pointer](#).

nMaskStep [Mask-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

nCOI [Channel_of_Interest Number](#).

pNormRel Pointer to the computed relative error for the L2 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL2GetBufferHostSize_16u_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), `NPP_COI_ERROR` if an invalid channel of interest is specified, or `NPP_DIVISOR_ERROR` if the L2 norm of the second image is zero.

7.106.2.9 `NppStatus nppiNormRel_L2_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[3], Npp8u * pDeviceBuffer)`

Three-channel 16-bit unsigned image NormRel_L2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the L2 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL2GetBufferHostSize_16u_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L2 norm of the second image is zero.

7.106.2.10 `NppStatus nppiNormRel_L2_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[4], Npp8u * pDeviceBuffer)`

Four-channel 16-bit unsigned image NormRel_L2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the L2 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL2GetBufferHostSize_16u_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L2 norm of the second image is zero.

7.106.2.11 `NppStatus nppiNormRel_L2_32f_AC4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[3], Npp8u * pDeviceBuffer)`

Four-channel 32-bit floating point image NormRel_L2 ignoring alpha channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the L2 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL2GetBufferHostSize_32f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), NPP_NOT_EVEN_STEP_ERROR if an invalid floating-point image is specified, or NPP_DIVISOR_ERROR if the L2 norm of the second image is zero.

7.106.2.12 `NppStatus nppiNormRel_L2_32f_C1MR (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

Masked one-channel 32-bit floating point image NormRel_L2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormRel Pointer to the computed relative error for the L2 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL2GetBufferHostSize_32f_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), NPP_NOT_EVEN_STEP_ERROR if an invalid floating-point image is specified, or NPP_DIVISOR_ERROR if the L2 norm of the second image is zero.

7.106.2.13 `NppStatus nppiNormRel_L2_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

One-channel 32-bit floating point image NormRel_L2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormRel Pointer to the computed relative error for the L2 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL2GetBufferHostSize_32f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), NPP_NOT_EVEN_STEP_ERROR if an invalid floating-point image is specified, or NPP_DIVISOR_ERROR if the L2 norm of the second image is zero.

7.106.2.14 NppStatus nppiNormRel_L2_32f_C3CMR (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)

Masked three-channel 32-bit floating point image NormRel_L2 affecting only single channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNormRel Pointer to the computed relative error for the L2 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL2GetBufferHostSize_32f_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), NPP_COI_ERROR if an invalid channel of interest is specified, or NPP_NOT_EVEN_STEP_ERROR if an invalid floating-point image is specified, or NPP_DIVISOR_ERROR if the L2 norm of the second image is zero.

7.106.2.15 NppStatus nppiNormRel_L2_32f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[3], Npp8u * pDeviceBuffer)

Three-channel 32-bit floating point image NormRel_L2.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).
aNormRel Array that contains the computed relative error for the L2 norm of two images.
pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
 Use [nppiNormRelL2GetBufferHostSize_32f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), NPP_NOT_EVEN_STEP_ERROR if an invalid floating-point image is specified, or NPP_DIVISOR_ERROR if the L2 norm of the second image is zero.

7.106.2.16 `NppStatus nppiNormRel_L2_32f_C4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[4], Npp8u * pDeviceBuffer)`

Four-channel 32-bit floating point image NormRel_L2.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).
aNormRel Array that contains the computed relative error for the L2 norm of two images.
pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
 Use [nppiNormRelL2GetBufferHostSize_32f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or NPP_NOT_EVEN_STEP_ERROR if an invalid floating-point image is specified, or NPP_DIVISOR_ERROR if the L2 norm of the second image is zero.

7.106.2.17 `NppStatus nppiNormRel_L2_8s_C1MR (const Npp8s * pSrc1, int nSrc1Step, const Npp8s * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

Masked one-channel 8-bit signed image NormRel_L2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormRel Pointer to the computed relative error for the L2 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).

Use [nppiNormRelL2GetBufferHostSize_8s_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L2 norm of the second image is zero.

7.106.2.18 `NppStatus nppiNormRel_L2_8s_C3CMR (const Npp8s * pSrc1, int nSrc1Step, const Npp8s * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

Masked three-channel 8-bit signed image NormRel_L2 affecting only single channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNormRel Pointer to the computed relative error for the L2 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).

Use [nppiNormRelL2GetBufferHostSize_8s_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified, or `NPP_DIVISOR_ERROR` if the L2 norm of the second image is zero.

7.106.2.19 `NppStatus nppiNormRel_L2_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[3], Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image NormRel_L2 ignoring alpha channel.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- aNormRel* Array that contains the computed relative error for the L2 norm of two images.
- pDeviceBuffer* Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL2GetBufferHostSize_8u_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L2 norm of the second image is zero.

7.106.2.20 `NppStatus nppiNormRel_L2_8u_C1MR (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

Masked one-channel 8-bit unsigned image NormRel_L2.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pMask* Mask-Image Pointer.
- nMaskStep* Mask-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- pNormRel* Pointer to the computed relative error for the L2 norm of two images.
- pDeviceBuffer* Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL2GetBufferHostSize_8u_C1MR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L2 norm of the second image is zero.

7.106.2.21 `NppStatus nppiNormRel_L2_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

One-channel 8-bit unsigned image NormRel_L2.

Parameters:

- pSrc1* Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pNormRel Pointer to the computed relative error for the L2 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL2GetBufferHostSize_8u_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L2 norm of the second image is zero.

7.106.2.22 `NppStatus nppiNormRel_L2_8u_C3CMR (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, NppiSize oSizeROI, int nCOI, Npp64f * pNormRel, Npp8u * pDeviceBuffer)`

Masked three-channel 8-bit unsigned image NormRel_L2 affecting only single channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nCOI Channel_of_Interest Number.

pNormRel Pointer to the computed relative error for the L2 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL2GetBufferHostSize_8u_C3CMR](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_COI_ERROR` if an invalid channel of interest is specified, or `NPP_DIVISOR_ERROR` if the L2 norm of the second image is zero.

7.106.2.23 `NppStatus nppiNormRel_L2_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[3], Npp8u * pDeviceBuffer)`

Three-channel 8-bit unsigned image NormRel_L2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the L2 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL2GetBufferHostSize_8u_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L2 norm of the second image is zero.

7.106.2.24 `NppStatus nppiNormRel_L2_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aNormRel[4], Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image NormRel_L2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aNormRel Array that contains the computed relative error for the L2 norm of two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiNormRelL2GetBufferHostSize_8u_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_DIVISOR_ERROR` if the L2 norm of the second image is zero.

7.106.2.25 `NppStatus nppiNormRelL2GetBufferHostSize_16s_AC4R (NppiSize oSizeROI, int * hpBufferSize)`

Computes the device scratch buffer size (in bytes) for `nppiNormRel_L2_16s_AC4R`.

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: `hpBufferSize` is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if `hpBufferSize` is 0 (NULL), [ROI Related Error Codes](#).

7.106.2.26 NppStatus nppiNormRelL2GetBufferHostSize_16s_C1R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_16s_C1R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.106.2.27 NppStatus nppiNormRelL2GetBufferHostSize_16s_C3R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_16s_C3R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.106.2.28 NppStatus nppiNormRelL2GetBufferHostSize_16s_C4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_16s_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.106.2.29 NppStatus nppiNormRelL2GetBufferHostSize_16u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_16u_AC4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.106.2.30 NppStatus nppiNormRelL2GetBufferHostSize_16u_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_L2_16u_C1MR*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.106.2.31 NppStatus nppiNormRelL2GetBufferHostSize_16u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_L2_16u_C1R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.106.2.32 NppStatus nppiNormRelL2GetBufferHostSize_16u_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_L2_16u_C3CMR*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.106.2.33 NppStatus nppiNormRelL2GetBufferHostSize_16u_C3R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_16u_C3R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.106.2.34 NppStatus nppiNormRelL2GetBufferHostSize_16u_C4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_16u_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.106.2.35 NppStatus nppiNormRelL2GetBufferHostSize_32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_32f_AC4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.106.2.36 NppStatus nppiNormRelL2GetBufferHostSize_32f_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_32f_C1MR.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.106.2.37 NppStatus nppiNormRelL2GetBufferHostSize_32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_L2_32f_C1R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.106.2.38 NppStatus nppiNormRelL2GetBufferHostSize_32f_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_L2_32f_C3CMR*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.106.2.39 NppStatus nppiNormRelL2GetBufferHostSize_32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_L2_32f_C3R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.106.2.40 NppStatus nppiNormRelL2GetBufferHostSize_32f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_32f_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.106.2.41 NppStatus nppiNormRelL2GetBufferHostSize_8s_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_8s_C1MR.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.106.2.42 NppStatus nppiNormRelL2GetBufferHostSize_8s_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_8s_C3CMR.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.106.2.43 NppStatus nppiNormRelL2GetBufferHostSize_8u_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_8u_AC4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.106.2.44 NppStatus nppiNormRelL2GetBufferHostSize_8u_C1MR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_L2_8u_C1MR*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.106.2.45 NppStatus nppiNormRelL2GetBufferHostSize_8u_C1R (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_L2_8u_C1R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.106.2.46 NppStatus nppiNormRelL2GetBufferHostSize_8u_C3CMR (NppiSize oSizeROI, int * hpBufferSize)

Computes the device scratch buffer size (in bytes) for *nppiNormRel_L2_8u_C3CMR*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.106.2.47 NppStatus nppiNormRelL2GetBufferHostSize_8u_C3R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_8u_C3R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.106.2.48 NppStatus nppiNormRelL2GetBufferHostSize_8u_C4R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Computes the device scratch buffer size (in bytes) for nppiNormRel_L2_8u_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107 DotProd

Primitives for computing the dot product of two images.

DotProd

Given two images $pSrc1$ and $pSrc2$ both with width W and height H , the dot product will be computed as

$$DotProd = \sum_{j=0}^{H-1} \sum_{i=0}^{W-1} [pSrc1(j, i) \cdot pSrc2(j, i)]$$

The functions require additional scratch buffer for computations.

- **NppStatus nppiDotProd_8u64f_C1R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pDp, **Npp8u** *pDeviceBuffer)
One-channel 8-bit unsigned image DotProd.
- **NppStatus nppiDotProd_8s64f_C1R** (const **Npp8s** *pSrc1, int nSrc1Step, const **Npp8s** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pDp, **Npp8u** *pDeviceBuffer)
One-channel 8-bit signed image DotProd.
- **NppStatus nppiDotProd_16u64f_C1R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pDp, **Npp8u** *pDeviceBuffer)
One-channel 16-bit unsigned image DotProd.
- **NppStatus nppiDotProd_16s64f_C1R** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pDp, **Npp8u** *pDeviceBuffer)
One-channel 16-bit signed image DotProd.
- **NppStatus nppiDotProd_32u64f_C1R** (const **Npp32u** *pSrc1, int nSrc1Step, const **Npp32u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pDp, **Npp8u** *pDeviceBuffer)
One-channel 32-bit unsigned image DotProd.
- **NppStatus nppiDotProd_32s64f_C1R** (const **Npp32s** *pSrc1, int nSrc1Step, const **Npp32s** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pDp, **Npp8u** *pDeviceBuffer)
One-channel 32-bit signed image DotProd.
- **NppStatus nppiDotProd_32f64f_C1R** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** *pDp, **Npp8u** *pDeviceBuffer)
One-channel 32-bit floating point image DotProd.
- **NppStatus nppiDotProd_8u64f_C3R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aDp[3], **Npp8u** *pDeviceBuffer)
Three-channel 8-bit unsigned image DotProd.
- **NppStatus nppiDotProd_8s64f_C3R** (const **Npp8s** *pSrc1, int nSrc1Step, const **Npp8s** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aDp[3], **Npp8u** *pDeviceBuffer)
Three-channel 8-bit signed image DotProd.
- **NppStatus nppiDotProd_16u64f_C3R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **NppiSize** oSizeROI, **Npp64f** aDp[3], **Npp8u** *pDeviceBuffer)

Three-channel 16-bit unsigned image DotProd.

- `NppStatus nppiDotProd_16s64f_C3R` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` aDp[3], `Npp8u` *pDeviceBuffer)

Three-channel 16-bit signed image DotProd.

- `NppStatus nppiDotProd_32u64f_C3R` (const `Npp32u` *pSrc1, int nSrc1Step, const `Npp32u` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` aDp[3], `Npp8u` *pDeviceBuffer)

Three-channel 32-bit unsigned image DotProd.

- `NppStatus nppiDotProd_32s64f_C3R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` aDp[3], `Npp8u` *pDeviceBuffer)

Three-channel 32-bit signed image DotProd.

- `NppStatus nppiDotProd_32f64f_C3R` (const `Npp32f` *pSrc1, int nSrc1Step, const `Npp32f` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` aDp[3], `Npp8u` *pDeviceBuffer)

Three-channel 32-bit floating point image DotProd.

- `NppStatus nppiDotProd_8u64f_C4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` aDp[4], `Npp8u` *pDeviceBuffer)

Four-channel 8-bit unsigned image DotProd.

- `NppStatus nppiDotProd_8s64f_C4R` (const `Npp8s` *pSrc1, int nSrc1Step, const `Npp8s` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` aDp[4], `Npp8u` *pDeviceBuffer)

Four-channel 8-bit signed image DotProd.

- `NppStatus nppiDotProd_16u64f_C4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` aDp[4], `Npp8u` *pDeviceBuffer)

Four-channel 16-bit unsigned image DotProd.

- `NppStatus nppiDotProd_16s64f_C4R` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` aDp[4], `Npp8u` *pDeviceBuffer)

Four-channel 16-bit signed image DotProd.

- `NppStatus nppiDotProd_32u64f_C4R` (const `Npp32u` *pSrc1, int nSrc1Step, const `Npp32u` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` aDp[4], `Npp8u` *pDeviceBuffer)

Four-channel 32-bit unsigned image DotProd.

- `NppStatus nppiDotProd_32s64f_C4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` aDp[4], `Npp8u` *pDeviceBuffer)

Four-channel 32-bit signed image DotProd.

- `NppStatus nppiDotProd_32f64f_C4R` (const `Npp32f` *pSrc1, int nSrc1Step, const `Npp32f` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` aDp[4], `Npp8u` *pDeviceBuffer)

Four-channel 32-bit floating point image DotProd.

- `NppStatus nppiDotProd_8u64f_AC4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` aDp[3], `Npp8u` *pDeviceBuffer)

Four-channel 8-bit unsigned image DotProd ignoring alpha channel.

- `NppStatus nppiDotProd_8s64f_AC4R` (const `Npp8s` *pSrc1, int nSrc1Step, const `Npp8s` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` aDp[3], `Npp8u` *pDeviceBuffer)
Four-channel 8-bit signed image DotProd ignoring alpha channel.
- `NppStatus nppiDotProd_16u64f_AC4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` aDp[3], `Npp8u` *pDeviceBuffer)
Four-channel 16-bit unsigned image DotProd ignoring alpha channel.
- `NppStatus nppiDotProd_16s64f_AC4R` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` aDp[3], `Npp8u` *pDeviceBuffer)
Four-channel 16-bit signed image DotProd ignoring alpha channel.
- `NppStatus nppiDotProd_32u64f_AC4R` (const `Npp32u` *pSrc1, int nSrc1Step, const `Npp32u` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` aDp[3], `Npp8u` *pDeviceBuffer)
Four-channel 32-bit unsigned image DotProd ignoring alpha channel.
- `NppStatus nppiDotProd_32s64f_AC4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` aDp[3], `Npp8u` *pDeviceBuffer)
Four-channel 32-bit signed image DotProd ignoring alpha channel.
- `NppStatus nppiDotProd_32f64f_AC4R` (const `Npp32f` *pSrc1, int nSrc1Step, const `Npp32f` *pSrc2, int nSrc2Step, `NppiSize` oSizeROI, `Npp64f` aDp[3], `Npp8u` *pDeviceBuffer)
Four-channel 32-bit floating point image DotProd ignoring alpha channel.

DotProdGetBufferHostSize

Companion primitives for computing the device buffer size (in bytes) required by the Mean_StdDev primitives.

- `NppStatus nppiDotProdGetBufferHostSize_8u64f_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppiDotProd_8u64f_C1R.
- `NppStatus nppiDotProdGetBufferHostSize_8s64f_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppiDotProd_8s64f_C1R.
- `NppStatus nppiDotProdGetBufferHostSize_16u64f_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppiDotProd_16u64f_C1R.
- `NppStatus nppiDotProdGetBufferHostSize_16s64f_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppiDotProd_16s64f_C1R.
- `NppStatus nppiDotProdGetBufferHostSize_32u64f_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppiDotProd_32u64f_C1R.
- `NppStatus nppiDotProdGetBufferHostSize_32s64f_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppiDotProd_32s64f_C1R.
- `NppStatus nppiDotProdGetBufferHostSize_32f64f_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppiDotProd_32f64f_C1R.

- [NppStatus nppiDotProdGetBufferHostSize_8u64f_C3R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppiDotProd_8u64f_C3R.
- [NppStatus nppiDotProdGetBufferHostSize_8s64f_C3R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppiDotProd_8s64f_C3R.
- [NppStatus nppiDotProdGetBufferHostSize_16u64f_C3R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppiDotProd_16u64f_C3R.
- [NppStatus nppiDotProdGetBufferHostSize_16s64f_C3R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppiDotProd_16s64f_C3R.
- [NppStatus nppiDotProdGetBufferHostSize_32u64f_C3R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppiDotProd_32u64f_C3R.
- [NppStatus nppiDotProdGetBufferHostSize_32s64f_C3R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppiDotProd_32s64f_C3R.
- [NppStatus nppiDotProdGetBufferHostSize_32f64f_C3R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppiDotProd_32f64f_C3R.
- [NppStatus nppiDotProdGetBufferHostSize_8u64f_C4R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppiDotProd_8u64f_C4R.
- [NppStatus nppiDotProdGetBufferHostSize_8s64f_C4R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppiDotProd_8s64f_C4R.
- [NppStatus nppiDotProdGetBufferHostSize_16u64f_C4R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppiDotProd_16u64f_C4R.
- [NppStatus nppiDotProdGetBufferHostSize_16s64f_C4R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppiDotProd_16s64f_C4R.
- [NppStatus nppiDotProdGetBufferHostSize_32u64f_C4R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppiDotProd_32u64f_C4R.
- [NppStatus nppiDotProdGetBufferHostSize_32s64f_C4R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppiDotProd_32s64f_C4R.
- [NppStatus nppiDotProdGetBufferHostSize_32f64f_C4R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppiDotProd_32f64f_C4R.
- [NppStatus nppiDotProdGetBufferHostSize_8u64f_AC4R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppiDotProd_8u64f_AC4R.
- [NppStatus nppiDotProdGetBufferHostSize_8s64f_AC4R](#) ([NppiSize](#) oSizeROI, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppiDotProd_8s64f_AC4R.

- **NppStatus** [nppiDotProdGetBufferHostSize_16u64f_AC4R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)
Device scratch buffer size (in bytes) for nppiDotProd_16u64f_AC4R.
- **NppStatus** [nppiDotProdGetBufferHostSize_16s64f_AC4R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)
Device scratch buffer size (in bytes) for nppiDotProd_16s64f_AC4R.
- **NppStatus** [nppiDotProdGetBufferHostSize_32u64f_AC4R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)
Device scratch buffer size (in bytes) for nppiDotProd_32u64f_AC4R.
- **NppStatus** [nppiDotProdGetBufferHostSize_32s64f_AC4R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)
Device scratch buffer size (in bytes) for nppiDotProd_32s64f_AC4R.
- **NppStatus** [nppiDotProdGetBufferHostSize_32f64f_AC4R](#) (**NppiSize** **oSizeROI**, **int** ***hpBufferSize**)
Device scratch buffer size (in bytes) for nppiDotProd_32f64f_AC4R.

7.107.1 Detailed Description

Primitives for computing the dot product of two images.

7.107.2 Function Documentation

7.107.2.1 **NppStatus** [nppiDotProd_16s64f_AC4R](#) (**const Npp16s** * *pSrc1*, **int** *nSrc1Step*, **const Npp16s** * *pSrc2*, **int** *nSrc2Step*, **NppiSize** *oSizeROI*, **Npp64f** *aDp*[3], **Npp8u** * *pDeviceBuffer*)

Four-channel 16-bit signed image DotProd ignoring alpha channel.

Parameters:

pSrc1 [Source-Image Pointer](#).

nSrc1Step [Source-Image Line Step](#).

pSrc2 [Source-Image Pointer](#).

nSrc2Step [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aDp Array that contains the computed dot product of the two images.

pDeviceBuffer [Pointer to the required device memory allocation](#), [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_16s64f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.2 `NppStatus nppiDotProd_16s64f_C1R (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pDp, Npp8u * pDeviceBuffer)`

One-channel 16-bit signed image DotProd.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDp Pointer to the computed dot product of the two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_16s64f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.3 `NppStatus nppiDotProd_16s64f_C3R (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aDp[3], Npp8u * pDeviceBuffer)`

Three-channel 16-bit signed image DotProd.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDp Array that contains the computed dot product of the two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_16s64f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.4 `NppStatus nppiDotProd_16s64f_C4R (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aDp[4], Npp8u * pDeviceBuffer)`

Four-channel 16-bit signed image DotProd.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).
aDp Array that contains the computed dot product of the two images.
pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
 Use [nppiDotProdGetBufferHostSize_16s64f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.5 `NppStatus nppiDotProd_16u64f_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aDp[3], Npp8u * pDeviceBuffer)`

Four-channel 16-bit unsigned image DotProd ignoring alpha channel.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).
aDp Array that contains the computed Inf-norm of differences.
pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
 Use [nppiDotProdGetBufferHostSize_16u64f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.6 `NppStatus nppiDotProd_16u64f_C1R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pDp, Npp8u * pDeviceBuffer)`

One-channel 16-bit unsigned image DotProd.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDp Pointer to the computed dot product of the two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_16u64f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.7 `NppStatus nppiDotProd_16u64f_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aDp[3], Npp8u * pDeviceBuffer)`

Three-channel 16-bit unsigned image DotProd.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDp Array that contains the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_16u64f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.8 `NppStatus nppiDotProd_16u64f_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aDp[4], Npp8u * pDeviceBuffer)`

Four-channel 16-bit unsigned image DotProd.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDp Array that contains the computed Inf-norm of differences.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_16u64f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.9 `NppStatus nppiDotProd_32f64f_AC4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aDp[3], Npp8u * pDeviceBuffer)`

Four-channel 32-bit floating point image DotProd ignoring alpha channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDp Array that contains the computed dot product of the two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_32f64f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.10 `NppStatus nppiDotProd_32f64f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pDp, Npp8u * pDeviceBuffer)`

One-channel 32-bit floating point image DotProd.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDp Pointer to the computed dot product of the two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_32f64f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.11 `NppStatus nppiDotProd_32f64f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aDp[3], Npp8u * pDeviceBuffer)`

Three-channel 32-bit floating point image DotProd.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDp Array that contains the computed dot product of the two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_32f64f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.12 `NppStatus nppiDotProd_32f64f_C4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aDp[4], Npp8u * pDeviceBuffer)`

Four-channel 32-bit floating point image DotProd.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDp Array that contains the computed dot product of the two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_32f64f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.13 `NppStatus nppiDotProd_32s64f_AC4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aDp[3], Npp8u * pDeviceBuffer)`

Four-channel 32-bit signed image DotProd ignoring alpha channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDp Array that contains the computed dot product of the two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_32s64f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.14 `NppStatus nppiDotProd_32s64f_C1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pDp, Npp8u * pDeviceBuffer)`

One-channel 32-bit signed image DotProd.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDp Pointer to the computed dot product of the two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_32s64f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.15 `NppStatus nppiDotProd_32s64f_C3R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aDp[3], Npp8u * pDeviceBuffer)`

Three-channel 32-bit signed image DotProd.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDp Array that contains the computed dot product of the two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_32s64f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.16 `NppStatus nppiDotProd_32s64f_C4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aDp[4], Npp8u * pDeviceBuffer)`

Four-channel 32-bit signed image DotProd.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDp Array that contains the computed dot product of the two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_32s64f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.17 `NppStatus nppiDotProd_32u64f_AC4R (const Npp32u * pSrc1, int nSrc1Step, const Npp32u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aDp[3], Npp8u * pDeviceBuffer)`

Four-channel 32-bit unsigned image DotProd ignoring alpha channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDp Array that contains the computed dot product of the two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_32u64f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.18 `NppStatus nppiDotProd_32u64f_C1R (const Npp32u * pSrc1, int nSrc1Step, const Npp32u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pDp, Npp8u * pDeviceBuffer)`

One-channel 32-bit unsigned image DotProd.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- pDp* Pointer to the computed dot product of the two images.
- pDeviceBuffer* Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_32u64f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.19 `NppStatus nppiDotProd_32u64f_C3R (const Npp32u * pSrc1, int nSrc1Step, const Npp32u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aDp[3], Npp8u * pDeviceBuffer)`

Three-channel 32-bit unsigned image DotProd.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- aDp* Array that contains the computed dot product of the two images.
- pDeviceBuffer* Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_32u64f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.20 `NppStatus nppiDotProd_32u64f_C4R (const Npp32u * pSrc1, int nSrc1Step, const Npp32u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aDp[4], Npp8u * pDeviceBuffer)`

Four-channel 32-bit unsigned image DotProd.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDp Array that contains the computed dot product of the two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_32u64f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.21 `NppStatus nppiDotProd_8s64f_AC4R (const Npp8s * pSrc1, int nSrc1Step, const Npp8s * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aDp[3], Npp8u * pDeviceBuffer)`

Four-channel 8-bit signed image DotProd ignoring alpha channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDp Array that contains the computed dot product of the two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_8s64f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.22 `NppStatus nppiDotProd_8s64f_C1R (const Npp8s * pSrc1, int nSrc1Step, const Npp8s * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pDp, Npp8u * pDeviceBuffer)`

One-channel 8-bit signed image DotProd.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDp Pointer to the computed dot product of the two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_8s64f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.23 `NppStatus nppiDotProd_8s64f_C3R (const Npp8s * pSrc1, int nSrc1Step, const Npp8s * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aDp[3], Npp8u * pDeviceBuffer)`

Three-channel 8-bit signed image DotProd.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDp Array that contains the computed dot product of the two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_8s64f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.24 `NppStatus nppiDotProd_8s64f_C4R (const Npp8s * pSrc1, int nSrc1Step, const Npp8s * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aDp[4], Npp8u * pDeviceBuffer)`

Four-channel 8-bit signed image DotProd.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDp Array that contains the computed dot product of the two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_8s64f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.25 `NppStatus nppiDotProd_8u64f_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aDp[3], Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image DotProd ignoring alpha channel.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDp Array that contains the computed dot product of the two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_8u64f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.26 `NppStatus nppiDotProd_8u64f_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f * pDp, Npp8u * pDeviceBuffer)`

One-channel 8-bit unsigned image DotProd.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDp Pointer to the computed dot product of the two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_8u64f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.27 `NppStatus nppiDotProd_8u64f_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aDp[3], Npp8u * pDeviceBuffer)`

Three-channel 8-bit unsigned image DotProd.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDp Array that contains the computed dot product of the two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_8u64f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.28 `NppStatus nppiDotProd_8u64f_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oSizeROI, Npp64f aDp[4], Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image DotProd.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aDp Array that contains the computed dot product of the two images.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiDotProdGetBufferHostSize_8u64f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.107.2.29 `NppStatus nppiDotProdGetBufferHostSize_16s64f_AC4R (NppiSize oSizeROI, int * hpBufferSize)`

Device scratch buffer size (in bytes) for `nppiDotProd_16s64f_AC4R`.

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.30 `NppStatus nppiDotProdGetBufferHostSize_16s64f_C1R (NppiSize oSizeROI, int * hpBufferSize)`

Device scratch buffer size (in bytes) for `nppiDotProd_16s64f_C1R`.

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.31 NppStatus nppiDotProdGetBufferHostSize_16s64f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for `nppiDotProd_16s64f_C3R`.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.32 NppStatus nppiDotProdGetBufferHostSize_16s64f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for `nppiDotProd_16s64f_C4R`.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.33 NppStatus nppiDotProdGetBufferHostSize_16u64f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for `nppiDotProd_16u64f_AC4R`.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.34 NppStatus nppiDotProdGetBufferHostSize_16u64f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppiDotProd_16u64f_C1R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.35 NppStatus nppiDotProdGetBufferHostSize_16u64f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppiDotProd_16u64f_C3R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.36 NppStatus nppiDotProdGetBufferHostSize_16u64f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppiDotProd_16u64f_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.37 NppStatus nppiDotProdGetBufferHostSize_32f64f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppiDotProd_32f64f_AC4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.38 NppStatus nppiDotProdGetBufferHostSize_32f64f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for `nppiDotProd_32f64f_C1R`.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.39 NppStatus nppiDotProdGetBufferHostSize_32f64f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for `nppiDotProd_32f64f_C3R`.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.40 NppStatus nppiDotProdGetBufferHostSize_32f64f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for `nppiDotProd_32f64f_C4R`.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.41 NppStatus nppiDotProdGetBufferHostSize_32s64f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppiDotProd_32s64f_AC4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.42 NppStatus nppiDotProdGetBufferHostSize_32s64f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppiDotProd_32s64f_C1R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.43 NppStatus nppiDotProdGetBufferHostSize_32s64f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppiDotProd_32s64f_C3R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.44 NppStatus nppiDotProdGetBufferHostSize_32s64f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppiDotProd_32s64f_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.45 NppStatus nppiDotProdGetBufferHostSize_32u64f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for `nppiDotProd_32u64f_AC4R`.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.46 NppStatus nppiDotProdGetBufferHostSize_32u64f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for `nppiDotProd_32u64f_C1R`.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.47 NppStatus nppiDotProdGetBufferHostSize_32u64f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for `nppiDotProd_32u64f_C3R`.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.48 NppStatus nppiDotProdGetBufferHostSize_32u64f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppiDotProd_32u64f_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.49 NppStatus nppiDotProdGetBufferHostSize_8s64f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppiDotProd_8s64f_AC4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.50 NppStatus nppiDotProdGetBufferHostSize_8s64f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppiDotProd_8s64f_C1R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.51 NppStatus nppiDotProdGetBufferHostSize_8s64f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppiDotProd_8s64f_C3R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.52 NppStatus nppiDotProdGetBufferHostSize_8s64f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for `nppiDotProd_8s64f_C4R`.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.53 NppStatus nppiDotProdGetBufferHostSize_8u64f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for `nppiDotProd_8u64f_AC4R`.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.54 NppStatus nppiDotProdGetBufferHostSize_8u64f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for `nppiDotProd_8u64f_C1R`.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.55 NppStatus nppiDotProdGetBufferHostSize_8u64f_C3R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppiDotProd_8u64f_C3R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.107.2.56 NppStatus nppiDotProdGetBufferHostSize_8u64f_C4R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppiDotProd_8u64f_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.108 CountInRange.

Primitives for computing the amount of pixels that fall into the specified intensity range.

CountInRange

The lower bound and the upper bound are inclusive.

The functions require additional scratch buffer for computations.

- `NppStatus nppiCountInRange_8u_C1R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, int *pCounts, `Npp8u` nLowerBound, `Npp8u` nUpperBound, `Npp8u` *pDeviceBuffer)
One-channel 8-bit unsigned image CountInRange.
- `NppStatus nppiCountInRange_32f_C1R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSizeROI, int *pCounts, `Npp32f` nLowerBound, `Npp32f` nUpperBound, `Npp8u` *pDeviceBuffer)
One-channel 32-bit floating point image CountInRange.
- `NppStatus nppiCountInRange_8u_C3R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, int aCounts[3], `Npp8u` aLowerBound[3], `Npp8u` aUpperBound[3], `Npp8u` *pDeviceBuffer)
Three-channel 8-bit unsigned image CountInRange.
- `NppStatus nppiCountInRange_32f_C3R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSizeROI, int aCounts[3], `Npp32f` aLowerBound[3], `Npp32f` aUpperBound[3], `Npp8u` *pDeviceBuffer)
Three-channel 32-bit floating point image CountInRange.
- `NppStatus nppiCountInRange_8u_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSizeROI, int aCounts[3], `Npp8u` aLowerBound[3], `Npp8u` aUpperBound[3], `Npp8u` *pDeviceBuffer)
Four-channel 8-bit unsigned image CountInRange ignoring alpha channel.
- `NppStatus nppiCountInRange_32f_AC4R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSizeROI, int aCounts[3], `Npp32f` aLowerBound[3], `Npp32f` aUpperBound[3], `Npp8u` *pDeviceBuffer)
Four-channel 32-bit floating point image CountInRange ignoring alpha channel.

CountInRangeGetBufferHostSize

Companion primitives for computing the device buffer size (in bytes) required by the CountInRange primitives.

- `NppStatus nppiCountInRangeGetBufferHostSize_8u_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppiCountInRange_8u_C1R.
- `NppStatus nppiCountInRangeGetBufferHostSize_32f_C1R` (`NppiSize` oSizeROI, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppiCountInRange_32f_C1R.
- `NppStatus nppiCountInRangeGetBufferHostSize_8u_C3R` (`NppiSize` oSizeROI, int *hpBufferSize)

Device scratch buffer size (in bytes) for nppiCountInRange_8u_C3R.

- **NppStatus** [nppiCountInRangeGetBufferHostSize_32f_C3R](#) (**NppiSize** oSizeROI, int *hpBufferSize)

Device scratch buffer size (in bytes) for nppiCountInRange_32f_C3R.

- **NppStatus** [nppiCountInRangeGetBufferHostSize_8u_AC4R](#) (**NppiSize** oSizeROI, int *hpBufferSize)

Device scratch buffer size (in bytes) for nppiCountInRange_8u_AC4R.

- **NppStatus** [nppiCountInRangeGetBufferHostSize_32f_AC4R](#) (**NppiSize** oSizeROI, int *hpBufferSize)

Device scratch buffer size (in bytes) for nppiCountInRange_32f_AC4R.

7.108.1 Detailed Description

Primitives for computing the amount of pixels that fall into the specified intensity range.

7.108.2 Function Documentation

- 7.108.2.1** **NppStatus** [nppiCountInRange_32f_AC4R](#) (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSizeROI, int aCounts[3], **Npp32f** aLowerBound[3], **Npp32f** aUpperBound[3], **Npp8u** *pDeviceBuffer)

Four-channel 32-bit floating point image CountInRange ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aCounts Array that contains the number of pixels that fall into the specified range for Three-channels.

aLowerBound Fixed size array of the lower bound of the specified range, one per channel.

aUpperBound Fixed size array of the upper bound of the specified range, one per channel.

pDeviceBuffer [Pointer to the required device memory allocation, Scratch Buffer and Host Pointer](#).
Use [nppiCountInRangeGetBufferHostSize_32f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_RANGE_ERROR` if the lower bound is larger than the upper bound.

- 7.108.2.2** **NppStatus** [nppiCountInRange_32f_C1R](#) (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSizeROI, int *pCounts, **Npp32f** nLowerBound, **Npp32f** nUpperBound, **Npp8u** *pDeviceBuffer)

One-channel 32-bit floating point image CountInRange.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- pCounts* Pointer to the number of pixels that fall into the specified range.
- nLowerBound* Lower bound of the specified range.
- nUpperBound* Upper bound of the specified range.
- pDeviceBuffer* Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiCountInRangeGetBufferHostSize_32f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_RANGE_ERROR` if the lower bound is larger than the upper bound.

7.108.2.3 `NppStatus nppiCountInRange_32f_C3R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, int aCounts[3], Npp32f aLowerBound[3], Npp32f aUpperBound[3], Npp8u * pDeviceBuffer)`

Three-channel 32-bit floating point image CountInRange.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- aCounts* Array that contains the number of pixels that fall into the specified range for Three-channels.
- aLowerBound* Fixed size array of the lower bound of the specified range, one per channel.
- aUpperBound* Fixed size array of the upper bound of the specified range, one per channel.
- pDeviceBuffer* Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiCountInRangeGetBufferHostSize_32f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_RANGE_ERROR` if the lower bound is larger than the upper bound.

7.108.2.4 `NppStatus nppiCountInRange_8u_AC4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, int aCounts[3], Npp8u aLowerBound[3], Npp8u aUpperBound[3], Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image CountInRange ignoring alpha channel.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

aCounts Array that contains the number of pixels that fall into the specified range for Three-channels.
aLowerBound Fixed size array of the lower bound of the specified range, one per channel.
aUpperBound Fixed size array of the upper bound of the specified range, one per channel.
pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
 Use [nppiCountInRangeGetBufferHostSize_8u_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_RANGE_ERROR` if the lower bound is larger than the upper bound.

7.108.2.5 `NppStatus nppiCountInRange_8u_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, int * pCounts, Npp8u nLowerBound, Npp8u nUpperBound, Npp8u * pDeviceBuffer)`

One-channel 8-bit unsigned image CountInRange.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSizeROI [Region-of-Interest \(ROI\)](#).
pCounts Pointer to the number of pixels that fall into the specified range.
nLowerBound Lower bound of the specified range.
nUpperBound Upper bound of the specified range.
pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
 Use [nppiCountInRangeGetBufferHostSize_8u_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_RANGE_ERROR` if the lower bound is larger than the upper bound.

7.108.2.6 `NppStatus nppiCountInRange_8u_C3R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, int aCounts[3], Npp8u aLowerBound[3], Npp8u aUpperBound[3], Npp8u * pDeviceBuffer)`

Three-channel 8-bit unsigned image CountInRange.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSizeROI [Region-of-Interest \(ROI\)](#).
aCounts Array that contains the number of pixels that fall into the specified range for Three-channels.
aLowerBound Fixed size array of the lower bound of the specified range, one per channel.
aUpperBound Fixed size array of the upper bound of the specified range, one per channel.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiCountInRangeGetBufferHostSize_8u_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or NPP_RANGE_ERROR if the lower bound is larger than the upper bound.

7.108.2.7 NppStatus nppiCountInRangeGetBufferHostSize_32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppiCountInRange_32f_AC4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if hpBufferSize is 0 (NULL), [ROI Related Error Codes](#).

7.108.2.8 NppStatus nppiCountInRangeGetBufferHostSize_32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppiCountInRange_32f_C1R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if hpBufferSize is 0 (NULL), [ROI Related Error Codes](#).

7.108.2.9 NppStatus nppiCountInRangeGetBufferHostSize_32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppiCountInRange_32f_C3R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if hpBufferSize is 0 (NULL), [ROI Related Error Codes](#).

7.108.2.10 NppStatus nppiCountInRangeGetBufferHostSize_8u_AC4R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppiCountInRange_8u_AC4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.108.2.11 NppStatus nppiCountInRangeGetBufferHostSize_8u_C1R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppiCountInRange_8u_C1R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.108.2.12 NppStatus nppiCountInRangeGetBufferHostSize_8u_C3R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppiCountInRange_8u_C3R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.109 MaxEvery

Primitives for computing the maximal value of the pixel pair from two images.

MaxEvery

The maximum is stored into the second image.

- **NppStatus nppiMaxEvery_8u_C1IR** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One-channel 8-bit unsigned image MaxEvery.
- **NppStatus nppiMaxEvery_16u_C1IR** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One-channel 16-bit unsigned image MaxEvery.
- **NppStatus nppiMaxEvery_16s_C1IR** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One-channel 16-bit signed image MaxEvery.
- **NppStatus nppiMaxEvery_32f_C1IR** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One-channel 32-bit floating point image MaxEvery.
- **NppStatus nppiMaxEvery_8u_C3IR** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three-channel 8-bit unsigned image MaxEvery.
- **NppStatus nppiMaxEvery_16u_C3IR** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three-channel 16-bit unsigned image MaxEvery.
- **NppStatus nppiMaxEvery_16s_C3IR** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three-channel 16-bit signed image MaxEvery.
- **NppStatus nppiMaxEvery_32f_C3IR** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three-channel 32-bit floating point image MaxEvery.
- **NppStatus nppiMaxEvery_8u_C4IR** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four-channel 8-bit unsigned image MaxEvery.
- **NppStatus nppiMaxEvery_16u_C4IR** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four-channel 16-bit unsigned image MaxEvery.
- **NppStatus nppiMaxEvery_16s_C4IR** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)

Four-channel 16-bit signed image MaxEvery.

- [NppStatus nppiMaxEvery_32f_C4IR](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)

Four-channel 32-bit floating point image MaxEvery.

- [NppStatus nppiMaxEvery_8u_AC4IR](#) (const [Npp8u](#) *pSrc, int nSrcStep, [Npp8u](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)

Four-channel 8-bit unsigned image MaxEvery ignoring alpha channel.

- [NppStatus nppiMaxEvery_16u_AC4IR](#) (const [Npp16u](#) *pSrc, int nSrcStep, [Npp16u](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)

Four-channel 16-bit unsigned image MaxEvery ignoring alpha channel.

- [NppStatus nppiMaxEvery_16s_AC4IR](#) (const [Npp16s](#) *pSrc, int nSrcStep, [Npp16s](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)

Four-channel 16-bit signed image MaxEvery ignoring alpha channel.

- [NppStatus nppiMaxEvery_32f_AC4IR](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)

Four-channel 32-bit floating point image MaxEvery ignoring alpha channel.

7.109.1 Detailed Description

Primitives for computing the maximal value of the pixel pair from two images.

7.109.2 Function Documentation

7.109.2.1 [NppStatus nppiMaxEvery_16s_AC4IR](#) (const [Npp16s](#) *pSrc, int nSrcStep, [Npp16s](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)

Four-channel 16-bit signed image MaxEvery ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.109.2.2 NppStatus nppiMaxEvery_16s_C1IR (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One-channel 16-bit signed image MaxEvery.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.109.2.3 NppStatus nppiMaxEvery_16s_C3IR (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three-channel 16-bit signed image MaxEvery.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.109.2.4 NppStatus nppiMaxEvery_16s_C4IR (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four-channel 16-bit signed image MaxEvery.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.109.2.5 `NppStatus nppiMaxEvery_16u_AC4IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four-channel 16-bit unsigned image MaxEvery ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.109.2.6 `NppStatus nppiMaxEvery_16u_C1IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One-channel 16-bit unsigned image MaxEvery.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.109.2.7 `NppStatus nppiMaxEvery_16u_C3IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Three-channel 16-bit unsigned image MaxEvery.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.109.2.8 NppStatus nppiMaxEvery_16u_C4IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four-channel 16-bit unsigned image MaxEvery.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.109.2.9 NppStatus nppiMaxEvery_32f_AC4IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four-channel 32-bit floating point image MaxEvery ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.109.2.10 NppStatus nppiMaxEvery_32f_C1IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One-channel 32-bit floating point image MaxEvery.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.109.2.11 NppStatus nppiMaxEvery_32f_C3IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three-channel 32-bit floating point image MaxEvery.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.109.2.12 NppStatus nppiMaxEvery_32f_C4IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four-channel 32-bit floating point image MaxEvery.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.109.2.13 NppStatus nppiMaxEvery_8u_AC4IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four-channel 8-bit unsigned image MaxEvery ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.109.2.14 NppStatus nppiMaxEvery_8u_C1IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One-channel 8-bit unsigned image MaxEvery.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.109.2.15 NppStatus nppiMaxEvery_8u_C3IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three-channel 8-bit unsigned image MaxEvery.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.109.2.16 NppStatus nppiMaxEvery_8u_C4IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four-channel 8-bit unsigned image MaxEvery.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.110 MinEvery

Primitives for computing the minimal value of the pixel pair from two images.

MinEvery

The minimum is stored into the second image.

- [NppStatus nppiMinEvery_8u_C1IR](#) (const [Npp8u](#) *pSrc, int nSrcStep, [Npp8u](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
One-channel 8-bit unsigned image MinEvery.
- [NppStatus nppiMinEvery_16u_C1IR](#) (const [Npp16u](#) *pSrc, int nSrcStep, [Npp16u](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
One-channel 16-bit unsigned image MinEvery.
- [NppStatus nppiMinEvery_16s_C1IR](#) (const [Npp16s](#) *pSrc, int nSrcStep, [Npp16s](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
One-channel 16-bit signed image MinEvery.
- [NppStatus nppiMinEvery_32f_C1IR](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
One-channel 32-bit floating point image MinEvery.
- [NppStatus nppiMinEvery_8u_C3IR](#) (const [Npp8u](#) *pSrc, int nSrcStep, [Npp8u](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
Three-channel 8-bit unsigned image MinEvery.
- [NppStatus nppiMinEvery_16u_C3IR](#) (const [Npp16u](#) *pSrc, int nSrcStep, [Npp16u](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
Three-channel 16-bit unsigned image MinEvery.
- [NppStatus nppiMinEvery_16s_C3IR](#) (const [Npp16s](#) *pSrc, int nSrcStep, [Npp16s](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
Three-channel 16-bit signed image MinEvery.
- [NppStatus nppiMinEvery_32f_C3IR](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
Three-channel 32-bit floating point image MinEvery.
- [NppStatus nppiMinEvery_8u_C4IR](#) (const [Npp8u](#) *pSrc, int nSrcStep, [Npp8u](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
Four-channel 8-bit unsigned image MinEvery.
- [NppStatus nppiMinEvery_16u_C4IR](#) (const [Npp16u](#) *pSrc, int nSrcStep, [Npp16u](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
Four-channel 16-bit unsigned image MinEvery.
- [NppStatus nppiMinEvery_16s_C4IR](#) (const [Npp16s](#) *pSrc, int nSrcStep, [Npp16s](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)

Four-channel 16-bit signed image MinEvery.

- [NppStatus nppiMinEvery_32f_C4IR](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)

Four-channel 32-bit floating point image MinEvery.

- [NppStatus nppiMinEvery_8u_AC4IR](#) (const [Npp8u](#) *pSrc, int nSrcStep, [Npp8u](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)

Four-channel 8-bit unsigned image MinEvery ignoring alpha channel.

- [NppStatus nppiMinEvery_16u_AC4IR](#) (const [Npp16u](#) *pSrc, int nSrcStep, [Npp16u](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)

Four-channel 16-bit unsigned image MinEvery ignoring alpha channel.

- [NppStatus nppiMinEvery_16s_AC4IR](#) (const [Npp16s](#) *pSrc, int nSrcStep, [Npp16s](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)

Four-channel 16-bit signed image MinEvery ignoring alpha channel.

- [NppStatus nppiMinEvery_32f_AC4IR](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)

Four-channel 32-bit floating point image MinEvery ignoring alpha channel.

7.110.1 Detailed Description

Primitives for computing the minimal value of the pixel pair from two images.

7.110.2 Function Documentation

7.110.2.1 [NppStatus nppiMinEvery_16s_AC4IR](#) (const [Npp16s](#) * pSrc, int nSrcStep, [Npp16s](#) * pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)

Four-channel 16-bit signed image MinEvery ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.110.2.2 NppStatus nppiMinEvery_16s_C1IR (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One-channel 16-bit signed image MinEvery.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.110.2.3 NppStatus nppiMinEvery_16s_C3IR (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three-channel 16-bit signed image MinEvery.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.110.2.4 NppStatus nppiMinEvery_16s_C4IR (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four-channel 16-bit signed image MinEvery.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.110.2.5 NppStatus nppiMinEvery_16u_AC4IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four-channel 16-bit unsigned image MinEvery ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.110.2.6 NppStatus nppiMinEvery_16u_C1IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One-channel 16-bit unsigned image MinEvery.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.110.2.7 NppStatus nppiMinEvery_16u_C3IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three-channel 16-bit unsigned image MinEvery.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.110.2.8 NppStatus nppiMinEvery_16u_C4IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four-channel 16-bit unsigned image MinEvery.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.110.2.9 NppStatus nppiMinEvery_32f_AC4IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four-channel 32-bit floating point image MinEvery ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.110.2.10 NppStatus nppiMinEvery_32f_C1IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One-channel 32-bit floating point image MinEvery.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.110.2.11 NppStatus nppiMinEvery_32f_C3IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three-channel 32-bit floating point image MinEvery.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.110.2.12 NppStatus nppiMinEvery_32f_C4IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four-channel 32-bit floating point image MinEvery.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.110.2.13 NppStatus nppiMinEvery_8u_AC4IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four-channel 8-bit unsigned image MinEvery ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.110.2.14 NppStatus nppiMinEvery_8u_C1IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One-channel 8-bit unsigned image MinEvery.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.110.2.15 NppStatus nppiMinEvery_8u_C3IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three-channel 8-bit unsigned image MinEvery.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.110.2.16 NppStatus nppiMinEvery_8u_C4IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four-channel 8-bit unsigned image MinEvery.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.111 Integral

Primitives for computing the integral image of a given image.

Integral

Given an input image $pSrc$ and the specified value $nVal$, the pixel value of the integral image $pDst$ at coordinate (i, j) will be computed as

$$pDst(j, i) = nVal + \sum_{l=0}^{j-1} \sum_{k=0}^{i-1} pSrc(l, k)$$

If the size of the input image is $W \times H$, the size of the integral image will be $(W + 1) \times (H + 1)$.

- [NppStatus nppiIntegral_8u32s_C1R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oROI, [Npp32s](#) nVal)
One-channel 8-bit unsigned image Integral with 32-bit signed output.
- [NppStatus nppiIntegral_8u32f_C1R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oROI, [Npp32f](#) nVal)
One-channel 8-bit unsigned image Integral with 32-bit floating point output.

7.111.1 Detailed Description

Primitives for computing the integral image of a given image.

7.111.2 Function Documentation

7.111.2.1 [NppStatus nppiIntegral_8u32f_C1R](#) (const [Npp8u](#) * pSrc, int nSrcStep, [Npp32f](#) * pDst, int nDstStep, [NppiSize](#) oROI, [Npp32f](#) nVal)

One-channel 8-bit unsigned image Integral with 32-bit floating point output.

Parameters:

- pSrc* [Source-Image Pointer](#).
- nSrcStep* [Source-Image Line Step](#).
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oROI* [Region-of-Interest \(ROI\)](#).
- nVal* The value to add to pDst image pixels

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.111.2.2 NppStatus nppiIntegral_8u32s_C1R (const Npp8u * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oROI, Npp32s nVal)

One-channel 8-bit unsigned image Integral with 32-bit signed output.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

nVal The value to add to pDst image pixels

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.112 SqrIntegral

Primitives for computing both the integral and the squared integral images of a given image.

SqrIntegral

Given an input image $pSrc$ and the specified value $nVal$, the pixel value of the integral image $pDst$ at coordinate (i, j) will be computed as

$$pDst(j, i) = nVal + \sum_{l=0}^{j-1} \sum_{k=0}^{i-1} pSrc(l, k)$$

Given an input image $pSrc$ and the specified value $nValSqr$, the pixel value of the squared integral image $pSqr$ at coordinate (i, j) will be computed as

$$pSqr(j, i) = nValSqr + \sum_{l=0}^{j-1} \sum_{k=0}^{i-1} pSrc(l, k)^2$$

If the size of the input image is $W \times H$, the size of the squared integral image will be $(W + 1) \times (H + 1)$.

- **NppStatus nppiSqrIntegral_8u32s_C1R** (const **Npp8u** *pSrc, int nSrcStep, **Npp32s** *pDst, int nDstStep, **Npp32s** *pSqr, int nSqrStep, **NppiSize** oSrcROI, **Npp32s** nVal, **Npp32s** nValSqr)
One-channel 8-bit unsigned image SqrIntegral.
- **NppStatus nppiSqrIntegral_8u32s64f_C1R** (const **Npp8u** *pSrc, int nSrcStep, **Npp32s** *pDst, int nDstStep, **Npp64f** *pSqr, int nSqrStep, **NppiSize** oSrcROI, **Npp32s** nVal, **Npp64f** nValSqr)
One-channel 8-bit unsigned image SqrIntegral.
- **NppStatus nppiSqrIntegral_8u32f64f_C1R** (const **Npp8u** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **Npp64f** *pSqr, int nSqrStep, **NppiSize** oSrcROI, **Npp32f** nVal, **Npp64f** nValSqr)
One-channel 8-bit unsigned image SqrIntegral.

7.112.1 Detailed Description

Primitives for computing both the integral and the squared integral images of a given image.

7.112.2 Function Documentation

7.112.2.1 NppStatus nppiSqrIntegral_8u32f64f_C1R (const **Npp8u** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **Npp64f** *pSqr, int nSqrStep, **NppiSize** oSrcROI, **Npp32f** nVal, **Npp64f** nValSqr)

One-channel 8-bit unsigned image SqrIntegral.

Destination integral image is 32-bit floating point. Destination square integral image is 64-bit double floating point.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
pSqr Destination-Image Pointer.
nSqrStep Destination-Image Line Step.
oSrcROI Region-of-Interest (ROI).
nVal The value to add to pDst image pixels
nValSqr The value to add to pSqr image pixels

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.112.2.2 `NppStatus nppiSqrIntegral_8u32s64f_C1R (const Npp8u * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, Npp64f * pSqr, int nSqrStep, NppiSize oSrcROI, Npp32s nVal, Npp64f nValSqr)`

One-channel 8-bit unsigned image SqrIntegral.

Destination integral image is 32-bit signed int. Destination square integral image is 64-bit double floating point.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
pSqr Destination-Image Pointer.
nSqrStep Destination-Image Line Step.
oSrcROI Region-of-Interest (ROI).
nVal The value to add to pDst image pixels
nValSqr The value to add to pSqr image pixels

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.112.2.3 `NppStatus nppiSqrIntegral_8u32s_C1R (const Npp8u * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, Npp32s * pSqr, int nSqrStep, NppiSize oSrcROI, Npp32s nVal, Npp32s nValSqr)`

One-channel 8-bit unsigned image SqrIntegral.

Destination integral image and square integral image are 32-bit signed int.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pSqr Destination-Image Pointer.

nSqrStep Destination-Image Line Step.

oSrcROI Region-of-Interest (ROI).

nVal The value to add to pDst image pixels

nValSqr The value to add to pSqr image pixels

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.113 RectStdDev

Primitives for computing the standard deviation of the integral images.

RectStdDev

- **NppStatus nppiRectStdDev_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, const **Npp64f** *pSqr, int nSqrStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppiRect** oRect)
One-channel 32-bit floating point image RectStdDev.
- **NppStatus nppiRectStdDev_32s_C1RSfs** (const **Npp32s** *pSrc, int nSrcStep, const **Npp32s** *pSqr, int nSqrStep, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppiRect** oRect, int nScaleFactor)
One-channel 32-bit signed image RectStdDev, scaled by $2^{(- nScaleFactor)}$.
- **NppStatus nppiRectStdDev_32s32f_C1R** (const **Npp32s** *pSrc, int nSrcStep, const **Npp64f** *pSqr, int nSqrStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppiRect** oRect)
One-channel 32-bit signed image RectStdDev.

7.113.1 Detailed Description

Primitives for computing the standard deviation of the integral images.

The function computes the standard deviation of the pixel in the rectangular window with the integral image *pSrc* and the squared integral image *pSqr*, which can be obtained by calling [Integral](#) and [SqrIntegral](#).

The standard deviation of the pixel (*j*, *i*) can be computed using the formula:

$$pDst(j, i) = \sqrt{\max(0, \frac{\sum(SqrIntegral) \cdot N - (\sum(Integral))^2}{N^2})}$$

where $\sum(SqrIntegral) = pSqr[j + oRect.y + oRect.height, i + oRect.x + oRect.width] - pSqr[j + oRect.y, i + oRect.x + oRect.width] - pSqr[j + oRect.y + oRect.height, i + oRect.x] + pSqr[j + oRect.y, i + oRect.x]$, $\sum(Integral) = pSrc[j + oRect.y + oRect.height, i + oRect.x + oRect.width] - pSrc[j + oRect.y, i + oRect.x + oRect.width] - pSrc[j + oRect.y + oRect.height, i + oRect.x] + pSrc[j + oRect.y, i + oRect.x]$, $N = oRect.width \cdot oRect.height$.

The size of the *pSrc* and *pSqr* should be $(oSizeROI.width + oRect.x + oRect.width, oSizeROI.height + oRect.y + oRect.height)$.

7.113.2 Function Documentation

7.113.2.1 **NppStatus nppiRectStdDev_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, const **Npp64f** *pSqr, int nSqrStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppiRect** oRect)

One-channel 32-bit floating point image RectStdDev.

Parameters:

- pSrc* [Source-Image Pointer](#).
- nSrcStep* [Source-Image Line Step](#).
- pSqr* [Destination-Image Pointer](#).

nSqrStep Destination-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
oRect rectangular window

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.113.2.2 NppStatus nppiRectStdDev_32s32f_C1R (const Npp32s * pSrc, int nSrcStep, const Npp64f * pSqr, int nSqrStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, NppiRect oRect)

One-channel 32-bit signed image RectStdDev.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSqr Destination-Image Pointer.
nSqrStep Destination-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
oRect rectangular window

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.113.2.3 NppStatus nppiRectStdDev_32s_C1RSfs (const Npp32s * pSrc, int nSrcStep, const Npp32s * pSqr, int nSqrStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, NppiRect oRect, int nScaleFactor)

One-channel 32-bit signed image RectStdDev, scaled by $2^{(-nScaleFactor)}$.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSqr Destination-Image Pointer.
nSqrStep Destination-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
oRect rectangular window

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.114 HistogramEven

Primitives for computing the histogram of an image with evenly distributed bins.

HistogramEven

The $nLowerLevel$ (inclusive) and $nUpperLevel$ (exclusive) define the boundaries of the range, which are evenly segmented into $nLevel - 1$ bins.

The computed histogram is stored in $pHist$. The levels are calculated by another primitive [nppiEvenLevelsHost_32s](#) and are stored in a host pointer $hpLevels$. The number of levels is also $nLevel - 1$. The histogram $pHist[k]$ is defined as the total number of pixels that fall into the range: $hpLevels[k] \leq pSrc(j, i) < hpLevels[k + 1]$. The functions require additional scratch buffer for computations.

- [NppStatus nppiEvenLevelsHost_32s](#) ([Npp32s](#) *hpLevels, int nLevels, [Npp32s](#) nLowerLevel, [Npp32s](#) nUpperLevel)
Compute levels with even distribution.
- [NppStatus nppiHistogramEven_8u_C1R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [NppiSize](#) oSizeROI, [Npp32s](#) *pHist, int nLevels, [Npp32s](#) nLowerLevel, [Npp32s](#) nUpperLevel, [Npp8u](#) *pBuffer)
One-channel 8-bit unsigned HistogramEven.
- [NppStatus nppiHistogramEven_8u_C3R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [NppiSize](#) oSizeROI, [Npp32s](#) *pHist[3], int nLevels[3], [Npp32s](#) nLowerLevel[3], [Npp32s](#) nUpperLevel[3], [Npp8u](#) *pBuffer)
Three-channel 8-bit unsigned HistogramEven.
- [NppStatus nppiHistogramEven_8u_C4R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [NppiSize](#) oSizeROI, [Npp32s](#) *pHist[4], int nLevels[4], [Npp32s](#) nLowerLevel[4], [Npp32s](#) nUpperLevel[4], [Npp8u](#) *pBuffer)
Four-channel 8-bit unsigned HistogramEven.
- [NppStatus nppiHistogramEven_8u_AC4R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [NppiSize](#) oSizeROI, [Npp32s](#) *pHist[3], int nLevels[3], [Npp32s](#) nLowerLevel[3], [Npp32s](#) nUpperLevel[3], [Npp8u](#) *pBuffer)
Four-channel 8-bit unsigned HistogramEven ignoring alpha channel.
- [NppStatus nppiHistogramEven_16u_C1R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [NppiSize](#) oSizeROI, [Npp32s](#) *pHist, int nLevels, [Npp32s](#) nLowerLevel, [Npp32s](#) nUpperLevel, [Npp8u](#) *pBuffer)
One-channel 16-bit unsigned HistogramEven.
- [NppStatus nppiHistogramEven_16u_C3R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [NppiSize](#) oSizeROI, [Npp32s](#) *pHist[3], int nLevels[3], [Npp32s](#) nLowerLevel[3], [Npp32s](#) nUpperLevel[3], [Npp8u](#) *pBuffer)
Three-channel 16-bit unsigned HistogramEven.
- [NppStatus nppiHistogramEven_16u_C4R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [NppiSize](#) oSizeROI, [Npp32s](#) *pHist[4], int nLevels[4], [Npp32s](#) nLowerLevel[4], [Npp32s](#) nUpperLevel[4], [Npp8u](#) *pBuffer)
Four-channel 16-bit unsigned HistogramEven.

- `NppStatus nppiHistogramEven_16u_AC4R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp32s *pHist[3]`, int `nLevels[3]`, `Npp32s` `nLowerLevel[3]`, `Npp32s` `nUpperLevel[3]`, `Npp8u *pBuffer`)
Four-channel 16-bit unsigned HistogramEven ignoring alpha channel.
- `NppStatus nppiHistogramEven_16s_C1R` (const `Npp16s *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp32s *pHist`, int `nLevels`, `Npp32s` `nLowerLevel`, `Npp32s` `nUpperLevel`, `Npp8u *pBuffer`)
One-channel 16-bit signed HistogramEven.
- `NppStatus nppiHistogramEven_16s_C3R` (const `Npp16s *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp32s *pHist[3]`, int `nLevels[3]`, `Npp32s` `nLowerLevel[3]`, `Npp32s` `nUpperLevel[3]`, `Npp8u *pBuffer`)
Three-channel 16-bit signed HistogramEven.
- `NppStatus nppiHistogramEven_16s_C4R` (const `Npp16s *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp32s *pHist[4]`, int `nLevels[4]`, `Npp32s` `nLowerLevel[4]`, `Npp32s` `nUpperLevel[4]`, `Npp8u *pBuffer`)
Four-channel 16-bit signed HistogramEven.
- `NppStatus nppiHistogramEven_16s_AC4R` (const `Npp16s *pSrc`, int `nSrcStep`, `NppiSize` `oSizeROI`, `Npp32s *pHist[3]`, int `nLevels[3]`, `Npp32s` `nLowerLevel[3]`, `Npp32s` `nUpperLevel[3]`, `Npp8u *pBuffer`)
Four-channel 16-bit signed HistogramEven ignoring alpha channel.

HistogramEvenGetBufferSize

Companion primitives for computing the device buffer size (in bytes) required by the HistogramEven primitives.

- `NppStatus nppiHistogramEvenGetBufferSize_8u_C1R` (`NppiSize` `oSizeROI`, int `nLevels`, int `*hpBufferSize`)
Buffer size for `nppiHistogramEven_8u_C1R`.
- `NppStatus nppiHistogramEvenGetBufferSize_8u_C3R` (`NppiSize` `oSizeROI`, int `nLevels[3]`, int `*hpBufferSize`)
Buffer size for `nppiHistogramEven_8u_C3R`.
- `NppStatus nppiHistogramEvenGetBufferSize_8u_C4R` (`NppiSize` `oSizeROI`, int `nLevels[4]`, int `*hpBufferSize`)
Buffer size for `nppiHistogramEven_8u_C4R`.
- `NppStatus nppiHistogramEvenGetBufferSize_8u_AC4R` (`NppiSize` `oSizeROI`, int `nLevels[3]`, int `*hpBufferSize`)
Buffer size for `nppiHistogramEven_8u_AC4R`.
- `NppStatus nppiHistogramEvenGetBufferSize_16u_C1R` (`NppiSize` `oSizeROI`, int `nLevels`, int `*hpBufferSize`)
Buffer size for `nppiHistogramEven_16u_C1R`.

- **NppStatus** `nppiHistogramEvenGetBufferSize_16u_C3R` (**NppiSize** `oSizeROI`, **int** `nLevels[3]`, **int** `*hpBufferSize`)
Buffer size for `nppiHistogramEven_16u_C3R`.
- **NppStatus** `nppiHistogramEvenGetBufferSize_16u_C4R` (**NppiSize** `oSizeROI`, **int** `nLevels[4]`, **int** `*hpBufferSize`)
Buffer size for `nppiHistogramEven_16u_C4R`.
- **NppStatus** `nppiHistogramEvenGetBufferSize_16u_AC4R` (**NppiSize** `oSizeROI`, **int** `nLevels[3]`, **int** `*hpBufferSize`)
Buffer size for `nppiHistogramEven_16u_AC4R`.
- **NppStatus** `nppiHistogramEvenGetBufferSize_16s_C1R` (**NppiSize** `oSizeROI`, **int** `nLevels`, **int** `*hpBufferSize`)
Buffer size for `nppiHistogramEven_16s_C1R`.
- **NppStatus** `nppiHistogramEvenGetBufferSize_16s_C3R` (**NppiSize** `oSizeROI`, **int** `nLevels[3]`, **int** `*hpBufferSize`)
Buffer size for `nppiHistogramEven_16s_C3R`.
- **NppStatus** `nppiHistogramEvenGetBufferSize_16s_C4R` (**NppiSize** `oSizeROI`, **int** `nLevels[4]`, **int** `*hpBufferSize`)
Buffer size for `nppiHistogramEven_16s_C4R`.
- **NppStatus** `nppiHistogramEvenGetBufferSize_16s_AC4R` (**NppiSize** `oSizeROI`, **int** `nLevels[3]`, **int** `*hpBufferSize`)
Buffer size for `nppiHistogramEven_16s_AC4R`.

7.114.1 Detailed Description

Primitives for computing the histogram of an image with evenly distributed bins.

7.114.2 Function Documentation

7.114.2.1 **NppStatus** `nppiEvenLevelsHost_32s` (**Npp32s** `*hpLevels`, **int** `nLevels`, **Npp32s** `nLowerLevel`, **Npp32s** `nUpperLevel`)

Compute levels with even distribution.

Parameters:

hpLevels A host pointer to array which receives the levels being computed. The array needs to be of size `nLevels`.

nLevels The number of levels being computed. `nLevels` must be at least 2.

nLowerLevel Lower boundary value of the lowest level.

nUpperLevel Upper boundary value of the greatest level.

Returns:

image_data_error_codes, or NPP_HISTO_NUMBER_OF_LEVELS_ERROR if an invalid nLevels is specified.

7.114.2.2 NppStatus nppiHistogramEven_16s_AC4R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[3], int nLevels[3], Npp32s nLowerLevel[3], Npp32s nUpperLevel[3], Npp8u * pBuffer)

Four-channel 16-bit signed HistogramEven ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pHist Array of pointers which are receiving computed histograms per color channel. Array pointed by pHist[i] be of size nLevels[i]-1.

nLevels Array containing number of levels per color channel.

nLowerLevel Array containing lower-level of lowest bin per color channel.

nUpperLevel Array containing upper-level of highest bin per color channel.

pBuffer Pointer to appropriately sized ([nppiHistogramEvenGetBufferSize_16s_AC4R](#)) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.114.2.3 NppStatus nppiHistogramEven_16s_C1R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist, int nLevels, Npp32s nLowerLevel, Npp32s nUpperLevel, Npp8u * pBuffer)

One-channel 16-bit signed HistogramEven.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pHist Pointer to array that receives the computed histogram. The array must be of size nLevels-1.

nLevels Number of levels.

nLowerLevel Lower boundary of lowest level bin.

nUpperLevel Upper boundary of highest level bin.

pBuffer Pointer to appropriately sized ([nppiHistogramEvenGetBufferSize_16s_C1R](#)) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.114.2.4 `NppStatus nppiHistogramEven_16s_C3R` (`const Npp16s * pSrc`, `int nSrcStep`, `NppiSize oSizeROI`, `Npp32s * pHist[3]`, `int nLevels[3]`, `Npp32s nLowerLevel[3]`, `Npp32s nUpperLevel[3]`, `Npp8u * pBuffer`)

Three-channel 16-bit signed HistogramEven.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pHist Array of pointers which are receiving computed histograms per color channel. Array pointed by *pHist*[*i*] be of size *nLevels*[*i*]-1.

nLevels Array containing number of levels per color channel.

nLowerLevel Array containing lower-level of lowest bin per color channel.

nUpperLevel Array containing upper-level of highest bin per color channel.

pBuffer Pointer to appropriately sized (`nppiHistogramEvenGetBufferSize_16s_C3R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.114.2.5 `NppStatus nppiHistogramEven_16s_C4R` (`const Npp16s * pSrc`, `int nSrcStep`, `NppiSize oSizeROI`, `Npp32s * pHist[4]`, `int nLevels[4]`, `Npp32s nLowerLevel[4]`, `Npp32s nUpperLevel[4]`, `Npp8u * pBuffer`)

Four-channel 16-bit signed HistogramEven.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pHist Array of pointers which are receiving computed histograms per color channel. Array pointed by *pHist*[*i*] be of size *nLevels*[*i*]-1.

nLevels Array containing number of levels per color channel.

nLowerLevel Array containing lower-level of lowest bin per color channel.

nUpperLevel Array containing upper-level of highest bin per color channel.

pBuffer Pointer to appropriately sized (`nppiHistogramEvenGetBufferSize_16s_C4R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.114.2.6 `NppStatus nppiHistogramEven_16u_AC4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[3], int nLevels[3], Npp32s nLowerLevel[3], Npp32s nUpperLevel[3], Npp8u * pBuffer)`

Four-channel 16-bit unsigned HistogramEven ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pHist Array of pointers which are receiving computed histograms per color channel. Array pointed by *pHist*[*i*] be of size *nLevels*[*i*]-1.

nLevels Array containing number of levels per color channel.

nLowerLevel Array containing lower-level of lowest bin per color channel.

nUpperLevel Array containing upper-level of highest bin per color channel.

pBuffer Pointer to appropriately sized (`nppiHistogramEvenGetBufferSize_16u_AC4R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.114.2.7 `NppStatus nppiHistogramEven_16u_C1R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist, int nLevels, Npp32s nLowerLevel, Npp32s nUpperLevel, Npp8u * pBuffer)`

One-channel 16-bit unsigned HistogramEven.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pHist Pointer to array that receives the computed histogram. The array must be of size *nLevels*-1.

nLevels Number of levels.

nLowerLevel Lower boundary of lowest level bin.

nUpperLevel Upper boundary of highest level bin.

pBuffer Pointer to appropriately sized (`nppiHistogramEvenGetBufferSize_16u_C1R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.114.2.8 `NppStatus nppiHistogramEven_16u_C3R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[3], int nLevels[3], Npp32s nLowerLevel[3], Npp32s nUpperLevel[3], Npp8u * pBuffer)`

Three-channel 16-bit unsigned HistogramEven.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pHist Array of pointers which are receiving computed histograms per color channel. Array pointed by *pHist*[*i*] be of size *nLevels*[*i*]-1.

nLevels Array containing number of levels per color channel.

nLowerLevel Array containing lower-level of lowest bin per color channel.

nUpperLevel Array containing upper-level of highest bin per color channel.

pBuffer Pointer to appropriately sized (`nppiHistogramEvenGetBufferSize_16u_C3R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.114.2.9 `NppStatus nppiHistogramEven_16u_C4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[4], int nLevels[4], Npp32s nLowerLevel[4], Npp32s nUpperLevel[4], Npp8u * pBuffer)`

Four-channel 16-bit unsigned HistogramEven.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pHist Array of pointers which are receiving computed histograms per color channel. Array pointed by *pHist*[*i*] be of size *nLevels*[*i*]-1.

nLevels Array containing number of levels per color channel.

nLowerLevel Array containing lower-level of lowest bin per color channel.

nUpperLevel Array containing upper-level of highest bin per color channel.

pBuffer Pointer to appropriately sized (`nppiHistogramEvenGetBufferSize_16u_C4R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.114.2.10 `NppStatus nppiHistogramEven_8u_AC4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[3], int nLevels[3], Npp32s nLowerLevel[3], Npp32s nUpperLevel[3], Npp8u * pBuffer)`

Four-channel 8-bit unsigned HistogramEven ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pHist Array of pointers which are receiving computed histograms per color channel. Array pointed by *pHist*[*i*] be of size *nLevels*[*i*]-1.

nLevels Array containing number of levels per color channel.

nLowerLevel Array containing lower-level of lowest bin per color channel.

nUpperLevel Array containing upper-level of highest bin per color channel.

pBuffer Pointer to appropriately sized (`nppiHistogramEvenGetBufferSize_8u_AC4R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.114.2.11 `NppStatus nppiHistogramEven_8u_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist, int nLevels, Npp32s nLowerLevel, Npp32s nUpperLevel, Npp8u * pBuffer)`

One-channel 8-bit unsigned HistogramEven.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pHist Pointer to array that receives the computed histogram. The array must be of size *nLevels*-1.

nLevels Number of levels.

nLowerLevel Lower boundary of lowest level bin.

nUpperLevel Upper boundary of highest level bin.

pBuffer Pointer to appropriately sized (`nppiHistogramEvenGetBufferSize_8u_C1R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.114.2.12 `NppStatus nppiHistogramEven_8u_C3R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[3], int nLevels[3], Npp32s nLowerLevel[3], Npp32s nUpperLevel[3], Npp8u * pBuffer)`

Three-channel 8-bit unsigned HistogramEven.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).
pHist Array of pointers which are receiving computed histograms per color channel. Array pointed by *pHist[i]* be of size *nLevels[i]*-1.
nLevels Array containing number of levels per color channel.
nLowerLevel Array containing lower-level of lowest bin per color channel.
nUpperLevel Array containing upper-level of highest bin per color channel.
pBuffer Pointer to appropriately sized ([nppiHistogramEvenGetBufferSize_8u_C3R](#)) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.114.2.13 NppStatus nppiHistogramEven_8u_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[4], int nLevels[4], Npp32s nLowerLevel[4], Npp32s nUpperLevel[4], Npp8u * pBuffer)

Four-channel 8-bit unsigned HistogramEven.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).
pHist Array of pointers which are receiving computed histograms per color channel. Array pointed by *pHist[i]* be of size *nLevels[i]*-1.
nLevels Array containing number of levels per color channel.
nLowerLevel Array containing lower-level of lowest bin per color channel.
nUpperLevel Array containing upper-level of highest bin per color channel.
pBuffer Pointer to appropriately sized ([nppiHistogramEvenGetBufferSize_8u_C4R](#)) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.114.2.14 NppStatus nppiHistogramEvenGetBufferSize_16s_AC4R (NppiSize oSizeROI, int nLevels[3], int * hpBufferSize)

Buffer size for [nppiHistogramEven_16s_AC4R](#).

Parameters:

oSizeROI Region-of-Interest (ROI).
nLevels Array containing number of levels per color channel.
hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#)..

7.114.2.15 NppStatus nppiHistogramEvenGetBufferSize_16s_C1R (NppiSize *oSizeROI*, int *nLevels*, int * *hpBufferSize*)

Buffer size for [nppiHistogramEven_16s_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Number of levels in the histogram.

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#)..

7.114.2.16 NppStatus nppiHistogramEvenGetBufferSize_16s_C3R (NppiSize *oSizeROI*, int *nLevels*[3], int * *hpBufferSize*)

Buffer size for [nppiHistogramEven_16s_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Array containing number of levels per color channel.

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#)..

7.114.2.17 NppStatus nppiHistogramEvenGetBufferSize_16s_C4R (NppiSize *oSizeROI*, int *nLevels*[4], int * *hpBufferSize*)

Buffer size for [nppiHistogramEven_16s_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Array containing number of levels per color channel.

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#)..

7.114.2.18 NppStatus nppiHistogramEvenGetBufferSize_16u_AC4R (NppiSize oSizeROI, int nLevels[3], int * hpBufferSize)

Buffer size for [nppiHistogramEven_16u_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Array containing number of levels per color channel.

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#)..

7.114.2.19 NppStatus nppiHistogramEvenGetBufferSize_16u_C1R (NppiSize oSizeROI, int nLevels, int * hpBufferSize)

Buffer size for [nppiHistogramEven_16u_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Number of levels in the histogram.

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#)..

7.114.2.20 NppStatus nppiHistogramEvenGetBufferSize_16u_C3R (NppiSize oSizeROI, int nLevels[3], int * hpBufferSize)

Buffer size for [nppiHistogramEven_16u_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Array containing number of levels per color channel.

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#)..

7.114.2.21 NppStatus nppiHistogramEvenGetBufferSize_16u_C4R (NppiSize oSizeROI, int nLevels[4], int * hpBufferSize)

Buffer size for [nppiHistogramEven_16u_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Array containing number of levels per color channel.

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#)..

7.114.2.22 NppStatus nppiHistogramEvenGetBufferSize_8u_AC4R (NppiSize oSizeROI, int nLevels[3], int * hpBufferSize)

Buffer size for [nppiHistogramEven_8u_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Array containing number of levels per color channel.

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#)..

7.114.2.23 NppStatus nppiHistogramEvenGetBufferSize_8u_C1R (NppiSize oSizeROI, int nLevels, int * hpBufferSize)

Buffer size for [nppiHistogramEven_8u_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Number of levels in the histogram.

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#)..

7.114.2.24 NppStatus nppiHistogramEvenGetBufferSize_8u_C3R (NppiSize oSizeROI, int nLevels[3], int * hpBufferSize)

Buffer size for [nppiHistogramEven_8u_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Number of levels in the histogram.

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#)..

7.114.2.25 NppStatus nppiHistogramEvenGetBufferSize_8u_C4R (NppiSize oSizeROI, int nLevels[4], int * hpBufferSize)

Buffer size for [nppiHistogramEven_8u_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Array containing number of levels per color channel.

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#)..

7.115 HistogramRange

Primitives for computing the histogram of an image within specified ranges.

HistogramEven

The histogram is computed according to the ranges provided in *pLevels*.

The histogram $pHist[k]$ is defined as the total number of pixels that fall into the range: $pLevels[k] \leq pSrc(j, i) < pLevels[k + 1]$. The number of the histogram bins is $nLevel - 1$. The functions require additional scratch buffer for computations.

- `NppStatus nppiHistogramRange_8u_C1R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp32s *pHist`, const `Npp32s *pLevels`, int `nLevels`, `Npp8u *pBuffer`)
One-channel 8-bit unsigned HistogramRange.
- `NppStatus nppiHistogramRange_8u_C3R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp32s *pHist[3]`, const `Npp32s *pLevels[3]`, int `nLevels[3]`, `Npp8u *pBuffer`)
Three-channel 8-bit unsigned HistogramRange.
- `NppStatus nppiHistogramRange_8u_C4R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp32s *pHist[4]`, const `Npp32s *pLevels[4]`, int `nLevels[4]`, `Npp8u *pBuffer`)
Four-channel 8-bit unsigned HistogramRange.
- `NppStatus nppiHistogramRange_8u_AC4R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp32s *pHist[3]`, const `Npp32s *pLevels[3]`, int `nLevels[3]`, `Npp8u *pBuffer`)
Four-channel 8-bit unsigned HistogramRange ignoring alpha channel.
- `NppStatus nppiHistogramRange_16u_C1R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp32s *pHist`, const `Npp32s *pLevels`, int `nLevels`, `Npp8u *pBuffer`)
One-channel 16-bit unsigned HistogramRange.
- `NppStatus nppiHistogramRange_16u_C3R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp32s *pHist[3]`, const `Npp32s *pLevels[3]`, int `nLevels[3]`, `Npp8u *pBuffer`)
Three-channel 16-bit unsigned HistogramRange.
- `NppStatus nppiHistogramRange_16u_C4R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp32s *pHist[4]`, const `Npp32s *pLevels[4]`, int `nLevels[4]`, `Npp8u *pBuffer`)
Four-channel 16-bit unsigned HistogramRange.
- `NppStatus nppiHistogramRange_16u_AC4R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp32s *pHist[3]`, const `Npp32s *pLevels[3]`, int `nLevels[3]`, `Npp8u *pBuffer`)
Four-channel 16-bit unsigned HistogramRange ignoring alpha channel.
- `NppStatus nppiHistogramRange_16s_C1R` (const `Npp16s *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp32s *pHist`, const `Npp32s *pLevels`, int `nLevels`, `Npp8u *pBuffer`)
One-channel 16-bit signed HistogramRange.
- `NppStatus nppiHistogramRange_16s_C3R` (const `Npp16s *pSrc`, int `nSrcStep`, `NppiSize oSizeROI`, `Npp32s *pHist[3]`, const `Npp32s *pLevels[3]`, int `nLevels[3]`, `Npp8u *pBuffer`)
Three-channel 16-bit signed HistogramRange.

- **NppStatus nppiHistogramRange_16s_C4R** (const **Npp16s** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp32s** *pHist[4], const **Npp32s** *pLevels[4], int nLevels[4], **Npp8u** *pBuffer)
Four-channel 16-bit signed HistogramRange.
- **NppStatus nppiHistogramRange_16s_AC4R** (const **Npp16s** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp32s** *pHist[3], const **Npp32s** *pLevels[3], int nLevels[3], **Npp8u** *pBuffer)
Four-channel 16-bit signed HistogramRange.
- **NppStatus nppiHistogramRange_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp32s** *pHist, const **Npp32f** *pLevels, int nLevels, **Npp8u** *pBuffer)
One-channel 32-bit floating point HistogramRange.
- **NppStatus nppiHistogramRange_32f_C3R** (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp32s** *pHist[3], const **Npp32f** *pLevels[3], int nLevels[3], **Npp8u** *pBuffer)
Three-channel 32-bit floating point HistogramRange.
- **NppStatus nppiHistogramRange_32f_C4R** (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp32s** *pHist[4], const **Npp32f** *pLevels[4], int nLevels[4], **Npp8u** *pBuffer)
Four-channel 32-bit floating point HistogramRange.
- **NppStatus nppiHistogramRange_32f_AC4R** (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp32s** *pHist[3], const **Npp32f** *pLevels[3], int nLevels[3], **Npp8u** *pBuffer)
Four-channel 32-bit floating point HistogramRange ignoring alpha channel.

HistogramRangeGetBufferSize

Companion primitives for computing the device buffer size (in bytes) required by the HistogramRange primitives.

- **NppStatus nppiHistogramRangeGetBufferSize_8u_C1R** (**NppiSize** oSizeROI, int nLevels, int *hpBufferSize)
Scratch-buffer size for nppiHistogramRange_8u_C1R.
- **NppStatus nppiHistogramRangeGetBufferSize_8u_C3R** (**NppiSize** oSizeROI, int nLevels[3], int *hpBufferSize)
Scratch-buffer size for nppiHistogramRange_8u_C3R.
- **NppStatus nppiHistogramRangeGetBufferSize_8u_C4R** (**NppiSize** oSizeROI, int nLevels[4], int *hpBufferSize)
Scratch-buffer size for nppiHistogramRange_8u_C4R.
- **NppStatus nppiHistogramRangeGetBufferSize_8u_AC4R** (**NppiSize** oSizeROI, int nLevels[3], int *hpBufferSize)
Scratch-buffer size for nppiHistogramRange_8u_AC4R.
- **NppStatus nppiHistogramRangeGetBufferSize_16u_C1R** (**NppiSize** oSizeROI, int nLevels, int *hpBufferSize)
Scratch-buffer size for nppiHistogramRange_16u_C1R.

- **NppStatus** `nppiHistogramRangeGetBufferSize_16u_C3R` (`NppiSize` `oSizeROI`, `int` `nLevels[3]`, `int` `*hpBufferSize`)
Scratch-buffer size for nppiHistogramRange_16u_C3R.
- **NppStatus** `nppiHistogramRangeGetBufferSize_16u_C4R` (`NppiSize` `oSizeROI`, `int` `nLevels[4]`, `int` `*hpBufferSize`)
Scratch-buffer size for nppiHistogramRange_16u_C4R.
- **NppStatus** `nppiHistogramRangeGetBufferSize_16u_AC4R` (`NppiSize` `oSizeROI`, `int` `nLevels[3]`, `int` `*hpBufferSize`)
Scratch-buffer size for nppiHistogramRange_16u_AC4R.
- **NppStatus** `nppiHistogramRangeGetBufferSize_16s_C1R` (`NppiSize` `oSizeROI`, `int` `nLevels`, `int` `*hpBufferSize`)
Scratch-buffer size for nppiHistogramRange_16s_C1R.
- **NppStatus** `nppiHistogramRangeGetBufferSize_16s_C3R` (`NppiSize` `oSizeROI`, `int` `nLevels[3]`, `int` `*hpBufferSize`)
Scratch-buffer size for nppiHistogramRange_16s_C3R.
- **NppStatus** `nppiHistogramRangeGetBufferSize_16s_C4R` (`NppiSize` `oSizeROI`, `int` `nLevels[4]`, `int` `*hpBufferSize`)
Scratch-buffer size for nppiHistogramRange_16s_C4R.
- **NppStatus** `nppiHistogramRangeGetBufferSize_16s_AC4R` (`NppiSize` `oSizeROI`, `int` `nLevels[3]`, `int` `*hpBufferSize`)
Scratch-buffer size for nppiHistogramRange_16s_AC4R.
- **NppStatus** `nppiHistogramRangeGetBufferSize_32f_C1R` (`NppiSize` `oSizeROI`, `int` `nLevels`, `int` `*hpBufferSize`)
Scratch-buffer size for nppiHistogramRange_32f_C1R.
- **NppStatus** `nppiHistogramRangeGetBufferSize_32f_C3R` (`NppiSize` `oSizeROI`, `int` `nLevels[3]`, `int` `*hpBufferSize`)
Scratch-buffer size for nppiHistogramRange_32f_C3R.
- **NppStatus** `nppiHistogramRangeGetBufferSize_32f_C4R` (`NppiSize` `oSizeROI`, `int` `nLevels[4]`, `int` `*hpBufferSize`)
Scratch-buffer size for nppiHistogramRange_32f_C4R.
- **NppStatus** `nppiHistogramRangeGetBufferSize_32f_AC4R` (`NppiSize` `oSizeROI`, `int` `nLevels[3]`, `int` `*hpBufferSize`)
Scratch-buffer size for nppiHistogramRange_32f_AC4R.

7.115.1 Detailed Description

Primitives for computing the histogram of an image within specified ranges.

7.115.2 Function Documentation

7.115.2.1 `NppStatus nppiHistogramRange_16s_AC4R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[3], const Npp32s * pLevels[3], int nLevels[3], Npp8u * pBuffer)`

Four-channel 16-bit signed HistogramRange.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pHist Array of pointers which are receiving the computed histograms per color channel. Array pointed by pHist[i] must be of size nLevels[i]-1.

nLevels Array containing number of levels per color channel.

pLevels Array containing pointers to level-arrays per color channel. Array pointed by pLevel[i] must be of size nLevels[i].

pBuffer Pointer to appropriately sized (`nppiHistogramRangeGetBufferSize_16s_AC4R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.115.2.2 `NppStatus nppiHistogramRange_16s_C1R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist, const Npp32s * pLevels, int nLevels, Npp8u * pBuffer)`

One-channel 16-bit signed HistogramRange.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pHist Pointer to array that receives the computed histogram. The array must be of size nLevels-1.

pLevels Pointer to array containing the level sizes of the bins. The array must be of size nLevels.

nLevels Number of levels in histogram.

pBuffer Pointer to appropriately sized (`nppiHistogramRangeGetBufferSize_16s_C1R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.115.2.3 `NppStatus nppiHistogramRange_16s_C3R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[3], const Npp32s * pLevels[3], int nLevels[3], Npp8u * pBuffer)`

Three-channel 16-bit signed HistogramRange.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pHist Array of pointers which are receiving the computed histograms per color channel. Array pointed by pHist[i] must be of size nLevels[i]-1.

nLevels Array containing number of levels per color channel.

pLevels Array containing pointers to level-arrays per color channel. Array pointed by pLevel[i] must be of size nLevels[i].

pBuffer Pointer to appropriately sized (`nppiHistogramRangeGetBufferSize_16s_C3R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.115.2.4 `NppStatus nppiHistogramRange_16s_C4R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[4], const Npp32s * pLevels[4], int nLevels[4], Npp8u * pBuffer)`

Four-channel 16-bit signed HistogramRange.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pHist Array of pointers which are receiving the computed histograms per color channel. Array pointed by pHist[i] must be of size nLevels[i]-1.

nLevels Array containing number of levels per color channel.

pLevels Array containing pointers to level-arrays per color channel. Array pointed by pLevel[i] must be of size nLevels[i].

pBuffer Pointer to appropriately sized (`nppiHistogramRangeGetBufferSize_16s_C4R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.115.2.5 `NppStatus nppiHistogramRange_16u_AC4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[3], const Npp32s * pLevels[3], int nLevels[3], Npp8u * pBuffer)`

Four-channel 16-bit unsigned HistogramRange ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pHist Array of pointers which are receiving the computed histograms per color channel. Array pointed by *pHist*[*i*] must be of size *nLevels*[*i*]-1.

nLevels Array containing number of levels per color channel.

pLevels Array containing pointers to level-arrays per color channel. Array pointed by *pLevel*[*i*] must be of size *nLevels*[*i*].

pBuffer Pointer to appropriately sized ([nppiHistogramRangeGetBufferSize_16u_AC4R](#)) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.115.2.6 `NppStatus nppiHistogramRange_16u_C1R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist, const Npp32s * pLevels, int nLevels, Npp8u * pBuffer)`

One-channel 16-bit unsigned HistogramRange.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pHist Pointer to array that receives the computed histogram. The array must be of size *nLevels*-1.

pLevels Pointer to array containing the level sizes of the bins. The array must be of size *nLevels*.

nLevels Number of levels in histogram.

pBuffer Pointer to appropriately sized ([nppiHistogramRangeGetBufferSize_16u_C1R](#)) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.115.2.7 `NppStatus nppiHistogramRange_16u_C3R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[3], const Npp32s * pLevels[3], int nLevels[3], Npp8u * pBuffer)`

Three-channel 16-bit unsigned HistogramRange.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pHist Array of pointers which are receiving the computed histograms per color channel. Array pointed by pHist[i] must be of size nLevels[i]-1.

nLevels Array containing number of levels per color channel.

pLevels Array containing pointers to level-arrays per color channel. Array pointed by pLevel[i] must be of size nLevels[i].

pBuffer Pointer to appropriately sized ([nppiHistogramRangeGetBufferSize_16u_C3R](#)) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.115.2.8 `NppStatus nppiHistogramRange_16u_C4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[4], const Npp32s * pLevels[4], int nLevels[4], Npp8u * pBuffer)`

Four-channel 16-bit unsigned HistogramRange.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pHist Array of pointers which are receiving the computed histograms per color channel. Array pointed by pHist[i] must be of size nLevels[i]-1.

nLevels Array containing number of levels per color channel.

pLevels Array containing pointers to level-arrays per color channel. Array pointed by pLevel[i] must be of size nLevels[i].

pBuffer Pointer to appropriately sized ([nppiHistogramRangeGetBufferSize_16u_C4R](#)) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.115.2.9 `NppStatus nppiHistogramRange_32f_AC4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[3], const Npp32f * pLevels[3], int nLevels[3], Npp8u * pBuffer)`

Four-channel 32-bit floating point HistogramRange ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pHist Array of pointers which are receiving the computed histograms per color channel. Array pointed by pHist[i] must be of size nLevels[i]-1.

nLevels Array containing number of levels per color channel.

pLevels Array containing pointers to level-arrays per color channel. Array pointed by *pLevel[i]* must be of size *nLevels[i]*.

pBuffer Pointer to appropriately sized (`nppiHistogramRangeGetBufferSize_32f_AC4R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.115.2.10 NppStatus nppiHistogramRange_32f_C1R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist, const Npp32f * pLevels, int nLevels, Npp8u * pBuffer)

One-channel 32-bit floating point HistogramRange.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pHist Pointer to array that receives the computed histogram. The array must be of size *nLevels*-1.

pLevels Pointer to array containing the level sizes of the bins. The array must be of size *nLevels*.

nLevels Number of levels in histogram.

pBuffer Pointer to appropriately sized (`nppiHistogramRangeGetBufferSize_32f_C1R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.115.2.11 NppStatus nppiHistogramRange_32f_C3R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[3], const Npp32f * pLevels[3], int nLevels[3], Npp8u * pBuffer)

Three-channel 32-bit floating point HistogramRange.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pHist Array of pointers which are receiving the computed histograms per color channel. Array pointed by *pHist[i]* must be of size *nLevels[i]*-1.

nLevels Array containing number of levels per color channel.

pLevels Array containing pointers to level-arrays per color channel. Array pointed by *pLevel[i]* must be of size *nLevels[i]*.

pBuffer Pointer to appropriately sized (`nppiHistogramRangeGetBufferSize_32f_C3R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.115.2.12 `NppStatus nppiHistogramRange_32f_C4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[4], const Npp32f * pLevels[4], int nLevels[4], Npp8u * pBuffer)`

Four-channel 32-bit floating point HistogramRange.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pHist Array of pointers which are receiving the computed histograms per color channel. Array pointed by pHist[i] must be of size nLevels[i]-1.

nLevels Array containing number of levels per color channel.

pLevels Array containing pointers to level-arrays per color channel. Array pointed by pLevel[i] must be of size nLevels[i].

pBuffer Pointer to appropriately sized (`nppiHistogramRangeGetBufferSize_32f_C4R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.115.2.13 `NppStatus nppiHistogramRange_8u_AC4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[3], const Npp32s * pLevels[3], int nLevels[3], Npp8u * pBuffer)`

Four-channel 8-bit unsigned HistogramRange ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pHist Array of pointers which are receiving the computed histograms per color channel. Array pointed by pHist[i] must be of size nLevels[i]-1.

nLevels Array containing number of levels per color channel.

pLevels Array containing pointers to level-arrays per color channel. Array pointed by pLevel[i] must be of size nLevels[i].

pBuffer Pointer to appropriately sized (`nppiHistogramRangeGetBufferSize_8u_AC4R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.115.2.14 `NppStatus nppiHistogramRange_8u_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist, const Npp32s * pLevels, int nLevels, Npp8u * pBuffer)`

One-channel 8-bit unsigned HistogramRange.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pHist Pointer to array that receives the computed histogram. The array must be of size nLevels-1.

pLevels Pointer to array containing the level sizes of the bins. The array must be of size nLevels.

nLevels Number of levels in histogram.

pBuffer Pointer to appropriately sized ([nppiHistogramRangeGetBufferSize_8u_C1R](#)) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.115.2.15 `NppStatus nppiHistogramRange_8u_C3R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[3], const Npp32s * pLevels[3], int nLevels[3], Npp8u * pBuffer)`

Three-channel 8-bit unsigned HistogramRange.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pHist Array of pointers which are receiving the computed histograms per color channel. Array pointed by pHist[i] must be of size nLevels[i]-1.

nLevels Array containing number of levels per color channel.

pLevels Array containing pointers to level-arrays per color channel. Array pointed by pLevel[i] must be of size nLevels[i].

pBuffer Pointer to appropriately sized ([nppiHistogramRangeGetBufferSize_8u_C3R](#)) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.115.2.16 `NppStatus nppiHistogramRange_8u_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[4], const Npp32s * pLevels[4], int nLevels[4], Npp8u * pBuffer)`

Four-channel 8-bit unsigned HistogramRange.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pHist Array of pointers which are receiving the computed histograms per color channel. Array pointed by *pHist[i]* must be of size *nLevels[i]-1*.

nLevels Array containing number of levels per color channel.

pLevels Array containing pointers to level-arrays per color channel. Array pointed by *pLevel[i]* must be of size *nLevels[i]*.

pBuffer Pointer to appropriately sized ([nppiHistogramRangeGetBufferSize_8u_C4R](#)) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.115.2.17 NppStatus nppiHistogramRangeGetBufferSize_16s_AC4R (NppiSize oSizeROI, int nLevels[3], int * hpBufferSize)

Scratch-buffer size for [nppiHistogramRange_16s_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Array containing number of levels per color channel.

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

[NPP_NULL_POINTER_ERROR](#) if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#)..

7.115.2.18 NppStatus nppiHistogramRangeGetBufferSize_16s_C1R (NppiSize oSizeROI, int nLevels, int * hpBufferSize)

Scratch-buffer size for [nppiHistogramRange_16s_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Number of levels in the histogram.

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

[NPP_NULL_POINTER_ERROR](#) if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#)..

7.115.2.19 NppStatus nppiHistogramRangeGetBufferSize_16s_C3R (NppiSize oSizeROI, int nLevels[3], int * hpBufferSize)

Scratch-buffer size for nppiHistogramRange_16s_C3R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Array containing number of levels per color channel.

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if hpBufferSize is 0 (NULL), [ROI Related Error Codes](#)..

7.115.2.20 NppStatus nppiHistogramRangeGetBufferSize_16s_C4R (NppiSize oSizeROI, int nLevels[4], int * hpBufferSize)

Scratch-buffer size for nppiHistogramRange_16s_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Array containing number of levels per color channel.

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if hpBufferSize is 0 (NULL), [ROI Related Error Codes](#)..

7.115.2.21 NppStatus nppiHistogramRangeGetBufferSize_16u_AC4R (NppiSize oSizeROI, int nLevels[3], int * hpBufferSize)

Scratch-buffer size for nppiHistogramRange_16u_AC4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Array containing number of levels per color channel.

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if hpBufferSize is 0 (NULL), [ROI Related Error Codes](#)..

7.115.2.22 NppStatus nppiHistogramRangeGetBufferSize_16u_C1R (NppiSize oSizeROI, int nLevels, int * hpBufferSize)

Scratch-buffer size for nppiHistogramRange_16u_C1R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Number of levels in the histogram.

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#)..

7.115.2.23 NppStatus nppiHistogramRangeGetBufferSize_16u_C3R (NppiSize oSizeROI, int nLevels[3], int * hpBufferSize)

Scratch-buffer size for nppiHistogramRange_16u_C3R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Array containing number of levels per color channel.

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#)..

7.115.2.24 NppStatus nppiHistogramRangeGetBufferSize_16u_C4R (NppiSize oSizeROI, int nLevels[4], int * hpBufferSize)

Scratch-buffer size for nppiHistogramRange_16u_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Array containing number of levels per color channel.

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#)..

7.115.2.25 NppStatus nppiHistogramRangeGetBufferSize_32f_AC4R (NppiSize oSizeROI, int nLevels[3], int * hpBufferSize)

Scratch-buffer size for nppiHistogramRange_32f_AC4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Array containing number of levels per color channel.

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if hpBufferSize is 0 (NULL), [ROI Related Error Codes](#)..

7.115.2.26 NppStatus nppiHistogramRangeGetBufferSize_32f_C1R (NppiSize oSizeROI, int nLevels, int * hpBufferSize)

Scratch-buffer size for nppiHistogramRange_32f_C1R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Number of levels in the histogram.

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if hpBufferSize is 0 (NULL), [ROI Related Error Codes](#)..

7.115.2.27 NppStatus nppiHistogramRangeGetBufferSize_32f_C3R (NppiSize oSizeROI, int nLevels[3], int * hpBufferSize)

Scratch-buffer size for nppiHistogramRange_32f_C3R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Array containing number of levels per color channel.

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if hpBufferSize is 0 (NULL), [ROI Related Error Codes](#)..

7.115.2.28 NppStatus nppiHistogramRangeGetBufferSize_32f_C4R (NppiSize oSizeROI, int nLevels[4], int * hpBufferSize)

Scratch-buffer size for nppiHistogramRange_32f_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Array containing number of levels per color channel.

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if hpBufferSize is 0 (NULL), [ROI Related Error Codes](#)..

7.115.2.29 NppStatus nppiHistogramRangeGetBufferSize_8u_AC4R (NppiSize oSizeROI, int nLevels[3], int * hpBufferSize)

Scratch-buffer size for nppiHistogramRange_8u_AC4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Array containing number of levels per color channel.

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if hpBufferSize is 0 (NULL), [ROI Related Error Codes](#)..

7.115.2.30 NppStatus nppiHistogramRangeGetBufferSize_8u_C1R (NppiSize oSizeROI, int nLevels, int * hpBufferSize)

Scratch-buffer size for nppiHistogramRange_8u_C1R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Number of levels in the histogram.

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if hpBufferSize is 0 (NULL), [ROI Related Error Codes](#)..

7.115.2.31 NppStatus nppiHistogramRangeGetBufferSize_8u_C3R (NppiSize oSizeROI, int nLevels[3], int * hpBufferSize)

Scratch-buffer size for nppiHistogramRange_8u_C3R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Array containing number of levels per color channel.

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#)..

7.115.2.32 NppStatus nppiHistogramRangeGetBufferSize_8u_C4R (NppiSize oSizeROI, int nLevels[4], int * hpBufferSize)

Scratch-buffer size for nppiHistogramRange_8u_C4R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Array containing number of levels per color channel.

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#)..

7.116 Image Proximity

Primitives for computing the proximity measure between a source image and a template image.

Modules

- [SqrDistanceFull_Norm](#)
Primitives for computing the normalized Euclidean distance between two images with full mode.
- [SqrDistanceSame_Norm](#)
Primitives for computing the normalized Euclidean distance between two images with same mode.
- [SqrDistanceValid_Norm](#)
Primitives for computing the normalized Euclidean distance between two images with valid mode.
- [CrossCorrFull_Norm](#)
Primitives for computing the normalized cross correlation between two images with full mode.
- [CrossCorrSame_Norm](#)
Primitives for computing the normalized cross correlation between two images with same mode.
- [CrossCorrValid_Norm](#)
Primitives for computing the normalized cross correlation between two images with valid mode.
- [CrossCorrValid](#)
Primitives for computing the cross correlation between two images with valid mode.
- [CrossCorrFull_NormLevel](#)
Primitives for computing the normalized cross correlation coefficient between two images with full mode.
- [CrossCorrSame_NormLevel](#)
Primitives for computing the normalized cross correlation coefficient between two images with same mode.
- [CrossCorrValid_NormLevel](#)
Primitives for computing the normalized cross correlation coefficient between two images with valid mode.

7.116.1 Detailed Description

Primitives for computing the proximity measure between a source image and a template image.

7.116.2 General Introduction

There are basically two approaches to compute the proximity measure for template matching, Euclidean distance and the cross correlation.

1. Euclidean distance computes the sum of the squared distance (SSD) between the corresponding pixels of the source image and the template image. The smaller the distance is, the more similar the source image and the template image is around the pixel. The anchor of the template image is used during the computations, which always lies in the gemotric center of the image. Given a source image $pSrc$ ($W_s \times H_s$) and a template image $pTpl$ ($W_t \times H_t$), the Euclidean distance $D_{st}(c, r)$ between two images at pixel r and column c is computed as (s stands for source image and t for template image for short):

$$D_{st}(c, r) = \sum_{j=0}^{H_t-1} \sum_{i=0}^{W_t-1} [pTpl(j, i) - pSrc(j + c - \frac{H_t}{2}, i + r - \frac{W_t}{2})]^2$$

2. Cross correlation computes the sum of the product between the corresponding pixels of the source image and the template image. The cross correlation $R_{st}(c, r)$ is calculated as:

$$R_{st}(c, r) = \sum_{j=0}^{H_t-1} \sum_{i=0}^{W_t-1} [pTpl(j, i) \cdot pSrc(j + c - \frac{H_t}{2}, i + r - \frac{W_t}{2})]$$

The larger the cross correlation value is, the more similar the source image and the template image is around the pixel.

3. The cross correlation $R_{st}(c, r)$ is affected by the brightness of the images which may vary due to the lighting and exposure conditions. Therefore, NPP computes the cross correlation coefficient to circumvent this dependence. This is typically done at every step by subtracting the mean from every pixel value, i.e.,

$$\tilde{R}_{st}(c, r) = \sum_{j=0}^{H_t-1} \sum_{i=0}^{W_t-1} [pTpl(j, i) - Mean_t] \cdot [pSrc(j + c - \frac{H_t}{2}, i + r - \frac{W_t}{2}) - Mean_s]$$

NPP computes the normalized values of Euclidean distance, cross correlation and the cross correlation coefficient.

1. The normalized Euclidean distance $\sigma_{st}(c, r)$ is defined as:

$$\sigma_{st}(c, r) = \frac{D_{st}(c, r)}{\sqrt{R_{ss}(c, r) \cdot R_{tt}(\frac{H_t}{2}, \frac{W_t}{2})}}$$

2. The normalized cross correlation $\rho_{st}(c, r)$ is defined as:

$$\rho_{st}(c, r) = \frac{R_{st}(c, r)}{\sqrt{R_{ss}(c, r) \cdot R_{tt}(\frac{H_t}{2}, \frac{W_t}{2})}}$$

The $R_{ss}(c, r)$ and $R_{tt}(\frac{H_t}{2}, \frac{W_t}{2})$ denote the auto correlation of the source image and the template image individually. They are defined as:

$$R_{ss}(c, r) = \sum_{j=c-\frac{H_t}{2}}^{c+\frac{H_t}{2}} \sum_{i=r-\frac{W_t}{2}}^{r+\frac{W_t}{2}} pSrc(j, i)$$

$$R_{tt}(\frac{H_t}{2}, \frac{W_t}{2}) = \sum_{j=0}^{H_t-1} \sum_{i=0}^{W_t-1} pTpl(j, i)$$

3. Similarly, the normalized cross correlation coefficient $\gamma_{st}(c, r)$ is calculated as:

$$\gamma_{st}(c, r) = \frac{\tilde{R}_{st}(c, r)}{\sqrt{\tilde{R}_{ss}(c, r) \cdot \tilde{R}_{tt}(\frac{H_t}{2}, \frac{W_t}{2})}}$$

The $\tilde{R}_{ss}(c, r)$ and $\tilde{R}_{tt}(\frac{H_t}{2}, \frac{W_t}{2})$ are defined as:

$$\tilde{R}_{ss}(c, r) = \sum_{j=c-\frac{H_t}{2}}^{c+\frac{H_t}{2}} \sum_{i=r-\frac{W_t}{2}}^{r+\frac{W_t}{2}} [pSrc(j, i) - Mean_s]$$

$$\tilde{R}_{tt}(\frac{H_t}{2}, \frac{W_t}{2}) = \sum_{j=0}^{H_t-1} \sum_{i=0}^{W_t-1} [pTpl(j, i) - Mean_t]$$

7.116.3 Categorizations

The Euclidean distance and the cross correlation are categorized into three types, full, same, and valid.

1. Full mode indicates that the anchor of the template image starts from the outside of the source image, assuming the out-of-boundary pixels are zero-padded. The size of the destination image is $(W_s + W_t - 1) \times (H_s + H_t - 1)$.
2. Same mode means that the anchor of the template image starts from the top left pixel of the source image. All the out-of-boundary pixels are also zero-padded. The size of the destination image is the same as the source one, i.e., $W_s \times H_s$.
3. Valid mode indicates that there are no out-of-boundary readings from the source image. The anchor of the template image starts from the inside of the source image. The size of the destination image is $(W_s - W_t + 1) \times (H_s - H_t + 1)$.

7.117 SqrDistanceFull_Norm

Primitives for computing the normalized Euclidean distance between two images with full mode.

SqrDistanceFull_Norm

The functions compute the $\sigma_{st}(c, r)$ in [General Introduction](#) with full mode (see [Categorizations](#)).

- [NppStatus nppiSqrDistanceFull_Norm_8u_C1RSfs](#) (const [Npp8u](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8u](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp8u](#) *pDst, int nDstStep, int nScaleFactor)
One-channel 8-bit unsigned image SqrDistanceFull_Norm, scaled by $2^{\ell} - nScaleFactor$.
- [NppStatus nppiSqrDistanceFull_Norm_8u_C3RSfs](#) (const [Npp8u](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8u](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp8u](#) *pDst, int nDstStep, int nScaleFactor)
Three-channel 8-bit unsigned image SqrDistanceFull_Norm, scaled by $2^{\ell} - nScaleFactor$.
- [NppStatus nppiSqrDistanceFull_Norm_8u_C4RSfs](#) (const [Npp8u](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8u](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp8u](#) *pDst, int nDstStep, int nScaleFactor)
Four-channel 8-bit unsigned image SqrDistanceFull_Norm, scaled by $2^{\ell} - nScaleFactor$.
- [NppStatus nppiSqrDistanceFull_Norm_8u_AC4RSfs](#) (const [Npp8u](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8u](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp8u](#) *pDst, int nDstStep, int nScaleFactor)
Four-channel 8-bit unsigned image SqrDistanceFull_Norm ignoring alpha channel, scaled by $2^{\ell} - nScaleFactor$.
- [NppStatus nppiSqrDistanceFull_Norm_32f_C1R](#) (const [Npp32f](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp32f](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)
One-channel 32-bit floating point image SqrDistanceFull_Norm.
- [NppStatus nppiSqrDistanceFull_Norm_32f_C3R](#) (const [Npp32f](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp32f](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)
Three-channel 32-bit floating point image SqrDistanceFull_Norm.
- [NppStatus nppiSqrDistanceFull_Norm_32f_C4R](#) (const [Npp32f](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp32f](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)
Four-channel 32-bit floating point image SqrDistanceFull_Norm.
- [NppStatus nppiSqrDistanceFull_Norm_32f_AC4R](#) (const [Npp32f](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp32f](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)
Four-channel 32-bit floating point image SqrDistanceFull_Norm ignoring alpha channel.
- [NppStatus nppiSqrDistanceFull_Norm_8u32f_C1R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8u](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)
One-channel 8-bit unsigned image SqrDistanceFull_Norm.
- [NppStatus nppiSqrDistanceFull_Norm_8u32f_C3R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8u](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)

Three-channel 8-bit unsigned image SqrDistanceFull_Norm.

- `NppStatus nppiSqrDistanceFull_Norm_8u32f_C4R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Four-channel 8-bit unsigned image SqrDistanceFull_Norm.

- `NppStatus nppiSqrDistanceFull_Norm_8u32f_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Four-channel 8-bit unsigned image SqrDistanceFull_Norm ignoring alpha channel.

- `NppStatus nppiSqrDistanceFull_Norm_8s32f_C1R` (const `Npp8s` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8s` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

One-channel 8-bit signed image SqrDistanceFull_Norm.

- `NppStatus nppiSqrDistanceFull_Norm_8s32f_C3R` (const `Npp8s` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8s` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Three-channel 8-bit signed image SqrDistanceFull_Norm.

- `NppStatus nppiSqrDistanceFull_Norm_8s32f_C4R` (const `Npp8s` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8s` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Four-channel 8-bit signed image SqrDistanceFull_Norm.

- `NppStatus nppiSqrDistanceFull_Norm_8s32f_AC4R` (const `Npp8s` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8s` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Four-channel 8-bit signed image SqrDistanceFull_Norm ignoring alpha channel.

- `NppStatus nppiSqrDistanceFull_Norm_16u32f_C1R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp16u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

One-channel 16-bit unsigned image SqrDistanceFull_Norm.

- `NppStatus nppiSqrDistanceFull_Norm_16u32f_C3R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp16u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Three-channel 16-bit unsigned image SqrDistanceFull_Norm.

- `NppStatus nppiSqrDistanceFull_Norm_16u32f_C4R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp16u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Four-channel 16-bit unsigned image SqrDistanceFull_Norm.

- `NppStatus nppiSqrDistanceFull_Norm_16u32f_AC4R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp16u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Four-channel 16-bit unsigned image SqrDistanceFull_Norm ignoring alpha channel.

7.117.1 Detailed Description

Primitives for computing the normalized Euclidean distance between two images with full mode.

7.117.2 Function Documentation

7.117.2.1 `NppStatus nppiSqrDistanceFull_Norm_16u32f_AC4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 16-bit unsigned image SqrDistanceFull_Norm ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.117.2.2 `NppStatus nppiSqrDistanceFull_Norm_16u32f_C1R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

One-channel 16-bit unsigned image SqrDistanceFull_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.117.2.3 `NppStatus nppiSqrDistanceFull_Norm_16u32f_C3R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Three-channel 16-bit unsigned image SqrDistanceFull_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.117.2.4 `NppStatus nppiSqrDistanceFull_Norm_16u32f_C4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 16-bit unsigned image SqrDistanceFull_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.117.2.5 `NppStatus nppiSqrDistanceFull_Norm_32f_AC4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 32-bit floating point image SqrDistanceFull_Norm ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.117.2.6 `NppStatus nppiSqrDistanceFull_Norm_32f_C1R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

One-channel 32-bit floating point image SqrDistanceFull_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.117.2.7 `NppStatus nppiSqrDistanceFull_Norm_32f_C3R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Three-channel 32-bit floating point image SqrDistanceFull_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.117.2.8 `NppStatus nppiSqrDistanceFull_Norm_32f_C4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 32-bit floating point image SqrDistanceFull_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.117.2.9 `NppStatus nppiSqrDistanceFull_Norm_8s32f_AC4R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 8-bit signed image SqrDistanceFull_Norm ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.117.2.10 `NppStatus nppiSqrDistanceFull_Norm_8s32f_C1R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

One-channel 8-bit signed image SqrDistanceFull_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.117.2.11 `NppStatus nppiSqrDistanceFull_Norm_8s32f_C3R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Three-channel 8-bit signed image SqrDistanceFull_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.117.2.12 `NppStatus nppiSqrDistanceFull_Norm_8s32f_C4R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 8-bit signed image SqrDistanceFull_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.117.2.13 **NppStatus nppiSqrDistanceFull_Norm_8u32f_AC4R** (const Npp8u * *pSrc*, int *nSrcStep*, NppiSize *oSrcRoiSize*, const Npp8u * *pTpl*, int *nTplStep*, NppiSize *oTplRoiSize*, Npp32f * *pDst*, int *nDstStep*)

Four-channel 8-bit unsigned image SqrDistanceFull_Norm ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.117.2.14 **NppStatus nppiSqrDistanceFull_Norm_8u32f_C1R** (const Npp8u * *pSrc*, int *nSrcStep*, NppiSize *oSrcRoiSize*, const Npp8u * *pTpl*, int *nTplStep*, NppiSize *oTplRoiSize*, Npp32f * *pDst*, int *nDstStep*)

One-channel 8-bit unsigned image SqrDistanceFull_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.117.2.15 `NppStatus nppiSqrDistanceFull_Norm_8u32f_C3R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Three-channel 8-bit unsigned image SqrDistanceFull_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.117.2.16 `NppStatus nppiSqrDistanceFull_Norm_8u32f_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 8-bit unsigned image SqrDistanceFull_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.117.2.17 NppStatus nppiSqrDistanceFull_Norm_8u_AC4RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor)

Four-channel 8-bit unsigned image SqrDistanceFull_Norm ignoring alpha channel, scaled by $2^{(- nScaleFactor)}$.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- oSrcRoiSize* Region-of-Interest (ROI).
- pTpl* Pointer to the template image.
- nTplStep* Number of bytes between successive rows in the template image.
- oTplRoiSize* Region-of-Interest (ROI).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.117.2.18 NppStatus nppiSqrDistanceFull_Norm_8u_C1RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor)

One-channel 8-bit unsigned image SqrDistanceFull_Norm, scaled by $2^{(- nScaleFactor)}$.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- oSrcRoiSize* Region-of-Interest (ROI).
- pTpl* Pointer to the template image.
- nTplStep* Number of bytes between successive rows in the template image.
- oTplRoiSize* Region-of-Interest (ROI).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.117.2.19 `NppStatus nppiSqrDistanceFull_Norm_8u_C3RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor)`

Three-channel 8-bit unsigned image SqrDistanceFull_Norm, scaled by $2^{(- nScaleFactor)}$.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.117.2.20 `NppStatus nppiSqrDistanceFull_Norm_8u_C4RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor)`

Four-channel 8-bit unsigned image SqrDistanceFull_Norm, scaled by $2^{(- nScaleFactor)}$.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.118 SqrDistanceSame_Norm

Primitives for computing the normalized Euclidean distance between two images with same mode.

SqrDistanceSame_Norm

The functions compute the $\sigma_{st}(c, r)$ in [General Introduction](#) with same mode (see [Categorizations](#)).

- `NppStatus nppiSqrDistanceSame_Norm_8u_C1RSfs` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp8u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp8u *pDst`, int `nDstStep`, int `nScaleFactor`)
One-channel 8-bit unsigned image SqrDistanceSame_Norm, scaled by $2^{\ell - nScaleFactor}$.
- `NppStatus nppiSqrDistanceSame_Norm_8u_C3RSfs` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp8u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp8u *pDst`, int `nDstStep`, int `nScaleFactor`)
Three-channel 8-bit unsigned image SqrDistanceSame_Norm, scaled by $2^{\ell - nScaleFactor}$.
- `NppStatus nppiSqrDistanceSame_Norm_8u_C4RSfs` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp8u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp8u *pDst`, int `nDstStep`, int `nScaleFactor`)
Four-channel 8-bit unsigned image SqrDistanceSame_Norm, scaled by $2^{\ell - nScaleFactor}$.
- `NppStatus nppiSqrDistanceSame_Norm_8u_AC4RSfs` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp8u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp8u *pDst`, int `nDstStep`, int `nScaleFactor`)
Four-channel 8-bit unsigned image SqrDistanceSame_Norm ignoring alpha channel, scaled by $2^{\ell - nScaleFactor}$.
- `NppStatus nppiSqrDistanceSame_Norm_32f_C1R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp32f *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`)
One-channel 32-bit floating point image SqrDistanceSame_Norm.
- `NppStatus nppiSqrDistanceSame_Norm_32f_C3R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp32f *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`)
Three-channel 32-bit floating point image SqrDistanceSame_Norm.
- `NppStatus nppiSqrDistanceSame_Norm_32f_C4R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp32f *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`)
Four-channel 32-bit floating point image SqrDistanceSame_Norm.
- `NppStatus nppiSqrDistanceSame_Norm_32f_AC4R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp32f *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`)
Four-channel 32-bit floating point image SqrDistanceSame_Norm ignoring alpha channel.
- `NppStatus nppiSqrDistanceSame_Norm_8u32f_C1R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp8u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`)
One-channel 8-bit unsigned image SqrDistanceSame_Norm.

- [NppStatus nppiSqrDistanceSame_Norm_8u32f_C3R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8u](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)
Three-channel 8-bit unsigned image SqrDistanceSame_Norm.
- [NppStatus nppiSqrDistanceSame_Norm_8u32f_C4R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8u](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)
Four-channel 8-bit unsigned image SqrDistanceSame_Norm.
- [NppStatus nppiSqrDistanceSame_Norm_8u32f_AC4R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8u](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)
Four-channel 8-bit unsigned image SqrDistanceSame_Norm ignoring alpha channel.
- [NppStatus nppiSqrDistanceSame_Norm_8s32f_C1R](#) (const [Npp8s](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8s](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)
One-channel 8-bit signed image SqrDistanceSame_Norm.
- [NppStatus nppiSqrDistanceSame_Norm_8s32f_C3R](#) (const [Npp8s](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8s](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)
Three-channel 8-bit signed image SqrDistanceSame_Norm.
- [NppStatus nppiSqrDistanceSame_Norm_8s32f_C4R](#) (const [Npp8s](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8s](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)
Four-channel 8-bit signed image SqrDistanceSame_Norm.
- [NppStatus nppiSqrDistanceSame_Norm_8s32f_AC4R](#) (const [Npp8s](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8s](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)
Four-channel 8-bit signed image SqrDistanceSame_Norm ignoring alpha channel.
- [NppStatus nppiSqrDistanceSame_Norm_16u32f_C1R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp16u](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)
One-channel 16-bit unsigned image SqrDistanceSame_Norm.
- [NppStatus nppiSqrDistanceSame_Norm_16u32f_C3R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp16u](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)
Three-channel 16-bit unsigned image SqrDistanceSame_Norm.
- [NppStatus nppiSqrDistanceSame_Norm_16u32f_C4R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp16u](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)
Four-channel 16-bit unsigned image SqrDistanceSame_Norm.

- `NppStatus nppiSqrDistanceSame_Norm_16u32f_AC4R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize oSrcRoiSize`, const `Npp16u *pTpl`, int `nTplStep`, `NppiSize oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`)

Four-channel 16-bit unsigned image SqrDistanceSame_Norm ignoring alpha channel.

7.118.1 Detailed Description

Primitives for computing the normalized Euclidean distance between two images with same mode.

7.118.2 Function Documentation

- 7.118.2.1 `NppStatus nppiSqrDistanceSame_Norm_16u32f_AC4R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize oSrcRoiSize`, const `Npp16u *pTpl`, int `nTplStep`, `NppiSize oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`)

Four-channel 16-bit unsigned image SqrDistanceSame_Norm ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- 7.118.2.2 `NppStatus nppiSqrDistanceSame_Norm_16u32f_C1R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize oSrcRoiSize`, const `Npp16u *pTpl`, int `nTplStep`, `NppiSize oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`)

One-channel 16-bit unsigned image SqrDistanceSame_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.118.2.3 `NppStatus nppiSqrDistanceSame_Norm_16u32f_C3R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Three-channel 16-bit unsigned image SqrDistanceSame_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.118.2.4 `NppStatus nppiSqrDistanceSame_Norm_16u32f_C4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 16-bit unsigned image SqrDistanceSame_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.118.2.5 `NppStatus nppiSqrDistanceSame_Norm_32f_AC4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 32-bit floating point image SqrDistanceSame_Norm ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.118.2.6 `NppStatus nppiSqrDistanceSame_Norm_32f_C1R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

One-channel 32-bit floating point image SqrDistanceSame_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.118.2.7 `NppStatus nppiSqrDistanceSame_Norm_32f_C3R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Three-channel 32-bit floating point image SqrDistanceSame_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.118.2.8 `NppStatus nppiSqrDistanceSame_Norm_32f_C4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 32-bit floating point image SqrDistanceSame_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.118.2.9 `NppStatus nppiSqrDistanceSame_Norm_8s32f_AC4R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 8-bit signed image SqrDistanceSame_Norm ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.118.2.10 `NppStatus nppiSqrDistanceSame_Norm_8s32f_C1R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

One-channel 8-bit signed image SqrDistanceSame_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.118.2.11 `NppStatus nppiSqrDistanceSame_Norm_8s32f_C3R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Three-channel 8-bit signed image SqrDistanceSame_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.118.2.12 `NppStatus nppiSqrDistanceSame_Norm_8s32f_C4R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 8-bit signed image SqrDistanceSame_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.118.2.13 `NppStatus nppiSqrDistanceSame_Norm_8u32f_AC4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 8-bit unsigned image SqrDistanceSame_Norm ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.118.2.14 `NppStatus nppiSqrDistanceSame_Norm_8u32f_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

One-channel 8-bit unsigned image SqrDistanceSame_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.118.2.15 `NppStatus nppiSqrDistanceSame_Norm_8u32f_C3R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Three-channel 8-bit unsigned image SqrDistanceSame_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.118.2.16 `NppStatus nppiSqrDistanceSame_Norm_8u32f_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 8-bit unsigned image SqrDistanceSame_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.118.2.17 `NppStatus nppiSqrDistanceSame_Norm_8u_AC4RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor)`

Four-channel 8-bit unsigned image SqrDistanceSame_Norm ignoring alpha channel, scaled by $2^{(- nScaleFactor)}$.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.118.2.18 `NppStatus nppiSqrDistanceSame_Norm_8u_C1RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor)`

One-channel 8-bit unsigned image SqrDistanceSame_Norm, scaled by $2^{(- nScaleFactor)}$.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.118.2.19 `NppStatus nppiSqrDistanceSame_Norm_8u_C3RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor)`

Three-channel 8-bit unsigned image SqrDistanceSame_Norm, scaled by $2^{(- nScaleFactor)}$.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.118.2.20 `NppStatus nppiSqrDistanceSame_Norm_8u_C4RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor)`

Four-channel 8-bit unsigned image SqrDistanceSame_Norm, scaled by $2^{(- nScaleFactor)}$.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.119 SqrDistanceValid_Norm

Primitives for computing the normalized Euclidean distance between two images with valid mode.

SqrDistanceValid_Norm

The functions compute the $\sigma_{st}(c, r)$ in [General Introduction](#) with valid mode (see [Categorizations](#)).

- `NppStatus nppiSqrDistanceValid_Norm_8u_C1RSfs` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp8u` *pDst, int nDstStep, int nScaleFactor)
One-channel 8-bit unsigned image SqrDistanceValid_Norm, scaled by $2^{\ell - nScaleFactor}$.
- `NppStatus nppiSqrDistanceValid_Norm_8u_C3RSfs` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp8u` *pDst, int nDstStep, int nScaleFactor)
Three-channel 8-bit unsigned image SqrDistanceValid_Norm, scaled by $2^{\ell - nScaleFactor}$.
- `NppStatus nppiSqrDistanceValid_Norm_8u_C4RSfs` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp8u` *pDst, int nDstStep, int nScaleFactor)
Four-channel 8-bit unsigned image SqrDistanceValid_Norm, scaled by $2^{\ell - nScaleFactor}$.
- `NppStatus nppiSqrDistanceValid_Norm_8u_AC4RSfs` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp8u` *pDst, int nDstStep, int nScaleFactor)
Four-channel 8-bit unsigned image SqrDistanceValid_Norm ignoring alpha channel, scaled by $2^{\ell - nScaleFactor}$.
- `NppStatus nppiSqrDistanceValid_Norm_32f_C1R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp32f` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)
One-channel 32-bit floating point image SqrDistanceValid_Norm.
- `NppStatus nppiSqrDistanceValid_Norm_32f_C3R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp32f` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)
Three-channel 32-bit floating point image SqrDistanceValid_Norm.
- `NppStatus nppiSqrDistanceValid_Norm_32f_C4R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp32f` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)
Four-channel 32-bit floating point image SqrDistanceValid_Norm.
- `NppStatus nppiSqrDistanceValid_Norm_32f_AC4R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp32f` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)
Four-channel 32-bit floating point image SqrDistanceValid_Norm ignoring alpha channel.
- `NppStatus nppiSqrDistanceValid_Norm_8u32f_C1R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)
One-channel 8-bit unsigned image SqrDistanceValid_Norm.

- [NppStatus nppiSqrDistanceValid_Norm_8u32f_C3R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8u](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)
Three-channel 8-bit unsigned image SqrDistanceValid_Norm.
- [NppStatus nppiSqrDistanceValid_Norm_8u32f_C4R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8u](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)
Four-channel 8-bit unsigned image SqrDistanceValid_Norm.
- [NppStatus nppiSqrDistanceValid_Norm_8u32f_AC4R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8u](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)
Four-channel 8-bit unsigned image SqrDistanceValid_Norm ignoring alpha channel.
- [NppStatus nppiSqrDistanceValid_Norm_8s32f_C1R](#) (const [Npp8s](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8s](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)
One-channel 8-bit signed image SqrDistanceValid_Norm.
- [NppStatus nppiSqrDistanceValid_Norm_8s32f_C3R](#) (const [Npp8s](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8s](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)
Three-channel 8-bit signed image SqrDistanceValid_Norm.
- [NppStatus nppiSqrDistanceValid_Norm_8s32f_C4R](#) (const [Npp8s](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8s](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)
Four-channel 8-bit signed image SqrDistanceValid_Norm.
- [NppStatus nppiSqrDistanceValid_Norm_8s32f_AC4R](#) (const [Npp8s](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8s](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)
Four-channel 8-bit signed image SqrDistanceValid_Norm ignoring alpha channel.
- [NppStatus nppiSqrDistanceValid_Norm_16u32f_C1R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp16u](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)
One-channel 16-bit unsigned image SqrDistanceValid_Norm.
- [NppStatus nppiSqrDistanceValid_Norm_16u32f_C3R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp16u](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)
Three-channel 16-bit unsigned image SqrDistanceValid_Norm.
- [NppStatus nppiSqrDistanceValid_Norm_16u32f_C4R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp16u](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep)
Four-channel 16-bit unsigned image SqrDistanceValid_Norm.

- `NppStatus nppiSqrDistanceValid_Norm_16u32f_AC4R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize oSrcRoiSize`, const `Npp16u *pTpl`, int `nTplStep`, `NppiSize oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`)

Four-channel 16-bit unsigned image SqrDistanceValid_Norm ignoring alpha channel.

7.119.1 Detailed Description

Primitives for computing the normalized Euclidean distance between two images with valid mode.

7.119.2 Function Documentation

- 7.119.2.1** `NppStatus nppiSqrDistanceValid_Norm_16u32f_AC4R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize oSrcRoiSize`, const `Npp16u *pTpl`, int `nTplStep`, `NppiSize oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`)

Four-channel 16-bit unsigned image SqrDistanceValid_Norm ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- 7.119.2.2** `NppStatus nppiSqrDistanceValid_Norm_16u32f_C1R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize oSrcRoiSize`, const `Npp16u *pTpl`, int `nTplStep`, `NppiSize oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`)

One-channel 16-bit unsigned image SqrDistanceValid_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.119.2.3 `NppStatus nppiSqrDistanceValid_Norm_16u32f_C3R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Three-channel 16-bit unsigned image SqrDistanceValid_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.119.2.4 `NppStatus nppiSqrDistanceValid_Norm_16u32f_C4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 16-bit unsigned image SqrDistanceValid_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.119.2.5 `NppStatus nppiSqrDistanceValid_Norm_32f_AC4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 32-bit floating point image SqrDistanceValid_Norm ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.119.2.6 `NppStatus nppiSqrDistanceValid_Norm_32f_C1R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

One-channel 32-bit floating point image SqrDistanceValid_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.119.2.7 `NppStatus nppiSqrDistanceValid_Norm_32f_C3R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Three-channel 32-bit floating point image SqrDistanceValid_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.119.2.8 `NppStatus nppiSqrDistanceValid_Norm_32f_C4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 32-bit floating point image SqrDistanceValid_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.119.2.9 `NppStatus nppiSqrDistanceValid_Norm_8s32f_AC4R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 8-bit signed image SqrDistanceValid_Norm ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.119.2.10 `NppStatus nppiSqrDistanceValid_Norm_8s32f_C1R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

One-channel 8-bit signed image SqrDistanceValid_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.119.2.11 `NppStatus nppiSqrDistanceValid_Norm_8s32f_C3R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Three-channel 8-bit signed image SqrDistanceValid_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.119.2.12 `NppStatus nppiSqrDistanceValid_Norm_8s32f_C4R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 8-bit signed image SqrDistanceValid_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.119.2.13 `NppStatus nppiSqrDistanceValid_Norm_8u32f_AC4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 8-bit unsigned image SqrDistanceValid_Norm ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.119.2.14 `NppStatus nppiSqrDistanceValid_Norm_8u32f_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

One-channel 8-bit unsigned image SqrDistanceValid_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.119.2.15 `NppStatus nppiSqrDistanceValid_Norm_8u32f_C3R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Three-channel 8-bit unsigned image SqrDistanceValid_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.119.2.16 `NppStatus nppiSqrDistanceValid_Norm_8u32f_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 8-bit unsigned image SqrDistanceValid_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.119.2.17 **NppStatus nppiSqrDistanceValid_Norm_8u_AC4RSfs** (const Npp8u * *pSrc*, int *nSrcStep*, NppiSize *oSrcRoiSize*, const Npp8u * *pTpl*, int *nTplStep*, NppiSize *oTplRoiSize*, Npp8u * *pDst*, int *nDstStep*, int *nScaleFactor*)

Four-channel 8-bit unsigned image SqrDistanceValid_Norm ignoring alpha channel, scaled by $2^{\lceil -nScaleFactor \rceil}$.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.119.2.18 **NppStatus nppiSqrDistanceValid_Norm_8u_C1RSfs** (const Npp8u * *pSrc*, int *nSrcStep*, NppiSize *oSrcRoiSize*, const Npp8u * *pTpl*, int *nTplStep*, NppiSize *oTplRoiSize*, Npp8u * *pDst*, int *nDstStep*, int *nScaleFactor*)

One-channel 8-bit unsigned image SqrDistanceValid_Norm, scaled by $2^{\lceil -nScaleFactor \rceil}$.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.119.2.19 NppStatus nppiSqrDistanceValid_Norm_8u_C3RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor)

Three-channel 8-bit unsigned image SqrDistanceValid_Norm, scaled by $2^{(- nScaleFactor)}$.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.119.2.20 NppStatus nppiSqrDistanceValid_Norm_8u_C4RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor)

Four-channel 8-bit unsigned image SqrDistanceValid_Norm, scaled by $2^{(- nScaleFactor)}$.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.120 CrossCorrFull_Norm

Primitives for computing the normalized cross correlation between two images with full mode.

CrossCorrFull_Norm

The functions compute the $\rho_{st}(c, r)$ in [General Introduction](#) with full mode (see [Categorizations](#)).

- `NppStatus nppiCrossCorrFull_Norm_8u_C1RSfs` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp8u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp8u *pDst`, int `nDstStep`, int `nScaleFactor`)
One-channel 8-bit unsigned image CrossCorrFull_Norm, scaled by $2^{\ell} - nScaleFactor$.
- `NppStatus nppiCrossCorrFull_Norm_8u_C3RSfs` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp8u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp8u *pDst`, int `nDstStep`, int `nScaleFactor`)
Three-channel 8-bit unsigned image CrossCorrFull_Norm, scaled by $2^{\ell} - nScaleFactor$.
- `NppStatus nppiCrossCorrFull_Norm_8u_C4RSfs` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp8u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp8u *pDst`, int `nDstStep`, int `nScaleFactor`)
Four-channel 8-bit unsigned image CrossCorrFull_Norm, scaled by $2^{\ell} - nScaleFactor$.
- `NppStatus nppiCrossCorrFull_Norm_8u_AC4RSfs` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp8u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp8u *pDst`, int `nDstStep`, int `nScaleFactor`)
Four-channel 8-bit unsigned image CrossCorrFull_Norm ignoring alpha channel, scaled by $2^{\ell} - nScaleFactor$.
- `NppStatus nppiCrossCorrFull_Norm_32f_C1R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp32f *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`)
One-channel 32-bit floating point image CrossCorrFull_Norm.
- `NppStatus nppiCrossCorrFull_Norm_32f_C3R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp32f *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`)
Three-channel 32-bit floating point image CrossCorrFull_Norm.
- `NppStatus nppiCrossCorrFull_Norm_32f_C4R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp32f *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`)
Four-channel 32-bit floating point image CrossCorrFull_Norm.
- `NppStatus nppiCrossCorrFull_Norm_32f_AC4R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp32f *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`)
Four-channel 32-bit floating point image CrossCorrFull_Norm ignoring alpha channel.
- `NppStatus nppiCrossCorrFull_Norm_8u32f_C1R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp8u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`)
One-channel 8-bit unsigned image CrossCorrFull_Norm.
- `NppStatus nppiCrossCorrFull_Norm_8u32f_C3R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp8u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`)

Three-channel 8-bit unsigned image CrossCorrFull_Norm.

- `NppStatus nppiCrossCorrFull_Norm_8u32f_C4R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Four-channel 8-bit unsigned image CrossCorrFull_Norm.

- `NppStatus nppiCrossCorrFull_Norm_8u32f_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Four-channel 8-bit unsigned image CrossCorrFull_Norm ignoring alpha channel.

- `NppStatus nppiCrossCorrFull_Norm_8s32f_C1R` (const `Npp8s` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8s` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

One-channel 8-bit signed image CrossCorrFull_Norm.

- `NppStatus nppiCrossCorrFull_Norm_8s32f_C3R` (const `Npp8s` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8s` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Three-channel 8-bit signed image CrossCorrFull_Norm.

- `NppStatus nppiCrossCorrFull_Norm_8s32f_C4R` (const `Npp8s` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8s` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Four-channel 8-bit signed image CrossCorrFull_Norm.

- `NppStatus nppiCrossCorrFull_Norm_8s32f_AC4R` (const `Npp8s` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8s` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Four-channel 8-bit signed image CrossCorrFull_Norm ignoring alpha channel.

- `NppStatus nppiCrossCorrFull_Norm_16u32f_C1R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp16u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

One-channel 16-bit unsigned image CrossCorrFull_Norm.

- `NppStatus nppiCrossCorrFull_Norm_16u32f_C3R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp16u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Three-channel 16-bit unsigned image CrossCorrFull_Norm.

- `NppStatus nppiCrossCorrFull_Norm_16u32f_C4R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp16u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Four-channel 16-bit unsigned image CrossCorrFull_Norm.

- `NppStatus nppiCrossCorrFull_Norm_16u32f_AC4R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp16u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Four-channel 16-bit unsigned image CrossCorrFull_Norm ignoring alpha channel.

7.120.1 Detailed Description

Primitives for computing the normalized cross correlation between two images with full mode.

7.120.2 Function Documentation

7.120.2.1 `NppStatus nppiCrossCorrFull_Norm_16u32f_AC4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 16-bit unsigned image CrossCorrFull_Norm ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.120.2.2 `NppStatus nppiCrossCorrFull_Norm_16u32f_C1R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

One-channel 16-bit unsigned image CrossCorrFull_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.120.2.3 `NppStatus nppiCrossCorrFull_Norm_16u32f_C3R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Three-channel 16-bit unsigned image CrossCorrFull_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.120.2.4 `NppStatus nppiCrossCorrFull_Norm_16u32f_C4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 16-bit unsigned image CrossCorrFull_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.120.2.5 `NppStatus nppiCrossCorrFull_Norm_32f_AC4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 32-bit floating point image CrossCorrFull_Norm ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.120.2.6 `NppStatus nppiCrossCorrFull_Norm_32f_C1R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

One-channel 32-bit floating point image CrossCorrFull_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.120.2.7 `NppStatus nppiCrossCorrFull_Norm_32f_C3R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Three-channel 32-bit floating point image CrossCorrFull_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.120.2.8 `NppStatus nppiCrossCorrFull_Norm_32f_C4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 32-bit floating point image CrossCorrFull_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.120.2.9 `NppStatus nppiCrossCorrFull_Norm_8s32f_AC4R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 8-bit signed image CrossCorrFull_Norm ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.120.2.10 `NppStatus nppiCrossCorrFull_Norm_8s32f_C1R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

One-channel 8-bit signed image CrossCorrFull_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.120.2.11 `NppStatus nppiCrossCorrFull_Norm_8s32f_C3R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Three-channel 8-bit signed image CrossCorrFull_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.120.2.12 `NppStatus nppiCrossCorrFull_Norm_8s32f_C4R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 8-bit signed image CrossCorrFull_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.120.2.13 `NppStatus nppiCrossCorrFull_Norm_8u32f_AC4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 8-bit unsigned image CrossCorrFull_Norm ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.120.2.14 `NppStatus nppiCrossCorrFull_Norm_8u32f_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

One-channel 8-bit unsigned image CrossCorrFull_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.120.2.15 `NppStatus nppiCrossCorrFull_Norm_8u32f_C3R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Three-channel 8-bit unsigned image CrossCorrFull_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.120.2.16 `NppStatus nppiCrossCorrFull_Norm_8u32f_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 8-bit unsigned image CrossCorrFull_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.120.2.17 `NppStatus nppiCrossCorrFull_Norm_8u_AC4RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor)`

Four-channel 8-bit unsigned image CrossCorrFull_Norm ignoring alpha channel, scaled by $2^{(- nScaleFactor)}$.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.120.2.18 `NppStatus nppiCrossCorrFull_Norm_8u_C1RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor)`

One-channel 8-bit unsigned image CrossCorrFull_Norm, scaled by $2^{(- nScaleFactor)}$.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.120.2.19 `NppStatus nppiCrossCorrFull_Norm_8u_C3RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor)`

Three-channel 8-bit unsigned image CrossCorrFull_Norm, scaled by $2^{(-nScaleFactor)}$.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.120.2.20 `NppStatus nppiCrossCorrFull_Norm_8u_C4RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor)`

Four-channel 8-bit unsigned image CrossCorrFull_Norm, scaled by $2^{(-nScaleFactor)}$.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.121 CrossCorrSame_Norm

Primitives for computing the normalized cross correlation between two images with same mode.

CrossCorrSame_Norm

The functions compute the $\rho_{st}(c, r)$ in [General Introduction](#) with same mode (see [Categorizations](#)).

- `NppStatus nppiCrossCorrSame_Norm_8u_C1RSfs` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp8u` *pDst, int nDstStep, int nScaleFactor)
One-channel 8-bit unsigned image CrossCorrSame_Norm, scaled by $2^{\ell - nScaleFactor}$.
- `NppStatus nppiCrossCorrSame_Norm_8u_C3RSfs` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp8u` *pDst, int nDstStep, int nScaleFactor)
Three-channel 8-bit unsigned image CrossCorrSame_Norm, scaled by $2^{\ell - nScaleFactor}$.
- `NppStatus nppiCrossCorrSame_Norm_8u_C4RSfs` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp8u` *pDst, int nDstStep, int nScaleFactor)
Four-channel 8-bit unsigned image CrossCorrSame_Norm, scaled by $2^{\ell - nScaleFactor}$.
- `NppStatus nppiCrossCorrSame_Norm_8u_AC4RSfs` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp8u` *pDst, int nDstStep, int nScaleFactor)
Four-channel 8-bit unsigned image CrossCorrSame_Norm ignoring alpha channel, scaled by $2^{\ell - nScaleFactor}$.
- `NppStatus nppiCrossCorrSame_Norm_32f_C1R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp32f` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)
One-channel 32-bit floating point image CrossCorrSame_Norm.
- `NppStatus nppiCrossCorrSame_Norm_32f_C3R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp32f` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)
Three-channel 32-bit floating point image CrossCorrSame_Norm.
- `NppStatus nppiCrossCorrSame_Norm_32f_C4R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp32f` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)
Four-channel 32-bit floating point image CrossCorrSame_Norm.
- `NppStatus nppiCrossCorrSame_Norm_32f_AC4R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp32f` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)
Four-channel 32-bit floating point image CrossCorrSame_Norm ignoring alpha channel.
- `NppStatus nppiCrossCorrSame_Norm_8u32f_C1R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)
One-channel 8-bit unsigned image CrossCorrSame_Norm.
- `NppStatus nppiCrossCorrSame_Norm_8u32f_C3R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Three-channel 8-bit unsigned image CrossCorrSame_Norm.

- `NppStatus nppiCrossCorrSame_Norm_8u32f_C4R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Four-channel 8-bit unsigned image CrossCorrSame_Norm.

- `NppStatus nppiCrossCorrSame_Norm_8u32f_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Four-channel 8-bit unsigned image CrossCorrSame_Norm ignoring alpha channel.

- `NppStatus nppiCrossCorrSame_Norm_8s32f_C1R` (const `Npp8s` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8s` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

One-channel 8-bit signed image CrossCorrSame_Norm.

- `NppStatus nppiCrossCorrSame_Norm_8s32f_C3R` (const `Npp8s` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8s` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Three-channel 8-bit signed image CrossCorrSame_Norm.

- `NppStatus nppiCrossCorrSame_Norm_8s32f_C4R` (const `Npp8s` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8s` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Four-channel 8-bit signed image CrossCorrSame_Norm.

- `NppStatus nppiCrossCorrSame_Norm_8s32f_AC4R` (const `Npp8s` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8s` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Four-channel 8-bit signed image CrossCorrSame_Norm ignoring alpha channel.

- `NppStatus nppiCrossCorrSame_Norm_16u32f_C1R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp16u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

One-channel 16-bit unsigned image CrossCorrSame_Norm.

- `NppStatus nppiCrossCorrSame_Norm_16u32f_C3R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp16u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Three-channel 16-bit unsigned image CrossCorrSame_Norm.

- `NppStatus nppiCrossCorrSame_Norm_16u32f_C4R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp16u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Four-channel 16-bit unsigned image CrossCorrSame_Norm.

- `NppStatus nppiCrossCorrSame_Norm_16u32f_AC4R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp16u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Four-channel 16-bit unsigned image CrossCorrSame_Norm ignoring alpha channel.

7.121.1 Detailed Description

Primitives for computing the normalized cross correlation between two images with same mode.

7.121.2 Function Documentation

7.121.2.1 `NppStatus nppiCrossCorrSame_Norm_16u32f_AC4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 16-bit unsigned image CrossCorrSame_Norm ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.121.2.2 `NppStatus nppiCrossCorrSame_Norm_16u32f_C1R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

One-channel 16-bit unsigned image CrossCorrSame_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.121.2.3 `NppStatus nppiCrossCorrSame_Norm_16u32f_C3R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Three-channel 16-bit unsigned image CrossCorrSame_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.121.2.4 `NppStatus nppiCrossCorrSame_Norm_16u32f_C4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 16-bit unsigned image CrossCorrSame_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.121.2.5 `NppStatus nppiCrossCorrSame_Norm_32f_AC4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 32-bit floating point image CrossCorrSame_Norm ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.121.2.6 `NppStatus nppiCrossCorrSame_Norm_32f_C1R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

One-channel 32-bit floating point image CrossCorrSame_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.121.2.7 `NppStatus nppiCrossCorrSame_Norm_32f_C3R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Three-channel 32-bit floating point image CrossCorrSame_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.121.2.8 `NppStatus nppiCrossCorrSame_Norm_32f_C4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 32-bit floating point image CrossCorrSame_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.121.2.9 `NppStatus nppiCrossCorrSame_Norm_8s32f_AC4R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 8-bit signed image CrossCorrSame_Norm ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.121.2.10 `NppStatus nppiCrossCorrSame_Norm_8s32f_C1R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

One-channel 8-bit signed image CrossCorrSame_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.121.2.11 `NppStatus nppiCrossCorrSame_Norm_8s32f_C3R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Three-channel 8-bit signed image CrossCorrSame_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.121.2.12 `NppStatus nppiCrossCorrSame_Norm_8s32f_C4R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 8-bit signed image CrossCorrSame_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.121.2.13 `NppStatus nppiCrossCorrSame_Norm_8u32f_AC4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 8-bit unsigned image CrossCorrSame_Norm ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.121.2.14 `NppStatus nppiCrossCorrSame_Norm_8u32f_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

One-channel 8-bit unsigned image CrossCorrSame_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.121.2.15 `NppStatus nppiCrossCorrSame_Norm_8u32f_C3R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Three-channel 8-bit unsigned image CrossCorrSame_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.121.2.16 `NppStatus nppiCrossCorrSame_Norm_8u32f_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 8-bit unsigned image CrossCorrSame_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.121.2.17 NppStatus nppiCrossCorrSame_Norm_8u_AC4RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor)

Four-channel 8-bit unsigned image CrossCorrSame_Norm ignoring alpha channel, scaled by $2^{(- nScaleFactor)}$.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- oSrcRoiSize* Region-of-Interest (ROI).
- pTpl* Pointer to the template image.
- nTplStep* Number of bytes between successive rows in the template image.
- oTplRoiSize* Region-of-Interest (ROI).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.121.2.18 NppStatus nppiCrossCorrSame_Norm_8u_C1RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor)

One-channel 8-bit unsigned image CrossCorrSame_Norm, scaled by $2^{(- nScaleFactor)}$.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- oSrcRoiSize* Region-of-Interest (ROI).
- pTpl* Pointer to the template image.
- nTplStep* Number of bytes between successive rows in the template image.
- oTplRoiSize* Region-of-Interest (ROI).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.121.2.19 `NppStatus nppiCrossCorrSame_Norm_8u_C3RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor)`

Three-channel 8-bit unsigned image CrossCorrSame_Norm, scaled by $2^{(- nScaleFactor)}$.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.121.2.20 `NppStatus nppiCrossCorrSame_Norm_8u_C4RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor)`

Four-channel 8-bit unsigned image CrossCorrSame_Norm, scaled by $2^{(- nScaleFactor)}$.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.122 CrossCorrValid_Norm

Primitives for computing the normalized cross correlation between two images with valid mode.

CrossCorrValid_Norm

The functions compute the $\rho_{st}(c, r)$ in [General Introduction](#) with valid mode (see [Categorizations](#)).

- `NppStatus nppiCrossCorrValid_Norm_8u_C1RSfs` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp8u` *pDst, int nDstStep, int nScaleFactor)
One-channel 8-bit unsigned image CrossCorrValid_Norm, scaled by $2^{\ell - nScaleFactor}$.
- `NppStatus nppiCrossCorrValid_Norm_8u_C3RSfs` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp8u` *pDst, int nDstStep, int nScaleFactor)
Three-channel 8-bit unsigned image CrossCorrValid_Norm, scaled by $2^{\ell - nScaleFactor}$.
- `NppStatus nppiCrossCorrValid_Norm_8u_C4RSfs` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp8u` *pDst, int nDstStep, int nScaleFactor)
Four-channel 8-bit unsigned image CrossCorrValid_Norm, scaled by $2^{\ell - nScaleFactor}$.
- `NppStatus nppiCrossCorrValid_Norm_8u_AC4RSfs` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp8u` *pDst, int nDstStep, int nScaleFactor)
Four-channel 8-bit unsigned image CrossCorrValid_Norm ignoring alpha channel, scaled by $2^{\ell - nScaleFactor}$.
- `NppStatus nppiCrossCorrValid_Norm_32f_C1R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp32f` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)
One-channel 32-bit floating point image CrossCorrValid_Norm.
- `NppStatus nppiCrossCorrValid_Norm_32f_C3R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp32f` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)
Three-channel 32-bit floating point image CrossCorrValid_Norm.
- `NppStatus nppiCrossCorrValid_Norm_32f_C4R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp32f` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)
Four-channel 32-bit floating point image CrossCorrValid_Norm.
- `NppStatus nppiCrossCorrValid_Norm_32f_AC4R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp32f` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)
Four-channel 32-bit floating point image CrossCorrValid_Norm ignoring alpha channel.
- `NppStatus nppiCrossCorrValid_Norm_8u32f_C1R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)
One-channel 8-bit unsigned image CrossCorrValid_Norm.
- `NppStatus nppiCrossCorrValid_Norm_8u32f_C3R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Three-channel 8-bit unsigned image CrossCorrValid_Norm.

- `NppStatus nppiCrossCorrValid_Norm_8u32f_C4R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Four-channel 8-bit unsigned image CrossCorrValid_Norm.

- `NppStatus nppiCrossCorrValid_Norm_8u32f_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Four-channel 8-bit unsigned image CrossCorrValid_Norm ignoring alpha channel.

- `NppStatus nppiCrossCorrValid_Norm_8s32f_C1R` (const `Npp8s` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8s` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

One-channel 8-bit signed image CrossCorrValid_Norm.

- `NppStatus nppiCrossCorrValid_Norm_8s32f_C3R` (const `Npp8s` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8s` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Three-channel 8-bit signed image CrossCorrValid_Norm.

- `NppStatus nppiCrossCorrValid_Norm_8s32f_C4R` (const `Npp8s` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8s` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Four-channel 8-bit signed image CrossCorrValid_Norm.

- `NppStatus nppiCrossCorrValid_Norm_8s32f_AC4R` (const `Npp8s` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8s` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Four-channel 8-bit signed image CrossCorrValid_Norm ignoring alpha channel.

- `NppStatus nppiCrossCorrValid_Norm_16u32f_C1R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp16u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

One-channel 16-bit unsigned image CrossCorrValid_Norm.

- `NppStatus nppiCrossCorrValid_Norm_16u32f_C3R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp16u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Three-channel 16-bit unsigned image CrossCorrValid_Norm.

- `NppStatus nppiCrossCorrValid_Norm_16u32f_C4R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp16u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Four-channel 16-bit unsigned image CrossCorrValid_Norm.

- `NppStatus nppiCrossCorrValid_Norm_16u32f_AC4R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp16u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep)

Four-channel 16-bit unsigned image CrossCorrValid_Norm ignoring alpha channel.

7.122.1 Detailed Description

Primitives for computing the normalized cross correlation between two images with valid mode.

7.122.2 Function Documentation

7.122.2.1 `NppStatus nppiCrossCorrValid_Norm_16u32f_AC4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 16-bit unsigned image CrossCorrValid_Norm ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.122.2.2 `NppStatus nppiCrossCorrValid_Norm_16u32f_C1R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

One-channel 16-bit unsigned image CrossCorrValid_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.122.2.3 `NppStatus nppiCrossCorrValid_Norm_16u32f_C3R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Three-channel 16-bit unsigned image CrossCorrValid_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.122.2.4 `NppStatus nppiCrossCorrValid_Norm_16u32f_C4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 16-bit unsigned image CrossCorrValid_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.122.2.5 `NppStatus nppiCrossCorrValid_Norm_32f_AC4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 32-bit floating point image CrossCorrValid_Norm ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.122.2.6 `NppStatus nppiCrossCorrValid_Norm_32f_C1R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

One-channel 32-bit floating point image CrossCorrValid_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.122.2.7 `NppStatus nppiCrossCorrValid_Norm_32f_C3R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Three-channel 32-bit floating point image CrossCorrValid_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.122.2.8 `NppStatus nppiCrossCorrValid_Norm_32f_C4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 32-bit floating point image CrossCorrValid_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.122.2.9 `NppStatus nppiCrossCorrValid_Norm_8s32f_AC4R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 8-bit signed image CrossCorrValid_Norm ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.122.2.10 `NppStatus nppiCrossCorrValid_Norm_8s32f_C1R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

One-channel 8-bit signed image CrossCorrValid_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.122.2.11 `NppStatus nppiCrossCorrValid_Norm_8s32f_C3R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Three-channel 8-bit signed image CrossCorrValid_Norm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.122.2.12 `NppStatus nppiCrossCorrValid_Norm_8s32f_C4R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 8-bit signed image CrossCorrValid_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.122.2.13 `NppStatus nppiCrossCorrValid_Norm_8u32f_AC4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 8-bit unsigned image CrossCorrValid_Norm ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.122.2.14 `NppStatus nppiCrossCorrValid_Norm_8u32f_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

One-channel 8-bit unsigned image CrossCorrValid_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.122.2.15 `NppStatus nppiCrossCorrValid_Norm_8u32f_C3R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Three-channel 8-bit unsigned image CrossCorrValid_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.122.2.16 `NppStatus nppiCrossCorrValid_Norm_8u32f_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

Four-channel 8-bit unsigned image CrossCorrValid_Norm.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcRoiSize Region-of-Interest (ROI).
pTpl Pointer to the template image.
nTplStep Number of bytes between successive rows in the template image.
oTplRoiSize Region-of-Interest (ROI).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.122.2.17 NppStatus nppiCrossCorrValid_Norm_8u_AC4RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor)

Four-channel 8-bit unsigned image CrossCorrValid_Norm ignoring alpha channel, scaled by $2^{(-nScaleFactor)}$.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- oSrcRoiSize* Region-of-Interest (ROI).
- pTpl* Pointer to the template image.
- nTplStep* Number of bytes between successive rows in the template image.
- oTplRoiSize* Region-of-Interest (ROI).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.122.2.18 NppStatus nppiCrossCorrValid_Norm_8u_C1RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor)

One-channel 8-bit unsigned image CrossCorrValid_Norm, scaled by $2^{(-nScaleFactor)}$.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- oSrcRoiSize* Region-of-Interest (ROI).
- pTpl* Pointer to the template image.
- nTplStep* Number of bytes between successive rows in the template image.
- oTplRoiSize* Region-of-Interest (ROI).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.122.2.19 `NppStatus nppiCrossCorrValid_Norm_8u_C3RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor)`

Three-channel 8-bit unsigned image CrossCorrValid_Norm, scaled by $2^{(-nScaleFactor)}$.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.122.2.20 `NppStatus nppiCrossCorrValid_Norm_8u_C4RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor)`

Four-channel 8-bit unsigned image CrossCorrValid_Norm, scaled by $2^{(-nScaleFactor)}$.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.123 CrossCorrValid

Primitives for computing the cross correlation between two images with valid mode.

CrossCorrValid

The functions compute the $R_{st}(c, r)$ in [General Introduction](#) with valid mode (see [Categorizations](#)).

- `NppStatus nppiCrossCorrValid_32f_C1R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp32f *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`)
One-channel 32-bit floating point images CrossCorrValid.
- `NppStatus nppiCrossCorrValid_8u32f_C1R` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp8u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`)
One-channel 8-bit unsigned images CrossCorrValid.
- `NppStatus nppiCrossCorrValid_8s32f_C1R` (const `Npp8s *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp8s *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`)
One-channel 8-bit signed images CrossCorrValid.
- `NppStatus nppiCrossCorrValid_16u32f_C1R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp16u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`)
One-channel 16-bit unsigned images CrossCorrValid.

7.123.1 Detailed Description

Primitives for computing the cross correlation between two images with valid mode.

7.123.2 Function Documentation

7.123.2.1 `NppStatus nppiCrossCorrValid_16u32f_C1R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp16u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`)

One-channel 16-bit unsigned images CrossCorrValid.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.123.2.2 `NppStatus nppiCrossCorrValid_32f_C1R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

One-channel 32-bit floating point images CrossCorrValid.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcRoiSize [Region-of-Interest \(ROI\)](#).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize [Region-of-Interest \(ROI\)](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.123.2.3 `NppStatus nppiCrossCorrValid_8s32f_C1R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

One-channel 8-bit signed images CrossCorrValid.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcRoiSize [Region-of-Interest \(ROI\)](#).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize [Region-of-Interest \(ROI\)](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.123.2.4 `NppStatus nppiCrossCorrValid_8u32f_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep)`

One-channel 8-bit unsigned images CrossCorrValid.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.124 CrossCorrFull_NormLevel

Primitives for computing the normalized cross correlation coefficient between two images with full mode.

CrossCorrFull_NormLevel

The functions compute the $\gamma_{st}(c, r)$ in [General Introduction](#) with full mode (see [Categorizations](#)).

The functions require additional scratch buffer for computations.

- `NppStatus nppiCrossCorrFull_NormLevel_8u_C1RSfs` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp8u` *pDst, int nDstStep, int nScaleFactor, `Npp8u` *pDeviceBuffer)

One-channel 8-bit unsigned image CrossCorrFull_NormLevel.
- `NppStatus nppiCrossCorrFull_NormLevel_8u_C3RSfs` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp8u` *pDst, int nDstStep, int nScaleFactor, `Npp8u` *pDeviceBuffer)

Three-channel 8-bit unsigned image CrossCorrFull_NormLevel.
- `NppStatus nppiCrossCorrFull_NormLevel_8u_C4RSfs` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp8u` *pDst, int nDstStep, int nScaleFactor, `Npp8u` *pDeviceBuffer)

Four-channel 8-bit unsigned image CrossCorrFull_NormLevel.
- `NppStatus nppiCrossCorrFull_NormLevel_8u_AC4RSfs` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp8u` *pDst, int nDstStep, int nScaleFactor, `Npp8u` *pDeviceBuffer)

Four-channel 8-bit unsigned image CrossCorrFull_NormLevel ignoring alpha channel.
- `NppStatus nppiCrossCorrFull_NormLevel_32f_C1R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp32f` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep, `Npp8u` *pDeviceBuffer)

One-channel 32-bit floating point image CrossCorrFull_NormLevel.
- `NppStatus nppiCrossCorrFull_NormLevel_32f_C3R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp32f` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep, `Npp8u` *pDeviceBuffer)

Three-channel 32-bit floating point image CrossCorrFull_NormLevel.
- `NppStatus nppiCrossCorrFull_NormLevel_32f_C4R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp32f` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep, `Npp8u` *pDeviceBuffer)

Four-channel 32-bit floating point image CrossCorrFull_NormLevel.
- `NppStatus nppiCrossCorrFull_NormLevel_32f_AC4R` (const `Npp32f` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp32f` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep, `Npp8u` *pDeviceBuffer)

Four-channel 32-bit floating point image CrossCorrFull_NormLevel ignoring alpha channel.

- **NppStatus nppiCrossCorrFull_NormLevel_8u32f_C1R** (const **Npp8u** *pSrc, int nSrcStep, **NppiSize** oSrcRoiSize, const **Npp8u** *pTpl, int nTplStep, **NppiSize** oTplRoiSize, **Npp32f** *pDst, int nDstStep, **Npp8u** *pDeviceBuffer)

One-channel 8-bit unsigned image CrossCorrFull_NormLevel.
- **NppStatus nppiCrossCorrFull_NormLevel_8u32f_C3R** (const **Npp8u** *pSrc, int nSrcStep, **NppiSize** oSrcRoiSize, const **Npp8u** *pTpl, int nTplStep, **NppiSize** oTplRoiSize, **Npp32f** *pDst, int nDstStep, **Npp8u** *pDeviceBuffer)

Three-channel 8-bit unsigned image CrossCorrFull_NormLevel.
- **NppStatus nppiCrossCorrFull_NormLevel_8u32f_C4R** (const **Npp8u** *pSrc, int nSrcStep, **NppiSize** oSrcRoiSize, const **Npp8u** *pTpl, int nTplStep, **NppiSize** oTplRoiSize, **Npp32f** *pDst, int nDstStep, **Npp8u** *pDeviceBuffer)

Four-channel 8-bit unsigned image CrossCorrFull_NormLevel.
- **NppStatus nppiCrossCorrFull_NormLevel_8u32f_AC4R** (const **Npp8u** *pSrc, int nSrcStep, **NppiSize** oSrcRoiSize, const **Npp8u** *pTpl, int nTplStep, **NppiSize** oTplRoiSize, **Npp32f** *pDst, int nDstStep, **Npp8u** *pDeviceBuffer)

Four-channel 8-bit unsigned image CrossCorrFull_NormLevel ignoring alpha channel.
- **NppStatus nppiCrossCorrFull_NormLevel_8s32f_C1R** (const **Npp8s** *pSrc, int nSrcStep, **NppiSize** oSrcRoiSize, const **Npp8s** *pTpl, int nTplStep, **NppiSize** oTplRoiSize, **Npp32f** *pDst, int nDstStep, **Npp8u** *pDeviceBuffer)

One-channel 8-bit signed image CrossCorrFull_NormLevel.
- **NppStatus nppiCrossCorrFull_NormLevel_8s32f_C3R** (const **Npp8s** *pSrc, int nSrcStep, **NppiSize** oSrcRoiSize, const **Npp8s** *pTpl, int nTplStep, **NppiSize** oTplRoiSize, **Npp32f** *pDst, int nDstStep, **Npp8u** *pDeviceBuffer)

Three-channel 8-bit signed image CrossCorrFull_NormLevel.
- **NppStatus nppiCrossCorrFull_NormLevel_8s32f_C4R** (const **Npp8s** *pSrc, int nSrcStep, **NppiSize** oSrcRoiSize, const **Npp8s** *pTpl, int nTplStep, **NppiSize** oTplRoiSize, **Npp32f** *pDst, int nDstStep, **Npp8u** *pDeviceBuffer)

Four-channel 8-bit signed image CrossCorrFull_NormLevel.
- **NppStatus nppiCrossCorrFull_NormLevel_8s32f_AC4R** (const **Npp8s** *pSrc, int nSrcStep, **NppiSize** oSrcRoiSize, const **Npp8s** *pTpl, int nTplStep, **NppiSize** oTplRoiSize, **Npp32f** *pDst, int nDstStep, **Npp8u** *pDeviceBuffer)

Four-channel 8-bit signed image CrossCorrFull_NormLevel ignoring alpha channel.
- **NppStatus nppiCrossCorrFull_NormLevel_16u32f_C1R** (const **Npp16u** *pSrc, int nSrcStep, **NppiSize** oSrcRoiSize, const **Npp16u** *pTpl, int nTplStep, **NppiSize** oTplRoiSize, **Npp32f** *pDst, int nDstStep, **Npp8u** *pDeviceBuffer)

One-channel 16-bit unsigned image CrossCorrFull_NormLevel.
- **NppStatus nppiCrossCorrFull_NormLevel_16u32f_C3R** (const **Npp16u** *pSrc, int nSrcStep, **NppiSize** oSrcRoiSize, const **Npp16u** *pTpl, int nTplStep, **NppiSize** oTplRoiSize, **Npp32f** *pDst, int nDstStep, **Npp8u** *pDeviceBuffer)

Three-channel 16-bit unsigned image CrossCorrFull_NormLevel.

- `NppStatus nppiCrossCorrFull_NormLevel_16u32f_C4R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp16u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`, `Npp8u *pDeviceBuffer`)
Four-channel 16-bit unsigned image CrossCorrFull_NormLevel.
- `NppStatus nppiCrossCorrFull_NormLevel_16u32f_AC4R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp16u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`, `Npp8u *pDeviceBuffer`)
Four-channel 16-bit unsigned image CrossCorrFull_NormLevel ignoring alpha channel.

FullNormLevelGetBufferHostSize

Companion primitives for computing the device buffer size (in bytes) required by the `CrossCorrFull_NormLevel` primitives.

- `NppStatus nppiFullNormLevelGetBufferHostSize_8u_C1RSfs` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size (in bytes) for `nppiCrossCorrFull_NormLevel_8u_C1RSfs`.
- `NppStatus nppiFullNormLevelGetBufferHostSize_8u_C3RSfs` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size (in bytes) for `nppiCrossCorrFull_NormLevel_8u_C3RSfs`.
- `NppStatus nppiFullNormLevelGetBufferHostSize_8u_C4RSfs` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size (in bytes) for `nppiCrossCorrFull_NormLevel_8u_C4RSfs`.
- `NppStatus nppiFullNormLevelGetBufferHostSize_8u_AC4RSfs` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size (in bytes) for `nppiCrossCorrFull_NormLevel_8u_AC4RSfs`.
- `NppStatus nppiFullNormLevelGetBufferHostSize_32f_C1R` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size (in bytes) for `nppiCrossCorrFull_NormLevel_32f_C1R`.
- `NppStatus nppiFullNormLevelGetBufferHostSize_32f_C3R` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size (in bytes) for `nppiCrossCorrFull_NormLevel_32f_C3R`.
- `NppStatus nppiFullNormLevelGetBufferHostSize_32f_C4R` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size (in bytes) for `nppiCrossCorrFull_NormLevel_32f_C4R`.
- `NppStatus nppiFullNormLevelGetBufferHostSize_32f_AC4R` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size (in bytes) for `nppiCrossCorrFull_NormLevel_32f_AC4R`.
- `NppStatus nppiFullNormLevelGetBufferHostSize_8u32f_C1R` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)

- Buffer size (in bytes) for nppiCrossCorrFull_NormLevel_8u32f_C1R.*
- **NppStatus** `nppiFullNormLevelGetBufferHostSize_8u32f_C3R` (NppiSize oSizeROI, int *hpBufferSize)
Buffer size (in bytes) for nppiCrossCorrFull_NormLevel_8u32f_C3R.
 - **NppStatus** `nppiFullNormLevelGetBufferHostSize_8u32f_C4R` (NppiSize oSizeROI, int *hpBufferSize)
Buffer size (in bytes) for nppiCrossCorrFull_NormLevel_8u32f_C4R.
 - **NppStatus** `nppiFullNormLevelGetBufferHostSize_8u32f_AC4R` (NppiSize oSizeROI, int *hpBufferSize)
Buffer size (in bytes) for nppiCrossCorrFull_NormLevel_8u32f_AC4R.
 - **NppStatus** `nppiFullNormLevelGetBufferHostSize_8s32f_C1R` (NppiSize oSizeROI, int *hpBufferSize)
Buffer size (in bytes) for nppiCrossCorrFull_NormLevel_8s32f_C1R.
 - **NppStatus** `nppiFullNormLevelGetBufferHostSize_8s32f_C3R` (NppiSize oSizeROI, int *hpBufferSize)
Buffer size (in bytes) for nppiCrossCorrFull_NormLevel_8s32f_C3R.
 - **NppStatus** `nppiFullNormLevelGetBufferHostSize_8s32f_C4R` (NppiSize oSizeROI, int *hpBufferSize)
Buffer size (in bytes) for nppiCrossCorrFull_NormLevel_8s32f_C4R.
 - **NppStatus** `nppiFullNormLevelGetBufferHostSize_8s32f_AC4R` (NppiSize oSizeROI, int *hpBufferSize)
Buffer size (in bytes) for nppiCrossCorrFull_NormLevel_8s32f_AC4R.
 - **NppStatus** `nppiFullNormLevelGetBufferHostSize_16u32f_C1R` (NppiSize oSizeROI, int *hpBufferSize)
Buffer size (in bytes) for nppiCrossCorrFull_NormLevel_16u32f_C1R.
 - **NppStatus** `nppiFullNormLevelGetBufferHostSize_16u32f_C3R` (NppiSize oSizeROI, int *hpBufferSize)
Buffer size (in bytes) for nppiCrossCorrFull_NormLevel_16u32f_C3R.
 - **NppStatus** `nppiFullNormLevelGetBufferHostSize_16u32f_C4R` (NppiSize oSizeROI, int *hpBufferSize)
Buffer size (in bytes) for nppiCrossCorrFull_NormLevel_16u32f_C4R.
 - **NppStatus** `nppiFullNormLevelGetBufferHostSize_16u32f_AC4R` (NppiSize oSizeROI, int *hpBufferSize)
Buffer size (in bytes) for nppiCrossCorrFull_NormLevel_16u32f_AC4R.

7.124.1 Detailed Description

Primitives for computing the normalized cross correlation coefficient between two images with full mode.

7.124.2 Function Documentation

7.124.2.1 `NppStatus nppiCrossCorrFull_NormLevel_16u32f_AC4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Four-channel 16-bit unsigned image CrossCorrFull_NormLevel ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#). Use [nppiFullNormLevelGetBufferHostSize_16u32f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.124.2.2 `NppStatus nppiCrossCorrFull_NormLevel_16u32f_C1R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

One-channel 16-bit unsigned image CrossCorrFull_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#). Use [nppiFullNormLevelGetBufferHostSize_16u32f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.124.2.3 `NppStatus nppiCrossCorrFull_NormLevel_16u32f_C3R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Three-channel 16-bit unsigned image CrossCorrFull_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use `nppiFullNormLevelGetBufferHostSize_16u32f_C3R` to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.124.2.4 `NppStatus nppiCrossCorrFull_NormLevel_16u32f_C4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Four-channel 16-bit unsigned image CrossCorrFull_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use `nppiFullNormLevelGetBufferHostSize_16u32f_C4R` to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.124.2.5 NppStatus nppiCrossCorrFull_NormLevel_32f_AC4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)

Four-channel 32-bit floating point image CrossCorrFull_NormLevel ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiFullNormLevelGetBufferHostSize_32f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.124.2.6 NppStatus nppiCrossCorrFull_NormLevel_32f_C1R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)

One-channel 32-bit floating point image CrossCorrFull_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiFullNormLevelGetBufferHostSize_32f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.124.2.7 `NppStatus nppiCrossCorrFull_NormLevel_32f_C3R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Three-channel 32-bit floating point image CrossCorrFull_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiFullNormLevelGetBufferHostSize_32f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.124.2.8 `NppStatus nppiCrossCorrFull_NormLevel_32f_C4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Four-channel 32-bit floating point image CrossCorrFull_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiFullNormLevelGetBufferHostSize_32f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.124.2.9 NppStatus nppiCrossCorrFull_NormLevel_8s32f_AC4R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)

Four-channel 8-bit signed image CrossCorrFull_NormLevel ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiFullNormLevelGetBufferHostSize_8s32f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.124.2.10 NppStatus nppiCrossCorrFull_NormLevel_8s32f_C1R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)

One-channel 8-bit signed image CrossCorrFull_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiFullNormLevelGetBufferHostSize_8s32f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.124.2.11 `NppStatus nppiCrossCorrFull_NormLevel_8s32f_C3R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Three-channel 8-bit signed image CrossCorrFull_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiFullNormLevelGetBufferHostSize_8s32f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.124.2.12 `NppStatus nppiCrossCorrFull_NormLevel_8s32f_C4R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Four-channel 8-bit signed image CrossCorrFull_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiFullNormLevelGetBufferHostSize_8s32f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.124.2.13 `NppStatus nppiCrossCorrFull_NormLevel_8u32f_AC4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image CrossCorrFull_NormLevel ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiFullNormLevelGetBufferHostSize_8u32f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.124.2.14 `NppStatus nppiCrossCorrFull_NormLevel_8u32f_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

One-channel 8-bit unsigned image CrossCorrFull_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiFullNormLevelGetBufferHostSize_8u32f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.124.2.15 `NppStatus nppiCrossCorrFull_NormLevel_8u32f_C3R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Three-channel 8-bit unsigned image CrossCorrFull_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiFullNormLevelGetBufferHostSize_8u32f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.124.2.16 `NppStatus nppiCrossCorrFull_NormLevel_8u32f_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image CrossCorrFull_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiFullNormLevelGetBufferHostSize_8u32f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.124.2.17 `NppStatus nppiCrossCorrFull_NormLevel_8u_AC4RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor, Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image CrossCorrFull_NormLevel ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiFullNormLevelGetBufferHostSize_8u_AC4RSfs](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.124.2.18 `NppStatus nppiCrossCorrFull_NormLevel_8u_C1RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor, Npp8u * pDeviceBuffer)`

One-channel 8-bit unsigned image CrossCorrFull_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiFullNormLevelGetBufferHostSize_8u_C1RSfs](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.124.2.19 `NppStatus nppiCrossCorrFull_NormLevel_8u_C3RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor, Npp8u * pDeviceBuffer)`

Three-channel 8-bit unsigned image CrossCorrFull_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiFullNormLevelGetBufferHostSize_8u_C3RSfs](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.124.2.20 `NppStatus nppiCrossCorrFull_NormLevel_8u_C4RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor, Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image CrossCorrFull_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiFullNormLevelGetBufferHostSize_8u_C4RSfs](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.124.2.21 NppStatus nppiFullNormLevelGetBufferHostSize_16u32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrFull_NormLevel_16u32f_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.124.2.22 NppStatus nppiFullNormLevelGetBufferHostSize_16u32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrFull_NormLevel_16u32f_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.124.2.23 NppStatus nppiFullNormLevelGetBufferHostSize_16u32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrFull_NormLevel_16u32f_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.124.2.24 NppStatus nppiFullNormLevelGetBufferHostSize_16u32f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrFull_NormLevel_16u32f_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.124.2.25 NppStatus nppiFullNormLevelGetBufferHostSize_32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrFull_NormLevel_32f_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.124.2.26 NppStatus nppiFullNormLevelGetBufferHostSize_32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrFull_NormLevel_32f_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.124.2.27 NppStatus nppiFullNormLevelGetBufferHostSize_32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrFull_NormLevel_32f_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.124.2.28 NppStatus nppiFullNormLevelGetBufferHostSize_32f_C4R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size (in bytes) for [nppiCrossCorrFull_NormLevel_32f_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.124.2.29 NppStatus nppiFullNormLevelGetBufferHostSize_8s32f_AC4R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size (in bytes) for [nppiCrossCorrFull_NormLevel_8s32f_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.124.2.30 NppStatus nppiFullNormLevelGetBufferHostSize_8s32f_C1R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size (in bytes) for [nppiCrossCorrFull_NormLevel_8s32f_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.124.2.31 NppStatus nppiFullNormLevelGetBufferHostSize_8s32f_C3R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size (in bytes) for [nppiCrossCorrFull_NormLevel_8s32f_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.124.2.32 NppStatus nppiFullNormLevelGetBufferHostSize_8s32f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrFull_NormLevel_8s32f_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.124.2.33 NppStatus nppiFullNormLevelGetBufferHostSize_8u32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrFull_NormLevel_8u32f_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.124.2.34 NppStatus nppiFullNormLevelGetBufferHostSize_8u32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrFull_NormLevel_8u32f_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.124.2.35 NppStatus nppiFullNormLevelGetBufferHostSize_8u32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrFull_NormLevel_8u32f_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.124.2.36 NppStatus nppiFullNormLevelGetBufferHostSize_8u32f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrFull_NormLevel_8u32f_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.124.2.37 NppStatus nppiFullNormLevelGetBufferHostSize_8u_AC4RSfs (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrFull_NormLevel_8u_AC4RSfs](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.124.2.38 NppStatus nppiFullNormLevelGetBufferHostSize_8u_C1RSfs (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrFull_NormLevel_8u_C1RSfs](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.124.2.39 NppStatus nppiFullNormLevelGetBufferHostSize_8u_C3RSfs (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrFull_NormLevel_8u_C3RSfs](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.124.2.40 NppStatus nppiFullNormLevelGetBufferHostSize_8u_C4RSfs (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrFull_NormLevel_8u_C4RSfs](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.125 CrossCorrSame_NormLevel

Primitives for computing the normalized cross correlation coefficient between two images with same mode.

CrossCorrSame_NormLevel

The functions compute the $\gamma_{st}(c, r)$ in [General Introduction](#) with same mode (see [Categorizations](#)).

The functions require additional scratch buffer for computations.

- `NppStatus nppiCrossCorrSame_NormLevel_8u_C1RSfs` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp8u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp8u *pDst`, int `nDstStep`, int `nScaleFactor`, `Npp8u *pDeviceBuffer`)
One-channel 8-bit unsigned image CrossCorrSame_NormLevel.
- `NppStatus nppiCrossCorrSame_NormLevel_8u_C3RSfs` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp8u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp8u *pDst`, int `nDstStep`, int `nScaleFactor`, `Npp8u *pDeviceBuffer`)
Three-channel 8-bit unsigned image CrossCorrSame_NormLevel.
- `NppStatus nppiCrossCorrSame_NormLevel_8u_C4RSfs` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp8u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp8u *pDst`, int `nDstStep`, int `nScaleFactor`, `Npp8u *pDeviceBuffer`)
Four-channel 8-bit unsigned image CrossCorrSame_NormLevel.
- `NppStatus nppiCrossCorrSame_NormLevel_8u_AC4RSfs` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp8u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp8u *pDst`, int `nDstStep`, int `nScaleFactor`, `Npp8u *pDeviceBuffer`)
Four-channel 8-bit unsigned image CrossCorrSame_NormLevel ignoring alpha channel.
- `NppStatus nppiCrossCorrSame_NormLevel_32f_C1R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp32f *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`, `Npp8u *pDeviceBuffer`)
One-channel 32-bit floating point image CrossCorrSame_NormLevel.
- `NppStatus nppiCrossCorrSame_NormLevel_32f_C3R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp32f *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`, `Npp8u *pDeviceBuffer`)
Three-channel 32-bit floating point image CrossCorrSame_NormLevel.
- `NppStatus nppiCrossCorrSame_NormLevel_32f_C4R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp32f *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`, `Npp8u *pDeviceBuffer`)
Four-channel 32-bit floating point image CrossCorrSame_NormLevel.
- `NppStatus nppiCrossCorrSame_NormLevel_32f_AC4R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp32f *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`, `Npp8u *pDeviceBuffer`)
Four-channel 32-bit floating point image CrossCorrSame_NormLevel ignoring alpha channel.

- `NppStatus nppiCrossCorrSame_NormLevel_8u32f_C1R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep, `Npp8u` *pDeviceBuffer)
One-channel 8-bit unsigned image CrossCorrSame_NormLevel.
- `NppStatus nppiCrossCorrSame_NormLevel_8u32f_C3R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep, `Npp8u` *pDeviceBuffer)
Three-channel 8-bit unsigned image CrossCorrSame_NormLevel.
- `NppStatus nppiCrossCorrSame_NormLevel_8u32f_C4R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep, `Npp8u` *pDeviceBuffer)
Four-channel 8-bit unsigned image CrossCorrSame_NormLevel.
- `NppStatus nppiCrossCorrSame_NormLevel_8u32f_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep, `Npp8u` *pDeviceBuffer)
Four-channel 8-bit unsigned image CrossCorrSame_NormLevel ignoring alpha channel.
- `NppStatus nppiCrossCorrSame_NormLevel_8s32f_C1R` (const `Npp8s` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8s` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep, `Npp8u` *pDeviceBuffer)
One-channel 8-bit signed image CrossCorrSame_NormLevel.
- `NppStatus nppiCrossCorrSame_NormLevel_8s32f_C3R` (const `Npp8s` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8s` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep, `Npp8u` *pDeviceBuffer)
Three-channel 8-bit signed image CrossCorrSame_NormLevel.
- `NppStatus nppiCrossCorrSame_NormLevel_8s32f_C4R` (const `Npp8s` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8s` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep, `Npp8u` *pDeviceBuffer)
Four-channel 8-bit signed image CrossCorrSame_NormLevel.
- `NppStatus nppiCrossCorrSame_NormLevel_8s32f_AC4R` (const `Npp8s` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp8s` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep, `Npp8u` *pDeviceBuffer)
Four-channel 8-bit signed image CrossCorrSame_NormLevel ignoring alpha channel.
- `NppStatus nppiCrossCorrSame_NormLevel_16u32f_C1R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp16u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep, `Npp8u` *pDeviceBuffer)
One-channel 16-bit unsigned image CrossCorrSame_NormLevel.
- `NppStatus nppiCrossCorrSame_NormLevel_16u32f_C3R` (const `Npp16u` *pSrc, int nSrcStep, `NppiSize` oSrcRoiSize, const `Npp16u` *pTpl, int nTplStep, `NppiSize` oTplRoiSize, `Npp32f` *pDst, int nDstStep, `Npp8u` *pDeviceBuffer)
Three-channel 16-bit unsigned image CrossCorrSame_NormLevel.

- `NppStatus nppiCrossCorrSame_NormLevel_16u32f_C4R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp16u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`, `Npp8u *pDeviceBuffer`)
Four-channel 16-bit unsigned image CrossCorrSame_NormLevel.
- `NppStatus nppiCrossCorrSame_NormLevel_16u32f_AC4R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp16u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`, `Npp8u *pDeviceBuffer`)
Four-channel 16-bit unsigned image CrossCorrSame_NormLevel ignoring alpha channel.

SameNormLevelGetBufferHostSize

Companion primitives for computing the device buffer size (in bytes) required by the `CrossCorrSame_` `NormLevel` primitives.

- `NppStatus nppiSameNormLevelGetBufferHostSize_8u_C1RSfs` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size (in bytes) for `nppiCrossCorrSame_NormLevel_8u_C1RSfs`.
- `NppStatus nppiSameNormLevelGetBufferHostSize_8u_C3RSfs` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size (in bytes) for `nppiCrossCorrSame_NormLevel_8u_C3RSfs`.
- `NppStatus nppiSameNormLevelGetBufferHostSize_8u_C4RSfs` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size (in bytes) for `nppiCrossCorrSame_NormLevel_8u_C4RSfs`.
- `NppStatus nppiSameNormLevelGetBufferHostSize_8u_AC4RSfs` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size (in bytes) for `nppiCrossCorrSame_NormLevel_8u_AC4RSfs`.
- `NppStatus nppiSameNormLevelGetBufferHostSize_32f_C1R` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size (in bytes) for `nppiCrossCorrSame_NormLevel_32f_C1R`.
- `NppStatus nppiSameNormLevelGetBufferHostSize_32f_C3R` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size (in bytes) for `nppiCrossCorrSame_NormLevel_32f_C3R`.
- `NppStatus nppiSameNormLevelGetBufferHostSize_32f_C4R` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size (in bytes) for `nppiCrossCorrSame_NormLevel_32f_C4R`.
- `NppStatus nppiSameNormLevelGetBufferHostSize_32f_AC4R` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size (in bytes) for `nppiCrossCorrSame_NormLevel_32f_AC4R`.
- `NppStatus nppiSameNormLevelGetBufferHostSize_8u32f_C1R` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)

Buffer size (in bytes) for nppiCrossCorrSame_NormLevel_8u32f_C1R.

- **NppStatus** `nppiSameNormLevelGetBufferHostSize_8u32f_C3R` (NppiSize oSizeROI, int *hpBufferSize)

Buffer size (in bytes) for nppiCrossCorrSame_NormLevel_8u32f_C3R.

- **NppStatus** `nppiSameNormLevelGetBufferHostSize_8u32f_C4R` (NppiSize oSizeROI, int *hpBufferSize)

Buffer size (in bytes) for nppiCrossCorrSame_NormLevel_8u32f_C4R.

- **NppStatus** `nppiSameNormLevelGetBufferHostSize_8u32f_AC4R` (NppiSize oSizeROI, int *hpBufferSize)

Buffer size (in bytes) for nppiCrossCorrSame_NormLevel_8u32f_AC4R.

- **NppStatus** `nppiSameNormLevelGetBufferHostSize_8s32f_C1R` (NppiSize oSizeROI, int *hpBufferSize)

Buffer size (in bytes) for nppiCrossCorrSame_NormLevel_8s32f_C1R.

- **NppStatus** `nppiSameNormLevelGetBufferHostSize_8s32f_C3R` (NppiSize oSizeROI, int *hpBufferSize)

Buffer size (in bytes) for nppiCrossCorrSame_NormLevel_8s32f_C3R.

- **NppStatus** `nppiSameNormLevelGetBufferHostSize_8s32f_C4R` (NppiSize oSizeROI, int *hpBufferSize)

Buffer size (in bytes) for nppiCrossCorrSame_NormLevel_8s32f_C4R.

- **NppStatus** `nppiSameNormLevelGetBufferHostSize_8s32f_AC4R` (NppiSize oSizeROI, int *hpBufferSize)

Buffer size (in bytes) for nppiCrossCorrSame_NormLevel_8s32f_AC4R.

- **NppStatus** `nppiSameNormLevelGetBufferHostSize_16u32f_C1R` (NppiSize oSizeROI, int *hpBufferSize)

Buffer size (in bytes) for nppiCrossCorrSame_NormLevel_16u32f_C1R.

- **NppStatus** `nppiSameNormLevelGetBufferHostSize_16u32f_C3R` (NppiSize oSizeROI, int *hpBufferSize)

Buffer size (in bytes) for nppiCrossCorrSame_NormLevel_16u32f_C3R.

- **NppStatus** `nppiSameNormLevelGetBufferHostSize_16u32f_C4R` (NppiSize oSizeROI, int *hpBufferSize)

Buffer size (in bytes) for nppiCrossCorrSame_NormLevel_16u32f_C4R.

- **NppStatus** `nppiSameNormLevelGetBufferHostSize_16u32f_AC4R` (NppiSize oSizeROI, int *hpBufferSize)

Buffer size (in bytes) for nppiCrossCorrSame_NormLevel_16u32f_AC4R.

7.125.1 Detailed Description

Primitives for computing the normalized cross correlation coefficient between two images with same mode.

7.125.2 Function Documentation

7.125.2.1 `NppStatus nppiCrossCorrSame_NormLevel_16u32f_AC4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Four-channel 16-bit unsigned image CrossCorrSame_NormLevel ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#). Use [nppiSameNormLevelGetBufferHostSize_16u32f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.125.2.2 `NppStatus nppiCrossCorrSame_NormLevel_16u32f_C1R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

One-channel 16-bit unsigned image CrossCorrSame_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#). Use [nppiSameNormLevelGetBufferHostSize_16u32f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.125.2.3 `NppStatus nppiCrossCorrSame_NormLevel_16u32f_C3R` (`const Npp16u * pSrc`, `int nSrcStep`, `NppiSize oSrcRoiSize`, `const Npp16u * pTpl`, `int nTplStep`, `NppiSize oTplRoiSize`, `Npp32f * pDst`, `int nDstStep`, `Npp8u * pDeviceBuffer`)

Three-channel 16-bit unsigned image CrossCorrSame_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiSameNormLevelGetBufferHostSize_16u32f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.125.2.4 `NppStatus nppiCrossCorrSame_NormLevel_16u32f_C4R` (`const Npp16u * pSrc`, `int nSrcStep`, `NppiSize oSrcRoiSize`, `const Npp16u * pTpl`, `int nTplStep`, `NppiSize oTplRoiSize`, `Npp32f * pDst`, `int nDstStep`, `Npp8u * pDeviceBuffer`)

Four-channel 16-bit unsigned image CrossCorrSame_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiSameNormLevelGetBufferHostSize_16u32f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.125.2.5 `NppStatus nppiCrossCorrSame_NormLevel_32f_AC4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Four-channel 32-bit floating point image CrossCorrSame_NormLevel ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiSameNormLevelGetBufferHostSize_32f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.125.2.6 `NppStatus nppiCrossCorrSame_NormLevel_32f_C1R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

One-channel 32-bit floating point image CrossCorrSame_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiSameNormLevelGetBufferHostSize_32f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.125.2.7 `NppStatus nppiCrossCorrSame_NormLevel_32f_C3R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Three-channel 32-bit floating point image CrossCorrSame_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiSameNormLevelGetBufferHostSize_32f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.125.2.8 `NppStatus nppiCrossCorrSame_NormLevel_32f_C4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Four-channel 32-bit floating point image CrossCorrSame_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiSameNormLevelGetBufferHostSize_32f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.125.2.9 `NppStatus nppiCrossCorrSame_NormLevel_8s32f_AC4R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Four-channel 8-bit signed image CrossCorrSame_NormLevel ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiSameNormLevelGetBufferHostSize_8s32f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.125.2.10 `NppStatus nppiCrossCorrSame_NormLevel_8s32f_C1R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

One-channel 8-bit signed image CrossCorrSame_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiSameNormLevelGetBufferHostSize_8s32f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.125.2.11 `NppStatus nppiCrossCorrSame_NormLevel_8s32f_C3R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Three-channel 8-bit signed image CrossCorrSame_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiSameNormLevelGetBufferHostSize_8s32f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.125.2.12 `NppStatus nppiCrossCorrSame_NormLevel_8s32f_C4R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Four-channel 8-bit signed image CrossCorrSame_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiSameNormLevelGetBufferHostSize_8s32f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.125.2.13 `NppStatus nppiCrossCorrSame_NormLevel_8u32f_AC4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image CrossCorrSame_NormLevel ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#). Use [nppiSameNormLevelGetBufferHostSize_8u32f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.125.2.14 `NppStatus nppiCrossCorrSame_NormLevel_8u32f_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

One-channel 8-bit unsigned image CrossCorrSame_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#). Use [nppiSameNormLevelGetBufferHostSize_8u32f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.125.2.15 `NppStatus nppiCrossCorrSame_NormLevel_8u32f_C3R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Three-channel 8-bit unsigned image CrossCorrSame_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiSameNormLevelGetBufferHostSize_8u32f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.125.2.16 `NppStatus nppiCrossCorrSame_NormLevel_8u32f_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image CrossCorrSame_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiSameNormLevelGetBufferHostSize_8u32f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.125.2.17 `NppStatus nppiCrossCorrSame_NormLevel_8u_AC4RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor, Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image CrossCorrSame_NormLevel ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#). Use [nppiSameNormLevelGetBufferHostSize_8u_AC4RSfs](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.125.2.18 `NppStatus nppiCrossCorrSame_NormLevel_8u_C1RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor, Npp8u * pDeviceBuffer)`

One-channel 8-bit unsigned image CrossCorrSame_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#). Use [nppiSameNormLevelGetBufferHostSize_8u_C1RSfs](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.125.2.19 `NppStatus nppiCrossCorrSame_NormLevel_8u_C3RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor, Npp8u * pDeviceBuffer)`

Three-channel 8-bit unsigned image CrossCorrSame_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#). Use [nppiSameNormLevelGetBufferHostSize_8u_C3RSfs](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.125.2.20 `NppStatus nppiCrossCorrSame_NormLevel_8u_C4RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor, Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image CrossCorrSame_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#). Use [nppiSameNormLevelGetBufferHostSize_8u_C4RSfs](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.125.2.21 NppStatus nppiSameNormLevelGetBufferHostSize_16u32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrSame_NormLevel_16u32f_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.125.2.22 NppStatus nppiSameNormLevelGetBufferHostSize_16u32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrSame_NormLevel_16u32f_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.125.2.23 NppStatus nppiSameNormLevelGetBufferHostSize_16u32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrSame_NormLevel_16u32f_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.125.2.24 NppStatus nppiSameNormLevelGetBufferHostSize_16u32f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrSame_NormLevel_16u32f_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.125.2.25 NppStatus nppiSameNormLevelGetBufferHostSize_32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrSame_NormLevel_32f_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.125.2.26 NppStatus nppiSameNormLevelGetBufferHostSize_32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrSame_NormLevel_32f_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.125.2.27 NppStatus nppiSameNormLevelGetBufferHostSize_32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrSame_NormLevel_32f_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.125.2.28 NppStatus nppiSameNormLevelGetBufferHostSize_32f_C4R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size (in bytes) for [nppiCrossCorrSame_NormLevel_32f_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.125.2.29 NppStatus nppiSameNormLevelGetBufferHostSize_8s32f_AC4R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size (in bytes) for [nppiCrossCorrSame_NormLevel_8s32f_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.125.2.30 NppStatus nppiSameNormLevelGetBufferHostSize_8s32f_C1R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size (in bytes) for [nppiCrossCorrSame_NormLevel_8s32f_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.125.2.31 NppStatus nppiSameNormLevelGetBufferHostSize_8s32f_C3R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size (in bytes) for [nppiCrossCorrSame_NormLevel_8s32f_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.125.2.32 NppStatus nppiSameNormLevelGetBufferHostSize_8s32f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrSame_NormLevel_8s32f_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.125.2.33 NppStatus nppiSameNormLevelGetBufferHostSize_8u32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrSame_NormLevel_8u32f_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.125.2.34 NppStatus nppiSameNormLevelGetBufferHostSize_8u32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrSame_NormLevel_8u32f_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.125.2.35 NppStatus nppiSameNormLevelGetBufferHostSize_8u32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrSame_NormLevel_8u32f_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.125.2.36 NppStatus nppiSameNormLevelGetBufferHostSize_8u32f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrSame_NormLevel_8u32f_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.125.2.37 NppStatus nppiSameNormLevelGetBufferHostSize_8u_AC4RSfs (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrSame_NormLevel_8u_AC4RSfs](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.125.2.38 NppStatus nppiSameNormLevelGetBufferHostSize_8u_C1RSfs (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrSame_NormLevel_8u_C1RSfs](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.125.2.39 NppStatus nppiSameNormLevelGetBufferHostSize_8u_C3RSfs (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrSame_NormLevel_8u_C3RSfs](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.125.2.40 NppStatus nppiSameNormLevelGetBufferHostSize_8u_C4RSfs (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrSame_NormLevel_8u_C4RSfs](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.126 CrossCorrValid_NormLevel

Primitives for computing the normalized cross correlation coefficient between two images with valid mode.

CrossCorrValid_NormLevel

The functions compute the $\gamma_{st}(c, r)$ in [General Introduction](#) with valid mode (see [Categorizations](#)).

The functions require additional scratch buffer for computations.

- `NppStatus nppiCrossCorrValid_NormLevel_8u_C1RSfs` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp8u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp8u *pDst`, int `nDstStep`, int `nScaleFactor`, `Npp8u *pDeviceBuffer`)
One-channel 8-bit unsigned image CrossCorrValid_NormLevel.
- `NppStatus nppiCrossCorrValid_NormLevel_8u_C3RSfs` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp8u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp8u *pDst`, int `nDstStep`, int `nScaleFactor`, `Npp8u *pDeviceBuffer`)
Three-channel 8-bit unsigned image CrossCorrValid_NormLevel.
- `NppStatus nppiCrossCorrValid_NormLevel_8u_C4RSfs` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp8u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp8u *pDst`, int `nDstStep`, int `nScaleFactor`, `Npp8u *pDeviceBuffer`)
Four-channel 8-bit unsigned image CrossCorrValid_NormLevel.
- `NppStatus nppiCrossCorrValid_NormLevel_8u_AC4RSfs` (const `Npp8u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp8u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp8u *pDst`, int `nDstStep`, int `nScaleFactor`, `Npp8u *pDeviceBuffer`)
Four-channel 8-bit unsigned image CrossCorrValid_NormLevel ignoring alpha channel.
- `NppStatus nppiCrossCorrValid_NormLevel_32f_C1R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp32f *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`, `Npp8u *pDeviceBuffer`)
One-channel 32-bit floating point image CrossCorrValid_NormLevel.
- `NppStatus nppiCrossCorrValid_NormLevel_32f_C3R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp32f *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`, `Npp8u *pDeviceBuffer`)
Three-channel 32-bit floating point image CrossCorrValid_NormLevel.
- `NppStatus nppiCrossCorrValid_NormLevel_32f_C4R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp32f *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`, `Npp8u *pDeviceBuffer`)
Four-channel 32-bit floating point image CrossCorrValid_NormLevel.
- `NppStatus nppiCrossCorrValid_NormLevel_32f_AC4R` (const `Npp32f *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp32f *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`, `Npp8u *pDeviceBuffer`)
Four-channel 32-bit floating point image CrossCorrValid_NormLevel ignoring alpha channel.

- [NppStatus nppiCrossCorrValid_NormLevel_8u32f_C1R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8u](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep, [Npp8u](#) *pDeviceBuffer)

One-channel 8-bit unsigned image CrossCorrValid_NormLevel.
- [NppStatus nppiCrossCorrValid_NormLevel_8u32f_C3R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8u](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep, [Npp8u](#) *pDeviceBuffer)

Three-channel 8-bit unsigned image CrossCorrValid_NormLevel.
- [NppStatus nppiCrossCorrValid_NormLevel_8u32f_C4R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8u](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep, [Npp8u](#) *pDeviceBuffer)

Four-channel 8-bit unsigned image CrossCorrValid_NormLevel.
- [NppStatus nppiCrossCorrValid_NormLevel_8u32f_AC4R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8u](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep, [Npp8u](#) *pDeviceBuffer)

Four-channel 8-bit unsigned image CrossCorrValid_NormLevel ignoring alpha channel.
- [NppStatus nppiCrossCorrValid_NormLevel_8s32f_C1R](#) (const [Npp8s](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8s](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep, [Npp8u](#) *pDeviceBuffer)

One-channel 8-bit signed image CrossCorrValid_NormLevel.
- [NppStatus nppiCrossCorrValid_NormLevel_8s32f_C3R](#) (const [Npp8s](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8s](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep, [Npp8u](#) *pDeviceBuffer)

Three-channel 8-bit signed image CrossCorrValid_NormLevel.
- [NppStatus nppiCrossCorrValid_NormLevel_8s32f_C4R](#) (const [Npp8s](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8s](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep, [Npp8u](#) *pDeviceBuffer)

Four-channel 8-bit signed image CrossCorrValid_NormLevel.
- [NppStatus nppiCrossCorrValid_NormLevel_8s32f_AC4R](#) (const [Npp8s](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp8s](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep, [Npp8u](#) *pDeviceBuffer)

Four-channel 8-bit signed image CrossCorrValid_NormLevel ignoring alpha channel.
- [NppStatus nppiCrossCorrValid_NormLevel_16u32f_C1R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp16u](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep, [Npp8u](#) *pDeviceBuffer)

One-channel 16-bit unsigned image CrossCorrValid_NormLevel.
- [NppStatus nppiCrossCorrValid_NormLevel_16u32f_C3R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [NppiSize](#) oSrcRoiSize, const [Npp16u](#) *pTpl, int nTplStep, [NppiSize](#) oTplRoiSize, [Npp32f](#) *pDst, int nDstStep, [Npp8u](#) *pDeviceBuffer)

Three-channel 16-bit unsigned image CrossCorrValid_NormLevel.

- `NppStatus nppiCrossCorrValid_NormLevel_16u32f_C4R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp16u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`, `Npp8u *pDeviceBuffer`)
Four-channel 16-bit unsigned image CrossCorrValid_NormLevel.
- `NppStatus nppiCrossCorrValid_NormLevel_16u32f_AC4R` (const `Npp16u *pSrc`, int `nSrcStep`, `NppiSize` `oSrcRoiSize`, const `Npp16u *pTpl`, int `nTplStep`, `NppiSize` `oTplRoiSize`, `Npp32f *pDst`, int `nDstStep`, `Npp8u *pDeviceBuffer`)
Four-channel 16-bit unsigned image CrossCorrValid_NormLevel ignoring alpha channel.

ValidNormLevelGetBufferHostSize

Companion primitives for computing the device buffer size (in bytes) required by the `CrossCorrValid_` `NormLevel` primitives.

- `NppStatus nppiValidNormLevelGetBufferHostSize_8u_C1RSfs` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size (in bytes) for nppiCrossCorrValid_NormLevel_8u_C1RSfs.
- `NppStatus nppiValidNormLevelGetBufferHostSize_8u_C3RSfs` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size (in bytes) for nppiCrossCorrValid_NormLevel_8u_C3RSfs.
- `NppStatus nppiValidNormLevelGetBufferHostSize_8u_C4RSfs` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size (in bytes) for nppiCrossCorrValid_NormLevel_8u_C4RSfs.
- `NppStatus nppiValidNormLevelGetBufferHostSize_8u_AC4RSfs` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size (in bytes) for nppiCrossCorrValid_NormLevel_8u_AC4RSfs.
- `NppStatus nppiValidNormLevelGetBufferHostSize_32f_C1R` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size (in bytes) for nppiCrossCorrValid_NormLevel_32f_C1R.
- `NppStatus nppiValidNormLevelGetBufferHostSize_32f_C3R` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size (in bytes) for nppiCrossCorrValid_NormLevel_32f_C3R.
- `NppStatus nppiValidNormLevelGetBufferHostSize_32f_C4R` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size (in bytes) for nppiCrossCorrValid_NormLevel_32f_C4R.
- `NppStatus nppiValidNormLevelGetBufferHostSize_32f_AC4R` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)
Buffer size (in bytes) for nppiCrossCorrValid_NormLevel_32f_AC4R.
- `NppStatus nppiValidNormLevelGetBufferHostSize_8u32f_C1R` (`NppiSize` `oSizeROI`, int `*hpBufferSize`)

Buffer size (in bytes) for nppiCrossCorrValid_NormLevel_8u32f_C1R.

- **NppStatus** `nppiValidNormLevelGetBufferHostSize_8u32f_C3R` (NppiSize oSizeROI, int *hpBufferSize)

Buffer size (in bytes) for nppiCrossCorrValid_NormLevel_8u32f_C3R.

- **NppStatus** `nppiValidNormLevelGetBufferHostSize_8u32f_C4R` (NppiSize oSizeROI, int *hpBufferSize)

Buffer size (in bytes) for nppiCrossCorrValid_NormLevel_8u32f_C4R.

- **NppStatus** `nppiValidNormLevelGetBufferHostSize_8u32f_AC4R` (NppiSize oSizeROI, int *hpBufferSize)

Buffer size (in bytes) for nppiCrossCorrValid_NormLevel_8u32f_AC4R.

- **NppStatus** `nppiValidNormLevelGetBufferHostSize_8s32f_C1R` (NppiSize oSizeROI, int *hpBufferSize)

Buffer size (in bytes) for nppiCrossCorrValid_NormLevel_8s32f_C1R.

- **NppStatus** `nppiValidNormLevelGetBufferHostSize_8s32f_C3R` (NppiSize oSizeROI, int *hpBufferSize)

Buffer size (in bytes) for nppiCrossCorrValid_NormLevel_8s32f_C3R.

- **NppStatus** `nppiValidNormLevelGetBufferHostSize_8s32f_C4R` (NppiSize oSizeROI, int *hpBufferSize)

Buffer size (in bytes) for nppiCrossCorrValid_NormLevel_8s32f_C4R.

- **NppStatus** `nppiValidNormLevelGetBufferHostSize_8s32f_AC4R` (NppiSize oSizeROI, int *hpBufferSize)

Buffer size (in bytes) for nppiCrossCorrValid_NormLevel_8s32f_AC4R.

- **NppStatus** `nppiValidNormLevelGetBufferHostSize_16u32f_C1R` (NppiSize oSizeROI, int *hpBufferSize)

Buffer size (in bytes) for nppiCrossCorrValid_NormLevel_16u32f_C1R.

- **NppStatus** `nppiValidNormLevelGetBufferHostSize_16u32f_C3R` (NppiSize oSizeROI, int *hpBufferSize)

Buffer size (in bytes) for nppiCrossCorrValid_NormLevel_16u32f_C3R.

- **NppStatus** `nppiValidNormLevelGetBufferHostSize_16u32f_C4R` (NppiSize oSizeROI, int *hpBufferSize)

Buffer size (in bytes) for nppiCrossCorrValid_NormLevel_16u32f_C4R.

- **NppStatus** `nppiValidNormLevelGetBufferHostSize_16u32f_AC4R` (NppiSize oSizeROI, int *hpBufferSize)

Buffer size (in bytes) for nppiCrossCorrValid_NormLevel_16u32f_AC4R.

7.126.1 Detailed Description

Primitives for computing the normalized cross correlation coefficient between two images with valid mode.

7.126.2 Function Documentation

7.126.2.1 `NppStatus nppiCrossCorrValid_NormLevel_16u32f_AC4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Four-channel 16-bit unsigned image CrossCorrValid_NormLevel ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#). Use [nppiValidNormLevelGetBufferHostSize_16u32f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.126.2.2 `NppStatus nppiCrossCorrValid_NormLevel_16u32f_C1R (const Npp16u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp16u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

One-channel 16-bit unsigned image CrossCorrValid_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#). Use [nppiValidNormLevelGetBufferHostSize_16u32f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.126.2.3 `NppStatus nppiCrossCorrValid_NormLevel_16u32f_C3R` (`const Npp16u * pSrc`, `int nSrcStep`, `NppiSize oSrcRoiSize`, `const Npp16u * pTpl`, `int nTplStep`, `NppiSize oTplRoiSize`, `Npp32f * pDst`, `int nDstStep`, `Npp8u * pDeviceBuffer`)

Three-channel 16-bit unsigned image CrossCorrValid_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiValidNormLevelGetBufferHostSize_16u32f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.126.2.4 `NppStatus nppiCrossCorrValid_NormLevel_16u32f_C4R` (`const Npp16u * pSrc`, `int nSrcStep`, `NppiSize oSrcRoiSize`, `const Npp16u * pTpl`, `int nTplStep`, `NppiSize oTplRoiSize`, `Npp32f * pDst`, `int nDstStep`, `Npp8u * pDeviceBuffer`)

Four-channel 16-bit unsigned image CrossCorrValid_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiValidNormLevelGetBufferHostSize_16u32f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.126.2.5 NppStatus nppiCrossCorrValid_NormLevel_32f_AC4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)

Four-channel 32-bit floating point image CrossCorrValid_NormLevel ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiValidNormLevelGetBufferHostSize_32f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.126.2.6 NppStatus nppiCrossCorrValid_NormLevel_32f_C1R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)

One-channel 32-bit floating point image CrossCorrValid_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiValidNormLevelGetBufferHostSize_32f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.126.2.7 `NppStatus nppiCrossCorrValid_NormLevel_32f_C3R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Three-channel 32-bit floating point image CrossCorrValid_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiValidNormLevelGetBufferHostSize_32f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.126.2.8 `NppStatus nppiCrossCorrValid_NormLevel_32f_C4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp32f * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Four-channel 32-bit floating point image CrossCorrValid_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiValidNormLevelGetBufferHostSize_32f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.126.2.9 `NppStatus nppiCrossCorrValid_NormLevel_8s32f_AC4R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Four-channel 8-bit signed image CrossCorrValid_NormLevel ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiValidNormLevelGetBufferHostSize_8s32f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.126.2.10 `NppStatus nppiCrossCorrValid_NormLevel_8s32f_C1R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

One-channel 8-bit signed image CrossCorrValid_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiValidNormLevelGetBufferHostSize_8s32f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.126.2.11 `NppStatus nppiCrossCorrValid_NormLevel_8s32f_C3R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Three-channel 8-bit signed image CrossCorrValid_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiValidNormLevelGetBufferHostSize_8s32f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.126.2.12 `NppStatus nppiCrossCorrValid_NormLevel_8s32f_C4R (const Npp8s * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8s * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Four-channel 8-bit signed image CrossCorrValid_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiValidNormLevelGetBufferHostSize_8s32f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.126.2.13 `NppStatus nppiCrossCorrValid_NormLevel_8u32f_AC4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image CrossCorrValid_NormLevel ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiValidNormLevelGetBufferHostSize_8u32f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.126.2.14 `NppStatus nppiCrossCorrValid_NormLevel_8u32f_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

One-channel 8-bit unsigned image CrossCorrValid_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiValidNormLevelGetBufferHostSize_8u32f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.126.2.15 `NppStatus nppiCrossCorrValid_NormLevel_8u32f_C3R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Three-channel 8-bit unsigned image CrossCorrValid_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiValidNormLevelGetBufferHostSize_8u32f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.126.2.16 `NppStatus nppiCrossCorrValid_NormLevel_8u32f_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp32f * pDst, int nDstStep, Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image CrossCorrValid_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiValidNormLevelGetBufferHostSize_8u32f_C4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.126.2.17 `NppStatus nppiCrossCorrValid_NormLevel_8u_AC4RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor, Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image CrossCorrValid_NormLevel ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiValidNormLevelGetBufferHostSize_8u_AC4RSfs](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.126.2.18 `NppStatus nppiCrossCorrValid_NormLevel_8u_C1RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor, Npp8u * pDeviceBuffer)`

One-channel 8-bit unsigned image CrossCorrValid_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiValidNormLevelGetBufferHostSize_8u_C1RSfs](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.126.2.19 `NppStatus nppiCrossCorrValid_NormLevel_8u_C3RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor, Npp8u * pDeviceBuffer)`

Three-channel 8-bit unsigned image CrossCorrValid_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiValidNormLevelGetBufferHostSize_8u_C3RSfs](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.126.2.20 `NppStatus nppiCrossCorrValid_NormLevel_8u_C4RSfs (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcRoiSize, const Npp8u * pTpl, int nTplStep, NppiSize oTplRoiSize, Npp8u * pDst, int nDstStep, int nScaleFactor, Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image CrossCorrValid_NormLevel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcRoiSize Region-of-Interest (ROI).

pTpl Pointer to the template image.

nTplStep Number of bytes between successive rows in the template image.

oTplRoiSize Region-of-Interest (ROI).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiValidNormLevelGetBufferHostSize_8u_C4RSfs](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.126.2.21 NppStatus nppiValidNormLevelGetBufferHostSize_16u32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrValid_NormLevel_16u32f_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.126.2.22 NppStatus nppiValidNormLevelGetBufferHostSize_16u32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrValid_NormLevel_16u32f_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.126.2.23 NppStatus nppiValidNormLevelGetBufferHostSize_16u32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrValid_NormLevel_16u32f_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.126.2.24 NppStatus nppiValidNormLevelGetBufferHostSize_16u32f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrValid_NormLevel_16u32f_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.126.2.25 NppStatus nppiValidNormLevelGetBufferHostSize_32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrValid_NormLevel_32f_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.126.2.26 NppStatus nppiValidNormLevelGetBufferHostSize_32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrValid_NormLevel_32f_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.126.2.27 NppStatus nppiValidNormLevelGetBufferHostSize_32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrValid_NormLevel_32f_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.126.2.28 NppStatus nppiValidNormLevelGetBufferHostSize_32f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrValid_NormLevel_32f_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.126.2.29 NppStatus nppiValidNormLevelGetBufferHostSize_8s32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrValid_NormLevel_8s32f_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.126.2.30 NppStatus nppiValidNormLevelGetBufferHostSize_8s32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrValid_NormLevel_8s32f_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.126.2.31 NppStatus nppiValidNormLevelGetBufferHostSize_8s32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrValid_NormLevel_8s32f_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.126.2.32 NppStatus nppiValidNormLevelGetBufferHostSize_8s32f_C4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrValid_NormLevel_8s32f_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.126.2.33 NppStatus nppiValidNormLevelGetBufferHostSize_8u32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrValid_NormLevel_8u32f_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.126.2.34 NppStatus nppiValidNormLevelGetBufferHostSize_8u32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrValid_NormLevel_8u32f_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.126.2.35 NppStatus nppiValidNormLevelGetBufferHostSize_8u32f_C3R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size (in bytes) for [nppiCrossCorrValid_NormLevel_8u32f_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.126.2.36 NppStatus nppiValidNormLevelGetBufferHostSize_8u32f_C4R (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size (in bytes) for [nppiCrossCorrValid_NormLevel_8u32f_C4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.126.2.37 NppStatus nppiValidNormLevelGetBufferHostSize_8u_AC4RSfs (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size (in bytes) for [nppiCrossCorrValid_NormLevel_8u_AC4RSfs](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.126.2.38 NppStatus nppiValidNormLevelGetBufferHostSize_8u_C1RSfs (NppiSize *oSizeROI*, int * *hpBufferSize*)

Buffer size (in bytes) for [nppiCrossCorrValid_NormLevel_8u_C1RSfs](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.126.2.39 NppStatus nppiValidNormLevelGetBufferHostSize_8u_C3RSfs (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrValid_NormLevel_8u_C3RSfs](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.126.2.40 NppStatus nppiValidNormLevelGetBufferHostSize_8u_C4RSfs (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiCrossCorrValid_NormLevel_8u_C4RSfs](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.127 Image Quality Index

Primitives for computing the image quality index of two images.

QualityIndex

Given two images M and N (both $W \times H$), the mathematical formula to calculate the image quality index Q between them is expressed as:

$$Q = \frac{4\sigma_{MN}\tilde{M}\tilde{N}}{[(\tilde{M}^2) + (\tilde{N}^2)][(\sigma_M)^2 + (\sigma_N)^2]}$$

where

$$\tilde{M} = \frac{1}{W \cdot H} \sum_{j=0}^{H-1} \sum_{i=0}^{W-1} M(j, i)$$

$$\tilde{N} = \frac{1}{W \cdot H} \sum_{j=0}^{H-1} \sum_{i=0}^{W-1} N(j, i)$$

$$\sigma_M = \sqrt{\frac{1}{W \cdot H - 1} \sum_{j=0}^{H-1} \sum_{i=0}^{W-1} [M(j, i) - \tilde{M}]^2}$$

$$\sigma_N = \sqrt{\frac{1}{W \cdot H - 1} \sum_{j=0}^{H-1} \sum_{i=0}^{W-1} [N(j, i) - \tilde{N}]^2}$$

$$\sigma_{MN} = \frac{1}{W \cdot H - 1} \sum_{j=0}^{H-1} \sum_{i=0}^{W-1} [M(j, i) - \tilde{M}][N(j, i) - \tilde{N}]$$

The functions require additional scratch buffer for computations.

- [NppStatus nppiQualityIndex_8u32f_C1R](#) (const [Npp8u](#) *pSrc1, int nSrc1Step, const [Npp8u](#) *pSrc2, int nSrc2Step, [NppiSize](#) oRoiSize, [Npp32f](#) *pDst, [Npp8u](#) *pDeviceBuffer)
One-channel 8-bit unsigned image QualityIndex.
- [NppStatus nppiQualityIndex_16u32f_C1R](#) (const [Npp16u](#) *pSrc1, int nSrc1Step, const [Npp16u](#) *pSrc2, int nSrc2Step, [NppiSize](#) oRoiSize, [Npp32f](#) *pDst, [Npp8u](#) *pDeviceBuffer)
One-channel 16-bit unsigned image QualityIndex.
- [NppStatus nppiQualityIndex_32f_C1R](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [NppiSize](#) oRoiSize, [Npp32f](#) *pDst, [Npp8u](#) *pDeviceBuffer)
One-channel 32-bit floating point image QualityIndex.
- [NppStatus nppiQualityIndex_8u32f_C3R](#) (const [Npp8u](#) *pSrc1, int nSrc1Step, const [Npp8u](#) *pSrc2, int nSrc2Step, [NppiSize](#) oRoiSize, [Npp32f](#) *pDst, [Npp8u](#) *pDeviceBuffer)
Three-channel 8-bit unsigned image QualityIndex.
- [NppStatus nppiQualityIndex_16u32f_C3R](#) (const [Npp16u](#) *pSrc1, int nSrc1Step, const [Npp16u](#) *pSrc2, int nSrc2Step, [NppiSize](#) oRoiSize, [Npp32f](#) *pDst, [Npp8u](#) *pDeviceBuffer)
Three-channel 16-bit unsigned image QualityIndex.

- **NppStatus** `nppiQualityIndex_32f_C3R` (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, **NppiSize** oRoiSize, **Npp32f** *pDst, **Npp8u** *pDeviceBuffer)
Three-channel 32-bit floating point image QualityIndex.
- **NppStatus** `nppiQualityIndex_8u32f_AC4R` (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **NppiSize** oRoiSize, **Npp32f** *pDst, **Npp8u** *pDeviceBuffer)
Four-channel 8-bit unsigned image QualityIndex.
- **NppStatus** `nppiQualityIndex_16u32f_AC4R` (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **NppiSize** oRoiSize, **Npp32f** *pDst, **Npp8u** *pDeviceBuffer)
Four-channel 16-bit unsigned image QualityIndex.
- **NppStatus** `nppiQualityIndex_32f_AC4R` (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, **NppiSize** oRoiSize, **Npp32f** *pDst, **Npp8u** *pDeviceBuffer)
Four-channel 32-bit floating point image QualityIndex.

QualityIndexGetBufferHostSize

Companion primitives for computing the device buffer size (in bytes) required by the QualityIndex primitives.

- **NppStatus** `nppiQualityIndexGetBufferHostSize_8u32f_C1R` (**NppiSize** oSizeROI, int *hpBufferSize)
Buffer size (in bytes) for `nppiQualityIndex_8u32f_C1R`.
- **NppStatus** `nppiQualityIndexGetBufferHostSize_16u32f_C1R` (**NppiSize** oSizeROI, int *hpBufferSize)
Buffer size (in bytes) for `nppiQualityIndex_16u32f_C1R`.
- **NppStatus** `nppiQualityIndexGetBufferHostSize_32f_C1R` (**NppiSize** oSizeROI, int *hpBufferSize)
Buffer size (in bytes) for `nppiQualityIndex_32f_C1R`.
- **NppStatus** `nppiQualityIndexGetBufferHostSize_8u32f_C3R` (**NppiSize** oSizeROI, int *hpBufferSize)
Buffer size (in bytes) for `nppiQualityIndex_8u32f_C3R`.
- **NppStatus** `nppiQualityIndexGetBufferHostSize_16u32f_C3R` (**NppiSize** oSizeROI, int *hpBufferSize)
Buffer size (in bytes) for `nppiQualityIndex_16u32f_C3R`.
- **NppStatus** `nppiQualityIndexGetBufferHostSize_32f_C3R` (**NppiSize** oSizeROI, int *hpBufferSize)
Buffer size (in bytes) for `nppiQualityIndex_32f_C3R`.
- **NppStatus** `nppiQualityIndexGetBufferHostSize_8u32f_AC4R` (**NppiSize** oSizeROI, int *hpBufferSize)
Buffer size (in bytes) for `nppiQualityIndex_8u32f_AC4R`.

- `NppStatus nppiQualityIndexGetBufferHostSize_16u32f_AC4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size (in bytes) for [nppiQualityIndex_16u32f_AC4R](#).
- `NppStatus nppiQualityIndexGetBufferHostSize_32f_AC4R` (`NppiSize` `oSizeROI`, `int *hpBufferSize`)
Buffer size (in bytes) for [nppiQualityIndex_32f_AC4R](#).

7.127.1 Detailed Description

Primitives for computing the image quality index of two images.

7.127.2 Function Documentation

7.127.2.1 `NppStatus nppiQualityIndex_16u32f_AC4R` (`const Npp16u *pSrc1`, `int nSrc1Step`, `const Npp16u *pSrc2`, `int nSrc2Step`, `NppiSize oRoiSize`, `Npp32f *pDst`, `Npp8u *pDeviceBuffer`)

Four-channel 16-bit unsigned image QualityIndex.

Parameters:

pSrc1 [Source-Image Pointer](#).

nSrc1Step [Source-Image Line Step](#).

pSrc2 [Source-Image Pointer](#).

nSrc2Step [Source-Image Line Step](#).

oRoiSize [Region-of-Interest \(ROI\)](#).

pDst [Pointer to the quality index](#).

pDeviceBuffer [Pointer to the required device memory allocation, Scratch Buffer and Host Pointer](#).
 Use [nppiQualityIndexGetBufferHostSize_16u32f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_QUALITY_INDEX_ERROR` if pixels of either image are constant numberse.

7.127.2.2 `NppStatus nppiQualityIndex_16u32f_C1R` (`const Npp16u *pSrc1`, `int nSrc1Step`, `const Npp16u *pSrc2`, `int nSrc2Step`, `NppiSize oRoiSize`, `Npp32f *pDst`, `Npp8u *pDeviceBuffer`)

One-channel 16-bit unsigned image QualityIndex.

Parameters:

pSrc1 [Source-Image Pointer](#).

nSrc1Step [Source-Image Line Step](#).

pSrc2 [Source-Image Pointer](#).

nSrc2Step Source-Image Line Step.

oRoiSize Region-of-Interest (ROI).

pDst Pointer to the quality index.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiQualityIndexGetBufferHostSize_16u32f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_QUALITY_INDEX_ERROR` if pixels of either image are constant numberse.

7.127.2.3 `NppStatus nppiQualityIndex_16u32f_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, NppiSize oRoiSize, Npp32f * pDst, Npp8u * pDeviceBuffer)`

Three-channel 16-bit unsigned image QualityIndex.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oRoiSize Region-of-Interest (ROI).

pDst Pointer to the quality index.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiQualityIndexGetBufferHostSize_16u32f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_QUALITY_INDEX_ERROR` if pixels of either image are constant numberse.

7.127.2.4 `NppStatus nppiQualityIndex_32f_AC4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oRoiSize, Npp32f * pDst, Npp8u * pDeviceBuffer)`

Four-channel 32-bit floating point image QualityIndex.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oRoiSize Region-of-Interest (ROI).

pDst Pointer to the quality index.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiQualityIndexGetBufferHostSize_32f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_QUALITY_INDEX_ERROR` if pixels of either image are constant numberse.

7.127.2.5 `NppStatus nppiQualityIndex_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oRoiSize, Npp32f * pDst, Npp8u * pDeviceBuffer)`

One-channel 32-bit floating point image QualityIndex.

Parameters:

pSrc1 [Source-Image Pointer](#).

nSrc1Step [Source-Image Line Step](#).

pSrc2 [Source-Image Pointer](#).

nSrc2Step [Source-Image Line Step](#).

oRoiSize [Region-of-Interest \(ROI\)](#).

pDst Pointer to the quality index.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiQualityIndexGetBufferHostSize_32f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_QUALITY_INDEX_ERROR` if pixels of either image are constant numberse.

7.127.2.6 `NppStatus nppiQualityIndex_32f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, NppiSize oRoiSize, Npp32f * pDst, Npp8u * pDeviceBuffer)`

Three-channel 32-bit floating point image QualityIndex.

Parameters:

pSrc1 [Source-Image Pointer](#).

nSrc1Step [Source-Image Line Step](#).

pSrc2 [Source-Image Pointer](#).

nSrc2Step [Source-Image Line Step](#).

oRoiSize [Region-of-Interest \(ROI\)](#).

pDst Pointer to the quality index.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiQualityIndexGetBufferHostSize_32f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_QUALITY_INDEX_ERROR` if pixels of either image are constant numberse.

7.127.2.7 `NppStatus nppiQualityIndex_8u32f_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oRoiSize, Npp32f * pDst, Npp8u * pDeviceBuffer)`

Four-channel 8-bit unsigned image QualityIndex.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oRoiSize Region-of-Interest (ROI).

pDst Pointer to the quality index.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiQualityIndexGetBufferHostSize_8u32f_AC4R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_QUALITY_INDEX_ERROR` if pixels of either image are constant numberse.

7.127.2.8 `NppStatus nppiQualityIndex_8u32f_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oRoiSize, Npp32f * pDst, Npp8u * pDeviceBuffer)`

One-channel 8-bit unsigned image QualityIndex.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oRoiSize Region-of-Interest (ROI).

pDst Pointer to the quality index.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiQualityIndexGetBufferHostSize_8u32f_C1R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_QUALITY_INDEX_ERROR` if pixels of either image are constant numberse.

7.127.2.9 `NppStatus nppiQualityIndex_8u32f_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, NppiSize oRoiSize, Npp32f * pDst, Npp8u * pDeviceBuffer)`

Three-channel 8-bit unsigned image QualityIndex.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

oRoiSize Region-of-Interest (ROI).

pDst Pointer to the quality index.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppiQualityIndexGetBufferHostSize_8u32f_C3R](#) to compute the required size (in bytes).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_QUALITY_INDEX_ERROR` if pixels of either image are constant numberse.

7.127.2.10 `NppStatus nppiQualityIndexGetBufferHostSize_16u32f_AC4R` (`NppiSize oSizeROI`, `int * hpBufferSize`)

Buffer size (in bytes) for [nppiQualityIndex_16u32f_AC4R](#).

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.127.2.11 `NppStatus nppiQualityIndexGetBufferHostSize_16u32f_C1R` (`NppiSize oSizeROI`, `int * hpBufferSize`)

Buffer size (in bytes) for [nppiQualityIndex_16u32f_C1R](#).

Parameters:

oSizeROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

`NPP_NULL_POINTER_ERROR` if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.127.2.12 NppStatus nppiQualityIndexGetBufferHostSize_16u32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiQualityIndex_16u32f_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.127.2.13 NppStatus nppiQualityIndexGetBufferHostSize_32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiQualityIndex_32f_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.127.2.14 NppStatus nppiQualityIndexGetBufferHostSize_32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiQualityIndex_32f_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.127.2.15 NppStatus nppiQualityIndexGetBufferHostSize_32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiQualityIndex_32f_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.127.2.16 NppStatus nppiQualityIndexGetBufferHostSize_8u32f_AC4R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiQualityIndex_8u32f_AC4R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.127.2.17 NppStatus nppiQualityIndexGetBufferHostSize_8u32f_C1R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiQualityIndex_8u32f_C1R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.127.2.18 NppStatus nppiQualityIndexGetBufferHostSize_8u32f_C3R (NppiSize oSizeROI, int * hpBufferSize)

Buffer size (in bytes) for [nppiQualityIndex_8u32f_C3R](#).

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_NULL_POINTER_ERROR if *hpBufferSize* is 0 (NULL), [ROI Related Error Codes](#).

7.128 Memory Management

Routines for allocating and deallocating pitched image storage.

Functions

- void [nppiFree](#) (void *pData)
Free method for any 2D allocated memory.

Image Memory Allocation

ImageAllocator methods for 2D arrays of data.

The allocators have width and height parameters to specify the size of the image data being allocated. They return a pointer to the newly created memory and return the numbers of bytes between successive lines.

If the memory allocation failed due to lack of free device memory or device memory fragmentation the routine returns 0.

All allocators return memory with line strides that are beneficial for performance. It is not mandatory to use these allocators. Any valid CUDA device-memory pointers can be used by the NPP primitives and there are no restrictions on line strides.

- $\text{Npp8u} * \text{nppiMalloc_8u_C1}$ (int nWidthPixels, int nHeightPixels, int *pStepBytes)
8-bit unsigned image memory allocator.
- $\text{Npp8u} * \text{nppiMalloc_8u_C2}$ (int nWidthPixels, int nHeightPixels, int *pStepBytes)
2 channel 8-bit unsigned image memory allocator.
- $\text{Npp8u} * \text{nppiMalloc_8u_C3}$ (int nWidthPixels, int nHeightPixels, int *pStepBytes)
3 channel 8-bit unsigned image memory allocator.
- $\text{Npp8u} * \text{nppiMalloc_8u_C4}$ (int nWidthPixels, int nHeightPixels, int *pStepBytes)
4 channel 8-bit unsigned image memory allocator.
- $\text{Npp16u} * \text{nppiMalloc_16u_C1}$ (int nWidthPixels, int nHeightPixels, int *pStepBytes)
16-bit unsigned image memory allocator.
- $\text{Npp16u} * \text{nppiMalloc_16u_C2}$ (int nWidthPixels, int nHeightPixels, int *pStepBytes)
2 channel 16-bit unsigned image memory allocator.
- $\text{Npp16u} * \text{nppiMalloc_16u_C3}$ (int nWidthPixels, int nHeightPixels, int *pStepBytes)
3 channel 16-bit unsigned image memory allocator.
- $\text{Npp16u} * \text{nppiMalloc_16u_C4}$ (int nWidthPixels, int nHeightPixels, int *pStepBytes)
4 channel 16-bit unsigned image memory allocator.
- $\text{Npp16s} * \text{nppiMalloc_16s_C1}$ (int nWidthPixels, int nHeightPixels, int *pStepBytes)
16-bit signed image memory allocator.

- `Npp16s * nppiMalloc_16s_C2` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
2 channel 16-bit signed image memory allocator.
- `Npp16s * nppiMalloc_16s_C4` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
4 channel 16-bit signed image memory allocator.
- `Npp16sc * nppiMalloc_16sc_C1` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
1 channel 16-bit signed complex image memory allocator.
- `Npp16sc * nppiMalloc_16sc_C2` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
2 channel 16-bit signed complex image memory allocator.
- `Npp16sc * nppiMalloc_16sc_C3` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
3 channel 16-bit signed complex image memory allocator.
- `Npp16sc * nppiMalloc_16sc_C4` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
4 channel 16-bit signed complex image memory allocator.
- `Npp32s * nppiMalloc_32s_C1` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
32-bit signed image memory allocator.
- `Npp32s * nppiMalloc_32s_C3` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
3 channel 32-bit signed image memory allocator.
- `Npp32s * nppiMalloc_32s_C4` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
4 channel 32-bit signed image memory allocator.
- `Npp32sc * nppiMalloc_32sc_C1` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
32-bit integer complex image memory allocator.
- `Npp32sc * nppiMalloc_32sc_C2` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
2 channel 32-bit integer complex image memory allocator.
- `Npp32sc * nppiMalloc_32sc_C3` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
3 channel 32-bit integer complex image memory allocator.
- `Npp32sc * nppiMalloc_32sc_C4` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
4 channel 32-bit integer complex image memory allocator.
- `Npp32f * nppiMalloc_32f_C1` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
32-bit floating point image memory allocator.
- `Npp32f * nppiMalloc_32f_C2` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
2 channel 32-bit floating point image memory allocator.
- `Npp32f * nppiMalloc_32f_C3` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
3 channel 32-bit floating point image memory allocator.
- `Npp32f * nppiMalloc_32f_C4` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
4 channel 32-bit floating point image memory allocator.

- `Npp32fc * nppiMalloc_32fc_C1` (int *nWidthPixels*, int *nHeightPixels*, int **pStepBytes*)
32-bit float complex image memory allocator.
- `Npp32fc * nppiMalloc_32fc_C2` (int *nWidthPixels*, int *nHeightPixels*, int **pStepBytes*)
2 channel 32-bit float complex image memory allocator.
- `Npp32fc * nppiMalloc_32fc_C3` (int *nWidthPixels*, int *nHeightPixels*, int **pStepBytes*)
3 channel 32-bit float complex image memory allocator.
- `Npp32fc * nppiMalloc_32fc_C4` (int *nWidthPixels*, int *nHeightPixels*, int **pStepBytes*)
4 channel 32-bit float complex image memory allocator.

7.128.1 Detailed Description

Routines for allocating and deallocating pitched image storage.

These methods are provided for convenience. They allocate memory that may contain additional padding bytes at the end of each line of pixels. Though padding is not necessary for any of the NPP image-processing primitives to work correctly, its absence may cause severe performance degradation compared to properly padded images.

7.128.2 Function Documentation

7.128.2.1 void nppiFree (void * *pData*)

Free method for any 2D allocated memory.

This method should be used to free memory allocated with any of the `nppiMalloc_<modifier>` methods.

Parameters:

pData A pointer to memory allocated using `nppiMalloc_<modifier>`.

7.128.2.2 Npp16s* nppiMalloc_16s_C1 (int *nWidthPixels*, int *nHeightPixels*, int **pStepBytes*)

16-bit signed image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes Line Step.

Returns:

Pointer to new image data.

7.128.2.3 Npp16s* nppiMalloc_16s_C2 (int *nWidthPixels*, int *nHeightPixels*, int * *pStepBytes*)

2 channel 16-bit signed image memory allocator.

Parameters:

nWidthPixels Image width.
nHeightPixels Image height.
pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.4 Npp16s* nppiMalloc_16s_C4 (int *nWidthPixels*, int *nHeightPixels*, int * *pStepBytes*)

4 channel 16-bit signed image memory allocator.

Parameters:

nWidthPixels Image width.
nHeightPixels Image height.
pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.5 Npp16sc* nppiMalloc_16sc_C1 (int *nWidthPixels*, int *nHeightPixels*, int * *pStepBytes*)

1 channel 16-bit signed complex image memory allocator.

Parameters:

nWidthPixels Image width.
nHeightPixels Image height.
pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.6 Npp16sc* nppiMalloc_16sc_C2 (int *nWidthPixels*, int *nHeightPixels*, int * *pStepBytes*)

2 channel 16-bit signed complex image memory allocator.

Parameters:

nWidthPixels Image width.
nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.7 Npp16sc* nppiMalloc_16sc_C3 (int nWidthPixels, int nHeightPixels, int * pStepBytes)

3 channel 16-bit signed complex image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.8 Npp16sc* nppiMalloc_16sc_C4 (int nWidthPixels, int nHeightPixels, int * pStepBytes)

4 channel 16-bit signed complex image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.9 Npp16u* nppiMalloc_16u_C1 (int nWidthPixels, int nHeightPixels, int * pStepBytes)

16-bit unsigned image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.10 Npp16u* nppiMalloc_16u_C2 (int nWidthPixels, int nHeightPixels, int * pStepBytes)

2 channel 16-bit unsigned image memory allocator.

Parameters:

nWidthPixels Image width.
nHeightPixels Image height.
pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.11 Npp16u* nppiMalloc_16u_C3 (int nWidthPixels, int nHeightPixels, int * pStepBytes)

3 channel 16-bit unsigned image memory allocator.

Parameters:

nWidthPixels Image width.
nHeightPixels Image height.
pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.12 Npp16u* nppiMalloc_16u_C4 (int nWidthPixels, int nHeightPixels, int * pStepBytes)

4 channel 16-bit unsigned image memory allocator.

Parameters:

nWidthPixels Image width.
nHeightPixels Image height.
pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.13 Npp32f* nppiMalloc_32f_C1 (int nWidthPixels, int nHeightPixels, int * pStepBytes)

32-bit floating point image memory allocator.

Parameters:

nWidthPixels Image width.
nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.14 Npp32f* nppiMalloc_32f_C2 (int nWidthPixels, int nHeightPixels, int * pStepBytes)

2 channel 32-bit floating point image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.15 Npp32f* nppiMalloc_32f_C3 (int nWidthPixels, int nHeightPixels, int * pStepBytes)

3 channel 32-bit floating point image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.16 Npp32f* nppiMalloc_32f_C4 (int nWidthPixels, int nHeightPixels, int * pStepBytes)

4 channel 32-bit floating point image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.17 Npp32fc* nppiMalloc_32fc_C1 (int *nWidthPixels*, int *nHeightPixels*, int * *pStepBytes*)

32-bit float complex image memory allocator.

Parameters:

nWidthPixels Image width.
nHeightPixels Image height.
pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.18 Npp32fc* nppiMalloc_32fc_C2 (int *nWidthPixels*, int *nHeightPixels*, int * *pStepBytes*)

2 channel 32-bit float complex image memory allocator.

Parameters:

nWidthPixels Image width.
nHeightPixels Image height.
pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.19 Npp32fc* nppiMalloc_32fc_C3 (int *nWidthPixels*, int *nHeightPixels*, int * *pStepBytes*)

3 channel 32-bit float complex image memory allocator.

Parameters:

nWidthPixels Image width.
nHeightPixels Image height.
pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.20 Npp32fc* nppiMalloc_32fc_C4 (int *nWidthPixels*, int *nHeightPixels*, int * *pStepBytes*)

4 channel 32-bit float complex image memory allocator.

Parameters:

nWidthPixels Image width.
nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.21 Npp32s* nppiMalloc_32s_C1 (int nWidthPixels, int nHeightPixels, int * pStepBytes)

32-bit signed image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.22 Npp32s* nppiMalloc_32s_C3 (int nWidthPixels, int nHeightPixels, int * pStepBytes)

3 channel 32-bit signed image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.23 Npp32s* nppiMalloc_32s_C4 (int nWidthPixels, int nHeightPixels, int * pStepBytes)

4 channel 32-bit signed image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.24 Npp32sc* nppiMalloc_32sc_C1 (int nWidthPixels, int nHeightPixels, int * pStepBytes)

32-bit integer complex image memory allocator.

Parameters:

nWidthPixels Image width.
nHeightPixels Image height.
pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.25 Npp32sc* nppiMalloc_32sc_C2 (int nWidthPixels, int nHeightPixels, int * pStepBytes)

2 channel 32-bit integer complex image memory allocator.

Parameters:

nWidthPixels Image width.
nHeightPixels Image height.
pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.26 Npp32sc* nppiMalloc_32sc_C3 (int nWidthPixels, int nHeightPixels, int * pStepBytes)

3 channel 32-bit integer complex image memory allocator.

Parameters:

nWidthPixels Image width.
nHeightPixels Image height.
pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.27 Npp32sc* nppiMalloc_32sc_C4 (int nWidthPixels, int nHeightPixels, int * pStepBytes)

4 channel 32-bit integer complex image memory allocator.

Parameters:

nWidthPixels Image width.
nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.28 Npp8u* nppiMalloc_8u_C1 (int nWidthPixels, int nHeightPixels, int * pStepBytes)

8-bit unsigned image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.29 Npp8u* nppiMalloc_8u_C2 (int nWidthPixels, int nHeightPixels, int * pStepBytes)

2 channel 8-bit unsigned image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.30 Npp8u* nppiMalloc_8u_C3 (int nWidthPixels, int nHeightPixels, int * pStepBytes)

3 channel 8-bit unsigned image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.128.2.31 Npp8u* nppiMalloc_8u_C4 (int *nWidthPixels*, int *nHeightPixels*, int * *pStepBytes*)

4 channel 8-bit unsigned image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data.

7.129 Threshold and Compare Operations

Methods for pixel-wise threshold and compare operations.

Modules

- [Threshold Operations](#)

Threshold image pixels.

- [Compare Operations](#)

Compare the pixels of two images and create a binary result image.

7.129.1 Detailed Description

Methods for pixel-wise threshold and compare operations.

7.130 Threshold Operations

Threshold image pixels.

Functions

- `NppStatus nppiThreshold_8u_C1R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` nThreshold, `NppCmpOp` eComparisonOperation)
1 channel 8-bit unsigned char threshold.
- `NppStatus nppiThreshold_8u_C1IR` (`Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp8u` nThreshold, `NppCmpOp` eComparisonOperation)
1 channel 8-bit unsigned char in place threshold.
- `NppStatus nppiThreshold_16u_C1R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16u` nThreshold, `NppCmpOp` eComparisonOperation)
1 channel 16-bit unsigned short threshold.
- `NppStatus nppiThreshold_16u_C1IR` (`Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp16u` nThreshold, `NppCmpOp` eComparisonOperation)
1 channel 16-bit unsigned short in place threshold.
- `NppStatus nppiThreshold_16s_C1R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16s` nThreshold, `NppCmpOp` eComparisonOperation)
1 channel 16-bit signed short threshold.
- `NppStatus nppiThreshold_16s_C1IR` (`Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp16s` nThreshold, `NppCmpOp` eComparisonOperation)
1 channel 16-bit signed short in place threshold.
- `NppStatus nppiThreshold_32f_C1R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32f` nThreshold, `NppCmpOp` eComparisonOperation)
1 channel 32-bit floating point threshold.
- `NppStatus nppiThreshold_32f_C1IR` (`Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32f` nThreshold, `NppCmpOp` eComparisonOperation)
1 channel 32-bit floating point in place threshold.
- `NppStatus nppiThreshold_8u_C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` rThresholds[3], `NppCmpOp` eComparisonOperation)
3 channel 8-bit unsigned char threshold.
- `NppStatus nppiThreshold_8u_C3IR` (`Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp8u` rThresholds[3], `NppCmpOp` eComparisonOperation)
3 channel 8-bit unsigned char in place threshold.
- `NppStatus nppiThreshold_16u_C3R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16u` rThresholds[3], `NppCmpOp` eComparisonOperation)
3 channel 16-bit unsigned short threshold.

- `NppStatus nppiThreshold_16u_C3IR` (`Npp16u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp16u rThresholds[3]`, `NppCmpOp eComparisonOperation`)
3 channel 16-bit unsigned short in place threshold.
- `NppStatus nppiThreshold_16s_C3R` (`const Npp16s *pSrc`, `int nSrcStep`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp16s rThresholds[3]`, `NppCmpOp eComparisonOperation`)
3 channel 16-bit signed short threshold.
- `NppStatus nppiThreshold_16s_C3IR` (`Npp16s *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp16s rThresholds[3]`, `NppCmpOp eComparisonOperation`)
3 channel 16-bit signed short in place threshold.
- `NppStatus nppiThreshold_32f_C3R` (`const Npp32f *pSrc`, `int nSrcStep`, `Npp32f *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp32f rThresholds[3]`, `NppCmpOp eComparisonOperation`)
3 channel 32-bit floating point threshold.
- `NppStatus nppiThreshold_32f_C3IR` (`Npp32f *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp32f rThresholds[3]`, `NppCmpOp eComparisonOperation`)
3 channel 32-bit floating point in place threshold.
- `NppStatus nppiThreshold_8u_AC4R` (`const Npp8u *pSrc`, `int nSrcStep`, `Npp8u *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp8u rThresholds[3]`, `NppCmpOp eComparisonOperation`)
4 channel 8-bit unsigned char image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_8u_AC4IR` (`Npp8u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp8u rThresholds[3]`, `NppCmpOp eComparisonOperation`)
4 channel 8-bit unsigned char in place image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_16u_AC4R` (`const Npp16u *pSrc`, `int nSrcStep`, `Npp16u *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp16u rThresholds[3]`, `NppCmpOp eComparisonOperation`)
4 channel 16-bit unsigned short image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_16u_AC4IR` (`Npp16u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp16u rThresholds[3]`, `NppCmpOp eComparisonOperation`)
4 channel 16-bit unsigned short in place image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_16s_AC4R` (`const Npp16s *pSrc`, `int nSrcStep`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp16s rThresholds[3]`, `NppCmpOp eComparisonOperation`)
4 channel 16-bit signed short image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_16s_AC4IR` (`Npp16s *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp16s rThresholds[3]`, `NppCmpOp eComparisonOperation`)
4 channel 16-bit signed short in place image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_32f_AC4R` (`const Npp32f *pSrc`, `int nSrcStep`, `Npp32f *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp32f rThresholds[3]`, `NppCmpOp eComparisonOperation`)
4 channel 32-bit floating point image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_32f_AC4IR` (`Npp32f *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp32f rThresholds[3]`, `NppCmpOp eComparisonOperation`)
4 channel 32-bit floating point in place image threshold, not affecting Alpha.

- `NppStatus nppiThreshold_GT_8u_C1R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` nThreshold)
1 channel 8-bit unsigned char threshold.
- `NppStatus nppiThreshold_GT_8u_C1IR` (`Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp8u` nThreshold)
1 channel 8-bit unsigned char in place threshold.
- `NppStatus nppiThreshold_GT_16u_C1R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16u` nThreshold)
1 channel 16-bit unsigned short threshold.
- `NppStatus nppiThreshold_GT_16u_C1IR` (`Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp16u` nThreshold)
1 channel 16-bit unsigned short in place threshold.
- `NppStatus nppiThreshold_GT_16s_C1R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16s` nThreshold)
1 channel 16-bit signed short threshold.
- `NppStatus nppiThreshold_GT_16s_C1IR` (`Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp16s` nThreshold)
1 channel 16-bit signed short in place threshold.
- `NppStatus nppiThreshold_GT_32f_C1R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32f` nThreshold)
1 channel 32-bit floating point threshold.
- `NppStatus nppiThreshold_GT_32f_C1IR` (`Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32f` nThreshold)
1 channel 32-bit floating point in place threshold.
- `NppStatus nppiThreshold_GT_8u_C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` rThresholds[3])
3 channel 8-bit unsigned char threshold.
- `NppStatus nppiThreshold_GT_8u_C3IR` (`Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp8u` rThresholds[3])
3 channel 8-bit unsigned char in place threshold.
- `NppStatus nppiThreshold_GT_16u_C3R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16u` rThresholds[3])
3 channel 16-bit unsigned short threshold.
- `NppStatus nppiThreshold_GT_16u_C3IR` (`Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp16u` rThresholds[3])
3 channel 16-bit unsigned short in place threshold.
- `NppStatus nppiThreshold_GT_16s_C3R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16s` rThresholds[3])

3 channel 16-bit signed short threshold.

- `NppStatus nppiThreshold_GT_16s_C3IR` (`Npp16s *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp16s rThresholds[3]`)

3 channel 16-bit signed short in place threshold.

- `NppStatus nppiThreshold_GT_32f_C3R` (`const Npp32f *pSrc`, `int nSrcStep`, `Npp32f *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp32f rThresholds[3]`)

3 channel 32-bit floating point threshold.

- `NppStatus nppiThreshold_GT_32f_C3IR` (`Npp32f *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp32f rThresholds[3]`)

3 channel 32-bit floating point in place threshold.

- `NppStatus nppiThreshold_GT_8u_AC4R` (`const Npp8u *pSrc`, `int nSrcStep`, `Npp8u *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp8u rThresholds[3]`)

4 channel 8-bit unsigned char image threshold, not affecting Alpha.

- `NppStatus nppiThreshold_GT_8u_AC4IR` (`Npp8u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp8u rThresholds[3]`)

4 channel 8-bit unsigned char in place image threshold, not affecting Alpha.

- `NppStatus nppiThreshold_GT_16u_AC4R` (`const Npp16u *pSrc`, `int nSrcStep`, `Npp16u *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp16u rThresholds[3]`)

4 channel 16-bit unsigned short image threshold, not affecting Alpha.

- `NppStatus nppiThreshold_GT_16u_AC4IR` (`Npp16u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp16u rThresholds[3]`)

4 channel 16-bit unsigned short in place image threshold, not affecting Alpha.

- `NppStatus nppiThreshold_GT_16s_AC4R` (`const Npp16s *pSrc`, `int nSrcStep`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp16s rThresholds[3]`)

4 channel 16-bit signed short image threshold, not affecting Alpha.

- `NppStatus nppiThreshold_GT_16s_AC4IR` (`Npp16s *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp16s rThresholds[3]`)

4 channel 16-bit signed short in place image threshold, not affecting Alpha.

- `NppStatus nppiThreshold_GT_32f_AC4R` (`const Npp32f *pSrc`, `int nSrcStep`, `Npp32f *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp32f rThresholds[3]`)

4 channel 32-bit floating point image threshold, not affecting Alpha.

- `NppStatus nppiThreshold_GT_32f_AC4IR` (`Npp32f *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp32f rThresholds[3]`)

4 channel 32-bit floating point in place image threshold, not affecting Alpha.

- `NppStatus nppiThreshold_LT_8u_C1R` (`const Npp8u *pSrc`, `int nSrcStep`, `Npp8u *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp8u nThreshold`)

1 channel 8-bit unsigned char threshold.

- `NppStatus nppiThreshold_LT_8u_C1R` (`Npp8u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp8u nThreshold`)
1 channel 8-bit unsigned char in place threshold.
- `NppStatus nppiThreshold_LT_16u_C1R` (`const Npp16u *pSrc`, `int nSrcStep`, `Npp16u *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp16u nThreshold`)
1 channel 16-bit unsigned short threshold.
- `NppStatus nppiThreshold_LT_16u_C1IR` (`Npp16u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp16u nThreshold`)
1 channel 16-bit unsigned short in place threshold.
- `NppStatus nppiThreshold_LT_16s_C1R` (`const Npp16s *pSrc`, `int nSrcStep`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp16s nThreshold`)
1 channel 16-bit signed short threshold.
- `NppStatus nppiThreshold_LT_16s_C1IR` (`Npp16s *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp16s nThreshold`)
1 channel 16-bit signed short in place threshold.
- `NppStatus nppiThreshold_LT_32f_C1R` (`const Npp32f *pSrc`, `int nSrcStep`, `Npp32f *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp32f nThreshold`)
1 channel 32-bit floating point threshold.
- `NppStatus nppiThreshold_LT_32f_C1IR` (`Npp32f *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp32f nThreshold`)
1 channel 32-bit floating point in place threshold.
- `NppStatus nppiThreshold_LT_8u_C3R` (`const Npp8u *pSrc`, `int nSrcStep`, `Npp8u *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp8u rThresholds[3]`)
3 channel 8-bit unsigned char threshold.
- `NppStatus nppiThreshold_LT_8u_C3IR` (`Npp8u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp8u rThresholds[3]`)
3 channel 8-bit unsigned char in place threshold.
- `NppStatus nppiThreshold_LT_16u_C3R` (`const Npp16u *pSrc`, `int nSrcStep`, `Npp16u *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp16u rThresholds[3]`)
3 channel 16-bit unsigned short threshold.
- `NppStatus nppiThreshold_LT_16u_C3IR` (`Npp16u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp16u rThresholds[3]`)
3 channel 16-bit unsigned short in place threshold.
- `NppStatus nppiThreshold_LT_16s_C3R` (`const Npp16s *pSrc`, `int nSrcStep`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp16s rThresholds[3]`)
3 channel 16-bit signed short threshold.
- `NppStatus nppiThreshold_LT_16s_C3IR` (`Npp16s *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp16s rThresholds[3]`)
3 channel 16-bit signed short in place threshold.

- `NppStatus nppiThreshold_LT_32f_C3R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32f` rThresholds[3])
3 channel 32-bit floating point threshold.
- `NppStatus nppiThreshold_LT_32f_C3IR` (`Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32f` rThresholds[3])
3 channel 32-bit floating point in place threshold.
- `NppStatus nppiThreshold_LT_8u_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` rThresholds[3])
4 channel 8-bit unsigned char image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_LT_8u_AC4IR` (`Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp8u` rThresholds[3])
4 channel 8-bit unsigned char in place image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_LT_16u_AC4R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16u` rThresholds[3])
4 channel 16-bit unsigned short image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_LT_16u_AC4IR` (`Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp16u` rThresholds[3])
4 channel 16-bit unsigned short in place image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_LT_16s_AC4R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16s` rThresholds[3])
4 channel 16-bit signed short image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_LT_16s_AC4IR` (`Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp16s` rThresholds[3])
4 channel 16-bit signed short in place image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_LT_32f_AC4R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32f` rThresholds[3])
4 channel 32-bit floating point image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_LT_32f_AC4IR` (`Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32f` rThresholds[3])
4 channel 32-bit floating point in place image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_Val_8u_C1R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` nThreshold, const `Npp8u` nValue, `NppCmpOp` eComparisonOperation)
1 channel 8-bit unsigned char threshold.
- `NppStatus nppiThreshold_Val_8u_C1IR` (`Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp8u` nThreshold, const `Npp8u` nValue, `NppCmpOp` eComparisonOperation)
1 channel 8-bit unsigned char in place threshold.

- `NppStatus nppiThreshold_Val_16u_C1R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16u` nThreshold, const `Npp16u` nValue, `NppCmpOp` eComparisonOperation)

1 channel 16-bit unsigned short threshold.
- `NppStatus nppiThreshold_Val_16u_C1IR` (`Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp16u` nThreshold, const `Npp16u` nValue, `NppCmpOp` eComparisonOperation)

1 channel 16-bit unsigned short in place threshold.
- `NppStatus nppiThreshold_Val_16s_C1R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16s` nThreshold, const `Npp16s` nValue, `NppCmpOp` eComparisonOperation)

1 channel 16-bit signed short threshold.
- `NppStatus nppiThreshold_Val_16s_C1IR` (`Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp16s` nThreshold, const `Npp16s` nValue, `NppCmpOp` eComparisonOperation)

1 channel 16-bit signed short in place threshold.
- `NppStatus nppiThreshold_Val_32f_C1R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32f` nThreshold, const `Npp32f` nValue, `NppCmpOp` eComparisonOperation)

1 channel 32-bit floating point threshold.
- `NppStatus nppiThreshold_Val_32f_C1IR` (`Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32f` nThreshold, const `Npp32f` nValue, `NppCmpOp` eComparisonOperation)

1 channel 32-bit floating point in place threshold.
- `NppStatus nppiThreshold_Val_8u_C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` rThresholds[3], const `Npp8u` rValues[3], `NppCmpOp` eComparisonOperation)

3 channel 8-bit unsigned char threshold.
- `NppStatus nppiThreshold_Val_8u_C3IR` (`Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp8u` rThresholds[3], const `Npp8u` rValues[3], `NppCmpOp` eComparisonOperation)

3 channel 8-bit unsigned char in place threshold.
- `NppStatus nppiThreshold_Val_16u_C3R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16u` rThresholds[3], const `Npp16u` rValues[3], `NppCmpOp` eComparisonOperation)

3 channel 16-bit unsigned short threshold.
- `NppStatus nppiThreshold_Val_16u_C3IR` (`Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp16u` rThresholds[3], const `Npp16u` rValues[3], `NppCmpOp` eComparisonOperation)

3 channel 16-bit unsigned short in place threshold.
- `NppStatus nppiThreshold_Val_16s_C3R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16s` rThresholds[3], const `Npp16s` rValues[3], `NppCmpOp` eComparisonOperation)

3 channel 16-bit signed short threshold.

- `NppStatus nppiThreshold_Val_16s_C3IR` (`Npp16s *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp16s rThresholds[3]`, `const Npp16s rValues[3]`, `NppCmpOp eComparisonOperation`)
3 channel 16-bit signed short in place threshold.
- `NppStatus nppiThreshold_Val_32f_C3R` (`const Npp32f *pSrc`, `int nSrcStep`, `Npp32f *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp32f rThresholds[3]`, `const Npp32f rValues[3]`, `NppCmpOp eComparisonOperation`)
3 channel 32-bit floating point threshold.
- `NppStatus nppiThreshold_Val_32f_C3IR` (`Npp32f *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp32f rThresholds[3]`, `const Npp32f rValues[3]`, `NppCmpOp eComparisonOperation`)
3 channel 32-bit floating point in place threshold.
- `NppStatus nppiThreshold_Val_8u_AC4R` (`const Npp8u *pSrc`, `int nSrcStep`, `Npp8u *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp8u rThresholds[3]`, `const Npp8u rValues[3]`, `NppCmpOp eComparisonOperation`)
4 channel 8-bit unsigned char image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_Val_8u_AC4IR` (`Npp8u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp8u rThresholds[3]`, `const Npp8u rValues[3]`, `NppCmpOp eComparisonOperation`)
4 channel 8-bit unsigned char in place image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_Val_16u_AC4R` (`const Npp16u *pSrc`, `int nSrcStep`, `Npp16u *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp16u rThresholds[3]`, `const Npp16u rValues[3]`, `NppCmpOp eComparisonOperation`)
4 channel 16-bit unsigned short image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_Val_16u_AC4IR` (`Npp16u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp16u rThresholds[3]`, `const Npp16u rValues[3]`, `NppCmpOp eComparisonOperation`)
4 channel 16-bit unsigned short in place image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_Val_16s_AC4R` (`const Npp16s *pSrc`, `int nSrcStep`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp16s rThresholds[3]`, `const Npp16s rValues[3]`, `NppCmpOp eComparisonOperation`)
4 channel 16-bit signed short image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_Val_16s_AC4IR` (`Npp16s *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp16s rThresholds[3]`, `const Npp16s rValues[3]`, `NppCmpOp eComparisonOperation`)
4 channel 16-bit signed short in place image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_Val_32f_AC4R` (`const Npp32f *pSrc`, `int nSrcStep`, `Npp32f *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp32f rThresholds[3]`, `const Npp32f rValues[3]`, `NppCmpOp eComparisonOperation`)
4 channel 32-bit floating point image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_Val_32f_AC4IR` (`Npp32f *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp32f rThresholds[3]`, `const Npp32f rValues[3]`, `NppCmpOp eComparisonOperation`)
4 channel 32-bit floating point in place image threshold, not affecting Alpha.

- `NppStatus nppiThreshold_GTVal_8u_C1R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` nThreshold, const `Npp8u` nValue)
1 channel 8-bit unsigned char threshold.
- `NppStatus nppiThreshold_GTVal_8u_C1IR` (`Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp8u` nThreshold, const `Npp8u` nValue)
1 channel 8-bit unsigned char in place threshold.
- `NppStatus nppiThreshold_GTVal_16u_C1R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16u` nThreshold, const `Npp16u` nValue)
1 channel 16-bit unsigned short threshold.
- `NppStatus nppiThreshold_GTVal_16u_C1IR` (`Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp16u` nThreshold, const `Npp16u` nValue)
1 channel 16-bit unsigned short in place threshold.
- `NppStatus nppiThreshold_GTVal_16s_C1R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16s` nThreshold, const `Npp16s` nValue)
1 channel 16-bit signed short threshold.
- `NppStatus nppiThreshold_GTVal_16s_C1IR` (`Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp16s` nThreshold, const `Npp16s` nValue)
1 channel 16-bit signed short in place threshold.
- `NppStatus nppiThreshold_GTVal_32f_C1R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32f` nThreshold, const `Npp32f` nValue)
1 channel 32-bit floating point threshold.
- `NppStatus nppiThreshold_GTVal_32f_C1IR` (`Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32f` nThreshold, const `Npp32f` nValue)
1 channel 32-bit floating point in place threshold.
- `NppStatus nppiThreshold_GTVal_8u_C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` rThresholds[3], const `Npp8u` rValues[3])
3 channel 8-bit unsigned char threshold.
- `NppStatus nppiThreshold_GTVal_8u_C3IR` (`Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp8u` rThresholds[3], const `Npp8u` rValues[3])
3 channel 8-bit unsigned char in place threshold.
- `NppStatus nppiThreshold_GTVal_16u_C3R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16u` rThresholds[3], const `Npp16u` rValues[3])
3 channel 16-bit unsigned short threshold.
- `NppStatus nppiThreshold_GTVal_16u_C3IR` (`Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp16u` rThresholds[3], const `Npp16u` rValues[3])
3 channel 16-bit unsigned short in place threshold.
- `NppStatus nppiThreshold_GTVal_16s_C3R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16s` rThresholds[3], const `Npp16s` rValues[3])
3 channel 16-bit signed short threshold.

- `NppStatus nppiThreshold_GTVal_16s_C3IR` (`Npp16s *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp16s rThresholds[3]`, `const Npp16s rValues[3]`)
3 channel 16-bit signed short in place threshold.
- `NppStatus nppiThreshold_GTVal_32f_C3R` (`const Npp32f *pSrc`, `int nSrcStep`, `Npp32f *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp32f rThresholds[3]`, `const Npp32f rValues[3]`)
3 channel 32-bit floating point threshold.
- `NppStatus nppiThreshold_GTVal_32f_C3IR` (`Npp32f *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp32f rThresholds[3]`, `const Npp32f rValues[3]`)
3 channel 32-bit floating point in place threshold.
- `NppStatus nppiThreshold_GTVal_8u_AC4R` (`const Npp8u *pSrc`, `int nSrcStep`, `Npp8u *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp8u rThresholds[3]`, `const Npp8u rValues[3]`)
4 channel 8-bit unsigned char image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_GTVal_8u_AC4IR` (`Npp8u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp8u rThresholds[3]`, `const Npp8u rValues[3]`)
4 channel 8-bit unsigned char in place image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_GTVal_16u_AC4R` (`const Npp16u *pSrc`, `int nSrcStep`, `Npp16u *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp16u rThresholds[3]`, `const Npp16u rValues[3]`)
4 channel 16-bit unsigned short image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_GTVal_16u_AC4IR` (`Npp16u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp16u rThresholds[3]`, `const Npp16u rValues[3]`)
4 channel 16-bit unsigned short in place image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_GTVal_16s_AC4R` (`const Npp16s *pSrc`, `int nSrcStep`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp16s rThresholds[3]`, `const Npp16s rValues[3]`)
4 channel 16-bit signed short image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_GTVal_16s_AC4IR` (`Npp16s *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp16s rThresholds[3]`, `const Npp16s rValues[3]`)
4 channel 16-bit signed short in place image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_GTVal_32f_AC4R` (`const Npp32f *pSrc`, `int nSrcStep`, `Npp32f *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp32f rThresholds[3]`, `const Npp32f rValues[3]`)
4 channel 32-bit floating point image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_GTVal_32f_AC4IR` (`Npp32f *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp32f rThresholds[3]`, `const Npp32f rValues[3]`)
4 channel 32-bit floating point in place image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_LTVal_8u_C1R` (`const Npp8u *pSrc`, `int nSrcStep`, `Npp8u *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `const Npp8u nThreshold`, `const Npp8u nValue`)
1 channel 8-bit unsigned char threshold.
- `NppStatus nppiThreshold_LTVal_8u_C1IR` (`Npp8u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`, `const Npp8u nThreshold`, `const Npp8u nValue`)

1 channel 8-bit unsigned char in place threshold.

- `NppStatus nppiThreshold_LTVal_16u_C1R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16u` nThreshold, const `Npp16u` nValue)

1 channel 16-bit unsigned short threshold.

- `NppStatus nppiThreshold_LTVal_16u_C1IR` (`Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp16u` nThreshold, const `Npp16u` nValue)

1 channel 16-bit unsigned short in place threshold.

- `NppStatus nppiThreshold_LTVal_16s_C1R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16s` nThreshold, const `Npp16s` nValue)

1 channel 16-bit signed short threshold.

- `NppStatus nppiThreshold_LTVal_16s_C1IR` (`Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp16s` nThreshold, const `Npp16s` nValue)

1 channel 16-bit signed short in place threshold.

- `NppStatus nppiThreshold_LTVal_32f_C1R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32f` nThreshold, const `Npp32f` nValue)

1 channel 32-bit floating point threshold.

- `NppStatus nppiThreshold_LTVal_32f_C1IR` (`Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32f` nThreshold, const `Npp32f` nValue)

1 channel 32-bit floating point in place threshold.

- `NppStatus nppiThreshold_LTVal_8u_C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` rThresholds[3], const `Npp8u` rValues[3])

3 channel 8-bit unsigned char threshold.

- `NppStatus nppiThreshold_LTVal_8u_C3IR` (`Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp8u` rThresholds[3], const `Npp8u` rValues[3])

3 channel 8-bit unsigned char in place threshold.

- `NppStatus nppiThreshold_LTVal_16u_C3R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16u` rThresholds[3], const `Npp16u` rValues[3])

3 channel 16-bit unsigned short threshold.

- `NppStatus nppiThreshold_LTVal_16u_C3IR` (`Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp16u` rThresholds[3], const `Npp16u` rValues[3])

3 channel 16-bit unsigned short in place threshold.

- `NppStatus nppiThreshold_LTVal_16s_C3R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16s` rThresholds[3], const `Npp16s` rValues[3])

3 channel 16-bit signed short threshold.

- `NppStatus nppiThreshold_LTVal_16s_C3IR` (`Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp16s` rThresholds[3], const `Npp16s` rValues[3])

3 channel 16-bit signed short in place threshold.

- `NppStatus nppiThreshold_LTVal_32f_C3R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32f` rThresholds[3], const `Npp32f` rValues[3])
3 channel 32-bit floating point threshold.
- `NppStatus nppiThreshold_LTVal_32f_C3IR` (`Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32f` rThresholds[3], const `Npp32f` rValues[3])
3 channel 32-bit floating point in place threshold.
- `NppStatus nppiThreshold_LTVal_8u_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` rThresholds[3], const `Npp8u` rValues[3])
4 channel 8-bit unsigned char image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_LTVal_8u_AC4IR` (`Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp8u` rThresholds[3], const `Npp8u` rValues[3])
4 channel 8-bit unsigned char in place image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_LTVal_16u_AC4R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16u` rThresholds[3], const `Npp16u` rValues[3])
4 channel 16-bit unsigned short image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_LTVal_16u_AC4IR` (`Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp16u` rThresholds[3], const `Npp16u` rValues[3])
4 channel 16-bit unsigned short in place image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_LTVal_16s_AC4R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16s` rThresholds[3], const `Npp16s` rValues[3])
4 channel 16-bit signed short image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_LTVal_16s_AC4IR` (`Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp16s` rThresholds[3], const `Npp16s` rValues[3])
4 channel 16-bit signed short in place image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_LTVal_32f_AC4R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32f` rThresholds[3], const `Npp32f` rValues[3])
4 channel 32-bit floating point image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_LTVal_32f_AC4IR` (`Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32f` rThresholds[3], const `Npp32f` rValues[3])
4 channel 32-bit floating point in place image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_LTValGTVal_8u_C1R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` nThresholdLT, const `Npp8u` nValueLT, const `Npp8u` nThresholdGT, const `Npp8u` nValueGT)
1 channel 8-bit unsigned char threshold.
- `NppStatus nppiThreshold_LTValGTVal_8u_C1IR` (`Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp8u` nThresholdLT, const `Npp8u` nValueLT, const `Npp8u` nThresholdGT, const `Npp8u` nValueGT)
1 channel 8-bit unsigned char in place threshold.

- `NppStatus nppiThreshold_LTValGTVal_16u_C1R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16u` nThresholdLT, const `Npp16u` nValueLT, const `Npp16u` nThresholdGT, const `Npp16u` nValueGT)

1 channel 16-bit unsigned short threshold.
- `NppStatus nppiThreshold_LTValGTVal_16u_C1IR` (`Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp16u` nThresholdLT, const `Npp16u` nValueLT, const `Npp16u` nThresholdGT, const `Npp16u` nValueGT)

1 channel 16-bit unsigned short in place threshold.
- `NppStatus nppiThreshold_LTValGTVal_16s_C1R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16s` nThresholdLT, const `Npp16s` nValueLT, const `Npp16s` nThresholdGT, const `Npp16s` nValueGT)

1 channel 16-bit signed short threshold.
- `NppStatus nppiThreshold_LTValGTVal_16s_C1IR` (`Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp16s` nThresholdLT, const `Npp16s` nValueLT, const `Npp16s` nThresholdGT, const `Npp16s` nValueGT)

1 channel 16-bit signed short in place threshold.
- `NppStatus nppiThreshold_LTValGTVal_32f_C1R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32f` nThresholdLT, const `Npp32f` nValueLT, const `Npp32f` nThresholdGT, const `Npp32f` nValueGT)

1 channel 32-bit floating point threshold.
- `NppStatus nppiThreshold_LTValGTVal_32f_C1IR` (`Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32f` nThresholdLT, const `Npp32f` nValueLT, const `Npp32f` nThresholdGT, const `Npp32f` nValueGT)

1 channel 32-bit floating point in place threshold.
- `NppStatus nppiThreshold_LTValGTVal_8u_C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` rThresholdsLT[3], const `Npp8u` rValuesLT[3], const `Npp8u` rThresholdsGT[3], const `Npp8u` rValuesGT[3])

3 channel 8-bit unsigned char threshold.
- `NppStatus nppiThreshold_LTValGTVal_8u_C3IR` (`Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp8u` rThresholdsLT[3], const `Npp8u` rValuesLT[3], const `Npp8u` rThresholdsGT[3], const `Npp8u` rValuesGT[3])

3 channel 8-bit unsigned char in place threshold.
- `NppStatus nppiThreshold_LTValGTVal_16u_C3R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16u` rThresholdsLT[3], const `Npp16u` rValuesLT[3], const `Npp16u` rThresholdsGT[3], const `Npp16u` rValuesGT[3])

3 channel 16-bit unsigned short threshold.
- `NppStatus nppiThreshold_LTValGTVal_16u_C3IR` (`Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp16u` rThresholdsLT[3], const `Npp16u` rValuesLT[3], const `Npp16u` rThresholdsGT[3], const `Npp16u` rValuesGT[3])

3 channel 16-bit unsigned short in place threshold.

- `NppStatus nppiThreshold_LTValGTVal_16s_C3R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16s` rThresholdsLT[3], const `Npp16s` rValuesLT[3], const `Npp16s` rThresholdsGT[3], const `Npp16s` rValuesGT[3])
3 channel 16-bit signed short threshold.
- `NppStatus nppiThreshold_LTValGTVal_16s_C3IR` (`Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp16s` rThresholdsLT[3], const `Npp16s` rValuesLT[3], const `Npp16s` rThresholdsGT[3], const `Npp16s` rValuesGT[3])
3 channel 16-bit signed short in place threshold.
- `NppStatus nppiThreshold_LTValGTVal_32f_C3R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32f` rThresholdsLT[3], const `Npp32f` rValuesLT[3], const `Npp32f` rThresholdsGT[3], const `Npp32f` rValuesGT[3])
3 channel 32-bit floating point threshold.
- `NppStatus nppiThreshold_LTValGTVal_32f_C3IR` (`Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp32f` rThresholdsLT[3], const `Npp32f` rValuesLT[3], const `Npp32f` rThresholdsGT[3], const `Npp32f` rValuesGT[3])
3 channel 32-bit floating point in place threshold.
- `NppStatus nppiThreshold_LTValGTVal_8u_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` rThresholdsLT[3], const `Npp8u` rValuesLT[3], const `Npp8u` rThresholdsGT[3], const `Npp8u` rValuesGT[3])
4 channel 8-bit unsigned char image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_LTValGTVal_8u_AC4IR` (`Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp8u` rThresholdsLT[3], const `Npp8u` rValuesLT[3], const `Npp8u` rThresholdsGT[3], const `Npp8u` rValuesGT[3])
4 channel 8-bit unsigned char in place image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_LTValGTVal_16u_AC4R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16u` rThresholdsLT[3], const `Npp16u` rValuesLT[3], const `Npp16u` rThresholdsGT[3], const `Npp16u` rValuesGT[3])
4 channel 16-bit unsigned short image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_LTValGTVal_16u_AC4IR` (`Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp16u` rThresholdsLT[3], const `Npp16u` rValuesLT[3], const `Npp16u` rThresholdsGT[3], const `Npp16u` rValuesGT[3])
4 channel 16-bit unsigned short in place image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_LTValGTVal_16s_AC4R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp16s` rThresholdsLT[3], const `Npp16s` rValuesLT[3], const `Npp16s` rThresholdsGT[3], const `Npp16s` rValuesGT[3])
4 channel 16-bit signed short image threshold, not affecting Alpha.
- `NppStatus nppiThreshold_LTValGTVal_16s_AC4IR` (`Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, const `Npp16s` rThresholdsLT[3], const `Npp16s` rValuesLT[3], const `Npp16s` rThresholdsGT[3], const `Npp16s` rValuesGT[3])
4 channel 16-bit signed short in place image threshold, not affecting Alpha.

- `NppStatus nppiThreshold_LTValGTVal_32f_AC4R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp32f rThresholdsLT[3]`, const `Npp32f rValuesLT[3]`, const `Npp32f rThresholdsGT[3]`, const `Npp32f rValuesGT[3]`)

4 channel 32-bit floating point image threshold, not affecting Alpha.

- `NppStatus nppiThreshold_LTValGTVal_32f_AC4IR` (`Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, const `Npp32f rThresholdsLT[3]`, const `Npp32f rValuesLT[3]`, const `Npp32f rThresholdsGT[3]`, const `Npp32f rValuesGT[3]`)

4 channel 32-bit floating point in place image threshold, not affecting Alpha.

7.130.1 Detailed Description

Threshold image pixels.

7.130.2 Function Documentation

7.130.2.1 `NppStatus nppiThreshold_16s_AC4IR` (`Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, const `Npp16s rThresholds[3]`, `NppCmpOp eComparisonOperation`)

4 channel 16-bit signed short in place image threshold, not affecting Alpha.

If for a comparison operations OP the predicate (sourcePixel.channel OP nThreshold) is true, the channel value is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

rThresholds The threshold values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: `NPP_CMP_LESS` and `NPP_CMP_GREATER`.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_SUPPORTED_MODE_ERROR` if an invalid comparison operation type is specified.

7.130.2.2 `NppStatus nppiThreshold_16s_AC4R` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, const `Npp16s rThresholds[3]`, `NppCmpOp eComparisonOperation`)

4 channel 16-bit signed short image threshold, not affecting Alpha.

If for a comparison operations OP the predicate (sourcePixel.channel OP nThreshold) is true, the channel value is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.3 NppStatus nppiThreshold_16s_C1IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16s nThreshold, NppCmpOp eComparisonOperation)

1 channel 16-bit signed short in place threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.4 NppStatus nppiThreshold_16s_C1R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp16s nThreshold, NppCmpOp eComparisonOperation)

1 channel 16-bit signed short threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI [Region-of-Interest \(ROI\)](#).

nThreshold The threshold value.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.5 NppStatus nppiThreshold_16s_C3IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16s rThresholds[3], NppCmpOp eComparisonOperation)

3 channel 16-bit signed short in place threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

rThresholds The threshold values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.6 NppStatus nppiThreshold_16s_C3R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp16s rThresholds[3], NppCmpOp eComparisonOperation)

3 channel 16-bit signed short threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

rThresholds The threshold values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_SUPPORTED_MODE_ERROR` if an invalid comparison operation type is specified.

7.130.2.7 NppStatus nppiThreshold_16u_AC4IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16u rThresholds[3], NppCmpOp eComparisonOperation)

4 channel 16-bit unsigned short in place image threshold, not affecting Alpha.

If for a comparison operations OP the predicate (`sourcePixel.channel OP nThreshold`) is true, the channel value is set to `nThreshold`, otherwise it is set to `sourcePixel`.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

rThresholds The threshold values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: `NPP_CMP_LESS` and `NPP_CMP_GREATER`.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_SUPPORTED_MODE_ERROR` if an invalid comparison operation type is specified.

7.130.2.8 NppStatus nppiThreshold_16u_AC4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp16u rThresholds[3], NppCmpOp eComparisonOperation)

4 channel 16-bit unsigned short image threshold, not affecting Alpha.

If for a comparison operations OP the predicate (`sourcePixel.channel OP nThreshold`) is true, the channel value is set to `nThreshold`, otherwise it is set to `sourcePixel`.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

rThresholds The threshold values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: `NPP_CMP_LESS` and `NPP_CMP_GREATER`.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_SUPPORTED_MODE_ERROR` if an invalid comparison operation type is specified.

7.130.2.9 **NppStatus nppiThreshold_16u_C1IR** (**Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16u nThreshold, NppCmpOp eComparisonOperation**)

1 channel 16-bit unsigned short in place threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.10 **NppStatus nppiThreshold_16u_C1R** (**const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp16u nThreshold, NppCmpOp eComparisonOperation**)

1 channel 16-bit unsigned short threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.11 **NppStatus nppiThreshold_16u_C3IR** (**Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16u rThresholds[3], NppCmpOp eComparisonOperation**)

3 channel 16-bit unsigned short in place threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

rThresholds The threshold values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.12 NppStatus nppiThreshold_16u_C3R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp16u rThresholds[3], NppCmpOp eComparisonOperation)

3 channel 16-bit unsigned short threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

rThresholds The threshold values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.13 NppStatus nppiThreshold_32f_AC4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f rThresholds[3], NppCmpOp eComparisonOperation)

4 channel 32-bit floating point in place image threshold, not affecting Alpha.

If for a comparison operations OP the predicate (sourcePixel.channel OP nThreshold) is true, the channel value is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

rThresholds The threshold values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.14 NppStatus nppiThreshold_32f_AC4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f rThresholds[3], NppCmpOp eComparisonOperation)

4 channel 32-bit floating point image threshold, not affecting Alpha.

If for a comparison operations OP the predicate (sourcePixel.channel OP nThreshold) is true, the channel value is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

rThresholds The threshold values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.15 NppStatus nppiThreshold_32f_C11R (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f nThreshold, NppCmpOp eComparisonOperation)

1 channel 32-bit floating point in place threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

nThreshold The threshold value.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_SUPPORTED_MODE_ERROR` if an invalid comparison operation type is specified.

7.130.2.16 `NppStatus nppiThreshold_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f nThreshold, NppCmpOp eComparisonOperation)`

1 channel 32-bit floating point threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

nThreshold The threshold value.

eComparisonOperation The type of comparison operation to be used. The only valid values are: `NPP_CMP_LESS` and `NPP_CMP_GREATER`.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_SUPPORTED_MODE_ERROR` if an invalid comparison operation type is specified.

7.130.2.17 `NppStatus nppiThreshold_32f_C3IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f rThresholds[3], NppCmpOp eComparisonOperation)`

3 channel 32-bit floating point in place threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

rThresholds The threshold values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: `NPP_CMP_LESS` and `NPP_CMP_GREATER`.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or `NPP_NOT_SUPPORTED_MODE_ERROR` if an invalid comparison operation type is specified.

7.130.2.18 `NppStatus nppiThreshold_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f rThresholds[3], NppCmpOp eComparisonOperation)`

3 channel 32-bit floating point threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

rThresholds The threshold values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.19 `NppStatus nppiThreshold_8u_AC4IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp8u rThresholds[3], NppCmpOp eComparisonOperation)`

4 channel 8-bit unsigned char in place image threshold, not affecting Alpha.

If for a comparison operations OP the predicate (sourcePixel.channel OP nThreshold) is true, the channel value is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

rThresholds The threshold values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.20 `NppStatus nppiThreshold_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u rThresholds[3], NppCmpOp eComparisonOperation)`

4 channel 8-bit unsigned char image threshold, not affecting Alpha.

If for a comparison operations OP the predicate (sourcePixel.channel OP nThreshold) is true, the channel value is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

rThresholds The threshold values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.21 `NppStatus nppiThreshold_8u_C1IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp8u nThreshold, NppCmpOp eComparisonOperation)`

1 channel 8-bit unsigned char in place threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

nThreshold The threshold value.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.22 NppStatus nppiThreshold_8u_C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u nThreshold, NppCmpOp eComparisonOperation)

1 channel 8-bit unsigned char threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

nThreshold The threshold value.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.23 NppStatus nppiThreshold_8u_C3IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp8u rThresholds[3], NppCmpOp eComparisonOperation)

3 channel 8-bit unsigned char in place threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

rThresholds The threshold values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.24 NppStatus nppiThreshold_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u rThresholds[3], NppCmpOp eComparisonOperation)

3 channel 8-bit unsigned char threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.25 NppStatus nppiThreshold_GT_16s_AC4IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16s rThresholds[3])

4 channel 16-bit signed short in place image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set value is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.26 NppStatus nppiThreshold_GT_16s_AC4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp16s rThresholds[3])

4 channel 16-bit signed short image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set value is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
rThresholds The threshold values, one per color channel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.27 **NppStatus nppiThreshold_GT_16s_C1IR** (Npp16s * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, const Npp16s *nThreshold*)

1 channel 16-bit signed short in place threshold.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nThreshold The threshold value.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.28 **NppStatus nppiThreshold_GT_16s_C1R** (const Npp16s * *pSrc*, int *nSrcStep*, Npp16s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, const Npp16s *nThreshold*)

1 channel 16-bit signed short threshold.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nThreshold The threshold value.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.29 NppStatus nppiThreshold_GT_16s_C3IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16s rThresholds[3])

3 channel 16-bit signed short in place threshold.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.30 NppStatus nppiThreshold_GT_16s_C3R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp16s rThresholds[3])

3 channel 16-bit signed short threshold.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.31 NppStatus nppiThreshold_GT_16u_AC4IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16u rThresholds[3])

4 channel 16-bit unsigned short in place image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set value is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.32 NppStatus nppiThreshold_GT_16u_AC4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp16u rThresholds[3])

4 channel 16-bit unsigned short image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set value is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.33 NppStatus nppiThreshold_GT_16u_C1IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16u nThreshold)

1 channel 16-bit unsigned short in place threshold.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.34 NppStatus nppiThreshold_GT_16u_C1R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp16u nThreshold)

1 channel 16-bit unsigned short threshold.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nThreshold* The threshold value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.35 NppStatus nppiThreshold_GT_16u_C3IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16u rThresholds[3])

3 channel 16-bit unsigned short in place threshold.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- rThresholds* The threshold values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.36 NppStatus nppiThreshold_GT_16u_C3R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp16u rThresholds[3])

3 channel 16-bit unsigned short threshold.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.

pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
rThresholds The threshold values, one per color channel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.37 **NppStatus nppiThreshold_GT_32f_AC4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f rThresholds[3])**

4 channel 32-bit floating point in place image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set value is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
rThresholds The threshold values, one per color channel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.38 **NppStatus nppiThreshold_GT_32f_AC4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f rThresholds[3])**

4 channel 32-bit floating point image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set value is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
rThresholds The threshold values, one per color channel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.39 NppStatus nppiThreshold_GT_32f_C1IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f nThreshold)

1 channel 32-bit floating point in place threshold.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.40 NppStatus nppiThreshold_GT_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f nThreshold)

1 channel 32-bit floating point threshold.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.41 NppStatus nppiThreshold_GT_32f_C3IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f rThresholds[3])

3 channel 32-bit floating point in place threshold.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.42 NppStatus nppiThreshold_GT_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f rThresholds[3])

3 channel 32-bit floating point threshold.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.43 NppStatus nppiThreshold_GT_8u_AC4IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp8u rThresholds[3])

4 channel 8-bit unsigned char in place image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set value is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.44 NppStatus nppiThreshold_GT_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u rThresholds[3])

4 channel 8-bit unsigned char image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set value is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.45 NppStatus nppiThreshold_GT_8u_C1IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp8u nThreshold)

1 channel 8-bit unsigned char in place threshold.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.46 NppStatus nppiThreshold_GT_8u_C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u nThreshold)

1 channel 8-bit unsigned char threshold.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.47 NppStatus nppiThreshold_GT_8u_C3IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp8u rThresholds[3])

3 channel 8-bit unsigned char in place threshold.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.48 NppStatus nppiThreshold_GT_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u rThresholds[3])

3 channel 8-bit unsigned char threshold.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.49 `NppStatus nppiThreshold_GTVal_16s_AC4IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16s rThresholds[3], const Npp16s rValues[3])`

4 channel 16-bit signed short in place image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is greater than rThreshold is true, the pixel is set value is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.50 `NppStatus nppiThreshold_GTVal_16s_AC4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp16s rThresholds[3], const Npp16s rValues[3])`

4 channel 16-bit signed short image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is greater than rThreshold is true, the pixel is set value is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.51 `NppStatus nppiThreshold_GTVal_16s_C1IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16s nThreshold, const Npp16s nValue)`

1 channel 16-bit signed short in place threshold.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nThreshold The threshold value.
nValue The threshold replacement value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.52 **NppStatus nppiThreshold_GTVal_16s_C1R** (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp16s nThreshold, const Npp16s nValue)

1 channel 16-bit signed short threshold.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nThreshold The threshold value.
nValue The threshold replacement value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.53 **NppStatus nppiThreshold_GTVal_16s_C3IR** (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16s rThresholds[3], const Npp16s rValues[3])

3 channel 16-bit signed short in place threshold.

If for a comparison operations sourcePixel is greater than rThreshold is true, the pixel is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
rThresholds The threshold values, one per color channel.
rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.54 `NppStatus nppiThreshold_GTVAl_16s_C3R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp16s rThresholds[3], const Npp16s rValues[3])`

3 channel 16-bit signed short threshold.

If for a comparison operations sourcePixel is greater than rThreshold is true, the pixel is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.55 `NppStatus nppiThreshold_GTVAl_16u_AC4IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16u rThresholds[3], const Npp16u rValues[3])`

4 channel 16-bit unsigned short in place image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is greater than rThreshold is true, the pixel is set value is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.56 `NppStatus nppiThreshold_GTVAl_16u_AC4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp16u rThresholds[3], const Npp16u rValues[3])`

4 channel 16-bit unsigned short image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is greater than rThreshold is true, the pixel is set value is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
rThresholds The threshold values, one per color channel.
rValues The threshold replacement values, one per color channel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.57 **NppStatus nppiThreshold_GTVVal_16u_C1IR** (Npp16u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, const Npp16u *nThreshold*, const Npp16u *nValue*)

1 channel 16-bit unsigned short in place threshold.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nThreshold The threshold value.
nValue The threshold replacement value.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.58 **NppStatus nppiThreshold_GTVVal_16u_C1R** (const Npp16u * *pSrc*, int *nSrcStep*, Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, const Npp16u *nThreshold*, const Npp16u *nValue*)

1 channel 16-bit unsigned short threshold.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

nValue The threshold replacement value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.59 `NppStatus nppiThreshold_GTVal_16u_C3IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16u rThresholds[3], const Npp16u rValues[3])`

3 channel 16-bit unsigned short in place threshold.

If for a comparison operations sourcePixel is greater than rThreshold is true, the pixel is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.60 `NppStatus nppiThreshold_GTVal_16u_C3R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp16u rThresholds[3], const Npp16u rValues[3])`

3 channel 16-bit unsigned short threshold.

If for a comparison operations sourcePixel is greater than rThreshold is true, the pixel is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.61 NppStatus nppiThreshold_GTVAl_32f_AC4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f rThresholds[3], const Npp32f rValues[3])

4 channel 32-bit floating point in place image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is greater than rThreshold is true, the pixel is set value is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.62 NppStatus nppiThreshold_GTVAl_32f_AC4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f rThresholds[3], const Npp32f rValues[3])

4 channel 32-bit floating point image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is greater than rThreshold is true, the pixel is set value is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.63 NppStatus nppiThreshold_GTVAl_32f_C1IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f nThreshold, const Npp32f nValue)

1 channel 32-bit floating point in place threshold.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nThreshold The threshold value.
nValue The threshold replacement values.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.64 NppStatus nppiThreshold_GTVAl_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f nThreshold, const Npp32f nValue)

1 channel 32-bit floating point threshold.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nThreshold The threshold value.
nValue The threshold replacement value.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.65 NppStatus nppiThreshold_GTVAl_32f_C3IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f rThresholds[3], const Npp32f rValues[3])

3 channel 32-bit floating point in place threshold.

If for a comparison operations sourcePixel is greater than rThreshold is true, the pixel is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
rThresholds The threshold values, one per color channel.
rValues The threshold replacement values, one per color channel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.66 `NppStatus nppiThreshold_GTVal_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f rThresholds[3], const Npp32f rValues[3])`

3 channel 32-bit floating point threshold.

If for a comparison operations sourcePixel is greater than rThreshold is true, the pixel is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.67 `NppStatus nppiThreshold_GTVal_8u_AC4IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp8u rThresholds[3], const Npp8u rValues[3])`

4 channel 8-bit unsigned char in place image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is greater than rThreshold is true, the pixel is set value is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.68 `NppStatus nppiThreshold_GTVal_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u rThresholds[3], const Npp8u rValues[3])`

4 channel 8-bit unsigned char image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is greater than rThreshold is true, the pixel is set value is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
rThresholds The threshold values, one per color channel.
rValues The threshold replacement values, one per color channel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.69 NppStatus nppiThreshold_GTVVal_8u_C1IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp8u nThreshold, const Npp8u nValue)

1 channel 8-bit unsigned char in place threshold.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nThreshold The threshold value.
nValue The threshold replacement value.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.70 NppStatus nppiThreshold_GTVVal_8u_C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u nThreshold, const Npp8u nValue)

1 channel 8-bit unsigned char threshold.

If for a comparison operations sourcePixel is greater than nThreshold is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

nValue The threshold replacement value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.71 `NppStatus nppiThreshold_GTVal_8u_C3IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp8u rThresholds[3], const Npp8u rValues[3])`

3 channel 8-bit unsigned char in place threshold.

If for a comparison operations sourcePixel is greater than rThreshold is true, the pixel is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.72 `NppStatus nppiThreshold_GTVal_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u rThresholds[3], const Npp8u rValues[3])`

3 channel 8-bit unsigned char threshold.

If for a comparison operations sourcePixel is greater than rThreshold is true, the pixel is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.73 NppStatus nppiThreshold_LT_16s_AC4IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16s rThresholds[3])

4 channel 16-bit signed short in place image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set value is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.74 NppStatus nppiThreshold_LT_16s_AC4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp16s rThresholds[3])

4 channel 16-bit signed short image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set value is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.75 NppStatus nppiThreshold_LT_16s_C1IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16s nThreshold)

1 channel 16-bit signed short in place threshold.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.76 NppStatus nppiThreshold_LT_16s_C1R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp16s nThreshold)

1 channel 16-bit signed short threshold.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.77 NppStatus nppiThreshold_LT_16s_C3IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16s rThresholds[3])

3 channel 16-bit signed short in place threshold.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.78 NppStatus nppiThreshold_LT_16s_C3R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp16s rThresholds[3])

3 channel 16-bit signed short threshold.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.79 NppStatus nppiThreshold_LT_16u_AC4IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16u rThresholds[3])

4 channel 16-bit unsigned short in place image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set value is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.80 NppStatus nppiThreshold_LT_16u_AC4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp16u rThresholds[3])

4 channel 16-bit unsigned short image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set value is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
rThresholds The threshold values, one per color channel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.81 NppStatus nppiThreshold_LT_16u_C1IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16u nThreshold)

1 channel 16-bit unsigned short in place threshold.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nThreshold The threshold value.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.82 NppStatus nppiThreshold_LT_16u_C1R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp16u nThreshold)

1 channel 16-bit unsigned short threshold.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nThreshold The threshold value.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.83 `NppStatus nppiThreshold_LT_16u_C3IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16u rThresholds[3])`

3 channel 16-bit unsigned short in place threshold.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.84 `NppStatus nppiThreshold_LT_16u_C3R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp16u rThresholds[3])`

3 channel 16-bit unsigned short threshold.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.85 `NppStatus nppiThreshold_LT_32f_AC4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f rThresholds[3])`

4 channel 32-bit floating point in place image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set value is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.86 NppStatus nppiThreshold_LT_32f_AC4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f rThresholds[3])

4 channel 32-bit floating point image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set value is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.87 NppStatus nppiThreshold_LT_32f_C1IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f nThreshold)

1 channel 32-bit floating point in place threshold.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.88 `NppStatus nppiThreshold_LT_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f nThreshold)`

1 channel 32-bit floating point threshold.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nThreshold* The threshold value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.89 `NppStatus nppiThreshold_LT_32f_C3IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f rThresholds[3])`

3 channel 32-bit floating point in place threshold.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- rThresholds* The threshold values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.90 `NppStatus nppiThreshold_LT_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f rThresholds[3])`

3 channel 32-bit floating point threshold.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.

pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
rThresholds The threshold values, one per color channel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.91 **NppStatus nppiThreshold_LT_8u_AC4IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp8u rThresholds[3])**

4 channel 8-bit unsigned char in place image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set value is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
rThresholds The threshold values, one per color channel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.92 **NppStatus nppiThreshold_LT_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u rThresholds[3])**

4 channel 8-bit unsigned char image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set value is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
rThresholds The threshold values, one per color channel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.93 NppStatus nppiThreshold_LT_8u_C1IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp8u nThreshold)

1 channel 8-bit unsigned char in place threshold.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.94 NppStatus nppiThreshold_LT_8u_C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u nThreshold)

1 channel 8-bit unsigned char threshold.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.95 NppStatus nppiThreshold_LT_8u_C3IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp8u rThresholds[3])

3 channel 8-bit unsigned char in place threshold.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.96 `NppStatus nppiThreshold_LT_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u rThresholds[3])`

3 channel 8-bit unsigned char threshold.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.97 `NppStatus nppiThreshold_LTVAl_16s_AC4IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16s rThresholds[3], const Npp16s rValues[3])`

4 channel 16-bit signed short in place image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is less than rThreshold is true, the pixel is set value is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.98 `NppStatus nppiThreshold_LTVal_16s_AC4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp16s rThresholds[3], const Npp16s rValues[3])`

4 channel 16-bit signed short image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is less than rThreshold is true, the pixel is set value is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.99 `NppStatus nppiThreshold_LTVal_16s_C1IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16s nThreshold, const Npp16s nValue)`

1 channel 16-bit signed short in place threshold.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

nValue The threshold replacement value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.100 `NppStatus nppiThreshold_LTVal_16s_C1R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp16s nThreshold, const Npp16s nValue)`

1 channel 16-bit signed short threshold.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nThreshold The threshold value.
nValue The threshold replacement value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.101 **NppStatus nppiThreshold_LTVal_16s_C3IR** (Npp16s * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, const Npp16s *rThresholds*[3], const Npp16s *rValues*[3])

3 channel 16-bit signed short in place threshold.

If for a comparison operations sourcePixel is less than rThreshold is true, the pixel is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
rThresholds The threshold values, one per color channel.
rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.102 **NppStatus nppiThreshold_LTVal_16s_C3R** (const Npp16s * *pSrc*, int *nSrcStep*, Npp16s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, const Npp16s *rThresholds*[3], const Npp16s *rValues*[3])

3 channel 16-bit signed short threshold.

If for a comparison operations sourcePixel is less than rThreshold is true, the pixel is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.103 NppStatus nppiThreshold_LTVal_16u_AC4IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16u rThresholds[3], const Npp16u rValues[3])

4 channel 16-bit unsigned short in place image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is less than rThreshold is true, the pixel is set value is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.104 NppStatus nppiThreshold_LTVal_16u_AC4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp16u rThresholds[3], const Npp16u rValues[3])

4 channel 16-bit unsigned short image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is less than rThreshold is true, the pixel is set value is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.105 `NppStatus nppiThreshold_LTVal_16u_C1IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16u nThreshold, const Npp16u nValue)`

1 channel 16-bit unsigned short in place threshold.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

nThreshold The threshold value.

nValue The threshold replacement value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.106 `NppStatus nppiThreshold_LTVal_16u_C1R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp16u nThreshold, const Npp16u nValue)`

1 channel 16-bit unsigned short threshold.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

nThreshold The threshold value.

nValue The threshold replacement value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.107 `NppStatus nppiThreshold_LTVal_16u_C3IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16u rThresholds[3], const Npp16u rValues[3])`

3 channel 16-bit unsigned short in place threshold.

If for a comparison operations sourcePixel is less than rThreshold is true, the pixel is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
rThresholds The threshold values, one per color channel.
rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.108 `NppStatus nppiThreshold_LTVAl_16u_C3R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp16u rThresholds[3], const Npp16u rValues[3])`

3 channel 16-bit unsigned short threshold.

If for a comparison operations sourcePixel is less than rThreshold is true, the pixel is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
rThresholds The threshold values, one per color channel.
rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.109 `NppStatus nppiThreshold_LTVAl_32f_AC4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f rThresholds[3], const Npp32f rValues[3])`

4 channel 32-bit floating point in place image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is less than rThreshold is true, the pixel is set value is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
rThresholds The threshold values, one per color channel.
rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.110 `NppStatus nppiThreshold_LTVal_32f_AC4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f rThresholds[3], const Npp32f rValues[3])`

4 channel 32-bit floating point image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is less than rThreshold is true, the pixel is set value is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.111 `NppStatus nppiThreshold_LTVal_32f_C1IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f nThreshold, const Npp32f nValue)`

1 channel 32-bit floating point in place threshold.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

nValue The threshold replacement value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.112 `NppStatus nppiThreshold_LTVal_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f nThreshold, const Npp32f nValue)`

1 channel 32-bit floating point threshold.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nThreshold The threshold value.
nValue The threshold replacement value.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.113 `NppStatus nppiThreshold_LTVAl_32f_C3IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f rThresholds[3], const Npp32f rValues[3])`

3 channel 32-bit floating point in place threshold.

If for a comparison operations sourcePixel is less than rThreshold is true, the pixel is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
rThresholds The threshold values, one per color channel.
rValues The threshold replacement values, one per color channel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.114 `NppStatus nppiThreshold_LTVAl_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f rThresholds[3], const Npp32f rValues[3])`

3 channel 32-bit floating point threshold.

If for a comparison operations sourcePixel is less than rThreshold is true, the pixel is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.115 `NppStatus nppiThreshold_LTVal_8u_AC4IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp8u rThresholds[3], const Npp8u rValues[3])`

4 channel 8-bit unsigned char in place image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is less than rThreshold is true, the pixel is set value is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.116 `NppStatus nppiThreshold_LTVal_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u rThresholds[3], const Npp8u rValues[3])`

4 channel 8-bit unsigned char image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is less than rThreshold is true, the pixel is set value is set to rValue, otherwise it is set to sourcePixel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.117 `NppStatus nppiThreshold_LTVal_8u_C1IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp8u nThreshold, const Npp8u nValue)`

1 channel 8-bit unsigned char in place threshold.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

nValue The threshold replacement value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.118 `NppStatus nppiThreshold_LTVal_8u_C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u nThreshold, const Npp8u nValue)`

1 channel 8-bit unsigned char threshold.

If for a comparison operations sourcePixel is less than nThreshold is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

nValue The threshold replacement value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.119 `NppStatus nppiThreshold_LTVal_8u_C3IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp8u rThresholds[3], const Npp8u rValues[3])`

3 channel 8-bit unsigned char in place threshold.

If for a comparison operations sourcePixel is less than rThreshold is true, the pixel is set to rValue, otherwise it is set to sourcePixel.

Parameters:

- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- rThresholds* The threshold values, one per color channel.
- rValues* The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.120 `NppStatus nppiThreshold_LTVal_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u rThresholds[3], const Npp8u rValues[3])`

3 channel 8-bit unsigned char threshold.

If for a comparison operations sourcePixel is less than rThreshold is true, the pixel is set to rValue, otherwise it is set to sourcePixel.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- rThresholds* The threshold values, one per color channel.
- rValues* The threshold replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.121 `NppStatus nppiThreshold_LTValGTVal_16s_AC4IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16s rThresholdsLT[3], const Npp16s rValuesLT[3], const Npp16s rThresholdsGT[3], const Npp16s rValuesGT[3])`

4 channel 16-bit signed short in place image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is less than rThresholdLT is true, the pixel is set value is set to rValueLT, else if sourcePixel is greater than rThresholdGT the pixel is set to rValueGT, otherwise it is set to sourcePixel.

Parameters:

- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- rThresholdsLT* The thresholdLT values, one per color channel.

rValuesLT The thresholdLT replacement values, one per color channel.

rThresholdsGT The thresholdGT values, one per channel.

rValuesGT The thresholdGT replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.122 `NppStatus nppiThreshold_LTValGTVal_16s_AC4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp16s rThresholdsLT[3], const Npp16s rValuesLT[3], const Npp16s rThresholdsGT[3], const Npp16s rValuesGT[3])`

4 channel 16-bit signed short image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is less than rThresholdLT is true, the pixel is set value is set to rValueLT, else if sourcePixel is greater than rThresholdGT the pixel is set to rValueGT, otherwise it is set to sourcePixel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

rThresholdsLT The thresholdLT values, one per color channel.

rValuesLT The thresholdLT replacement values, one per color channel.

rThresholdsGT The thresholdGT values, one per channel.

rValuesGT The thresholdGT replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.123 `NppStatus nppiThreshold_LTValGTVal_16s_C1IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16s nThresholdLT, const Npp16s nValueLT, const Npp16s nThresholdGT, const Npp16s nValueGT)`

1 channel 16-bit signed short in place threshold.

If for a comparison operations sourcePixel is less than nThresholdLT is true, the pixel is set to nValueLT, else if sourcePixel is greater than nThresholdGT the pixel is set to nValueGT, otherwise it is set to sourcePixel.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

nThresholdLT The thresholdLT value.
nValueLT The thresholdLT replacement value.
nThresholdGT The thresholdGT value.
nValueGT The thresholdGT replacement value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.124 `NppStatus nppiThreshold_LTValGTVal_16s_C1R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp16s nThresholdLT, const Npp16s nValueLT, const Npp16s nThresholdGT, const Npp16s nValueGT)`

1 channel 16-bit signed short threshold.

If for a comparison operations sourcePixel is less than nThresholdLT is true, the pixel is set to nValueLT, else if sourcePixel is greater than nThresholdGT the pixel is set to nValueGT, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nThresholdLT The thresholdLT value.
nValueLT The thresholdLT replacement value.
nThresholdGT The thresholdGT value.
nValueGT The thresholdGT replacement value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.125 `NppStatus nppiThreshold_LTValGTVal_16s_C3IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16s rThresholdsLT[3], const Npp16s rValuesLT[3], const Npp16s rThresholdsGT[3], const Npp16s rValuesGT[3])`

3 channel 16-bit signed short in place threshold.

If for a comparison operations sourcePixel is less than rThresholdLT is true, the pixel is set to rValueLT, else if sourcePixel is greater than rThresholdGT the pixel is set to rValueGT, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

rThresholdsLT The thresholdLT values, one per color channel.

rValuesLT The thresholdLT replacement values, one per color channel.

rThresholdsGT The thresholdGT values, one per channel.

rValuesGT The thresholdGT replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.126 `NppStatus nppiThreshold_LTValGTVal_16s_C3R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp16s rThresholdsLT[3], const Npp16s rValuesLT[3], const Npp16s rThresholdsGT[3], const Npp16s rValuesGT[3])`

3 channel 16-bit signed short threshold.

If for a comparison operations sourcePixel is less than rThresholdLT is true, the pixel is set to rValueLT, else if sourcePixel is greater than rThresholdGT the pixel is set to rValueGT, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholdsLT The thresholdLT values, one per color channel.

rValuesLT The thresholdLT replacement values, one per color channel.

rThresholdsGT The thresholdGT values, one per channel.

rValuesGT The thresholdGT replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.127 `NppStatus nppiThreshold_LTValGTVal_16u_AC4IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16u rThresholdsLT[3], const Npp16u rValuesLT[3], const Npp16u rThresholdsGT[3], const Npp16u rValuesGT[3])`

4 channel 16-bit unsigned short in place image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is less than rThresholdLT is true, the pixel is set value is set to rValueLT, else if sourcePixel is greater than rThresholdGT the pixel is set to rValueGT, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI [Region-of-Interest \(ROI\)](#).

rThresholdsLT The thresholdLT values, one per color channel.

rValuesLT The thresholdLT replacement values, one per color channel.

rThresholdsGT The thresholdGT values, one per channel.

rValuesGT The thresholdGT replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.128 `NppStatus nppiThreshold_LTValGTVal_16u_AC4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp16u rThresholdsLT[3], const Npp16u rValuesLT[3], const Npp16u rThresholdsGT[3], const Npp16u rValuesGT[3])`

4 channel 16-bit unsigned short image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is less than rThresholdLT is true, the pixel is set value is set to rValueLT, else if sourcePixel is greater than rThresholdGT the pixel is set to rValueGT, otherwise it is set to sourcePixel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

rThresholdsLT The thresholdLT values, one per color channel.

rValuesLT The thresholdLT replacement values, one per color channel.

rThresholdsGT The thresholdGT values, one per channel.

rValuesGT The thresholdGT replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.129 `NppStatus nppiThreshold_LTValGTVal_16u_C1IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16u nThresholdLT, const Npp16u nValueLT, const Npp16u nThresholdGT, const Npp16u nValueGT)`

1 channel 16-bit unsigned short in place threshold.

If for a comparison operations sourcePixel is less than nThresholdLT is true, the pixel is set to nValueLT, else if sourcePixel is greater than nThresholdGT the pixel is set to nValueGT, otherwise it is set to sourcePixel.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nThresholdLT The thresholdLT value.
nValueLT The thresholdLT replacement value.
nThresholdGT The thresholdGT value.
nValueGT The thresholdGT replacement value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.130 `NppStatus nppiThreshold_LTValGTVal_16u_C1R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp16u nThresholdLT, const Npp16u nValueLT, const Npp16u nThresholdGT, const Npp16u nValueGT)`

1 channel 16-bit unsigned short threshold.

If for a comparison operations sourcePixel is less than nThresholdLT is true, the pixel is set to nValueLT, else if sourcePixel is greater than nThresholdGT the pixel is set to nValueGT, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nThresholdLT The thresholdLT value.
nValueLT The thresholdLT replacement value.
nThresholdGT The thresholdGT value.
nValueGT The thresholdGT replacement value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.131 `NppStatus nppiThreshold_LTValGTVal_16u_C3IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16u rThresholdsLT[3], const Npp16u rValuesLT[3], const Npp16u rThresholdsGT[3], const Npp16u rValuesGT[3])`

3 channel 16-bit unsigned short in place threshold.

If for a comparison operations sourcePixel is less than rThresholdLT is true, the pixel is set to rValueLT, else if sourcePixel is greater than rThresholdGT the pixel is set to rValueGT, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholdsLT The thresholdLT values, one per color channel.

rValuesLT The thresholdLT replacement values, one per color channel.

rThresholdsGT The thresholdGT values, one per channel.

rValuesGT The thresholdGT replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.132 `NppStatus nppiThreshold_LTValGTVal_16u_C3R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp16u rThresholdsLT[3], const Npp16u rValuesLT[3], const Npp16u rThresholdsGT[3], const Npp16u rValuesGT[3])`

3 channel 16-bit unsigned short threshold.

If for a comparison operations sourcePixel is less than rThresholdLT is true, the pixel is set to rValueLT, else if sourcePixel is greater than rThresholdGT the pixel is set to rValueGT, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholdsLT The thresholdLT values, one per color channel.

rValuesLT The thresholdLT replacement values, one per color channel.

rThresholdsGT The thresholdGT values, one per channel.

rValuesGT The thresholdGT replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.133 `NppStatus nppiThreshold_LTValGTVal_32f_AC4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f rThresholdsLT[3], const Npp32f rValuesLT[3], const Npp32f rThresholdsGT[3], const Npp32f rValuesGT[3])`

4 channel 32-bit floating point in place image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is less than rThresholdLT is true, the pixel is set value is set to rValueLT, else if sourcePixel is greater than rThresholdGT the pixel is set to rValueGT, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholdsLT The thresholdLT values, one per color channel.

rValuesLT The thresholdLT replacement values, one per color channel.

rThresholdsGT The thresholdGT values, one per channel.

rValuesGT The thresholdGT replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.134 `NppStatus nppiThreshold_LTValGTVal_32f_AC4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f rThresholdsLT[3], const Npp32f rValuesLT[3], const Npp32f rThresholdsGT[3], const Npp32f rValuesGT[3])`

4 channel 32-bit floating point image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is less than rThresholdLT is true, the pixel is set value is set to rValueLT, else if sourcePixel is greater than rThresholdGT the pixel is set to rValueGT, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholdsLT The thresholdLT values, one per color channel.

rValuesLT The thresholdLT replacement values, one per color channel.

rThresholdsGT The thresholdGT values, one per channel.

rValuesGT The thresholdGT replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.135 `NppStatus nppiThreshold_LTValGTVal_32f_C1IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f nThresholdLT, const Npp32f nValueLT, const Npp32f nThresholdGT, const Npp32f nValueGT)`

1 channel 32-bit floating point in place threshold.

If for a comparison operations sourcePixel is less than nThresholdLT is true, the pixel is set to nValueLT, else if sourcePixel is greater than nThresholdGT the pixel is set to nValueGT, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nThresholdLT The thresholdLT value.
nValueLT The thresholdLT replacement value.
nThresholdGT The thresholdGT value.
nValueGT The thresholdGT replacement value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.136 `NppStatus nppiThreshold_LTValGTVal_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f nThresholdLT, const Npp32f nValueLT, const Npp32f nThresholdGT, const Npp32f nValueGT)`

1 channel 32-bit floating point threshold.

If for a comparison operations sourcePixel is less than nThresholdLT is true, the pixel is set to nValueLT, else if sourcePixel is greater than nThresholdGT the pixel is set to nValueGT, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nThresholdLT The thresholdLT value.
nValueLT The thresholdLT replacement value.
nThresholdGT The thresholdGT value.
nValueGT The thresholdGT replacement value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.137 `NppStatus nppiThreshold_LTValGTVal_32f_C3IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f rThresholdsLT[3], const Npp32f rValuesLT[3], const Npp32f rThresholdsGT[3], const Npp32f rValuesGT[3])`

3 channel 32-bit floating point in place threshold.

If for a comparison operations sourcePixel is less than rThresholdLT is true, the pixel is set to rValueLT, else if sourcePixel is greater than rThresholdGT the pixel is set to rValueGT, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholdsLT The thresholdLT values, one per color channel.

rValuesLT The thresholdLT replacement values, one per color channel.

rThresholdsGT The thresholdGT values, one per channel.

rValuesGT The thresholdGT replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.138 `NppStatus nppiThreshold_LTValGTVal_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f rThresholdsLT[3], const Npp32f rValuesLT[3], const Npp32f rThresholdsGT[3], const Npp32f rValuesGT[3])`

3 channel 32-bit floating point threshold.

If for a comparison operations sourcePixel is less than rThresholdLT is true, the pixel is set to rValueLT, else if sourcePixel is greater than rThresholdGT the pixel is set to rValueGT, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholdsLT The thresholdLT values, one per color channel.

rValuesLT The thresholdLT replacement values, one per color channel.

rThresholdsGT The thresholdGT values, one per channel.

rValuesGT The thresholdGT replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.139 `NppStatus nppiThreshold_LTValGTVal_8u_AC4IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp8u rThresholdsLT[3], const Npp8u rValuesLT[3], const Npp8u rThresholdsGT[3], const Npp8u rValuesGT[3])`

4 channel 8-bit unsigned char in place image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is less than rThresholdLT is true, the pixel is set value is set to rValueLT, else if sourcePixel is greater than rThresholdGT the pixel is set to rValueGT, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholdsLT The thresholdLT values, one per color channel.

rValuesLT The thresholdLT replacement values, one per color channel.

rThresholdsGT The thresholdGT values, one per channel.

rValuesGT The thresholdGT replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.140 `NppStatus nppiThreshold_LTValGTVal_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u rThresholdsLT[3], const Npp8u rValuesLT[3], const Npp8u rThresholdsGT[3], const Npp8u rValuesGT[3])`

4 channel 8-bit unsigned char image threshold, not affecting Alpha.

If for a comparison operations sourcePixel is less than rThresholdLT is true, the pixel is set value is set to rValueLT, else if sourcePixel is greater than rThresholdGT the pixel is set to rValueGT, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholdsLT The thresholdLT values, one per color channel.

rValuesLT The thresholdLT replacement values, one per color channel.

rThresholdsGT The thresholdGT values, one per channel.

rValuesGT The thresholdGT replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.141 `NppStatus nppiThreshold_LTValGTVal_8u_C1IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp8u nThresholdLT, const Npp8u nValueLT, const Npp8u nThresholdGT, const Npp8u nValueGT)`

1 channel 8-bit unsigned char in place threshold.

If for a comparison operations sourcePixel is less than nThresholdLT is true, the pixel is set to nValueLT, else if sourcePixel is greater than nThresholdGT the pixel is set to nValueGT, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nThresholdLT The thresholdLT value.
nValueLT The thresholdLT replacement value.
nThresholdGT The thresholdGT value.
nValueGT The thresholdGT replacement value.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.142 `NppStatus nppiThreshold_LTValGTVal_8u_C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u nThresholdLT, const Npp8u nValueLT, const Npp8u nThresholdGT, const Npp8u nValueGT)`

1 channel 8-bit unsigned char threshold.

If for a comparison operations sourcePixel is less than nThresholdLT is true, the pixel is set to nValueLT, else if sourcePixel is greater than nThresholdGT the pixel is set to nValueGT, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nThresholdLT The thresholdLT value.
nValueLT The thresholdLT replacement value.
nThresholdGT The thresholdGT value.
nValueGT The thresholdGT replacement value.

Returns:

Image Data Related Error Codes, ROI Related Error Codes.

7.130.2.143 `NppStatus nppiThreshold_LTValGTVal_8u_C3IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp8u rThresholdsLT[3], const Npp8u rValuesLT[3], const Npp8u rThresholdsGT[3], const Npp8u rValuesGT[3])`

3 channel 8-bit unsigned char in place threshold.

If for a comparison operations sourcePixel is less than rThresholdLT is true, the pixel is set to rValueLT, else if sourcePixel is greater than rThresholdGT the pixel is set to rValueGT, otherwise it is set to sourcePixel.

Parameters:

pSrcDst Destination-Image Pointer.

nSrcDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholdsLT The thresholdLT values, one per color channel.

rValuesLT The thresholdLT replacement values, one per color channel.

rThresholdsGT The thresholdGT values, one per channel.

rValuesGT The thresholdGT replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.144 `NppStatus nppiThreshold_LTValGTVal_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u rThresholdsLT[3], const Npp8u rValuesLT[3], const Npp8u rThresholdsGT[3], const Npp8u rValuesGT[3])`

3 channel 8-bit unsigned char threshold.

If for a comparison operations sourcePixel is less than rThresholdLT is true, the pixel is set to rValueLT, else if sourcePixel is greater than rThresholdGT the pixel is set to rValueGT, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholdsLT The thresholdLT values, one per color channel.

rValuesLT The thresholdLT replacement values, one per color channel.

rThresholdsGT The thresholdGT values, one per channel.

rValuesGT The thresholdGT replacement values, one per color channel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#).

7.130.2.145 `NppStatus nppiThreshold_Val_16s_AC4IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16s rThresholds[3], const Npp16s rValues[3], NppCmpOp eComparisonOperation)`

4 channel 16-bit signed short in place image threshold, not affecting Alpha.

If for a comparison operations OP the predicate (sourcePixel.channel OP nThreshold) is true, the channel value is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.146 `NppStatus nppiThreshold_Val_16s_AC4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp16s rThresholds[3], const Npp16s rValues[3], NppCmpOp eComparisonOperation)`

4 channel 16-bit signed short image threshold, not affecting Alpha.

If for a comparison operations OP the predicate (sourcePixel.channel OP nThreshold) is true, the channel value is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.147 `NppStatus nppiThreshold_Val_16s_C1IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16s nThreshold, const Npp16s nValue, NppCmpOp eComparisonOperation)`

1 channel 16-bit signed short in place threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

nValue The threshold replacement value.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.148 `NppStatus nppiThreshold_Val_16s_C1R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp16s nThreshold, const Npp16s nValue, NppCmpOp eComparisonOperation)`

1 channel 16-bit signed short threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

nValue The threshold replacement value.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.149 `NppStatus nppiThreshold_Val_16s_C3IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16s rThresholds[3], const Npp16s rValues[3], NppCmpOp eComparisonOperation)`

3 channel 16-bit signed short in place threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.150 `NppStatus nppiThreshold_Val_16s_C3R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp16s rThresholds[3], const Npp16s rValues[3], NppCmpOp eComparisonOperation)`

3 channel 16-bit signed short threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.151 `NppStatus nppiThreshold_Val_16u_AC4IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16u rThresholds[3], const Npp16u rValues[3], NppCmpOp eComparisonOperation)`

4 channel 16-bit unsigned short in place image threshold, not affecting Alpha.

If for a comparison operations OP the predicate (sourcePixel.channel OP nThreshold) is true, the channel value is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.152 `NppStatus nppiThreshold_Val_16u_AC4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp16u rThresholds[3], const Npp16u rValues[3], NppCmpOp eComparisonOperation)`

4 channel 16-bit unsigned short image threshold, not affecting Alpha.

If for a comparison operations OP the predicate (sourcePixel.channel OP nThreshold) is true, the channel value is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.153 `NppStatus nppiThreshold_Val_16u_C1IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16u nThreshold, const Npp16u nValue, NppCmpOp eComparisonOperation)`

1 channel 16-bit unsigned short in place threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

nValue The threshold replacement value.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.154 `NppStatus nppiThreshold_Val_16u_C1R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp16u nThreshold, const Npp16u nValue, NppCmpOp eComparisonOperation)`

1 channel 16-bit unsigned short threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

nValue The threshold replacement value.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.155 `NppStatus nppiThreshold_Val_16u_C3IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp16u rThresholds[3], const Npp16u rValues[3], NppCmpOp eComparisonOperation)`

3 channel 16-bit unsigned short in place threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.156 `NppStatus nppiThreshold_Val_16u_C3R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp16u rThresholds[3], const Npp16u rValues[3], NppCmpOp eComparisonOperation)`

3 channel 16-bit unsigned short threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.157 `NppStatus nppiThreshold_Val_32f_AC4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f rThresholds[3], const Npp32f rValues[3], NppCmpOp eComparisonOperation)`

4 channel 32-bit floating point in place image threshold, not affecting Alpha.

If for a comparison operations OP the predicate (sourcePixel.channel OP nThreshold) is true, the channel value is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.158 `NppStatus nppiThreshold_Val_32f_AC4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f rThresholds[3], const Npp32f rValues[3], NppCmpOp eComparisonOperation)`

4 channel 32-bit floating point image threshold, not affecting Alpha.

If for a comparison operations OP the predicate (sourcePixel.channel OP nThreshold) is true, the channel value is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.159 `NppStatus nppiThreshold_Val_32f_C1IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f nThreshold, const Npp32f nValue, NppCmpOp eComparisonOperation)`

1 channel 32-bit floating point in place threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

nValue The threshold replacement value.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.160 `NppStatus nppiThreshold_Val_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f nThreshold, const Npp32f nValue, NppCmpOp eComparisonOperation)`

1 channel 32-bit floating point threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

nValue The threshold replacement value.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.161 `NppStatus nppiThreshold_Val_32f_C3IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp32f rThresholds[3], const Npp32f rValues[3], NppCmpOp eComparisonOperation)`

3 channel 32-bit floating point in place threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.162 `NppStatus nppiThreshold_Val_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f rThresholds[3], const Npp32f rValues[3], NppCmpOp eComparisonOperation)`

3 channel 32-bit floating point threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.163 `NppStatus nppiThreshold_Val_8u_AC4IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp8u rThresholds[3], const Npp8u rValues[3], NppCmpOp eComparisonOperation)`

4 channel 8-bit unsigned char in place image threshold, not affecting Alpha.

If for a comparison operations OP the predicate (sourcePixel.channel OP nThreshold) is true, the channel value is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.164 `NppStatus nppiThreshold_Val_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u rThresholds[3], const Npp8u rValues[3], NppCmpOp eComparisonOperation)`

4 channel 8-bit unsigned char image threshold, not affecting Alpha.

If for a comparison operations OP the predicate (sourcePixel.channel OP nThreshold) is true, the channel value is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.165 `NppStatus nppiThreshold_Val_8u_C1IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp8u nThreshold, const Npp8u nValue, NppCmpOp eComparisonOperation)`

1 channel 8-bit unsigned char in place threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

nValue The threshold replacement value.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.166 `NppStatus nppiThreshold_Val_8u_C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u nThreshold, const Npp8u nValue, NppCmpOp eComparisonOperation)`

1 channel 8-bit unsigned char threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

nValue The threshold replacement value.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.167 `NppStatus nppiThreshold_Val_8u_C3IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const Npp8u rThresholds[3], const Npp8u rValues[3], NppCmpOp eComparisonOperation)`

3 channel 8-bit unsigned char in place threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.130.2.168 `NppStatus nppiThreshold_Val_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u rThresholds[3], const Npp8u rValues[3], NppCmpOp eComparisonOperation)`

3 channel 8-bit unsigned char threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nValue, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rThresholds The threshold values, one per color channel.

rValues The threshold replacement values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.131 Compare Operations

Compare the pixels of two images and create a binary result image.

Functions

- **NppStatus nppiCompare_8u_C1R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppCmpOp** eComparisonOperation)
1 channel 8-bit unsigned char image compare.
- **NppStatus nppiCompare_8u_C3R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppCmpOp** eComparisonOperation)
3 channel 8-bit unsigned char image compare.
- **NppStatus nppiCompare_8u_C4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppCmpOp** eComparisonOperation)
4 channel 8-bit unsigned char image compare.
- **NppStatus nppiCompare_8u_AC4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppCmpOp** eComparisonOperation)
4 channel 8-bit unsigned char image compare, not affecting Alpha.
- **NppStatus nppiCompare_16u_C1R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppCmpOp** eComparisonOperation)
1 channel 16-bit unsigned short image compare.
- **NppStatus nppiCompare_16u_C3R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppCmpOp** eComparisonOperation)
3 channel 16-bit unsigned short image compare.
- **NppStatus nppiCompare_16u_C4R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppCmpOp** eComparisonOperation)
4 channel 16-bit unsigned short image compare.
- **NppStatus nppiCompare_16u_AC4R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppCmpOp** eComparisonOperation)
4 channel 16-bit unsigned short image compare, not affecting Alpha.
- **NppStatus nppiCompare_16s_C1R** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppCmpOp** eComparisonOperation)
1 channel 16-bit signed short image compare.
- **NppStatus nppiCompare_16s_C3R** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppCmpOp** eComparisonOperation)
3 channel 16-bit signed short image compare.
- **NppStatus nppiCompare_16s_C4R** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppCmpOp** eComparisonOperation)
4 channel 16-bit signed short image compare.

- [NppStatus nppiCompare_16s_AC4R](#) (const [Npp16s](#) *pSrc1, int nSrc1Step, const [Npp16s](#) *pSrc2, int nSrc2Step, [Npp8u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, [NppCmpOp](#) eComparisonOperation)
4 channel 16-bit signed short image compare, not affecting Alpha.
- [NppStatus nppiCompare_32f_C1R](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [Npp8u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, [NppCmpOp](#) eComparisonOperation)
1 channel 32-bit floating point image compare.
- [NppStatus nppiCompare_32f_C3R](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [Npp8u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, [NppCmpOp](#) eComparisonOperation)
3 channel 32-bit floating point image compare.
- [NppStatus nppiCompare_32f_C4R](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [Npp8u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, [NppCmpOp](#) eComparisonOperation)
4 channel 32-bit floating point image compare.
- [NppStatus nppiCompare_32f_AC4R](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [Npp8u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, [NppCmpOp](#) eComparisonOperation)
4 channel 32-bit signed floating point compare, not affecting Alpha.
- [NppStatus nppiCompareC_8u_C1R](#) (const [Npp8u](#) *pSrc, int nSrcStep, const [Npp8u](#) nConstant, [Npp8u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, [NppCmpOp](#) eComparisonOperation)
1 channel 8-bit unsigned char image compare with constant value.
- [NppStatus nppiCompareC_8u_C3R](#) (const [Npp8u](#) *pSrc, int nSrcStep, const [Npp8u](#) *pConstants, [Npp8u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, [NppCmpOp](#) eComparisonOperation)
3 channel 8-bit unsigned char image compare with constant value.
- [NppStatus nppiCompareC_8u_C4R](#) (const [Npp8u](#) *pSrc, int nSrcStep, const [Npp8u](#) *pConstants, [Npp8u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, [NppCmpOp](#) eComparisonOperation)
4 channel 8-bit unsigned char image compare with constant value.
- [NppStatus nppiCompareC_8u_AC4R](#) (const [Npp8u](#) *pSrc, int nSrcStep, const [Npp8u](#) *pConstants, [Npp8u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, [NppCmpOp](#) eComparisonOperation)
4 channel 8-bit unsigned char image compare, not affecting Alpha.
- [NppStatus nppiCompareC_16u_C1R](#) (const [Npp16u](#) *pSrc, int nSrcStep, const [Npp16u](#) nConstant, [Npp8u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, [NppCmpOp](#) eComparisonOperation)
1 channel 16-bit unsigned short image compare with constant value.
- [NppStatus nppiCompareC_16u_C3R](#) (const [Npp16u](#) *pSrc, int nSrcStep, const [Npp16u](#) *pConstants, [Npp8u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, [NppCmpOp](#) eComparisonOperation)
3 channel 16-bit unsigned short image compare with constant value.
- [NppStatus nppiCompareC_16u_C4R](#) (const [Npp16u](#) *pSrc, int nSrcStep, const [Npp16u](#) *pConstants, [Npp8u](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, [NppCmpOp](#) eComparisonOperation)
4 channel 16-bit unsigned short image compare with constant value.

- **NppStatus** `nppiCompareC_16u_AC4R` (const **Npp16u** *pSrc, int nSrcStep, const **Npp16u** *pConstants, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppCmpOp** eComparisonOperation)
4 channel 16-bit unsigned short image compare, not affecting Alpha.
- **NppStatus** `nppiCompareC_16s_C1R` (const **Npp16s** *pSrc, int nSrcStep, const **Npp16s** nConstant, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppCmpOp** eComparisonOperation)
1 channel 16-bit signed short image compare with constant value.
- **NppStatus** `nppiCompareC_16s_C3R` (const **Npp16s** *pSrc, int nSrcStep, const **Npp16s** *pConstants, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppCmpOp** eComparisonOperation)
3 channel 16-bit signed short image compare with constant value.
- **NppStatus** `nppiCompareC_16s_C4R` (const **Npp16s** *pSrc, int nSrcStep, const **Npp16s** *pConstants, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppCmpOp** eComparisonOperation)
4 channel 16-bit signed short image compare with constant value.
- **NppStatus** `nppiCompareC_16s_AC4R` (const **Npp16s** *pSrc, int nSrcStep, const **Npp16s** *pConstants, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppCmpOp** eComparisonOperation)
4 channel 16-bit signed short image compare, not affecting Alpha.
- **NppStatus** `nppiCompareC_32f_C1R` (const **Npp32f** *pSrc, int nSrcStep, const **Npp32f** nConstant, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppCmpOp** eComparisonOperation)
1 channel 32-bit floating point image compare with constant value.
- **NppStatus** `nppiCompareC_32f_C3R` (const **Npp32f** *pSrc, int nSrcStep, const **Npp32f** *pConstants, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppCmpOp** eComparisonOperation)
3 channel 32-bit floating point image compare with constant value.
- **NppStatus** `nppiCompareC_32f_C4R` (const **Npp32f** *pSrc, int nSrcStep, const **Npp32f** *pConstants, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppCmpOp** eComparisonOperation)
4 channel 32-bit floating point image compare with constant value.
- **NppStatus** `nppiCompareC_32f_AC4R` (const **Npp32f** *pSrc, int nSrcStep, const **Npp32f** *pConstants, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppCmpOp** eComparisonOperation)
4 channel 32-bit signed floating point compare, not affecting Alpha.
- **NppStatus** `nppiCompareEqualEps_32f_C1R` (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **Npp32f** nEpsilon)
1 channel 32-bit floating point image compare whether two images are equal within epsilon.
- **NppStatus** `nppiCompareEqualEps_32f_C3R` (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **Npp32f** nEpsilon)
3 channel 32-bit floating point image compare whether two images are equal within epsilon.
- **NppStatus** `nppiCompareEqualEps_32f_C4R` (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **Npp32f** nEpsilon)
4 channel 32-bit floating point image compare whether two images are equal within epsilon.

- **NppStatus nppiCompareEqualEps_32f_AC4R** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **Npp32f** nEpsilon)
4 channel 32-bit signed floating point compare whether two images are equal within epsilon, not affecting Alpha.
- **NppStatus nppiCompareEqualEpsC_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, const **Npp32f** nConstant, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **Npp32f** nEpsilon)
1 channel 32-bit floating point image compare whether image and constant are equal within epsilon.
- **NppStatus nppiCompareEqualEpsC_32f_C3R** (const **Npp32f** *pSrc, int nSrcStep, const **Npp32f** *pConstants, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **Npp32f** nEpsilon)
3 channel 32-bit floating point image compare whether image and constant are equal within epsilon.
- **NppStatus nppiCompareEqualEpsC_32f_C4R** (const **Npp32f** *pSrc, int nSrcStep, const **Npp32f** *pConstants, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **Npp32f** nEpsilon)
4 channel 32-bit floating point image compare whether image and constant are equal within epsilon.
- **NppStatus nppiCompareEqualEpsC_32f_AC4R** (const **Npp32f** *pSrc, int nSrcStep, const **Npp32f** *pConstants, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **Npp32f** nEpsilon)
4 channel 32-bit signed floating point compare whether image and constant are equal within epsilon, not affecting Alpha.

7.131.1 Detailed Description

Compare the pixels of two images and create a binary result image.

In case of multi-channel image types, the condition must be fulfilled for all channels, otherwise the comparison is considered false. The "binary" result image is of type 8u_C1. False is represented by 0, true by NPP_MAX_8U.

7.131.2 Function Documentation

7.131.2.1 NppStatus nppiCompare_16s_AC4R (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppCmpOp** eComparisonOperation)

4 channel 16-bit signed short image compare, not affecting Alpha.

Compare pSrc1's pixels with corresponding pixels in pSrc2.

Parameters:

- pSrc1** Source-Image Pointer.
- nSrc1Step** Source-Image Line Step.
- pSrc2** Source-Image Pointer.
- nSrc2Step** Source-Image Line Step.
- pDst** Destination-Image Pointer.
- nDstStep** Destination-Image Line Step.
- oSizeROI** Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.2 NppStatus nppiCompare_16s_C1R (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)

1 channel 16-bit signed short image compare.

Compare pSrc1's pixels with corresponding pixels in pSrc2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.3 NppStatus nppiCompare_16s_C3R (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)

3 channel 16-bit signed short image compare.

Compare pSrc1's pixels with corresponding pixels in pSrc2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.4 NppStatus nppiCompare_16s_C4R (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)

4 channel 16-bit signed short image compare.

Compare pSrc1's pixels with corresponding pixels in pSrc2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.5 NppStatus nppiCompare_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)

4 channel 16-bit unsigned short image compare, not affecting Alpha.

Compare pSrc1's pixels with corresponding pixels in pSrc2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.6 `NppStatus nppiCompare_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)`

1 channel 16-bit unsigned short image compare.

Compare pSrc1's pixels with corresponding pixels in pSrc2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.7 `NppStatus nppiCompare_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)`

3 channel 16-bit unsigned short image compare.

Compare pSrc1's pixels with corresponding pixels in pSrc2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.8 NppStatus nppiCompare_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)

4 channel 16-bit unsigned short image compare.

Compare pSrc1's pixels with corresponding pixels in pSrc2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.9 NppStatus nppiCompare_32f_AC4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)

4 channel 32-bit signed floating point compare, not affecting Alpha.

Compare pSrc1's pixels with corresponding pixels in pSrc2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.10 NppStatus nppiCompare_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)

1 channel 32-bit floating point image compare.

Compare pSrc1's pixels with corresponding pixels in pSrc2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.11 NppStatus nppiCompare_32f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)

3 channel 32-bit floating point image compare.

Compare pSrc1's pixels with corresponding pixels in pSrc2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.12 **NppStatus nppiCompare_32f_C4R** (*const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation*)

4 channel 32-bit floating point image compare.

Compare pSrc1's pixels with corresponding pixels in pSrc2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.13 **NppStatus nppiCompare_8u_AC4R** (*const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation*)

4 channel 8-bit unsigned char image compare, not affecting Alpha.

Compare pSrc1's pixels with corresponding pixels in pSrc2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.14 NppStatus nppiCompare_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)

1 channel 8-bit unsigned char image compare.

Compare pSrc1's pixels with corresponding pixels in pSrc2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.15 NppStatus nppiCompare_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)

3 channel 8-bit unsigned char image compare.

Compare pSrc1's pixels with corresponding pixels in pSrc2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.16 `NppStatus nppiCompare_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)`

4 channel 8-bit unsigned char image compare.

Compare pSrc1's pixels with corresponding pixels in pSrc2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.17 `NppStatus nppiCompareC_16s_AC4R (const Npp16s * pSrc, int nSrcStep, const Npp16s * pConstants, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)`

4 channel 16-bit signed short image compare, not affecting Alpha.

Compare pSrc's pixels with constant value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pConstants pointer to a list of constants, one per color channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.18 `NppStatus nppiCompareC_16s_C1R (const Npp16s * pSrc, int nSrcStep, const Npp16s nConstant, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)`

1 channel 16-bit signed short image compare with constant value.

Compare pSrc's pixels with constant value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
nConstant constant value.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.131.2.19 `NppStatus nppiCompareC_16s_C3R (const Npp16s * pSrc, int nSrcStep, const Npp16s * pConstants, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)`

3 channel 16-bit signed short image compare with constant value.

Compare pSrc's pixels with constant value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pConstants pointer to a list of constants, one per color channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.131.2.20 `NppStatus nppiCompareC_16s_C4R (const Npp16s * pSrc, int nSrcStep, const Npp16s * pConstants, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)`

4 channel 16-bit signed short image compare with constant value.

Compare pSrc's pixels with constant value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pConstants pointer to a list of constants, one per color channel.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.21 NppStatus nppiCompareC_16u_AC4R (const Npp16u * pSrc, int nSrcStep, const Npp16u * pConstants, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)

4 channel 16-bit unsigned short image compare, not affecting Alpha.

Compare pSrc's pixels with constant value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pConstants pointer to a list of constants, one per color channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.22 NppStatus nppiCompareC_16u_C1R (const Npp16u * pSrc, int nSrcStep, const Npp16u nConstant, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)

1 channel 16-bit unsigned short image compare with constant value.

Compare pSrc's pixels with constant value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

nConstant constant value

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.23 NppStatus nppiCompareC_16u_C3R (const Npp16u * pSrc, int nSrcStep, const Npp16u * pConstants, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)

3 channel 16-bit unsigned short image compare with constant value.

Compare pSrc's pixels with constant value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pConstants pointer to a list of constants, one per color channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.24 NppStatus nppiCompareC_16u_C4R (const Npp16u * pSrc, int nSrcStep, const Npp16u * pConstants, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)

4 channel 16-bit unsigned short image compare with constant value.

Compare pSrc's pixels with constant value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pConstants pointer to a list of constants, one per color channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.25 NppStatus nppiCompareC_32f_AC4R (const Npp32f * pSrc, int nSrcStep, const Npp32f * pConstants, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)

4 channel 32-bit signed floating point compare, not affecting Alpha.

Compare pSrc's pixels with constant value.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pConstants* pointer to a list of constants, one per color channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eComparisonOperation* Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.26 NppStatus nppiCompareC_32f_C1R (const Npp32f * pSrc, int nSrcStep, const Npp32f nConstant, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)

1 channel 32-bit floating point image compare with constant value.

Compare pSrc's pixels with constant value.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- nConstant* constant value
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eComparisonOperation* Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.27 NppStatus nppiCompareC_32f_C3R (const Npp32f * pSrc, int nSrcStep, const Npp32f * pConstants, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)

3 channel 32-bit floating point image compare with constant value.

Compare pSrc's pixels with constant value.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pConstants* pointer to a list of constants, one per color channel.
- pDst* Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.28 NppStatus nppiCompareC_32f_C4R (const Npp32f * pSrc, int nSrcStep, const Npp32f * pConstants, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)

4 channel 32-bit floating point image compare with constant value.

Compare pSrc's pixels with constant value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pConstants pointer to a list of constants, one per color channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.29 NppStatus nppiCompareC_8u_AC4R (const Npp8u * pSrc, int nSrcStep, const Npp8u * pConstants, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)

4 channel 8-bit unsigned char image compare, not affecting Alpha.

Compare pSrc's pixels with constant value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pConstants pointer to a list of constants, one per color channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.30 NppStatus nppiCompareC_8u_C1R (const Npp8u * pSrc, int nSrcStep, const Npp8u nConstant, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)

1 channel 8-bit unsigned char image compare with constant value.

Compare pSrc's pixels with constant value.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

nConstant constant value.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.31 NppStatus nppiCompareC_8u_C3R (const Npp8u * pSrc, int nSrcStep, const Npp8u * pConstants, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)

3 channel 8-bit unsigned char image compare with constant value.

Compare pSrc's pixels with constant value.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pConstants pointer to a list of constant values, one per color channel..

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.32 NppStatus nppiCompareC_8u_C4R (const Npp8u * pSrc, int nSrcStep, const Npp8u * pConstants, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)

4 channel 8-bit unsigned char image compare with constant value.

Compare pSrc's pixels with constant value.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pConstants* pointer to a list of constants, one per color channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eComparisonOperation* Specifies the comparison operation to be used in the pixel comparison.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.33 NppStatus nppiCompareEqualEps_32f_AC4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, Npp32f nEpsilon)

4 channel 32-bit signed floating point compare whether two images are equal within epsilon, not affecting Alpha.

Compare pSrc1's pixels with corresponding pixels in pSrc2 to determine whether they are equal with a difference of epsilon.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nEpsilon* epsilon tolerance value to compare to per color channel pixel absolute differences

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.34 NppStatus nppiCompareEqualEps_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, Npp32f nEpsilon)

1 channel 32-bit floating point image compare whether two images are equal within epsilon.

Compare pSrc1's pixels with corresponding pixels in pSrc2 to determine whether they are equal with a difference of epsilon.

Parameters:

- pSrc1* Source-Image Pointer.

nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nEpsilon epsilon tolerance value to compare to pixel absolute differences

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.35 `NppStatus nppiCompareEqualEps_32f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, Npp32f nEpsilon)`

3 channel 32-bit floating point image compare whether two images are equal within epsilon.

Compare pSrc1's pixels with corresponding pixels in pSrc2 to determine whether they are equal with a difference of epsilon.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nEpsilon epsilon tolerance value to compare to per color channel pixel absolute differences

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.36 `NppStatus nppiCompareEqualEps_32f_C4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, Npp32f nEpsilon)`

4 channel 32-bit floating point image compare whether two images are equal within epsilon.

Compare pSrc1's pixels with corresponding pixels in pSrc2 to determine whether they are equal with a difference of epsilon.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nEpsilon epsilon tolerance value to compare to per color channel pixel absolute differences

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.37 NppStatus nppiCompareEqualEpsC_32f_AC4R (const Npp32f * pSrc, int nSrcStep, const Npp32f * pConstants, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, Npp32f nEpsilon)

4 channel 32-bit signed floating point compare whether image and constant are equal within epsilon, not affecting Alpha.

Compare pSrc's pixels with constant value to determine whether they are equal within a difference of epsilon.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pConstants pointer to a list of constants, one per color channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nEpsilon epsilon tolerance value to compare to per color channel pixel absolute differences

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.38 NppStatus nppiCompareEqualEpsC_32f_C1R (const Npp32f * pSrc, int nSrcStep, const Npp32f nConstant, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, Npp32f nEpsilon)

1 channel 32-bit floating point image compare whether image and constant are equal within epsilon.

Compare pSrc's pixels with constant value to determine whether they are equal within a difference of epsilon.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

nConstant constant value

pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nEpsilon epsilon tolerance value to compare to pixel absolute differences

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.39 `NppStatus nppiCompareEqualEpsC_32f_C3R (const Npp32f * pSrc, int nSrcStep, const Npp32f * pConstants, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, Npp32f nEpsilon)`

3 channel 32-bit floating point image compare whether image and constant are equal within epsilon.

Compare pSrc's pixels with constant value to determine whether they are equal within a difference of epsilon.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pConstants pointer to a list of constants, one per color channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nEpsilon epsilon tolerance value to compare to per color channel pixel absolute differences

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.131.2.40 `NppStatus nppiCompareEqualEpsC_32f_C4R (const Npp32f * pSrc, int nSrcStep, const Npp32f * pConstants, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, Npp32f nEpsilon)`

4 channel 32-bit floating point image compare whether image and constant are equal within epsilon.

Compare pSrc's pixels with constant value to determine whether they are equal within a difference of epsilon.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pConstants pointer to a list of constants, one per color channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

nEpsilon epsilon tolerance value to compare to per color channel pixel absolute differences

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.132 NPP Signal Processing

Modules

- [Arithmetic and Logical Operations](#)
- [Conversion Functions](#)
- [Filtering Functions](#)

Functions that provide functionality of generating output signal based on the input signal like signal integral, etc.

- [Initialization](#)
- [Statistical Functions](#)

Functions that provide global signal statistics like: sum, mean, standard deviation, min, max, etc.

- [Memory Management](#)

7.133 Arithmetic and Logical Operations

Modules

- [Arithmetic Operations](#)
- [Logical And Shift Operations](#)

7.134 Arithmetic Operations

Modules

- [AddC](#)
Adds a constant value to each sample of a signal.
- [AddProductC](#)
Adds product of a constant and each sample of a source signal to the each sample of destination signal.
- [MulC](#)
Multiplies each sample of a signal by a constant value.
- [SubC](#)
Subtracts a constant from each sample of a signal.
- [SubCRev](#)
Subtracts each sample of a signal from a constant.
- [DivC](#)
Divides each sample of a signal by a constant.
- [DivCRev](#)
Divides a constant by each sample of a signal.
- [Add](#)
Sample by sample addition of two signals.
- [AddProduct](#)
Adds sample by sample product of two signals to the destination signal.
- [Mul](#)
Sample by sample multiplication the samples of two signals.
- [Sub](#)
Sample by sample subtraction of the samples of two signals.
- [Div](#)
Sample by sample division of the samples of two signals.
- [Div_Round](#)
Sample by sample division of the samples of two signals with rounding.
- [Abs](#)
Absolute value of each sample of a signal.
- [Sqr](#)
Squares each sample of a signal.
- [Sqrt](#)

Square root of each sample of a signal.

- [Cubrt](#)

Cube root of each sample of a signal.

- [Exp](#)

E raised to the power of each sample of a signal.

- [Ln](#)

Natural logarithm of each sample of a signal.

- [10Log10](#)

Ten times the decimal logarithm of each sample of a signal.

- [SumLn](#)

Sums up the natural logarithm of each sample of a signal.

- [Arctan](#)

Inverse tangent of each sample of a signal.

- [Normalize](#)

Normalize each sample of a real or complex signal using offset and division operations.

- [Cauchy, CauchyD, and CauchyDD2](#)

Determine Cauchy robust error function and its first and second derivatives for each sample of a signal.

7.135 AddC

Adds a constant value to each sample of a signal.

Functions

- **NppStatus nppsAddC_8u_ISfs** (**Npp8u** nValue, **Npp8u** *pSrcDst, int nLength, int nScaleFactor)
8-bit unsigned char in place signal add constant, scale, then clamp to saturated value
- **NppStatus nppsAddC_8u_Sfs** (const **Npp8u** *pSrc, **Npp8u** nValue, **Npp8u** *pDst, int nLength, int nScaleFactor)
8-bit unsigned charvector add constant, scale, then clamp to saturated value.
- **NppStatus nppsAddC_16u_ISfs** (**Npp16u** nValue, **Npp16u** *pSrcDst, int nLength, int nScaleFactor)
16-bit unsigned short in place signal add constant, scale, then clamp to saturated value.
- **NppStatus nppsAddC_16u_Sfs** (const **Npp16u** *pSrc, **Npp16u** nValue, **Npp16u** *pDst, int nLength, int nScaleFactor)
16-bit unsigned short vector add constant, scale, then clamp to saturated value.
- **NppStatus nppsAddC_16s_ISfs** (**Npp16s** nValue, **Npp16s** *pSrcDst, int nLength, int nScaleFactor)
16-bit signed short in place signal add constant, scale, then clamp to saturated value.
- **NppStatus nppsAddC_16s_Sfs** (const **Npp16s** *pSrc, **Npp16s** nValue, **Npp16s** *pDst, int nLength, int nScaleFactor)
16-bit signed short signal add constant, scale, then clamp to saturated value.
- **NppStatus nppsAddC_16sc_ISfs** (**Npp16sc** nValue, **Npp16sc** *pSrcDst, int nLength, int nScaleFactor)
16-bit integer complex number (16 bit real, 16 bit imaginary)signal add constant, scale, then clamp to saturated value.
- **NppStatus nppsAddC_16sc_Sfs** (const **Npp16sc** *pSrc, **Npp16sc** nValue, **Npp16sc** *pDst, int nLength, int nScaleFactor)
16-bit integer complex number (16 bit real, 16 bit imaginary) signal add constant, scale, then clamp to saturated value.
- **NppStatus nppsAddC_32s_ISfs** (**Npp32s** nValue, **Npp32s** *pSrcDst, int nLength, int nScaleFactor)
32-bit signed integer in place signal add constant and scale.
- **NppStatus nppsAddC_32s_Sfs** (const **Npp32s** *pSrc, **Npp32s** nValue, **Npp32s** *pDst, int nLength, int nScaleFactor)
32-bit signed integersignal add constant and scale.
- **NppStatus nppsAddC_32sc_ISfs** (**Npp32sc** nValue, **Npp32sc** *pSrcDst, int nLength, int nScaleFactor)
32-bit integer complex number (32 bit real, 32 bit imaginary) in place signal add constant and scale.
- **NppStatus nppsAddC_32sc_Sfs** (const **Npp32sc** *pSrc, **Npp32sc** nValue, **Npp32sc** *pDst, int nLength, int nScaleFactor)

32-bit integer complex number (32 bit real, 32 bit imaginary) signal add constant and scale.

- **NppStatus nppsAddC_32f_I** (**Npp32f** nValue, **Npp32f** *pSrcDst, int nLength)
32-bit floating point in place signal add constant.
- **NppStatus nppsAddC_32f** (const **Npp32f** *pSrc, **Npp32f** nValue, **Npp32f** *pDst, int nLength)
32-bit floating point signal add constant.
- **NppStatus nppsAddC_32fc_I** (**Npp32fc** nValue, **Npp32fc** *pSrcDst, int nLength)
32-bit floating point complex number (32 bit real, 32 bit imaginary) in place signal add constant.
- **NppStatus nppsAddC_32fc** (const **Npp32fc** *pSrc, **Npp32fc** nValue, **Npp32fc** *pDst, int nLength)
32-bit floating point complex number (32 bit real, 32 bit imaginary) signal add constant.
- **NppStatus nppsAddC_64f_I** (**Npp64f** nValue, **Npp64f** *pSrcDst, int nLength)
64-bit floating point, in place signal add constant.
- **NppStatus nppsAddC_64f** (const **Npp64f** *pSrc, **Npp64f** nValue, **Npp64f** *pDst, int nLength)
64-bit floating pointsignal add constant.
- **NppStatus nppsAddC_64fc_I** (**Npp64fc** nValue, **Npp64fc** *pSrcDst, int nLength)
64-bit floating point complex number (64 bit real, 64 bit imaginary) in place signal add constant.
- **NppStatus nppsAddC_64fc** (const **Npp64fc** *pSrc, **Npp64fc** nValue, **Npp64fc** *pDst, int nLength)
64-bit floating point complex number (64 bit real, 64 bit imaginary) signal add constant.

7.135.1 Detailed Description

Adds a constant value to each sample of a signal.

7.135.2 Function Documentation

7.135.2.1 **NppStatus nppsAddC_16s_ISfs** (**Npp16s** nValue, **Npp16s** *pSrcDst, int nLength, int nScaleFactor)

16-bit signed short in place signal add constant, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be added to each vector element

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.135.2.2 NppStatus nppsAddC_16s_Sfs (const Npp16s * pSrc, Npp16s nValue, Npp16s * pDst, int nLength, int nScaleFactor)

16-bit signed short signal add constant, scale, then clamp to saturated value.

Parameters:

- pSrc* [Source Signal Pointer](#).
- nValue* Constant value to be added to each vector element
- pDst* [Destination Signal Pointer](#).
- nLength* [Signal Length](#).
- nScaleFactor* [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.135.2.3 NppStatus nppsAddC_16sc_ISfs (Npp16sc nValue, Npp16sc * pSrcDst, int nLength, int nScaleFactor)

16-bit integer complex number (16 bit real, 16 bit imaginary) signal add constant, scale, then clamp to saturated value.

Parameters:

- pSrcDst* [In-Place Signal Pointer](#).
- nValue* Constant value to be added to each vector element
- nLength* [Signal Length](#).
- nScaleFactor* [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.135.2.4 NppStatus nppsAddC_16sc_Sfs (const Npp16sc * pSrc, Npp16sc nValue, Npp16sc * pDst, int nLength, int nScaleFactor)

16-bit integer complex number (16 bit real, 16 bit imaginary) signal add constant, scale, then clamp to saturated value.

Parameters:

- pSrc* [Source Signal Pointer](#).
- nValue* Constant value to be added to each vector element
- pDst* [Destination Signal Pointer](#).
- nLength* [Signal Length](#).
- nScaleFactor* [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.135.2.5 NppStatus nppsAddC_16u_ISfs (Npp16u *nValue*, Npp16u * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit unsigned short in place signal add constant, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be added to each vector element

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.135.2.6 NppStatus nppsAddC_16u_Sfs (const Npp16u * *pSrc*, Npp16u *nValue*, Npp16u * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit unsigned short vector add constant, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be added to each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.135.2.7 NppStatus nppsAddC_32f (const Npp32f * *pSrc*, Npp32f *nValue*, Npp32f * *pDst*, int *nLength*)

32-bit floating point signal add constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be added to each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.135.2.8 NppStatus nppsAddC_32f_I (Npp32f nValue, Npp32f * pSrcDst, int nLength)

32-bit floating point in place signal add constant.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be added to each vector element

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.135.2.9 NppStatus nppsAddC_32fc (const Npp32fc * pSrc, Npp32fc nValue, Npp32fc * pDst, int nLength)

32-bit floating point complex number (32 bit real, 32 bit imaginary) signal add constant.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be added to each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.135.2.10 NppStatus nppsAddC_32fc_I (Npp32fc nValue, Npp32fc * pSrcDst, int nLength)

32-bit floating point complex number (32 bit real, 32 bit imaginary) in place signal add constant.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be added to each vector element

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.135.2.11 NppStatus nppsAddC_32s_ISfs (Npp32s nValue, Npp32s * pSrcDst, int nLength, int nScaleFactor)

32-bit signed integer in place signal add constant and scale.

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value to be added to each vector element
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.135.2.12 NppStatus nppsAddC_32s_Sfs (const Npp32s * pSrc, Npp32s nValue, Npp32s * pDst, int nLength, int nScaleFactor)

32-bit signed integersignal add constant and scale.

Parameters:

pSrc Source Signal Pointer.
nValue Constant value to be added to each vector element
pDst Destination Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.135.2.13 NppStatus nppsAddC_32sc_ISfs (Npp32sc nValue, Npp32sc * pSrcDst, int nLength, int nScaleFactor)

32-bit integer complex number (32 bit real, 32 bit imaginary) in place signal add constant and scale.

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value to be added to each vector element
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.135.2.14 NppStatus nppsAddC_32sc_Sfs (const Npp32sc * pSrc, Npp32sc nValue, Npp32sc * pDst, int nLength, int nScaleFactor)

32-bit integer complex number (32 bit real, 32 bit imaginary) signal add constant and scale.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be added to each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.135.2.15 NppStatus nppsAddC_64f (const Npp64f * pSrc, Npp64f nValue, Npp64f * pDst, int nLength)

64-bit floating pointsignal add constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be added to each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.135.2.16 NppStatus nppsAddC_64f_I (Npp64f nValue, Npp64f * pSrcDst, int nLength)

64-bit floating point, in place signal add constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be added to each vector element

nLength Length of the vectors, number of items.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.135.2.17 NppStatus nppsAddC_64fc (const Npp64fc * pSrc, Npp64fc nValue, Npp64fc * pDst, int nLength)

64-bit floating point complex number (64 bit real, 64 bit imaginary) signal add constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be added to each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.135.2.18 NppStatus nppsAddC_64fc_I (Npp64fc nValue, Npp64fc * pSrcDst, int nLength)

64-bit floating point complex number (64 bit real, 64 bit imaginary) in place signal add constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be added to each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.135.2.19 NppStatus nppsAddC_8u_ISfs (Npp8u nValue, Npp8u * pSrcDst, int nLength, int nScaleFactor)

8-bit unsigned char in place signal add constant, scale, then clamp to saturated value

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be added to each vector element

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.135.2.20 NppStatus nppsAddC_8u_Sfs (const Npp8u * pSrc, Npp8u nValue, Npp8u * pDst, int nLength, int nScaleFactor)

8-bit unsigned charvector add constant, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be added to each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.136 AddProductC

Adds product of a constant and each sample of a source signal to the each sample of destination signal.

Functions

- `NppStatus nppsAddProductC_32f` (const `Npp32f` *pSrc, `Npp32f` nValue, `Npp32f` *pDst, int nLength)

32-bit floating point signal add product of signal times constant to destination signal.

7.136.1 Detailed Description

Adds product of a constant and each sample of a source signal to the each sample of destination signal.

7.136.2 Function Documentation

7.136.2.1 `NppStatus nppsAddProductC_32f` (const `Npp32f` *pSrc, `Npp32f` nValue, `Npp32f` *pDst, int nLength)

32-bit floating point signal add product of signal times constant to destination signal.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be multiplied by each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.137 MulC

Multiplies each sample of a signal by a constant value.

Functions

- **NppStatus nppsMulC_8u_ISfs** (**Npp8u** nValue, **Npp8u** *pSrcDst, int nLength, int nScaleFactor)
8-bit unsigned char in place signal times constant, scale, then clamp to saturated value
- **NppStatus nppsMulC_8u_Sfs** (const **Npp8u** *pSrc, **Npp8u** nValue, **Npp8u** *pDst, int nLength, int nScaleFactor)
8-bit unsigned char signal times constant, scale, then clamp to saturated value.
- **NppStatus nppsMulC_16u_ISfs** (**Npp16u** nValue, **Npp16u** *pSrcDst, int nLength, int nScaleFactor)
16-bit unsigned short in place signal times constant, scale, then clamp to saturated value.
- **NppStatus nppsMulC_16u_Sfs** (const **Npp16u** *pSrc, **Npp16u** nValue, **Npp16u** *pDst, int nLength, int nScaleFactor)
16-bit unsigned short signal times constant, scale, then clamp to saturated value.
- **NppStatus nppsMulC_16s_ISfs** (**Npp16s** nValue, **Npp16s** *pSrcDst, int nLength, int nScaleFactor)
16-bit signed short in place signal times constant, scale, then clamp to saturated value.
- **NppStatus nppsMulC_16s_Sfs** (const **Npp16s** *pSrc, **Npp16s** nValue, **Npp16s** *pDst, int nLength, int nScaleFactor)
16-bit signed short signal times constant, scale, then clamp to saturated value.
- **NppStatus nppsMulC_16sc_ISfs** (**Npp16sc** nValue, **Npp16sc** *pSrcDst, int nLength, int nScaleFactor)
16-bit integer complex number (16 bit real, 16 bit imaginary)signal times constant, scale, then clamp to saturated value.
- **NppStatus nppsMulC_16sc_Sfs** (const **Npp16sc** *pSrc, **Npp16sc** nValue, **Npp16sc** *pDst, int nLength, int nScaleFactor)
16-bit integer complex number (16 bit real, 16 bit imaginary)signal times constant, scale, then clamp to saturated value.
- **NppStatus nppsMulC_32s_ISfs** (**Npp32s** nValue, **Npp32s** *pSrcDst, int nLength, int nScaleFactor)
32-bit signed integer in place signal times constant and scale.
- **NppStatus nppsMulC_32s_Sfs** (const **Npp32s** *pSrc, **Npp32s** nValue, **Npp32s** *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal times constant and scale.
- **NppStatus nppsMulC_32sc_ISfs** (**Npp32sc** nValue, **Npp32sc** *pSrcDst, int nLength, int nScaleFactor)
32-bit integer complex number (32 bit real, 32 bit imaginary) in place signal times constant and scale.
- **NppStatus nppsMulC_32sc_Sfs** (const **Npp32sc** *pSrc, **Npp32sc** nValue, **Npp32sc** *pDst, int nLength, int nScaleFactor)

32-bit integer complex number (32 bit real, 32 bit imaginary) signal times constant and scale.

- **NppStatus nppsMulC_32f_I** (**Npp32f** nValue, **Npp32f** *pSrcDst, int nLength)
32-bit floating point in place signal times constant.
- **NppStatus nppsMulC_32f** (const **Npp32f** *pSrc, **Npp32f** nValue, **Npp32f** *pDst, int nLength)
32-bit floating point signal times constant.
- **NppStatus nppsMulC_Low_32f16s** (const **Npp32f** *pSrc, **Npp32f** nValue, **Npp16s** *pDst, int nLength)
32-bit floating point signal times constant with output converted to 16-bit signed integer.
- **NppStatus nppsMulC_32f16s_Sfs** (const **Npp32f** *pSrc, **Npp32f** nValue, **Npp16s** *pDst, int nLength, int nScaleFactor)
32-bit floating point signal times constant with output converted to 16-bit signed integer with scaling and saturation of output result.
- **NppStatus nppsMulC_32fc_I** (**Npp32fc** nValue, **Npp32fc** *pSrcDst, int nLength)
32-bit floating point complex number (32 bit real, 32 bit imaginary) in place signal times constant.
- **NppStatus nppsMulC_32fc** (const **Npp32fc** *pSrc, **Npp32fc** nValue, **Npp32fc** *pDst, int nLength)
32-bit floating point complex number (32 bit real, 32 bit imaginary) signal times constant.
- **NppStatus nppsMulC_64f_I** (**Npp64f** nValue, **Npp64f** *pSrcDst, int nLength)
64-bit floating point, in place signal times constant.
- **NppStatus nppsMulC_64f** (const **Npp64f** *pSrc, **Npp64f** nValue, **Npp64f** *pDst, int nLength)
64-bit floating point signal times constant.
- **NppStatus nppsMulC_64f64s_ISfs** (**Npp64f** nValue, **Npp64s** *pDst, int nLength, int nScaleFactor)
64-bit floating point signal times constant with in place conversion to 64-bit signed integer and with scaling and saturation of output result.
- **NppStatus nppsMulC_64fc_I** (**Npp64fc** nValue, **Npp64fc** *pSrcDst, int nLength)
64-bit floating point complex number (64 bit real, 64 bit imaginary) in place signal times constant.
- **NppStatus nppsMulC_64fc** (const **Npp64fc** *pSrc, **Npp64fc** nValue, **Npp64fc** *pDst, int nLength)
64-bit floating point complex number (64 bit real, 64 bit imaginary) signal times constant.

7.137.1 Detailed Description

Multiplies each sample of a signal by a constant value.

7.137.2 Function Documentation

7.137.2.1 **NppStatus nppsMulC_16s_ISfs** (**Npp16s** nValue, **Npp16s** *pSrcDst, int nLength, int nScaleFactor)

16-bit signed short in place signal times constant, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value to be multiplied by each vector element
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.137.2.2 NppStatus nppsMulC_16s_Sfs (const Npp16s * pSrc, Npp16s nValue, Npp16s * pDst, int nLength, int nScaleFactor)

16-bit signed short signal times constant, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.
nValue Constant value to be multiplied by each vector element
pDst Destination Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.137.2.3 NppStatus nppsMulC_16sc_ISfs (Npp16sc nValue, Npp16sc * pSrcDst, int nLength, int nScaleFactor)

16-bit integer complex number (16 bit real, 16 bit imaginary) signal times constant, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value to be multiplied by each vector element
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.137.2.4 NppStatus nppsMulC_16sc_Sfs (const Npp16sc * pSrc, Npp16sc nValue, Npp16sc * pDst, int nLength, int nScaleFactor)

16-bit integer complex number (16 bit real, 16 bit imaginary) signal times constant, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be multiplied by each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.137.2.5 NppStatus nppsMulC_16u_ISfs (Npp16u nValue, Npp16u * pSrcDst, int nLength, int nScaleFactor)

16-bit unsigned short in place signal times constant, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be multiplied by each vector element

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.137.2.6 NppStatus nppsMulC_16u_Sfs (const Npp16u * pSrc, Npp16u nValue, Npp16u * pDst, int nLength, int nScaleFactor)

16-bit unsigned short signal times constant, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be multiplied by each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.137.2.7 NppStatus nppsMulC_32f (const Npp32f * pSrc, Npp32f nValue, Npp32f * pDst, int nLength)

32-bit floating point signal times constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be multiplied by each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.137.2.8 NppStatus nppsMulC_32f16s_Sfs (const Npp32f * pSrc, Npp32f nValue, Npp16s * pDst, int nLength, int nScaleFactor)

32-bit floating point signal times constant with output converted to 16-bit signed integer with scaling and saturation of output result.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be multiplied by each vector element

pDst Destination Signal Pointer.

nScaleFactor Integer Result Scaling.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.137.2.9 NppStatus nppsMulC_32f_I (Npp32f nValue, Npp32f * pSrcDst, int nLength)

32-bit floating point in place signal times constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be multiplied by each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.137.2.10 NppStatus nppsMulC_32fc (const Npp32fc * pSrc, Npp32fc nValue, Npp32fc * pDst, int nLength)

32-bit floating point complex number (32 bit real, 32 bit imaginary) signal times constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be multiplied by each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.137.2.11 NppStatus nppsMulC_32fc_I (Npp32fc nValue, Npp32fc * pSrcDst, int nLength)

32-bit floating point complex number (32 bit real, 32 bit imaginary) in place signal times constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be multiplied by each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.137.2.12 NppStatus nppsMulC_32s_ISfs (Npp32s nValue, Npp32s * pSrcDst, int nLength, int nScaleFactor)

32-bit signed integer in place signal times constant and scale.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be multiplied by each vector element

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.137.2.13 NppStatus nppsMulC_32s_Sfs (const Npp32s * pSrc, Npp32s nValue, Npp32s * pDst, int nLength, int nScaleFactor)

32-bit signed integer signal times constant and scale.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be multiplied by each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.137.2.14 NppStatus nppsMulC_32sc_ISfs (Npp32sc nValue, Npp32sc * pSrcDst, int nLength, int nScaleFactor)

32-bit integer complex number (32 bit real, 32 bit imaginary) in place signal times constant and scale.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be multiplied by each vector element

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.137.2.15 NppStatus nppsMulC_32sc_Sfs (const Npp32sc * pSrc, Npp32sc nValue, Npp32sc * pDst, int nLength, int nScaleFactor)

32-bit integer complex number (32 bit real, 32 bit imaginary) signal times constant and scale.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be multiplied by each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.137.2.16 NppStatus nppsMulC_64f (const Npp64f * pSrc, Npp64f nValue, Npp64f * pDst, int nLength)

64-bit floating point signal times constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be multiplied by each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.137.2.17 NppStatus nppsMulC_64f64s_ISfs (Npp64f nValue, Npp64s * pDst, int nLength, int nScaleFactor)

64-bit floating point signal times constant with in place conversion to 64-bit signed integer and with scaling and saturation of output result.

Parameters:

nValue Constant value to be multiplied by each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.137.2.18 NppStatus nppsMulC_64f_I (Npp64f nValue, Npp64f * pSrcDst, int nLength)

64-bit floating point, in place signal times constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be multiplied by each vector element

nLength Length of the vectors, number of items.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.137.2.19 NppStatus nppsMulC_64fc (const Npp64fc * pSrc, Npp64fc nValue, Npp64fc * pDst, int nLength)

64-bit floating point complex number (64 bit real, 64 bit imaginary) signal times constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be multiplied by each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.137.2.20 NppStatus nppsMulC_64fc_I (Npp64fc nValue, Npp64fc * pSrcDst, int nLength)

64-bit floating point complex number (64 bit real, 64 bit imaginary) in place signal times constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be multiplied by each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.137.2.21 NppStatus nppsMulC_8u_ISfs (Npp8u nValue, Npp8u * pSrcDst, int nLength, int nScaleFactor)

8-bit unsigned char in place signal times constant, scale, then clamp to saturated value

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be multiplied by each vector element

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.137.2.22 NppStatus nppsMulC_8u_Sfs (const Npp8u * pSrc, Npp8u nValue, Npp8u * pDst, int nLength, int nScaleFactor)

8-bit unsigned char signal times constant, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be multiplied by each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.137.2.23 NppStatus nppsMulC_Low_32f16s (const Npp32f * pSrc, Npp32f nValue, Npp16s * pDst, int nLength)

32-bit floating point signal times constant with output converted to 16-bit signed integer.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be multiplied by each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.138 SubC

Subtracts a constant from each sample of a signal.

Functions

- **NppStatus nppsSubC_8u_ISfs** (**Npp8u** nValue, **Npp8u** *pSrcDst, int nLength, int nScaleFactor)
8-bit unsigned char in place signal subtract constant, scale, then clamp to saturated value
- **NppStatus nppsSubC_8u_Sfs** (const **Npp8u** *pSrc, **Npp8u** nValue, **Npp8u** *pDst, int nLength, int nScaleFactor)
8-bit unsigned char signal subtract constant, scale, then clamp to saturated value.
- **NppStatus nppsSubC_16u_ISfs** (**Npp16u** nValue, **Npp16u** *pSrcDst, int nLength, int nScaleFactor)
16-bit unsigned short in place signal subtract constant, scale, then clamp to saturated value.
- **NppStatus nppsSubC_16u_Sfs** (const **Npp16u** *pSrc, **Npp16u** nValue, **Npp16u** *pDst, int nLength, int nScaleFactor)
16-bit unsigned short signal subtract constant, scale, then clamp to saturated value.
- **NppStatus nppsSubC_16s_ISfs** (**Npp16s** nValue, **Npp16s** *pSrcDst, int nLength, int nScaleFactor)
16-bit signed short in place signal subtract constant, scale, then clamp to saturated value.
- **NppStatus nppsSubC_16s_Sfs** (const **Npp16s** *pSrc, **Npp16s** nValue, **Npp16s** *pDst, int nLength, int nScaleFactor)
16-bit signed short signal subtract constant, scale, then clamp to saturated value.
- **NppStatus nppsSubC_16sc_ISfs** (**Npp16sc** nValue, **Npp16sc** *pSrcDst, int nLength, int nScaleFactor)
16-bit integer complex number (16 bit real, 16 bit imaginary) signal subtract constant, scale, then clamp to saturated value.
- **NppStatus nppsSubC_16sc_Sfs** (const **Npp16sc** *pSrc, **Npp16sc** nValue, **Npp16sc** *pDst, int nLength, int nScaleFactor)
16-bit integer complex number (16 bit real, 16 bit imaginary) signal subtract constant, scale, then clamp to saturated value.
- **NppStatus nppsSubC_32s_ISfs** (**Npp32s** nValue, **Npp32s** *pSrcDst, int nLength, int nScaleFactor)
32-bit signed integer in place signal subtract constant and scale.
- **NppStatus nppsSubC_32s_Sfs** (const **Npp32s** *pSrc, **Npp32s** nValue, **Npp32s** *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal subtract constant and scale.
- **NppStatus nppsSubC_32sc_ISfs** (**Npp32sc** nValue, **Npp32sc** *pSrcDst, int nLength, int nScaleFactor)
32-bit integer complex number (32 bit real, 32 bit imaginary) in place signal subtract constant and scale.
- **NppStatus nppsSubC_32sc_Sfs** (const **Npp32sc** *pSrc, **Npp32sc** nValue, **Npp32sc** *pDst, int nLength, int nScaleFactor)

32-bit integer complex number (32 bit real, 32 bit imaginary) signal subtract constant and scale.

- **NppStatus nppsSubC_32f_I** (**Npp32f** nValue, **Npp32f** *pSrcDst, int nLength)
32-bit floating point in place signal subtract constant.
- **NppStatus nppsSubC_32f** (const **Npp32f** *pSrc, **Npp32f** nValue, **Npp32f** *pDst, int nLength)
32-bit floating point signal subtract constant.
- **NppStatus nppsSubC_32fc_I** (**Npp32fc** nValue, **Npp32fc** *pSrcDst, int nLength)
32-bit floating point complex number (32 bit real, 32 bit imaginary) in place signal subtract constant.
- **NppStatus nppsSubC_32fc** (const **Npp32fc** *pSrc, **Npp32fc** nValue, **Npp32fc** *pDst, int nLength)
32-bit floating point complex number (32 bit real, 32 bit imaginary) signal subtract constant.
- **NppStatus nppsSubC_64f_I** (**Npp64f** nValue, **Npp64f** *pSrcDst, int nLength)
64-bit floating point, in place signal subtract constant.
- **NppStatus nppsSubC_64f** (const **Npp64f** *pSrc, **Npp64f** nValue, **Npp64f** *pDst, int nLength)
64-bit floating point signal subtract constant.
- **NppStatus nppsSubC_64fc_I** (**Npp64fc** nValue, **Npp64fc** *pSrcDst, int nLength)
64-bit floating point complex number (64 bit real, 64 bit imaginary) in place signal subtract constant.
- **NppStatus nppsSubC_64fc** (const **Npp64fc** *pSrc, **Npp64fc** nValue, **Npp64fc** *pDst, int nLength)
64-bit floating point complex number (64 bit real, 64 bit imaginary) signal subtract constant.

7.138.1 Detailed Description

Subtracts a constant from each sample of a signal.

7.138.2 Function Documentation

7.138.2.1 **NppStatus nppsSubC_16s_ISfs** (**Npp16s** nValue, **Npp16s** *pSrcDst, int nLength, int nScaleFactor)

16-bit signed short in place signal subtract constant, scale, then clamp to saturated value.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be subtracted from each vector element

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.138.2.2 NppStatus nppsSubC_16s_Sfs (const Npp16s * pSrc, Npp16s nValue, Npp16s * pDst, int nLength, int nScaleFactor)

16-bit signed short signal subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be subtracted from each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.138.2.3 NppStatus nppsSubC_16sc_ISfs (Npp16sc nValue, Npp16sc * pSrcDst, int nLength, int nScaleFactor)

16-bit integer complex number (16 bit real, 16 bit imaginary) signal subtract constant, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be subtracted from each vector element

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.138.2.4 NppStatus nppsSubC_16sc_Sfs (const Npp16sc * pSrc, Npp16sc nValue, Npp16sc * pDst, int nLength, int nScaleFactor)

16-bit integer complex number (16 bit real, 16 bit imaginary) signal subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be subtracted from each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.138.2.5 NppStatus nppsSubC_16u_ISfs (Npp16u nValue, Npp16u * pSrcDst, int nLength, int nScaleFactor)

16-bit unsigned short in place signal subtract constant, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be subtracted from each vector element

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.138.2.6 NppStatus nppsSubC_16u_Sfs (const Npp16u * pSrc, Npp16u nValue, Npp16u * pDst, int nLength, int nScaleFactor)

16-bit unsigned short signal subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be subtracted from each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.138.2.7 NppStatus nppsSubC_32f (const Npp32f * pSrc, Npp32f nValue, Npp32f * pDst, int nLength)

32-bit floating point signal subtract constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be subtracted from each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.138.2.8 NppStatus nppsSubC_32f_I (Npp32f nValue, Npp32f * pSrcDst, int nLength)

32-bit floating point in place signal subtract constant.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be subtracted from each vector element

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.138.2.9 NppStatus nppsSubC_32fc (const Npp32fc * pSrc, Npp32fc nValue, Npp32fc * pDst, int nLength)

32-bit floating point complex number (32 bit real, 32 bit imaginary) signal subtract constant.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be subtracted from each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.138.2.10 NppStatus nppsSubC_32fc_I (Npp32fc nValue, Npp32fc * pSrcDst, int nLength)

32-bit floating point complex number (32 bit real, 32 bit imaginary) in place signal subtract constant.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be subtracted from each vector element

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.138.2.11 NppStatus nppsSubC_32s_ISfs (Npp32s nValue, Npp32s * pSrcDst, int nLength, int nScaleFactor)

32-bit signed integer in place signal subtract constant and scale.

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value to be subtracted from each vector element
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.138.2.12 NppStatus nppsSubC_32s_Sfs (const Npp32s * pSrc, Npp32s nValue, Npp32s * pDst, int nLength, int nScaleFactor)

32-bit signed integer signal subtract constant and scale.

Parameters:

pSrc Source Signal Pointer.
nValue Constant value to be subtracted from each vector element
pDst Destination Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.138.2.13 NppStatus nppsSubC_32sc_ISfs (Npp32sc nValue, Npp32sc * pSrcDst, int nLength, int nScaleFactor)

32-bit integer complex number (32 bit real, 32 bit imaginary) in place signal subtract constant and scale.

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value to be subtracted from each vector element
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.138.2.14 NppStatus nppsSubC_32sc_Sfs (const Npp32sc * pSrc, Npp32sc nValue, Npp32sc * pDst, int nLength, int nScaleFactor)

32-bit integer complex number (32 bit real, 32 bit imaginary) signal subtract constant and scale.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be subtracted from each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.138.2.15 NppStatus nppsSubC_64f (const Npp64f * pSrc, Npp64f nValue, Npp64f * pDst, int nLength)

64-bit floating point signal subtract constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be subtracted from each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.138.2.16 NppStatus nppsSubC_64f_I (Npp64f nValue, Npp64f * pSrcDst, int nLength)

64-bit floating point, in place signal subtract constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be subtracted from each vector element

nLength Length of the vectors, number of items.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.138.2.17 NppStatus nppsSubC_64fc (const Npp64fc * pSrc, Npp64fc nValue, Npp64fc * pDst, int nLength)

64-bit floating point complex number (64 bit real, 64 bit imaginary) signal subtract constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be subtracted from each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.138.2.18 NppStatus nppsSubC_64fc_I (Npp64fc nValue, Npp64fc * pSrcDst, int nLength)

64-bit floating point complex number (64 bit real, 64 bit imaginary) in place signal subtract constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be subtracted from each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.138.2.19 NppStatus nppsSubC_8u_ISfs (Npp8u nValue, Npp8u * pSrcDst, int nLength, int nScaleFactor)

8-bit unsigned char in place signal subtract constant, scale, then clamp to saturated value

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be subtracted from each vector element

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.138.2.20 NppStatus nppsSubC_8u_Sfs (const Npp8u * *pSrc*, Npp8u *nValue*, Npp8u * *pDst*, int *nLength*, int *nScaleFactor*)

8-bit unsigned char signal subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be subtracted from each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.139 SubCRev

Subtracts each sample of a signal from a constant.

Functions

- **NppStatus** `nppsSubCRev_8u_ISfs` (**Npp8u** nValue, **Npp8u** *pSrcDst, int nLength, int nScaleFactor)
8-bit unsigned char in place signal subtract from constant, scale, then clamp to saturated value
- **NppStatus** `nppsSubCRev_8u_Sfs` (const **Npp8u** *pSrc, **Npp8u** nValue, **Npp8u** *pDst, int nLength, int nScaleFactor)
8-bit unsigned char signal subtract from constant, scale, then clamp to saturated value.
- **NppStatus** `nppsSubCRev_16u_ISfs` (**Npp16u** nValue, **Npp16u** *pSrcDst, int nLength, int nScaleFactor)
16-bit unsigned short in place signal subtract from constant, scale, then clamp to saturated value.
- **NppStatus** `nppsSubCRev_16u_Sfs` (const **Npp16u** *pSrc, **Npp16u** nValue, **Npp16u** *pDst, int nLength, int nScaleFactor)
16-bit unsigned short signal subtract from constant, scale, then clamp to saturated value.
- **NppStatus** `nppsSubCRev_16s_ISfs` (**Npp16s** nValue, **Npp16s** *pSrcDst, int nLength, int nScaleFactor)
16-bit signed short in place signal subtract from constant, scale, then clamp to saturated value.
- **NppStatus** `nppsSubCRev_16s_Sfs` (const **Npp16s** *pSrc, **Npp16s** nValue, **Npp16s** *pDst, int nLength, int nScaleFactor)
16-bit signed short signal subtract from constant, scale, then clamp to saturated value.
- **NppStatus** `nppsSubCRev_16sc_ISfs` (**Npp16sc** nValue, **Npp16sc** *pSrcDst, int nLength, int nScaleFactor)
16-bit integer complex number (16 bit real, 16 bit imaginary) signal subtract from constant, scale, then clamp to saturated value.
- **NppStatus** `nppsSubCRev_16sc_Sfs` (const **Npp16sc** *pSrc, **Npp16sc** nValue, **Npp16sc** *pDst, int nLength, int nScaleFactor)
16-bit integer complex number (16 bit real, 16 bit imaginary) signal subtract from constant, scale, then clamp to saturated value.
- **NppStatus** `nppsSubCRev_32s_ISfs` (**Npp32s** nValue, **Npp32s** *pSrcDst, int nLength, int nScaleFactor)
32-bit signed integer in place signal subtract from constant and scale.
- **NppStatus** `nppsSubCRev_32s_Sfs` (const **Npp32s** *pSrc, **Npp32s** nValue, **Npp32s** *pDst, int nLength, int nScaleFactor)
32-bit signed integersignal subtract from constant and scale.
- **NppStatus** `nppsSubCRev_32sc_ISfs` (**Npp32sc** nValue, **Npp32sc** *pSrcDst, int nLength, int nScaleFactor)

32-bit integer complex number (32 bit real, 32 bit imaginary) in place signal subtract from constant and scale.

- **NppStatus nppsSubCRev_32sc_Sfs** (const **Npp32sc** *pSrc, **Npp32sc** nValue, **Npp32sc** *pDst, int nLength, int nScaleFactor)
32-bit integer complex number (32 bit real, 32 bit imaginary) signal subtract from constant and scale.
- **NppStatus nppsSubCRev_32f_I** (**Npp32f** nValue, **Npp32f** *pSrcDst, int nLength)
32-bit floating point in place signal subtract from constant.
- **NppStatus nppsSubCRev_32f** (const **Npp32f** *pSrc, **Npp32f** nValue, **Npp32f** *pDst, int nLength)
32-bit floating point signal subtract from constant.
- **NppStatus nppsSubCRev_32fc_I** (**Npp32fc** nValue, **Npp32fc** *pSrcDst, int nLength)
32-bit floating point complex number (32 bit real, 32 bit imaginary) in place signal subtract from constant.
- **NppStatus nppsSubCRev_32fc** (const **Npp32fc** *pSrc, **Npp32fc** nValue, **Npp32fc** *pDst, int nLength)
32-bit floating point complex number (32 bit real, 32 bit imaginary) signal subtract from constant.
- **NppStatus nppsSubCRev_64f_I** (**Npp64f** nValue, **Npp64f** *pSrcDst, int nLength)
64-bit floating point, in place signal subtract from constant.
- **NppStatus nppsSubCRev_64f** (const **Npp64f** *pSrc, **Npp64f** nValue, **Npp64f** *pDst, int nLength)
64-bit floating point signal subtract from constant.
- **NppStatus nppsSubCRev_64fc_I** (**Npp64fc** nValue, **Npp64fc** *pSrcDst, int nLength)
64-bit floating point complex number (64 bit real, 64 bit imaginary) in place signal subtract from constant.
- **NppStatus nppsSubCRev_64fc** (const **Npp64fc** *pSrc, **Npp64fc** nValue, **Npp64fc** *pDst, int nLength)
64-bit floating point complex number (64 bit real, 64 bit imaginary) signal subtract from constant.

7.139.1 Detailed Description

Subtracts each sample of a signal from a constant.

7.139.2 Function Documentation

7.139.2.1 **NppStatus nppsSubCRev_16s_ISfs** (**Npp16s** nValue, **Npp16s** *pSrcDst, int nLength, int nScaleFactor)

16-bit signed short in place signal subtract from constant, scale, then clamp to saturated value.

Parameters:

pSrcDst *In-Place Signal Pointer.*

nValue *Constant value each vector element is to be subtracted from*

nLength *Signal Length.*

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.139.2.2 `NppStatus nppsSubCRev_16s_Sfs (const Npp16s * pSrc, Npp16s nValue, Npp16s * pDst, int nLength, int nScaleFactor)`

16-bit signed short signal subtract from constant, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value each vector element is to be subtracted from

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.139.2.3 `NppStatus nppsSubCRev_16sc_ISfs (Npp16sc nValue, Npp16sc * pSrcDst, int nLength, int nScaleFactor)`

16-bit integer complex number (16 bit real, 16 bit imaginary) signal subtract from constant, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value each vector element is to be subtracted from

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.139.2.4 `NppStatus nppsSubCRev_16sc_Sfs (const Npp16sc * pSrc, Npp16sc nValue, Npp16sc * pDst, int nLength, int nScaleFactor)`

16-bit integer complex number (16 bit real, 16 bit imaginary) signal subtract from constant, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value each vector element is to be subtracted from
pDst Destination Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.139.2.5 NppStatus nppsSubCRev_16u_ISfs (Npp16u nValue, Npp16u * pSrcDst, int nLength, int nScaleFactor)

16-bit unsigned short in place signal subtract from constant, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value each vector element is to be subtracted from
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.139.2.6 NppStatus nppsSubCRev_16u_Sfs (const Npp16u * pSrc, Npp16u nValue, Npp16u * pDst, int nLength, int nScaleFactor)

16-bit unsigned short signal subtract from constant, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.
nValue Constant value each vector element is to be subtracted from
pDst Destination Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.139.2.7 NppStatus nppsSubCRev_32f (const Npp32f * pSrc, Npp32f nValue, Npp32f * pDst, int nLength)

32-bit floating point signal subtract from constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value each vector element is to be subtracted from
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.139.2.8 NppStatus nppsSubCRev_32f_I (Npp32f nValue, Npp32f * pSrcDst, int nLength)

32-bit floating point in place signal subtract from constant.

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value each vector element is to be subtracted from
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.139.2.9 NppStatus nppsSubCRev_32fc (const Npp32fc * pSrc, Npp32fc nValue, Npp32fc * pDst, int nLength)

32-bit floating point complex number (32 bit real, 32 bit imaginary) signal subtract from constant.

Parameters:

pSrc Source Signal Pointer.
nValue Constant value each vector element is to be subtracted from
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.139.2.10 NppStatus nppsSubCRev_32fc_I (Npp32fc nValue, Npp32fc * pSrcDst, int nLength)

32-bit floating point complex number (32 bit real, 32 bit imaginary) in place signal subtract from constant.

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value each vector element is to be subtracted from
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.139.2.11 NppStatus nppsSubCRev_32s_ISfs (Npp32s *nValue*, Npp32s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer in place signal subtract from constant and scale.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value each vector element is to be subtracted from

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.139.2.12 NppStatus nppsSubCRev_32s_Sfs (const Npp32s * *pSrc*, Npp32s *nValue*, Npp32s * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integersignal subtract from constant and scale.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value each vector element is to be subtracted from

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.139.2.13 NppStatus nppsSubCRev_32sc_ISfs (Npp32sc *nValue*, Npp32sc * *pSrcDst*, int *nLength*, int *nScaleFactor*)

32-bit integer complex number (32 bit real, 32 bit imaginary) in place signal subtract from constant and scale.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value each vector element is to be subtracted from

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.139.2.14 NppStatus nppsSubCRev_32sc_Sfs (const Npp32sc * pSrc, Npp32sc nValue, Npp32sc * pDst, int nLength, int nScaleFactor)

32-bit integer complex number (32 bit real, 32 bit imaginary) signal subtract from constant and scale.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value each vector element is to be subtracted from

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.139.2.15 NppStatus nppsSubCRev_64f (const Npp64f * pSrc, Npp64f nValue, Npp64f * pDst, int nLength)

64-bit floating point signal subtract from constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value each vector element is to be subtracted from

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.139.2.16 NppStatus nppsSubCRev_64f_I (Npp64f nValue, Npp64f * pSrcDst, int nLength)

64-bit floating point, in place signal subtract from constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value each vector element is to be subtracted from

nLength Length of the vectors, number of items.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.139.2.17 NppStatus nppsSubCRev_64fc (const Npp64fc * pSrc, Npp64fc nValue, Npp64fc * pDst, int nLength)

64-bit floating point complex number (64 bit real, 64 bit imaginary) signal subtract from constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value each vector element is to be subtracted from

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.139.2.18 NppStatus nppsSubCRev_64fc_I (Npp64fc nValue, Npp64fc * pSrcDst, int nLength)

64-bit floating point complex number (64 bit real, 64 bit imaginary) in place signal subtract from constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value each vector element is to be subtracted from

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.139.2.19 NppStatus nppsSubCRev_8u_ISfs (Npp8u nValue, Npp8u * pSrcDst, int nLength, int nScaleFactor)

8-bit unsigned char in place signal subtract from constant, scale, then clamp to saturated value

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value each vector element is to be subtracted from

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.139.2.20 NppStatus nppsSubCRev_8u_Sfs (const Npp8u * pSrc, Npp8u nValue, Npp8u * pDst, int nLength, int nScaleFactor)

8-bit unsigned char signal subtract from constant, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value each vector element is to be subtracted from

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.140 DivC

Divides each sample of a signal by a constant.

Functions

- **NppStatus nppsDivC_8u_ISfs** (**Npp8u** nValue, **Npp8u** *pSrcDst, int nLength, int nScaleFactor)
8-bit unsigned char in place signal divided by constant, scale, then clamp to saturated value
- **NppStatus nppsDivC_8u_Sfs** (const **Npp8u** *pSrc, **Npp8u** nValue, **Npp8u** *pDst, int nLength, int nScaleFactor)
8-bit unsigned char signal divided by constant, scale, then clamp to saturated value.
- **NppStatus nppsDivC_16u_ISfs** (**Npp16u** nValue, **Npp16u** *pSrcDst, int nLength, int nScaleFactor)
16-bit unsigned short in place signal divided by constant, scale, then clamp to saturated value.
- **NppStatus nppsDivC_16u_Sfs** (const **Npp16u** *pSrc, **Npp16u** nValue, **Npp16u** *pDst, int nLength, int nScaleFactor)
16-bit unsigned short signal divided by constant, scale, then clamp to saturated value.
- **NppStatus nppsDivC_16s_ISfs** (**Npp16s** nValue, **Npp16s** *pSrcDst, int nLength, int nScaleFactor)
16-bit signed short in place signal divided by constant, scale, then clamp to saturated value.
- **NppStatus nppsDivC_16s_Sfs** (const **Npp16s** *pSrc, **Npp16s** nValue, **Npp16s** *pDst, int nLength, int nScaleFactor)
16-bit signed short signal divided by constant, scale, then clamp to saturated value.
- **NppStatus nppsDivC_16sc_ISfs** (**Npp16sc** nValue, **Npp16sc** *pSrcDst, int nLength, int nScaleFactor)
16-bit integer complex number (16 bit real, 16 bit imaginary) signal divided by constant, scale, then clamp to saturated value.
- **NppStatus nppsDivC_16sc_Sfs** (const **Npp16sc** *pSrc, **Npp16sc** nValue, **Npp16sc** *pDst, int nLength, int nScaleFactor)
16-bit integer complex number (16 bit real, 16 bit imaginary) signal divided by constant, scale, then clamp to saturated value.
- **NppStatus nppsDivC_32f_I** (**Npp32f** nValue, **Npp32f** *pSrcDst, int nLength)
32-bit floating point in place signal divided by constant.
- **NppStatus nppsDivC_32f** (const **Npp32f** *pSrc, **Npp32f** nValue, **Npp32f** *pDst, int nLength)
32-bit floating point signal divided by constant.
- **NppStatus nppsDivC_32fc_I** (**Npp32fc** nValue, **Npp32fc** *pSrcDst, int nLength)
32-bit floating point complex number (32 bit real, 32 bit imaginary) in place signal divided by constant.
- **NppStatus nppsDivC_32fc** (const **Npp32fc** *pSrc, **Npp32fc** nValue, **Npp32fc** *pDst, int nLength)
32-bit floating point complex number (32 bit real, 32 bit imaginary) signal divided by constant.
- **NppStatus nppsDivC_64f_I** (**Npp64f** nValue, **Npp64f** *pSrcDst, int nLength)

64-bit floating point in place signal divided by constant.

- **NppStatus nppsDivC_64f** (const **Npp64f** *pSrc, **Npp64f** nValue, **Npp64f** *pDst, int nLength)
64-bit floating point signal divided by constant.
- **NppStatus nppsDivC_64fc_I** (**Npp64fc** nValue, **Npp64fc** *pSrcDst, int nLength)
64-bit floating point complex number (64 bit real, 64 bit imaginary) in place signal divided by constant.
- **NppStatus nppsDivC_64fc** (const **Npp64fc** *pSrc, **Npp64fc** nValue, **Npp64fc** *pDst, int nLength)
64-bit floating point complex number (64 bit real, 64 bit imaginary) signal divided by constant.

7.140.1 Detailed Description

Divides each sample of a signal by a constant.

7.140.2 Function Documentation

7.140.2.1 **NppStatus nppsDivC_16s_ISfs** (**Npp16s** nValue, **Npp16s** *pSrcDst, int nLength, int nScaleFactor)

16-bit signed short in place signal divided by constant, scale, then clamp to saturated value.

Parameters:

- pSrcDst** In-Place Signal Pointer.
- nValue** Constant value to be divided into each vector element
- nLength** Signal Length.
- nScaleFactor** Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.140.2.2 **NppStatus nppsDivC_16s_Sfs** (const **Npp16s** *pSrc, **Npp16s** nValue, **Npp16s** *pDst, int nLength, int nScaleFactor)

16-bit signed short signal divided by constant, scale, then clamp to saturated value.

Parameters:

- pSrc** Source Signal Pointer.
- nValue** Constant value to be divided into each vector element
- pDst** Destination Signal Pointer.
- nLength** Signal Length.
- nScaleFactor** Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.140.2.3 `NppStatus nppsDivC_16sc_ISfs` (`Npp16sc nValue`, `Npp16sc * pSrcDst`, `int nLength`, `int nScaleFactor`)

16-bit integer complex number (16 bit real, 16 bit imaginary) signal divided by constant, scale, then clamp to saturated value.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be divided into each vector element

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.140.2.4 `NppStatus nppsDivC_16sc_Sfs` (`const Npp16sc * pSrc`, `Npp16sc nValue`, `Npp16sc * pDst`, `int nLength`, `int nScaleFactor`)

16-bit integer complex number (16 bit real, 16 bit imaginary) signal divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be divided into each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.140.2.5 `NppStatus nppsDivC_16u_ISfs` (`Npp16u nValue`, `Npp16u * pSrcDst`, `int nLength`, `int nScaleFactor`)

16-bit unsigned short in place signal divided by constant, scale, then clamp to saturated value.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be divided into each vector element

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.140.2.6 NppStatus nppsDivC_16u_Sfs (const Npp16u * pSrc, Npp16u nValue, Npp16u * pDst, int nLength, int nScaleFactor)

16-bit unsigned short signal divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be divided into each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.140.2.7 NppStatus nppsDivC_32f (const Npp32f * pSrc, Npp32f nValue, Npp32f * pDst, int nLength)

32-bit floating point signal divided by constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be divided into each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.140.2.8 NppStatus nppsDivC_32f_I (Npp32f nValue, Npp32f * pSrcDst, int nLength)

32-bit floating point in place signal divided by constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be divided into each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.140.2.9 NppStatus nppsDivC_32fc (const Npp32fc * pSrc, Npp32fc nValue, Npp32fc * pDst, int nLength)

32-bit floating point complex number (32 bit real, 32 bit imaginary) signal divided by constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be divided into each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.140.2.10 NppStatus nppsDivC_32fc_I (Npp32fc nValue, Npp32fc * pSrcDst, int nLength)

32-bit floating point complex number (32 bit real, 32 bit imaginary) in place signal divided by constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be divided into each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.140.2.11 NppStatus nppsDivC_64f (const Npp64f * pSrc, Npp64f nValue, Npp64f * pDst, int nLength)

64-bit floating point signal divided by constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be divided into each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.140.2.12 NppStatus nppsDivC_64f_I (Npp64f nValue, Npp64f * pSrcDst, int nLength)

64-bit floating point in place signal divided by constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be divided into each vector element

nLength Length of the vectors, number of items.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.140.2.13 NppStatus nppsDivC_64fc (const Npp64fc * pSrc, Npp64fc nValue, Npp64fc * pDst, int nLength)

64-bit floating point complex number (64 bit real, 64 bit imaginary) signal divided by constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be divided into each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.140.2.14 NppStatus nppsDivC_64fc_I (Npp64fc nValue, Npp64fc * pSrcDst, int nLength)

64-bit floating point complex number (64 bit real, 64 bit imaginary) in place signal divided by constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be divided into each vector element

nLength Signal Length.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.140.2.15 NppStatus nppsDivC_8u_ISfs (Npp8u nValue, Npp8u * pSrcDst, int nLength, int nScaleFactor)

8-bit unsigned char in place signal divided by constant, scale, then clamp to saturated value

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be divided into each vector element

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.140.2.16 NppStatus nppsDivC_8u_Sfs (const Npp8u * pSrc, Npp8u nValue, Npp8u * pDst, int nLength, int nScaleFactor)

8-bit unsigned char signal divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be divided into each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.141 DivCRev

Divides a constant by each sample of a signal.

Functions

- `NppStatus nppsDivCRev_16u_I(Npp16u nValue, Npp16u *pSrcDst, int nLength)`
16-bit unsigned short in place constant divided by signal, then clamp to saturated value.
- `NppStatus nppsDivCRev_16u(const Npp16u *pSrc, Npp16u nValue, Npp16u *pDst, int nLength)`
16-bit unsigned short signal divided by constant, then clamp to saturated value.
- `NppStatus nppsDivCRev_32f_I(Npp32f nValue, Npp32f *pSrcDst, int nLength)`
32-bit floating point in place constant divided by signal.
- `NppStatus nppsDivCRev_32f(const Npp32f *pSrc, Npp32f nValue, Npp32f *pDst, int nLength)`
32-bit floating point constant divided by signal.

7.141.1 Detailed Description

Divides a constant by each sample of a signal.

7.141.2 Function Documentation

7.141.2.1 `NppStatus nppsDivCRev_16u(const Npp16u *pSrc, Npp16u nValue, Npp16u *pDst, int nLength)`

16-bit unsigned short signal divided by constant, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be divided by each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.141.2.2 `NppStatus nppsDivCRev_16u_I(Npp16u nValue, Npp16u *pSrcDst, int nLength)`

16-bit unsigned short in place constant divided by signal, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be divided by each vector element
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.141.2.3 NppStatus nppsDivCRev_32f (const Npp32f * pSrc, Npp32f nValue, Npp32f * pDst, int nLength)

32-bit floating point constant divided by signal.

Parameters:

pSrc Source Signal Pointer.
nValue Constant value to be divided by each vector element
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.141.2.4 NppStatus nppsDivCRev_32f_I (Npp32f nValue, Npp32f * pSrcDst, int nLength)

32-bit floating point in place constant divided by signal.

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value to be divided by each vector element
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142 Add

Sample by sample addition of two signals.

Functions

- **NppStatus** `nppsAdd_16s` (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp16s** *pDst, int nLength)
16-bit signed short signal add signal, then clamp to saturated value.
- **NppStatus** `nppsAdd_16u` (const **Npp16u** *pSrc1, const **Npp16u** *pSrc2, **Npp16u** *pDst, int nLength)
16-bit unsigned short signal add signal, then clamp to saturated value.
- **NppStatus** `nppsAdd_32u` (const **Npp32u** *pSrc1, const **Npp32u** *pSrc2, **Npp32u** *pDst, int nLength)
32-bit unsigned int signal add signal, then clamp to saturated value.
- **NppStatus** `nppsAdd_32f` (const **Npp32f** *pSrc1, const **Npp32f** *pSrc2, **Npp32f** *pDst, int nLength)
32-bit floating point signal add signal, then clamp to saturated value.
- **NppStatus** `nppsAdd_64f` (const **Npp64f** *pSrc1, const **Npp64f** *pSrc2, **Npp64f** *pDst, int nLength)
64-bit floating point signal add signal, then clamp to saturated value.
- **NppStatus** `nppsAdd_32fc` (const **Npp32fc** *pSrc1, const **Npp32fc** *pSrc2, **Npp32fc** *pDst, int nLength)
32-bit complex floating point signal add signal, then clamp to saturated value.
- **NppStatus** `nppsAdd_64fc` (const **Npp64fc** *pSrc1, const **Npp64fc** *pSrc2, **Npp64fc** *pDst, int nLength)
64-bit complex floating point signal add signal, then clamp to saturated value.
- **NppStatus** `nppsAdd_8u16u` (const **Npp8u** *pSrc1, const **Npp8u** *pSrc2, **Npp16u** *pDst, int nLength)
8-bit unsigned char signal add signal with 16-bit unsigned result, then clamp to saturated value.
- **NppStatus** `nppsAdd_16s32f` (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp32f** *pDst, int nLength)
16-bit signed short signal add signal with 32-bit floating point result, then clamp to saturated value.
- **NppStatus** `nppsAdd_8u_Sfs` (const **Npp8u** *pSrc1, const **Npp8u** *pSrc2, **Npp8u** *pDst, int nLength, int nScaleFactor)
8-bit unsigned char add signal, scale, then clamp to saturated value.
- **NppStatus** `nppsAdd_16u_Sfs` (const **Npp16u** *pSrc1, const **Npp16u** *pSrc2, **Npp16u** *pDst, int nLength, int nScaleFactor)
16-bit unsigned short add signal, scale, then clamp to saturated value.
- **NppStatus** `nppsAdd_16s_Sfs` (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp16s** *pDst, int nLength, int nScaleFactor)

16-bit signed short add signal, scale, then clamp to saturated value.

- `NppStatus nppsAdd_32s_Sfs` (const `Npp32s` *pSrc1, const `Npp32s` *pSrc2, `Npp32s` *pDst, int nLength, int nScaleFactor)

32-bit signed integer add signal, scale, then clamp to saturated value.

- `NppStatus nppsAdd_64s_Sfs` (const `Npp64s` *pSrc1, const `Npp64s` *pSrc2, `Npp64s` *pDst, int nLength, int nScaleFactor)

64-bit signed integer add signal, scale, then clamp to saturated value.

- `NppStatus nppsAdd_16sc_Sfs` (const `Npp16sc` *pSrc1, const `Npp16sc` *pSrc2, `Npp16sc` *pDst, int nLength, int nScaleFactor)

16-bit signed complex short add signal, scale, then clamp to saturated value.

- `NppStatus nppsAdd_32sc_Sfs` (const `Npp32sc` *pSrc1, const `Npp32sc` *pSrc2, `Npp32sc` *pDst, int nLength, int nScaleFactor)

32-bit signed complex integer add signal, scale, then clamp to saturated value.

- `NppStatus nppsAdd_16s_I` (const `Npp16s` *pSrc, `Npp16s` *pSrcDst, int nLength)

16-bit signed short in place signal add signal, then clamp to saturated value.

- `NppStatus nppsAdd_32f_I` (const `Npp32f` *pSrc, `Npp32f` *pSrcDst, int nLength)

32-bit floating point in place signal add signal, then clamp to saturated value.

- `NppStatus nppsAdd_64f_I` (const `Npp64f` *pSrc, `Npp64f` *pSrcDst, int nLength)

64-bit floating point in place signal add signal, then clamp to saturated value.

- `NppStatus nppsAdd_32fc_I` (const `Npp32fc` *pSrc, `Npp32fc` *pSrcDst, int nLength)

32-bit complex floating point in place signal add signal, then clamp to saturated value.

- `NppStatus nppsAdd_64fc_I` (const `Npp64fc` *pSrc, `Npp64fc` *pSrcDst, int nLength)

64-bit complex floating point in place signal add signal, then clamp to saturated value.

- `NppStatus nppsAdd_16s32s_I` (const `Npp16s` *pSrc, `Npp32s` *pSrcDst, int nLength)

16/32-bit signed short in place signal add signal with 32-bit signed integer results, then clamp to saturated value.

- `NppStatus nppsAdd_8u_ISfs` (const `Npp8u` *pSrc, `Npp8u` *pSrcDst, int nLength, int nScaleFactor)

8-bit unsigned char in place signal add signal, with scaling, then clamp to saturated value.

- `NppStatus nppsAdd_16u_ISfs` (const `Npp16u` *pSrc, `Npp16u` *pSrcDst, int nLength, int nScaleFactor)

16-bit unsigned short in place signal add signal, with scaling, then clamp to saturated value.

- `NppStatus nppsAdd_16s_ISfs` (const `Npp16s` *pSrc, `Npp16s` *pSrcDst, int nLength, int nScaleFactor)

16-bit signed short in place signal add signal, with scaling, then clamp to saturated value.

- `NppStatus nppsAdd_32s_ISfs` (const `Npp32s` *pSrc, `Npp32s` *pSrcDst, int nLength, int nScaleFactor)

32-bit signed integer in place signal add signal, with scaling, then clamp to saturated value.

- `NppStatus nppsAdd_16sc_ISfs` (const `Npp16sc *pSrc`, `Npp16sc *pSrcDst`, int `nLength`, int `nScaleFactor`)
16-bit complex signed short in place signal add signal, with scaling, then clamp to saturated value.
- `NppStatus nppsAdd_32sc_ISfs` (const `Npp32sc *pSrc`, `Npp32sc *pSrcDst`, int `nLength`, int `nScaleFactor`)
32-bit complex signed integer in place signal add signal, with scaling, then clamp to saturated value.

7.142.1 Detailed Description

Sample by sample addition of two signals.

7.142.2 Function Documentation

7.142.2.1 `NppStatus nppsAdd_16s` (const `Npp16s *pSrc1`, const `Npp16s *pSrc2`, `Npp16s *pDst`, int `nLength`)

16-bit signed short signal add signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be added to signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.2 `NppStatus nppsAdd_16s32f` (const `Npp16s *pSrc1`, const `Npp16s *pSrc2`, `Npp32f *pDst`, int `nLength`)

16-bit signed short signal add signal with 32-bit floating point result, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be added to signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.3 NppStatus nppsAdd_16s32s_I (const Npp16s * pSrc, Npp32s * pSrcDst, int nLength)

16/32-bit signed short in place signal add signal with 32-bit signed integer results, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be added to signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.4 NppStatus nppsAdd_16s_I (const Npp16s * pSrc, Npp16s * pSrcDst, int nLength)

16-bit signed short in place signal add signal, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be added to signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.5 NppStatus nppsAdd_16s_ISfs (const Npp16s * pSrc, Npp16s * pSrcDst, int nLength, int nScaleFactor)

16-bit signed short in place signal add signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be added to signal1 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.6 NppStatus nppsAdd_16s_Sfs (const Npp16s * pSrc1, const Npp16s * pSrc2, Npp16s * pDst, int nLength, int nScaleFactor)

16-bit signed short add signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal2 elements to be added to signal1 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.7 NppStatus nppsAdd_16sc_ISfs (const Npp16sc * pSrc, Npp16sc * pSrcDst, int nLength, int nScaleFactor)

16-bit complex signed short in place signal add signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be added to signal1 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.8 NppStatus nppsAdd_16sc_Sfs (const Npp16sc * pSrc1, const Npp16sc * pSrc2, Npp16sc * pDst, int nLength, int nScaleFactor)

16-bit signed complex short add signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal2 elements to be added to signal1 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.9 NppStatus nppsAdd_16u (const Npp16u * pSrc1, const Npp16u * pSrc2, Npp16u * pDst, int nLength)

16-bit unsigned short signal add signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be added to signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.10 NppStatus nppsAdd_16u_ISfs (const Npp16u * pSrc, Npp16u * pSrcDst, int nLength, int nScaleFactor)

16-bit unsigned short in place signal add signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be added to signal1 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.11 NppStatus nppsAdd_16u_Sfs (const Npp16u * pSrc1, const Npp16u * pSrc2, Npp16u * pDst, int nLength, int nScaleFactor)

16-bit unsigned short add signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal2 elements to be added to signal1 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.12 NppStatus nppsAdd_32f (const Npp32f * pSrc1, const Npp32f * pSrc2, Npp32f * pDst, int nLength)

32-bit floating point signal add signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be added to signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.13 NppStatus nppsAdd_32f_I (const Npp32f * pSrc, Npp32f * pSrcDst, int nLength)

32-bit floating point in place signal add signal, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be added to signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.14 NppStatus nppsAdd_32fc (const Npp32fc * pSrc1, const Npp32fc * pSrc2, Npp32fc * pDst, int nLength)

32-bit complex floating point signal add signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be added to signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.15 NppStatus nppsAdd_32fc_I (const Npp32fc * pSrc, Npp32fc * pSrcDst, int nLength)

32-bit complex floating point in place signal add signal, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be added to signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.16 NppStatus nppsAdd_32s_ISfs (const Npp32s * pSrc, Npp32s * pSrcDst, int nLength, int nScaleFactor)

32-bit signed integer in place signal add signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be added to signal1 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.17 NppStatus nppsAdd_32s_Sfs (const Npp32s * pSrc1, const Npp32s * pSrc2, Npp32s * pDst, int nLength, int nScaleFactor)

32-bit signed integer add signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal2 elements to be added to signal1 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.18 NppStatus nppsAdd_32sc_ISfs (const Npp32sc * pSrc, Npp32sc * pSrcDst, int nLength, int nScaleFactor)

32-bit complex signed integer in place signal add signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be added to signal1 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.19 NppStatus nppsAdd_32sc_Sfs (const Npp32sc * pSrc1, const Npp32sc * pSrc2, Npp32sc * pDst, int nLength, int nScaleFactor)

32-bit signed complex integer add signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal2 elements to be added to signal1 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.20 NppStatus nppsAdd_32u (const Npp32u * pSrc1, const Npp32u * pSrc2, Npp32u * pDst, int nLength)

32-bit unsigned int signal add signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be added to signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.21 NppStatus nppsAdd_64f (const Npp64f * pSrc1, const Npp64f * pSrc2, Npp64f * pDst, int nLength)

64-bit floating point signal add signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be added to signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.22 NppStatus nppsAdd_64f_I (const Npp64f * pSrc, Npp64f * pSrcDst, int nLength)

64-bit floating point in place signal add signal, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be added to signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.23 NppStatus nppsAdd_64fc (const Npp64fc * pSrc1, const Npp64fc * pSrc2, Npp64fc * pDst, int nLength)

64-bit complex floating point signal add signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be added to signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.24 NppStatus nppsAdd_64fc_I (const Npp64fc * pSrc, Npp64fc * pSrcDst, int nLength)

64-bit complex floating point in place signal add signal, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be added to signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.25 NppStatus nppsAdd_64s_Sfs (const Npp64s * pSrc1, const Npp64s * pSrc2, Npp64s * pDst, int nLength, int nScaleFactor)

64-bit signed integer add signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal2 elements to be added to signal1 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.26 NppStatus nppsAdd_8u16u (const Npp8u * pSrc1, const Npp8u * pSrc2, Npp16u * pDst, int nLength)

8-bit unsigned char signal add signal with 16-bit unsigned result, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be added to signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.27 NppStatus nppsAdd_8u_ISfs (const Npp8u * pSrc, Npp8u * pSrcDst, int nLength, int nScaleFactor)

8-bit unsigned char in place signal add signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be added to signal1 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.142.2.28 NppStatus nppsAdd_8u_Sfs (const Npp8u * pSrc1, const Npp8u * pSrc2, Npp8u * pDst, int nLength, int nScaleFactor)

8-bit unsigned char add signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal2 elements to be added to signal1 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.143 AddProduct

Adds sample by sample product of two signals to the destination signal.

Functions

- NppStatus** `nppsAddProduct_32f` (const **Npp32f** *pSrc1, const **Npp32f** *pSrc2, **Npp32f** *pDst, int nLength)

32-bit floating point signal add product of source signal times destination signal to destination signal, then clamp to saturated value.
- NppStatus** `nppsAddProduct_64f` (const **Npp64f** *pSrc1, const **Npp64f** *pSrc2, **Npp64f** *pDst, int nLength)

64-bit floating point signal add product of source signal times destination signal to destination signal, then clamp to saturated value.
- NppStatus** `nppsAddProduct_32fc` (const **Npp32fc** *pSrc1, const **Npp32fc** *pSrc2, **Npp32fc** *pDst, int nLength)

32-bit complex floating point signal add product of source signal times destination signal to destination signal, then clamp to saturated value.
- NppStatus** `nppsAddProduct_64fc` (const **Npp64fc** *pSrc1, const **Npp64fc** *pSrc2, **Npp64fc** *pDst, int nLength)

64-bit complex floating point signal add product of source signal times destination signal to destination signal, then clamp to saturated value.
- NppStatus** `nppsAddProduct_16s_Sfs` (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp16s** *pDst, int nLength, int nScaleFactor)

16-bit signed short signal add product of source signal1 times source signal2 to destination signal, with scaling, then clamp to saturated value.
- NppStatus** `nppsAddProduct_32s_Sfs` (const **Npp32s** *pSrc1, const **Npp32s** *pSrc2, **Npp32s** *pDst, int nLength, int nScaleFactor)

32-bit signed short signal add product of source signal1 times source signal2 to destination signal, with scaling, then clamp to saturated value.
- NppStatus** `nppsAddProduct_16s32s_Sfs` (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp32s** *pDst, int nLength, int nScaleFactor)

16-bit signed short signal add product of source signal1 times source signal2 to 32-bit signed integer destination signal, with scaling, then clamp to saturated value.

7.143.1 Detailed Description

Adds sample by sample product of two signals to the destination signal.

7.143.2 Function Documentation

7.143.2.1 `NppStatus nppsAddProduct_16s32s_Sfs (const Npp16s * pSrc1, const Npp16s * pSrc2, Npp32s * pDst, int nLength, int nScaleFactor)`

16-bit signed short signal add product of source signal1 times source signal2 to 32-bit signed integer destination signal, with scaling, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

pDst Destination Signal Pointer. product of source1 and source2 signal elements to be added to destination elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.143.2.2 `NppStatus nppsAddProduct_16s_Sfs (const Npp16s * pSrc1, const Npp16s * pSrc2, Npp16s * pDst, int nLength, int nScaleFactor)`

16-bit signed short signal add product of source signal1 times source signal2 to destination signal, with scaling, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

pDst Destination Signal Pointer. product of source1 and source2 signal elements to be added to destination elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.143.2.3 `NppStatus nppsAddProduct_32f (const Npp32f * pSrc1, const Npp32f * pSrc2, Npp32f * pDst, int nLength)`

32-bit floating point signal add product of source signal times destination signal to destination signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

pDst [Destination Signal Pointer](#). product of source1 and source2 signal elements to be added to destination elements

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.143.2.4 `NppStatus nppsAddProduct_32fc (const Npp32fc * pSrc1, const Npp32fc * pSrc2, Npp32fc * pDst, int nLength)`

32-bit complex floating point signal add product of source signal times destination signal to destination signal, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#).

pDst [Destination Signal Pointer](#). product of source1 and source2 signal elements to be added to destination elements

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.143.2.5 `NppStatus nppsAddProduct_32s_Sfs (const Npp32s * pSrc1, const Npp32s * pSrc2, Npp32s * pDst, int nLength, int nScaleFactor)`

32-bit signed short signal add product of source signal1 times source signal2 to destination signal, with scaling, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#).

pDst [Destination Signal Pointer](#). product of source1 and source2 signal elements to be added to destination elements

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.143.2.6 NppStatus nppsAddProduct_64f (const Npp64f * pSrc1, const Npp64f * pSrc2, Npp64f * pDst, int nLength)

64-bit floating point signal add product of source signal times destination signal to destination signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

pDst Destination Signal Pointer. product of source1 and source2 signal elements to be added to destination elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.143.2.7 NppStatus nppsAddProduct_64fc (const Npp64fc * pSrc1, const Npp64fc * pSrc2, Npp64fc * pDst, int nLength)

64-bit complex floating point signal add product of source signal times destination signal to destination signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

pDst Destination Signal Pointer. product of source1 and source2 signal elements to be added to destination elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144 Mul

Sample by sample multiplication the samples of two signals.

Functions

- **NppStatus nppsMul_16s** (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp16s** *pDst, int nLength)
16-bit signed short signal times signal, then clamp to saturated value.
- **NppStatus nppsMul_32f** (const **Npp32f** *pSrc1, const **Npp32f** *pSrc2, **Npp32f** *pDst, int nLength)
32-bit floating point signal times signal, then clamp to saturated value.
- **NppStatus nppsMul_64f** (const **Npp64f** *pSrc1, const **Npp64f** *pSrc2, **Npp64f** *pDst, int nLength)
64-bit floating point signal times signal, then clamp to saturated value.
- **NppStatus nppsMul_32fc** (const **Npp32fc** *pSrc1, const **Npp32fc** *pSrc2, **Npp32fc** *pDst, int nLength)
32-bit complex floating point signal times signal, then clamp to saturated value.
- **NppStatus nppsMul_64fc** (const **Npp64fc** *pSrc1, const **Npp64fc** *pSrc2, **Npp64fc** *pDst, int nLength)
64-bit complex floating point signal times signal, then clamp to saturated value.
- **NppStatus nppsMul_8u16u** (const **Npp8u** *pSrc1, const **Npp8u** *pSrc2, **Npp16u** *pDst, int nLength)
8-bit unsigned char signal times signal with 16-bit unsigned result, then clamp to saturated value.
- **NppStatus nppsMul_16s32f** (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp32f** *pDst, int nLength)
16-bit signed short signal times signal with 32-bit floating point result, then clamp to saturated value.
- **NppStatus nppsMul_32f32fc** (const **Npp32f** *pSrc1, const **Npp32fc** *pSrc2, **Npp32fc** *pDst, int nLength)
32-bit floating point signal times 32-bit complex floating point signal with complex 32-bit floating point result, then clamp to saturated value.
- **NppStatus nppsMul_8u_Sfs** (const **Npp8u** *pSrc1, const **Npp8u** *pSrc2, **Npp8u** *pDst, int nLength, int nScaleFactor)
8-bit unsigned char signal times signal, scale, then clamp to saturated value.
- **NppStatus nppsMul_16u_Sfs** (const **Npp16u** *pSrc1, const **Npp16u** *pSrc2, **Npp16u** *pDst, int nLength, int nScaleFactor)
16-bit unsigned short signal time signal, scale, then clamp to saturated value.
- **NppStatus nppsMul_16s_Sfs** (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp16s** *pDst, int nLength, int nScaleFactor)
16-bit signed short signal times signal, scale, then clamp to saturated value.
- **NppStatus nppsMul_32s_Sfs** (const **Npp32s** *pSrc1, const **Npp32s** *pSrc2, **Npp32s** *pDst, int nLength, int nScaleFactor)

32-bit signed integer signal times signal, scale, then clamp to saturated value.

- `NppStatus nppsMul_16sc_Sfs` (const `Npp16sc` *pSrc1, const `Npp16sc` *pSrc2, `Npp16sc` *pDst, int nLength, int nScaleFactor)

16-bit signed complex short signal times signal, scale, then clamp to saturated value.

- `NppStatus nppsMul_32sc_Sfs` (const `Npp32sc` *pSrc1, const `Npp32sc` *pSrc2, `Npp32sc` *pDst, int nLength, int nScaleFactor)

32-bit signed complex integer signal times signal, scale, then clamp to saturated value.

- `NppStatus nppsMul_16u16s_Sfs` (const `Npp16u` *pSrc1, const `Npp16s` *pSrc2, `Npp16s` *pDst, int nLength, int nScaleFactor)

16-bit unsigned short signal times 16-bit signed short signal, scale, then clamp to 16-bit signed saturated value.

- `NppStatus nppsMul_16s32s_Sfs` (const `Npp16s` *pSrc1, const `Npp16s` *pSrc2, `Npp32s` *pDst, int nLength, int nScaleFactor)

16-bit signed short signal times signal, scale, then clamp to 32-bit signed saturated value.

- `NppStatus nppsMul_32s32sc_Sfs` (const `Npp32s` *pSrc1, const `Npp32sc` *pSrc2, `Npp32sc` *pDst, int nLength, int nScaleFactor)

32-bit signed integer signal times 32-bit complex signed integer signal, scale, then clamp to 32-bit complex integer saturated value.

- `NppStatus nppsMul_Low_32s_Sfs` (const `Npp32s` *pSrc1, const `Npp32s` *pSrc2, `Npp32s` *pDst, int nLength, int nScaleFactor)

32-bit signed integer signal times signal, scale, then clamp to saturated value.

- `NppStatus nppsMul_16s_I` (const `Npp16s` *pSrc, `Npp16s` *pSrcDst, int nLength)

16-bit signed short in place signal times signal, then clamp to saturated value.

- `NppStatus nppsMul_32f_I` (const `Npp32f` *pSrc, `Npp32f` *pSrcDst, int nLength)

32-bit floating point in place signal times signal, then clamp to saturated value.

- `NppStatus nppsMul_64f_I` (const `Npp64f` *pSrc, `Npp64f` *pSrcDst, int nLength)

64-bit floating point in place signal times signal, then clamp to saturated value.

- `NppStatus nppsMul_32fc_I` (const `Npp32fc` *pSrc, `Npp32fc` *pSrcDst, int nLength)

32-bit complex floating point in place signal times signal, then clamp to saturated value.

- `NppStatus nppsMul_64fc_I` (const `Npp64fc` *pSrc, `Npp64fc` *pSrcDst, int nLength)

64-bit complex floating point in place signal times signal, then clamp to saturated value.

- `NppStatus nppsMul_32f32fc_I` (const `Npp32f` *pSrc, `Npp32fc` *pSrcDst, int nLength)

32-bit complex floating point in place signal times 32-bit floating point signal, then clamp to 32-bit complex floating point saturated value.

- `NppStatus nppsMul_8u_ISfs` (const `Npp8u` *pSrc, `Npp8u` *pSrcDst, int nLength, int nScaleFactor)

8-bit unsigned char in place signal times signal, with scaling, then clamp to saturated value.

- **NppStatus nppsMul_16u_ISfs** (const **Npp16u** *pSrc, **Npp16u** *pSrcDst, int nLength, int nScaleFactor)
16-bit unsigned short in place signal times signal, with scaling, then clamp to saturated value.
- **NppStatus nppsMul_16s_ISfs** (const **Npp16s** *pSrc, **Npp16s** *pSrcDst, int nLength, int nScaleFactor)
16-bit signed short in place signal times signal, with scaling, then clamp to saturated value.
- **NppStatus nppsMul_32s_ISfs** (const **Npp32s** *pSrc, **Npp32s** *pSrcDst, int nLength, int nScaleFactor)
32-bit signed integer in place signal times signal, with scaling, then clamp to saturated value.
- **NppStatus nppsMul_16sc_ISfs** (const **Npp16sc** *pSrc, **Npp16sc** *pSrcDst, int nLength, int nScaleFactor)
16-bit complex signed short in place signal times signal, with scaling, then clamp to saturated value.
- **NppStatus nppsMul_32sc_ISfs** (const **Npp32sc** *pSrc, **Npp32sc** *pSrcDst, int nLength, int nScaleFactor)
32-bit complex signed integer in place signal times signal, with scaling, then clamp to saturated value.
- **NppStatus nppsMul_32s32sc_ISfs** (const **Npp32s** *pSrc, **Npp32sc** *pSrcDst, int nLength, int nScaleFactor)
32-bit complex signed integer in place signal times 32-bit signed integer signal, with scaling, then clamp to saturated value.

7.144.1 Detailed Description

Sample by sample multiplication the samples of two signals.

7.144.2 Function Documentation

7.144.2.1 **NppStatus nppsMul_16s** (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp16s** *pDst, int nLength)

16-bit signed short signal times signal, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#). signal2 elements to be multiplied by signal1 elements

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.144.2.2 NppStatus nppsMul_16s32f (const Npp16s * pSrc1, const Npp16s * pSrc2, Npp32f * pDst, int nLength)

16-bit signed short signal times signal with 32-bit floating point result, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be multiplied by signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.3 NppStatus nppsMul_16s32s_Sfs (const Npp16s * pSrc1, const Npp16s * pSrc2, Npp32s * pDst, int nLength, int nScaleFactor)

16-bit signed short signal times signal, scale, then clamp to 32-bit signed saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal2 elements to be multiplied by signal1 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.4 NppStatus nppsMul_16s_I (const Npp16s * pSrc, Npp16s * pSrcDst, int nLength)

16-bit signed short in place signal times signal, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be multiplied by signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.5 NppStatus nppsMul_16s_ISfs (const Npp16s * pSrc, Npp16s * pSrcDst, int nLength, int nScaleFactor)

16-bit signed short in place signal times signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be multiplied by signal1 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.6 NppStatus nppsMul_16s_Sfs (const Npp16s * pSrc1, const Npp16s * pSrc2, Npp16s * pDst, int nLength, int nScaleFactor)

16-bit signed short signal times signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal2 elements to be multiplied by signal1 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.7 NppStatus nppsMul_16sc_ISfs (const Npp16sc * pSrc, Npp16sc * pSrcDst, int nLength, int nScaleFactor)

16-bit complex signed short in place signal times signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be multiplied by signal1 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.8 NppStatus nppsMul_16sc_Sfs (const Npp16sc * pSrc1, const Npp16sc * pSrc2, Npp16sc * pDst, int nLength, int nScaleFactor)

16-bit signed complex short signal times signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal2 elements to be multiplied by signal1 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.9 NppStatus nppsMul_16u16s_Sfs (const Npp16u * pSrc1, const Npp16s * pSrc2, Npp16s * pDst, int nLength, int nScaleFactor)

16-bit unsigned short signal times 16-bit signed short signal, scale, then clamp to 16-bit signed saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal2 elements to be multiplied by signal1 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.10 NppStatus nppsMul_16u_ISfs (const Npp16u * pSrc, Npp16u * pSrcDst, int nLength, int nScaleFactor)

16-bit unsigned short in place signal times signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be multiplied by signal1 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.11 NppStatus nppsMul_16u_Sfs (const Npp16u * pSrc1, const Npp16u * pSrc2, Npp16u * pDst, int nLength, int nScaleFactor)

16-bit unsigned short signal time signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal2 elements to be multiplied by signal1 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.12 NppStatus nppsMul_32f (const Npp32f * pSrc1, const Npp32f * pSrc2, Npp32f * pDst, int nLength)

32-bit floating point signal times signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal2 elements to be multiplied by signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.13 NppStatus nppsMul_32f32fc (const Npp32f * pSrc1, const Npp32fc * pSrc2, Npp32fc * pDst, int nLength)

32-bit floating point signal times 32-bit complex floating point signal with complex 32-bit floating point result, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal2 elements to be multiplied by signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.14 NppStatus nppsMul_32f32fc_I (const Npp32f * pSrc, Npp32fc * pSrcDst, int nLength)

32-bit complex floating point in place signal times 32-bit floating point signal, then clamp to 32-bit complex floating point saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be multiplied by signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.15 NppStatus nppsMul_32f_I (const Npp32f * pSrc, Npp32f * pSrcDst, int nLength)

32-bit floating point in place signal times signal, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be multiplied by signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.16 NppStatus nppsMul_32fc (const Npp32fc * pSrc1, const Npp32fc * pSrc2, Npp32fc * pDst, int nLength)

32-bit complex floating point signal times signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be multiplied by signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.17 NppStatus nppsMul_32fc_I (const Npp32fc * pSrc, Npp32fc * pSrcDst, int nLength)

32-bit complex floating point in place signal times signal, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be multiplied by signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.18 NppStatus nppsMul_32s32sc_ISfs (const Npp32s * pSrc, Npp32sc * pSrcDst, int nLength, int nScaleFactor)

32-bit complex signed integer in place signal times 32-bit signed integer signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be multiplied by signal1 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.19 NppStatus nppsMul_32s32sc_Sfs (const Npp32s * pSrc1, const Npp32sc * pSrc2, Npp32sc * pDst, int nLength, int nScaleFactor)

32-bit signed integer signal times 32-bit complex signed integer signal, scale, then clamp to 32-bit complex integer saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal2 elements to be multiplied by signal1 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.20 NppStatus nppsMul_32s_ISfs (const Npp32s * pSrc, Npp32s * pSrcDst, int nLength, int nScaleFactor)

32-bit signed integer in place signal times signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be multiplied by signal1 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.21 NppStatus nppsMul_32s_Sfs (const Npp32s * pSrc1, const Npp32s * pSrc2, Npp32s * pDst, int nLength, int nScaleFactor)

32-bit signed integer signal times signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal2 elements to be multiplied by signal1 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.22 NppStatus nppsMul_32sc_ISfs (const Npp32sc * pSrc, Npp32sc * pSrcDst, int nLength, int nScaleFactor)

32-bit complex signed integer in place signal times signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be multiplied by signal1 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.23 NppStatus nppsMul_32sc_Sfs (const Npp32sc * pSrc1, const Npp32sc * pSrc2, Npp32sc * pDst, int nLength, int nScaleFactor)

32-bit signed complex integer signal times signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal2 elements to be multiplied by signal1 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.24 NppStatus nppsMul_64f (const Npp64f * pSrc1, const Npp64f * pSrc2, Npp64f * pDst, int nLength)

64-bit floating point signal times signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal2 elements to be multiplied by signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.25 NppStatus nppsMul_64f_I (const Npp64f * pSrc, Npp64f * pSrcDst, int nLength)

64-bit floating point in place signal times signal, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer, signal2 elements to be multiplied by signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.26 NppStatus nppsMul_64fc (const Npp64fc * pSrc1, const Npp64fc * pSrc2, Npp64fc * pDst, int nLength)

64-bit complex floating point signal times signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be multiplied by signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.27 NppStatus nppsMul_64fc_I (const Npp64fc * pSrc, Npp64fc * pSrcDst, int nLength)

64-bit complex floating point in place signal times signal, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be multiplied by signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.28 NppStatus nppsMul_8u16u (const Npp8u * pSrc1, const Npp8u * pSrc2, Npp16u * pDst, int nLength)

8-bit unsigned char signal times signal with 16-bit unsigned result, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be multiplied by signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.29 NppStatus nppsMul_8u_ISfs (const Npp8u * pSrc, Npp8u * pSrcDst, int nLength, int nScaleFactor)

8-bit unsigned char in place signal times signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be multiplied by signal1 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.30 NppStatus nppsMul_8u_Sfs (const Npp8u * pSrc1, const Npp8u * pSrc2, Npp8u * pDst, int nLength, int nScaleFactor)

8-bit unsigned char signal times signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal2 elements to be multiplied by signal1 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.144.2.31 NppStatus nppsMul_Low_32s_Sfs (const Npp32s * pSrc1, const Npp32s * pSrc2, Npp32s * pDst, int nLength, int nScaleFactor)

32-bit signed integer signal times signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal2 elements to be multiplied by signal1 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.145 Sub

Sample by sample subtraction of the samples of two signals.

Functions

- **NppStatus nppsSub_16s** (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp16s** *pDst, int nLength)
16-bit signed short signal subtract signal, then clamp to saturated value.
- **NppStatus nppsSub_32f** (const **Npp32f** *pSrc1, const **Npp32f** *pSrc2, **Npp32f** *pDst, int nLength)
32-bit floating point signal subtract signal, then clamp to saturated value.
- **NppStatus nppsSub_64f** (const **Npp64f** *pSrc1, const **Npp64f** *pSrc2, **Npp64f** *pDst, int nLength)
64-bit floating point signal subtract signal, then clamp to saturated value.
- **NppStatus nppsSub_32fc** (const **Npp32fc** *pSrc1, const **Npp32fc** *pSrc2, **Npp32fc** *pDst, int nLength)
32-bit complex floating point signal subtract signal, then clamp to saturated value.
- **NppStatus nppsSub_64fc** (const **Npp64fc** *pSrc1, const **Npp64fc** *pSrc2, **Npp64fc** *pDst, int nLength)
64-bit complex floating point signal subtract signal, then clamp to saturated value.
- **NppStatus nppsSub_16s32f** (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp32f** *pDst, int nLength)
16-bit signed short signal subtract 16-bit signed short signal, then clamp and convert to 32-bit floating point saturated value.
- **NppStatus nppsSub_8u_Sfs** (const **Npp8u** *pSrc1, const **Npp8u** *pSrc2, **Npp8u** *pDst, int nLength, int nScaleFactor)
8-bit unsigned char signal subtract signal, scale, then clamp to saturated value.
- **NppStatus nppsSub_16u_Sfs** (const **Npp16u** *pSrc1, const **Npp16u** *pSrc2, **Npp16u** *pDst, int nLength, int nScaleFactor)
16-bit unsigned short signal subtract signal, scale, then clamp to saturated value.
- **NppStatus nppsSub_16s_Sfs** (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp16s** *pDst, int nLength, int nScaleFactor)
16-bit signed short signal subtract signal, scale, then clamp to saturated value.
- **NppStatus nppsSub_32s_Sfs** (const **Npp32s** *pSrc1, const **Npp32s** *pSrc2, **Npp32s** *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal subtract signal, scale, then clamp to saturated value.
- **NppStatus nppsSub_16sc_Sfs** (const **Npp16sc** *pSrc1, const **Npp16sc** *pSrc2, **Npp16sc** *pDst, int nLength, int nScaleFactor)
16-bit signed complex short signal subtract signal, scale, then clamp to saturated value.
- **NppStatus nppsSub_32sc_Sfs** (const **Npp32sc** *pSrc1, const **Npp32sc** *pSrc2, **Npp32sc** *pDst, int nLength, int nScaleFactor)

32-bit signed complex integer signal subtract signal, scale, then clamp to saturated value.

- **NppStatus nppsSub_16s_I** (const **Npp16s** *pSrc, **Npp16s** *pSrcDst, int nLength)
16-bit signed short in place signal subtract signal, then clamp to saturated value.
- **NppStatus nppsSub_32f_I** (const **Npp32f** *pSrc, **Npp32f** *pSrcDst, int nLength)
32-bit floating point in place signal subtract signal, then clamp to saturated value.
- **NppStatus nppsSub_64f_I** (const **Npp64f** *pSrc, **Npp64f** *pSrcDst, int nLength)
64-bit floating point in place signal subtract signal, then clamp to saturated value.
- **NppStatus nppsSub_32fc_I** (const **Npp32fc** *pSrc, **Npp32fc** *pSrcDst, int nLength)
32-bit complex floating point in place signal subtract signal, then clamp to saturated value.
- **NppStatus nppsSub_64fc_I** (const **Npp64fc** *pSrc, **Npp64fc** *pSrcDst, int nLength)
64-bit complex floating point in place signal subtract signal, then clamp to saturated value.
- **NppStatus nppsSub_8u_ISfs** (const **Npp8u** *pSrc, **Npp8u** *pSrcDst, int nLength, int nScaleFactor)
8-bit unsigned char in place signal subtract signal, with scaling, then clamp to saturated value.
- **NppStatus nppsSub_16u_ISfs** (const **Npp16u** *pSrc, **Npp16u** *pSrcDst, int nLength, int nScaleFactor)
16-bit unsigned short in place signal subtract signal, with scaling, then clamp to saturated value.
- **NppStatus nppsSub_16s_ISfs** (const **Npp16s** *pSrc, **Npp16s** *pSrcDst, int nLength, int nScaleFactor)
16-bit signed short in place signal subtract signal, with scaling, then clamp to saturated value.
- **NppStatus nppsSub_32s_ISfs** (const **Npp32s** *pSrc, **Npp32s** *pSrcDst, int nLength, int nScaleFactor)
32-bit signed integer in place signal subtract signal, with scaling, then clamp to saturated value.
- **NppStatus nppsSub_16sc_ISfs** (const **Npp16sc** *pSrc, **Npp16sc** *pSrcDst, int nLength, int nScaleFactor)
16-bit complex signed short in place signal subtract signal, with scaling, then clamp to saturated value.
- **NppStatus nppsSub_32sc_ISfs** (const **Npp32sc** *pSrc, **Npp32sc** *pSrcDst, int nLength, int nScaleFactor)
32-bit complex signed integer in place signal subtract signal, with scaling, then clamp to saturated value.

7.145.1 Detailed Description

Sample by sample subtraction of the samples of two signals.

7.145.2 Function Documentation

7.145.2.1 **NppStatus nppsSub_16s** (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp16s** *pDst, int nLength)

16-bit signed short signal subtract signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.
pSrc2 Source Signal Pointer. signal1 elements to be subtracted from signal2 elements
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.145.2.2 NppStatus nppsSub_16s32f (const Npp16s * pSrc1, const Npp16s * pSrc2, Npp32f * pDst, int nLength)

16-bit signed short signal subtract 16-bit signed short signal, then clamp and convert to 32-bit floating point saturated value.

Parameters:

pSrc1 Source Signal Pointer.
pSrc2 Source Signal Pointer. signal1 elements to be subtracted from signal2 elements
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.145.2.3 NppStatus nppsSub_16s_I (const Npp16s * pSrc, Npp16s * pSrcDst, int nLength)

16-bit signed short in place signal subtract signal, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.
pSrcDst In-Place Signal Pointer. signal1 elements to be subtracted from signal2 elements
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.145.2.4 NppStatus nppsSub_16s_ISfs (const Npp16s * pSrc, Npp16s * pSrcDst, int nLength, int nScaleFactor)

16-bit signed short in place signal subtract signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst **In-Place Signal Pointer**. signal1 elements to be subtracted from signal2 elements
nLength **Signal Length**.
nScaleFactor **Integer Result Scaling**.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.145.2.5 **NppStatus nppsSub_16s_Sfs (const Npp16s * pSrc1, const Npp16s * pSrc2, Npp16s * pDst, int nLength, int nScaleFactor)**

16-bit signed short signal subtract signal, scale, then clamp to saturated value.

Parameters:

pSrc1 **Source Signal Pointer**.
pSrc2 **Source Signal Pointer**, signal1 elements to be subtracted from signal2 elements.
pDst **Destination Signal Pointer**.
nLength **Signal Length**.
nScaleFactor **Integer Result Scaling**.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.145.2.6 **NppStatus nppsSub_16sc_ISfs (const Npp16sc * pSrc, Npp16sc * pSrcDst, int nLength, int nScaleFactor)**

16-bit complex signed short in place signal subtract signal, with scaling, then clamp to saturated value.

Parameters:

pSrc **Source Signal Pointer**.
pSrcDst **In-Place Signal Pointer**. signal1 elements to be subtracted from signal2 elements
nLength **Signal Length**.
nScaleFactor **Integer Result Scaling**.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.145.2.7 **NppStatus nppsSub_16sc_Sfs (const Npp16sc * pSrc1, const Npp16sc * pSrc2, Npp16sc * pDst, int nLength, int nScaleFactor)**

16-bit signed complex short signal subtract signal, scale, then clamp to saturated value.

Parameters:

pSrc1 **Source Signal Pointer**.

pSrc2 Source Signal Pointer, signal1 elements to be subtracted from signal2 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.145.2.8 NppStatus nppsSub_16u_ISfs (const Npp16u * pSrc, Npp16u * pSrcDst, int nLength, int nScaleFactor)

16-bit unsigned short in place signal subtract signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal1 elements to be subtracted from signal2 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.145.2.9 NppStatus nppsSub_16u_Sfs (const Npp16u * pSrc1, const Npp16u * pSrc2, Npp16u * pDst, int nLength, int nScaleFactor)

16-bit unsigned short signal subtract signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal1 elements to be subtracted from signal2 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.145.2.10 NppStatus nppsSub_32f (const Npp32f * pSrc1, const Npp32f * pSrc2, Npp32f * pDst, int nLength)

32-bit floating point signal subtract signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 [Source Signal Pointer](#). signal1 elements to be subtracted from signal2 elements
pDst [Destination Signal Pointer](#).
nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.145.2.11 NppStatus nppsSub_32f_I (const Npp32f * pSrc, Npp32f * pSrcDst, int nLength)

32-bit floating point in place signal subtract signal, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).
pSrcDst [In-Place Signal Pointer](#). signal1 elements to be subtracted from signal2 elements
nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.145.2.12 NppStatus nppsSub_32fc (const Npp32fc * pSrc1, const Npp32fc * pSrc2, Npp32fc * pDst, int nLength)

32-bit complex floating point signal subtract signal, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).
pSrc2 [Source Signal Pointer](#). signal1 elements to be subtracted from signal2 elements
pDst [Destination Signal Pointer](#).
nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.145.2.13 NppStatus nppsSub_32fc_I (const Npp32fc * pSrc, Npp32fc * pSrcDst, int nLength)

32-bit complex floating point in place signal subtract signal, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).
pSrcDst [In-Place Signal Pointer](#). signal1 elements to be subtracted from signal2 elements
nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.145.2.14 NppStatus nppsSub_32s_ISfs (const Npp32s * pSrc, Npp32s * pSrcDst, int nLength, int nScaleFactor)

32-bit signed integer in place signal subtract signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal1 elements to be subtracted from signal2 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.145.2.15 NppStatus nppsSub_32s_Sfs (const Npp32s * pSrc1, const Npp32s * pSrc2, Npp32s * pDst, int nLength, int nScaleFactor)

32-bit signed integer signal subtract signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal1 elements to be subtracted from signal2 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.145.2.16 NppStatus nppsSub_32sc_ISfs (const Npp32sc * pSrc, Npp32sc * pSrcDst, int nLength, int nScaleFactor)

32-bit complex signed integer in place signal subtract signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal1 elements to be subtracted from signal2 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.145.2.17 NppStatus nppsSub_32sc_Sfs (const Npp32sc * pSrc1, const Npp32sc * pSrc2, Npp32sc * pDst, int nLength, int nScaleFactor)

32-bit signed complex integer signal subtract signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal1 elements to be subtracted from signal2 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.145.2.18 NppStatus nppsSub_64f (const Npp64f * pSrc1, const Npp64f * pSrc2, Npp64f * pDst, int nLength)

64-bit floating point signal subtract signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal1 elements to be subtracted from signal2 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.145.2.19 NppStatus nppsSub_64f_I (const Npp64f * pSrc, Npp64f * pSrcDst, int nLength)

64-bit floating point in place signal subtract signal, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer, signal1 elements to be subtracted from signal2 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.145.2.20 NppStatus nppsSub_64fc (const Npp64fc * pSrc1, const Npp64fc * pSrc2, Npp64fc * pDst, int nLength)

64-bit complex floating point signal subtract signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal1 elements to be subtracted from signal2 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.145.2.21 NppStatus nppsSub_64fc_I (const Npp64fc * pSrc, Npp64fc * pSrcDst, int nLength)

64-bit complex floating point in place signal subtract signal, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal1 elements to be subtracted from signal2 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.145.2.22 NppStatus nppsSub_8u_ISfs (const Npp8u * pSrc, Npp8u * pSrcDst, int nLength, int nScaleFactor)

8-bit unsigned char in place signal subtract signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal1 elements to be subtracted from signal2 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.145.2.23 `NppStatus nppsSub_8u_Sfs (const Npp8u * pSrc1, const Npp8u * pSrc2, Npp8u * pDst, int nLength, int nScaleFactor)`

8-bit unsigned char signal subtract signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal1 elements to be subtracted from signal2 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.146 Div

Sample by sample division of the samples of two signals.

Functions

- **NppStatus nppsDiv_8u_Sfs** (const **Npp8u** *pSrc1, const **Npp8u** *pSrc2, **Npp8u** *pDst, int nLength, int nScaleFactor)
8-bit unsigned char signal divide signal, scale, then clamp to saturated value.
- **NppStatus nppsDiv_16u_Sfs** (const **Npp16u** *pSrc1, const **Npp16u** *pSrc2, **Npp16u** *pDst, int nLength, int nScaleFactor)
16-bit unsigned short signal divide signal, scale, then clamp to saturated value.
- **NppStatus nppsDiv_16s_Sfs** (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp16s** *pDst, int nLength, int nScaleFactor)
16-bit signed short signal divide signal, scale, then clamp to saturated value.
- **NppStatus nppsDiv_32s_Sfs** (const **Npp32s** *pSrc1, const **Npp32s** *pSrc2, **Npp32s** *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal divide signal, scale, then clamp to saturated value.
- **NppStatus nppsDiv_16sc_Sfs** (const **Npp16sc** *pSrc1, const **Npp16sc** *pSrc2, **Npp16sc** *pDst, int nLength, int nScaleFactor)
16-bit signed complex short signal divide signal, scale, then clamp to saturated value.
- **NppStatus nppsDiv_32s16s_Sfs** (const **Npp16s** *pSrc1, const **Npp32s** *pSrc2, **Npp16s** *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal divided by 16-bit signed short signal, scale, then clamp to 16-bit signed short saturated value.
- **NppStatus nppsDiv_32f** (const **Npp32f** *pSrc1, const **Npp32f** *pSrc2, **Npp32f** *pDst, int nLength)
32-bit floating point signal divide signal, then clamp to saturated value.
- **NppStatus nppsDiv_64f** (const **Npp64f** *pSrc1, const **Npp64f** *pSrc2, **Npp64f** *pDst, int nLength)
64-bit floating point signal divide signal, then clamp to saturated value.
- **NppStatus nppsDiv_32fc** (const **Npp32fc** *pSrc1, const **Npp32fc** *pSrc2, **Npp32fc** *pDst, int nLength)
32-bit complex floating point signal divide signal, then clamp to saturated value.
- **NppStatus nppsDiv_64fc** (const **Npp64fc** *pSrc1, const **Npp64fc** *pSrc2, **Npp64fc** *pDst, int nLength)
64-bit complex floating point signal divide signal, then clamp to saturated value.
- **NppStatus nppsDiv_8u_ISfs** (const **Npp8u** *pSrc, **Npp8u** *pSrcDst, int nLength, int nScaleFactor)
8-bit unsigned char in place signal divide signal, with scaling, then clamp to saturated value.
- **NppStatus nppsDiv_16u_ISfs** (const **Npp16u** *pSrc, **Npp16u** *pSrcDst, int nLength, int nScaleFactor)

16-bit unsigned short in place signal divide signal, with scaling, then clamp to saturated value.

- **NppStatus nppsDiv_16s_ISfs** (const **Npp16s** *pSrc, **Npp16s** *pSrcDst, int nLength, int nScaleFactor)

16-bit signed short in place signal divide signal, with scaling, then clamp to saturated value.

- **NppStatus nppsDiv_16sc_ISfs** (const **Npp16sc** *pSrc, **Npp16sc** *pSrcDst, int nLength, int nScaleFactor)

16-bit complex signed short in place signal divide signal, with scaling, then clamp to saturated value.

- **NppStatus nppsDiv_32s_ISfs** (const **Npp32s** *pSrc, **Npp32s** *pSrcDst, int nLength, int nScaleFactor)

32-bit signed integer in place signal divide signal, with scaling, then clamp to saturated value.

- **NppStatus nppsDiv_32f_I** (const **Npp32f** *pSrc, **Npp32f** *pSrcDst, int nLength)

32-bit floating point in place signal divide signal, then clamp to saturated value.

- **NppStatus nppsDiv_64f_I** (const **Npp64f** *pSrc, **Npp64f** *pSrcDst, int nLength)

64-bit floating point in place signal divide signal, then clamp to saturated value.

- **NppStatus nppsDiv_32fc_I** (const **Npp32fc** *pSrc, **Npp32fc** *pSrcDst, int nLength)

32-bit complex floating point in place signal divide signal, then clamp to saturated value.

- **NppStatus nppsDiv_64fc_I** (const **Npp64fc** *pSrc, **Npp64fc** *pSrcDst, int nLength)

64-bit complex floating point in place signal divide signal, then clamp to saturated value.

7.146.1 Detailed Description

Sample by sample division of the samples of two signals.

7.146.2 Function Documentation

7.146.2.1 **NppStatus nppsDiv_16s_ISfs** (const **Npp16s** *pSrc, **Npp16s** *pSrcDst, int nLength, int nScaleFactor)

16-bit signed short in place signal divide signal, with scaling, then clamp to saturated value.

Parameters:

pSrc **Source Signal Pointer.**

pSrcDst **In-Place Signal Pointer.** signal1 divisor elements to be divided into signal2 dividend elements

nLength **Signal Length.**

nScaleFactor **Integer Result Scaling.**

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.146.2.2 NppStatus nppsDiv_16s_Sfs (const Npp16s * pSrc1, const Npp16s * pSrc2, Npp16s * pDst, int nLength, int nScaleFactor)

16-bit signed short signal divide signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal1 divisor elements to be divided into signal2 dividend elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.146.2.3 NppStatus nppsDiv_16sc_ISfs (const Npp16sc * pSrc, Npp16sc * pSrcDst, int nLength, int nScaleFactor)

16-bit complex signed short in place signal divide signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal1 divisor elements to be divided into signal2 dividend elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.146.2.4 NppStatus nppsDiv_16sc_Sfs (const Npp16sc * pSrc1, const Npp16sc * pSrc2, Npp16sc * pDst, int nLength, int nScaleFactor)

16-bit signed complex short signal divide signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal1 divisor elements to be divided into signal2 dividend elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.146.2.5 NppStatus nppsDiv_16u_ISfs (const Npp16u * pSrc, Npp16u * pSrcDst, int nLength, int nScaleFactor)

16-bit unsigned short in place signal divide signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal1 divisor elements to be divided into signal2 dividend elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.146.2.6 NppStatus nppsDiv_16u_Sfs (const Npp16u * pSrc1, const Npp16u * pSrc2, Npp16u * pDst, int nLength, int nScaleFactor)

16-bit unsigned short signal divide signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal1 divisor elements to be divided into signal2 dividend elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.146.2.7 NppStatus nppsDiv_32f (const Npp32f * pSrc1, const Npp32f * pSrc2, Npp32f * pDst, int nLength)

32-bit floating point signal divide signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal1 divisor elements to be divided into signal2 dividend elements.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.146.2.8 NppStatus nppsDiv_32f_I (const Npp32f * pSrc, Npp32f * pSrcDst, int nLength)

32-bit floating point in place signal divide signal, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal1 divisor elements to be divided into signal2 dividend elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.146.2.9 NppStatus nppsDiv_32fc (const Npp32fc * pSrc1, const Npp32fc * pSrc2, Npp32fc * pDst, int nLength)

32-bit complex floating point signal divide signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal1 divisor elements to be divided into signal2 dividend elements.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.146.2.10 NppStatus nppsDiv_32fc_I (const Npp32fc * pSrc, Npp32fc * pSrcDst, int nLength)

32-bit complex floating point in place signal divide signal, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal1 divisor elements to be divided into signal2 dividend elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.146.2.11 NppStatus nppsDiv_32s16s_Sfs (const Npp16s * pSrc1, const Npp32s * pSrc2, Npp16s * pDst, int nLength, int nScaleFactor)

32-bit signed integer signal divided by 16-bit signed short signal, scale, then clamp to 16-bit signed short saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal1 divisor elements to be divided into signal2 dividend elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.146.2.12 NppStatus nppsDiv_32s_ISfs (const Npp32s * pSrc, Npp32s * pSrcDst, int nLength, int nScaleFactor)

32-bit signed integer in place signal divide signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal1 divisor elements to be divided into signal2 dividend elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.146.2.13 NppStatus nppsDiv_32s_Sfs (const Npp32s * pSrc1, const Npp32s * pSrc2, Npp32s * pDst, int nLength, int nScaleFactor)

32-bit signed integer signal divide signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal1 divisor elements to be divided into signal2 dividend elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.146.2.14 NppStatus nppsDiv_64f (const Npp64f * pSrc1, const Npp64f * pSrc2, Npp64f * pDst, int nLength)

64-bit floating point signal divide signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal1 divisor elements to be divided into signal2 dividend elements.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.146.2.15 NppStatus nppsDiv_64f_I (const Npp64f * pSrc, Npp64f * pSrcDst, int nLength)

64-bit floating point in place signal divide signal, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal1 divisor elements to be divided into signal2 dividend elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.146.2.16 NppStatus nppsDiv_64fc (const Npp64fc * pSrc1, const Npp64fc * pSrc2, Npp64fc * pDst, int nLength)

64-bit complex floating point signal divide signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal1 divisor elements to be divided into signal2 dividend elements.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.146.2.17 NppStatus nppsDiv_64fc_I (const Npp64fc * pSrc, Npp64fc * pSrcDst, int nLength)

64-bit complex floating point in place signal divide signal, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal1 divisor elements to be divided into signal2 dividend elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.146.2.18 NppStatus nppsDiv_8u_ISfs (const Npp8u * pSrc, Npp8u * pSrcDst, int nLength, int nScaleFactor)

8-bit unsigned char in place signal divide signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal1 divisor elements to be divided into signal2 dividend elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.146.2.19 NppStatus nppsDiv_8u_Sfs (const Npp8u * pSrc1, const Npp8u * pSrc2, Npp8u * pDst, int nLength, int nScaleFactor)

8-bit unsigned char signal divide signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal1 divisor elements to be divided into signal2 dividend elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.147 Div_Round

Sample by sample division of the samples of two signals with rounding.

Functions

- `NppStatus nppsDiv_Round_8u_Sfs` (const `Npp8u` *pSrc1, const `Npp8u` *pSrc2, `Npp8u` *pDst, int nLength, `NppRoundMode` nRndMode, int nScaleFactor)
8-bit unsigned char signal divide signal, scale, then clamp to saturated value.
- `NppStatus nppsDiv_Round_16u_Sfs` (const `Npp16u` *pSrc1, const `Npp16u` *pSrc2, `Npp16u` *pDst, int nLength, `NppRoundMode` nRndMode, int nScaleFactor)
16-bit unsigned short signal divide signal, scale, round, then clamp to saturated value.
- `NppStatus nppsDiv_Round_16s_Sfs` (const `Npp16s` *pSrc1, const `Npp16s` *pSrc2, `Npp16s` *pDst, int nLength, `NppRoundMode` nRndMode, int nScaleFactor)
16-bit signed short signal divide signal, scale, round, then clamp to saturated value.
- `NppStatus nppsDiv_Round_8u_ISfs` (const `Npp8u` *pSrc, `Npp8u` *pSrcDst, int nLength, `NppRoundMode` nRndMode, int nScaleFactor)
8-bit unsigned char in place signal divide signal, with scaling, rounding then clamp to saturated value.
- `NppStatus nppsDiv_Round_16u_ISfs` (const `Npp16u` *pSrc, `Npp16u` *pSrcDst, int nLength, `NppRoundMode` nRndMode, int nScaleFactor)
16-bit unsigned short in place signal divide signal, with scaling, rounding then clamp to saturated value.
- `NppStatus nppsDiv_Round_16s_ISfs` (const `Npp16s` *pSrc, `Npp16s` *pSrcDst, int nLength, `NppRoundMode` nRndMode, int nScaleFactor)
16-bit signed short in place signal divide signal, with scaling, rounding then clamp to saturated value.

7.147.1 Detailed Description

Sample by sample division of the samples of two signals with rounding.

7.147.2 Function Documentation

7.147.2.1 `NppStatus nppsDiv_Round_16s_ISfs` (const `Npp16s` * pSrc, `Npp16s` * pSrcDst, int nLength, `NppRoundMode` nRndMode, int nScaleFactor)

16-bit signed short in place signal divide signal, with scaling, rounding then clamp to saturated value.

Parameters:

pSrc **Source Signal Pointer.**

pSrcDst **In-Place Signal Pointer.** signal1 divisor elements to be divided into signal2 dividend elements
nLength **Signal Length.**

nRndMode various rounding modes.

nScaleFactor **Integer Result Scaling.**

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.147.2.2 NppStatus nppsDiv_Round_16s_Sfs (const Npp16s * pSrc1, const Npp16s * pSrc2, Npp16s * pDst, int nLength, NppRoundMode nRndMode, int nScaleFactor)

16-bit signed short signal divide signal, scale, round, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal1 divisor elements to be divided into signal2 dividend elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nRndMode various rounding modes.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.147.2.3 NppStatus nppsDiv_Round_16u_ISfs (const Npp16u * pSrc, Npp16u * pSrcDst, int nLength, NppRoundMode nRndMode, int nScaleFactor)

16-bit unsigned short in place signal divide signal, with scaling, rounding then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal1 divisor elements to be divided into signal2 dividend elements

nLength Signal Length.

nRndMode various rounding modes.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.147.2.4 NppStatus nppsDiv_Round_16u_Sfs (const Npp16u * pSrc1, const Npp16u * pSrc2, Npp16u * pDst, int nLength, NppRoundMode nRndMode, int nScaleFactor)

16-bit unsigned short signal divide signal, scale, round, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal1 divisor elements to be divided into signal2 dividend elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nRndMode various rounding modes.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.147.2.5 `NppStatus nppsDiv_Round_8u_ISfs (const Npp8u * pSrc, Npp8u * pSrcDst, int nLength, NppRoundMode nRndMode, int nScaleFactor)`

8-bit unsigned char in place signal divide signal, with scaling, rounding then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal1 divisor elements to be divided into signal2 dividend elements

nLength Signal Length.

nRndMode various rounding modes.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.147.2.6 `NppStatus nppsDiv_Round_8u_Sfs (const Npp8u * pSrc1, const Npp8u * pSrc2, Npp8u * pDst, int nLength, NppRoundMode nRndMode, int nScaleFactor)`

8-bit unsigned char signal divide signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal1 divisor elements to be divided into signal2 dividend elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nRndMode various rounding modes.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.148 Abs

Absolute value of each sample of a signal.

Functions

- `NppStatus nppsAbs_16s` (const `Npp16s` *pSrc, `Npp16s` *pDst, int nLength)
16-bit signed short signal absolute value.
- `NppStatus nppsAbs_32s` (const `Npp32s` *pSrc, `Npp32s` *pDst, int nLength)
32-bit signed integer signal absolute value.
- `NppStatus nppsAbs_32f` (const `Npp32f` *pSrc, `Npp32f` *pDst, int nLength)
32-bit floating point signal absolute value.
- `NppStatus nppsAbs_64f` (const `Npp64f` *pSrc, `Npp64f` *pDst, int nLength)
64-bit floating point signal absolute value.
- `NppStatus nppsAbs_16s_I` (`Npp16s` *pSrcDst, int nLength)
16-bit signed short signal absolute value.
- `NppStatus nppsAbs_32s_I` (`Npp32s` *pSrcDst, int nLength)
32-bit signed integer signal absolute value.
- `NppStatus nppsAbs_32f_I` (`Npp32f` *pSrcDst, int nLength)
32-bit floating point signal absolute value.
- `NppStatus nppsAbs_64f_I` (`Npp64f` *pSrcDst, int nLength)
64-bit floating point signal absolute value.

7.148.1 Detailed Description

Absolute value of each sample of a signal.

7.148.2 Function Documentation

7.148.2.1 `NppStatus nppsAbs_16s` (const `Npp16s` *pSrc, `Npp16s` *pDst, int nLength)

16-bit signed short signal absolute value.

Parameters:

- pSrc* Source Signal Pointer.
- pDst* Destination Signal Pointer.
- nLength* Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.148.2.2 NppStatus nppsAbs_16s_I (Npp16s * pSrcDst, int nLength)

16-bit signed short signal absolute value.

Parameters:

pSrcDst In-Place Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.148.2.3 NppStatus nppsAbs_32f (const Npp32f * pSrc, Npp32f * pDst, int nLength)

32-bit floating point signal absolute value.

Parameters:

pSrc Source Signal Pointer.
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.148.2.4 NppStatus nppsAbs_32f_I (Npp32f * pSrcDst, int nLength)

32-bit floating point signal absolute value.

Parameters:

pSrcDst In-Place Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.148.2.5 NppStatus nppsAbs_32s (const Npp32s * pSrc, Npp32s * pDst, int nLength)

32-bit signed integer signal absolute value.

Parameters:

pSrc Source Signal Pointer.
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.148.2.6 NppStatus nppsAbs_32s_I (Npp32s * pSrcDst, int nLength)

32-bit signed integer signal absolute value.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.148.2.7 NppStatus nppsAbs_64f (const Npp64f * pSrc, Npp64f * pDst, int nLength)

64-bit floating point signal absolute value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.148.2.8 NppStatus nppsAbs_64f_I (Npp64f * pSrcDst, int nLength)

64-bit floating point signal absolute value.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.149 Sqr

Squares each sample of a signal.

Functions

- `NppStatus nppsSqr_32f` (const `Npp32f` *pSrc, `Npp32f` *pDst, int nLength)
32-bit floating point signal squared.
- `NppStatus nppsSqr_64f` (const `Npp64f` *pSrc, `Npp64f` *pDst, int nLength)
64-bit floating point signal squared.
- `NppStatus nppsSqr_32fc` (const `Npp32fc` *pSrc, `Npp32fc` *pDst, int nLength)
32-bit complex floating point signal squared.
- `NppStatus nppsSqr_64fc` (const `Npp64fc` *pSrc, `Npp64fc` *pDst, int nLength)
64-bit complex floating point signal squared.
- `NppStatus nppsSqr_32f_I` (`Npp32f` *pSrcDst, int nLength)
32-bit floating point signal squared.
- `NppStatus nppsSqr_64f_I` (`Npp64f` *pSrcDst, int nLength)
64-bit floating point signal squared.
- `NppStatus nppsSqr_32fc_I` (`Npp32fc` *pSrcDst, int nLength)
32-bit complex floating point signal squared.
- `NppStatus nppsSqr_64fc_I` (`Npp64fc` *pSrcDst, int nLength)
64-bit complex floating point signal squared.
- `NppStatus nppsSqr_8u_Sfs` (const `Npp8u` *pSrc, `Npp8u` *pDst, int nLength, int nScaleFactor)
8-bit unsigned char signal squared, scale, then clamp to saturated value.
- `NppStatus nppsSqr_16u_Sfs` (const `Npp16u` *pSrc, `Npp16u` *pDst, int nLength, int nScaleFactor)
16-bit unsigned short signal squared, scale, then clamp to saturated value.
- `NppStatus nppsSqr_16s_Sfs` (const `Npp16s` *pSrc, `Npp16s` *pDst, int nLength, int nScaleFactor)
16-bit signed short signal squared, scale, then clamp to saturated value.
- `NppStatus nppsSqr_16sc_Sfs` (const `Npp16sc` *pSrc, `Npp16sc` *pDst, int nLength, int nScaleFactor)
16-bit complex signed short signal squared, scale, then clamp to saturated value.
- `NppStatus nppsSqr_8u_ISfs` (`Npp8u` *pSrcDst, int nLength, int nScaleFactor)
8-bit unsigned char signal squared, scale, then clamp to saturated value.
- `NppStatus nppsSqr_16u_ISfs` (`Npp16u` *pSrcDst, int nLength, int nScaleFactor)
16-bit unsigned short signal squared, scale, then clamp to saturated value.

- `NppStatus nppsSqr_16s_ISfs` (`Npp16s *pSrcDst`, `int nLength`, `int nScaleFactor`)
16-bit signed short signal squared, scale, then clamp to saturated value.
- `NppStatus nppsSqr_16sc_ISfs` (`Npp16sc *pSrcDst`, `int nLength`, `int nScaleFactor`)
16-bit complex signed short signal squared, scale, then clamp to saturated value.

7.149.1 Detailed Description

Squares each sample of a signal.

7.149.2 Function Documentation

7.149.2.1 `NppStatus nppsSqr_16s_ISfs` (`Npp16s *pSrcDst`, `int nLength`, `int nScaleFactor`)

16-bit signed short signal squared, scale, then clamp to saturated value.

Parameters:

- pSrcDst* [In-Place Signal Pointer](#).
- nLength* [Signal Length](#).
- nScaleFactor* [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.149.2.2 `NppStatus nppsSqr_16s_Sfs` (`const Npp16s *pSrc`, `Npp16s *pDst`, `int nLength`, `int nScaleFactor`)

16-bit signed short signal squared, scale, then clamp to saturated value.

Parameters:

- pSrc* [Source Signal Pointer](#).
- pDst* [Destination Signal Pointer](#).
- nLength* [Signal Length](#).
- nScaleFactor* [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.149.2.3 `NppStatus nppsSqr_16sc_ISfs` (`Npp16sc *pSrcDst`, `int nLength`, `int nScaleFactor`)

16-bit complex signed short signal squared, scale, then clamp to saturated value.

Parameters:

- pSrcDst* [In-Place Signal Pointer](#).

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.149.2.4 NppStatus nppsSqr_16sc_Sfs (const Npp16sc * pSrc, Npp16sc * pDst, int nLength, int nScaleFactor)

16-bit complex signed short signal squared, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.149.2.5 NppStatus nppsSqr_16u_ISfs (Npp16u * pSrcDst, int nLength, int nScaleFactor)

16-bit unsigned short signal squared, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.149.2.6 NppStatus nppsSqr_16u_Sfs (const Npp16u * pSrc, Npp16u * pDst, int nLength, int nScaleFactor)

16-bit unsigned short signal squared, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.149.2.7 NppStatus nppsSqr_32f (const Npp32f * pSrc, Npp32f * pDst, int nLength)

32-bit floating point signal squared.

Parameters:

pSrc Source Signal Pointer.
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.149.2.8 NppStatus nppsSqr_32f_I (Npp32f * pSrcDst, int nLength)

32-bit floating point signal squared.

Parameters:

pSrcDst In-Place Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.149.2.9 NppStatus nppsSqr_32fc (const Npp32fc * pSrc, Npp32fc * pDst, int nLength)

32-bit complex floating point signal squared.

Parameters:

pSrc Source Signal Pointer.
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.149.2.10 NppStatus nppsSqr_32fc_I (Npp32fc * pSrcDst, int nLength)

32-bit complex floating point signal squared.

Parameters:

pSrcDst In-Place Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.149.2.11 NppStatus nppsSqr_64f (const Npp64f * pSrc, Npp64f * pDst, int nLength)

64-bit floating point signal squared.

Parameters:

pSrc Source Signal Pointer.
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.149.2.12 NppStatus nppsSqr_64f_I (Npp64f * pSrcDst, int nLength)

64-bit floating point signal squared.

Parameters:

pSrcDst In-Place Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.149.2.13 NppStatus nppsSqr_64fc (const Npp64fc * pSrc, Npp64fc * pDst, int nLength)

64-bit complex floating point signal squared.

Parameters:

pSrc Source Signal Pointer.
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.149.2.14 NppStatus nppsSqr_64fc_I (Npp64fc * pSrcDst, int nLength)

64-bit complex floating point signal squared.

Parameters:

pSrcDst In-Place Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.149.2.15 NppStatus nppsSqr_8u_ISfs (Npp8u * pSrcDst, int nLength, int nScaleFactor)

8-bit unsigned char signal squared, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.149.2.16 NppStatus nppsSqr_8u_Sfs (const Npp8u * pSrc, Npp8u * pDst, int nLength, int nScaleFactor)

8-bit unsigned char signal squared, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.150 Sqrt

Square root of each sample of a signal.

Functions

- `NppStatus nppsSqrt_32f` (const `Npp32f` *pSrc, `Npp32f` *pDst, int nLength)
32-bit floating point signal square root.
- `NppStatus nppsSqrt_64f` (const `Npp64f` *pSrc, `Npp64f` *pDst, int nLength)
64-bit floating point signal square root.
- `NppStatus nppsSqrt_32fc` (const `Npp32fc` *pSrc, `Npp32fc` *pDst, int nLength)
32-bit complex floating point signal square root.
- `NppStatus nppsSqrt_64fc` (const `Npp64fc` *pSrc, `Npp64fc` *pDst, int nLength)
64-bit complex floating point signal square root.
- `NppStatus nppsSqrt_32f_I` (`Npp32f` *pSrcDst, int nLength)
32-bit floating point signal square root.
- `NppStatus nppsSqrt_64f_I` (`Npp64f` *pSrcDst, int nLength)
64-bit floating point signal square root.
- `NppStatus nppsSqrt_32fc_I` (`Npp32fc` *pSrcDst, int nLength)
32-bit complex floating point signal square root.
- `NppStatus nppsSqrt_64fc_I` (`Npp64fc` *pSrcDst, int nLength)
64-bit complex floating point signal square root.
- `NppStatus nppsSqrt_8u_Sfs` (const `Npp8u` *pSrc, `Npp8u` *pDst, int nLength, int nScaleFactor)
8-bit unsigned char signal square root, scale, then clamp to saturated value.
- `NppStatus nppsSqrt_16u_Sfs` (const `Npp16u` *pSrc, `Npp16u` *pDst, int nLength, int nScaleFactor)
16-bit unsigned short signal square root, scale, then clamp to saturated value.
- `NppStatus nppsSqrt_16s_Sfs` (const `Npp16s` *pSrc, `Npp16s` *pDst, int nLength, int nScaleFactor)
16-bit signed short signal square root, scale, then clamp to saturated value.
- `NppStatus nppsSqrt_16sc_Sfs` (const `Npp16sc` *pSrc, `Npp16sc` *pDst, int nLength, int nScaleFactor)
16-bit complex signed short signal square root, scale, then clamp to saturated value.
- `NppStatus nppsSqrt_64s_Sfs` (const `Npp64s` *pSrc, `Npp64s` *pDst, int nLength, int nScaleFactor)
64-bit signed integer signal square root, scale, then clamp to saturated value.
- `NppStatus nppsSqrt_32s16s_Sfs` (const `Npp32s` *pSrc, `Npp16s` *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal square root, scale, then clamp to 16-bit signed integer saturated value.

- **NppStatus nppsSqrt_64s16s_Sfs** (const **Npp64s** *pSrc, **Npp16s** *pDst, int nLength, int nScaleFactor)
64-bit signed integer signal square root, scale, then clamp to 16-bit signed integer saturated value.
- **NppStatus nppsSqrt_8u_ISfs** (**Npp8u** *pSrcDst, int nLength, int nScaleFactor)
8-bit unsigned char signal square root, scale, then clamp to saturated value.
- **NppStatus nppsSqrt_16u_ISfs** (**Npp16u** *pSrcDst, int nLength, int nScaleFactor)
16-bit unsigned short signal square root, scale, then clamp to saturated value.
- **NppStatus nppsSqrt_16s_ISfs** (**Npp16s** *pSrcDst, int nLength, int nScaleFactor)
16-bit signed short signal square root, scale, then clamp to saturated value.
- **NppStatus nppsSqrt_16sc_ISfs** (**Npp16sc** *pSrcDst, int nLength, int nScaleFactor)
16-bit complex signed short signal square root, scale, then clamp to saturated value.
- **NppStatus nppsSqrt_64s_ISfs** (**Npp64s** *pSrcDst, int nLength, int nScaleFactor)
64-bit signed integer signal square root, scale, then clamp to saturated value.

7.150.1 Detailed Description

Square root of each sample of a signal.

7.150.2 Function Documentation

7.150.2.1 **NppStatus nppsSqrt_16s_ISfs** (**Npp16s** *pSrcDst, int nLength, int nScaleFactor)

16-bit signed short signal square root, scale, then clamp to saturated value.

Parameters:

pSrcDst **In-Place Signal Pointer.**

nLength **Signal Length.**

nScaleFactor **Integer Result Scaling.**

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.150.2.2 **NppStatus nppsSqrt_16s_Sfs** (const **Npp16s** *pSrc, **Npp16s** *pDst, int nLength, int nScaleFactor)

16-bit signed short signal square root, scale, then clamp to saturated value.

Parameters:

pSrc **Source Signal Pointer.**

pDst Destination Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.150.2.3 NppStatus nppsSqrt_16sc_ISfs (Npp16sc * pSrcDst, int nLength, int nScaleFactor)

16-bit complex signed short signal square root, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.150.2.4 NppStatus nppsSqrt_16sc_Sfs (const Npp16sc * pSrc, Npp16sc * pDst, int nLength, int nScaleFactor)

16-bit complex signed short signal square root, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.
pDst Destination Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.150.2.5 NppStatus nppsSqrt_16u_ISfs (Npp16u * pSrcDst, int nLength, int nScaleFactor)

16-bit unsigned short signal square root, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.150.2.6 NppStatus nppsSqrt_16u_Sfs (const Npp16u * pSrc, Npp16u * pDst, int nLength, int nScaleFactor)

16-bit unsigned short signal square root, scale, then clamp to saturated value.

Parameters:

- pSrc* Source Signal Pointer.
- pDst* Destination Signal Pointer.
- nLength* Signal Length.
- nScaleFactor* Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.150.2.7 NppStatus nppsSqrt_32f (const Npp32f * pSrc, Npp32f * pDst, int nLength)

32-bit floating point signal square root.

Parameters:

- pSrc* Source Signal Pointer.
- pDst* Destination Signal Pointer.
- nLength* Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.150.2.8 NppStatus nppsSqrt_32f_I (Npp32f * pSrcDst, int nLength)

32-bit floating point signal square root.

Parameters:

- pSrcDst* In-Place Signal Pointer.
- nLength* Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.150.2.9 NppStatus nppsSqrt_32fc (const Npp32fc * pSrc, Npp32fc * pDst, int nLength)

32-bit complex floating point signal square root.

Parameters:

- pSrc* Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.150.2.10 NppStatus nppsSqrt_32fc_I (Npp32fc * pSrcDst, int nLength)

32-bit complex floating point signal square root.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.150.2.11 NppStatus nppsSqrt_32s16s_Sfs (const Npp32s * pSrc, Npp16s * pDst, int nLength, int nScaleFactor)

32-bit signed integer signal square root, scale, then clamp to 16-bit signed integer saturated value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.150.2.12 NppStatus nppsSqrt_64f (const Npp64f * pSrc, Npp64f * pDst, int nLength)

64-bit floating point signal square root.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.150.2.13 NppStatus nppsSqrt_64f_I (Npp64f * pSrcDst, int nLength)

64-bit floating point signal square root.

Parameters:

pSrcDst In-Place Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.150.2.14 NppStatus nppsSqrt_64fc (const Npp64fc * pSrc, Npp64fc * pDst, int nLength)

64-bit complex floating point signal square root.

Parameters:

pSrc Source Signal Pointer.
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.150.2.15 NppStatus nppsSqrt_64fc_I (Npp64fc * pSrcDst, int nLength)

64-bit complex floating point signal square root.

Parameters:

pSrcDst In-Place Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.150.2.16 NppStatus nppsSqrt_64s16s_Sfs (const Npp64s * pSrc, Npp16s * pDst, int nLength, int nScaleFactor)

64-bit signed integer signal square root, scale, then clamp to 16-bit signed integer saturated value.

Parameters:

pSrc Source Signal Pointer.
pDst Destination Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.150.2.17 NppStatus nppsSqrt_64s_ISfs (Npp64s * pSrcDst, int nLength, int nScaleFactor)

64-bit signed integer signal square root, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.150.2.18 NppStatus nppsSqrt_64s_Sfs (const Npp64s * pSrc, Npp64s * pDst, int nLength, int nScaleFactor)

64-bit signed integer signal square root, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.150.2.19 NppStatus nppsSqrt_8u_ISfs (Npp8u * pSrcDst, int nLength, int nScaleFactor)

8-bit unsigned char signal square root, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.150.2.20 NppStatus nppsSqrt_8u_Sfs (const Npp8u * pSrc, Npp8u * pDst, int nLength, int nScaleFactor)

8-bit unsigned char signal square root, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.151 Cubrt

Cube root of each sample of a signal.

Functions

- **NppStatus nppsCubrt_32f** (const **Npp32f** *pSrc, **Npp32f** *pDst, int nLength)
32-bit floating point signal cube root.
- **NppStatus nppsCubrt_32s16s_Sfs** (const **Npp32s** *pSrc, **Npp16s** *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal cube root, scale, then clamp to 16-bit signed integer saturated value.

7.151.1 Detailed Description

Cube root of each sample of a signal.

7.151.2 Function Documentation

7.151.2.1 **NppStatus nppsCubrt_32f** (const **Npp32f** *pSrc, **Npp32f** *pDst, int nLength)

32-bit floating point signal cube root.

Parameters:

- pSrc* Source Signal Pointer.
- pDst* Destination Signal Pointer.
- nLength* Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.151.2.2 **NppStatus nppsCubrt_32s16s_Sfs** (const **Npp32s** *pSrc, **Npp16s** *pDst, int nLength, int nScaleFactor)

32-bit signed integer signal cube root, scale, then clamp to 16-bit signed integer saturated value.

Parameters:

- pSrc* Source Signal Pointer.
- pDst* Destination Signal Pointer.
- nLength* Signal Length.
- nScaleFactor* Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.152 Exp

E raised to the power of each sample of a signal.

Functions

- `NppStatus nppsExp_32f` (const `Npp32f` *pSrc, `Npp32f` *pDst, int nLength)
32-bit floating point signal exponent.
- `NppStatus nppsExp_64f` (const `Npp64f` *pSrc, `Npp64f` *pDst, int nLength)
64-bit floating point signal exponent.
- `NppStatus nppsExp_32f64f` (const `Npp32f` *pSrc, `Npp64f` *pDst, int nLength)
32-bit floating point signal exponent with 64-bit floating point result.
- `NppStatus nppsExp_32f_I` (`Npp32f` *pSrcDst, int nLength)
32-bit floating point signal exponent.
- `NppStatus nppsExp_64f_I` (`Npp64f` *pSrcDst, int nLength)
64-bit floating point signal exponent.
- `NppStatus nppsExp_16s_Sfs` (const `Npp16s` *pSrc, `Npp16s` *pDst, int nLength, int nScaleFactor)
16-bit signed short signal exponent, scale, then clamp to saturated value.
- `NppStatus nppsExp_32s_Sfs` (const `Npp32s` *pSrc, `Npp32s` *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal exponent, scale, then clamp to saturated value.
- `NppStatus nppsExp_64s_Sfs` (const `Npp64s` *pSrc, `Npp64s` *pDst, int nLength, int nScaleFactor)
64-bit signed integer signal exponent, scale, then clamp to saturated value.
- `NppStatus nppsExp_16s_ISfs` (`Npp16s` *pSrcDst, int nLength, int nScaleFactor)
16-bit signed short signal exponent, scale, then clamp to saturated value.
- `NppStatus nppsExp_32s_ISfs` (`Npp32s` *pSrcDst, int nLength, int nScaleFactor)
32-bit signed integer signal exponent, scale, then clamp to saturated value.
- `NppStatus nppsExp_64s_ISfs` (`Npp64s` *pSrcDst, int nLength, int nScaleFactor)
64-bit signed integer signal exponent, scale, then clamp to saturated value.

7.152.1 Detailed Description

E raised to the power of each sample of a signal.

7.152.2 Function Documentation

7.152.2.1 `NppStatus nppsExp_16s_ISfs` (`Npp16s` *pSrcDst, int nLength, int nScaleFactor)

16-bit signed short signal exponent, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.152.2.2 NppStatus nppsExp_16s_Sfs (const Npp16s * pSrc, Npp16s * pDst, int nLength, int nScaleFactor)

16-bit signed short signal exponent, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.
pDst Destination Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.152.2.3 NppStatus nppsExp_32f (const Npp32f * pSrc, Npp32f * pDst, int nLength)

32-bit floating point signal exponent.

Parameters:

pSrc Source Signal Pointer.
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.152.2.4 NppStatus nppsExp_32f64f (const Npp32f * pSrc, Npp64f * pDst, int nLength)

32-bit floating point signal exponent with 64-bit floating point result.

Parameters:

pSrc Source Signal Pointer.
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.152.2.5 NppStatus nppsExp_32f_I (Npp32f * pSrcDst, int nLength)

32-bit floating point signal exponent.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.152.2.6 NppStatus nppsExp_32s_ISfs (Npp32s * pSrcDst, int nLength, int nScaleFactor)

32-bit signed integer signal exponent, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.152.2.7 NppStatus nppsExp_32s_Sfs (const Npp32s * pSrc, Npp32s * pDst, int nLength, int nScaleFactor)

32-bit signed integer signal exponent, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.152.2.8 NppStatus nppsExp_64f (const Npp64f * pSrc, Npp64f * pDst, int nLength)

64-bit floating point signal exponent.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.152.2.9 NppStatus nppsExp_64f_I (Npp64f * pSrcDst, int nLength)

64-bit floating point signal exponent.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.152.2.10 NppStatus nppsExp_64s_ISfs (Npp64s * pSrcDst, int nLength, int nScaleFactor)

64-bit signed integer signal exponent, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.152.2.11 NppStatus nppsExp_64s_Sfs (const Npp64s * pSrc, Npp64s * pDst, int nLength, int nScaleFactor)

64-bit signed integer signal exponent, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.153 Ln

Natural logarithm of each sample of a signal.

Functions

- **NppStatus nppsLn_32f** (const **Npp32f** *pSrc, **Npp32f** *pDst, int nLength)
32-bit floating point signal natural logarithm.
- **NppStatus nppsLn_64f** (const **Npp64f** *pSrc, **Npp64f** *pDst, int nLength)
64-bit floating point signal natural logarithm.
- **NppStatus nppsLn_64f32f** (const **Npp64f** *pSrc, **Npp32f** *pDst, int nLength)
64-bit floating point signal natural logarithm with 32-bit floating point result.
- **NppStatus nppsLn_32f_I** (**Npp32f** *pSrcDst, int nLength)
32-bit floating point signal natural logarithm.
- **NppStatus nppsLn_64f_I** (**Npp64f** *pSrcDst, int nLength)
64-bit floating point signal natural logarithm.
- **NppStatus nppsLn_16s_Sfs** (const **Npp16s** *pSrc, **Npp16s** *pDst, int nLength, int nScaleFactor)
16-bit signed short signal natural logarithm, scale, then clamp to saturated value.
- **NppStatus nppsLn_32s_Sfs** (const **Npp32s** *pSrc, **Npp32s** *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal natural logarithm, scale, then clamp to saturated value.
- **NppStatus nppsLn_32s16s_Sfs** (const **Npp32s** *pSrc, **Npp16s** *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal natural logarithm, scale, then clamp to 16-bit signed short saturated value.
- **NppStatus nppsLn_16s_ISfs** (**Npp16s** *pSrcDst, int nLength, int nScaleFactor)
16-bit signed short signal natural logarithm, scale, then clamp to saturated value.
- **NppStatus nppsLn_32s_ISfs** (**Npp32s** *pSrcDst, int nLength, int nScaleFactor)
32-bit signed integer signal natural logarithm, scale, then clamp to saturated value.

7.153.1 Detailed Description

Natural logarithm of each sample of a signal.

7.153.2 Function Documentation

7.153.2.1 **NppStatus nppsLn_16s_ISfs** (**Npp16s** *pSrcDst, int nLength, int nScaleFactor)

16-bit signed short signal natural logarithm, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.153.2.2 NppStatus nppsLn_16s_Sfs (const Npp16s * pSrc, Npp16s * pDst, int nLength, int nScaleFactor)

16-bit signed short signal natural logarithm, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.
pDst Destination Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.153.2.3 NppStatus nppsLn_32f (const Npp32f * pSrc, Npp32f * pDst, int nLength)

32-bit floating point signal natural logarithm.

Parameters:

pSrc Source Signal Pointer.
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.153.2.4 NppStatus nppsLn_32f_I (Npp32f * pSrcDst, int nLength)

32-bit floating point signal natural logarithm.

Parameters:

pSrcDst In-Place Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.153.2.5 NppStatus nppsLn_32s16s_Sfs (const Npp32s * *pSrc*, Npp16s * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer signal natural logarithm, scale, then clamp to 16-bit signed short saturated value.

Parameters:

- pSrc* Source Signal Pointer.
- pDst* Destination Signal Pointer.
- nLength* Signal Length.
- nScaleFactor* Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.153.2.6 NppStatus nppsLn_32s_ISfs (Npp32s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer signal natural logarithm, scale, then clamp to saturated value.

Parameters:

- pSrcDst* In-Place Signal Pointer.
- nLength* Signal Length.
- nScaleFactor* Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.153.2.7 NppStatus nppsLn_32s_Sfs (const Npp32s * *pSrc*, Npp32s * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer signal natural logarithm, scale, then clamp to saturated value.

Parameters:

- pSrc* Source Signal Pointer.
- pDst* Destination Signal Pointer.
- nLength* Signal Length.
- nScaleFactor* Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.153.2.8 NppStatus nppsLn_64f (const Npp64f * pSrc, Npp64f * pDst, int nLength)

64-bit floating point signal natural logarithm.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.153.2.9 NppStatus nppsLn_64f32f (const Npp64f * pSrc, Npp32f * pDst, int nLength)

64-bit floating point signal natural logarithm with 32-bit floating point result.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.153.2.10 NppStatus nppsLn_64f_I (Npp64f * pSrcDst, int nLength)

64-bit floating point signal natural logarithm.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.154 10Log10

Ten times the decimal logarithm of each sample of a signal.

Functions

- `NppStatus npps10Log10_32s_Sfs` (const `Npp32s` *pSrc, `Npp32s` *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal 10 times base 10 logarithm, scale, then clamp to saturated value.
- `NppStatus npps10Log10_32s_ISfs` (`Npp32s` *pSrcDst, int nLength, int nScaleFactor)
32-bit signed integer signal 10 times base 10 logarithm, scale, then clamp to saturated value.

7.154.1 Detailed Description

Ten times the decimal logarithm of each sample of a signal.

7.154.2 Function Documentation

7.154.2.1 `NppStatus npps10Log10_32s_ISfs` (`Npp32s` *pSrcDst, int nLength, int nScaleFactor)

32-bit signed integer signal 10 times base 10 logarithm, scale, then clamp to saturated value.

Parameters:

- pSrcDst* In-Place Signal Pointer.
- nLength* Signal Length.
- nScaleFactor* Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.154.2.2 `NppStatus npps10Log10_32s_Sfs` (const `Npp32s` *pSrc, `Npp32s` *pDst, int nLength, int nScaleFactor)

32-bit signed integer signal 10 times base 10 logarithm, scale, then clamp to saturated value.

Parameters:

- pSrc* Source Signal Pointer.
- pDst* Destination Signal Pointer.
- nLength* Signal Length.
- nScaleFactor* Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.155 SumLn

Sums up the natural logarithm of each sample of a signal.

Functions

- `NppStatus nppsSumLnGetBufferSize_32f` (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for 32f SumLn.
- `NppStatus nppsSumLn_32f` (const `Npp32f` *pSrc, int nLength, `Npp32f` *pDst, `Npp8u` *pDeviceBuffer)
32-bit floating point signal sum natural logarithm.
- `NppStatus nppsSumLnGetBufferSize_64f` (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for 64f SumLn.
- `NppStatus nppsSumLn_64f` (const `Npp64f` *pSrc, int nLength, `Npp64f` *pDst, `Npp8u` *pDeviceBuffer)
64-bit floating point signal sum natural logarithm.
- `NppStatus nppsSumLnGetBufferSize_32f64f` (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for 32f64f SumLn.
- `NppStatus nppsSumLn_32f64f` (const `Npp32f` *pSrc, int nLength, `Npp64f` *pDst, `Npp8u` *pDeviceBuffer)
32-bit floating point input, 64-bit floating point output signal sum natural logarithm.
- `NppStatus nppsSumLnGetBufferSize_16s32f` (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for 16s32f SumLn.
- `NppStatus nppsSumLn_16s32f` (const `Npp16s` *pSrc, int nLength, `Npp32f` *pDst, `Npp8u` *pDeviceBuffer)
16-bit signed short integer input, 32-bit floating point output signal sum natural logarithm.

7.155.1 Detailed Description

Sums up the natural logarithm of each sample of a signal.

7.155.2 Function Documentation

7.155.2.1 `NppStatus nppsSumLn_16s32f` (const `Npp16s` *pSrc, int nLength, `Npp32f` *pDst, `Npp8u` *pDeviceBuffer)

16-bit signed short integer input, 32-bit floating point output signal sum natural logarithm.

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pDst Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.155.2.2 NppStatus nppsSumLn_32f (const Npp32f * pSrc, int nLength, Npp32f * pDst, Npp8u * pDeviceBuffer)

32-bit floating point signal sum natural logarithm.

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pDst Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.155.2.3 NppStatus nppsSumLn_32f64f (const Npp32f * pSrc, int nLength, Npp64f * pDst, Npp8u * pDeviceBuffer)

32-bit floating point input, 64-bit floating point output signal sum natural logarithm.

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pDst Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.155.2.4 NppStatus nppsSumLn_64f (const Npp64f * pSrc, int nLength, Npp64f * pDst, Npp8u * pDeviceBuffer)

64-bit floating point signal sum natural logarithm.

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pDst Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.155.2.5 NppStatus nppsSumLnGetBufferSize_16s32f (int nLength, int * hpBufferSize)

Device scratch buffer size (in bytes) for 16s32f SumLn.

This primitive provides the correct buffer size for nppsSumLn_16s32f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.155.2.6 NppStatus nppsSumLnGetBufferSize_32f (int nLength, int * hpBufferSize)

Device scratch buffer size (in bytes) for 32f SumLn.

This primitive provides the correct buffer size for nppsSumLn_32f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.155.2.7 NppStatus nppsSumLnGetBufferSize_32f64f (int nLength, int * hpBufferSize)

Device scratch buffer size (in bytes) for 32f64f SumLn.

This primitive provides the correct buffer size for nppsSumLn_32f64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.155.2.8 NppStatus nppsSumLnGetBufferSize_64f (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for 64f SumLn.

This primitive provides the correct buffer size for nppsSumLn_64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.156 Arctan

Inverse tangent of each sample of a signal.

Functions

- `NppStatus nppsArctan_32f` (const `Npp32f` *pSrc, `Npp32f` *pDst, int nLength)
32-bit floating point signal inverse tangent.
- `NppStatus nppsArctan_64f` (const `Npp64f` *pSrc, `Npp64f` *pDst, int nLength)
64-bit floating point signal inverse tangent.
- `NppStatus nppsArctan_32f_I` (`Npp32f` *pSrcDst, int nLength)
32-bit floating point signal inverse tangent.
- `NppStatus nppsArctan_64f_I` (`Npp64f` *pSrcDst, int nLength)
64-bit floating point signal inverse tangent.

7.156.1 Detailed Description

Inverse tangent of each sample of a signal.

7.156.2 Function Documentation

7.156.2.1 `NppStatus nppsArctan_32f` (const `Npp32f` * pSrc, `Npp32f` * pDst, int nLength)

32-bit floating point signal inverse tangent.

Parameters:

- pSrc* Source Signal Pointer.
- pDst* Destination Signal Pointer.
- nLength* Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.156.2.2 `NppStatus nppsArctan_32f_I` (`Npp32f` * pSrcDst, int nLength)

32-bit floating point signal inverse tangent.

Parameters:

- pSrcDst* In-Place Signal Pointer.
- nLength* Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.156.2.3 NppStatus nppsArctan_64f (const Npp64f * pSrc, Npp64f * pDst, int nLength)

64-bit floating point signal inverse tangent.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.156.2.4 NppStatus nppsArctan_64f_I (Npp64f * pSrcDst, int nLength)

64-bit floating point signal inverse tangent.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.157 Normalize

Normalize each sample of a real or complex signal using offset and division operations.

Functions

- `NppStatus nppsNormalize_32f` (const `Npp32f` *pSrc, `Npp32f` *pDst, int nLength, `Npp32f` vSub, `Npp32f` vDiv)
32-bit floating point signal normalize.
- `NppStatus nppsNormalize_32fc` (const `Npp32fc` *pSrc, `Npp32fc` *pDst, int nLength, `Npp32fc` vSub, `Npp32fc` vDiv)
32-bit complex floating point signal normalize.
- `NppStatus nppsNormalize_64f` (const `Npp64f` *pSrc, `Npp64f` *pDst, int nLength, `Npp64f` vSub, `Npp64f` vDiv)
64-bit floating point signal normalize.
- `NppStatus nppsNormalize_64fc` (const `Npp64fc` *pSrc, `Npp64fc` *pDst, int nLength, `Npp64fc` vSub, `Npp64fc` vDiv)
64-bit complex floating point signal normalize.
- `NppStatus nppsNormalize_16s_Sfs` (const `Npp16s` *pSrc, `Npp16s` *pDst, int nLength, `Npp16s` vSub, int vDiv, int nScaleFactor)
16-bit signed short signal normalize, scale, then clamp to saturated value.
- `NppStatus nppsNormalize_16sc_Sfs` (const `Npp16sc` *pSrc, `Npp16sc` *pDst, int nLength, `Npp16sc` vSub, int vDiv, int nScaleFactor)
16-bit complex signed short signal normalize, scale, then clamp to saturated value.

7.157.1 Detailed Description

Normalize each sample of a real or complex signal using offset and division operations.

7.157.2 Function Documentation

7.157.2.1 `NppStatus nppsNormalize_16s_Sfs` (const `Npp16s` * pSrc, `Npp16s` * pDst, int nLength, `Npp16s` vSub, int vDiv, int nScaleFactor)

16-bit signed short signal normalize, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

vSub value subtracted from each signal element before division

vDiv divisor of post-subtracted signal element dividend

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.157.2.2 NppStatus nppsNormalize_16sc_Sfs (const Npp16sc * pSrc, Npp16sc * pDst, int nLength, Npp16sc vSub, int vDiv, int nScaleFactor)

16-bit complex signed short signal normalize, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

vSub value subtracted from each signal element before division

vDiv divisor of post-subtracted signal element dividend

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.157.2.3 NppStatus nppsNormalize_32f (const Npp32f * pSrc, Npp32f * pDst, int nLength, Npp32f vSub, Npp32f vDiv)

32-bit floating point signal normalize.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

vSub value subtracted from each signal element before division

vDiv divisor of post-subtracted signal element dividend

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.157.2.4 NppStatus nppsNormalize_32fc (const Npp32fc * pSrc, Npp32fc * pDst, int nLength, Npp32fc vSub, Npp32fc vDiv)

32-bit complex floating point signal normalize.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

vSub value subtracted from each signal element before division

vDiv divisor of post-subtracted signal element dividend

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.157.2.5 NppStatus nppsNormalize_64f (const Npp64f * pSrc, Npp64f * pDst, int nLength, Npp64f vSub, Npp64f vDiv)

64-bit floating point signal normalize.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

vSub value subtracted from each signal element before division

vDiv divisor of post-subtracted signal element dividend

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.157.2.6 NppStatus nppsNormalize_64fc (const Npp64fc * pSrc, Npp64fc * pDst, int nLength, Npp64fc vSub, Npp64fc vDiv)

64-bit complex floating point signal normalize.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

vSub value subtracted from each signal element before division

vDiv divisor of post-subtracted signal element dividend

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.158 Cauchy, CauchyD, and CauchyDD2

Determine Cauchy robust error function and its first and second derivatives for each sample of a signal.

Functions

- `NppStatus nppsCauchy_32f_I (Npp32f *pSrcDst, int nLength, Npp32f nParam)`
32-bit floating point signal Cauchy error calculation.
- `NppStatus nppsCauchyD_32f_I (Npp32f *pSrcDst, int nLength, Npp32f nParam)`
32-bit floating point signal Cauchy first derivative.
- `NppStatus nppsCauchyDD2_32f_I (Npp32f *pSrcDst, Npp32f *pD2FVal, int nLength, Npp32f nParam)`
32-bit floating point signal Cauchy first and second derivatives.

7.158.1 Detailed Description

Determine Cauchy robust error function and its first and second derivatives for each sample of a signal.

7.158.2 Function Documentation

7.158.2.1 `NppStatus nppsCauchy_32f_I (Npp32f *pSrcDst, int nLength, Npp32f nParam)`

32-bit floating point signal Cauchy error calculation.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nLength [Signal Length](#).

nParam constant used in Cauchy formula

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.158.2.2 `NppStatus nppsCauchyD_32f_I (Npp32f *pSrcDst, int nLength, Npp32f nParam)`

32-bit floating point signal Cauchy first derivative.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nLength [Signal Length](#).

nParam constant used in Cauchy formula

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.158.2.3 NppStatus nppsCauchyDD2_32f_I (Npp32f * pSrcDst, Npp32f * pD2FVal, int nLength, Npp32f nParam)

32-bit floating point signal Cauchy first and second derivatives.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

pD2FVal [Source Signal Pointer](#). This signal contains the second derivative of the source signal.

nLength [Signal Length](#).

nParam constant used in Cauchy formula

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.159 Logical And Shift Operations

Modules

- [AndC](#)
Bitwise AND of a constant and each sample of a signal.
- [And](#)
Sample by sample bitwise AND of samples from two signals.
- [OrC](#)
Bitwise OR of a constant and each sample of a signal.
- [Or](#)
Sample by sample bitwise OR of the samples from two signals.
- [XorC](#)
Bitwise XOR of a constant and each sample of a signal.
- [Xor](#)
Sample by sample bitwise XOR of the samples from two signals.
- [Not](#)
Bitwise NOT of each sample of a signal.
- [LShiftC](#)
Left shifts the bits of each sample of a signal by a constant amount.
- [RShiftC](#)
Right shifts the bits of each sample of a signal by a constant amount.

7.160 AndC

Bitwise AND of a constant and each sample of a signal.

Functions

- `NppStatus nppsAndC_8u` (const `Npp8u *pSrc`, `Npp8u nValue`, `Npp8u *pDst`, int `nLength`)
8-bit unsigned char signal and with constant.
- `NppStatus nppsAndC_16u` (const `Npp16u *pSrc`, `Npp16u nValue`, `Npp16u *pDst`, int `nLength`)
16-bit unsigned short signal and with constant.
- `NppStatus nppsAndC_32u` (const `Npp32u *pSrc`, `Npp32u nValue`, `Npp32u *pDst`, int `nLength`)
32-bit unsigned integer signal and with constant.
- `NppStatus nppsAndC_8u_I` (`Npp8u nValue`, `Npp8u *pSrcDst`, int `nLength`)
8-bit unsigned char in place signal and with constant.
- `NppStatus nppsAndC_16u_I` (`Npp16u nValue`, `Npp16u *pSrcDst`, int `nLength`)
16-bit unsigned short in place signal and with constant.
- `NppStatus nppsAndC_32u_I` (`Npp32u nValue`, `Npp32u *pSrcDst`, int `nLength`)
32-bit unsigned signed integer in place signal and with constant.

7.160.1 Detailed Description

Bitwise AND of a constant and each sample of a signal.

7.160.2 Function Documentation

7.160.2.1 `NppStatus nppsAndC_16u` (const `Npp16u *pSrc`, `Npp16u nValue`, `Npp16u *pDst`, int `nLength`)

16-bit unsigned short signal and with constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be anded with each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.160.2.2 NppStatus nppsAndC_16u_I (Npp16u nValue, Npp16u * pSrcDst, int nLength)

16-bit unsigned short in place signal and with constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be added with each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.160.2.3 NppStatus nppsAndC_32u (const Npp32u * pSrc, Npp32u nValue, Npp32u * pDst, int nLength)

32-bit unsigned integer signal and with constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be added with each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.160.2.4 NppStatus nppsAndC_32u_I (Npp32u nValue, Npp32u * pSrcDst, int nLength)

32-bit unsigned signed integer in place signal and with constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be added with each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.160.2.5 NppStatus nppsAndC_8u (const Npp8u * pSrc, Npp8u nValue, Npp8u * pDst, int nLength)

8-bit unsigned char signal and with constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be added with each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.160.2.6 NppStatus nppsAndC_8u_I (Npp8u nValue, Npp8u * pSrcDst, int nLength)

8-bit unsigned char in place signal and with constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be added with each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.161 And

Sample by sample bitwise AND of samples from two signals.

Functions

- `NppStatus nppsAnd_8u` (const `Npp8u` *pSrc1, const `Npp8u` *pSrc2, `Npp8u` *pDst, int nLength)
8-bit unsigned char signal and with signal.
- `NppStatus nppsAnd_16u` (const `Npp16u` *pSrc1, const `Npp16u` *pSrc2, `Npp16u` *pDst, int nLength)
16-bit unsigned short signal and with signal.
- `NppStatus nppsAnd_32u` (const `Npp32u` *pSrc1, const `Npp32u` *pSrc2, `Npp32u` *pDst, int nLength)
32-bit unsigned integer signal and with signal.
- `NppStatus nppsAnd_8u_I` (const `Npp8u` *pSrc, `Npp8u` *pSrcDst, int nLength)
8-bit unsigned char in place signal and with signal.
- `NppStatus nppsAnd_16u_I` (const `Npp16u` *pSrc, `Npp16u` *pSrcDst, int nLength)
16-bit unsigned short in place signal and with signal.
- `NppStatus nppsAnd_32u_I` (const `Npp32u` *pSrc, `Npp32u` *pSrcDst, int nLength)
32-bit unsigned integer in place signal and with signal.

7.161.1 Detailed Description

Sample by sample bitwise AND of samples from two signals.

7.161.2 Function Documentation

7.161.2.1 `NppStatus nppsAnd_16u` (const `Npp16u` *pSrc1, const `Npp16u` *pSrc2, `Npp16u` *pDst, int nLength)

16-bit unsigned short signal and with signal.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be anded with signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.161.2.2 NppStatus nppsAnd_16u_I (const Npp16u * pSrc, Npp16u * pSrcDst, int nLength)

16-bit unsigned short in place signal and with signal.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be anded with signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.161.2.3 NppStatus nppsAnd_32u (const Npp32u * pSrc1, const Npp32u * pSrc2, Npp32u * pDst, int nLength)

32-bit unsigned integer signal and with signal.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be anded with signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.161.2.4 NppStatus nppsAnd_32u_I (const Npp32u * pSrc, Npp32u * pSrcDst, int nLength)

32-bit unsigned integer in place signal and with signal.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be anded with signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.161.2.5 NppStatus nppsAnd_8u (const Npp8u * pSrc1, const Npp8u * pSrc2, Npp8u * pDst, int nLength)

8-bit unsigned char signal and with signal.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be anded with signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.161.2.6 NppStatus nppsAnd_8u_I (const Npp8u * pSrc, Npp8u * pSrcDst, int nLength)

8-bit unsigned char in place signal and with signal.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be anded with signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.162 OrC

Bitwise OR of a constant and each sample of a signal.

Functions

- `NppStatus nppsOrC_8u` (const `Npp8u` *pSrc, `Npp8u` nValue, `Npp8u` *pDst, int nLength)
8-bit unsigned char signal or with constant.
- `NppStatus nppsOrC_16u` (const `Npp16u` *pSrc, `Npp16u` nValue, `Npp16u` *pDst, int nLength)
16-bit unsigned short signal or with constant.
- `NppStatus nppsOrC_32u` (const `Npp32u` *pSrc, `Npp32u` nValue, `Npp32u` *pDst, int nLength)
32-bit unsigned integer signal or with constant.
- `NppStatus nppsOrC_8u_I` (`Npp8u` nValue, `Npp8u` *pSrcDst, int nLength)
8-bit unsigned char in place signal or with constant.
- `NppStatus nppsOrC_16u_I` (`Npp16u` nValue, `Npp16u` *pSrcDst, int nLength)
16-bit unsigned short in place signal or with constant.
- `NppStatus nppsOrC_32u_I` (`Npp32u` nValue, `Npp32u` *pSrcDst, int nLength)
32-bit unsigned signed integer in place signal or with constant.

7.162.1 Detailed Description

Bitwise OR of a constant and each sample of a signal.

7.162.2 Function Documentation

7.162.2.1 `NppStatus nppsOrC_16u` (const `Npp16u` *pSrc, `Npp16u` nValue, `Npp16u` *pDst, int nLength)

16-bit unsigned short signal or with constant.

Parameters:

- pSrc* Source Signal Pointer.
- nValue* Constant value to be ored with each vector element
- pDst* Destination Signal Pointer.
- nLength* Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.162.2.2 NppStatus nppsOrC_16u_I (Npp16u nValue, Npp16u * pSrcDst, int nLength)

16-bit unsigned short in place signal or with constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be ored with each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.162.2.3 NppStatus nppsOrC_32u (const Npp32u * pSrc, Npp32u nValue, Npp32u * pDst, int nLength)

32-bit unsigned integer signal or with constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be ored with each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.162.2.4 NppStatus nppsOrC_32u_I (Npp32u nValue, Npp32u * pSrcDst, int nLength)

32-bit unsigned signed integer in place signal or with constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be ored with each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.162.2.5 NppStatus nppsOrC_8u (const Npp8u * pSrc, Npp8u nValue, Npp8u * pDst, int nLength)

8-bit unsigned char signal or with constant.

Parameters:

pSrc Source Signal Pointer.
nValue Constant value to be ored with each vector element
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.162.2.6 NppStatus nppsOrC_8u_I (Npp8u nValue, Npp8u * pSrcDst, int nLength)

8-bit unsigned char in place signal or with constant.

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value to be ored with each vector element
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.163 Or

Sample by sample bitwise OR of the samples from two signals.

Functions

- `NppStatus nppsOr_8u` (const `Npp8u` *pSrc1, const `Npp8u` *pSrc2, `Npp8u` *pDst, int nLength)
8-bit unsigned char signal or with signal.
- `NppStatus nppsOr_16u` (const `Npp16u` *pSrc1, const `Npp16u` *pSrc2, `Npp16u` *pDst, int nLength)
16-bit unsigned short signal or with signal.
- `NppStatus nppsOr_32u` (const `Npp32u` *pSrc1, const `Npp32u` *pSrc2, `Npp32u` *pDst, int nLength)
32-bit unsigned integer signal or with signal.
- `NppStatus nppsOr_8u_I` (const `Npp8u` *pSrc, `Npp8u` *pSrcDst, int nLength)
8-bit unsigned char in place signal or with signal.
- `NppStatus nppsOr_16u_I` (const `Npp16u` *pSrc, `Npp16u` *pSrcDst, int nLength)
16-bit unsigned short in place signal or with signal.
- `NppStatus nppsOr_32u_I` (const `Npp32u` *pSrc, `Npp32u` *pSrcDst, int nLength)
32-bit unsigned integer in place signal or with signal.

7.163.1 Detailed Description

Sample by sample bitwise OR of the samples from two signals.

7.163.2 Function Documentation

7.163.2.1 `NppStatus nppsOr_16u` (const `Npp16u` *pSrc1, const `Npp16u` *pSrc2, `Npp16u` *pDst, int nLength)

16-bit unsigned short signal or with signal.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be ored with signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.163.2.2 NppStatus nppsOr_16u_I (const Npp16u * pSrc, Npp16u * pSrcDst, int nLength)

16-bit unsigned short in place signal or with signal.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be ored with signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.163.2.3 NppStatus nppsOr_32u (const Npp32u * pSrc1, const Npp32u * pSrc2, Npp32u * pDst, int nLength)

32-bit unsigned integer signal or with signal.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be ored with signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.163.2.4 NppStatus nppsOr_32u_I (const Npp32u * pSrc, Npp32u * pSrcDst, int nLength)

32-bit unsigned integer in place signal or with signal.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be ored with signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.163.2.5 NppStatus nppsOr_8u (const Npp8u * pSrc1, const Npp8u * pSrc2, Npp8u * pDst, int nLength)

8-bit unsigned char signal or with signal.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be ored with signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.163.2.6 NppStatus nppsOr_8u_I (const Npp8u * pSrc, Npp8u * pSrcDst, int nLength)

8-bit unsigned char in place signal or with signal.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be ored with signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.164 XorC

Bitwise XOR of a constant and each sample of a signal.

Functions

- `NppStatus nppsXorC_8u` (const `Npp8u *pSrc`, `Npp8u nValue`, `Npp8u *pDst`, int `nLength`)
8-bit unsigned char signal exclusive or with constant.
- `NppStatus nppsXorC_16u` (const `Npp16u *pSrc`, `Npp16u nValue`, `Npp16u *pDst`, int `nLength`)
16-bit unsigned short signal exclusive or with constant.
- `NppStatus nppsXorC_32u` (const `Npp32u *pSrc`, `Npp32u nValue`, `Npp32u *pDst`, int `nLength`)
32-bit unsigned integer signal exclusive or with constant.
- `NppStatus nppsXorC_8u_I` (`Npp8u nValue`, `Npp8u *pSrcDst`, int `nLength`)
8-bit unsigned char in place signal exclusive or with constant.
- `NppStatus nppsXorC_16u_I` (`Npp16u nValue`, `Npp16u *pSrcDst`, int `nLength`)
16-bit unsigned short in place signal exclusive or with constant.
- `NppStatus nppsXorC_32u_I` (`Npp32u nValue`, `Npp32u *pSrcDst`, int `nLength`)
32-bit unsigned signed integer in place signal exclusive or with constant.

7.164.1 Detailed Description

Bitwise XOR of a constant and each sample of a signal.

7.164.2 Function Documentation

7.164.2.1 `NppStatus nppsXorC_16u` (const `Npp16u *pSrc`, `Npp16u nValue`, `Npp16u *pDst`, int `nLength`)

16-bit unsigned short signal exclusive or with constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be exclusive ored with each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.164.2.2 NppStatus nppsXorC_16u_I (Npp16u nValue, Npp16u * pSrcDst, int nLength)

16-bit unsigned short in place signal exclusive or with constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be exclusive ored with each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.164.2.3 NppStatus nppsXorC_32u (const Npp32u * pSrc, Npp32u nValue, Npp32u * pDst, int nLength)

32-bit unsigned integer signal exclusive or with constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be exclusive ored with each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.164.2.4 NppStatus nppsXorC_32u_I (Npp32u nValue, Npp32u * pSrcDst, int nLength)

32-bit unsigned signed integer in place signal exclusive or with constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be exclusive ored with each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.164.2.5 NppStatus nppsXorC_8u (const Npp8u * pSrc, Npp8u nValue, Npp8u * pDst, int nLength)

8-bit unsigned char signal exclusive or with constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be exclusive ored with each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.164.2.6 NppStatus nppsXorC_8u_I (Npp8u nValue, Npp8u * pSrcDst, int nLength)

8-bit unsigned char in place signal exclusive or with constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be exclusive ored with each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.165 Xor

Sample by sample bitwise XOR of the samples from two signals.

Functions

- `NppStatus nppsXor_8u` (const `Npp8u` *pSrc1, const `Npp8u` *pSrc2, `Npp8u` *pDst, int nLength)
8-bit unsigned char signal exclusive or with signal.
- `NppStatus nppsXor_16u` (const `Npp16u` *pSrc1, const `Npp16u` *pSrc2, `Npp16u` *pDst, int nLength)
16-bit unsigned short signal exclusive or with signal.
- `NppStatus nppsXor_32u` (const `Npp32u` *pSrc1, const `Npp32u` *pSrc2, `Npp32u` *pDst, int nLength)
32-bit unsigned integer signal exclusive or with signal.
- `NppStatus nppsXor_8u_I` (const `Npp8u` *pSrc, `Npp8u` *pSrcDst, int nLength)
8-bit unsigned char in place signal exclusive or with signal.
- `NppStatus nppsXor_16u_I` (const `Npp16u` *pSrc, `Npp16u` *pSrcDst, int nLength)
16-bit unsigned short in place signal exclusive or with signal.
- `NppStatus nppsXor_32u_I` (const `Npp32u` *pSrc, `Npp32u` *pSrcDst, int nLength)
32-bit unsigned integer in place signal exclusive or with signal.

7.165.1 Detailed Description

Sample by sample bitwise XOR of the samples from two signals.

7.165.2 Function Documentation

7.165.2.1 `NppStatus nppsXor_16u` (const `Npp16u` *pSrc1, const `Npp16u` *pSrc2, `Npp16u` *pDst, int nLength)

16-bit unsigned short signal exclusive or with signal.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be exclusive ored with signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.165.2.2 NppStatus nppsXor_16u_I (const Npp16u * pSrc, Npp16u * pSrcDst, int nLength)

16-bit unsigned short in place signal exclusive or with signal.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be exclusive ored with signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.165.2.3 NppStatus nppsXor_32u (const Npp32u * pSrc1, const Npp32u * pSrc2, Npp32u * pDst, int nLength)

32-bit unsigned integer signal exclusive or with signal.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be exclusive ored with signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.165.2.4 NppStatus nppsXor_32u_I (const Npp32u * pSrc, Npp32u * pSrcDst, int nLength)

32-bit unsigned integer in place signal exclusive or with signal.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be exclusive ored with signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.165.2.5 NppStatus nppsXor_8u (const Npp8u * pSrc1, const Npp8u * pSrc2, Npp8u * pDst, int nLength)

8-bit unsigned char signal exclusive or with signal.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be exclusive ored with signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.165.2.6 NppStatus nppsXor_8u_I (const Npp8u * pSrc, Npp8u * pSrcDst, int nLength)

8-bit unsigned char in place signal exclusive or with signal.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be exclusive ored with signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.166 Not

Bitwise NOT of each sample of a signal.

Functions

- [NppStatus nppsNot_8u](#) (const [Npp8u](#) *pSrc, [Npp8u](#) *pDst, int nLength)
8-bit unsigned char not signal.
- [NppStatus nppsNot_16u](#) (const [Npp16u](#) *pSrc, [Npp16u](#) *pDst, int nLength)
16-bit unsigned short not signal.
- [NppStatus nppsNot_32u](#) (const [Npp32u](#) *pSrc, [Npp32u](#) *pDst, int nLength)
32-bit unsigned integer not signal.
- [NppStatus nppsNot_8u_I](#) ([Npp8u](#) *pSrcDst, int nLength)
8-bit unsigned char in place not signal.
- [NppStatus nppsNot_16u_I](#) ([Npp16u](#) *pSrcDst, int nLength)
16-bit unsigned short in place not signal.
- [NppStatus nppsNot_32u_I](#) ([Npp32u](#) *pSrcDst, int nLength)
32-bit unsigned signed integer in place not signal.

7.166.1 Detailed Description

Bitwise NOT of each sample of a signal.

7.166.2 Function Documentation

7.166.2.1 [NppStatus nppsNot_16u](#) (const [Npp16u](#) * pSrc, [Npp16u](#) * pDst, int nLength)

16-bit unsigned short not signal.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.166.2.2 NppStatus nppsNot_16u_I (Npp16u * pSrcDst, int nLength)

16-bit unsigned short in place not signal.

Parameters:

pSrcDst In-Place Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.166.2.3 NppStatus nppsNot_32u (const Npp32u * pSrc, Npp32u * pDst, int nLength)

32-bit unsigned integer not signal.

Parameters:

pSrc Source Signal Pointer.
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.166.2.4 NppStatus nppsNot_32u_I (Npp32u * pSrcDst, int nLength)

32-bit unsigned signed integer in place not signal.

Parameters:

pSrcDst In-Place Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.166.2.5 NppStatus nppsNot_8u (const Npp8u * pSrc, Npp8u * pDst, int nLength)

8-bit unsigned char not signal.

Parameters:

pSrc Source Signal Pointer.
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.166.2.6 `NppStatus nppsNot_8u_I(Npp8u * pSrcDst, int nLength)`

8-bit unsigned char in place not signal.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.167 LShiftC

Left shifts the bits of each sample of a signal by a constant amount.

Functions

- `NppStatus nppsLShiftC_8u` (const `Npp8u` *pSrc, int nValue, `Npp8u` *pDst, int nLength)
8-bit unsigned char signal left shift with constant.
- `NppStatus nppsLShiftC_16u` (const `Npp16u` *pSrc, int nValue, `Npp16u` *pDst, int nLength)
16-bit unsigned short signal left shift with constant.
- `NppStatus nppsLShiftC_16s` (const `Npp16s` *pSrc, int nValue, `Npp16s` *pDst, int nLength)
16-bit signed short signal left shift with constant.
- `NppStatus nppsLShiftC_32u` (const `Npp32u` *pSrc, int nValue, `Npp32u` *pDst, int nLength)
32-bit unsigned integer signal left shift with constant.
- `NppStatus nppsLShiftC_32s` (const `Npp32s` *pSrc, int nValue, `Npp32s` *pDst, int nLength)
32-bit signed integer signal left shift with constant.
- `NppStatus nppsLShiftC_8u_I` (int nValue, `Npp8u` *pSrcDst, int nLength)
8-bit unsigned char in place signal left shift with constant.
- `NppStatus nppsLShiftC_16u_I` (int nValue, `Npp16u` *pSrcDst, int nLength)
16-bit unsigned short in place signal left shift with constant.
- `NppStatus nppsLShiftC_16s_I` (int nValue, `Npp16s` *pSrcDst, int nLength)
16-bit signed short in place signal left shift with constant.
- `NppStatus nppsLShiftC_32u_I` (int nValue, `Npp32u` *pSrcDst, int nLength)
32-bit unsigned signed integer in place signal left shift with constant.
- `NppStatus nppsLShiftC_32s_I` (int nValue, `Npp32s` *pSrcDst, int nLength)
32-bit signed signed integer in place signal left shift with constant.

7.167.1 Detailed Description

Left shifts the bits of each sample of a signal by a constant amount.

7.167.2 Function Documentation

7.167.2.1 `NppStatus nppsLShiftC_16s` (const `Npp16s` *pSrc, int nValue, `Npp16s` *pDst, int nLength)

16-bit signed short signal left shift with constant.

Parameters:

pSrc Source Signal Pointer.
nValue Constant value to be used to left shift each vector element
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.167.2.2 NppStatus nppsLShiftC_16s_I (int nValue, Npp16s * pSrcDst, int nLength)

16-bit signed short in place signal left shift with constant.

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value to be used to left shift each vector element
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.167.2.3 NppStatus nppsLShiftC_16u (const Npp16u * pSrc, int nValue, Npp16u * pDst, int nLength)

16-bit unsigned short signal left shift with constant.

Parameters:

pSrc Source Signal Pointer.
nValue Constant value to be used to left shift each vector element
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.167.2.4 NppStatus nppsLShiftC_16u_I (int nValue, Npp16u * pSrcDst, int nLength)

16-bit unsigned short in place signal left shift with constant.

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value to be used to left shift each vector element
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.167.2.5 NppStatus nppsLShiftC_32s (const Npp32s * pSrc, int nValue, Npp32s * pDst, int nLength)

32-bit signed integer signal left shift with constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be used to left shift each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.167.2.6 NppStatus nppsLShiftC_32s_I (int nValue, Npp32s * pSrcDst, int nLength)

32-bit signed integer in place signal left shift with constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be used to left shift each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.167.2.7 NppStatus nppsLShiftC_32u (const Npp32u * pSrc, int nValue, Npp32u * pDst, int nLength)

32-bit unsigned integer signal left shift with constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be used to left shift each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.167.2.8 NppStatus nppsLShiftC_32u_I (int *nValue*, Npp32u * *pSrcDst*, int *nLength*)

32-bit unsigned signed integer in place signal left shift with constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be used to left shift each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.167.2.9 NppStatus nppsLShiftC_8u (const Npp8u * *pSrc*, int *nValue*, Npp8u * *pDst*, int *nLength*)

8-bit unsigned char signal left shift with constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be used to left shift each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.167.2.10 NppStatus nppsLShiftC_8u_I (int *nValue*, Npp8u * *pSrcDst*, int *nLength*)

8-bit unsigned char in place signal left shift with constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be used to left shift each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.168 RShiftC

Right shifts the bits of each sample of a signal by a constant amount.

Functions

- `NppStatus nppsRShiftC_8u` (const `Npp8u` *pSrc, int nValue, `Npp8u` *pDst, int nLength)
8-bit unsigned char signal right shift with constant.
- `NppStatus nppsRShiftC_16u` (const `Npp16u` *pSrc, int nValue, `Npp16u` *pDst, int nLength)
16-bit unsigned short signal right shift with constant.
- `NppStatus nppsRShiftC_16s` (const `Npp16s` *pSrc, int nValue, `Npp16s` *pDst, int nLength)
16-bit signed short signal right shift with constant.
- `NppStatus nppsRShiftC_32u` (const `Npp32u` *pSrc, int nValue, `Npp32u` *pDst, int nLength)
32-bit unsigned integer signal right shift with constant.
- `NppStatus nppsRShiftC_32s` (const `Npp32s` *pSrc, int nValue, `Npp32s` *pDst, int nLength)
32-bit signed integer signal right shift with constant.
- `NppStatus nppsRShiftC_8u_I` (int nValue, `Npp8u` *pSrcDst, int nLength)
8-bit unsigned char in place signal right shift with constant.
- `NppStatus nppsRShiftC_16u_I` (int nValue, `Npp16u` *pSrcDst, int nLength)
16-bit unsigned short in place signal right shift with constant.
- `NppStatus nppsRShiftC_16s_I` (int nValue, `Npp16s` *pSrcDst, int nLength)
16-bit signed short in place signal right shift with constant.
- `NppStatus nppsRShiftC_32u_I` (int nValue, `Npp32u` *pSrcDst, int nLength)
32-bit unsigned signed integer in place signal right shift with constant.
- `NppStatus nppsRShiftC_32s_I` (int nValue, `Npp32s` *pSrcDst, int nLength)
32-bit signed signed integer in place signal right shift with constant.

7.168.1 Detailed Description

Right shifts the bits of each sample of a signal by a constant amount.

7.168.2 Function Documentation

7.168.2.1 `NppStatus nppsRShiftC_16s` (const `Npp16s` *pSrc, int nValue, `Npp16s` *pDst, int nLength)

16-bit signed short signal right shift with constant.

Parameters:

pSrc Source Signal Pointer.
nValue Constant value to be used to right shift each vector element
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.168.2.2 NppStatus nppsRShiftC_16s_I (int nValue, Npp16s * pSrcDst, int nLength)

16-bit signed short in place signal right shift with constant.

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value to be used to right shift each vector element
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.168.2.3 NppStatus nppsRShiftC_16u (const Npp16u * pSrc, int nValue, Npp16u * pDst, int nLength)

16-bit unsigned short signal right shift with constant.

Parameters:

pSrc Source Signal Pointer.
nValue Constant value to be used to right shift each vector element
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.168.2.4 NppStatus nppsRShiftC_16u_I (int nValue, Npp16u * pSrcDst, int nLength)

16-bit unsigned short in place signal right shift with constant.

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value to be used to right shift each vector element
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.168.2.5 NppStatus nppsRShiftC_32s (const Npp32s * pSrc, int nValue, Npp32s * pDst, int nLength)

32-bit signed integer signal right shift with constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be used to right shift each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.168.2.6 NppStatus nppsRShiftC_32s_I (int nValue, Npp32s * pSrcDst, int nLength)

32-bit signed integer in place signal right shift with constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be used to right shift each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.168.2.7 NppStatus nppsRShiftC_32u (const Npp32u * pSrc, int nValue, Npp32u * pDst, int nLength)

32-bit unsigned integer signal right shift with constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be used to right shift each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.168.2.8 NppStatus nppsRShiftC_32u_I (int *nValue*, Npp32u * *pSrcDst*, int *nLength*)

32-bit unsigned signed integer in place signal right shift with constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be used to right shift each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.168.2.9 NppStatus nppsRShiftC_8u (const Npp8u * *pSrc*, int *nValue*, Npp8u * *pDst*, int *nLength*)

8-bit unsigned char signal right shift with constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be used to right shift each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.168.2.10 NppStatus nppsRShiftC_8u_I (int *nValue*, Npp8u * *pSrcDst*, int *nLength*)

8-bit unsigned char in place signal right shift with constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be used to right shift each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.169 Conversion Functions

Modules

- [Convert](#)
- [Threshold](#)

7.170 Convert

Convert

Routines for converting the sample-data type of signals.

- `NppStatus nppsConvert_8s16s` (const `Npp8s` *pSrc, `Npp16s` *pDst, int nLength)
- `NppStatus nppsConvert_8s32f` (const `Npp8s` *pSrc, `Npp32f` *pDst, int nLength)
- `NppStatus nppsConvert_8u32f` (const `Npp8u` *pSrc, `Npp32f` *pDst, int nLength)
- `NppStatus nppsConvert_16s8s_Sfs` (const `Npp16s` *pSrc, `Npp8s` *pDst, `Npp32u` nLength, `NppRoundMode` eRoundMode, int nScaleFactor)
- `NppStatus nppsConvert_16s32s` (const `Npp16s` *pSrc, `Npp32s` *pDst, int nLength)
- `NppStatus nppsConvert_16s32f` (const `Npp16s` *pSrc, `Npp32f` *pDst, int nLength)
- `NppStatus nppsConvert_16u32f` (const `Npp16u` *pSrc, `Npp32f` *pDst, int nLength)
- `NppStatus nppsConvert_32s16s` (const `Npp32s` *pSrc, `Npp16s` *pDst, int nLength)
- `NppStatus nppsConvert_32s32f` (const `Npp32s` *pSrc, `Npp32f` *pDst, int nLength)
- `NppStatus nppsConvert_32s64f` (const `Npp32s` *pSrc, `Npp64f` *pDst, int nLength)
- `NppStatus nppsConvert_32f64f` (const `Npp32f` *pSrc, `Npp64f` *pDst, int nLength)
- `NppStatus nppsConvert_64s64f` (const `Npp64s` *pSrc, `Npp64f` *pDst, int nLength)
- `NppStatus nppsConvert_64f32f` (const `Npp64f` *pSrc, `Npp32f` *pDst, int nLength)
- `NppStatus nppsConvert_16s32f_Sfs` (const `Npp16s` *pSrc, `Npp32f` *pDst, int nLength, int nScaleFactor)
- `NppStatus nppsConvert_16s64f_Sfs` (const `Npp16s` *pSrc, `Npp64f` *pDst, int nLength, int nScaleFactor)
- `NppStatus nppsConvert_32s16s_Sfs` (const `Npp32s` *pSrc, `Npp16s` *pDst, int nLength, int nScaleFactor)
- `NppStatus nppsConvert_32s32f_Sfs` (const `Npp32s` *pSrc, `Npp32f` *pDst, int nLength, int nScaleFactor)
- `NppStatus nppsConvert_32s64f_Sfs` (const `Npp32s` *pSrc, `Npp64f` *pDst, int nLength, int nScaleFactor)
- `NppStatus nppsConvert_32f8s_Sfs` (const `Npp32f` *pSrc, `Npp8s` *pDst, int nLength, `NppRoundMode` eRoundMode, int nScaleFactor)
- `NppStatus nppsConvert_32f8u_Sfs` (const `Npp32f` *pSrc, `Npp8u` *pDst, int nLength, `NppRoundMode` eRoundMode, int nScaleFactor)
- `NppStatus nppsConvert_32f16s_Sfs` (const `Npp32f` *pSrc, `Npp16s` *pDst, int nLength, `NppRoundMode` eRoundMode, int nScaleFactor)
- `NppStatus nppsConvert_32f16u_Sfs` (const `Npp32f` *pSrc, `Npp16u` *pDst, int nLength, `NppRoundMode` eRoundMode, int nScaleFactor)
- `NppStatus nppsConvert_32f32s_Sfs` (const `Npp32f` *pSrc, `Npp32s` *pDst, int nLength, `NppRoundMode` eRoundMode, int nScaleFactor)
- `NppStatus nppsConvert_64s32s_Sfs` (const `Npp64s` *pSrc, `Npp32s` *pDst, int nLength, `NppRoundMode` eRoundMode, int nScaleFactor)
- `NppStatus nppsConvert_64f16s_Sfs` (const `Npp64f` *pSrc, `Npp16s` *pDst, int nLength, `NppRoundMode` eRoundMode, int nScaleFactor)
- `NppStatus nppsConvert_64f32s_Sfs` (const `Npp64f` *pSrc, `Npp32s` *pDst, int nLength, `NppRoundMode` eRoundMode, int nScaleFactor)
- `NppStatus nppsConvert_64f64s_Sfs` (const `Npp64f` *pSrc, `Npp64s` *pDst, int nLength, `NppRoundMode` eRoundMode, int nScaleFactor)

7.170.1 Function Documentation

- 7.170.1.1 `NppStatus nppsConvert_16s32f` (const `Npp16s * pSrc`, `Npp32f * pDst`, `int nLength`)
- 7.170.1.2 `NppStatus nppsConvert_16s32f_Sfs` (const `Npp16s * pSrc`, `Npp32f * pDst`, `int nLength`, `int nScaleFactor`)
- 7.170.1.3 `NppStatus nppsConvert_16s32s` (const `Npp16s * pSrc`, `Npp32s * pDst`, `int nLength`)
- 7.170.1.4 `NppStatus nppsConvert_16s64f_Sfs` (const `Npp16s * pSrc`, `Npp64f * pDst`, `int nLength`, `int nScaleFactor`)
- 7.170.1.5 `NppStatus nppsConvert_16s8s_Sfs` (const `Npp16s * pSrc`, `Npp8s * pDst`, `Npp32u nLength`, `NppRoundMode eRoundMode`, `int nScaleFactor`)
- 7.170.1.6 `NppStatus nppsConvert_16u32f` (const `Npp16u * pSrc`, `Npp32f * pDst`, `int nLength`)
- 7.170.1.7 `NppStatus nppsConvert_32f16s_Sfs` (const `Npp32f * pSrc`, `Npp16s * pDst`, `int nLength`, `NppRoundMode eRoundMode`, `int nScaleFactor`)
- 7.170.1.8 `NppStatus nppsConvert_32f16u_Sfs` (const `Npp32f * pSrc`, `Npp16u * pDst`, `int nLength`, `NppRoundMode eRoundMode`, `int nScaleFactor`)
- 7.170.1.9 `NppStatus nppsConvert_32f32s_Sfs` (const `Npp32f * pSrc`, `Npp32s * pDst`, `int nLength`, `NppRoundMode eRoundMode`, `int nScaleFactor`)
- 7.170.1.10 `NppStatus nppsConvert_32f64f` (const `Npp32f * pSrc`, `Npp64f * pDst`, `int nLength`)
- 7.170.1.11 `NppStatus nppsConvert_32f8s_Sfs` (const `Npp32f * pSrc`, `Npp8s * pDst`, `int nLength`, `NppRoundMode eRoundMode`, `int nScaleFactor`)
- 7.170.1.12 `NppStatus nppsConvert_32f8u_Sfs` (const `Npp32f * pSrc`, `Npp8u * pDst`, `int nLength`, `NppRoundMode eRoundMode`, `int nScaleFactor`)
- 7.170.1.13 `NppStatus nppsConvert_32s16s` (const `Npp32s * pSrc`, `Npp16s * pDst`, `int nLength`)
- 7.170.1.14 `NppStatus nppsConvert_32s16s_Sfs` (const `Npp32s * pSrc`, `Npp16s * pDst`, `int nLength`, `int nScaleFactor`)
- 7.170.1.15 `NppStatus nppsConvert_32s32f` (const `Npp32s * pSrc`, `Npp32f * pDst`, `int nLength`)
- 7.170.1.16 `NppStatus nppsConvert_32s32f_Sfs` (const `Npp32s * pSrc`, `Npp32f * pDst`, `int nLength`, `int nScaleFactor`)
- 7.170.1.17 `NppStatus nppsConvert_32s64f` (const `Npp32s * pSrc`, `Npp64f * pDst`, `int nLength`)
- 7.170.1.18 `NppStatus nppsConvert_32s64f_Sfs` (const `Npp32s * pSrc`, `Npp64f * pDst`, `int nLength`, `int nScaleFactor`)
- 7.170.1.19 `NppStatus nppsConvert_64f16s_Sfs` (const `Npp64f * pSrc`, `Npp16s * pDst`, `int nLength`, `NppRoundMode eRoundMode`, `int nScaleFactor`)
- 7.170.1.20 `NppStatus nppsConvert_64f32f` (const `Npp64f * pSrc`, `Npp32f * pDst`, `int nLength`)
- 7.170.1.21 `NppStatus nppsConvert_64f32s_Sfs` (const `Npp64f * pSrc`, `Npp32s * pDst`, `int nLength`, `NppRoundMode eRoundMode`, `int nScaleFactor`)
- 7.170.1.22 `NppStatus nppsConvert_64f64s_Sfs` (const `Npp64f * pSrc`, `Npp64s * pDst`, `int nLength`, `NppRoundMode eRoundMode`, `int nScaleFactor`)
- 7.170.1.23 `NppStatus nppsConvert_64s32s_Sfs` (const `Npp64s * pSrc`, `Npp32s * pDst`, `int nLength`,

7.171 Threshold

Threshold Functions

Performs the threshold operation on the samples of a signal by limiting the sample values by a specified constant value.

- [NppStatus nppsThreshold_16s](#) (const [Npp16s](#) *pSrc, [Npp16s](#) *pDst, int nLength, [Npp16s](#) nLevel, [NppCmpOp](#) nRelOp)
16-bit signed short signal threshold with constant level.
- [NppStatus nppsThreshold_16s_I](#) ([Npp16s](#) *pSrcDst, int nLength, [Npp16s](#) nLevel, [NppCmpOp](#) nRelOp)
16-bit in place signed short signal threshold with constant level.
- [NppStatus nppsThreshold_16sc](#) (const [Npp16sc](#) *pSrc, [Npp16sc](#) *pDst, int nLength, [Npp16s](#) nLevel, [NppCmpOp](#) nRelOp)
16-bit signed short complex number signal threshold with constant level.
- [NppStatus nppsThreshold_16sc_I](#) ([Npp16sc](#) *pSrcDst, int nLength, [Npp16s](#) nLevel, [NppCmpOp](#) nRelOp)
16-bit in place signed short complex number signal threshold with constant level.
- [NppStatus nppsThreshold_32f](#) (const [Npp32f](#) *pSrc, [Npp32f](#) *pDst, int nLength, [Npp32f](#) nLevel, [NppCmpOp](#) nRelOp)
32-bit floating point signal threshold with constant level.
- [NppStatus nppsThreshold_32f_I](#) ([Npp32f](#) *pSrcDst, int nLength, [Npp32f](#) nLevel, [NppCmpOp](#) nRelOp)
32-bit in place floating point signal threshold with constant level.
- [NppStatus nppsThreshold_32fc](#) (const [Npp32fc](#) *pSrc, [Npp32fc](#) *pDst, int nLength, [Npp32f](#) nLevel, [NppCmpOp](#) nRelOp)
32-bit floating point complex number signal threshold with constant level.
- [NppStatus nppsThreshold_32fc_I](#) ([Npp32fc](#) *pSrcDst, int nLength, [Npp32f](#) nLevel, [NppCmpOp](#) nRelOp)
32-bit in place floating point complex number signal threshold with constant level.
- [NppStatus nppsThreshold_64f](#) (const [Npp64f](#) *pSrc, [Npp64f](#) *pDst, int nLength, [Npp64f](#) nLevel, [NppCmpOp](#) nRelOp)
64-bit floating point signal threshold with constant level.
- [NppStatus nppsThreshold_64f_I](#) ([Npp64f](#) *pSrcDst, int nLength, [Npp64f](#) nLevel, [NppCmpOp](#) nRelOp)
64-bit in place floating point signal threshold with constant level.
- [NppStatus nppsThreshold_64fc](#) (const [Npp64fc](#) *pSrc, [Npp64fc](#) *pDst, int nLength, [Npp64f](#) nLevel, [NppCmpOp](#) nRelOp)
64-bit floating point complex number signal threshold with constant level.

- **NppStatus nppsThreshold_64fc_I** (**Npp64fc** *pSrcDst, int nLength, **Npp64f** nLevel, **NppCmpOp** nRelOp)
64-bit in place floating point complex number signal threshold with constant level.
- **NppStatus nppsThreshold_LT_16s** (const **Npp16s** *pSrc, **Npp16s** *pDst, int nLength, **Npp16s** nLevel)
16-bit signed short signal NPP_CMP_LESS threshold with constant level.
- **NppStatus nppsThreshold_LT_16s_I** (**Npp16s** *pSrcDst, int nLength, **Npp16s** nLevel)
16-bit in place signed short signal NPP_CMP_LESS threshold with constant level.
- **NppStatus nppsThreshold_LT_16sc** (const **Npp16sc** *pSrc, **Npp16sc** *pDst, int nLength, **Npp16s** nLevel)
16-bit signed short complex number signal NPP_CMP_LESS threshold with constant level.
- **NppStatus nppsThreshold_LT_16sc_I** (**Npp16sc** *pSrcDst, int nLength, **Npp16s** nLevel)
16-bit in place signed short complex number signal NPP_CMP_LESS threshold with constant level.
- **NppStatus nppsThreshold_LT_32f** (const **Npp32f** *pSrc, **Npp32f** *pDst, int nLength, **Npp32f** nLevel)
32-bit floating point signal NPP_CMP_LESS threshold with constant level.
- **NppStatus nppsThreshold_LT_32f_I** (**Npp32f** *pSrcDst, int nLength, **Npp32f** nLevel)
32-bit in place floating point signal NPP_CMP_LESS threshold with constant level.
- **NppStatus nppsThreshold_LT_32fc** (const **Npp32fc** *pSrc, **Npp32fc** *pDst, int nLength, **Npp32f** nLevel)
32-bit floating point complex number signal NPP_CMP_LESS threshold with constant level.
- **NppStatus nppsThreshold_LT_32fc_I** (**Npp32fc** *pSrcDst, int nLength, **Npp32f** nLevel)
32-bit in place floating point complex number signal NPP_CMP_LESS threshold with constant level.
- **NppStatus nppsThreshold_LT_64f** (const **Npp64f** *pSrc, **Npp64f** *pDst, int nLength, **Npp64f** nLevel)
64-bit floating point signal NPP_CMP_LESS threshold with constant level.
- **NppStatus nppsThreshold_LT_64f_I** (**Npp64f** *pSrcDst, int nLength, **Npp64f** nLevel)
64-bit in place floating point signal NPP_CMP_LESS threshold with constant level.
- **NppStatus nppsThreshold_LT_64fc** (const **Npp64fc** *pSrc, **Npp64fc** *pDst, int nLength, **Npp64f** nLevel)
64-bit floating point complex number signal NPP_CMP_LESS threshold with constant level.
- **NppStatus nppsThreshold_LT_64fc_I** (**Npp64fc** *pSrcDst, int nLength, **Npp64f** nLevel)
64-bit in place floating point complex number signal NPP_CMP_LESS threshold with constant level.
- **NppStatus nppsThreshold_GT_16s** (const **Npp16s** *pSrc, **Npp16s** *pDst, int nLength, **Npp16s** nLevel)
16-bit signed short signal NPP_CMP_GREATER threshold with constant level.

- [NppStatus nppsThreshold_GT_16s_I](#) ([Npp16s](#) *pSrcDst, int nLength, [Npp16s](#) nLevel)
16-bit in place signed short signal NPP_CMP_GREATER threshold with constant level.
- [NppStatus nppsThreshold_GT_16sc](#) (const [Npp16sc](#) *pSrc, [Npp16sc](#) *pDst, int nLength, [Npp16s](#) nLevel)
16-bit signed short complex number signal NPP_CMP_GREATER threshold with constant level.
- [NppStatus nppsThreshold_GT_16sc_I](#) ([Npp16sc](#) *pSrcDst, int nLength, [Npp16s](#) nLevel)
16-bit in place signed short complex number signal NPP_CMP_GREATER threshold with constant level.
- [NppStatus nppsThreshold_GT_32f](#) (const [Npp32f](#) *pSrc, [Npp32f](#) *pDst, int nLength, [Npp32f](#) nLevel)
32-bit floating point signal NPP_CMP_GREATER threshold with constant level.
- [NppStatus nppsThreshold_GT_32f_I](#) ([Npp32f](#) *pSrcDst, int nLength, [Npp32f](#) nLevel)
32-bit in place floating point signal NPP_CMP_GREATER threshold with constant level.
- [NppStatus nppsThreshold_GT_32fc](#) (const [Npp32fc](#) *pSrc, [Npp32fc](#) *pDst, int nLength, [Npp32f](#) nLevel)
32-bit floating point complex number signal NPP_CMP_GREATER threshold with constant level.
- [NppStatus nppsThreshold_GT_32fc_I](#) ([Npp32fc](#) *pSrcDst, int nLength, [Npp32f](#) nLevel)
32-bit in place floating point complex number signal NPP_CMP_GREATER threshold with constant level.
- [NppStatus nppsThreshold_GT_64f](#) (const [Npp64f](#) *pSrc, [Npp64f](#) *pDst, int nLength, [Npp64f](#) nLevel)
64-bit floating point signal NPP_CMP_GREATER threshold with constant level.
- [NppStatus nppsThreshold_GT_64f_I](#) ([Npp64f](#) *pSrcDst, int nLength, [Npp64f](#) nLevel)
64-bit in place floating point signal NPP_CMP_GREATER threshold with constant level.
- [NppStatus nppsThreshold_GT_64fc](#) (const [Npp64fc](#) *pSrc, [Npp64fc](#) *pDst, int nLength, [Npp64f](#) nLevel)
64-bit floating point complex number signal NPP_CMP_GREATER threshold with constant level.
- [NppStatus nppsThreshold_GT_64fc_I](#) ([Npp64fc](#) *pSrcDst, int nLength, [Npp64f](#) nLevel)
64-bit in place floating point complex number signal NPP_CMP_GREATER threshold with constant level.
- [NppStatus nppsThreshold_LTVaL_16s](#) (const [Npp16s](#) *pSrc, [Npp16s](#) *pDst, int nLength, [Npp16s](#) nLevel, [Npp16s](#) nValue)
16-bit signed short signal NPP_CMP_LESS threshold with constant level.
- [NppStatus nppsThreshold_LTVaL_16s_I](#) ([Npp16s](#) *pSrcDst, int nLength, [Npp16s](#) nLevel, [Npp16s](#) nValue)
16-bit in place signed short signal NPP_CMP_LESS threshold with constant level.
- [NppStatus nppsThreshold_LTVaL_16sc](#) (const [Npp16sc](#) *pSrc, [Npp16sc](#) *pDst, int nLength, [Npp16s](#) nLevel, [Npp16sc](#) nValue)
16-bit signed short complex number signal NPP_CMP_LESS threshold with constant level.

- **NppStatus nppsThreshold_LTVaL_16sc_I** (**Npp16sc** *pSrcDst, int nLength, **Npp16s** nLevel, **Npp16sc** nValue)
16-bit in place signed short complex number signal NPP_CMP_LESS threshold with constant level.
- **NppStatus nppsThreshold_LTVaL_32f** (const **Npp32f** *pSrc, **Npp32f** *pDst, int nLength, **Npp32f** nLevel, **Npp32f** nValue)
32-bit floating point signal NPP_CMP_LESS threshold with constant level.
- **NppStatus nppsThreshold_LTVaL_32f_I** (**Npp32f** *pSrcDst, int nLength, **Npp32f** nLevel, **Npp32f** nValue)
32-bit in place floating point signal NPP_CMP_LESS threshold with constant level.
- **NppStatus nppsThreshold_LTVaL_32fc** (const **Npp32fc** *pSrc, **Npp32fc** *pDst, int nLength, **Npp32f** nLevel, **Npp32fc** nValue)
32-bit floating point complex number signal NPP_CMP_LESS threshold with constant level.
- **NppStatus nppsThreshold_LTVaL_32fc_I** (**Npp32fc** *pSrcDst, int nLength, **Npp32f** nLevel, **Npp32fc** nValue)
32-bit in place floating point complex number signal NPP_CMP_LESS threshold with constant level.
- **NppStatus nppsThreshold_LTVaL_64f** (const **Npp64f** *pSrc, **Npp64f** *pDst, int nLength, **Npp64f** nLevel, **Npp64f** nValue)
64-bit floating point signal NPP_CMP_LESS threshold with constant level.
- **NppStatus nppsThreshold_LTVaL_64f_I** (**Npp64f** *pSrcDst, int nLength, **Npp64f** nLevel, **Npp64f** nValue)
64-bit in place floating point signal NPP_CMP_LESS threshold with constant level.
- **NppStatus nppsThreshold_LTVaL_64fc** (const **Npp64fc** *pSrc, **Npp64fc** *pDst, int nLength, **Npp64f** nLevel, **Npp64fc** nValue)
64-bit floating point complex number signal NPP_CMP_LESS threshold with constant level.
- **NppStatus nppsThreshold_LTVaL_64fc_I** (**Npp64fc** *pSrcDst, int nLength, **Npp64f** nLevel, **Npp64fc** nValue)
64-bit in place floating point complex number signal NPP_CMP_LESS threshold with constant level.
- **NppStatus nppsThreshold_GTVaL_16s** (const **Npp16s** *pSrc, **Npp16s** *pDst, int nLength, **Npp16s** nLevel, **Npp16s** nValue)
16-bit signed short signal NPP_CMP_GREATER threshold with constant level.
- **NppStatus nppsThreshold_GTVaL_16s_I** (**Npp16s** *pSrcDst, int nLength, **Npp16s** nLevel, **Npp16s** nValue)
16-bit in place signed short signal NPP_CMP_GREATER threshold with constant level.
- **NppStatus nppsThreshold_GTVaL_16sc** (const **Npp16sc** *pSrc, **Npp16sc** *pDst, int nLength, **Npp16s** nLevel, **Npp16sc** nValue)
16-bit signed short complex number signal NPP_CMP_GREATER threshold with constant level.
- **NppStatus nppsThreshold_GTVaL_16sc_I** (**Npp16sc** *pSrcDst, int nLength, **Npp16s** nLevel, **Npp16sc** nValue)
16-bit in place signed short complex number signal NPP_CMP_GREATER threshold with constant level.

- **NppStatus nppsThreshold_GTVVal_32f** (const **Npp32f** *pSrc, **Npp32f** *pDst, int nLength, **Npp32f** nLevel, **Npp32f** nValue)
32-bit floating point signal NPP_CMP_GREATER threshold with constant level.
- **NppStatus nppsThreshold_GTVVal_32f_I** (**Npp32f** *pSrcDst, int nLength, **Npp32f** nLevel, **Npp32f** nValue)
32-bit in place floating point signal NPP_CMP_GREATER threshold with constant level.
- **NppStatus nppsThreshold_GTVVal_32fc** (const **Npp32fc** *pSrc, **Npp32fc** *pDst, int nLength, **Npp32f** nLevel, **Npp32fc** nValue)
32-bit floating point complex number signal NPP_CMP_GREATER threshold with constant level.
- **NppStatus nppsThreshold_GTVVal_32fc_I** (**Npp32fc** *pSrcDst, int nLength, **Npp32f** nLevel, **Npp32fc** nValue)
32-bit in place floating point complex number signal NPP_CMP_GREATER threshold with constant level.
- **NppStatus nppsThreshold_GTVVal_64f** (const **Npp64f** *pSrc, **Npp64f** *pDst, int nLength, **Npp64f** nLevel, **Npp64f** nValue)
64-bit floating point signal NPP_CMP_GREATER threshold with constant level.
- **NppStatus nppsThreshold_GTVVal_64f_I** (**Npp64f** *pSrcDst, int nLength, **Npp64f** nLevel, **Npp64f** nValue)
64-bit in place floating point signal NPP_CMP_GREATER threshold with constant level.
- **NppStatus nppsThreshold_GTVVal_64fc** (const **Npp64fc** *pSrc, **Npp64fc** *pDst, int nLength, **Npp64f** nLevel, **Npp64fc** nValue)
64-bit floating point complex number signal NPP_CMP_GREATER threshold with constant level.
- **NppStatus nppsThreshold_GTVVal_64fc_I** (**Npp64fc** *pSrcDst, int nLength, **Npp64f** nLevel, **Npp64fc** nValue)
64-bit in place floating point complex number signal NPP_CMP_GREATER threshold with constant level.

7.171.1 Function Documentation

7.171.1.1 **NppStatus nppsThreshold_16s** (const **Npp16s** * pSrc, **Npp16s** * pDst, int nLength, **Npp16s** nLevel, **NppCmpOp** nRelOp)

16-bit signed short signal threshold with constant level.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value to be used to limit each signal sample

nRelOp NppCmpOp type of thresholding operation (NPP_CMP_LESS or NPP_CMP_GREATER only).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.2 NppStatus nppsThreshold_16s_I (Npp16s * pSrcDst, int nLength, Npp16s nLevel, NppCmpOp nRelOp)

16-bit in place signed short signal threshold with constant level.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nLength [Signal Length](#).

nLevel Constant threshold value to be used to limit each signal sample

nRelOp NppCmpOp type of thresholding operation (NPP_CMP_LESS or NPP_CMP_GREATER only).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.3 NppStatus nppsThreshold_16sc (const Npp16sc * pSrc, Npp16sc * pDst, int nLength, Npp16s nLevel, NppCmpOp nRelOp)

16-bit signed short complex number signal threshold with constant level.

Parameters:

pSrc [Source Signal Pointer](#).

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

nRelOp NppCmpOp type of thresholding operation (NPP_CMP_LESS or NPP_CMP_GREATER only).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.4 NppStatus nppsThreshold_16sc_I (Npp16sc * pSrcDst, int nLength, Npp16s nLevel, NppCmpOp nRelOp)

16-bit in place signed short complex number signal threshold with constant level.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nLength [Signal Length](#).

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

nRelOp NppCmpOp type of thresholding operation (NPP_CMP_LESS or NPP_CMP_GREATER only).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.5 NppStatus nppsThreshold_32f (const Npp32f * pSrc, Npp32f * pDst, int nLength, Npp32f nLevel, NppCmpOp nRelOp)

32-bit floating point signal threshold with constant level.

Parameters:

pSrc [Source Signal Pointer](#).

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nLevel Constant threshold value to be used to limit each signal sample

nRelOp NppCmpOp type of thresholding operation (NPP_CMP_LESS or NPP_CMP_GREATER only).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.6 NppStatus nppsThreshold_32f_I (Npp32f * pSrcDst, int nLength, Npp32f nLevel, NppCmpOp nRelOp)

32-bit in place floating point signal threshold with constant level.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nLength [Signal Length](#).

nLevel Constant threshold value to be used to limit each signal sample

nRelOp NppCmpOp type of thresholding operation (NPP_CMP_LESS or NPP_CMP_GREATER only).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.7 NppStatus nppsThreshold_32fc (const Npp32fc * pSrc, Npp32fc * pDst, int nLength, Npp32f nLevel, NppCmpOp nRelOp)

32-bit floating point complex number signal threshold with constant level.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

nRelOp NppCmpOp type of thresholding operation (NPP_CMP_LESS or NPP_CMP_GREATER only).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.8 NppStatus nppsThreshold_32fc_I (Npp32fc * pSrcDst, int nLength, Npp32f nLevel, NppCmpOp nRelOp)

32-bit in place floating point complex number signal threshold with constant level.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

nRelOp NppCmpOp type of thresholding operation (NPP_CMP_LESS or NPP_CMP_GREATER only).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.9 NppStatus nppsThreshold_64f (const Npp64f * pSrc, Npp64f * pDst, int nLength, Npp64f nLevel, NppCmpOp nRelOp)

64-bit floating point signal threshold with constant level.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value to be used to limit each signal sample

nRelOp NppCmpOp type of thresholding operation (NPP_CMP_LESS or NPP_CMP_GREATER only).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.10 NppStatus nppsThreshold_64f_I (Npp64f * pSrcDst, int nLength, Npp64f nLevel, NppCmpOp nRelOp)

64-bit in place floating point signal threshold with constant level.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value to be used to limit each signal sample

nRelOp NppCmpOp type of thresholding operation (NPP_CMP_LESS or NPP_CMP_GREATER only).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.11 NppStatus nppsThreshold_64fc (const Npp64fc * pSrc, Npp64fc * pDst, int nLength, Npp64f nLevel, NppCmpOp nRelOp)

64-bit floating point complex number signal threshold with constant level.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

nRelOp NppCmpOp type of thresholding operation (NPP_CMP_LESS or NPP_CMP_GREATER only).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.12 NppStatus nppsThreshold_64fc_I (Npp64fc * pSrcDst, int nLength, Npp64f nLevel, NppCmpOp nRelOp)

64-bit in place floating point complex number signal threshold with constant level.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

nRelOp NppCmpOp type of thresholding operation (NPP_CMP_LESS or NPP_CMP_GREATER only).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.13 NppStatus nppsThreshold_GT_16s (const Npp16s * pSrc, Npp16s * pDst, int nLength, Npp16s nLevel)

16-bit signed short signal NPP_CMP_GREATER threshold with constant level.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value to be used to limit each signal sample

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.171.1.14 NppStatus nppsThreshold_GT_16s_I (Npp16s * pSrcDst, int nLength, Npp16s nLevel)

16-bit in place signed short signal NPP_CMP_GREATER threshold with constant level.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value to be used to limit each signal sample

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.171.1.15 NppStatus nppsThreshold_GT_16sc (const Npp16sc * pSrc, Npp16sc * pDst, int nLength, Npp16s nLevel)

16-bit signed short complex number signal NPP_CMP_GREATER threshold with constant level.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.171.1.16 NppStatus nppsThreshold_GT_16sc_I (Npp16sc * pSrcDst, int nLength, Npp16s nLevel)

16-bit in place signed short complex number signal NPP_CMP_GREATER threshold with constant level.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.171.1.17 NppStatus nppsThreshold_GT_32f (const Npp32f * pSrc, Npp32f * pDst, int nLength, Npp32f nLevel)

32-bit floating point signal NPP_CMP_GREATER threshold with constant level.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value to be used to limit each signal sample

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.171.1.18 NppStatus nppsThreshold_GT_32f_I (Npp32f * pSrcDst, int nLength, Npp32f nLevel)

32-bit in place floating point signal NPP_CMP_GREATER threshold with constant level.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value to be used to limit each signal sample

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.171.1.19 NppStatus nppsThreshold_GT_32fc (const Npp32fc * pSrc, Npp32fc * pDst, int nLength, Npp32f nLevel)

32-bit floating point complex number signal NPP_CMP_GREATER threshold with constant level.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.171.1.20 NppStatus nppsThreshold_GT_32fc_I (Npp32fc * pSrcDst, int nLength, Npp32f nLevel)

32-bit in place floating point complex number signal NPP_CMP_GREATER threshold with constant level.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.171.1.21 NppStatus nppsThreshold_GT_64f (const Npp64f * pSrc, Npp64f * pDst, int nLength, Npp64f nLevel)

64-bit floating point signal NPP_CMP_GREATER threshold with constant level.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value to be used to limit each signal sample

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.171.1.22 NppStatus nppsThreshold_GT_64f_I (Npp64f * pSrcDst, int nLength, Npp64f nLevel)

64-bit in place floating point signal NPP_CMP_GREATER threshold with constant level.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value to be used to limit each signal sample

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.171.1.23 NppStatus nppsThreshold_GT_64fc (const Npp64fc * pSrc, Npp64fc * pDst, int nLength, Npp64f nLevel)

64-bit floating point complex number signal NPP_CMP_GREATER threshold with constant level.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.171.1.24 NppStatus nppsThreshold_GT_64fc_I (Npp64fc * pSrcDst, int nLength, Npp64f nLevel)

64-bit in place floating point complex number signal NPP_CMP_GREATER threshold with constant level.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.171.1.25 NppStatus nppsThreshold_GTVVal_16s (const Npp16s * pSrc, Npp16s * pDst, int nLength, Npp16s nLevel, Npp16s nValue)

16-bit signed short signal NPP_CMP_GREATER threshold with constant level.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value to be used to limit each signal sample

nValue Constant value to replace source value when threshold test is true.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.26 NppStatus nppsThreshold_GTVVal_16s_I (Npp16s * pSrcDst, int nLength, Npp16s nLevel, Npp16s nValue)

16-bit in place signed short signal NPP_CMP_GREATER threshold with constant level.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value to be used to limit each signal sample

nValue Constant value to replace source value when threshold test is true.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.27 NppStatus nppsThreshold_GTVVal_16sc (const Npp16sc * pSrc, Npp16sc * pDst, int nLength, Npp16s nLevel, Npp16sc nValue)

16-bit signed short complex number signal NPP_CMP_GREATER threshold with constant level.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

nValue Constant value to replace source value when threshold test is true.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.28 NppStatus nppsThreshold_GTVVal_16sc_I (Npp16sc * pSrcDst, int nLength, Npp16s nLevel, Npp16sc nValue)

16-bit in place signed short complex number signal NPP_CMP_GREATER threshold with constant level.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

nValue Constant value to replace source value when threshold test is true.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.29 NppStatus nppsThreshold_GTVVal_32f (const Npp32f * pSrc, Npp32f * pDst, int nLength, Npp32f nLevel, Npp32f nValue)

32-bit floating point signal NPP_CMP_GREATER threshold with constant level.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value to be used to limit each signal sample

nValue Constant value to replace source value when threshold test is true.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.30 NppStatus nppsThreshold_GTVVal_32f_I (Npp32f * pSrcDst, int nLength, Npp32f nLevel, Npp32f nValue)

32-bit in place floating point signal NPP_CMP_GREATER threshold with constant level.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value to be used to limit each signal sample

nValue Constant value to replace source value when threshold test is true.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.31 NppStatus nppsThreshold_GTVal_32fc (const Npp32fc * pSrc, Npp32fc * pDst, int nLength, Npp32f nLevel, Npp32fc nValue)

32-bit floating point complex number signal NPP_CMP_GREATER threshold with constant level.

Parameters:

pSrc [Source Signal Pointer](#).

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

nValue Constant value to replace source value when threshold test is true.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.32 NppStatus nppsThreshold_GTVal_32fc_I (Npp32fc * pSrcDst, int nLength, Npp32f nLevel, Npp32fc nValue)

32-bit in place floating point complex number signal NPP_CMP_GREATER threshold with constant level.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nLength [Signal Length](#).

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

nValue Constant value to replace source value when threshold test is true.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.33 NppStatus nppsThreshold_GTVal_64f (const Npp64f * pSrc, Npp64f * pDst, int nLength, Npp64f nLevel, Npp64f nValue)

64-bit floating point signal NPP_CMP_GREATER threshold with constant level.

Parameters:

pSrc [Source Signal Pointer](#).

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nLevel Constant threshold value to be used to limit each signal sample

nValue Constant value to replace source value when threshold test is true.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.34 NppStatus nppsThreshold_GTVal_64f_I (Npp64f * pSrcDst, int nLength, Npp64f nLevel, Npp64f nValue)

64-bit in place floating point signal NPP_CMP_GREATER threshold with constant level.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value to be used to limit each signal sample

nValue Constant value to replace source value when threshold test is true.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.35 NppStatus nppsThreshold_GTVal_64fc (const Npp64fc * pSrc, Npp64fc * pDst, int nLength, Npp64fc nLevel, Npp64fc nValue)

64-bit floating point complex number signal NPP_CMP_GREATER threshold with constant level.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

nValue Constant value to replace source value when threshold test is true.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.36 NppStatus nppsThreshold_GTVal_64fc_I (Npp64fc * pSrcDst, int nLength, Npp64fc nLevel, Npp64fc nValue)

64-bit in place floating point complex number signal NPP_CMP_GREATER threshold with constant level.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

nValue Constant value to replace source value when threshold test is true.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.37 NppStatus nppsThreshold_LT_16s (const Npp16s * pSrc, Npp16s * pDst, int nLength, Npp16s nLevel)

16-bit signed short signal NPP_CMP_LESS threshold with constant level.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value to be used to limit each signal sample

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.171.1.38 NppStatus nppsThreshold_LT_16s_I (Npp16s * pSrcDst, int nLength, Npp16s nLevel)

16-bit in place signed short signal NPP_CMP_LESS threshold with constant level.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value to be used to limit each signal sample

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.171.1.39 NppStatus nppsThreshold_LT_16sc (const Npp16sc * pSrc, Npp16sc * pDst, int nLength, Npp16s nLevel)

16-bit signed short complex number signal NPP_CMP_LESS threshold with constant level.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.171.1.40 NppStatus nppsThreshold_LT_16sc_I (Npp16sc * pSrcDst, int nLength, Npp16s nLevel)

16-bit in place signed short complex number signal NPP_CMP_LESS threshold with constant level.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.41 NppStatus nppsThreshold_LT_32f (const Npp32f * pSrc, Npp32f * pDst, int nLength, Npp32f nLevel)

32-bit floating point signal NPP_CMP_LESS threshold with constant level.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value to be used to limit each signal sample

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.42 NppStatus nppsThreshold_LT_32f_I (Npp32f * pSrcDst, int nLength, Npp32f nLevel)

32-bit in place floating point signal NPP_CMP_LESS threshold with constant level.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value to be used to limit each signal sample

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.43 NppStatus nppsThreshold_LT_32fc (const Npp32fc * pSrc, Npp32fc * pDst, int nLength, Npp32f nLevel)

32-bit floating point complex number signal NPP_CMP_LESS threshold with constant level.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.171.1.44 NppStatus nppsThreshold_LT_32fc_I (Npp32fc * pSrcDst, int nLength, Npp32f nLevel)

32-bit in place floating point complex number signal NPP_CMP_LESS threshold with constant level.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.171.1.45 NppStatus nppsThreshold_LT_64f (const Npp64f * pSrc, Npp64f * pDst, int nLength, Npp64f nLevel)

64-bit floating point signal NPP_CMP_LESS threshold with constant level.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value to be used to limit each signal sample

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.171.1.46 NppStatus nppsThreshold_LT_64f_I (Npp64f * pSrcDst, int nLength, Npp64f nLevel)

64-bit in place floating point signal NPP_CMP_LESS threshold with constant level.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value to be used to limit each signal sample

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.171.1.47 NppStatus nppsThreshold_LT_64fc (const Npp64fc * pSrc, Npp64fc * pDst, int nLength, Npp64f nLevel)

64-bit floating point complex number signal NPP_CMP_LESS threshold with constant level.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.171.1.48 NppStatus nppsThreshold_LT_64fc_I (Npp64fc * pSrcDst, int nLength, Npp64f nLevel)

64-bit in place floating point complex number signal NPP_CMP_LESS threshold with constant level.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.171.1.49 NppStatus nppsThreshold_LTVVal_16s (const Npp16s * pSrc, Npp16s * pDst, int nLength, Npp16s nLevel, Npp16s nValue)

16-bit signed short signal NPP_CMP_LESS threshold with constant level.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value to be used to limit each signal sample

nValue Constant value to replace source value when threshold test is true.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.50 NppStatus nppsThreshold_LTVVal_16s_I (Npp16s * pSrcDst, int nLength, Npp16s nLevel, Npp16s nValue)

16-bit in place signed short signal NPP_CMP_LESS threshold with constant level.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value to be used to limit each signal sample

nValue Constant value to replace source value when threshold test is true.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.51 NppStatus nppsThreshold_LTVVal_16sc (const Npp16sc * pSrc, Npp16sc * pDst, int nLength, Npp16s nLevel, Npp16sc nValue)

16-bit signed short complex number signal NPP_CMP_LESS threshold with constant level.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

nValue Constant value to replace source value when threshold test is true.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.52 NppStatus nppsThreshold_LTVVal_16sc_I (Npp16sc * pSrcDst, int nLength, Npp16s nLevel, Npp16sc nValue)

16-bit in place signed short complex number signal NPP_CMP_LESS threshold with constant level.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

nValue Constant value to replace source value when threshold test is true.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.53 NppStatus nppsThreshold_LTVVal_32f (const Npp32f * pSrc, Npp32f * pDst, int nLength, Npp32f nLevel, Npp32f nValue)

32-bit floating point signal NPP_CMP_LESS threshold with constant level.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value to be used to limit each signal sample

nValue Constant value to replace source value when threshold test is true.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.54 NppStatus nppsThreshold_LTVVal_32f_I (Npp32f * pSrcDst, int nLength, Npp32f nLevel, Npp32f nValue)

32-bit in place floating point signal NPP_CMP_LESS threshold with constant level.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value to be used to limit each signal sample

nValue Constant value to replace source value when threshold test is true.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.55 NppStatus nppsThreshold_LTVVal_32fc (const Npp32fc * pSrc, Npp32fc * pDst, int nLength, Npp32f nLevel, Npp32fc nValue)

32-bit floating point complex number signal NPP_CMP_LESS threshold with constant level.

Parameters:

pSrc [Source Signal Pointer](#).

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

nValue Constant value to replace source value when threshold test is true.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.56 NppStatus nppsThreshold_LTVVal_32fc_I (Npp32fc * pSrcDst, int nLength, Npp32f nLevel, Npp32fc nValue)

32-bit in place floating point complex number signal NPP_CMP_LESS threshold with constant level.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nLength [Signal Length](#).

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

nValue Constant value to replace source value when threshold test is true.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.57 NppStatus nppsThreshold_LTVVal_64f (const Npp64f * pSrc, Npp64f * pDst, int nLength, Npp64f nLevel, Npp64f nValue)

64-bit floating point signal NPP_CMP_LESS threshold with constant level.

Parameters:

pSrc [Source Signal Pointer](#).

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nLevel Constant threshold value to be used to limit each signal sample

nValue Constant value to replace source value when threshold test is true.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.58 NppStatus nppsThreshold_LTVVal_64f_I (Npp64f * pSrcDst, int nLength, Npp64f nLevel, Npp64f nValue)

64-bit in place floating point signal NPP_CMP_LESS threshold with constant level.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value to be used to limit each signal sample

nValue Constant value to replace source value when threshold test is true.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.59 NppStatus nppsThreshold_LTVVal_64fc (const Npp64fc * pSrc, Npp64fc * pDst, int nLength, Npp64f nLevel, Npp64fc nValue)

64-bit floating point complex number signal NPP_CMP_LESS threshold with constant level.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

nValue Constant value to replace source value when threshold test is true.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.171.1.60 NppStatus nppsThreshold_LTVVal_64fc_I (Npp64fc * pSrcDst, int nLength, Npp64f nLevel, Npp64fc nValue)

64-bit in place floating point complex number signal NPP_CMP_LESS threshold with constant level.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nLevel Constant threshold value (real part only and must be greater than 0) to be used to limit each signal sample

nValue Constant value to replace source value when threshold test is true.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.172 Filtering Functions

Functions that provide functionality of generating output signal based on the input signal like signal integral, etc.

Modules

- [Integral](#)

Compute the indefinite interal of a given signal.

7.172.1 Detailed Description

Functions that provide functionality of generating output signal based on the input signal like signal integral, etc.

7.173 Integral

Compute the indefinite integral of a given signal.

Functions

- `NppStatus nppsIntegralGetBufferSize_32s` (int *nLength*, int **hpBufferSize*)
- `NppStatus nppsIntegral_32s` (const `Npp32s` **pSrc*, `Npp32s` **pDst*, int *nLength*, `Npp8u` **pDeviceBuffer*)

7.173.1 Detailed Description

Compute the indefinite integral of a given signal.

The *i*-th element is computed to be

$$s'_i = \sum_0^i s_j$$

7.173.2 Function Documentation

7.173.2.1 `NppStatus nppsIntegral_32s` (const `Npp32s` **pSrc*, `Npp32s` **pDst*, int *nLength*, `Npp8u` **pDeviceBuffer*)

7.173.2.2 `NppStatus nppsIntegralGetBufferSize_32s` (int *nLength*, int **hpBufferSize*)

7.174 Initialization

Modules

- [Set](#)
- [Zero](#)
- [Copy](#)

7.175 Set

Set

Set methods for 1D vectors of various types.

The copy methods operate on vector data given as a pointer to the underlying data-type (e.g. 8-bit vectors would be passed as pointers to Npp8u type) and length of the vectors, i.e. the number of items.

- **NppStatus nppsSet_8u** (Npp8u nValue, Npp8u *pDst, int nLength)
8-bit unsigned char, vector set method.
- **NppStatus nppsSet_16s** (Npp16s nValue, Npp16s *pDst, int nLength)
16-bit integer, vector set method.
- **NppStatus nppsSet_16sc** (Npp16sc nValue, Npp16sc *pDst, int nLength)
16-bit integer complex, vector set method.
- **NppStatus nppsSet_32s** (Npp32s nValue, Npp32s *pDst, int nLength)
32-bit integer, vector set method.
- **NppStatus nppsSet_32sc** (Npp32sc nValue, Npp32sc *pDst, int nLength)
32-bit integer complex, vector set method.
- **NppStatus nppsSet_32f** (Npp32f nValue, Npp32f *pDst, int nLength)
32-bit float, vector set method.
- **NppStatus nppsSet_32fc** (Npp32fc nValue, Npp32fc *pDst, int nLength)
32-bit float complex, vector set method.
- **NppStatus nppsSet_64s** (Npp64s nValue, Npp64s *pDst, int nLength)
64-bit long long integer, vector set method.
- **NppStatus nppsSet_64sc** (Npp64sc nValue, Npp64sc *pDst, int nLength)
64-bit long long integer complex, vector set method.
- **NppStatus nppsSet_64f** (Npp64f nValue, Npp64f *pDst, int nLength)
64-bit double, vector set method.
- **NppStatus nppsSet_64fc** (Npp64fc nValue, Npp64fc *pDst, int nLength)
64-bit double complex, vector set method.

7.175.1 Function Documentation

7.175.1.1 NppStatus nppsSet_16s (Npp16s nValue, Npp16s *pDst, int nLength)

16-bit integer, vector set method.

Parameters:

nValue Value used to initialize the vector pDst.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.175.1.2 NppStatus nppsSet_16sc (Npp16sc nValue, Npp16sc * pDst, int nLength)

16-bit integer complex, vector set method.

Parameters:

nValue Value used to initialize the vector pDst.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.175.1.3 NppStatus nppsSet_32f (Npp32f nValue, Npp32f * pDst, int nLength)

32-bit float, vector set method.

Parameters:

nValue Value used to initialize the vector pDst.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.175.1.4 NppStatus nppsSet_32fc (Npp32fc nValue, Npp32fc * pDst, int nLength)

32-bit float complex, vector set method.

Parameters:

nValue Value used to initialize the vector pDst.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.175.1.5 NppStatus nppsSet_32s (Npp32s *nValue*, Npp32s * *pDst*, int *nLength*)

32-bit integer, vector set method.

Parameters:

nValue Value used to initialize the vector pDst.
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.175.1.6 NppStatus nppsSet_32sc (Npp32sc *nValue*, Npp32sc * *pDst*, int *nLength*)

32-bit integer complex, vector set method.

Parameters:

nValue Value used to initialize the vector pDst.
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.175.1.7 NppStatus nppsSet_64f (Npp64f *nValue*, Npp64f * *pDst*, int *nLength*)

64-bit double, vector set method.

Parameters:

nValue Value used to initialize the vector pDst.
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.175.1.8 NppStatus nppsSet_64fc (Npp64fc *nValue*, Npp64fc * *pDst*, int *nLength*)

64-bit double complex, vector set method.

Parameters:

nValue Value used to initialize the vector pDst.
pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.175.1.9 NppStatus nppsSet_64s (Npp64s *nValue*, Npp64s * *pDst*, int *nLength*)

64-bit long long integer, vector set method.

Parameters:

nValue Value used to initialize the vector pDst.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.175.1.10 NppStatus nppsSet_64sc (Npp64sc *nValue*, Npp64sc * *pDst*, int *nLength*)

64-bit long long integer complex, vector set method.

Parameters:

nValue Value used to initialize the vector pDst.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.175.1.11 NppStatus nppsSet_8u (Npp8u *nValue*, Npp8u * *pDst*, int *nLength*)

8-bit unsigned char, vector set method.

Parameters:

nValue Value used to initialize the vector pDst.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.176 Zero

Zero

Set signals to zero.

- [NppStatus nppsZero_8u](#) ([Npp8u](#) *pDst, int nLength)
8-bit unsigned char, vector zero method.
- [NppStatus nppsZero_16s](#) ([Npp16s](#) *pDst, int nLength)
16-bit integer, vector zero method.
- [NppStatus nppsZero_16sc](#) ([Npp16sc](#) *pDst, int nLength)
16-bit integer complex, vector zero method.
- [NppStatus nppsZero_32s](#) ([Npp32s](#) *pDst, int nLength)
32-bit integer, vector zero method.
- [NppStatus nppsZero_32sc](#) ([Npp32sc](#) *pDst, int nLength)
32-bit integer complex, vector zero method.
- [NppStatus nppsZero_32f](#) ([Npp32f](#) *pDst, int nLength)
32-bit float, vector zero method.
- [NppStatus nppsZero_32fc](#) ([Npp32fc](#) *pDst, int nLength)
32-bit float complex, vector zero method.
- [NppStatus nppsZero_64s](#) ([Npp64s](#) *pDst, int nLength)
64-bit long long integer, vector zero method.
- [NppStatus nppsZero_64sc](#) ([Npp64sc](#) *pDst, int nLength)
64-bit long long integer complex, vector zero method.
- [NppStatus nppsZero_64f](#) ([Npp64f](#) *pDst, int nLength)
64-bit double, vector zero method.
- [NppStatus nppsZero_64fc](#) ([Npp64fc](#) *pDst, int nLength)
64-bit double complex, vector zero method.

7.176.1 Function Documentation

7.176.1.1 [NppStatus nppsZero_16s](#) ([Npp16s](#) *pDst, int nLength)

16-bit integer, vector zero method.

Parameters:

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.176.1.2 NppStatus nppsZero_16sc (Npp16sc * *pDst*, int *nLength*)

16-bit integer complex, vector zero method.

Parameters:

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.176.1.3 NppStatus nppsZero_32f (Npp32f * *pDst*, int *nLength*)

32-bit float, vector zero method.

Parameters:

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.176.1.4 NppStatus nppsZero_32fc (Npp32fc * *pDst*, int *nLength*)

32-bit float complex, vector zero method.

Parameters:

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.176.1.5 NppStatus nppsZero_32s (Npp32s * *pDst*, int *nLength*)

32-bit integer, vector zero method.

Parameters:

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.176.1.6 NppStatus nppsZero_32sc (Npp32sc * *pDst*, int *nLength*)

32-bit integer complex, vector zero method.

Parameters:

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.176.1.7 NppStatus nppsZero_64f (Npp64f * *pDst*, int *nLength*)

64-bit double, vector zero method.

Parameters:

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.176.1.8 NppStatus nppsZero_64fc (Npp64fc * *pDst*, int *nLength*)

64-bit double complex, vector zero method.

Parameters:

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.176.1.9 NppStatus nppsZero_64s (Npp64s * *pDst*, int *nLength*)

64-bit long long integer, vector zero method.

Parameters:

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.176.1.10 NppStatus nppsZero_64sc (Npp64sc * *pDst*, int *nLength*)

64-bit long long integer complex, vector zero method.

Parameters:

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.176.1.11 NppStatus nppsZero_8u (Npp8u * *pDst*, int *nLength*)

8-bit unsigned char, vector zero method.

Parameters:

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.177 Copy

Copy

Copy methods for various type signals.

Copy methods operate on signal data given as a pointer to the underlying data-type (e.g. 8-bit vectors would be passed as pointers to `Npp8u` type) and length of the vectors, i.e. the number of items.

- `NppStatus nppsCopy_8u` (const `Npp8u` *pSrc, `Npp8u` *pDst, int nLength)
8-bit unsigned char, vector copy method
- `NppStatus nppsCopy_16s` (const `Npp16s` *pSrc, `Npp16s` *pDst, int nLength)
16-bit signed short, vector copy method.
- `NppStatus nppsCopy_32s` (const `Npp32s` *pSrc, `Npp32s` *pDst, int nLength)
32-bit signed integer, vector copy method.
- `NppStatus nppsCopy_32f` (const `Npp32f` *pSrc, `Npp32f` *pDst, int nLength)
32-bit float, vector copy method.
- `NppStatus nppsCopy_64s` (const `Npp64s` *pSrc, `Npp64s` *pDst, int nLength)
64-bit signed integer, vector copy method.
- `NppStatus nppsCopy_16sc` (const `Npp16sc` *pSrc, `Npp16sc` *pDst, int nLength)
16-bit complex short, vector copy method.
- `NppStatus nppsCopy_32sc` (const `Npp32sc` *pSrc, `Npp32sc` *pDst, int nLength)
32-bit complex signed integer, vector copy method.
- `NppStatus nppsCopy_32fc` (const `Npp32fc` *pSrc, `Npp32fc` *pDst, int nLength)
32-bit complex float, vector copy method.
- `NppStatus nppsCopy_64sc` (const `Npp64sc` *pSrc, `Npp64sc` *pDst, int nLength)
64-bit complex signed integer, vector copy method.
- `NppStatus nppsCopy_64fc` (const `Npp64fc` *pSrc, `Npp64fc` *pDst, int nLength)
64-bit complex double, vector copy method.

7.177.1 Function Documentation

7.177.1.1 `NppStatus nppsCopy_16s` (const `Npp16s` *pSrc, `Npp16s` *pDst, int nLength)

16-bit signed short, vector copy method.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.177.1.2 NppStatus nppsCopy_16sc (const Npp16sc * pSrc, Npp16sc * pDst, int nLength)

16-bit complex short, vector copy method.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.177.1.3 NppStatus nppsCopy_32f (const Npp32f * pSrc, Npp32f * pDst, int nLength)

32-bit float, vector copy method.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.177.1.4 NppStatus nppsCopy_32fc (const Npp32fc * pSrc, Npp32fc * pDst, int nLength)

32-bit complex float, vector copy method.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.177.1.5 NppStatus nppsCopy_32s (const Npp32s * pSrc, Npp32s * pDst, int nLength)

32-bit signed integer, vector copy method.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.177.1.6 NppStatus nppsCopy_32sc (const Npp32sc * pSrc, Npp32sc * pDst, int nLength)

32-bit complex signed integer, vector copy method.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.177.1.7 NppStatus nppsCopy_64fc (const Npp64fc * pSrc, Npp64fc * pDst, int nLength)

64-bit complex double, vector copy method.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.177.1.8 NppStatus nppsCopy_64s (const Npp64s * pSrc, Npp64s * pDst, int nLength)

64-bit signed integer, vector copy method.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.177.1.9 NppStatus nppsCopy_64sc (const Npp64sc * pSrc, Npp64sc * pDst, int nLength)

64-bit complex signed integer, vector copy method.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.177.1.10 NppStatus nppsCopy_8u (const Npp8u * pSrc, Npp8u * pDst, int nLength)

8-bit unsigned char, vector copy method

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.178 Statistical Functions

Functions that provide global signal statistics like: sum, mean, standard deviation, min, max, etc.

Modules

- [MinEvery And MaxEvery Functions](#)

Performs the min or max operation on the samples of a signal.

- [Sum](#)

signal_min_every_or_max_every

- [Maximum](#)
- [Minimum](#)
- [Mean](#)
- [Standard Deviation](#)
- [Mean And Standard Deviation](#)
- [Minimum_Maximum](#)
- [Infinity Norm](#)
- [L1 Norm](#)
- [L2 Norm](#)
- [Infinity Norm Diff](#)
- [L1 Norm Diff](#)
- [L2 Norm Diff](#)
- [Dot Product](#)
- [Count In Range](#)
- [Count Zero Crossings](#)

7.178.1 Detailed Description

Functions that provide global signal statistics like: sum, mean, standard deviation, min, max, etc.

7.179 MinEvery And MaxEvery Functions

Performs the min or max operation on the samples of a signal.

Functions

- [NppStatus nppsMinEvery_8u_I](#) (const [Npp8u](#) *pSrc, [Npp8u](#) *pSrcDst, int nLength)
8-bit in place min value for each pair of elements.
- [NppStatus nppsMinEvery_16u_I](#) (const [Npp16u](#) *pSrc, [Npp16u](#) *pSrcDst, int nLength)
16-bit unsigned short integer in place min value for each pair of elements.
- [NppStatus nppsMinEvery_16s_I](#) (const [Npp16s](#) *pSrc, [Npp16s](#) *pSrcDst, int nLength)
16-bit signed short integer in place min value for each pair of elements.
- [NppStatus nppsMinEvery_32s_I](#) (const [Npp32s](#) *pSrc, [Npp32s](#) *pSrcDst, int nLength)
32-bit signed integer in place min value for each pair of elements.
- [NppStatus nppsMinEvery_32f_I](#) (const [Npp32f](#) *pSrc, [Npp32f](#) *pSrcDst, int nLength)
32-bit floating point in place min value for each pair of elements.
- [NppStatus nppsMinEvery_64f_I](#) (const [Npp64f](#) *pSrc, [Npp64f](#) *pSrcDst, int nLength)
64-bit floating point in place min value for each pair of elements.
- [NppStatus nppsMaxEvery_8u_I](#) (const [Npp8u](#) *pSrc, [Npp8u](#) *pSrcDst, int nLength)
8-bit in place max value for each pair of elements.
- [NppStatus nppsMaxEvery_16u_I](#) (const [Npp16u](#) *pSrc, [Npp16u](#) *pSrcDst, int nLength)
16-bit unsigned short integer in place max value for each pair of elements.
- [NppStatus nppsMaxEvery_16s_I](#) (const [Npp16s](#) *pSrc, [Npp16s](#) *pSrcDst, int nLength)
16-bit signed short integer in place max value for each pair of elements.
- [NppStatus nppsMaxEvery_32s_I](#) (const [Npp32s](#) *pSrc, [Npp32s](#) *pSrcDst, int nLength)
32-bit signed integer in place max value for each pair of elements.
- [NppStatus nppsMaxEvery_32f_I](#) (const [Npp32f](#) *pSrc, [Npp32f](#) *pSrcDst, int nLength)
32-bit floating point in place max value for each pair of elements.

7.179.1 Detailed Description

Performs the min or max operation on the samples of a signal.

7.179.2 Function Documentation

7.179.2.1 [NppStatus nppsMaxEvery_16s_I](#) (const [Npp16s](#) *pSrc, [Npp16s](#) *pSrcDst, int nLength)

16-bit signed short integer in place max value for each pair of elements.

Parameters:

pSrc Source Signal Pointer.
pSrcDst In-Place Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.179.2.2 NppStatus nppsMaxEvery_16u_I (const Npp16u * pSrc, Npp16u * pSrcDst, int nLength)

16-bit unsigned short integer in place max value for each pair of elements.

Parameters:

pSrc Source Signal Pointer.
pSrcDst In-Place Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.179.2.3 NppStatus nppsMaxEvery_32f_I (const Npp32f * pSrc, Npp32f * pSrcDst, int nLength)

32-bit floating point in place max value for each pair of elements.

Parameters:

pSrc Source Signal Pointer.
pSrcDst In-Place Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.179.2.4 NppStatus nppsMaxEvery_32s_I (const Npp32s * pSrc, Npp32s * pSrcDst, int nLength)

32-bit signed integer in place max value for each pair of elements.

Parameters:

pSrc Source Signal Pointer.
pSrcDst In-Place Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.179.2.5 NppStatus nppsMaxEvery_8u_I (const Npp8u * pSrc, Npp8u * pSrcDst, int nLength)

8-bit in place max value for each pair of elements.

Parameters:

pSrc Source Signal Pointer.
pSrcDst In-Place Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.179.2.6 NppStatus nppsMinEvery_16s_I (const Npp16s * pSrc, Npp16s * pSrcDst, int nLength)

16-bit signed short integer in place min value for each pair of elements.

Parameters:

pSrc Source Signal Pointer.
pSrcDst In-Place Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.179.2.7 NppStatus nppsMinEvery_16u_I (const Npp16u * pSrc, Npp16u * pSrcDst, int nLength)

16-bit unsigned short integer in place min value for each pair of elements.

Parameters:

pSrc Source Signal Pointer.
pSrcDst In-Place Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.179.2.8 NppStatus nppsMinEvery_32f_I (const Npp32f * pSrc, Npp32f * pSrcDst, int nLength)

32-bit floating point in place min value for each pair of elements.

Parameters:

pSrc Source Signal Pointer.
pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.179.2.9 NppStatus nppsMinEvery_32s_I (const Npp32s * pSrc, Npp32s * pSrcDst, int nLength)

32-bit signed integer in place min value for each pair of elements.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.179.2.10 NppStatus nppsMinEvery_64f_I (const Npp64f * pSrc, Npp64f * pSrcDst, int nLength)

64-bit floating point in place min value for each pair of elements.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.179.2.11 NppStatus nppsMinEvery_8u_I (const Npp8u * pSrc, Npp8u * pSrcDst, int nLength)

8-bit in place min value for each pair of elements.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.180 Sum

signal_min_every_or_max_every

Functions

- [NppStatus nppsSumGetBufferSize_32f](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsSum_32f.
- [NppStatus nppsSumGetBufferSize_32fc](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsSum_32fc.
- [NppStatus nppsSumGetBufferSize_64f](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsSum_64f.
- [NppStatus nppsSumGetBufferSize_64fc](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsSum_64fc.
- [NppStatus nppsSumGetBufferSize_16s_Sfs](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsSum_16s_Sfs.
- [NppStatus nppsSumGetBufferSize_16sc_Sfs](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsSum_16sc_Sfs.
- [NppStatus nppsSumGetBufferSize_16sc32sc_Sfs](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsSum_16sc32sc_Sfs.
- [NppStatus nppsSumGetBufferSize_32s_Sfs](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsSum_32s_Sfs.
- [NppStatus nppsSumGetBufferSize_16s32s_Sfs](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsSum_16s32s_Sfs.
- [NppStatus nppsSum_32f](#) (const [Npp32f](#) *pSrc, int nLength, [Npp32f](#) *pSum, [Npp8u](#) *pDeviceBuffer)
32-bit float vector sum method
- [NppStatus nppsSum_32fc](#) (const [Npp32fc](#) *pSrc, int nLength, [Npp32fc](#) *pSum, [Npp8u](#) *pDeviceBuffer)
32-bit float complex vector sum method
- [NppStatus nppsSum_64f](#) (const [Npp64f](#) *pSrc, int nLength, [Npp64f](#) *pSum, [Npp8u](#) *pDeviceBuffer)
64-bit double vector sum method
- [NppStatus nppsSum_64fc](#) (const [Npp64fc](#) *pSrc, int nLength, [Npp64fc](#) *pSum, [Npp8u](#) *pDeviceBuffer)
64-bit double complex vector sum method

- **NppStatus nppsSum_16s_Sfs** (const **Npp16s** *pSrc, int nLength, **Npp16s** *pSum, int nScaleFactor, **Npp8u** *pDeviceBuffer)
16-bit short vector sum with integer scaling method
- **NppStatus nppsSum_32s_Sfs** (const **Npp32s** *pSrc, int nLength, **Npp32s** *pSum, int nScaleFactor, **Npp8u** *pDeviceBuffer)
32-bit integer vector sum with integer scaling method
- **NppStatus nppsSum_16sc_Sfs** (const **Npp16sc** *pSrc, int nLength, **Npp16sc** *pSum, int nScaleFactor, **Npp8u** *pDeviceBuffer)
16-bit short complex vector sum with integer scaling method
- **NppStatus nppsSum_16sc32sc_Sfs** (const **Npp16sc** *pSrc, int nLength, **Npp32sc** *pSum, int nScaleFactor, **Npp8u** *pDeviceBuffer)
16-bit short complex vector sum (32bit int complex) with integer scaling method
- **NppStatus nppsSum_16s32s_Sfs** (const **Npp16s** *pSrc, int nLength, **Npp32s** *pSum, int nScaleFactor, **Npp8u** *pDeviceBuffer)
16-bit integer vector sum (32bit) with integer scaling method

7.180.1 Detailed Description

signal_min_every_or_max_every

7.180.2 Function Documentation

7.180.2.1 **NppStatus nppsSum_16s32s_Sfs** (const **Npp16s** *pSrc, int nLength, **Npp32s** *pSum, int nScaleFactor, **Npp8u** *pDeviceBuffer)

16-bit integer vector sum (32bit) with integer scaling method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pSum Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsSumGetBufferSize_16s32s_Sfs](#) to determine the minimum number of bytes required.

nScaleFactor Integer Result Scaling.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.180.2.2 **NppStatus nppsSum_16s_Sfs** (const **Npp16s** *pSrc, int nLength, **Npp16s** *pSum, int nScaleFactor, **Npp8u** *pDeviceBuffer)

16-bit short vector sum with integer scaling method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pSum Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsSumGetBufferSize_16s_Sfs](#) to determine the minium number of bytes required.

nScaleFactor Integer Result Scaling.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.180.2.3 `NppStatus nppsSum_16sc32sc_Sfs (const Npp16sc * pSrc, int nLength, Npp32sc * pSum, int nScaleFactor, Npp8u * pDeviceBuffer)`

16-bit short complex vector sum (32bit int complex) with integer scaling method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pSum Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsSumGetBufferSize_16sc32sc_Sfs](#) to determine the minium number of bytes required.

nScaleFactor Integer Result Scaling.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.180.2.4 `NppStatus nppsSum_16sc_Sfs (const Npp16sc * pSrc, int nLength, Npp16sc * pSum, int nScaleFactor, Npp8u * pDeviceBuffer)`

16-bit short complex vector sum with integer scaling method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pSum Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsSumGetBufferSize_16sc_Sfs](#) to determine the minium number of bytes required.

nScaleFactor Integer Result Scaling.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.180.2.5 NppStatus nppsSum_32f (const Npp32f * pSrc, int nLength, Npp32f * pSum, Npp8u * pDeviceBuffer)

32-bit float vector sum method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pSum Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsSumGetBufferSize_32f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.180.2.6 NppStatus nppsSum_32fc (const Npp32fc * pSrc, int nLength, Npp32fc * pSum, Npp8u * pDeviceBuffer)

32-bit float complex vector sum method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pSum Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsSumGetBufferSize_32fc](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.180.2.7 NppStatus nppsSum_32s_Sfs (const Npp32s * pSrc, int nLength, Npp32s * pSum, int nScaleFactor, Npp8u * pDeviceBuffer)

32-bit integer vector sum with integer scaling method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pSum Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsSumGetBufferSize_32s_Sfs](#) to determine the minium number of bytes required.

nScaleFactor Integer Result Scaling.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.180.2.8 NppStatus nppsSum_64f (const Npp64f * pSrc, int nLength, Npp64f * pSum, Npp8u * pDeviceBuffer)

64-bit double vector sum method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pSum Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsSumGetBufferSize_64f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.180.2.9 NppStatus nppsSum_64fc (const Npp64fc * pSrc, int nLength, Npp64fc * pSum, Npp8u * pDeviceBuffer)

64-bit double complex vector sum method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pSum Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsSumGetBufferSize_64fc](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.180.2.10 NppStatus nppsSumGetBufferSize_16s32s_Sfs (int nLength, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppsSum_16s32s_Sfs.

Parameters:

nLength Signal Length.

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.180.2.11 NppStatus nppsSumGetBufferSize_16s_Sfs (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsSum_16s_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.180.2.12 NppStatus nppsSumGetBufferSize_16sc32sc_Sfs (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsSum_16sc32sc_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.180.2.13 NppStatus nppsSumGetBufferSize_16sc_Sfs (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsSum_16sc_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.180.2.14 NppStatus nppsSumGetBufferSize_32f (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsSum_32f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.180.2.15 NppStatus nppsSumGetBufferSize_32fc (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsSum_32fc.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.180.2.16 NppStatus nppsSumGetBufferSize_32s_Sfs (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsSum_32s_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.180.2.17 NppStatus nppsSumGetBufferSize_64f (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsSum_64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.180.2.18 NppStatus nppsSumGetBufferSize_64fc (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsSum_64fc.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.181 Maximum

Functions

- [NppStatus nppsMaxGetBufferSize_16s](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMax_16s.
- [NppStatus nppsMaxGetBufferSize_32s](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMax_32s.
- [NppStatus nppsMaxGetBufferSize_32f](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMax_32f.
- [NppStatus nppsMaxGetBufferSize_64f](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMax_64f.
- [NppStatus nppsMax_16s](#) (const [Npp16s](#) *pSrc, int nLength, [Npp16s](#) *pMax, [Npp8u](#) *pDeviceBuffer)
16-bit integer vector max method
- [NppStatus nppsMax_32s](#) (const [Npp32s](#) *pSrc, int nLength, [Npp32s](#) *pMax, [Npp8u](#) *pDeviceBuffer)
32-bit integer vector max method
- [NppStatus nppsMax_32f](#) (const [Npp32f](#) *pSrc, int nLength, [Npp32f](#) *pMax, [Npp8u](#) *pDeviceBuffer)
32-bit float vector max method
- [NppStatus nppsMax_64f](#) (const [Npp64f](#) *pSrc, int nLength, [Npp64f](#) *pMax, [Npp8u](#) *pDeviceBuffer)
64-bit float vector max method
- [NppStatus nppsMaxIndxGetBufferSize_16s](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMaxIndx_16s.
- [NppStatus nppsMaxIndxGetBufferSize_32s](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMaxIndx_32s.
- [NppStatus nppsMaxIndxGetBufferSize_32f](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMaxIndx_32f.
- [NppStatus nppsMaxIndxGetBufferSize_64f](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMaxIndx_64f.
- [NppStatus nppsMaxIndx_16s](#) (const [Npp16s](#) *pSrc, int nLength, [Npp16s](#) *pMax, int *pIndx, [Npp8u](#) *pDeviceBuffer)
16-bit integer vector max index method
- [NppStatus nppsMaxIndx_32s](#) (const [Npp32s](#) *pSrc, int nLength, [Npp32s](#) *pMax, int *pIndx, [Npp8u](#) *pDeviceBuffer)

32-bit integer vector max index method

- [NppStatus nppsMaxIndx_32f](#) (const [Npp32f](#) *pSrc, int nLength, [Npp32f](#) *pMax, int *pIndx, [Npp8u](#) *pDeviceBuffer)

32-bit float vector max index method

- [NppStatus nppsMaxIndx_64f](#) (const [Npp64f](#) *pSrc, int nLength, [Npp64f](#) *pMax, int *pIndx, [Npp8u](#) *pDeviceBuffer)

64-bit float vector max index method

- [NppStatus nppsMaxAbsGetBufferSize_16s](#) (int nLength, int *hpBufferSize)

Device scratch buffer size (in bytes) for nppsMaxAbs_16s.

- [NppStatus nppsMaxAbsGetBufferSize_32s](#) (int nLength, int *hpBufferSize)

Device scratch buffer size (in bytes) for nppsMaxAbs_32s.

- [NppStatus nppsMaxAbs_16s](#) (const [Npp16s](#) *pSrc, int nLength, [Npp16s](#) *pMaxAbs, [Npp8u](#) *pDeviceBuffer)

16-bit integer vector max absolute method

- [NppStatus nppsMaxAbs_32s](#) (const [Npp32s](#) *pSrc, int nLength, [Npp32s](#) *pMaxAbs, [Npp8u](#) *pDeviceBuffer)

32-bit integer vector max absolute method

- [NppStatus nppsMaxAbsIndxGetBufferSize_16s](#) (int nLength, int *hpBufferSize)

Device scratch buffer size (in bytes) for nppsMaxAbsIndx_16s.

- [NppStatus nppsMaxAbsIndxGetBufferSize_32s](#) (int nLength, int *hpBufferSize)

Device scratch buffer size (in bytes) for nppsMaxAbsIndx_32s.

- [NppStatus nppsMaxAbsIndx_16s](#) (const [Npp16s](#) *pSrc, int nLength, [Npp16s](#) *pMaxAbs, int *pIndx, [Npp8u](#) *pDeviceBuffer)

16-bit integer vector max absolute index method

- [NppStatus nppsMaxAbsIndx_32s](#) (const [Npp32s](#) *pSrc, int nLength, [Npp32s](#) *pMaxAbs, int *pIndx, [Npp8u](#) *pDeviceBuffer)

32-bit integer vector max absolute index method

7.181.1 Function Documentation

7.181.1.1 [NppStatus nppsMax_16s](#) (const [Npp16s](#) *pSrc, int nLength, [Npp16s](#) *pMax, [Npp8u](#) *pDeviceBuffer)

16-bit integer vector max method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMax Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMaxGetBufferSize_16s](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.181.1.2 NppStatus nppsMax_32f (const Npp32f * pSrc, int nLength, Npp32f * pMax, Npp8u * pDeviceBuffer)

32-bit float vector max method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMax Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMaxGetBufferSize_32f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.181.1.3 NppStatus nppsMax_32s (const Npp32s * pSrc, int nLength, Npp32s * pMax, Npp8u * pDeviceBuffer)

32-bit integer vector max method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMax Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMaxGetBufferSize_32s](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.181.1.4 NppStatus nppsMax_64f (const Npp64f * pSrc, int nLength, Npp64f * pMax, Npp8u * pDeviceBuffer)

64-bit float vector max method

Parameters:

pSrc [Source Signal Pointer](#).

nLength Signal Length.

pMax Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMaxGetBufferSize_64f](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.181.1.5 NppStatus nppsMaxAbs_16s (const Npp16s * pSrc, int nLength, Npp16s * pMaxAbs, Npp8u * pDeviceBuffer)

16-bit integer vector max absolute method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pMaxAbs Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMaxAbsGetBufferSize_16s](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.181.1.6 NppStatus nppsMaxAbs_32s (const Npp32s * pSrc, int nLength, Npp32s * pMaxAbs, Npp8u * pDeviceBuffer)

32-bit integer vector max absolute method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pMaxAbs Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMaxAbsGetBufferSize_32s](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.181.1.7 NppStatus nppsMaxAbsGetBufferSize_16s (int nLength, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppsMaxAbs_16s.

Parameters:

nLength Signal Length.

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.181.1.8 NppStatus nppsMaxAbsGetBufferSize_32s (int nLength, int * hpBufferSize)

Device scratch buffer size (in bytes) for *nppsMaxAbs_32s*.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.181.1.9 NppStatus nppsMaxAbsIndx_16s (const Npp16s * pSrc, int nLength, Npp16s * pMaxAbs, int * pIndx, Npp8u * pDeviceBuffer)

16-bit integer vector max absolute index method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMaxAbs Pointer to the output result.

pIndx Pointer to the index value of the first maximum element.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMaxAbsIndxGetBufferSize_16s](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.181.1.10 NppStatus nppsMaxAbsIndx_32s (const Npp32s * pSrc, int nLength, Npp32s * pMaxAbs, int * pIndx, Npp8u * pDeviceBuffer)

32-bit integer vector max absolute index method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMaxAbs Pointer to the output result.

pIdx Pointer to the index value of the first maximum element.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMaxAbsIdxGetBufferSize_32s](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.181.1.11 NppStatus nppsMaxAbsIdxGetBufferSize_16s (int nLength, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppsMaxAbsIdx_16s.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.181.1.12 NppStatus nppsMaxAbsIdxGetBufferSize_32s (int nLength, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppsMaxAbsIdx_32s.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.181.1.13 NppStatus nppsMaxGetBufferSize_16s (int nLength, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppsMax_16s.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.181.1.14 NppStatus nppsMaxGetBufferSize_32f (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsMax_32f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.181.1.15 NppStatus nppsMaxGetBufferSize_32s (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsMax_32s.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.181.1.16 NppStatus nppsMaxGetBufferSize_64f (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsMax_64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.181.1.17 NppStatus nppsMaxIndx_16s (const Npp16s * *pSrc*, int *nLength*, Npp16s * *pMax*, int * *pIndx*, Npp8u * *pDeviceBuffer*)

16-bit integer vector max index method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMax Pointer to the output result.

pIndx Pointer to the index value of the first maximum element.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMaxIndxGetBufferSize_16s](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.181.1.18 NppStatus nppsMaxIndx_32f (const Npp32f * pSrc, int nLength, Npp32f * pMax, int * pIndx, Npp8u * pDeviceBuffer)

32-bit float vector max index method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMax Pointer to the output result.

pIndx Pointer to the index value of the first maximum element.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMaxIndxGetBufferSize_32f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.181.1.19 NppStatus nppsMaxIndx_32s (const Npp32s * pSrc, int nLength, Npp32s * pMax, int * pIndx, Npp8u * pDeviceBuffer)

32-bit integer vector max index method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMax Pointer to the output result.

pIndx Pointer to the index value of the first maximum element.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMaxIndxGetBufferSize_32s](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.181.1.20 NppStatus nppsMaxIndx_64f (const Npp64f * pSrc, int nLength, Npp64f * pMax, int * pIndx, Npp8u * pDeviceBuffer)

64-bit float vector max index method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pMax Pointer to the output result.

pIndx Pointer to the index value of the first maximum element.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMaxIndxGetBufferSize_64f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.181.1.21 NppStatus nppsMaxIndxGetBufferSize_16s (int nLength, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppsMaxIndx_16s.

Parameters:

nLength Signal Length.

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.181.1.22 NppStatus nppsMaxIndxGetBufferSize_32f (int nLength, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppsMaxIndx_32f.

Parameters:

nLength Signal Length.

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.181.1.23 NppStatus nppsMaxIdxGetBufferSize_32s (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsMaxIdx_32s.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.181.1.24 NppStatus nppsMaxIdxGetBufferSize_64f (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsMaxIdx_64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.182 Minimum

Functions

- [NppStatus nppsMinGetBufferSize_16s](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMin_16s.
- [NppStatus nppsMinGetBufferSize_32s](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMin_32s.
- [NppStatus nppsMinGetBufferSize_32f](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMin_32f.
- [NppStatus nppsMinGetBufferSize_64f](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMin_64f.
- [NppStatus nppsMin_16s](#) (const [Npp16s](#) *pSrc, int nLength, [Npp16s](#) *pMin, [Npp8u](#) *pDeviceBuffer)
16-bit integer vector min method
- [NppStatus nppsMin_32s](#) (const [Npp32s](#) *pSrc, int nLength, [Npp32s](#) *pMin, [Npp8u](#) *pDeviceBuffer)
32-bit integer vector min method
- [NppStatus nppsMin_32f](#) (const [Npp32f](#) *pSrc, int nLength, [Npp32f](#) *pMin, [Npp8u](#) *pDeviceBuffer)
32-bit integer vector min method
- [NppStatus nppsMin_64f](#) (const [Npp64f](#) *pSrc, int nLength, [Npp64f](#) *pMin, [Npp8u](#) *pDeviceBuffer)
64-bit integer vector min method
- [NppStatus nppsMinIndxGetBufferSize_16s](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMinIndx_16s.
- [NppStatus nppsMinIndxGetBufferSize_32s](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMinIndx_32s.
- [NppStatus nppsMinIndxGetBufferSize_32f](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMinIndx_32f.
- [NppStatus nppsMinIndxGetBufferSize_64f](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMinIndx_64f.
- [NppStatus nppsMinIndx_16s](#) (const [Npp16s](#) *pSrc, int nLength, [Npp16s](#) *pMin, int *pIndx, [Npp8u](#) *pDeviceBuffer)
16-bit integer vector min index method
- [NppStatus nppsMinIndx_32s](#) (const [Npp32s](#) *pSrc, int nLength, [Npp32s](#) *pMin, int *pIndx, [Npp8u](#) *pDeviceBuffer)

32-bit integer vector min index method

- **NppStatus nppsMinIndx_32f** (const **Npp32f** *pSrc, int nLength, **Npp32f** *pMin, int *pIndx, **Npp8u** *pDeviceBuffer)

32-bit float vector min index method

- **NppStatus nppsMinIndx_64f** (const **Npp64f** *pSrc, int nLength, **Npp64f** *pMin, int *pIndx, **Npp8u** *pDeviceBuffer)

64-bit float vector min index method

- **NppStatus nppsMinAbsGetBufferSize_16s** (int nLength, int *hpBufferSize)

Device scratch buffer size (in bytes) for nppsMinAbs_16s.

- **NppStatus nppsMinAbsGetBufferSize_32s** (int nLength, int *hpBufferSize)

Device scratch buffer size (in bytes) for nppsMinAbs_32s.

- **NppStatus nppsMinAbs_16s** (const **Npp16s** *pSrc, int nLength, **Npp16s** *pMinAbs, **Npp8u** *pDeviceBuffer)

16-bit integer vector min absolute method

- **NppStatus nppsMinAbs_32s** (const **Npp32s** *pSrc, int nLength, **Npp32s** *pMinAbs, **Npp8u** *pDeviceBuffer)

32-bit integer vector min absolute method

- **NppStatus nppsMinAbsIndxGetBufferSize_16s** (int nLength, int *hpBufferSize)

Device scratch buffer size (in bytes) for nppsMinAbsIndx_16s.

- **NppStatus nppsMinAbsIndxGetBufferSize_32s** (int nLength, int *hpBufferSize)

Device scratch buffer size (in bytes) for nppsMinAbsIndx_32s.

- **NppStatus nppsMinAbsIndx_16s** (const **Npp16s** *pSrc, int nLength, **Npp16s** *pMinAbs, int *pIndx, **Npp8u** *pDeviceBuffer)

16-bit integer vector min absolute index method

- **NppStatus nppsMinAbsIndx_32s** (const **Npp32s** *pSrc, int nLength, **Npp32s** *pMinAbs, int *pIndx, **Npp8u** *pDeviceBuffer)

32-bit integer vector min absolute index method

7.182.1 Function Documentation

7.182.1.1 **NppStatus nppsMin_16s** (const **Npp16s** *pSrc, int nLength, **Npp16s** *pMin, **Npp8u** *pDeviceBuffer)

16-bit integer vector min method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pMin Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).

Use [nppsMinGetBufferSize_16s](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.182.1.2 NppStatus nppsMin_32f (const Npp32f * pSrc, int nLength, Npp32f * pMin, Npp8u * pDeviceBuffer)

32-bit integer vector min method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMin Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).

Use [nppsMinGetBufferSize_32f](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.182.1.3 NppStatus nppsMin_32s (const Npp32s * pSrc, int nLength, Npp32s * pMin, Npp8u * pDeviceBuffer)

32-bit integer vector min method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMin Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).

Use [nppsMinGetBufferSize_32s](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.182.1.4 NppStatus nppsMin_64f (const Npp64f * pSrc, int nLength, Npp64f * pMin, Npp8u * pDeviceBuffer)

64-bit integer vector min method

Parameters:

pSrc [Source Signal Pointer](#).

nLength Signal Length.

pMin Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMinGetBufferSize_64f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.182.1.5 NppStatus nppsMinAbs_16s (const Npp16s * pSrc, int nLength, Npp16s * pMinAbs, Npp8u * pDeviceBuffer)

16-bit integer vector min absolute method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pMinAbs Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMinAbsGetBufferSize_16s](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.182.1.6 NppStatus nppsMinAbs_32s (const Npp32s * pSrc, int nLength, Npp32s * pMinAbs, Npp8u * pDeviceBuffer)

32-bit integer vector min absolute method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pMinAbs Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMinAbsGetBufferSize_16s](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.182.1.7 NppStatus nppsMinAbsGetBufferSize_16s (int nLength, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppsMinAbs_16s.

Parameters:

nLength Signal Length.

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.182.1.8 NppStatus nppsMinAbsGetBufferSize_32s (int nLength, int * hpBufferSize)

Device scratch buffer size (in bytes) for *nppsMinAbs_32s*.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.182.1.9 NppStatus nppsMinAbsIndx_16s (const Npp16s * pSrc, int nLength, Npp16s * pMinAbs, int * pIndx, Npp8u * pDeviceBuffer)

16-bit integer vector min absolute index method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMinAbs Pointer to the output result.

pIndx Pointer to the index value of the first minimum element.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMinAbsIndxGetBufferSize_16s](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.182.1.10 NppStatus nppsMinAbsIndx_32s (const Npp32s * pSrc, int nLength, Npp32s * pMinAbs, int * pIndx, Npp8u * pDeviceBuffer)

32-bit integer vector min absolute index method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMinAbs Pointer to the output result.

pIdx Pointer to the index value of the first minimum element.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMinAbsIdxGetBufferSize_32s](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.182.1.11 NppStatus nppsMinAbsIdxGetBufferSize_16s (int nLength, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppsMinAbsIdx_16s.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.182.1.12 NppStatus nppsMinAbsIdxGetBufferSize_32s (int nLength, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppsMinAbsIdx_32s.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.182.1.13 NppStatus nppsMinGetBufferSize_16s (int nLength, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppsMin_16s.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.182.1.14 NppStatus nppsMinGetBufferSize_32f (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsMin_32f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.182.1.15 NppStatus nppsMinGetBufferSize_32s (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsMin_32s.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.182.1.16 NppStatus nppsMinGetBufferSize_64f (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsMin_64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.182.1.17 NppStatus nppsMinIndx_16s (const Npp16s * *pSrc*, int *nLength*, Npp16s * *pMin*, int * *pIndx*, Npp8u * *pDeviceBuffer*)

16-bit integer vector min index method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMin Pointer to the output result.

pIndx Pointer to the index value of the first minimum element.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMinIndxGetBufferSize_16s](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.182.1.18 NppStatus nppsMinIndx_32f (const Npp32f * pSrc, int nLength, Npp32f * pMin, int * pIndx, Npp8u * pDeviceBuffer)

32-bit float vector min index method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMin Pointer to the output result.

pIndx Pointer to the index value of the first minimum element.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMinIndxGetBufferSize_32f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.182.1.19 NppStatus nppsMinIndx_32s (const Npp32s * pSrc, int nLength, Npp32s * pMin, int * pIndx, Npp8u * pDeviceBuffer)

32-bit integer vector min index method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMin Pointer to the output result.

pIndx Pointer to the index value of the first minimum element.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMinIndxGetBufferSize_32s](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.182.1.20 NppStatus nppsMinIndx_64f (const Npp64f * pSrc, int nLength, Npp64f * pMin, int * pIndx, Npp8u * pDeviceBuffer)

64-bit float vector min index method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMin Pointer to the output result.

pIndx Pointer to the index value of the first minimum element.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMinIndxGetBufferSize_64f](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.182.1.21 NppStatus nppsMinIndxGetBufferSize_16s (int nLength, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppsMinIndx_16s.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.182.1.22 NppStatus nppsMinIndxGetBufferSize_32f (int nLength, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppsMinIndx_32f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.182.1.23 NppStatus nppsMinIdxGetBufferSize_32s (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsMinIdx_32s.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.182.1.24 NppStatus nppsMinIdxGetBufferSize_64f (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsMinIdx_64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.183 Mean

Functions

- [NppStatus nppsMeanGetBufferSize_32f](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMean_32f.
- [NppStatus nppsMeanGetBufferSize_32fc](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMean_32fc.
- [NppStatus nppsMeanGetBufferSize_64f](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMean_64f.
- [NppStatus nppsMeanGetBufferSize_64fc](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMean_64fc.
- [NppStatus nppsMeanGetBufferSize_16s_Sfs](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMean_16s_Sfs.
- [NppStatus nppsMeanGetBufferSize_32s_Sfs](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMean_32s_Sfs.
- [NppStatus nppsMeanGetBufferSize_16sc_Sfs](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMean_16sc_Sfs.
- [NppStatus nppsMean_32f](#) (const [Npp32f](#) *pSrc, int nLength, [Npp32f](#) *pMean, [Npp8u](#) *pDeviceBuffer)
32-bit float vector mean method
- [NppStatus nppsMean_32fc](#) (const [Npp32fc](#) *pSrc, int nLength, [Npp32fc](#) *pMean, [Npp8u](#) *pDeviceBuffer)
32-bit float complex vector mean method
- [NppStatus nppsMean_64f](#) (const [Npp64f](#) *pSrc, int nLength, [Npp64f](#) *pMean, [Npp8u](#) *pDeviceBuffer)
64-bit double vector mean method
- [NppStatus nppsMean_64fc](#) (const [Npp64fc](#) *pSrc, int nLength, [Npp64fc](#) *pMean, [Npp8u](#) *pDeviceBuffer)
64-bit double complex vector mean method
- [NppStatus nppsMean_16s_Sfs](#) (const [Npp16s](#) *pSrc, int nLength, [Npp16s](#) *pMean, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)
16-bit short vector mean with integer scaling method
- [NppStatus nppsMean_32s_Sfs](#) (const [Npp32s](#) *pSrc, int nLength, [Npp32s](#) *pMean, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)
32-bit integer vector mean with integer scaling method
- [NppStatus nppsMean_16sc_Sfs](#) (const [Npp16sc](#) *pSrc, int nLength, [Npp16sc](#) *pMean, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)

16-bit short complex vector mean with integer scaling method

7.183.1 Function Documentation

7.183.1.1 `NppStatus nppsMean_16s_Sfs (const Npp16s * pSrc, int nLength, Npp16s * pMean, int nScaleFactor, Npp8u * pDeviceBuffer)`

16-bit short vector mean with integer scaling method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMean Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMeanGetBufferSize_16s_Sfs](#) to determine the minimum number of bytes required.

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.183.1.2 `NppStatus nppsMean_16sc_Sfs (const Npp16sc * pSrc, int nLength, Npp16sc * pMean, int nScaleFactor, Npp8u * pDeviceBuffer)`

16-bit short complex vector mean with integer scaling method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMean Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMeanGetBufferSize_16sc_Sfs](#) to determine the minimum number of bytes required.

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.183.1.3 `NppStatus nppsMean_32f (const Npp32f * pSrc, int nLength, Npp32f * pMean, Npp8u * pDeviceBuffer)`

32-bit float vector mean method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMean Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMeanGetBufferSize_32f](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.183.1.4 `NppStatus nppsMean_32fc (const Npp32fc * pSrc, int nLength, Npp32fc * pMean, Npp8u * pDeviceBuffer)`

32-bit float complex vector mean method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMean Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMeanGetBufferSize_32fc](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.183.1.5 `NppStatus nppsMean_32s_Sfs (const Npp32s * pSrc, int nLength, Npp32s * pMean, int nScaleFactor, Npp8u * pDeviceBuffer)`

32-bit integer vector mean with integer scaling method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMean Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMeanGetBufferSize_32s_Sfs](#) to determine the minimum number of bytes required.

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.183.1.6 NppStatus nppsMean_64f (const Npp64f * pSrc, int nLength, Npp64f * pMean, Npp8u * pDeviceBuffer)

64-bit double vector mean method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pMean Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMeanGetBufferSize_64f](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.183.1.7 NppStatus nppsMean_64fc (const Npp64fc * pSrc, int nLength, Npp64fc * pMean, Npp8u * pDeviceBuffer)

64-bit double complex vector mean method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pMean Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMeanGetBufferSize_64fc](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.183.1.8 NppStatus nppsMeanGetBufferSize_16s_Sfs (int nLength, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppsMean_16s_Sfs.

Parameters:

nLength Signal Length.

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.183.1.9 NppStatus nppsMeanGetBufferSize_16sc_Sfs (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsMean_16sc_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.183.1.10 NppStatus nppsMeanGetBufferSize_32f (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsMean_32f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.183.1.11 NppStatus nppsMeanGetBufferSize_32fc (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsMean_32fc.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.183.1.12 NppStatus nppsMeanGetBufferSize_32s_Sfs (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsMean_32s_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.183.1.13 NppStatus nppsMeanGetBufferSize_64f (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsMean_64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.183.1.14 NppStatus nppsMeanGetBufferSize_64fc (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsMean_64fc.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.184 Standard Deviation

Functions

- [NppStatus nppsStdDevGetBufferSize_32f](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsStdDev_32f.
- [NppStatus nppsStdDevGetBufferSize_64f](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsStdDev_64f.
- [NppStatus nppsStdDevGetBufferSize_16s32s_Sfs](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsStdDev_16s32s_Sfs.
- [NppStatus nppsStdDevGetBufferSize_16s_Sfs](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsStdDev_16s_Sfs.
- [NppStatus nppsStdDev_32f](#) (const [Npp32f](#) *pSrc, int nLength, [Npp32f](#) *pStdDev, [Npp8u](#) *pDeviceBuffer)
32-bit float vector standard deviation method
- [NppStatus nppsStdDev_64f](#) (const [Npp64f](#) *pSrc, int nLength, [Npp64f](#) *pStdDev, [Npp8u](#) *pDeviceBuffer)
64-bit float vector standard deviation method
- [NppStatus nppsStdDev_16s32s_Sfs](#) (const [Npp16s](#) *pSrc, int nLength, [Npp32s](#) *pStdDev, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)
16-bit float vector standard deviation method (return value is 32-bit)
- [NppStatus nppsStdDev_16s_Sfs](#) (const [Npp16s](#) *pSrc, int nLength, [Npp16s](#) *pStdDev, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)
16-bit float vector standard deviation method (return value is also 16-bit)

7.184.1 Function Documentation

7.184.1.1 [NppStatus nppsStdDev_16s32s_Sfs](#) (const [Npp16s](#) *pSrc, int nLength, [Npp32s](#) *pStdDev, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)

16-bit float vector standard deviation method (return value is 32-bit)

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pStdDev Pointer to the output result.

nScaleFactor [Integer Result Scaling](#).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsStdDevGetBufferSize_16s32s_Sfs](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.184.1.2 `NppStatus nppsStdDev_16s_Sfs (const Npp16s * pSrc, int nLength, Npp16s * pStdDev, int nScaleFactor, Npp8u * pDeviceBuffer)`

16-bit float vector standard deviation method (return value is also 16-bit)

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pStdDev Pointer to the output result.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsStdDevGetBufferSize_16s_Sfs](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.184.1.3 `NppStatus nppsStdDev_32f (const Npp32f * pSrc, int nLength, Npp32f * pStdDev, Npp8u * pDeviceBuffer)`

32-bit float vector standard deviation method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pStdDev Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsStdDevGetBufferSize_32f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.184.1.4 `NppStatus nppsStdDev_64f (const Npp64f * pSrc, int nLength, Npp64f * pStdDev, Npp8u * pDeviceBuffer)`

64-bit float vector standard deviation method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pStdDev Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsStdDevGetBufferSize_64f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.184.1.5 NppStatus nppsStdDevGetBufferSize_16s32s_Sfs (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsStdDev_16s32s_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.184.1.6 NppStatus nppsStdDevGetBufferSize_16s_Sfs (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsStdDev_16s_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.184.1.7 NppStatus nppsStdDevGetBufferSize_32f (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsStdDev_32f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.184.1.8 NppStatus nppsStdDevGetBufferSize_64f (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsStdDev_64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*. [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.185 Mean And Standard Deviation

Functions

- [NppStatus nppsMeanStdDevGetBufferSize_32f](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMeanStdDev_32f.
- [NppStatus nppsMeanStdDevGetBufferSize_64f](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMeanStdDev_64f.
- [NppStatus nppsMeanStdDevGetBufferSize_16s32s_Sfs](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMeanStdDev_16s32s_Sfs.
- [NppStatus nppsMeanStdDevGetBufferSize_16s_Sfs](#) (int nLength, int *hpBufferSize)
Device scratch buffer size (in bytes) for nppsMeanStdDev_16s_Sfs.
- [NppStatus nppsMeanStdDev_32f](#) (const [Npp32f](#) *pSrc, int nLength, [Npp32f](#) *pMean, [Npp32f](#) *pStdDev, [Npp8u](#) *pDeviceBuffer)
32-bit float vector mean and standard deviation method
- [NppStatus nppsMeanStdDev_64f](#) (const [Npp64f](#) *pSrc, int nLength, [Npp64f](#) *pMean, [Npp64f](#) *pStdDev, [Npp8u](#) *pDeviceBuffer)
64-bit float vector mean and standard deviation method
- [NppStatus nppsMeanStdDev_16s32s_Sfs](#) (const [Npp16s](#) *pSrc, int nLength, [Npp32s](#) *pMean, [Npp32s](#) *pStdDev, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)
16-bit float vector mean and standard deviation method (return values are 32-bit)
- [NppStatus nppsMeanStdDev_16s_Sfs](#) (const [Npp16s](#) *pSrc, int nLength, [Npp16s](#) *pMean, [Npp16s](#) *pStdDev, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)
16-bit float vector mean and standard deviation method (return values are also 16-bit)

7.185.1 Function Documentation

7.185.1.1 [NppStatus nppsMeanStdDev_16s32s_Sfs](#) (const [Npp16s](#) *pSrc, int nLength, [Npp32s](#) *pMean, [Npp32s](#) *pStdDev, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)

16-bit float vector mean and standard deviation method (return values are 32-bit)

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMean Pointer to the output mean value.

pStdDev Pointer to the output standard deviation value.

nScaleFactor [Integer Result Scaling](#).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#). Use [nppsMeanStdDevGetBufferSize_16s32s_Sfs](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.185.1.2 NppStatus nppsMeanStdDev_16s_Sfs (const Npp16s * pSrc, int nLength, Npp16s * pMean, Npp16s * pStdDev, int nScaleFactor, Npp8u * pDeviceBuffer)

16-bit float vector mean and standard deviation method (return values are also 16-bit)

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMean Pointer to the output mean value.

pStdDev Pointer to the output standard deviation value.

nScaleFactor [Integer Result Scaling](#).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMeanStdDevGetBufferSize_16s_Sfs](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.185.1.3 NppStatus nppsMeanStdDev_32f (const Npp32f * pSrc, int nLength, Npp32f * pMean, Npp32f * pStdDev, Npp8u * pDeviceBuffer)

32-bit float vector mean and standard deviation method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMean Pointer to the output mean value.

pStdDev Pointer to the output standard deviation value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMeanStdDevGetBufferSize_32f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.185.1.4 NppStatus nppsMeanStdDev_64f (const Npp64f * pSrc, int nLength, Npp64f * pMean, Npp64f * pStdDev, Npp8u * pDeviceBuffer)

64-bit float vector mean and standard deviation method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMean Pointer to the output mean value.

pStdDev Pointer to the output standard deviation value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMeanStdDevGetBufferSize_64f](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.185.1.5 NppStatus nppsMeanStdDevGetBufferSize_16s32s_Sfs (int nLength, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppsMeanStdDev_16s32s_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.185.1.6 NppStatus nppsMeanStdDevGetBufferSize_16s_Sfs (int nLength, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppsMeanStdDev_16s_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.185.1.7 NppStatus nppsMeanStdDevGetBufferSize_32f (int nLength, int * hpBufferSize)

Device scratch buffer size (in bytes) for nppsMeanStdDev_32f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.185.1.8 NppStatus nppsMeanStdDevGetBufferSize_64f (int *nLength*, int * *hpBufferSize*)

Device scratch buffer size (in bytes) for nppsMeanStdDev_64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*: [Scratch Buffer and Host Pointer](#).

Returns:

NPP_SUCCESS

7.186 Minimum_Maximum

Functions

- [NppStatus nppsMinMaxGetBufferSize_8u](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsMinMax_8u.
- [NppStatus nppsMinMaxGetBufferSize_16s](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsMinMax_16s.
- [NppStatus nppsMinMaxGetBufferSize_16u](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsMinMax_16u.
- [NppStatus nppsMinMaxGetBufferSize_32s](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsMinMax_32s.
- [NppStatus nppsMinMaxGetBufferSize_32u](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsMinMax_32u.
- [NppStatus nppsMinMaxGetBufferSize_32f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsMinMax_32f.
- [NppStatus nppsMinMaxGetBufferSize_64f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsMinMax_64f.
- [NppStatus nppsMinMax_8u](#) (const [Npp8u](#) *pSrc, int nLength, [Npp8u](#) *pMin, [Npp8u](#) *pMax, [Npp8u](#) *pDeviceBuffer)
8-bit char vector min and max method
- [NppStatus nppsMinMax_16s](#) (const [Npp16s](#) *pSrc, int nLength, [Npp16s](#) *pMin, [Npp16s](#) *pMax, [Npp8u](#) *pDeviceBuffer)
16-bit signed short vector min and max method
- [NppStatus nppsMinMax_16u](#) (const [Npp16u](#) *pSrc, int nLength, [Npp16u](#) *pMin, [Npp16u](#) *pMax, [Npp8u](#) *pDeviceBuffer)
16-bit unsigned short vector min and max method
- [NppStatus nppsMinMax_32u](#) (const [Npp32u](#) *pSrc, int nLength, [Npp32u](#) *pMin, [Npp32u](#) *pMax, [Npp8u](#) *pDeviceBuffer)
32-bit unsigned int vector min and max method
- [NppStatus nppsMinMax_32s](#) (const [Npp32s](#) *pSrc, int nLength, [Npp32s](#) *pMin, [Npp32s](#) *pMax, [Npp8u](#) *pDeviceBuffer)
32-bit signed int vector min and max method
- [NppStatus nppsMinMax_32f](#) (const [Npp32f](#) *pSrc, int nLength, [Npp32f](#) *pMin, [Npp32f](#) *pMax, [Npp8u](#) *pDeviceBuffer)
32-bit float vector min and max method
- [NppStatus nppsMinMax_64f](#) (const [Npp64f](#) *pSrc, int nLength, [Npp64f](#) *pMin, [Npp64f](#) *pMax, [Npp8u](#) *pDeviceBuffer)

64-bit double vector min and max method

- [NppStatus nppsMinMaxIdxGetBufferSize_8u](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsMinMaxIdx_8u.
- [NppStatus nppsMinMaxIdxGetBufferSize_16s](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsMinMaxIdx_16s.
- [NppStatus nppsMinMaxIdxGetBufferSize_16u](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsMinMaxIdx_16u.
- [NppStatus nppsMinMaxIdxGetBufferSize_32s](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsMinMaxIdx_32s.
- [NppStatus nppsMinMaxIdxGetBufferSize_32u](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsMinMaxIdx_32u.
- [NppStatus nppsMinMaxIdxGetBufferSize_32f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsMinMaxIdx_32f.
- [NppStatus nppsMinMaxIdxGetBufferSize_64f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsMinMaxIdx_64f.
- [NppStatus nppsMinMaxIdx_8u](#) (const [Npp8u](#) *pSrc, int nLength, [Npp8u](#) *pMin, int *pMinIdx, [Npp8u](#) *pMax, int *pMaxIdx, [Npp8u](#) *pDeviceBuffer)
8-bit char vector min and max with indices method
- [NppStatus nppsMinMaxIdx_16s](#) (const [Npp16s](#) *pSrc, int nLength, [Npp16s](#) *pMin, int *pMinIdx, [Npp16s](#) *pMax, int *pMaxIdx, [Npp8u](#) *pDeviceBuffer)
16-bit signed short vector min and max with indices method
- [NppStatus nppsMinMaxIdx_16u](#) (const [Npp16u](#) *pSrc, int nLength, [Npp16u](#) *pMin, int *pMinIdx, [Npp16u](#) *pMax, int *pMaxIdx, [Npp8u](#) *pDeviceBuffer)
16-bit unsigned short vector min and max with indices method
- [NppStatus nppsMinMaxIdx_32s](#) (const [Npp32s](#) *pSrc, int nLength, [Npp32s](#) *pMin, int *pMinIdx, [Npp32s](#) *pMax, int *pMaxIdx, [Npp8u](#) *pDeviceBuffer)
32-bit signed short vector min and max with indices method
- [NppStatus nppsMinMaxIdx_32u](#) (const [Npp32u](#) *pSrc, int nLength, [Npp32u](#) *pMin, int *pMinIdx, [Npp32u](#) *pMax, int *pMaxIdx, [Npp8u](#) *pDeviceBuffer)
32-bit unsigned short vector min and max with indices method
- [NppStatus nppsMinMaxIdx_32f](#) (const [Npp32f](#) *pSrc, int nLength, [Npp32f](#) *pMin, int *pMinIdx, [Npp32f](#) *pMax, int *pMaxIdx, [Npp8u](#) *pDeviceBuffer)
32-bit float vector min and max with indices method
- [NppStatus nppsMinMaxIdx_64f](#) (const [Npp64f](#) *pSrc, int nLength, [Npp64f](#) *pMin, int *pMinIdx, [Npp64f](#) *pMax, int *pMaxIdx, [Npp8u](#) *pDeviceBuffer)
64-bit float vector min and max with indices method

7.186.1 Function Documentation

7.186.1.1 `NppStatus nppsMinMax_16s (const Npp16s * pSrc, int nLength, Npp16s * pMin, Npp16s * pMax, Npp8u * pDeviceBuffer)`

16-bit signed short vector min and max method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pMin Pointer to the min output result.

pMax Pointer to the max output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMinMaxGetBufferSize_16s](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.186.1.2 `NppStatus nppsMinMax_16u (const Npp16u * pSrc, int nLength, Npp16u * pMin, Npp16u * pMax, Npp8u * pDeviceBuffer)`

16-bit unsigned short vector min and max method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pMin Pointer to the min output result.

pMax Pointer to the max output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMinMaxGetBufferSize_16u](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.186.1.3 `NppStatus nppsMinMax_32f (const Npp32f * pSrc, int nLength, Npp32f * pMin, Npp32f * pMax, Npp8u * pDeviceBuffer)`

32-bit float vector min and max method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pMin Pointer to the min output result.

pMax Pointer to the max output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMinMaxGetBufferSize_32f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.186.1.4 NppStatus nppsMinMax_32s (const Npp32s * pSrc, int nLength, Npp32s * pMin, Npp32s * pMax, Npp8u * pDeviceBuffer)

32-bit signed int vector min and max method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMin Pointer to the min output result.

pMax Pointer to the max output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMinMaxGetBufferSize_32s](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.186.1.5 NppStatus nppsMinMax_32u (const Npp32u * pSrc, int nLength, Npp32u * pMin, Npp32u * pMax, Npp8u * pDeviceBuffer)

32-bit unsigned int vector min and max method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMin Pointer to the min output result.

pMax Pointer to the max output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMinMaxGetBufferSize_32u](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.186.1.6 NppStatus nppsMinMax_64f (const Npp64f * pSrc, int nLength, Npp64f * pMin, Npp64f * pMax, Npp8u * pDeviceBuffer)

64-bit double vector min and max method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pMin Pointer to the min output result.

pMax Pointer to the max output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMinMaxGetBufferSize_64f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.186.1.7 NppStatus nppsMinMax_8u (const Npp8u * pSrc, int nLength, Npp8u * pMin, Npp8u * pMax, Npp8u * pDeviceBuffer)

8-bit char vector min and max method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pMin Pointer to the min output result.

pMax Pointer to the max output result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMinMaxGetBufferSize_8u](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.186.1.8 NppStatus nppsMinMaxGetBufferSize_16s (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsMinMax_16s.

Parameters:

nLength Signal Length.

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.186.1.9 NppStatus nppsMinMaxGetBufferSize_16u (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsMinMax_16u.

Parameters:

nLength Signal Length.

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.186.1.10 NppStatus nppsMinMaxGetBufferSize_32f (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for *nppsMinMax_32f*.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.186.1.11 NppStatus nppsMinMaxGetBufferSize_32s (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for *nppsMinMax_32s*.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.186.1.12 NppStatus nppsMinMaxGetBufferSize_32u (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for *nppsMinMax_32u*.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.186.1.13 NppStatus nppsMinMaxGetBufferSize_64f (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsMinMax_64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.186.1.14 NppStatus nppsMinMaxGetBufferSize_8u (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsMinMax_8u.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.186.1.15 NppStatus nppsMinMaxIndx_16s (const Npp16s * pSrc, int nLength, Npp16s * pMin, int * pMinIndx, Npp16s * pMax, int * pMaxIndx, Npp8u * pDeviceBuffer)

16-bit signed short vector min and max with indices method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMin Pointer to the min output result.

pMinIndx Pointer to the index of the first min value.

pMax Pointer to the max output result.

pMaxIndx Pointer to the index of the first max value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMinMaxIndxGetBufferSize_16s](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.186.1.16 NppStatus nppsMinMaxIndx_16u (const Npp16u * pSrc, int nLength, Npp16u * pMin, int * pMinIndx, Npp16u * pMax, int * pMaxIndx, Npp8u * pDeviceBuffer)

16-bit unsigned short vector min and max with indices method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMin Pointer to the min output result.

pMinIndx Pointer to the index of the first min value.

pMax Pointer to the max output result.

pMaxIndx Pointer to the index of the first max value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMinMaxIndxGetBufferSize_16u](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.186.1.17 NppStatus nppsMinMaxIndx_32f (const Npp32f * pSrc, int nLength, Npp32f * pMin, int * pMinIndx, Npp32f * pMax, int * pMaxIndx, Npp8u * pDeviceBuffer)

32-bit float vector min and max with indices method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMin Pointer to the min output result.

pMinIndx Pointer to the index of the first min value.

pMax Pointer to the max output result.

pMaxIndx Pointer to the index of the first max value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMinMaxIndxGetBufferSize_32f](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.186.1.18 NppStatus nppsMinMaxIndx_32s (const Npp32s * pSrc, int nLength, Npp32s * pMin, int * pMinIndx, Npp32s * pMax, int * pMaxIndx, Npp8u * pDeviceBuffer)

32-bit signed short vector min and max with indices method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMin Pointer to the min output result.
pMinIdx Pointer to the index of the first min value.
pMax Pointer to the max output result.
pMaxIdx Pointer to the index of the first max value.
pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
 Use [nppsMinMaxIdxGetBufferSize_32s](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.186.1.19 `NppStatus nppsMinMaxIdx_32u (const Npp32u * pSrc, int nLength, Npp32u * pMin, int * pMinIdx, Npp32u * pMax, int * pMaxIdx, Npp8u * pDeviceBuffer)`

32-bit unsigned short vector min and max with indices method

Parameters:

pSrc [Source Signal Pointer](#).
nLength [Signal Length](#).
pMin Pointer to the min output result.
pMinIdx Pointer to the index of the first min value.
pMax Pointer to the max output result.
pMaxIdx Pointer to the index of the first max value.
pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
 Use [nppsMinMaxIdxGetBufferSize_32u](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.186.1.20 `NppStatus nppsMinMaxIdx_64f (const Npp64f * pSrc, int nLength, Npp64f * pMin, int * pMinIdx, Npp64f * pMax, int * pMaxIdx, Npp8u * pDeviceBuffer)`

64-bit float vector min and max with indices method

Parameters:

pSrc [Source Signal Pointer](#).
nLength [Signal Length](#).
pMin Pointer to the min output result.
pMinIdx Pointer to the index of the first min value.
pMax Pointer to the max output result.
pMaxIdx Pointer to the index of the first max value.
pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
 Use [nppsMinMaxIdxGetBufferSize_64f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.186.1.21 `NppStatus nppsMinMaxIndx_8u (const Npp8u * pSrc, int nLength, Npp8u * pMin, int * pMinIdx, Npp8u * pMax, int * pMaxIdx, Npp8u * pDeviceBuffer)`

8-bit char vector min and max with indices method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pMin Pointer to the min output result.

pMinIdx Pointer to the index of the first min value.

pMax Pointer to the max output result.

pMaxIdx Pointer to the index of the first max value.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsMinMaxIndxGetBufferSize_8u](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.186.1.22 `NppStatus nppsMinMaxIndxGetBufferSize_16s (int nLength, int * hpBufferSize)`

Device-buffer size (in bytes) for nppsMinMaxIndx_16s.

Parameters:

nLength Signal Length.

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.186.1.23 `NppStatus nppsMinMaxIndxGetBufferSize_16u (int nLength, int * hpBufferSize)`

Device-buffer size (in bytes) for nppsMinMaxIndx_16u.

Parameters:

nLength Signal Length.

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.186.1.24 NppStatus nppsMinMaxIdxGetBufferSize_32f (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsMinMaxIdx_32f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.186.1.25 NppStatus nppsMinMaxIdxGetBufferSize_32s (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsMinMaxIdx_32s.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.186.1.26 NppStatus nppsMinMaxIdxGetBufferSize_32u (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsMinMaxIdx_32u.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.186.1.27 NppStatus nppsMinMaxIdxGetBufferSize_64f (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsMinMaxIdx_64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.186.1.28 NppStatus nppsMinMaxIndxGetBufferSize_8u (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsMinMaxIndx_8u.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.187 Infinity Norm

Functions

- [NppStatus nppsNormInfGetBufferSize_32f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNorm_Inf_32f.
- [NppStatus nppsNorm_Inf_32f](#) (const [Npp32f](#) *pSrc, int nLength, [Npp32f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
32-bit float vector C norm method
- [NppStatus nppsNormInfGetBufferSize_64f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNorm_Inf_64f.
- [NppStatus nppsNorm_Inf_64f](#) (const [Npp64f](#) *pSrc, int nLength, [Npp64f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
64-bit float vector C norm method
- [NppStatus nppsNormInfGetBufferSize_16s32f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNorm_Inf_16s32f.
- [NppStatus nppsNorm_Inf_16s32f](#) (const [Npp16s](#) *pSrc, int nLength, [Npp32f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
16-bit signed short integer vector C norm method, return value is 32-bit float.
- [NppStatus nppsNormInfGetBufferSize_32fc32f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNorm_Inf_32fc32f.
- [NppStatus nppsNorm_Inf_32fc32f](#) (const [Npp32fc](#) *pSrc, int nLength, [Npp32f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
32-bit float complex vector C norm method, return value is 32-bit float.
- [NppStatus nppsNormInfGetBufferSize_64fc64f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNorm_Inf_64fc64f.
- [NppStatus nppsNorm_Inf_64fc64f](#) (const [Npp64fc](#) *pSrc, int nLength, [Npp64f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
64-bit float complex vector C norm method, return value is 64-bit float.
- [NppStatus nppsNormInfGetBufferSize_16s32s_Sfs](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNorm_Inf_16s32s_Sfs.
- [NppStatus nppsNorm_Inf_16s32s_Sfs](#) (const [Npp16s](#) *pSrc, int nLength, [Npp32s](#) *pNorm, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)
16-bit signed short integer vector C norm method, return value is 32-bit signed integer.

7.187.1 Function Documentation

7.187.1.1 `NppStatus nppsNorm_Inf_16s32f (const Npp16s * pSrc, int nLength, Npp32f * pNorm, Npp8u * pDeviceBuffer)`

16-bit signed short integer vector C norm method, return value is 32-bit float.

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormInfGetBufferSize_16s32f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.187.1.2 `NppStatus nppsNorm_Inf_16s32s_Sfs (const Npp16s * pSrc, int nLength, Npp32s * pNorm, int nScaleFactor, Npp8u * pDeviceBuffer)`

16-bit signed short integer vector C norm method, return value is 32-bit signed integer.

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormInfGetBufferSize_16s32s_Sfs](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.187.1.3 `NppStatus nppsNorm_Inf_32f (const Npp32f * pSrc, int nLength, Npp32f * pNorm, Npp8u * pDeviceBuffer)`

32-bit float vector C norm method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormInfGetBufferSize_32f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.187.1.4 NppStatus nppsNorm_Inf_32fc32f (const Npp32fc * pSrc, int nLength, Npp32f * pNorm, Npp8u * pDeviceBuffer)

32-bit float complex vector C norm method, return value is 32-bit float.

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).

Use [nppsNormInfGetBufferSize_32fc32f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.187.1.5 NppStatus nppsNorm_Inf_64f (const Npp64f * pSrc, int nLength, Npp64f * pNorm, Npp8u * pDeviceBuffer)

64-bit float vector C norm method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).

Use [nppsNormInfGetBufferSize_64f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.187.1.6 NppStatus nppsNorm_Inf_64fc64f (const Npp64fc * pSrc, int nLength, Npp64f * pNorm, Npp8u * pDeviceBuffer)

64-bit float complex vector C norm method, return value is 64-bit float.

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).

Use [nppsNormInfGetBufferSize_64fc64f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.187.1.7 NppStatus nppsNormInfGetBufferSize_16s32f (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsNorm_Inf_16s32f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.187.1.8 NppStatus nppsNormInfGetBufferSize_16s32s_Sfs (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsNorm_Inf_16s32s_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.187.1.9 NppStatus nppsNormInfGetBufferSize_32f (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsNorm_Inf_32f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.187.1.10 NppStatus nppsNormInfGetBufferSize_32fc32f (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsNorm_Inf_32fc32f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.187.1.11 NppStatus nppsNormInfGetBufferSize_64f (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsNorm_Inf_64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.187.1.12 NppStatus nppsNormInfGetBufferSize_64fc64f (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsNorm_Inf_64fc64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.188 L1 Norm

Functions

- [NppStatus nppsNormL1GetBufferSize_32f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNorm_L1_32f.
- [NppStatus nppsNorm_L1_32f](#) (const [Npp32f](#) *pSrc, int nLength, [Npp32f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
32-bit float vector L1 norm method
- [NppStatus nppsNormL1GetBufferSize_64f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNorm_L1_64f.
- [NppStatus nppsNorm_L1_64f](#) (const [Npp64f](#) *pSrc, int nLength, [Npp64f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
64-bit float vector L1 norm method
- [NppStatus nppsNormL1GetBufferSize_16s32f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNorm_L1_16s32f.
- [NppStatus nppsNorm_L1_16s32f](#) (const [Npp16s](#) *pSrc, int nLength, [Npp32f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
16-bit signed short integer vector L1 norm method, return value is 32-bit float.
- [NppStatus nppsNormL1GetBufferSize_32fc64f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNorm_L1_32fc64f.
- [NppStatus nppsNorm_L1_32fc64f](#) (const [Npp32fc](#) *pSrc, int nLength, [Npp64f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
32-bit float complex vector L1 norm method, return value is 64-bit float.
- [NppStatus nppsNormL1GetBufferSize_64fc64f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNorm_L1_64fc64f.
- [NppStatus nppsNorm_L1_64fc64f](#) (const [Npp64fc](#) *pSrc, int nLength, [Npp64f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
64-bit float complex vector L1 norm method, return value is 64-bit float.
- [NppStatus nppsNormL1GetBufferSize_16s32s_Sfs](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNorm_L1_16s32s_Sfs.
- [NppStatus nppsNorm_L1_16s32s_Sfs](#) (const [Npp16s](#) *pSrc, int nLength, [Npp32s](#) *pNorm, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)
16-bit signed short integer vector L1 norm method, return value is 32-bit signed integer.
- [NppStatus nppsNormL1GetBufferSize_16s64s_Sfs](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNorm_L1_16s64s_Sfs.
- [NppStatus nppsNorm_L1_16s64s_Sfs](#) (const [Npp16s](#) *pSrc, int nLength, [Npp64s](#) *pNorm, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)

16-bit signed short integer vector L1 norm method, return value is 64-bit signed integer.

7.188.1 Function Documentation

7.188.1.1 NppStatus nppsNorm_L1_16s32f (const Npp16s * pSrc, int nLength, Npp32f * pNorm, Npp8u * pDeviceBuffer)

16-bit signed short integer vector L1 norm method, return value is 32-bit float.

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the L1 norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormL1GetBufferSize_16s32f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.188.1.2 NppStatus nppsNorm_L1_16s32s_Sfs (const Npp16s * pSrc, int nLength, Npp32s * pNorm, int nScaleFactor, Npp8u * pDeviceBuffer)

16-bit signed short integer vector L1 norm method, return value is 32-bit signed integer.

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormL1GetBufferSize_16s32s_Sfs](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.188.1.3 NppStatus nppsNorm_L1_16s64s_Sfs (const Npp16s * pSrc, int nLength, Npp64s * pNorm, int nScaleFactor, Npp8u * pDeviceBuffer)

16-bit signed short integer vector L1 norm method, return value is 64-bit signed integer.

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).

Use [nppsNormL1GetBufferSize_16s64s_Sfs](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.188.1.4 `NppStatus nppsNorm_L1_32f (const Npp32f * pSrc, int nLength, Npp32f * pNorm, Npp8u * pDeviceBuffer)`

32-bit float vector L1 norm method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).

Use [nppsNormL1GetBufferSize_32f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.188.1.5 `NppStatus nppsNorm_L1_32fc64f (const Npp32fc * pSrc, int nLength, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

32-bit float complex vector L1 norm method, return value is 64-bit float.

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).

Use [nppsNormL1GetBufferSize_32fc64f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.188.1.6 `NppStatus nppsNorm_L1_64f (const Npp64f * pSrc, int nLength, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

64-bit float vector L1 norm method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormL1GetBufferSize_64f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.188.1.7 NppStatus nppsNorm_L1_64fc64f (const Npp64fc * pSrc, int nLength, Npp64f * pNorm, Npp8u * pDeviceBuffer)

64-bit float complex vector L1 norm method, return value is 64-bit float.

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormL1GetBufferSize_64fc64f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.188.1.8 NppStatus nppsNormL1GetBufferSize_16s32f (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsNorm_L1_16s32f.

Parameters:

nLength Signal Length.

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.188.1.9 NppStatus nppsNormL1GetBufferSize_16s32s_Sfs (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsNorm_L1_16s32s_Sfs.

Parameters:

nLength Signal Length.

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.188.1.10 NppStatus nppsNormL1GetBufferSize_16s64s_Sfs (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsNorm_L1_16s64s_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.188.1.11 NppStatus nppsNormL1GetBufferSize_32f (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsNorm_L1_32f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.188.1.12 NppStatus nppsNormL1GetBufferSize_32fc64f (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsNorm_L1_32fc64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.188.1.13 NppStatus nppsNormL1GetBufferSize_64f (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsNorm_L1_64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.188.1.14 `NppStatus nppsNormL1GetBufferSize_64fc64f (int nLength, int * hpBufferSize)`

Device-buffer size (in bytes) for `nppsNorm_L1_64fc64f`.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: `hpBufferSize` is a *host pointer*.

Returns:

`NPP_SUCCESS`

7.189 L2 Norm

Functions

- [NppStatus nppsNormL2GetBufferSize_32f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNorm_L2_32f.
- [NppStatus nppsNorm_L2_32f](#) (const [Npp32f](#) *pSrc, int nLength, [Npp32f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
32-bit float vector L2 norm method
- [NppStatus nppsNormL2GetBufferSize_64f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNorm_L2_64f.
- [NppStatus nppsNorm_L2_64f](#) (const [Npp64f](#) *pSrc, int nLength, [Npp64f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
64-bit float vector L2 norm method
- [NppStatus nppsNormL2GetBufferSize_16s32f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNorm_L2_16s32f.
- [NppStatus nppsNorm_L2_16s32f](#) (const [Npp16s](#) *pSrc, int nLength, [Npp32f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
16-bit signed short integer vector L2 norm method, return value is 32-bit float.
- [NppStatus nppsNormL2GetBufferSize_32fc64f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNorm_L2_32fc64f.
- [NppStatus nppsNorm_L2_32fc64f](#) (const [Npp32fc](#) *pSrc, int nLength, [Npp64f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
32-bit float complex vector L2 norm method, return value is 64-bit float.
- [NppStatus nppsNormL2GetBufferSize_64fc64f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNorm_L2_64fc64f.
- [NppStatus nppsNorm_L2_64fc64f](#) (const [Npp64fc](#) *pSrc, int nLength, [Npp64f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
64-bit float complex vector L2 norm method, return value is 64-bit float.
- [NppStatus nppsNormL2GetBufferSize_16s32s_Sfs](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNorm_L2_16s32s_Sfs.
- [NppStatus nppsNorm_L2_16s32s_Sfs](#) (const [Npp16s](#) *pSrc, int nLength, [Npp32s](#) *pNorm, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)
16-bit signed short integer vector L2 norm method, return value is 32-bit signed integer.
- [NppStatus nppsNormL2SqrGetBufferSize_16s64s_Sfs](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNorm_L2Sqr_16s64s_Sfs.
- [NppStatus nppsNorm_L2Sqr_16s64s_Sfs](#) (const [Npp16s](#) *pSrc, int nLength, [Npp64s](#) *pNorm, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)

16-bit signed short integer vector L2 Square norm method, return value is 64-bit signed integer.

7.189.1 Function Documentation

7.189.1.1 `NppStatus nppsNorm_L2_16s32f (const Npp16s * pSrc, int nLength, Npp32f * pNorm, Npp8u * pDeviceBuffer)`

16-bit signed short integer vector L2 norm method, return value is 32-bit float.

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use `nppsNormL2GetBufferSize_16s32f` to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.189.1.2 `NppStatus nppsNorm_L2_16s32s_Sfs (const Npp16s * pSrc, int nLength, Npp32s * pNorm, int nScaleFactor, Npp8u * pDeviceBuffer)`

16-bit signed short integer vector L2 norm method, return value is 32-bit signed integer.

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use `nppsNormL2GetBufferSize_16s32s_Sfs` to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.189.1.3 `NppStatus nppsNorm_L2_32f (const Npp32f * pSrc, int nLength, Npp32f * pNorm, Npp8u * pDeviceBuffer)`

32-bit float vector L2 norm method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).

Use [nppsNormL2GetBufferSize_32f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.189.1.4 NppStatus nppsNorm_L2_32fc64f (const Npp32fc * pSrc, int nLength, Npp64f * pNorm, Npp8u * pDeviceBuffer)

32-bit float complex vector L2 norm method, return value is 64-bit float.

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).

Use [nppsNormL2GetBufferSize_32fc64f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.189.1.5 NppStatus nppsNorm_L2_64f (const Npp64f * pSrc, int nLength, Npp64f * pNorm, Npp8u * pDeviceBuffer)

64-bit float vector L2 norm method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).

Use [nppsNormL2GetBufferSize_64f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.189.1.6 NppStatus nppsNorm_L2_64fc64f (const Npp64fc * pSrc, int nLength, Npp64f * pNorm, Npp8u * pDeviceBuffer)

64-bit float complex vector L2 norm method, return value is 64-bit float.

Parameters:

pSrc [Source Signal Pointer](#).

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormL2GetBufferSize_64fc64f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.189.1.7 `NppStatus nppsNorm_L2Sqr_16s64s_Sfs (const Npp16s * pSrc, int nLength, Npp64s * pNorm, int nScaleFactor, Npp8u * pDeviceBuffer)`

16-bit signed short integer vector L2 Square norm method, return value is 64-bit signed integer.

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormL2SqrGetBufferSize_16s64s_Sfs](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.189.1.8 `NppStatus nppsNormL2GetBufferSize_16s32f (int nLength, int * hpBufferSize)`

Device-buffer size (in bytes) for nppsNorm_L2_16s32f.

Parameters:

nLength Signal Length.

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.189.1.9 `NppStatus nppsNormL2GetBufferSize_16s32s_Sfs (int nLength, int * hpBufferSize)`

Device-buffer size (in bytes) for nppsNorm_L2_16s32s_Sfs.

Parameters:

nLength Signal Length.

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.189.1.10 NppStatus nppsNormL2GetBufferSize_32f (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsNorm_L2_32f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.189.1.11 NppStatus nppsNormL2GetBufferSize_32fc64f (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsNorm_L2_32fc64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.189.1.12 NppStatus nppsNormL2GetBufferSize_64f (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsNorm_L2_64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.189.1.13 NppStatus nppsNormL2GetBufferSize_64fc64f (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsNorm_L2_64fc64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.189.1.14 `NppStatus nppsNormL2SqrGetBufferSize_16s64s_Sfs (int nLength, int * hpBufferSize)`

Device-buffer size (in bytes) for `nppsNorm_L2Sqr_16s64s_Sfs`.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: `hpBufferSize` is a *host pointer*.

Returns:

`NPP_SUCCESS`

7.190 Infinity Norm Diff

Functions

- [NppStatus nppsNormDiffInfGetBufferSize_32f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNormDiff_Inf_32f.
- [NppStatus nppsNormDiff_Inf_32f](#) (const [Npp32f](#) *pSrc1, const [Npp32f](#) *pSrc2, int nLength, [Npp32f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
32-bit float C norm method on two vectors' difference
- [NppStatus nppsNormDiffInfGetBufferSize_64f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNormDiff_Inf_64f.
- [NppStatus nppsNormDiff_Inf_64f](#) (const [Npp64f](#) *pSrc1, const [Npp64f](#) *pSrc2, int nLength, [Npp64f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
64-bit float C norm method on two vectors' difference
- [NppStatus nppsNormDiffInfGetBufferSize_16s32f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNormDiff_Inf_16s32f.
- [NppStatus nppsNormDiff_Inf_16s32f](#) (const [Npp16s](#) *pSrc1, const [Npp16s](#) *pSrc2, int nLength, [Npp32f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
16-bit signed short integer C norm method on two vectors' difference, return value is 32-bit float.
- [NppStatus nppsNormDiffInfGetBufferSize_32fc32f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNormDiff_Inf_32fc32f.
- [NppStatus nppsNormDiff_Inf_32fc32f](#) (const [Npp32fc](#) *pSrc1, const [Npp32fc](#) *pSrc2, int nLength, [Npp32f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
32-bit float complex C norm method on two vectors' difference, return value is 32-bit float.
- [NppStatus nppsNormDiffInfGetBufferSize_64fc64f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNormDiff_Inf_64fc64f.
- [NppStatus nppsNormDiff_Inf_64fc64f](#) (const [Npp64fc](#) *pSrc1, const [Npp64fc](#) *pSrc2, int nLength, [Npp64f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
64-bit float complex C norm method on two vectors' difference, return value is 64-bit float.
- [NppStatus nppsNormDiffInfGetBufferSize_16s32s_Sfs](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNormDiff_Inf_16s32s_Sfs.
- [NppStatus nppsNormDiff_Inf_16s32s_Sfs](#) (const [Npp16s](#) *pSrc1, const [Npp16s](#) *pSrc2, int nLength, [Npp32s](#) *pNorm, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)
16-bit signed short integer C norm method on two vectors' difference, return value is 32-bit signed integer.

7.190.1 Function Documentation

7.190.1.1 `NppStatus nppsNormDiff_Inf_16s32f` (`const Npp16s * pSrc1`, `const Npp16s * pSrc2`, `int nLength`, `Npp32f * pNorm`, `Npp8u * pDeviceBuffer`)

16-bit signed short integer C norm method on two vectors' difference, return value is 32-bit float.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormDiffInfGetBufferSize_16s32f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.190.1.2 `NppStatus nppsNormDiff_Inf_16s32s_Sfs` (`const Npp16s * pSrc1`, `const Npp16s * pSrc2`, `int nLength`, `Npp32s * pNorm`, `int nScaleFactor`, `Npp8u * pDeviceBuffer`)

16-bit signed short integer C norm method on two vectors' difference, return value is 32-bit signed integer.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormDiffInfGetBufferSize_16s32s_Sfs](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.190.1.3 `NppStatus nppsNormDiff_Inf_32f` (`const Npp32f * pSrc1`, `const Npp32f * pSrc2`, `int nLength`, `Npp32f * pNorm`, `Npp8u * pDeviceBuffer`)

32-bit float C norm method on two vectors' difference

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormDiffInfGetBufferSize_32f](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.190.1.4 NppStatus nppsNormDiff_Inf_32fc32f (const Npp32fc * pSrc1, const Npp32fc * pSrc2, int nLength, Npp32f * pNorm, Npp8u * pDeviceBuffer)

32-bit float complex C norm method on two vectors' difference, return value is 32-bit float.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormDiffInfGetBufferSize_32fc32f](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.190.1.5 NppStatus nppsNormDiff_Inf_64f (const Npp64f * pSrc1, const Npp64f * pSrc2, int nLength, Npp64f * pNorm, Npp8u * pDeviceBuffer)

64-bit float C norm method on two vectors' difference

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormDiffInfGetBufferSize_64f](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.190.1.6 `NppStatus nppsNormDiff_Inf_64fc64f (const Npp64fc * pSrc1, const Npp64fc * pSrc2, int nLength, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

64-bit float complex C norm method on two vectors' difference, return value is 64-bit float.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use `nppsNormDiffInfGetBufferSize_64fc64f` to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.190.1.7 `NppStatus nppsNormDiffInfGetBufferSize_16s32f (int nLength, int * hpBufferSize)`

Device-buffer size (in bytes) for `nppsNormDiff_Inf_16s32f`.

Parameters:

nLength Signal Length.

hpBufferSize Required buffer size. Important: `hpBufferSize` is a *host pointer*.

Returns:

NPP_SUCCESS

7.190.1.8 `NppStatus nppsNormDiffInfGetBufferSize_16s32s_Sfs (int nLength, int * hpBufferSize)`

Device-buffer size (in bytes) for `nppsNormDiff_Inf_16s32s_Sfs`.

Parameters:

nLength Signal Length.

hpBufferSize Required buffer size. Important: `hpBufferSize` is a *host pointer*.

Returns:

NPP_SUCCESS

7.190.1.9 `NppStatus nppsNormDiffInfGetBufferSize_32f (int nLength, int * hpBufferSize)`

Device-buffer size (in bytes) for `nppsNormDiff_Inf_32f`.

Parameters:

nLength Signal Length.

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.190.1.10 NppStatus nppsNormDiffInfGetBufferSize_32fc32f (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for `nppsNormDiff_Inf_32fc32f`.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.190.1.11 NppStatus nppsNormDiffInfGetBufferSize_64f (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for `nppsNormDiff_Inf_64f`.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.190.1.12 NppStatus nppsNormDiffInfGetBufferSize_64fc64f (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for `nppsNormDiff_Inf_64fc64f`.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.191 L1 Norm Diff

Functions

- [NppStatus nppsNormDiffL1GetBufferSize_32f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNormDiff_L1_32f.
- [NppStatus nppsNormDiff_L1_32f](#) (const [Npp32f](#) *pSrc1, const [Npp32f](#) *pSrc2, int nLength, [Npp32f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
32-bit float L1 norm method on two vectors' difference
- [NppStatus nppsNormDiffL1GetBufferSize_64f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNormDiff_L1_64f.
- [NppStatus nppsNormDiff_L1_64f](#) (const [Npp64f](#) *pSrc1, const [Npp64f](#) *pSrc2, int nLength, [Npp64f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
64-bit float L1 norm method on two vectors' difference
- [NppStatus nppsNormDiffL1GetBufferSize_16s32f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNormDiff_L1_16s32f.
- [NppStatus nppsNormDiff_L1_16s32f](#) (const [Npp16s](#) *pSrc1, const [Npp16s](#) *pSrc2, int nLength, [Npp32f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
16-bit signed short integer L1 norm method on two vectors' difference, return value is 32-bit float.
- [NppStatus nppsNormDiffL1GetBufferSize_32fc64f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNormDiff_L1_32fc64f.
- [NppStatus nppsNormDiff_L1_32fc64f](#) (const [Npp32fc](#) *pSrc1, const [Npp32fc](#) *pSrc2, int nLength, [Npp64f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
32-bit float complex L1 norm method on two vectors' difference, return value is 64-bit float.
- [NppStatus nppsNormDiffL1GetBufferSize_64fc64f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNormDiff_L1_64fc64f.
- [NppStatus nppsNormDiff_L1_64fc64f](#) (const [Npp64fc](#) *pSrc1, const [Npp64fc](#) *pSrc2, int nLength, [Npp64f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
64-bit float complex L1 norm method on two vectors' difference, return value is 64-bit float.
- [NppStatus nppsNormDiffL1GetBufferSize_16s32s_Sfs](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNormDiff_L1_16s32s_Sfs.
- [NppStatus nppsNormDiff_L1_16s32s_Sfs](#) (const [Npp16s](#) *pSrc1, const [Npp16s](#) *pSrc2, int nLength, [Npp32s](#) *pNorm, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)
16-bit signed short integer L1 norm method on two vectors' difference, return value is 32-bit signed integer.
- [NppStatus nppsNormDiffL1GetBufferSize_16s64s_Sfs](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNormDiff_L1_16s64s_Sfs.
- [NppStatus nppsNormDiff_L1_16s64s_Sfs](#) (const [Npp16s](#) *pSrc1, const [Npp16s](#) *pSrc2, int nLength, [Npp64s](#) *pNorm, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)

16-bit signed short integer L1 norm method on two vectors' difference, return value is 64-bit signed integer.

7.191.1 Function Documentation

7.191.1.1 `NppStatus nppsNormDiff_L1_16s32f (const Npp16s * pSrc1, const Npp16s * pSrc2, int nLength, Npp32f * pNorm, Npp8u * pDeviceBuffer)`

16-bit signed short integer L1 norm method on two vectors' difference, return value is 32-bit float.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the L1 norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormDiffL1GetBufferSize_16s32f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.191.1.2 `NppStatus nppsNormDiff_L1_16s32s_Sfs (const Npp16s * pSrc1, const Npp16s * pSrc2, int nLength, Npp32s * pNorm, int nScaleFactor, Npp8u * pDeviceBuffer)`

16-bit signed short integer L1 norm method on two vectors' difference, return value is 32-bit signed integer.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer..

nLength Signal Length.

pNorm Pointer to the norm result.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormDiffL1GetBufferSize_16s32s_Sfs](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.191.1.3 `NppStatus nppsNormDiff_L1_16s64s_Sfs (const Npp16s * pSrc1, const Npp16s * pSrc2, int nLength, Npp64s * pNorm, int nScaleFactor, Npp8u * pDeviceBuffer)`

16-bit signed short integer L1 norm method on two vectors' difference, return value is 64-bit signed integer.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormDiffL1GetBufferSize_16s64s_Sfs](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.191.1.4 NppStatus nppsNormDiff_L1_32f (const Npp32f * pSrc1, const Npp32f * pSrc2, int nLength, Npp32f * pNorm, Npp8u * pDeviceBuffer)

32-bit float L1 norm method on two vectors' difference

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormDiffL1GetBufferSize_32f](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.191.1.5 NppStatus nppsNormDiff_L1_32fc64f (const Npp32fc * pSrc1, const Npp32fc * pSrc2, int nLength, Npp64f * pNorm, Npp8u * pDeviceBuffer)

32-bit float complex L1 norm method on two vectors' difference, return value is 64-bit float.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormDiffL1GetBufferSize_32fc64f](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.191.1.6 `NppStatus nppsNormDiff_L1_64f (const Npp64f * pSrc1, const Npp64f * pSrc2, int nLength, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

64-bit float L1 norm method on two vectors' difference

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormDiffL1GetBufferSize_64f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.191.1.7 `NppStatus nppsNormDiff_L1_64fc64f (const Npp64fc * pSrc1, const Npp64fc * pSrc2, int nLength, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

64-bit float complex L1 norm method on two vectors' difference, return value is 64-bit float.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormDiffL1GetBufferSize_64fc64f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.191.1.8 `NppStatus nppsNormDiffL1GetBufferSize_16s32f (int nLength, int * hpBufferSize)`

Device-buffer size (in bytes) for `nppsNormDiff_L1_16s32f`.

Parameters:

nLength Signal Length.

hpBufferSize Required buffer size. Important: `hpBufferSize` is a *host pointer*.

Returns:

NPP_SUCCESS

7.191.1.9 NppStatus nppsNormDiffL1GetBufferSize_16s32s_Sfs (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsNormDiff_L1_16s32s_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.191.1.10 NppStatus nppsNormDiffL1GetBufferSize_16s64s_Sfs (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsNormDiff_L1_16s64s_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.191.1.11 NppStatus nppsNormDiffL1GetBufferSize_32f (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsNormDiff_L1_32f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.191.1.12 NppStatus nppsNormDiffL1GetBufferSize_32fc64f (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsNormDiff_L1_32fc64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.191.1.13 NppStatus nppsNormDiffL1GetBufferSize_64f (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsNormDiff_L1_64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.191.1.14 NppStatus nppsNormDiffL1GetBufferSize_64fc64f (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsNormDiff_L1_64fc64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.192 L2 Norm Diff

Functions

- [NppStatus nppsNormDiffL2GetBufferSize_32f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNormDiff_L2_32f.
- [NppStatus nppsNormDiff_L2_32f](#) (const [Npp32f](#) *pSrc1, const [Npp32f](#) *pSrc2, int nLength, [Npp32f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
32-bit float L2 norm method on two vectors' difference
- [NppStatus nppsNormDiffL2GetBufferSize_64f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNormDiff_L2_64f.
- [NppStatus nppsNormDiff_L2_64f](#) (const [Npp64f](#) *pSrc1, const [Npp64f](#) *pSrc2, int nLength, [Npp64f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
64-bit float L2 norm method on two vectors' difference
- [NppStatus nppsNormDiffL2GetBufferSize_16s32f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNormDiff_L2_16s32f.
- [NppStatus nppsNormDiff_L2_16s32f](#) (const [Npp16s](#) *pSrc1, const [Npp16s](#) *pSrc2, int nLength, [Npp32f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
16-bit signed short integer L2 norm method on two vectors' difference, return value is 32-bit float.
- [NppStatus nppsNormDiffL2GetBufferSize_32fc64f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNormDiff_L2_32fc64f.
- [NppStatus nppsNormDiff_L2_32fc64f](#) (const [Npp32fc](#) *pSrc1, const [Npp32fc](#) *pSrc2, int nLength, [Npp64f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
32-bit float complex L2 norm method on two vectors' difference, return value is 64-bit float.
- [NppStatus nppsNormDiffL2GetBufferSize_64fc64f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNormDiff_L2_64fc64f.
- [NppStatus nppsNormDiff_L2_64fc64f](#) (const [Npp64fc](#) *pSrc1, const [Npp64fc](#) *pSrc2, int nLength, [Npp64f](#) *pNorm, [Npp8u](#) *pDeviceBuffer)
64-bit float complex L2 norm method on two vectors' difference, return value is 64-bit float.
- [NppStatus nppsNormDiffL2GetBufferSize_16s32s_Sfs](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNormDiff_L2_16s32s_Sfs.
- [NppStatus nppsNormDiff_L2_16s32s_Sfs](#) (const [Npp16s](#) *pSrc1, const [Npp16s](#) *pSrc2, int nLength, [Npp32s](#) *pNorm, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)
16-bit signed short integer L2 norm method on two vectors' difference, return value is 32-bit signed integer.
- [NppStatus nppsNormDiffL2SqrGetBufferSize_16s64s_Sfs](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsNormDiff_L2Sqr_16s64s_Sfs.
- [NppStatus nppsNormDiff_L2Sqr_16s64s_Sfs](#) (const [Npp16s](#) *pSrc1, const [Npp16s](#) *pSrc2, int nLength, [Npp64s](#) *pNorm, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)

16-bit signed short integer L2 Square norm method on two vectors' difference, return value is 64-bit signed integer.

7.192.1 Function Documentation

7.192.1.1 `NppStatus nppsNormDiff_L2_16s32f (const Npp16s * pSrc1, const Npp16s * pSrc2, int nLength, Npp32f * pNorm, Npp8u * pDeviceBuffer)`

16-bit signed short integer L2 norm method on two vectors' difference, return value is 32-bit float.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormDiffL2GetBufferSize_16s32f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.192.1.2 `NppStatus nppsNormDiff_L2_16s32s_Sfs (const Npp16s * pSrc1, const Npp16s * pSrc2, int nLength, Npp32s * pNorm, int nScaleFactor, Npp8u * pDeviceBuffer)`

16-bit signed short integer L2 norm method on two vectors' difference, return value is 32-bit signed integer.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormDiffL2GetBufferSize_16s32s_Sfs](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.192.1.3 `NppStatus nppsNormDiff_L2_32f (const Npp32f * pSrc1, const Npp32f * pSrc2, int nLength, Npp32f * pNorm, Npp8u * pDeviceBuffer)`

32-bit float L2 norm method on two vectors' difference

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormDiffL2GetBufferSize_32f](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.192.1.4 NppStatus nppsNormDiff_L2_32fc64f (const Npp32fc * pSrc1, const Npp32fc * pSrc2, int nLength, Npp64f * pNorm, Npp8u * pDeviceBuffer)

32-bit float complex L2 norm method on two vectors' difference, return value is 64-bit float.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormDiffL2GetBufferSize_32fc64f](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.192.1.5 NppStatus nppsNormDiff_L2_64f (const Npp64f * pSrc1, const Npp64f * pSrc2, int nLength, Npp64f * pNorm, Npp8u * pDeviceBuffer)

64-bit float L2 norm method on two vectors' difference

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsNormDiffL2GetBufferSize_64f](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.192.1.6 `NppStatus nppsNormDiff_L2_64fc64f (const Npp64fc * pSrc1, const Npp64fc * pSrc2, int nLength, Npp64f * pNorm, Npp8u * pDeviceBuffer)`

64-bit float complex L2 norm method on two vectors' difference, return value is 64-bit float.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use `nppsNormDiffL2GetBufferSize_64fc64f` to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.192.1.7 `NppStatus nppsNormDiff_L2Sqr_16s64s_Sfs (const Npp16s * pSrc1, const Npp16s * pSrc2, int nLength, Npp64s * pNorm, int nScaleFactor, Npp8u * pDeviceBuffer)`

16-bit signed short integer L2 Square norm method on two vectors' difference, return value is 64-bit signed integer.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pNorm Pointer to the norm result.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use `nppsNormDiffL2SqrGetBufferSize_16s64s_Sfs` to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.192.1.8 `NppStatus nppsNormDiffL2GetBufferSize_16s32f (int nLength, int * hpBufferSize)`

Device-buffer size (in bytes) for `nppsNormDiff_L2_16s32f`.

Parameters:

nLength Signal Length.

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.192.1.9 NppStatus nppsNormDiffL2GetBufferSize_16s32s_Sfs (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsNormDiff_L2_16s32s_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.192.1.10 NppStatus nppsNormDiffL2GetBufferSize_32f (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsNormDiff_L2_32f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.192.1.11 NppStatus nppsNormDiffL2GetBufferSize_32fc64f (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsNormDiff_L2_32fc64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.192.1.12 NppStatus nppsNormDiffL2GetBufferSize_64f (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsNormDiff_L2_64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.192.1.13 NppStatus nppsNormDiffL2GetBufferSize_64fc64f (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsNormDiff_L2_64fc64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.192.1.14 NppStatus nppsNormDiffL2SqrGetBufferSize_16s64s_Sfs (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsNormDiff_L2Sqr_16s64s_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.193 Dot Product

Functions

- [NppStatus nppsDotProdGetBufferSize_32f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsDotProd_32f.
- [NppStatus nppsDotProd_32f](#) (const [Npp32f](#) *pSrc1, const [Npp32f](#) *pSrc2, int nLength, [Npp32f](#) *pDp, [Npp8u](#) *pDeviceBuffer)
32-bit float dot product method, return value is 32-bit float.
- [NppStatus nppsDotProdGetBufferSize_32fc](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsDotProd_32fc.
- [NppStatus nppsDotProd_32fc](#) (const [Npp32fc](#) *pSrc1, const [Npp32fc](#) *pSrc2, int nLength, [Npp32fc](#) *pDp, [Npp8u](#) *pDeviceBuffer)
32-bit float complex dot product method, return value is 32-bit float complex.
- [NppStatus nppsDotProdGetBufferSize_32f32fc](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsDotProd_32f32fc.
- [NppStatus nppsDotProd_32f32fc](#) (const [Npp32f](#) *pSrc1, const [Npp32fc](#) *pSrc2, int nLength, [Npp32fc](#) *pDp, [Npp8u](#) *pDeviceBuffer)
32-bit float and 32-bit float complex dot product method, return value is 32-bit float complex.
- [NppStatus nppsDotProdGetBufferSize_32f64f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsDotProd_32f64f.
- [NppStatus nppsDotProd_32f64f](#) (const [Npp32f](#) *pSrc1, const [Npp32f](#) *pSrc2, int nLength, [Npp64f](#) *pDp, [Npp8u](#) *pDeviceBuffer)
32-bit float dot product method, return value is 64-bit float.
- [NppStatus nppsDotProdGetBufferSize_32fc64fc](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsDotProd_32fc64fc.
- [NppStatus nppsDotProd_32fc64fc](#) (const [Npp32fc](#) *pSrc1, const [Npp32fc](#) *pSrc2, int nLength, [Npp64fc](#) *pDp, [Npp8u](#) *pDeviceBuffer)
32-bit float complex dot product method, return value is 64-bit float complex.
- [NppStatus nppsDotProdGetBufferSize_32f32fc64fc](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsDotProd_32f32fc64fc.
- [NppStatus nppsDotProd_32f32fc64fc](#) (const [Npp32f](#) *pSrc1, const [Npp32fc](#) *pSrc2, int nLength, [Npp64fc](#) *pDp, [Npp8u](#) *pDeviceBuffer)
32-bit float and 32-bit float complex dot product method, return value is 64-bit float complex.
- [NppStatus nppsDotProdGetBufferSize_64f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsDotProd_64f.
- [NppStatus nppsDotProd_64f](#) (const [Npp64f](#) *pSrc1, const [Npp64f](#) *pSrc2, int nLength, [Npp64f](#) *pDp, [Npp8u](#) *pDeviceBuffer)

64-bit float dot product method, return value is 64-bit float.

- **NppStatus nppsDotProdGetBufferSize_64fc** (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsDotProd_64fc.
- **NppStatus nppsDotProd_64fc** (const **Npp64fc** *pSrc1, const **Npp64fc** *pSrc2, int nLength, **Npp64fc** *pDp, **Npp8u** *pDeviceBuffer)
64-bit float complex dot product method, return value is 64-bit float complex.
- **NppStatus nppsDotProdGetBufferSize_64f64fc** (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsDotProd_64f64fc.
- **NppStatus nppsDotProd_64f64fc** (const **Npp64f** *pSrc1, const **Npp64fc** *pSrc2, int nLength, **Npp64fc** *pDp, **Npp8u** *pDeviceBuffer)
64-bit float and 64-bit float complex dot product method, return value is 64-bit float complex.
- **NppStatus nppsDotProdGetBufferSize_16s64s** (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsDotProd_16s64s.
- **NppStatus nppsDotProd_16s64s** (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, int nLength, **Npp64s** *pDp, **Npp8u** *pDeviceBuffer)
16-bit signed short integer dot product method, return value is 64-bit signed integer.
- **NppStatus nppsDotProdGetBufferSize_16sc64sc** (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsDotProd_16sc64sc.
- **NppStatus nppsDotProd_16sc64sc** (const **Npp16sc** *pSrc1, const **Npp16sc** *pSrc2, int nLength, **Npp64sc** *pDp, **Npp8u** *pDeviceBuffer)
16-bit signed short integer complex dot product method, return value is 64-bit signed integer complex.
- **NppStatus nppsDotProdGetBufferSize_16s16sc64sc** (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsDotProd_16s16sc64sc.
- **NppStatus nppsDotProd_16s16sc64sc** (const **Npp16s** *pSrc1, const **Npp16sc** *pSrc2, int nLength, **Npp64sc** *pDp, **Npp8u** *pDeviceBuffer)
16-bit signed short integer and 16-bit signed short integer short dot product method, return value is 64-bit signed integer complex.
- **NppStatus nppsDotProdGetBufferSize_16s32f** (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsDotProd_16s32f.
- **NppStatus nppsDotProd_16s32f** (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, int nLength, **Npp32f** *pDp, **Npp8u** *pDeviceBuffer)
16-bit signed short integer dot product method, return value is 32-bit float.
- **NppStatus nppsDotProdGetBufferSize_16sc32fc** (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsDotProd_16sc32fc.
- **NppStatus nppsDotProd_16sc32fc** (const **Npp16sc** *pSrc1, const **Npp16sc** *pSrc2, int nLength, **Npp32fc** *pDp, **Npp8u** *pDeviceBuffer)
16-bit signed short integer complex dot product method, return value is 32-bit float complex.

- [NppStatus nppsDotProdGetBufferSize_16s16sc32fc](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsDotProd_16s16sc32fc.
- [NppStatus nppsDotProd_16s16sc32fc](#) (const [Npp16s](#) *pSrc1, const [Npp16sc](#) *pSrc2, int nLength, [Npp32fc](#) *pDp, [Npp8u](#) *pDeviceBuffer)
16-bit signed short integer and 16-bit signed short integer complex dot product method, return value is 32-bit float complex.
- [NppStatus nppsDotProdGetBufferSize_16s_Sfs](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsDotProd_16s_Sfs.
- [NppStatus nppsDotProd_16s_Sfs](#) (const [Npp16s](#) *pSrc1, const [Npp16s](#) *pSrc2, int nLength, [Npp16s](#) *pDp, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)
16-bit signed short integer dot product method, return value is 16-bit signed short integer.
- [NppStatus nppsDotProdGetBufferSize_16sc_Sfs](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsDotProd_16sc_Sfs.
- [NppStatus nppsDotProd_16sc_Sfs](#) (const [Npp16sc](#) *pSrc1, const [Npp16sc](#) *pSrc2, int nLength, [Npp16sc](#) *pDp, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)
16-bit signed short integer complex dot product method, return value is 16-bit signed short integer complex.
- [NppStatus nppsDotProdGetBufferSize_32s_Sfs](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsDotProd_32s_Sfs.
- [NppStatus nppsDotProd_32s_Sfs](#) (const [Npp32s](#) *pSrc1, const [Npp32s](#) *pSrc2, int nLength, [Npp32s](#) *pDp, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)
32-bit signed integer dot product method, return value is 32-bit signed integer.
- [NppStatus nppsDotProdGetBufferSize_32sc_Sfs](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsDotProd_32sc_Sfs.
- [NppStatus nppsDotProd_32sc_Sfs](#) (const [Npp32sc](#) *pSrc1, const [Npp32sc](#) *pSrc2, int nLength, [Npp32sc](#) *pDp, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)
32-bit signed integer complex dot product method, return value is 32-bit signed integer complex.
- [NppStatus nppsDotProdGetBufferSize_16s32s_Sfs](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsDotProd_16s32s_Sfs.
- [NppStatus nppsDotProd_16s32s_Sfs](#) (const [Npp16s](#) *pSrc1, const [Npp16s](#) *pSrc2, int nLength, [Npp32s](#) *pDp, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)
16-bit signed short integer dot product method, return value is 32-bit signed integer.
- [NppStatus nppsDotProdGetBufferSize_16s16sc32sc_Sfs](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsDotProd_16s16sc32sc_Sfs.
- [NppStatus nppsDotProd_16s16sc32sc_Sfs](#) (const [Npp16s](#) *pSrc1, const [Npp16sc](#) *pSrc2, int nLength, [Npp32sc](#) *pDp, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)
16-bit signed short integer and 16-bit signed short integer complex dot product method, return value is 32-bit signed integer complex.

- [NppStatus nppsDotProdGetBufferSize_16s32s32s_Sfs](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsDotProd_16s32s32s_Sfs.
- [NppStatus nppsDotProd_16s32s32s_Sfs](#) (const [Npp16s](#) *pSrc1, const [Npp32s](#) *pSrc2, int nLength, [Npp32s](#) *pDp, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)
16-bit signed short integer and 32-bit signed integer dot product method, return value is 32-bit signed integer.
- [NppStatus nppsDotProdGetBufferSize_16s16sc_Sfs](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsDotProd_16s16sc_Sfs.
- [NppStatus nppsDotProd_16s16sc_Sfs](#) (const [Npp16s](#) *pSrc1, const [Npp16sc](#) *pSrc2, int nLength, [Npp16sc](#) *pDp, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)
16-bit signed short integer and 16-bit signed short integer complex dot product method, return value is 16-bit signed short integer complex.
- [NppStatus nppsDotProdGetBufferSize_16sc32sc_Sfs](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsDotProd_16sc32sc_Sfs.
- [NppStatus nppsDotProd_16sc32sc_Sfs](#) (const [Npp16sc](#) *pSrc1, const [Npp16sc](#) *pSrc2, int nLength, [Npp32sc](#) *pDp, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)
16-bit signed short integer complex dot product method, return value is 32-bit signed integer complex.
- [NppStatus nppsDotProdGetBufferSize_32s32sc_Sfs](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsDotProd_32s32sc_Sfs.
- [NppStatus nppsDotProd_32s32sc_Sfs](#) (const [Npp32s](#) *pSrc1, const [Npp32sc](#) *pSrc2, int nLength, [Npp32sc](#) *pDp, int nScaleFactor, [Npp8u](#) *pDeviceBuffer)
32-bit signed short integer and 32-bit signed short integer complex dot product method, return value is 32-bit signed integer complex.

7.193.1 Function Documentation

7.193.1.1 [NppStatus nppsDotProd_16s16sc32fc](#) (const [Npp16s](#) *pSrc1, const [Npp16sc](#) *pSrc2, int nLength, [Npp32fc](#) *pDp, [Npp8u](#) *pDeviceBuffer)

16-bit signed short integer and 16-bit signed short integer complex dot product method, return value is 32-bit float complex.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#).

nLength [Signal Length](#).

pDp [Pointer to the dot product result](#).

pDeviceBuffer [Pointer to the required device memory allocation, \[Scratch Buffer and Host Pointer\]\(#\)](#).
Use [nppsDotProdGetBufferSize_16s16sc32fc](#) to determine the minimum number of bytes required.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.193.1.2 NppStatus nppsDotProd_16s16sc32sc_Sfs (const Npp16s * pSrc1, const Npp16sc * pSrc2, int nLength, Npp32sc * pDp, int nScaleFactor, Npp8u * pDeviceBuffer)

16-bit signed short integer and 16-bit signed short integer complex dot product method, return value is 32-bit signed integer complex.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pDp Pointer to the dot product result.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#). Use [nppsDotProdGetBufferSize_16s16sc32sc_Sfs](#) to determine the minium number of bytes required.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.193.1.3 NppStatus nppsDotProd_16s16sc64sc (const Npp16s * pSrc1, const Npp16sc * pSrc2, int nLength, Npp64sc * pDp, Npp8u * pDeviceBuffer)

16-bit signed short integer and 16-bit signed short integer short dot product method, return value is 64-bit signed integer complex.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pDp Pointer to the dot product result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#). Use [nppsDotProdGetBufferSize_16s16sc64sc](#) to determine the minium number of bytes required.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.193.1.4 NppStatus nppsDotProd_16s16sc_Sfs (const Npp16s * pSrc1, const Npp16sc * pSrc2, int nLength, Npp16sc * pDp, int nScaleFactor, Npp8u * pDeviceBuffer)

16-bit signed short integer and 16-bit signed short integer complex dot product method, return value is 16-bit signed short integer complex.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pDp Pointer to the dot product result.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsDotProdGetBufferSize_16s16sc_Sfs](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.193.1.5 NppStatus nppsDotProd_16s32f (const Npp16s * pSrc1, const Npp16s * pSrc2, int nLength, Npp32f * pDp, Npp8u * pDeviceBuffer)

16-bit signed short integer dot product method, return value is 32-bit float.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pDp Pointer to the dot product result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsDotProdGetBufferSize_16s32f](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.193.1.6 NppStatus nppsDotProd_16s32s32s_Sfs (const Npp16s * pSrc1, const Npp32s * pSrc2, int nLength, Npp32s * pDp, int nScaleFactor, Npp8u * pDeviceBuffer)

16-bit signed short integer and 32-bit signed integer dot product method, return value is 32-bit signed integer.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pDp Pointer to the dot product result.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsDotProdGetBufferSize_16s32s32s_Sfs](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.193.1.7 `NppStatus nppsDotProd_16s32s_Sfs (const Npp16s * pSrc1, const Npp16s * pSrc2, int nLength, Npp32s * pDp, int nScaleFactor, Npp8u * pDeviceBuffer)`

16-bit signed short integer dot product method, return value is 32-bit signed integer.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pDp Pointer to the dot product result.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsDotProdGetBufferSize_16s32s_Sfs](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.193.1.8 `NppStatus nppsDotProd_16s64s (const Npp16s * pSrc1, const Npp16s * pSrc2, int nLength, Npp64s * pDp, Npp8u * pDeviceBuffer)`

16-bit signed short integer dot product method, return value is 64-bit signed integer.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pDp Pointer to the dot product result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsDotProdGetBufferSize_16s64s](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.193.1.9 NppStatus nppsDotProd_16s_Sfs (const Npp16s * pSrc1, const Npp16s * pSrc2, int nLength, Npp16s * pDp, int nScaleFactor, Npp8u * pDeviceBuffer)

16-bit signed short integer dot product method, return value is 16-bit signed short integer.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pDp Pointer to the dot product result.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsDotProdGetBufferSize_16s_Sfs](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.193.1.10 NppStatus nppsDotProd_16sc32fc (const Npp16sc * pSrc1, const Npp16sc * pSrc2, int nLength, Npp32fc * pDp, Npp8u * pDeviceBuffer)

16-bit signed short integer complex dot product method, return value is 32-bit float complex.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pDp Pointer to the dot product result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsDotProdGetBufferSize_16sc32fc](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.193.1.11 NppStatus nppsDotProd_16sc32sc_Sfs (const Npp16sc * pSrc1, const Npp16sc * pSrc2, int nLength, Npp32sc * pDp, int nScaleFactor, Npp8u * pDeviceBuffer)

16-bit signed short integer complex dot product method, return value is 32-bit signed integer complex.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pDp Pointer to the dot product result.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsDotProdGetBufferSize_16sc32sc_Sfs](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.193.1.12 **NppStatus nppsDotProd_16sc64sc (const Npp16sc * pSrc1, const Npp16sc * pSrc2, int nLength, Npp64sc * pDp, Npp8u * pDeviceBuffer)**

16-bit signed short integer complex dot product method, return value is 64-bit signed integer complex.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pDp Pointer to the dot product result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsDotProdGetBufferSize_16sc64sc](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.193.1.13 **NppStatus nppsDotProd_16sc_Sfs (const Npp16sc * pSrc1, const Npp16sc * pSrc2, int nLength, Npp16sc * pDp, int nScaleFactor, Npp8u * pDeviceBuffer)**

16-bit signed short integer complex dot product method, return value is 16-bit signed short integer complex.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pDp Pointer to the dot product result.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsDotProdGetBufferSize_16sc_Sfs](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.193.1.14 NppStatus nppsDotProd_32f (const Npp32f * pSrc1, const Npp32f * pSrc2, int nLength, Npp32f * pDp, Npp8u * pDeviceBuffer)

32-bit float dot product method, return value is 32-bit float.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pDp Pointer to the dot product result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsDotProdGetBufferSize_32f](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.193.1.15 NppStatus nppsDotProd_32f32fc (const Npp32f * pSrc1, const Npp32fc * pSrc2, int nLength, Npp32fc * pDp, Npp8u * pDeviceBuffer)

32-bit float and 32-bit float complex dot product method, return value is 32-bit float complex.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pDp Pointer to the dot product result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsDotProdGetBufferSize_32f32fc](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.193.1.16 NppStatus nppsDotProd_32f32fc64fc (const Npp32f * pSrc1, const Npp32fc * pSrc2, int nLength, Npp64fc * pDp, Npp8u * pDeviceBuffer)

32-bit float and 32-bit float complex dot product method, return value is 64-bit float complex.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pDp Pointer to the dot product result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsDotProdGetBufferSize_32f32fc64fc](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.193.1.17 NppStatus nppsDotProd_32f64f (const Npp32f * pSrc1, const Npp32f * pSrc2, int nLength, Npp64f * pDp, Npp8u * pDeviceBuffer)

32-bit float dot product method, return value is 64-bit float.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pDp Pointer to the dot product result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsDotProdGetBufferSize_32f64f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.193.1.18 NppStatus nppsDotProd_32fc (const Npp32fc * pSrc1, const Npp32fc * pSrc2, int nLength, Npp32fc * pDp, Npp8u * pDeviceBuffer)

32-bit float complex dot product method, return value is 32-bit float complex.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pDp Pointer to the dot product result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsDotProdGetBufferSize_32fc](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.193.1.19 NppStatus nppsDotProd_32fc64fc (const Npp32fc * pSrc1, const Npp32fc * pSrc2, int nLength, Npp64fc * pDp, Npp8u * pDeviceBuffer)

32-bit float complex dot product method, return value is 64-bit float complex.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pDp Pointer to the dot product result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsDotProdGetBufferSize_32fc64fc](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.193.1.20 NppStatus nppsDotProd_32s32sc_Sfs (const Npp32s * pSrc1, const Npp32sc * pSrc2, int nLength, Npp32sc * pDp, int nScaleFactor, Npp8u * pDeviceBuffer)

32-bit signed short integer and 32-bit signed short integer complex dot product method, return value is 32-bit signed integer complex.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pDp Pointer to the dot product result.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsDotProdGetBufferSize_32s32sc_Sfs](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.193.1.21 NppStatus nppsDotProd_32s_Sfs (const Npp32s * pSrc1, const Npp32s * pSrc2, int nLength, Npp32s * pDp, int nScaleFactor, Npp8u * pDeviceBuffer)

32-bit signed integer dot product method, return value is 32-bit signed integer.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pDp Pointer to the dot product result.

nScaleFactor Integer Result Scaling.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsDotProdGetBufferSize_32s_Sfs](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.193.1.22 NppStatus nppsDotProd_32sc_Sfs (const Npp32sc * pSrc1, const Npp32sc * pSrc2, int nLength, Npp32sc * pDp, int nScaleFactor, Npp8u * pDeviceBuffer)

32-bit signed integer complex dot product method, return value is 32-bit signed integer complex.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength [Signal Length](#).

pDp Pointer to the dot product result.

nScaleFactor [Integer Result Scaling](#).

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsDotProdGetBufferSize_32sc_Sfs](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.193.1.23 NppStatus nppsDotProd_64f (const Npp64f * pSrc1, const Npp64f * pSrc2, int nLength, Npp64f * pDp, Npp8u * pDeviceBuffer)

64-bit float dot product method, return value is 64-bit float.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#).

nLength [Signal Length](#).

pDp Pointer to the dot product result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsDotProdGetBufferSize_64f](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.193.1.24 NppStatus nppsDotProd_64f64fc (const Npp64f * pSrc1, const Npp64fc * pSrc2, int nLength, Npp64fc * pDp, Npp8u * pDeviceBuffer)

64-bit float and 64-bit float complex dot product method, return value is 64-bit float complex.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#).

nLength [Signal Length](#).

pDp Pointer to the dot product result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsDotProdGetBufferSize_64f64fc](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.193.1.25 NppStatus nppsDotProd_64fc (const Npp64fc * pSrc1, const Npp64fc * pSrc2, int nLength, Npp64fc * pDp, Npp8u * pDeviceBuffer)

64-bit float complex dot product method, return value is 64-bit float complex.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

nLength Signal Length.

pDp Pointer to the dot product result.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsDotProdGetBufferSize_64fc](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.193.1.26 NppStatus nppsDotProdGetBufferSize_16s16sc32fc (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsDotProd_16s16sc32fc.

Parameters:

nLength Signal Length.

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.193.1.27 NppStatus nppsDotProdGetBufferSize_16s16sc32sc_Sfs (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsDotProd_16s16sc32sc_Sfs.

Parameters:

nLength Signal Length.

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.193.1.28 NppStatus nppsDotProdGetBufferSize_16s16sc64sc (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsDotProd_16s16sc64sc.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.193.1.29 NppStatus nppsDotProdGetBufferSize_16s16sc_Sfs (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for *nppsDotProd_16s16sc_Sfs*.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.193.1.30 NppStatus nppsDotProdGetBufferSize_16s32f (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for *nppsDotProd_16s32f*.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.193.1.31 NppStatus nppsDotProdGetBufferSize_16s32s32s_Sfs (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for *nppsDotProd_16s32s32s_Sfs*.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.193.1.32 NppStatus nppsDotProdGetBufferSize_16s32s_Sfs (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsDotProd_16s32s_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.193.1.33 NppStatus nppsDotProdGetBufferSize_16s64s (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsDotProd_16s64s.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.193.1.34 NppStatus nppsDotProdGetBufferSize_16s_Sfs (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsDotProd_16s_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.193.1.35 NppStatus nppsDotProdGetBufferSize_16sc32fc (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsDotProd_16sc32fc.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.193.1.36 NppStatus nppsDotProdGetBufferSize_16sc32sc_Sfs (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsDotProd_16sc32sc_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.193.1.37 NppStatus nppsDotProdGetBufferSize_16sc64sc (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsDotProd_16sc64sc.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.193.1.38 NppStatus nppsDotProdGetBufferSize_16sc_Sfs (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsDotProd_16sc_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.193.1.39 NppStatus nppsDotProdGetBufferSize_32f (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsDotProd_32f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.193.1.40 NppStatus nppsDotProdGetBufferSize_32f32fc (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsDotProd_32f32fc.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.193.1.41 NppStatus nppsDotProdGetBufferSize_32f32fc64fc (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsDotProd_32f32fc64fc.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.193.1.42 NppStatus nppsDotProdGetBufferSize_32f64f (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsDotProd_32f64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.193.1.43 NppStatus nppsDotProdGetBufferSize_32fc (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsDotProd_32fc.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.193.1.44 NppStatus nppsDotProdGetBufferSize_32fc64fc (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsDotProd_32fc64fc.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.193.1.45 NppStatus nppsDotProdGetBufferSize_32s32sc_Sfs (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsDotProd_32s32sc_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.193.1.46 NppStatus nppsDotProdGetBufferSize_32s_Sfs (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsDotProd_32s_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.193.1.47 NppStatus nppsDotProdGetBufferSize_32sc_Sfs (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsDotProd_32sc_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.193.1.48 NppStatus nppsDotProdGetBufferSize_64f (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsDotProd_64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.193.1.49 NppStatus nppsDotProdGetBufferSize_64f64fc (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsDotProd_64f64fc.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.193.1.50 NppStatus nppsDotProdGetBufferSize_64fc (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsDotProd_64fc.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.194 Count In Range

Functions

- [NppStatus nppsCountInRangeGetBufferSize_32s](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsCountInRange_32s.
- [NppStatus nppsCountInRange_32s](#) (const [Npp32s](#) *pSrc, int nLength, int *pCounts, [Npp32s](#) nLowerBound, [Npp32s](#) nUpperBound, [Npp8u](#) *pDeviceBuffer)
Computes the number of elements whose values fall into the specified range on a 32-bit signed integer array.

7.194.1 Function Documentation

7.194.1.1 [NppStatus nppsCountInRange_32s](#) (const [Npp32s](#) *pSrc, int nLength, int *pCounts, [Npp32s](#) nLowerBound, [Npp32s](#) nUpperBound, [Npp8u](#) *pDeviceBuffer)

Computes the number of elements whose values fall into the specified range on a 32-bit signed integer array.

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pCounts Pointer to the number of elements.

nLowerBound Lower bound of the specified range.

nUpperBound Upper bound of the specified range.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).
Use [nppsCountInRangeGetBufferSize_32s](#) to determine the minimum number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.194.1.2 [NppStatus nppsCountInRangeGetBufferSize_32s](#) (int nLength, int *hpBufferSize)

Device-buffer size (in bytes) for nppsCountInRange_32s.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.195 Count Zero Crossings

Functions

- [NppStatus nppsZeroCrossingGetBufferSize_16s32f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsZeroCrossing_16s32f.
- [NppStatus nppsZeroCrossing_16s32f](#) (const [Npp16s](#) *pSrc, int nLength, [Npp32f](#) *pValZC, [NppsZCType](#) tZCType, [Npp8u](#) *pDeviceBuffer)
16-bit signed short integer zero crossing method, return value is 32-bit floating point.
- [NppStatus nppsZeroCrossingGetBufferSize_32f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsZeroCrossing_32f.
- [NppStatus nppsZeroCrossing_32f](#) (const [Npp32f](#) *pSrc, int nLength, [Npp32f](#) *pValZC, [NppsZCType](#) tZCType, [Npp8u](#) *pDeviceBuffer)
32-bit floating-point zero crossing method, return value is 32-bit floating point.

7.195.1 Function Documentation

7.195.1.1 [NppStatus nppsZeroCrossing_16s32f](#) (const [Npp16s](#) *pSrc, int nLength, [Npp32f](#) *pValZC, [NppsZCType](#) tZCType, [Npp8u](#) *pDeviceBuffer)

16-bit signed short integer zero crossing method, return value is 32-bit floating point.

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pValZC [Pointer to the output result](#).

tZCType [Type of the zero crossing measure: nppZCR, nppZCXor or nppZCC](#).

pDeviceBuffer [Pointer to the required device memory allocation, Scratch Buffer and Host Pointer](#).
Use [nppsZeroCrossingGetBufferSize_16s32f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.195.1.2 [NppStatus nppsZeroCrossing_32f](#) (const [Npp32f](#) *pSrc, int nLength, [Npp32f](#) *pValZC, [NppsZCType](#) tZCType, [Npp8u](#) *pDeviceBuffer)

32-bit floating-point zero crossing method, return value is 32-bit floating point.

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pValZC [Pointer to the output result](#).

tZCType Type of the zero crossing measure: nppZCR, nppZCXor or nppZCC.

pDeviceBuffer Pointer to the required device memory allocation, [Scratch Buffer and Host Pointer](#).

Use [nppsZeroCrossingGetBufferSize_32f](#) to determine the minium number of bytes required.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.195.1.3 NppStatus nppsZeroCrossingGetBufferSize_16s32f (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsZeroCrossing_16s32f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.195.1.4 NppStatus nppsZeroCrossingGetBufferSize_32f (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsZeroCrossing_32f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.196 Memory Management

Modules

- [Malloc](#)

Signal-allocator methods for allocating 1D arrays of data in device memory.

- [Free](#)

Free signal memory.

7.197 Malloc

Signal-allocator methods for allocating 1D arrays of data in device memory.

Functions

- [Npp8u * nppsMalloc_8u](#) (int nSize)
8-bit unsigned signal allocator.
- [Npp8s * nppsMalloc_8s](#) (int nSize)
8-bit signed signal allocator.
- [Npp16u * nppsMalloc_16u](#) (int nSize)
16-bit unsigned signal allocator.
- [Npp16s * nppsMalloc_16s](#) (int nSize)
16-bit signal allocator.
- [Npp16sc * nppsMalloc_16sc](#) (int nSize)
16-bit complex-value signal allocator.
- [Npp32u * nppsMalloc_32u](#) (int nSize)
32-bit unsigned signal allocator.
- [Npp32s * nppsMalloc_32s](#) (int nSize)
32-bit integer signal allocator.
- [Npp32sc * nppsMalloc_32sc](#) (int nSize)
32-bit complex integer signal allocator.
- [Npp32f * nppsMalloc_32f](#) (int nSize)
32-bit float signal allocator.
- [Npp32fc * nppsMalloc_32fc](#) (int nSize)
32-bit complex float signal allocator.
- [Npp64s * nppsMalloc_64s](#) (int nSize)
64-bit long integer signal allocator.
- [Npp64sc * nppsMalloc_64sc](#) (int nSize)
64-bit complex long integer signal allocator.
- [Npp64f * nppsMalloc_64f](#) (int nSize)
64-bit float (double) signal allocator.
- [Npp64fc * nppsMalloc_64fc](#) (int nSize)
64-bit complex complex signal allocator.

7.197.1 Detailed Description

Signal-allocator methods for allocating 1D arrays of data in device memory.

All allocators have size parameters to specify the size of the signal (1D array) being allocated.

The allocator methods return a pointer to the newly allocated memory of appropriate type. If device-memory allocation is not possible due to resource constraints the allocators return 0 (i.e. NULL pointer).

All signal allocators allocate memory aligned such that it is beneficial to the performance of the majority of the signal-processing primitives. It is no mandatory however to use these allocators. Any valid CUDA device-memory pointers can be passed to NPP primitives.

7.197.2 Function Documentation

7.197.2.1 Npp16s* nppsMalloc_16s (int nSize)

16-bit signal allocator.

Parameters:

nSize Number of shorts in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.197.2.2 Npp16sc* nppsMalloc_16sc (int nSize)

16-bit complex-value signal allocator.

Parameters:

nSize Number of 16-bit complex numbers in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.197.2.3 Npp16u* nppsMalloc_16u (int nSize)

16-bit unsigned signal allocator.

Parameters:

nSize Number of unsigned shorts in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.197.2.4 Npp32f* nppsMalloc_32f (int nSize)

32-bit float signal allocator.

Parameters:

nSize Number of floats in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.197.2.5 Npp32fc* nppsMalloc_32fc (int nSize)

32-bit complex float signal allocator.

Parameters:

nSize Number of complex float values in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.197.2.6 Npp32s* nppsMalloc_32s (int nSize)

32-bit integer signal allocator.

Parameters:

nSize Number of ints in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.197.2.7 Npp32sc* nppsMalloc_32sc (int nSize)

32-bit complex integer signal allocator.

Parameters:

nSize Number of complex integner values in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.197.2.8 Npp32u* nppsMalloc_32u (int nSize)

32-bit unsigned signal allocator.

Parameters:

nSize Number of unsigned ints in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.197.2.9 Npp64f* nppsMalloc_64f (int nSize)

64-bit float (double) signal allocator.

Parameters:

nSize Number of doubles in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.197.2.10 Npp64fc* nppsMalloc_64fc (int nSize)

64-bit complex complex signal allocator.

Parameters:

nSize Number of complex double values in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.197.2.11 Npp64s* nppsMalloc_64s (int nSize)

64-bit long integer signal allocator.

Parameters:

nSize Number of long ints in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.197.2.12 Npp64sc* nppsMalloc_64sc (int nSize)

64-bit complex long integer signal allocator.

Parameters:

nSize Number of complex long int values in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.197.2.13 Npp8s* nppsMalloc_8s (int nSize)

8-bit signed signal allocator.

Parameters:

nSize Number of (signed) chars in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.197.2.14 Npp8u* nppsMalloc_8u (int nSize)

8-bit unsigned signal allocator.

Parameters:

nSize Number of unsigned chars in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.198 Free

Free signal memory.

Functions

- void `nppsFree` (void **pValues*)
Free method for any signal memory.

7.198.1 Detailed Description

Free signal memory.

7.198.2 Function Documentation

7.198.2.1 void `nppsFree` (void * *pValues*)

Free method for any signal memory.

Parameters:

pValues A pointer to memory allocated using `nppiMalloc_<modifier>`.

Chapter 8

Data Structure Documentation

8.1 NPP_ALIGN_16 Struct Reference

Complex Number This struct represents a long long complex number.

```
#include <nppdefs.h>
```

Data Fields

- [Npp64s re](#)
Real part.
- [Npp64s im](#)
Imaginary part.
- [Npp64f re](#)
Real part.
- [Npp64f im](#)
Imaginary part.

8.1.1 Detailed Description

Complex Number This struct represents a long long complex number.

Complex Number This struct represents a double floating-point complex number.

8.1.2 Field Documentation

8.1.2.1 Npp64f NPP_ALIGN_16::im

Imaginary part.

8.1.2.2 Npp64s NPP_ALIGN_16::im

Imaginary part.

8.1.2.3 Npp64f NPP_ALIGN_16::re

Real part.

8.1.2.4 Npp64s NPP_ALIGN_16::re

Real part.

The documentation for this struct was generated from the following file:

- C:/Perforce/sw/rel/gpgpu/toolkit/r5.5/NPP/npp/include/nppdefs.h

8.2 NPP_ALIGN_8 Struct Reference

Complex Number This struct represents an unsigned int complex number.

```
#include <nppdefs.h>
```

Data Fields

- [Npp32u re](#)
Real part.
- [Npp32u im](#)
Imaginary part.
- [Npp32s re](#)
Real part.
- [Npp32s im](#)
Imaginary part.
- [Npp32f re](#)
Real part.
- [Npp32f im](#)
Imaginary part.

8.2.1 Detailed Description

Complex Number This struct represents an unsigned int complex number.

Complex Number This struct represents a single floating-point complex number.

Complex Number This struct represents a signed int complex number.

8.2.2 Field Documentation

8.2.2.1 Npp32f NPP_ALIGN_8::im

Imaginary part.

8.2.2.2 Npp32s NPP_ALIGN_8::im

Imaginary part.

8.2.2.3 Npp32u NPP_ALIGN_8::im

Imaginary part.

8.2.2.4 Npp32f NPP_ALIGN_8::re

Real part.

8.2.2.5 Npp32s NPP_ALIGN_8::re

Real part.

8.2.2.6 Npp32u NPP_ALIGN_8::re

Real part.

The documentation for this struct was generated from the following file:

- C:/Perforce/sw/rel/gpgpu/toolkit/r5.5/NPP/npp/include/nppdefs.h

8.3 NppiHaarBuffer Struct Reference

```
#include <nppdefs.h>
```

Data Fields

- int `haarBufferSize`
size of the buffer
- `Npp32s * haarBuffer`
buffer

8.3.1 Field Documentation

8.3.1.1 `Npp32s* NppiHaarBuffer::haarBuffer`

`buffer`

8.3.1.2 `int NppiHaarBuffer::haarBufferSize`

size of the buffer

The documentation for this struct was generated from the following file:

- `C:/Perforce/sw/rel/gpgpu/toolkit/r5.5/NPP/npp/include/nppdefs.h`

8.4 NppiHaarClassifier_32f Struct Reference

```
#include <nppdefs.h>
```

Data Fields

- int `numClassifiers`
number of classifiers
- `Npp32s * classifiers`
packed classifier data 40 bytes each
- `size_t classifierStep`
- `NppiSize classifierSize`
- `Npp32s * counterDevice`

8.4.1 Field Documentation

8.4.1.1 `Npp32s* NppiHaarClassifier_32f::classifiers`

packed classifier data 40 bytes each

8.4.1.2 `NppiSize NppiHaarClassifier_32f::classifierSize`

8.4.1.3 `size_t NppiHaarClassifier_32f::classifierStep`

8.4.1.4 `Npp32s* NppiHaarClassifier_32f::counterDevice`

8.4.1.5 `int NppiHaarClassifier_32f::numClassifiers`

number of classifiers

The documentation for this struct was generated from the following file:

- `C:/Perforce/sw/rel/gpgpu/toolkit/r5.5/NPP/npp/include/nppdefs.h`

8.5 NppiPoint Struct Reference

2D Point

```
#include <nppdefs.h>
```

Data Fields

- `int x`
x-coordinate.
- `int y`
y-coordinate.

8.5.1 Detailed Description

2D Point

8.5.2 Field Documentation

8.5.2.1 `int NppiPoint::x`

x-coordinate.

8.5.2.2 `int NppiPoint::y`

y-coordinate.

The documentation for this struct was generated from the following file:

- `C:/Perforce/sw/rel/gpgpu/toolkit/r5.5/NPP/npp/include/nppdefs.h`

8.6 NppiRect Struct Reference

2D Rectangle This struct contains position and size information of a rectangle in two space.

```
#include <nppdefs.h>
```

Data Fields

- `int x`
x-coordinate of upper left corner.
- `int y`
y-coordinate of upper left corner.
- `int width`
Rectangle width.
- `int height`
Rectangle height.

8.6.1 Detailed Description

2D Rectangle This struct contains position and size information of a rectangle in two space.

The rectangle's position is usually signified by the coordinate of its upper-left corner.

8.6.2 Field Documentation

8.6.2.1 `int NppiRect::height`

Rectangle height.

8.6.2.2 `int NppiRect::width`

Rectangle width.

8.6.2.3 `int NppiRect::x`

x-coordinate of upper left corner.

8.6.2.4 `int NppiRect::y`

y-coordinate of upper left corner.

The documentation for this struct was generated from the following file:

- `C:/Perforce/sw/rel/gpgpu/toolkit/r5.5/NPP/npp/include/nppdefs.h`

8.7 NppiSize Struct Reference

2D Size This struct typically represents the size of a rectangular region in two space.

```
#include <nppdefs.h>
```

Data Fields

- `int width`
Rectangle width.
- `int height`
Rectangle height.

8.7.1 Detailed Description

2D Size This struct typically represents the size of a rectangular region in two space.

8.7.2 Field Documentation

8.7.2.1 `int NppiSize::height`

Rectangle height.

8.7.2.2 `int NppiSize::width`

Rectangle width.

The documentation for this struct was generated from the following file:

- `C:/Perforce/sw/rel/gpgpu/toolkit/r5.5/NPP/npp/include/nppdefs.h`

8.8 NppLibraryVersion Struct Reference

```
#include <nppdefs.h>
```

Data Fields

- int [major](#)
Major version number.
- int [minor](#)
Minor version number.
- int [build](#)
Build number.

8.8.1 Field Documentation

8.8.1.1 int NppLibraryVersion::build

Build number.

This reflects the nightly build this release was made from.

8.8.1.2 int NppLibraryVersion::major

Major version number.

8.8.1.3 int NppLibraryVersion::minor

Minor version number.

The documentation for this struct was generated from the following file:

- C:/Perforce/sw/rel/gpgpu/toolkit/r5.5/NPP/npp/include/nppdefs.h

Index

- `__align__`
 - `npp_basic_types`, 49, 50
- 10Log10, 2117
- 1D Linear Filter, 925
- 1D Window Sum, 1007
- 2D Fixed Linear Filters, 1036

- Abs, 320, 2091
- AbsDiff, 327
- AbsDiffC, 166
- Add, 168, 2041
- AddC, 55, 1994
- AddProduct, 200, 2053
- AddProductC, 2003
- AddSquare, 197
- AddWeighted, 204
- Affine Transforms, 1173
- Alpha Composition, 472
- AlphaComp, 488
- AlphaCompC, 473
- AlphaPremul, 495
- AlphaPremulC, 481
- And, 432, 2133
- AndC, 371, 2130
- Arctan, 2122
- Arithmetic and Logical Operations, 52, 1991
- Arithmetic Operations, 53, 1992

- Basic NPP Data Types, 47
- build
 - `NppLibraryVersion`, 2334

- Cauchy, CauchyD, and CauchyDD2, 2127
- classifiers
 - `NppiHaarClassifier_32f`, 2330
- classifierSize
 - `NppiHaarClassifier_32f`, 2330
- classifierStep
 - `NppiHaarClassifier_32f`, 2330
- Color and Sampling Conversion, 497
- Color Gamma Correction, 600
- Color Model Conversion, 498
- Color Processing, 609
- Color Sampling Format Conversion, 572
- Compare Operations, 1967

- Complement Color Key, 606
- Compression, 690
- Conversion Functions, 2159
- Convert, 784, 2160
- Convolution, 1009
- Copy, 737, 2199
- Copy Constant Border, 843
- Copy Replicate Border, 856
- Copy Sub-Pixel, 881
- Copy Wrap Border, 868
- `core_npp`
 - `nppGetGpuComputeCapability`, 32
 - `nppGetGpuName`, 32
 - `nppGetGpuNumSMs`, 32
 - `nppGetLibVersion`, 32
 - `nppGetMaxThreadsPerBlock`, 32
 - `nppGetMaxThreadsPerSM`, 32
 - `nppGetStream`, 33
 - `nppSetStream`, 33
- Count In Range, 2314
- Count Zero Crossings, 2315
- `counterDevice`
 - `NppiHaarClassifier_32f`, 2330
- `CountInRange.`, 1667
- `CrossCorrFull_Norm`, 1760
- `CrossCorrFull_NormLevel`, 1796
- `crosscorrfullnorm`
 - `nppiCrossCorrFull_Norm_16u32f_AC4R`, 1762
 - `nppiCrossCorrFull_Norm_16u32f_C1R`, 1762
 - `nppiCrossCorrFull_Norm_16u32f_C3R`, 1762
 - `nppiCrossCorrFull_Norm_16u32f_C4R`, 1763
 - `nppiCrossCorrFull_Norm_32f_AC4R`, 1763
 - `nppiCrossCorrFull_Norm_32f_C1R`, 1764
 - `nppiCrossCorrFull_Norm_32f_C3R`, 1764
 - `nppiCrossCorrFull_Norm_32f_C4R`, 1765
 - `nppiCrossCorrFull_Norm_8s32f_AC4R`, 1765
 - `nppiCrossCorrFull_Norm_8s32f_C1R`, 1765
 - `nppiCrossCorrFull_Norm_8s32f_C3R`, 1766
 - `nppiCrossCorrFull_Norm_8s32f_C4R`, 1766
 - `nppiCrossCorrFull_Norm_8u32f_AC4R`, 1767
 - `nppiCrossCorrFull_Norm_8u32f_C1R`, 1767
 - `nppiCrossCorrFull_Norm_8u32f_C3R`, 1768
 - `nppiCrossCorrFull_Norm_8u32f_C4R`, 1768
 - `nppiCrossCorrFull_Norm_8u_AC4RSfs`, 1768

- nppiCrossCorrFull_Norm_8u_C1RSfs, 1769
- nppiCrossCorrFull_Norm_8u_C3RSfs, 1769
- nppiCrossCorrFull_Norm_8u_C4RSfs, 1770
- crosscorrfullnormlevel
 - nppiCrossCorrFull_NormLevel_16u32f_-AC4R, 1800
 - nppiCrossCorrFull_NormLevel_16u32f_C1R, 1800
 - nppiCrossCorrFull_NormLevel_16u32f_C3R, 1800
 - nppiCrossCorrFull_NormLevel_16u32f_C4R, 1801
 - nppiCrossCorrFull_NormLevel_32f_AC4R, 1801
 - nppiCrossCorrFull_NormLevel_32f_C1R, 1802
 - nppiCrossCorrFull_NormLevel_32f_C3R, 1802
 - nppiCrossCorrFull_NormLevel_32f_C4R, 1803
 - nppiCrossCorrFull_NormLevel_8s32f_AC4R, 1803
 - nppiCrossCorrFull_NormLevel_8s32f_C1R, 1804
 - nppiCrossCorrFull_NormLevel_8s32f_C3R, 1804
 - nppiCrossCorrFull_NormLevel_8s32f_C4R, 1805
 - nppiCrossCorrFull_NormLevel_8u32f_AC4R, 1805
 - nppiCrossCorrFull_NormLevel_8u32f_C1R, 1806
 - nppiCrossCorrFull_NormLevel_8u32f_C3R, 1806
 - nppiCrossCorrFull_NormLevel_8u32f_C4R, 1807
 - nppiCrossCorrFull_NormLevel_8u_AC4RSfs, 1807
 - nppiCrossCorrFull_NormLevel_8u_C1RSfs, 1808
 - nppiCrossCorrFull_NormLevel_8u_C3RSfs, 1808
 - nppiCrossCorrFull_NormLevel_8u_C4RSfs, 1809
 - nppiFullNormLevelGetBufferHostSize_-16u32f_AC4R, 1809
 - nppiFullNormLevelGetBufferHostSize_-16u32f_C1R, 1810
 - nppiFullNormLevelGetBufferHostSize_-16u32f_C3R, 1810
 - nppiFullNormLevelGetBufferHostSize_-16u32f_C4R, 1810
 - nppiFullNormLevelGetBufferHostSize_32f_-AC4R, 1811
 - nppiFullNormLevelGetBufferHostSize_32f_-C1R, 1811
 - nppiFullNormLevelGetBufferHostSize_32f_-C3R, 1811
 - nppiFullNormLevelGetBufferHostSize_32f_-C4R, 1811
 - nppiFullNormLevelGetBufferHostSize_-8s32f_AC4R, 1812
 - nppiFullNormLevelGetBufferHostSize_-8s32f_C1R, 1812
 - nppiFullNormLevelGetBufferHostSize_-8s32f_C3R, 1812
 - nppiFullNormLevelGetBufferHostSize_-8s32f_C4R, 1813
 - nppiFullNormLevelGetBufferHostSize_-8u32f_AC4R, 1813
 - nppiFullNormLevelGetBufferHostSize_-8u32f_C1R, 1813
 - nppiFullNormLevelGetBufferHostSize_-8u32f_C3R, 1813
 - nppiFullNormLevelGetBufferHostSize_-8u32f_C4R, 1814
 - nppiFullNormLevelGetBufferHostSize_8u_-AC4RSfs, 1814
 - nppiFullNormLevelGetBufferHostSize_8u_-C1RSfs, 1814
 - nppiFullNormLevelGetBufferHostSize_8u_-C3RSfs, 1815
 - nppiFullNormLevelGetBufferHostSize_8u_-C4RSfs, 1815
- CrossCorrSame_Norm, 1771
- CrossCorrSame_NormLevel, 1816
- crosscorrshamenorm
 - nppiCrossCorrSame_Norm_16u32f_AC4R, 1773
 - nppiCrossCorrSame_Norm_16u32f_C1R, 1773
 - nppiCrossCorrSame_Norm_16u32f_C3R, 1773
 - nppiCrossCorrSame_Norm_16u32f_C4R, 1774
 - nppiCrossCorrSame_Norm_32f_AC4R, 1774
 - nppiCrossCorrSame_Norm_32f_C1R, 1775
 - nppiCrossCorrSame_Norm_32f_C3R, 1775
 - nppiCrossCorrSame_Norm_32f_C4R, 1776
 - nppiCrossCorrSame_Norm_8s32f_AC4R, 1776
 - nppiCrossCorrSame_Norm_8s32f_C1R, 1776
 - nppiCrossCorrSame_Norm_8s32f_C3R, 1777
 - nppiCrossCorrSame_Norm_8s32f_C4R, 1777
 - nppiCrossCorrSame_Norm_8u32f_AC4R, 1778
 - nppiCrossCorrSame_Norm_8u32f_C1R, 1778
 - nppiCrossCorrSame_Norm_8u32f_C3R, 1779

- nppiCrossCorrSame_Norm_8u32f_C4R, 1779
- nppiCrossCorrSame_Norm_8u_AC4RSfs, 1779
- nppiCrossCorrSame_Norm_8u_C1RSfs, 1780
- nppiCrossCorrSame_Norm_8u_C3RSfs, 1780
- nppiCrossCorrSame_Norm_8u_C4RSfs, 1781
- crosscorrshamenormlevel
 - nppiCrossCorrSame_NormLevel_16u32f_AC4R, 1820
 - nppiCrossCorrSame_NormLevel_16u32f_C1R, 1820
 - nppiCrossCorrSame_NormLevel_16u32f_C3R, 1820
 - nppiCrossCorrSame_NormLevel_16u32f_C4R, 1821
 - nppiCrossCorrSame_NormLevel_32f_AC4R, 1821
 - nppiCrossCorrSame_NormLevel_32f_C1R, 1822
 - nppiCrossCorrSame_NormLevel_32f_C3R, 1822
 - nppiCrossCorrSame_NormLevel_32f_C4R, 1823
 - nppiCrossCorrSame_NormLevel_8s32f_AC4R, 1823
 - nppiCrossCorrSame_NormLevel_8s32f_C1R, 1824
 - nppiCrossCorrSame_NormLevel_8s32f_C3R, 1824
 - nppiCrossCorrSame_NormLevel_8s32f_C4R, 1825
 - nppiCrossCorrSame_NormLevel_8u32f_AC4R, 1825
 - nppiCrossCorrSame_NormLevel_8u32f_C1R, 1826
 - nppiCrossCorrSame_NormLevel_8u32f_C3R, 1826
 - nppiCrossCorrSame_NormLevel_8u32f_C4R, 1827
 - nppiCrossCorrSame_NormLevel_8u_AC4RSfs, 1827
 - nppiCrossCorrSame_NormLevel_8u_C1RSfs, 1828
 - nppiCrossCorrSame_NormLevel_8u_C3RSfs, 1828
 - nppiCrossCorrSame_NormLevel_8u_C4RSfs, 1829
 - nppiSameNormLevelGetBufferHostSize_16u32f_AC4R, 1829
 - nppiSameNormLevelGetBufferHostSize_16u32f_C1R, 1830
 - nppiSameNormLevelGetBufferHostSize_16u32f_C3R, 1830
 - nppiSameNormLevelGetBufferHostSize_16u32f_C4R, 1830
 - nppiSameNormLevelGetBufferHostSize_32f_AC4R, 1831
 - nppiSameNormLevelGetBufferHostSize_32f_C1R, 1831
 - nppiSameNormLevelGetBufferHostSize_32f_C3R, 1831
 - nppiSameNormLevelGetBufferHostSize_32f_C4R, 1831
 - nppiSameNormLevelGetBufferHostSize_8s32f_AC4R, 1832
 - nppiSameNormLevelGetBufferHostSize_8s32f_C1R, 1832
 - nppiSameNormLevelGetBufferHostSize_8s32f_C3R, 1832
 - nppiSameNormLevelGetBufferHostSize_8s32f_C4R, 1833
 - nppiSameNormLevelGetBufferHostSize_8u32f_AC4R, 1833
 - nppiSameNormLevelGetBufferHostSize_8u32f_C1R, 1833
 - nppiSameNormLevelGetBufferHostSize_8u32f_C3R, 1833
 - nppiSameNormLevelGetBufferHostSize_8u32f_C4R, 1834
 - nppiSameNormLevelGetBufferHostSize_8u_AC4RSfs, 1834
 - nppiSameNormLevelGetBufferHostSize_8u_C1RSfs, 1834
 - nppiSameNormLevelGetBufferHostSize_8u_C3RSfs, 1835
 - nppiSameNormLevelGetBufferHostSize_8u_C4RSfs, 1835
- CrossCorrValid, 1793
- crosscorrvalid
 - nppiCrossCorrValid_16u32f_C1R, 1793
 - nppiCrossCorrValid_32f_C1R, 1794
 - nppiCrossCorrValid_8s32f_C1R, 1794
 - nppiCrossCorrValid_8u32f_C1R, 1794
- CrossCorrValid_Norm, 1782
- CrossCorrValid_NormLevel, 1836
- crosscorrvalidnorm
 - nppiCrossCorrValid_Norm_16u32f_AC4R, 1784
 - nppiCrossCorrValid_Norm_16u32f_C1R, 1784
 - nppiCrossCorrValid_Norm_16u32f_C3R, 1784
 - nppiCrossCorrValid_Norm_16u32f_C4R, 1785
 - nppiCrossCorrValid_Norm_32f_AC4R, 1785
 - nppiCrossCorrValid_Norm_32f_C1R, 1786
 - nppiCrossCorrValid_Norm_32f_C3R, 1786

- nppiCrossCorrValid_Norm_32f_C4R, [1787](#)
- nppiCrossCorrValid_Norm_8s32f_AC4R, [1787](#)
- nppiCrossCorrValid_Norm_8s32f_C1R, [1787](#)
- nppiCrossCorrValid_Norm_8s32f_C3R, [1788](#)
- nppiCrossCorrValid_Norm_8s32f_C4R, [1788](#)
- nppiCrossCorrValid_Norm_8u32f_AC4R, [1789](#)
- nppiCrossCorrValid_Norm_8u32f_C1R, [1789](#)
- nppiCrossCorrValid_Norm_8u32f_C3R, [1790](#)
- nppiCrossCorrValid_Norm_8u32f_C4R, [1790](#)
- nppiCrossCorrValid_Norm_8u_AC4RSfs, [1790](#)
- nppiCrossCorrValid_Norm_8u_C1RSfs, [1791](#)
- nppiCrossCorrValid_Norm_8u_C3RSfs, [1791](#)
- nppiCrossCorrValid_Norm_8u_C4RSfs, [1792](#)
- crosscorrvalidnormlevel
 - nppiCrossCorrValid_NormLevel_16u32f_AC4R, [1840](#)
 - nppiCrossCorrValid_NormLevel_16u32f_C1R, [1840](#)
 - nppiCrossCorrValid_NormLevel_16u32f_C3R, [1840](#)
 - nppiCrossCorrValid_NormLevel_16u32f_C4R, [1841](#)
 - nppiCrossCorrValid_NormLevel_32f_AC4R, [1841](#)
 - nppiCrossCorrValid_NormLevel_32f_C1R, [1842](#)
 - nppiCrossCorrValid_NormLevel_32f_C3R, [1842](#)
 - nppiCrossCorrValid_NormLevel_32f_C4R, [1843](#)
 - nppiCrossCorrValid_NormLevel_8s32f_AC4R, [1843](#)
 - nppiCrossCorrValid_NormLevel_8s32f_C1R, [1844](#)
 - nppiCrossCorrValid_NormLevel_8s32f_C3R, [1844](#)
 - nppiCrossCorrValid_NormLevel_8s32f_C4R, [1845](#)
 - nppiCrossCorrValid_NormLevel_8u32f_AC4R, [1845](#)
 - nppiCrossCorrValid_NormLevel_8u32f_C1R, [1846](#)
 - nppiCrossCorrValid_NormLevel_8u32f_C3R, [1846](#)
 - nppiCrossCorrValid_NormLevel_8u32f_C4R, [1847](#)
 - nppiCrossCorrValid_NormLevel_8u_AC4RSfs, [1847](#)
 - nppiCrossCorrValid_NormLevel_8u_C1RSfs, [1848](#)
- nppiCrossCorrValid_NormLevel_8u_C3RSfs, [1848](#)
- nppiCrossCorrValid_NormLevel_8u_C4RSfs, [1849](#)
- nppiValidNormLevelGetBufferHostSize_16u32f_AC4R, [1849](#)
- nppiValidNormLevelGetBufferHostSize_16u32f_C1R, [1850](#)
- nppiValidNormLevelGetBufferHostSize_16u32f_C3R, [1850](#)
- nppiValidNormLevelGetBufferHostSize_16u32f_C4R, [1850](#)
- nppiValidNormLevelGetBufferHostSize_32f_AC4R, [1851](#)
- nppiValidNormLevelGetBufferHostSize_32f_C1R, [1851](#)
- nppiValidNormLevelGetBufferHostSize_32f_C3R, [1851](#)
- nppiValidNormLevelGetBufferHostSize_32f_C4R, [1851](#)
- nppiValidNormLevelGetBufferHostSize_8s32f_AC4R, [1852](#)
- nppiValidNormLevelGetBufferHostSize_8s32f_C1R, [1852](#)
- nppiValidNormLevelGetBufferHostSize_8s32f_C3R, [1852](#)
- nppiValidNormLevelGetBufferHostSize_8s32f_C4R, [1853](#)
- nppiValidNormLevelGetBufferHostSize_8u32f_AC4R, [1853](#)
- nppiValidNormLevelGetBufferHostSize_8u32f_C1R, [1853](#)
- nppiValidNormLevelGetBufferHostSize_8u32f_C3R, [1853](#)
- nppiValidNormLevelGetBufferHostSize_8u32f_C4R, [1854](#)
- nppiValidNormLevelGetBufferHostSize_8u_AC4RSfs, [1854](#)
- nppiValidNormLevelGetBufferHostSize_8u_C1RSfs, [1854](#)
- nppiValidNormLevelGetBufferHostSize_8u_C3RSfs, [1855](#)
- nppiValidNormLevelGetBufferHostSize_8u_C4RSfs, [1855](#)
- Cubrt, [2108](#)
- Data Exchange and Initialization, [706](#)
- Dilate3x3, [1287](#)
- Dilation, [1273](#)
- Div, [276](#), [2080](#)
- Div_Round, [305](#), [2088](#)
- DivC, [140](#), [2032](#)
- DivCRev, [2039](#)
- Dot Product, [2294](#)

- DotProd, 1642
- Duplicate Channel, 892
- Erode, 1280
- Erode3x3, 1293
- Exp, 363, 2109
- Filtering Functions, 924, 2188
- Fixed Filters, 1061
- fixed_filters
 - nppiFilterPrewittHoriz_16s_AC4R, 1067
 - nppiFilterPrewittHoriz_16s_C1R, 1067
 - nppiFilterPrewittHoriz_16s_C3R, 1068
 - nppiFilterPrewittHoriz_16s_C4R, 1068
 - nppiFilterPrewittHoriz_32f_AC4R, 1068
 - nppiFilterPrewittHoriz_32f_C1R, 1069
 - nppiFilterPrewittHoriz_32f_C3R, 1069
 - nppiFilterPrewittHoriz_32f_C4R, 1069
 - nppiFilterPrewittHoriz_8u_AC4R, 1070
 - nppiFilterPrewittHoriz_8u_C1R, 1070
 - nppiFilterPrewittHoriz_8u_C3R, 1070
 - nppiFilterPrewittHoriz_8u_C4R, 1071
 - nppiFilterPrewittVert_16s_AC4R, 1071
 - nppiFilterPrewittVert_16s_C1R, 1071
 - nppiFilterPrewittVert_16s_C3R, 1072
 - nppiFilterPrewittVert_16s_C4R, 1072
 - nppiFilterPrewittVert_32f_AC4R, 1072
 - nppiFilterPrewittVert_32f_C1R, 1073
 - nppiFilterPrewittVert_32f_C3R, 1073
 - nppiFilterPrewittVert_32f_C4R, 1073
 - nppiFilterPrewittVert_8u_AC4R, 1074
 - nppiFilterPrewittVert_8u_C1R, 1074
 - nppiFilterPrewittVert_8u_C3R, 1074
 - nppiFilterPrewittVert_8u_C4R, 1075
 - nppiFilterScharrHoriz_32f_C1R, 1075
 - nppiFilterScharrHoriz_8s16s_C1R, 1075
 - nppiFilterScharrHoriz_8u16s_C1R, 1076
 - nppiFilterScharrVert_32f_C1R, 1076
 - nppiFilterScharrVert_8s16s_C1R, 1076
 - nppiFilterScharrVert_8u16s_C1R, 1077
 - nppiFilterSobelHoriz_16s_AC4R, 1077
 - nppiFilterSobelHoriz_16s_C1R, 1077
 - nppiFilterSobelHoriz_16s_C3R, 1078
 - nppiFilterSobelHoriz_16s_C4R, 1078
 - nppiFilterSobelHoriz_32f_AC4R, 1078
 - nppiFilterSobelHoriz_32f_C1R, 1079
 - nppiFilterSobelHoriz_32f_C3R, 1079
 - nppiFilterSobelHoriz_32f_C4R, 1079
 - nppiFilterSobelHoriz_8s16s_C1R, 1080
 - nppiFilterSobelHoriz_8u16s_C1R, 1080
 - nppiFilterSobelHoriz_8u_AC4R, 1080
 - nppiFilterSobelHoriz_8u_C1R, 1081
 - nppiFilterSobelHoriz_8u_C3R, 1081
 - nppiFilterSobelHoriz_8u_C4R, 1081
 - nppiFilterSobelHorizMask_32f_C1R, 1082
 - nppiFilterSobelHorizSecond_32f_C1R, 1082
 - nppiFilterSobelHorizSecond_8s16s_C1R, 1082
 - nppiFilterSobelHorizSecond_8u16s_C1R, 1083
 - nppiFilterSobelVert_16s_AC4R, 1083
 - nppiFilterSobelVert_16s_C1R, 1084
 - nppiFilterSobelVert_16s_C3R, 1084
 - nppiFilterSobelVert_16s_C4R, 1084
 - nppiFilterSobelVert_32f_AC4R, 1085
 - nppiFilterSobelVert_32f_C1R, 1085
 - nppiFilterSobelVert_32f_C3R, 1085
 - nppiFilterSobelVert_32f_C4R, 1086
 - nppiFilterSobelVert_8s16s_C1R, 1086
 - nppiFilterSobelVert_8u16s_C1R, 1086
 - nppiFilterSobelVert_8u_AC4R, 1087
 - nppiFilterSobelVert_8u_C1R, 1087
 - nppiFilterSobelVert_8u_C3R, 1087
 - nppiFilterSobelVert_8u_C4R, 1088
 - nppiFilterSobelVertMask_32f_C1R, 1088
- Fourier Transforms, 1270
- Free, 2323
- Geometry Transforms, 1089
- GraphCut, 699
- haarBuffer
 - NppiHaarBuffer, 2329
- haarBufferSize
 - NppiHaarBuffer, 2329
- height
 - NppiRect, 2332
 - NppiSize, 2333
- HistogramEven, 1695
- HistogramRange, 1708
- im
 - NPP_ALIGN_16, 2325
 - NPP_ALIGN_8, 2327
- Image Norms, 1438
- Image Proximity, 1724
- Image Quality Index, 1856
- image_1D_linear_filter
 - nppiFilterColumn32f_16s_AC4R, 941
 - nppiFilterColumn32f_16s_C1R, 941
 - nppiFilterColumn32f_16s_C3R, 942
 - nppiFilterColumn32f_16s_C4R, 942
 - nppiFilterColumn32f_16u_AC4R, 942
 - nppiFilterColumn32f_16u_C1R, 943
 - nppiFilterColumn32f_16u_C3R, 943
 - nppiFilterColumn32f_16u_C4R, 944
 - nppiFilterColumn32f_8u_AC4R, 944
 - nppiFilterColumn32f_8u_C1R, 945

- nppiFilterColumn32f_8u_C3R, 945
- nppiFilterColumn32f_8u_C4R, 946
- nppiFilterColumn_16s_AC4R, 946
- nppiFilterColumn_16s_C1R, 947
- nppiFilterColumn_16s_C3R, 947
- nppiFilterColumn_16s_C4R, 948
- nppiFilterColumn_16u_AC4R, 948
- nppiFilterColumn_16u_C1R, 949
- nppiFilterColumn_16u_C3R, 949
- nppiFilterColumn_16u_C4R, 950
- nppiFilterColumn_32f_AC4R, 950
- nppiFilterColumn_32f_C1R, 951
- nppiFilterColumn_32f_C3R, 951
- nppiFilterColumn_32f_C4R, 952
- nppiFilterColumn_64f_C1R, 952
- nppiFilterColumn_8u_AC4R, 953
- nppiFilterColumn_8u_C1R, 953
- nppiFilterColumn_8u_C3R, 954
- nppiFilterColumn_8u_C4R, 954
- nppiFilterGauss_16s_AC4R, 955
- nppiFilterGauss_16s_C1R, 955
- nppiFilterGauss_16s_C3R, 956
- nppiFilterGauss_16s_C4R, 956
- nppiFilterGauss_16u_AC4R, 956
- nppiFilterGauss_16u_C1R, 957
- nppiFilterGauss_16u_C3R, 957
- nppiFilterGauss_16u_C4R, 957
- nppiFilterGauss_32f_AC4R, 958
- nppiFilterGauss_32f_C1R, 958
- nppiFilterGauss_32f_C3R, 958
- nppiFilterGauss_32f_C4R, 959
- nppiFilterGauss_8u_AC4R, 959
- nppiFilterGauss_8u_C1R, 959
- nppiFilterGauss_8u_C3R, 960
- nppiFilterGauss_8u_C4R, 960
- nppiFilterHighPass_16s_AC4R, 960
- nppiFilterHighPass_16s_C1R, 961
- nppiFilterHighPass_16s_C3R, 961
- nppiFilterHighPass_16s_C4R, 961
- nppiFilterHighPass_16u_AC4R, 962
- nppiFilterHighPass_16u_C1R, 962
- nppiFilterHighPass_16u_C3R, 962
- nppiFilterHighPass_16u_C4R, 963
- nppiFilterHighPass_32f_AC4R, 963
- nppiFilterHighPass_32f_C1R, 963
- nppiFilterHighPass_32f_C3R, 964
- nppiFilterHighPass_32f_C4R, 964
- nppiFilterHighPass_8u_AC4R, 964
- nppiFilterHighPass_8u_C1R, 965
- nppiFilterHighPass_8u_C3R, 965
- nppiFilterHighPass_8u_C4R, 965
- nppiFilterLaplace_16s_AC4R, 966
- nppiFilterLaplace_16s_C1R, 966
- nppiFilterLaplace_16s_C3R, 966
- nppiFilterLaplace_16s_C4R, 967
- nppiFilterLaplace_32f_AC4R, 967
- nppiFilterLaplace_32f_C1R, 967
- nppiFilterLaplace_32f_C3R, 968
- nppiFilterLaplace_32f_C4R, 968
- nppiFilterLaplace_8s16s_C1R, 968
- nppiFilterLaplace_8u16s_C1R, 969
- nppiFilterLaplace_8u_AC4R, 969
- nppiFilterLaplace_8u_C1R, 969
- nppiFilterLaplace_8u_C3R, 970
- nppiFilterLaplace_8u_C4R, 970
- nppiFilterLowPass_16s_AC4R, 970
- nppiFilterLowPass_16s_C1R, 971
- nppiFilterLowPass_16s_C3R, 971
- nppiFilterLowPass_16s_C4R, 971
- nppiFilterLowPass_16u_AC4R, 972
- nppiFilterLowPass_16u_C1R, 972
- nppiFilterLowPass_16u_C3R, 972
- nppiFilterLowPass_16u_C4R, 973
- nppiFilterLowPass_32f_AC4R, 973
- nppiFilterLowPass_32f_C1R, 973
- nppiFilterLowPass_32f_C3R, 974
- nppiFilterLowPass_32f_C4R, 974
- nppiFilterLowPass_8u_AC4R, 974
- nppiFilterLowPass_8u_C1R, 975
- nppiFilterLowPass_8u_C3R, 975
- nppiFilterLowPass_8u_C4R, 975
- nppiFilterRobertsDown_16s_AC4R, 976
- nppiFilterRobertsDown_16s_C1R, 976
- nppiFilterRobertsDown_16s_C3R, 976
- nppiFilterRobertsDown_16s_C4R, 977
- nppiFilterRobertsDown_32f_AC4R, 977
- nppiFilterRobertsDown_32f_C1R, 977
- nppiFilterRobertsDown_32f_C3R, 978
- nppiFilterRobertsDown_32f_C4R, 978
- nppiFilterRobertsDown_8u_AC4R, 978
- nppiFilterRobertsDown_8u_C1R, 979
- nppiFilterRobertsDown_8u_C3R, 979
- nppiFilterRobertsDown_8u_C4R, 979
- nppiFilterRobertsUp_16s_AC4R, 980
- nppiFilterRobertsUp_16s_C1R, 980
- nppiFilterRobertsUp_16s_C3R, 980
- nppiFilterRobertsUp_16s_C4R, 981
- nppiFilterRobertsUp_32f_AC4R, 981
- nppiFilterRobertsUp_32f_C1R, 981
- nppiFilterRobertsUp_32f_C3R, 982
- nppiFilterRobertsUp_32f_C4R, 982
- nppiFilterRobertsUp_8u_AC4R, 982
- nppiFilterRobertsUp_8u_C1R, 983
- nppiFilterRobertsUp_8u_C3R, 983
- nppiFilterRobertsUp_8u_C4R, 983
- nppiFilterRow32f_16s_AC4R, 984
- nppiFilterRow32f_16s_C1R, 984
- nppiFilterRow32f_16s_C3R, 985

- nppiFilterRow32f_16s_C4R, 985
- nppiFilterRow32f_16u_AC4R, 986
- nppiFilterRow32f_16u_C1R, 986
- nppiFilterRow32f_16u_C3R, 986
- nppiFilterRow32f_16u_C4R, 987
- nppiFilterRow32f_8u_AC4R, 987
- nppiFilterRow32f_8u_C1R, 988
- nppiFilterRow32f_8u_C3R, 988
- nppiFilterRow32f_8u_C4R, 989
- nppiFilterRow_16s_AC4R, 989
- nppiFilterRow_16s_C1R, 990
- nppiFilterRow_16s_C3R, 990
- nppiFilterRow_16s_C4R, 991
- nppiFilterRow_16u_AC4R, 991
- nppiFilterRow_16u_C1R, 992
- nppiFilterRow_16u_C3R, 992
- nppiFilterRow_16u_C4R, 993
- nppiFilterRow_32f_AC4R, 993
- nppiFilterRow_32f_C1R, 994
- nppiFilterRow_32f_C3R, 994
- nppiFilterRow_32f_C4R, 995
- nppiFilterRow_64f_C1R, 995
- nppiFilterRow_8u_AC4R, 996
- nppiFilterRow_8u_C1R, 996
- nppiFilterRow_8u_C3R, 997
- nppiFilterRow_8u_C4R, 997
- nppiFilterSharpen_16s_AC4R, 998
- nppiFilterSharpen_16s_C1R, 998
- nppiFilterSharpen_16s_C3R, 999
- nppiFilterSharpen_16s_C4R, 999
- nppiFilterSharpen_16u_AC4R, 999
- nppiFilterSharpen_16u_C1R, 1000
- nppiFilterSharpen_16u_C3R, 1000
- nppiFilterSharpen_16u_C4R, 1000
- nppiFilterSharpen_32f_AC4R, 1001
- nppiFilterSharpen_32f_C1R, 1001
- nppiFilterSharpen_32f_C3R, 1001
- nppiFilterSharpen_32f_C4R, 1002
- nppiFilterSharpen_8u_AC4R, 1002
- nppiFilterSharpen_8u_C1R, 1002
- nppiFilterSharpen_8u_C3R, 1003
- nppiFilterSharpen_8u_C4R, 1003
- nppiFilterSobelCross_32f_C1R, 1003
- nppiFilterSobelCross_8s16s_C1R, 1004
- nppiFilterSobelCross_8u16s_C1R, 1004
- nppiFilterSobelVertSecond_32f_C1R, 1004
- nppiFilterSobelVertSecond_8s16s_C1R, 1005
- nppiFilterSobelVertSecond_8u16s_C1R, 1005
- image_1D_window_sum
 - nppiSumWindowColumn_8u32f_C1R, 1007
 - nppiSumWindowRow_8u32f_C1R, 1007
- image_2D_fixed_linear_filters
 - nppiFilterBox_16s_AC4R, 1037
 - nppiFilterBox_16s_C1R, 1037
 - nppiFilterBox_16s_C3R, 1038
 - nppiFilterBox_16s_C4R, 1038
 - nppiFilterBox_16u_AC4R, 1039
 - nppiFilterBox_16u_C1R, 1039
 - nppiFilterBox_16u_C3R, 1039
 - nppiFilterBox_16u_C4R, 1040
 - nppiFilterBox_32f_AC4R, 1040
 - nppiFilterBox_32f_C1R, 1041
 - nppiFilterBox_32f_C3R, 1041
 - nppiFilterBox_32f_C4R, 1041
 - nppiFilterBox_64f_C1R, 1042
 - nppiFilterBox_8u_AC4R, 1042
 - nppiFilterBox_8u_C1R, 1043
 - nppiFilterBox_8u_C3R, 1043
 - nppiFilterBox_8u_C4R, 1043
- image_abs
 - nppiAbs_16s_AC4IR, 321
 - nppiAbs_16s_AC4R, 321
 - nppiAbs_16s_C1IR, 321
 - nppiAbs_16s_C1R, 322
 - nppiAbs_16s_C3IR, 322
 - nppiAbs_16s_C3R, 322
 - nppiAbs_16s_C4IR, 323
 - nppiAbs_16s_C4R, 323
 - nppiAbs_32f_AC4IR, 323
 - nppiAbs_32f_AC4R, 324
 - nppiAbs_32f_C1IR, 324
 - nppiAbs_32f_C1R, 324
 - nppiAbs_32f_C3IR, 325
 - nppiAbs_32f_C3R, 325
 - nppiAbs_32f_C4IR, 325
 - nppiAbs_32f_C4R, 326
- image_absdiff
 - nppiAbsDiff_16u_C1R, 327
 - nppiAbsDiff_32f_C1R, 328
 - nppiAbsDiff_8u_C1R, 328
 - nppiAbsDiff_8u_C3R, 328
 - nppiAbsDiff_8u_C4R, 329
- image_absdiffc
 - nppiAbsDiffC_16u_C1R, 166
 - nppiAbsDiffC_32f_C1R, 166
 - nppiAbsDiffC_8u_C1R, 167
- image_add
 - nppiAdd_16s_AC4IRSfs, 173
 - nppiAdd_16s_AC4RSfs, 173
 - nppiAdd_16s_C1IRSfs, 174
 - nppiAdd_16s_C1RSfs, 174
 - nppiAdd_16s_C3IRSfs, 175
 - nppiAdd_16s_C3RSfs, 175
 - nppiAdd_16s_C4IRSfs, 175
 - nppiAdd_16s_C4RSfs, 176
 - nppiAdd_16sc_AC4IRSfs, 176
 - nppiAdd_16sc_AC4RSfs, 177
 - nppiAdd_16sc_C1IRSfs, 177

- nppiAdd_16sc_C1RSfs, 177
- nppiAdd_16sc_C3IRSfs, 178
- nppiAdd_16sc_C3RSfs, 178
- nppiAdd_16u_AC4IRSfs, 179
- nppiAdd_16u_AC4RSfs, 179
- nppiAdd_16u_C1IRSfs, 180
- nppiAdd_16u_C1RSfs, 180
- nppiAdd_16u_C3IRSfs, 180
- nppiAdd_16u_C3RSfs, 181
- nppiAdd_16u_C4IRSfs, 181
- nppiAdd_16u_C4RSfs, 182
- nppiAdd_32f_AC4IR, 182
- nppiAdd_32f_AC4R, 182
- nppiAdd_32f_C1IR, 183
- nppiAdd_32f_C1R, 183
- nppiAdd_32f_C3IR, 184
- nppiAdd_32f_C3R, 184
- nppiAdd_32f_C4IR, 184
- nppiAdd_32f_C4R, 185
- nppiAdd_32fc_AC4IR, 185
- nppiAdd_32fc_AC4R, 185
- nppiAdd_32fc_C1IR, 186
- nppiAdd_32fc_C1R, 186
- nppiAdd_32fc_C3IR, 187
- nppiAdd_32fc_C3R, 187
- nppiAdd_32fc_C4IR, 187
- nppiAdd_32fc_C4R, 188
- nppiAdd_32s_C1IRSfs, 188
- nppiAdd_32s_C1R, 189
- nppiAdd_32s_C1RSfs, 189
- nppiAdd_32s_C3IRSfs, 189
- nppiAdd_32s_C3RSfs, 190
- nppiAdd_32sc_AC4IRSfs, 190
- nppiAdd_32sc_AC4RSfs, 191
- nppiAdd_32sc_C1IRSfs, 191
- nppiAdd_32sc_C1RSfs, 191
- nppiAdd_32sc_C3IRSfs, 192
- nppiAdd_32sc_C3RSfs, 192
- nppiAdd_8u_AC4IRSfs, 193
- nppiAdd_8u_AC4RSfs, 193
- nppiAdd_8u_C1IRSfs, 194
- nppiAdd_8u_C1RSfs, 194
- nppiAdd_8u_C3IRSfs, 194
- nppiAdd_8u_C3RSfs, 195
- nppiAdd_8u_C4IRSfs, 195
- nppiAdd_8u_C4RSfs, 196
- image_addc
 - nppiAddC_16s_AC4IRSfs, 60
 - nppiAddC_16s_AC4RSfs, 60
 - nppiAddC_16s_C1IRSfs, 60
 - nppiAddC_16s_C1RSfs, 61
 - nppiAddC_16s_C3IRSfs, 61
 - nppiAddC_16s_C3RSfs, 61
 - nppiAddC_16s_C4IRSfs, 62
- nppiAddC_16s_C4RSfs, 62
- nppiAddC_16sc_AC4IRSfs, 63
- nppiAddC_16sc_AC4RSfs, 63
- nppiAddC_16sc_C1IRSfs, 63
- nppiAddC_16sc_C1RSfs, 64
- nppiAddC_16sc_C3IRSfs, 64
- nppiAddC_16sc_C3RSfs, 65
- nppiAddC_16u_AC4IRSfs, 65
- nppiAddC_16u_AC4RSfs, 65
- nppiAddC_16u_C1IRSfs, 66
- nppiAddC_16u_C1RSfs, 66
- nppiAddC_16u_C3IRSfs, 67
- nppiAddC_16u_C3RSfs, 67
- nppiAddC_16u_C4IRSfs, 67
- nppiAddC_16u_C4RSfs, 68
- nppiAddC_32f_AC4IR, 68
- nppiAddC_32f_AC4R, 68
- nppiAddC_32f_C1IR, 69
- nppiAddC_32f_C1R, 69
- nppiAddC_32f_C3IR, 69
- nppiAddC_32f_C3R, 70
- nppiAddC_32f_C4IR, 70
- nppiAddC_32f_C4R, 70
- nppiAddC_32fc_AC4IR, 71
- nppiAddC_32fc_AC4R, 71
- nppiAddC_32fc_C1IR, 71
- nppiAddC_32fc_C1R, 72
- nppiAddC_32fc_C3IR, 72
- nppiAddC_32fc_C3R, 72
- nppiAddC_32fc_C4IR, 73
- nppiAddC_32fc_C4R, 73
- nppiAddC_32s_C1IRSfs, 74
- nppiAddC_32s_C1RSfs, 74
- nppiAddC_32s_C3IRSfs, 74
- nppiAddC_32s_C3RSfs, 75
- nppiAddC_32sc_AC4IRSfs, 75
- nppiAddC_32sc_AC4RSfs, 75
- nppiAddC_32sc_C1IRSfs, 76
- nppiAddC_32sc_C1RSfs, 76
- nppiAddC_32sc_C3IRSfs, 77
- nppiAddC_32sc_C3RSfs, 77
- nppiAddC_8u_AC4IRSfs, 77
- nppiAddC_8u_AC4RSfs, 78
- nppiAddC_8u_C1IRSfs, 78
- nppiAddC_8u_C1RSfs, 79
- nppiAddC_8u_C3IRSfs, 79
- nppiAddC_8u_C3RSfs, 79
- nppiAddC_8u_C4IRSfs, 80
- nppiAddC_8u_C4RSfs, 80
- image_addproduct
 - nppiAddProduct_16u32f_C1IMR, 200
 - nppiAddProduct_16u32f_C1IR, 201
 - nppiAddProduct_32f_C1IMR, 201
 - nppiAddProduct_32f_C1IR, 202

- nppiAddProduct_8u32f_C1IMR, 202
- nppiAddProduct_8u32f_C1IR, 202
- image_addsquare
 - nppiAddSquare_16u32f_C1IMR, 197
 - nppiAddSquare_16u32f_C1IR, 198
 - nppiAddSquare_32f_C1IMR, 198
 - nppiAddSquare_32f_C1IR, 198
 - nppiAddSquare_8u32f_C1IMR, 199
 - nppiAddSquare_8u32f_C1IR, 199
- image_addweighted
 - nppiAddWeighted_16u32f_C1IMR, 204
 - nppiAddWeighted_16u32f_C1IR, 205
 - nppiAddWeighted_32f_C1IMR, 205
 - nppiAddWeighted_32f_C1IR, 206
 - nppiAddWeighted_8u32f_C1IMR, 206
 - nppiAddWeighted_8u32f_C1IR, 206
- image_affine_transform
 - nppiGetAffineBound, 1182
 - nppiGetAffineQuad, 1182
 - nppiGetAffineTransform, 1183
 - nppiWarpAffine_16u_AC4R, 1183
 - nppiWarpAffine_16u_C1R, 1184
 - nppiWarpAffine_16u_C3R, 1184
 - nppiWarpAffine_16u_C4R, 1185
 - nppiWarpAffine_16u_P3R, 1185
 - nppiWarpAffine_16u_P4R, 1186
 - nppiWarpAffine_32f_AC4R, 1186
 - nppiWarpAffine_32f_C1R, 1187
 - nppiWarpAffine_32f_C3R, 1187
 - nppiWarpAffine_32f_C4R, 1188
 - nppiWarpAffine_32f_P3R, 1188
 - nppiWarpAffine_32f_P4R, 1189
 - nppiWarpAffine_32s_AC4R, 1189
 - nppiWarpAffine_32s_C1R, 1190
 - nppiWarpAffine_32s_C3R, 1190
 - nppiWarpAffine_32s_C4R, 1191
 - nppiWarpAffine_32s_P3R, 1191
 - nppiWarpAffine_32s_P4R, 1192
 - nppiWarpAffine_64f_AC4R, 1192
 - nppiWarpAffine_64f_C1R, 1193
 - nppiWarpAffine_64f_C3R, 1193
 - nppiWarpAffine_64f_C4R, 1194
 - nppiWarpAffine_64f_P3R, 1194
 - nppiWarpAffine_64f_P4R, 1195
 - nppiWarpAffine_8u_AC4R, 1195
 - nppiWarpAffine_8u_C1R, 1196
 - nppiWarpAffine_8u_C3R, 1196
 - nppiWarpAffine_8u_C4R, 1197
 - nppiWarpAffine_8u_P3R, 1197
 - nppiWarpAffine_8u_P4R, 1198
 - nppiWarpAffineBack_16u_AC4R, 1198
 - nppiWarpAffineBack_16u_C1R, 1199
 - nppiWarpAffineBack_16u_C3R, 1199
 - nppiWarpAffineBack_16u_C4R, 1200
 - nppiWarpAffineBack_16u_P3R, 1200
 - nppiWarpAffineBack_16u_P4R, 1201
 - nppiWarpAffineBack_32f_AC4R, 1201
 - nppiWarpAffineBack_32f_C1R, 1202
 - nppiWarpAffineBack_32f_C3R, 1202
 - nppiWarpAffineBack_32f_C4R, 1203
 - nppiWarpAffineBack_32f_P3R, 1203
 - nppiWarpAffineBack_32f_P4R, 1204
 - nppiWarpAffineBack_32s_AC4R, 1204
 - nppiWarpAffineBack_32s_C1R, 1205
 - nppiWarpAffineBack_32s_C3R, 1205
 - nppiWarpAffineBack_32s_C4R, 1206
 - nppiWarpAffineBack_32s_P3R, 1206
 - nppiWarpAffineBack_32s_P4R, 1207
 - nppiWarpAffineBack_8u_AC4R, 1207
 - nppiWarpAffineBack_8u_C1R, 1208
 - nppiWarpAffineBack_8u_C3R, 1208
 - nppiWarpAffineBack_8u_C4R, 1209
 - nppiWarpAffineBack_8u_P3R, 1209
 - nppiWarpAffineBack_8u_P4R, 1210
 - nppiWarpAffineQuad_16u_AC4R, 1210
 - nppiWarpAffineQuad_16u_C1R, 1211
 - nppiWarpAffineQuad_16u_C3R, 1211
 - nppiWarpAffineQuad_16u_C4R, 1212
 - nppiWarpAffineQuad_16u_P3R, 1212
 - nppiWarpAffineQuad_16u_P4R, 1213
 - nppiWarpAffineQuad_32f_AC4R, 1213
 - nppiWarpAffineQuad_32f_C1R, 1214
 - nppiWarpAffineQuad_32f_C3R, 1214
 - nppiWarpAffineQuad_32f_C4R, 1215
 - nppiWarpAffineQuad_32f_P3R, 1215
 - nppiWarpAffineQuad_32f_P4R, 1216
 - nppiWarpAffineQuad_32s_AC4R, 1216
 - nppiWarpAffineQuad_32s_C1R, 1217
 - nppiWarpAffineQuad_32s_C3R, 1217
 - nppiWarpAffineQuad_32s_C4R, 1218
 - nppiWarpAffineQuad_32s_P3R, 1218
 - nppiWarpAffineQuad_32s_P4R, 1219
 - nppiWarpAffineQuad_8u_AC4R, 1219
 - nppiWarpAffineQuad_8u_C1R, 1220
 - nppiWarpAffineQuad_8u_C3R, 1220
 - nppiWarpAffineQuad_8u_C4R, 1221
 - nppiWarpAffineQuad_8u_P3R, 1221
 - nppiWarpAffineQuad_8u_P4R, 1222
- image_alphacomp
 - nppiAlphaComp_16s_AC1R, 489
 - nppiAlphaComp_16u_AC1R, 489
 - nppiAlphaComp_16u_AC4R, 490
 - nppiAlphaComp_32f_AC1R, 490
 - nppiAlphaComp_32f_AC4R, 491
 - nppiAlphaComp_32s_AC1R, 491
 - nppiAlphaComp_32s_AC4R, 491
 - nppiAlphaComp_32u_AC1R, 492
 - nppiAlphaComp_32u_AC4R, 492

- nppiAlphaComp_8s_AC1R, 493
- nppiAlphaComp_8u_AC1R, 493
- nppiAlphaComp_8u_AC4R, 494
- image_alphacomp
 - nppiAlphaCompC_16s_C1R, 474
 - nppiAlphaCompC_16u_AC4R, 474
 - nppiAlphaCompC_16u_C1R, 475
 - nppiAlphaCompC_16u_C3R, 475
 - nppiAlphaCompC_16u_C4R, 476
 - nppiAlphaCompC_32f_C1R, 476
 - nppiAlphaCompC_32s_C1R, 477
 - nppiAlphaCompC_32u_C1R, 477
 - nppiAlphaCompC_8s_C1R, 478
 - nppiAlphaCompC_8u_AC4R, 478
 - nppiAlphaCompC_8u_C1R, 479
 - nppiAlphaCompC_8u_C3R, 479
 - nppiAlphaCompC_8u_C4R, 480
- image_alphapremul
 - nppiAlphaPremul_16u_AC4IR, 495
 - nppiAlphaPremul_16u_AC4R, 495
 - nppiAlphaPremul_8u_AC4IR, 496
 - nppiAlphaPremul_8u_AC4R, 496
- image_alphapremulc
 - nppiAlphaPremulC_16u_AC4IR, 482
 - nppiAlphaPremulC_16u_AC4R, 482
 - nppiAlphaPremulC_16u_C1IR, 483
 - nppiAlphaPremulC_16u_C1R, 483
 - nppiAlphaPremulC_16u_C3IR, 483
 - nppiAlphaPremulC_16u_C3R, 484
 - nppiAlphaPremulC_16u_C4IR, 484
 - nppiAlphaPremulC_16u_C4R, 484
 - nppiAlphaPremulC_8u_AC4IR, 485
 - nppiAlphaPremulC_8u_AC4R, 485
 - nppiAlphaPremulC_8u_C1IR, 485
 - nppiAlphaPremulC_8u_C1R, 486
 - nppiAlphaPremulC_8u_C3IR, 486
 - nppiAlphaPremulC_8u_C3R, 486
 - nppiAlphaPremulC_8u_C4IR, 487
 - nppiAlphaPremulC_8u_C4R, 487
- image_and
 - nppiAnd_16u_AC4IR, 434
 - nppiAnd_16u_AC4R, 434
 - nppiAnd_16u_C1IR, 434
 - nppiAnd_16u_C1R, 435
 - nppiAnd_16u_C3IR, 435
 - nppiAnd_16u_C3R, 435
 - nppiAnd_16u_C4IR, 436
 - nppiAnd_16u_C4R, 436
 - nppiAnd_32s_AC4IR, 437
 - nppiAnd_32s_AC4R, 437
 - nppiAnd_32s_C1IR, 437
 - nppiAnd_32s_C1R, 438
 - nppiAnd_32s_C3IR, 438
 - nppiAnd_32s_C3R, 438
- nppiAnd_32s_C4IR, 439
- nppiAnd_32s_C4R, 439
- nppiAnd_8u_AC4IR, 440
- nppiAnd_8u_AC4R, 440
- nppiAnd_8u_C1IR, 440
- nppiAnd_8u_C1R, 441
- nppiAnd_8u_C3IR, 441
- nppiAnd_8u_C3R, 441
- nppiAnd_8u_C4IR, 442
- nppiAnd_8u_C4R, 442
- image_andc
 - nppiAndC_16u_AC4IR, 373
 - nppiAndC_16u_AC4R, 373
 - nppiAndC_16u_C1IR, 373
 - nppiAndC_16u_C1R, 374
 - nppiAndC_16u_C3IR, 374
 - nppiAndC_16u_C3R, 374
 - nppiAndC_16u_C4IR, 375
 - nppiAndC_16u_C4R, 375
 - nppiAndC_32s_AC4IR, 375
 - nppiAndC_32s_AC4R, 376
 - nppiAndC_32s_C1IR, 376
 - nppiAndC_32s_C1R, 376
 - nppiAndC_32s_C3IR, 377
 - nppiAndC_32s_C3R, 377
 - nppiAndC_32s_C4IR, 377
 - nppiAndC_32s_C4R, 378
 - nppiAndC_8u_AC4IR, 378
 - nppiAndC_8u_AC4R, 378
 - nppiAndC_8u_C1IR, 379
 - nppiAndC_8u_C1R, 379
 - nppiAndC_8u_C3IR, 379
 - nppiAndC_8u_C3R, 380
 - nppiAndC_8u_C4IR, 380
 - nppiAndC_8u_C4R, 380
- image_color_gamma_correction
 - nppiGammaFwd_8u_AC4IR, 601
 - nppiGammaFwd_8u_AC4R, 601
 - nppiGammaFwd_8u_C3IR, 601
 - nppiGammaFwd_8u_C3R, 602
 - nppiGammaFwd_8u_IP3R, 602
 - nppiGammaFwd_8u_P3R, 602
 - nppiGammaInv_8u_AC4IR, 603
 - nppiGammaInv_8u_AC4R, 603
 - nppiGammaInv_8u_C3IR, 603
 - nppiGammaInv_8u_C3R, 604
 - nppiGammaInv_8u_IP3R, 604
 - nppiGammaInv_8u_P3R, 604
- image_color_model_conversion
 - nppiBGRToCbYCr422_709HDTV_8u_-AC4C2R, 523
 - nppiBGRToCbYCr422_709HDTV_8u_-C3C2R, 523
 - nppiBGRToCbYCr422_8u_AC4C2R, 523

- nppiBGRTtoHLS_8u_AC4P4R, 524
- nppiBGRTtoHLS_8u_AC4R, 524
- nppiBGRTtoHLS_8u_AP4C4R, 524
- nppiBGRTtoHLS_8u_AP4R, 525
- nppiBGRTtoHLS_8u_C3P3R, 525
- nppiBGRTtoHLS_8u_P3C3R, 525
- nppiBGRTtoHLS_8u_P3R, 526
- nppiBGRTtoLab_8u_C3R, 526
- nppiBGRTtoYCbCr411_8u_AC4P3R, 526
- nppiBGRTtoYCbCr411_8u_C3P3R, 527
- nppiBGRTtoYCbCr420_709CSC_8u_-
AC4P3R, 527
- nppiBGRTtoYCbCr420_709CSC_8u_C3P3R,
528
- nppiBGRTtoYCbCr420_709HDTV_8u_-
AC4P3R, 528
- nppiBGRTtoYCbCr420_8u_AC4P3R, 528
- nppiBGRTtoYCbCr420_8u_C3P3R, 529
- nppiBGRTtoYCbCr422_8u_AC4C2R, 529
- nppiBGRTtoYCbCr422_8u_AC4P3R, 530
- nppiBGRTtoYCbCr422_8u_C3C2R, 530
- nppiBGRTtoYCbCr422_8u_C3P3R, 530
- nppiBGRTtoYCrCb420_709CSC_8u_-
AC4P3R, 531
- nppiBGRTtoYCrCb420_709CSC_8u_C3P3R,
531
- nppiBGRTtoYCrCb420_8u_AC4P3R, 532
- nppiBGRTtoYCrCb420_8u_C3P3R, 532
- nppiBGRTtoYUV420_8u_AC4P3R, 532
- nppiCbYCr422ToBGR_709HDTV_8u_-
C2C3R, 533
- nppiCbYCr422ToBGR_709HDTV_8u_-
C2C4R, 533
- nppiCbYCr422ToBGR_8u_C2C4R, 534
- nppiCbYCr422ToRGB_8u_C2C3R, 534
- nppiColorToGray_16s_AC4C1R, 534
- nppiColorToGray_16s_C3C1R, 535
- nppiColorToGray_16u_AC4C1R, 535
- nppiColorToGray_16u_C3C1R, 535
- nppiColorToGray_32f_AC4C1R, 536
- nppiColorToGray_32f_C3C1R, 536
- nppiColorToGray_8u_AC4C1R, 537
- nppiColorToGray_8u_C3C1R, 537
- nppiHLSToBGR_8u_AC4P4R, 537
- nppiHLSToBGR_8u_AC4R, 538
- nppiHLSToBGR_8u_AP4C4R, 538
- nppiHLSToBGR_8u_AP4R, 538
- nppiHLSToBGR_8u_C3P3R, 539
- nppiHLSToBGR_8u_P3C3R, 539
- nppiHLSToBGR_8u_P3R, 539
- nppiHLSToRGB_8u_AC4R, 540
- nppiHLSToRGB_8u_C3R, 540
- nppiHSVToRGB_8u_AC4R, 540
- nppiHSVToRGB_8u_C3R, 541
- nppiLabToBGR_8u_C3R, 541
- nppiLUVToRGB_8u_AC4R, 541
- nppiLUVToRGB_8u_C3R, 542
- nppiRGBToCbYCr422_8u_C3C2R, 542
- nppiRGBToCbYCr422Gamma_8u_C3C2R,
542
- nppiRGBToGray_16s_AC4C1R, 543
- nppiRGBToGray_16s_C3C1R, 543
- nppiRGBToGray_16u_AC4C1R, 543
- nppiRGBToGray_16u_C3C1R, 544
- nppiRGBToGray_32f_AC4C1R, 544
- nppiRGBToGray_32f_C3C1R, 544
- nppiRGBToGray_8u_AC4C1R, 545
- nppiRGBToGray_8u_C3C1R, 545
- nppiRGBToHLS_8u_AC4R, 545
- nppiRGBToHLS_8u_C3R, 546
- nppiRGBToHSV_8u_AC4R, 546
- nppiRGBToHSV_8u_C3R, 546
- nppiRGBToLUV_8u_AC4R, 547
- nppiRGBToLUV_8u_C3R, 547
- nppiRGBToXYZ_8u_AC4R, 547
- nppiRGBToXYZ_8u_C3R, 548
- nppiRGBToYCbCr420_8u_C3P3R, 548
- nppiRGBToYCbCr422_8u_C3C2R, 548
- nppiRGBToYCbCr422_8u_C3P3R, 549
- nppiRGBToYCbCr422_8u_P3C2R, 549
- nppiRGBToYCbCr_8u_AC4P3R, 550
- nppiRGBToYCbCr_8u_AC4R, 550
- nppiRGBToYCbCr_8u_C3P3R, 550
- nppiRGBToYCbCr_8u_C3R, 551
- nppiRGBToYCbCr_8u_P3R, 551
- nppiRGBToYCC_8u_AC4R, 551
- nppiRGBToYCC_8u_C3R, 552
- nppiRGBToYCrCb420_8u_AC4P3R, 552
- nppiRGBToYCrCb422_8u_C3C2R, 552
- nppiRGBToYCrCb422_8u_P3C2R, 553
- nppiRGBToYUV420_8u_C3P3R, 553
- nppiRGBToYUV420_8u_P3R, 553
- nppiRGBToYUV422_8u_C3C2R, 554
- nppiRGBToYUV422_8u_C3P3R, 554
- nppiRGBToYUV422_8u_P3R, 554
- nppiRGBToYUV_8u_AC4P4R, 555
- nppiRGBToYUV_8u_AC4R, 555
- nppiRGBToYUV_8u_C3P3R, 556
- nppiRGBToYUV_8u_C3R, 556
- nppiRGBToYUV_8u_P3R, 556
- nppiXYZToRGB_8u_AC4R, 557
- nppiXYZToRGB_8u_C3R, 557
- nppiYCbCr411ToBGR_8u_P3C3R, 557
- nppiYCbCr411ToBGR_8u_P3C4R, 558
- nppiYCbCr420ToBGR_709CSC_8u_P3C3R,
558
- nppiYCbCr420ToBGR_709HDTV_8u_-
P3C4R, 558

- nppiYCbCr420ToBGR_8u_P3C3R, 559
- nppiYCbCr420ToBGR_8u_P3C4R, 559
- nppiYCbCr420ToRGB_8u_P3C3R, 560
- nppiYCbCr422ToBGR_8u_C2C3R, 560
- nppiYCbCr422ToBGR_8u_C2C4R, 560
- nppiYCbCr422ToBGR_8u_P3C3R, 561
- nppiYCbCr422ToRGB_8u_C2C3R, 561
- nppiYCbCr422ToRGB_8u_C2P3R, 561
- nppiYCbCr422ToRGB_8u_P3C3R, 562
- nppiYCbCrToBGR_709CSC_8u_P3C3R, 562
- nppiYCbCrToBGR_709CSC_8u_P3C4R, 562
- nppiYCbCrToBGR_8u_P3C3R, 563
- nppiYCbCrToBGR_8u_P3C4R, 563
- nppiYCbCrToRGB_8u_AC4R, 564
- nppiYCbCrToRGB_8u_C3R, 564
- nppiYCbCrToRGB_8u_P3C3R, 564
- nppiYCbCrToRGB_8u_P3C4R, 565
- nppiYCbCrToRGB_8u_P3R, 565
- nppiYCCToRGB_8u_AC4R, 565
- nppiYCCToRGB_8u_C3R, 566
- nppiYCrCb420ToRGB_8u_P3C4R, 566
- nppiYCrCb422ToRGB_8u_C2C3R, 566
- nppiYCrCb422ToRGB_8u_C2P3R, 567
- nppiYUV420ToBGR_8u_P3C3R, 567
- nppiYUV420ToRGB_8u_P3AC4R, 567
- nppiYUV420ToRGB_8u_P3C3R, 568
- nppiYUV420ToRGB_8u_P3R, 568
- nppiYUV422ToRGB_8u_C2C3R, 568
- nppiYUV422ToRGB_8u_P3AC4R, 569
- nppiYUV422ToRGB_8u_P3C3R, 569
- nppiYUV422ToRGB_8u_P3R, 569
- nppiYUVToRGB_8u_AC4R, 570
- nppiYUVToRGB_8u_C3R, 570
- nppiYUVToRGB_8u_P3C3R, 570
- nppiYUVToRGB_8u_P3R, 571
- image_color_processing
 - nppiColorTwist32f_16s_AC4IR, 621
 - nppiColorTwist32f_16s_AC4R, 621
 - nppiColorTwist32f_16s_C3IR, 621
 - nppiColorTwist32f_16s_C3R, 622
 - nppiColorTwist32f_16s_IP3R, 622
 - nppiColorTwist32f_16s_P3R, 622
 - nppiColorTwist32f_16u_AC4IR, 623
 - nppiColorTwist32f_16u_AC4R, 623
 - nppiColorTwist32f_16u_C3IR, 624
 - nppiColorTwist32f_16u_C3R, 624
 - nppiColorTwist32f_16u_IP3R, 624
 - nppiColorTwist32f_16u_P3R, 625
 - nppiColorTwist32f_8s_AC4IR, 625
 - nppiColorTwist32f_8s_AC4R, 626
 - nppiColorTwist32f_8s_C3IR, 626
 - nppiColorTwist32f_8s_C3R, 626
 - nppiColorTwist32f_8s_IP3R, 627
 - nppiColorTwist32f_8s_P3R, 627
 - nppiColorTwist32f_8u_AC4IR, 627
 - nppiColorTwist32f_8u_AC4R, 628
 - nppiColorTwist32f_8u_C3IR, 628
 - nppiColorTwist32f_8u_C3R, 629
 - nppiColorTwist32f_8u_IP3R, 629
 - nppiColorTwist32f_8u_P3R, 629
 - nppiColorTwist_32f_AC4IR, 630
 - nppiColorTwist_32f_AC4R, 630
 - nppiColorTwist_32f_C3IR, 631
 - nppiColorTwist_32f_C3R, 631
 - nppiColorTwist_32f_IP3R, 631
 - nppiColorTwist_32f_P3R, 632
 - nppiLUT_16s_AC4IR, 632
 - nppiLUT_16s_AC4R, 633
 - nppiLUT_16s_C1IR, 633
 - nppiLUT_16s_C1R, 634
 - nppiLUT_16s_C3IR, 634
 - nppiLUT_16s_C3R, 635
 - nppiLUT_16s_C4IR, 635
 - nppiLUT_16s_C4R, 636
 - nppiLUT_16u_AC4IR, 636
 - nppiLUT_16u_AC4R, 637
 - nppiLUT_16u_C1IR, 637
 - nppiLUT_16u_C1R, 638
 - nppiLUT_16u_C3IR, 638
 - nppiLUT_16u_C3R, 639
 - nppiLUT_16u_C4IR, 639
 - nppiLUT_16u_C4R, 640
 - nppiLUT_32f_AC4IR, 640
 - nppiLUT_32f_AC4R, 641
 - nppiLUT_32f_C1IR, 641
 - nppiLUT_32f_C1R, 642
 - nppiLUT_32f_C3IR, 642
 - nppiLUT_32f_C3R, 643
 - nppiLUT_32f_C4IR, 643
 - nppiLUT_32f_C4R, 644
 - nppiLUT_8u_AC4IR, 644
 - nppiLUT_8u_AC4R, 645
 - nppiLUT_8u_C1IR, 645
 - nppiLUT_8u_C1R, 646
 - nppiLUT_8u_C3IR, 646
 - nppiLUT_8u_C3R, 647
 - nppiLUT_8u_C4IR, 647
 - nppiLUT_8u_C4R, 648
 - nppiLUT_Cubic_16s_AC4IR, 648
 - nppiLUT_Cubic_16s_AC4R, 649
 - nppiLUT_Cubic_16s_C1IR, 649
 - nppiLUT_Cubic_16s_C1R, 650
 - nppiLUT_Cubic_16s_C3IR, 650
 - nppiLUT_Cubic_16s_C3R, 651
 - nppiLUT_Cubic_16s_C4IR, 651
 - nppiLUT_Cubic_16s_C4R, 652
 - nppiLUT_Cubic_16u_AC4IR, 652
 - nppiLUT_Cubic_16u_AC4R, 653

- nppiLUT_Cubic_16u_C1IR, 653
- nppiLUT_Cubic_16u_C1R, 654
- nppiLUT_Cubic_16u_C3IR, 654
- nppiLUT_Cubic_16u_C3R, 655
- nppiLUT_Cubic_16u_C4IR, 655
- nppiLUT_Cubic_16u_C4R, 656
- nppiLUT_Cubic_32f_AC4IR, 656
- nppiLUT_Cubic_32f_AC4R, 657
- nppiLUT_Cubic_32f_C1IR, 657
- nppiLUT_Cubic_32f_C1R, 658
- nppiLUT_Cubic_32f_C3IR, 658
- nppiLUT_Cubic_32f_C3R, 659
- nppiLUT_Cubic_32f_C4IR, 659
- nppiLUT_Cubic_32f_C4R, 660
- nppiLUT_Cubic_8u_AC4IR, 660
- nppiLUT_Cubic_8u_AC4R, 661
- nppiLUT_Cubic_8u_C1IR, 661
- nppiLUT_Cubic_8u_C1R, 662
- nppiLUT_Cubic_8u_C3IR, 662
- nppiLUT_Cubic_8u_C3R, 663
- nppiLUT_Cubic_8u_C4IR, 663
- nppiLUT_Cubic_8u_C4R, 664
- nppiLUT_Linear_16s_AC4IR, 664
- nppiLUT_Linear_16s_AC4R, 665
- nppiLUT_Linear_16s_C1IR, 665
- nppiLUT_Linear_16s_C1R, 666
- nppiLUT_Linear_16s_C3IR, 666
- nppiLUT_Linear_16s_C3R, 667
- nppiLUT_Linear_16s_C4IR, 667
- nppiLUT_Linear_16s_C4R, 668
- nppiLUT_Linear_16u_AC4IR, 668
- nppiLUT_Linear_16u_AC4R, 669
- nppiLUT_Linear_16u_C1IR, 670
- nppiLUT_Linear_16u_C1R, 670
- nppiLUT_Linear_16u_C3IR, 670
- nppiLUT_Linear_16u_C3R, 671
- nppiLUT_Linear_16u_C4IR, 671
- nppiLUT_Linear_16u_C4R, 672
- nppiLUT_Linear_32f_AC4IR, 672
- nppiLUT_Linear_32f_AC4R, 673
- nppiLUT_Linear_32f_C1IR, 673
- nppiLUT_Linear_32f_C1R, 674
- nppiLUT_Linear_32f_C3IR, 674
- nppiLUT_Linear_32f_C3R, 675
- nppiLUT_Linear_32f_C4IR, 675
- nppiLUT_Linear_32f_C4R, 676
- nppiLUT_Linear_8u_AC4IR, 676
- nppiLUT_Linear_8u_AC4R, 677
- nppiLUT_Linear_8u_C1IR, 678
- nppiLUT_Linear_8u_C1R, 678
- nppiLUT_Linear_8u_C3IR, 679
- nppiLUT_Linear_8u_C3R, 679
- nppiLUT_Linear_8u_C4IR, 680
- nppiLUT_Linear_8u_C4R, 680
- nppiLUTPalette_16u24u_C1R, 681
- nppiLUTPalette_16u32u_C1R, 681
- nppiLUTPalette_16u8u_C1R, 682
- nppiLUTPalette_16u_AC4R, 682
- nppiLUTPalette_16u_C1R, 683
- nppiLUTPalette_16u_C3R, 683
- nppiLUTPalette_16u_C4R, 684
- nppiLUTPalette_8u24u_C1R, 684
- nppiLUTPalette_8u32u_C1R, 685
- nppiLUTPalette_8u_AC4R, 685
- nppiLUTPalette_8u_C1R, 686
- nppiLUTPalette_8u_C3R, 686
- nppiLUTPalette_8u_C4R, 687
- nppiLUTPaletteSwap_16u_C3A0C4R, 687
- nppiLUTPaletteSwap_8u_C3A0C4R, 688
- image_color_sampling_format_conversion
 - nppiCbYCr422ToYCbCr411_8u_C2P3R, 579
 - nppiCbYCr422ToYCbCr420_8u_C2P2R, 580
 - nppiCbYCr422ToYCbCr420_8u_C2P3R, 580
 - nppiCbYCr422ToYCbCr422_8u_C2P3R, 580
 - nppiCbYCr422ToYCbCr422_8u_C2R, 581
 - nppiCbYCr422ToYCbCr420_8u_C2P3R, 581
 - nppiYCbCr411_8u_P2P3R, 582
 - nppiYCbCr411_8u_P3P2R, 582
 - nppiYCbCr411ToYCbCr420_8u_P2P3R, 582
 - nppiYCbCr411ToYCbCr420_8u_P3P2R, 583
 - nppiYCbCr411ToYCbCr420_8u_P3R, 583
 - nppiYCbCr411ToYCbCr422_8u_P2C2R, 584
 - nppiYCbCr411ToYCbCr422_8u_P2P3R, 584
 - nppiYCbCr411ToYCbCr422_8u_P3C2R, 584
 - nppiYCbCr411ToYCbCr422_8u_P3R, 585
 - nppiYCbCr411ToYCbCr420_8u_P2P3R, 585
 - nppiYCbCr411ToYCbCr422_8u_P3C2R, 586
 - nppiYCbCr411ToYCbCr422_8u_P3R, 586
 - nppiYCbCr420_8u_P2P3R, 586
 - nppiYCbCr420_8u_P3P2R, 587
 - nppiYCbCr420ToCbYCr422_8u_P2C2R, 587
 - nppiYCbCr420ToYCbCr411_8u_P2P3R, 588
 - nppiYCbCr420ToYCbCr411_8u_P3P2R, 588
 - nppiYCbCr420ToYCbCr422_8u_P2C2R, 589
 - nppiYCbCr420ToYCbCr422_8u_P2P3R, 589
 - nppiYCbCr420ToYCbCr422_8u_P3R, 589
 - nppiYCbCr420ToYCbCr420_8u_P2P3R, 590
 - nppiYCbCr422_8u_C2P3R, 590
 - nppiYCbCr422_8u_P3C2R, 591
 - nppiYCbCr422ToCbYCr422_8u_C2R, 591
 - nppiYCbCr422ToYCbCr411_8u_C2P2R, 591
 - nppiYCbCr422ToYCbCr411_8u_C2P3R, 592
 - nppiYCbCr422ToYCbCr411_8u_P3P2R, 592
 - nppiYCbCr422ToYCbCr411_8u_P3R, 593
 - nppiYCbCr422ToYCbCr420_8u_C2P2R, 593
 - nppiYCbCr422ToYCbCr420_8u_C2P3R, 594
 - nppiYCbCr422ToYCbCr420_8u_P3P2R, 594
 - nppiYCbCr422ToYCbCr420_8u_P3R, 594

- nppiYCbCr422ToYCrCb420_8u_C2P3R, 595
- nppiYCbCr422ToYCrCb422_8u_C2R, 595
- nppiYCbCr422ToYCrCb422_8u_P3C2R, 596
- nppiYCrCb420ToCbYCr422_8u_P3C2R, 596
- nppiYCrCb420ToYCbCr411_8u_P3P2R, 596
- nppiYCrCb420ToYCbCr420_8u_P3P2R, 597
- nppiYCrCb420ToYCbCr422_8u_P3C2R, 597
- nppiYCrCb420ToYCbCr422_8u_P3R, 598
- nppiYCrCb422ToYCbCr411_8u_C2P3R, 598
- nppiYCrCb422ToYCbCr420_8u_C2P3R, 599
- nppiYCrCb422ToYCbCr422_8u_C2P3R, 599
- image_compare_operations
 - nppiCompare_16s_AC4R, 1970
 - nppiCompare_16s_C1R, 1971
 - nppiCompare_16s_C3R, 1971
 - nppiCompare_16s_C4R, 1971
 - nppiCompare_16u_AC4R, 1972
 - nppiCompare_16u_C1R, 1972
 - nppiCompare_16u_C3R, 1973
 - nppiCompare_16u_C4R, 1973
 - nppiCompare_32f_AC4R, 1974
 - nppiCompare_32f_C1R, 1974
 - nppiCompare_32f_C3R, 1975
 - nppiCompare_32f_C4R, 1975
 - nppiCompare_8u_AC4R, 1976
 - nppiCompare_8u_C1R, 1976
 - nppiCompare_8u_C3R, 1977
 - nppiCompare_8u_C4R, 1977
 - nppiCompareC_16s_AC4R, 1978
 - nppiCompareC_16s_C1R, 1978
 - nppiCompareC_16s_C3R, 1979
 - nppiCompareC_16s_C4R, 1979
 - nppiCompareC_16u_AC4R, 1980
 - nppiCompareC_16u_C1R, 1980
 - nppiCompareC_16u_C3R, 1980
 - nppiCompareC_16u_C4R, 1981
 - nppiCompareC_32f_AC4R, 1981
 - nppiCompareC_32f_C1R, 1982
 - nppiCompareC_32f_C3R, 1982
 - nppiCompareC_32f_C4R, 1983
 - nppiCompareC_8u_AC4R, 1983
 - nppiCompareC_8u_C1R, 1983
 - nppiCompareC_8u_C3R, 1984
 - nppiCompareC_8u_C4R, 1984
 - nppiCompareEqualEps_32f_AC4R, 1985
 - nppiCompareEqualEps_32f_C1R, 1985
 - nppiCompareEqualEps_32f_C3R, 1986
 - nppiCompareEqualEps_32f_C4R, 1986
 - nppiCompareEqualEpsC_32f_AC4R, 1987
 - nppiCompareEqualEpsC_32f_C1R, 1987
 - nppiCompareEqualEpsC_32f_C3R, 1988
 - nppiCompareEqualEpsC_32f_C4R, 1988
- image_complement_color_key
 - nppiAlphaCompColorKey_8u_AC4R, 606
 - nppiCompColorKey_8u_C1R, 607
 - nppiCompColorKey_8u_C3R, 607
 - nppiCompColorKey_8u_C4R, 608
- image_compression
 - nppiDecodeHuffmanScanHost_JPEG_8u16s_P1R, 690
 - nppiDecodeHuffmanScanHost_JPEG_8u16s_P3R, 691
- image_convert
 - nppiConvert_16s16u_C1Rs, 792
 - nppiConvert_16s32f_AC4R, 792
 - nppiConvert_16s32f_C1R, 793
 - nppiConvert_16s32f_C3R, 793
 - nppiConvert_16s32f_C4R, 793
 - nppiConvert_16s32s_AC4R, 794
 - nppiConvert_16s32s_C1R, 794
 - nppiConvert_16s32s_C3R, 794
 - nppiConvert_16s32s_C4R, 795
 - nppiConvert_16s32u_C1Rs, 795
 - nppiConvert_16s8s_C1RSfs, 795
 - nppiConvert_16s8u_AC4R, 796
 - nppiConvert_16s8u_C1R, 796
 - nppiConvert_16s8u_C3R, 796
 - nppiConvert_16s8u_C4R, 797
 - nppiConvert_16u16s_C1RSfs, 797
 - nppiConvert_16u32f_AC4R, 797
 - nppiConvert_16u32f_C1R, 798
 - nppiConvert_16u32f_C3R, 798
 - nppiConvert_16u32f_C4R, 798
 - nppiConvert_16u32s_AC4R, 799
 - nppiConvert_16u32s_C1R, 799
 - nppiConvert_16u32s_C3R, 799
 - nppiConvert_16u32s_C4R, 800
 - nppiConvert_16u32u_C1R, 800
 - nppiConvert_16u8s_C1RSfs, 800
 - nppiConvert_16u8u_AC4R, 801
 - nppiConvert_16u8u_C1R, 801
 - nppiConvert_16u8u_C3R, 801
 - nppiConvert_16u8u_C4R, 802
 - nppiConvert_32f16s_AC4R, 802
 - nppiConvert_32f16s_C1R, 802
 - nppiConvert_32f16s_C1RSfs, 803
 - nppiConvert_32f16s_C3R, 803
 - nppiConvert_32f16s_C4R, 804
 - nppiConvert_32f16u_AC4R, 804
 - nppiConvert_32f16u_C1R, 804
 - nppiConvert_32f16u_C1RSfs, 805
 - nppiConvert_32f16u_C3R, 805
 - nppiConvert_32f16u_C4R, 806
 - nppiConvert_32f32s_C1RSfs, 806
 - nppiConvert_32f32u_C1RSfs, 806
 - nppiConvert_32f8s_AC4R, 807
 - nppiConvert_32f8s_C1R, 807
 - nppiConvert_32f8s_C1RSfs, 808

- nppiConvert_32f8s_C3R, 808
- nppiConvert_32f8s_C4R, 808
- nppiConvert_32f8u_AC4R, 809
- nppiConvert_32f8u_C1R, 809
- nppiConvert_32f8u_C1RSfs, 809
- nppiConvert_32f8u_C3R, 810
- nppiConvert_32f8u_C4R, 810
- nppiConvert_32s16s_C1RSfs, 811
- nppiConvert_32s16u_C1RSfs, 811
- nppiConvert_32s32f_C1R, 811
- nppiConvert_32s32u_C1Rs, 812
- nppiConvert_32s8s_AC4R, 812
- nppiConvert_32s8s_C1R, 812
- nppiConvert_32s8s_C3R, 813
- nppiConvert_32s8s_C4R, 813
- nppiConvert_32s8u_AC4R, 813
- nppiConvert_32s8u_C1R, 814
- nppiConvert_32s8u_C3R, 814
- nppiConvert_32s8u_C4R, 814
- nppiConvert_32u16s_C1RSfs, 815
- nppiConvert_32u16u_C1RSfs, 815
- nppiConvert_32u32f_C1R, 816
- nppiConvert_32u32s_C1RSfs, 816
- nppiConvert_32u8s_C1RSfs, 816
- nppiConvert_32u8u_C1RSfs, 817
- nppiConvert_8s16s_C1R, 817
- nppiConvert_8s16u_C1Rs, 818
- nppiConvert_8s32f_AC4R, 818
- nppiConvert_8s32f_C1R, 818
- nppiConvert_8s32f_C3R, 819
- nppiConvert_8s32f_C4R, 819
- nppiConvert_8s32s_AC4R, 819
- nppiConvert_8s32s_C1R, 820
- nppiConvert_8s32s_C3R, 820
- nppiConvert_8s32s_C4R, 820
- nppiConvert_8s32u_C1Rs, 821
- nppiConvert_8s8u_C1Rs, 821
- nppiConvert_8u16s_AC4R, 821
- nppiConvert_8u16s_C1R, 822
- nppiConvert_8u16s_C3R, 822
- nppiConvert_8u16s_C4R, 822
- nppiConvert_8u16u_AC4R, 823
- nppiConvert_8u16u_C1R, 823
- nppiConvert_8u16u_C3R, 823
- nppiConvert_8u16u_C4R, 824
- nppiConvert_8u32f_AC4R, 824
- nppiConvert_8u32f_C1R, 824
- nppiConvert_8u32f_C3R, 825
- nppiConvert_8u32f_C4R, 825
- nppiConvert_8u32s_AC4R, 825
- nppiConvert_8u32s_C1R, 826
- nppiConvert_8u32s_C3R, 826
- nppiConvert_8u32s_C4R, 826
- nppiConvert_8u8s_C1RSfs, 827
- image_convolution
 - nppiFilter32f_16s_AC4R, 1013
 - nppiFilter32f_16s_C1R, 1013
 - nppiFilter32f_16s_C3R, 1013
 - nppiFilter32f_16s_C4R, 1014
 - nppiFilter32f_16u_AC4R, 1014
 - nppiFilter32f_16u_C1R, 1015
 - nppiFilter32f_16u_C3R, 1015
 - nppiFilter32f_16u_C4R, 1016
 - nppiFilter32f_32s_AC4R, 1016
 - nppiFilter32f_32s_C1R, 1017
 - nppiFilter32f_32s_C3R, 1017
 - nppiFilter32f_32s_C4R, 1018
 - nppiFilter32f_8s16s_AC4R, 1018
 - nppiFilter32f_8s16s_C1R, 1019
 - nppiFilter32f_8s16s_C3R, 1019
 - nppiFilter32f_8s16s_C4R, 1020
 - nppiFilter32f_8s_AC4R, 1020
 - nppiFilter32f_8s_C1R, 1021
 - nppiFilter32f_8s_C3R, 1021
 - nppiFilter32f_8s_C4R, 1022
 - nppiFilter32f_8u16s_AC4R, 1022
 - nppiFilter32f_8u16s_C1R, 1023
 - nppiFilter32f_8u16s_C3R, 1023
 - nppiFilter32f_8u16s_C4R, 1024
 - nppiFilter32f_8u_AC4R, 1024
 - nppiFilter32f_8u_C1R, 1025
 - nppiFilter32f_8u_C3R, 1025
 - nppiFilter32f_8u_C4R, 1026
 - nppiFilter_16s_AC4R, 1026
 - nppiFilter_16s_C1R, 1027
 - nppiFilter_16s_C3R, 1027
 - nppiFilter_16s_C4R, 1028
 - nppiFilter_16u_AC4R, 1028
 - nppiFilter_16u_C1R, 1029
 - nppiFilter_16u_C3R, 1029
 - nppiFilter_16u_C4R, 1030
 - nppiFilter_32f_AC4R, 1030
 - nppiFilter_32f_C1R, 1031
 - nppiFilter_32f_C3R, 1031
 - nppiFilter_32f_C4R, 1032
 - nppiFilter_64f_C1R, 1032
 - nppiFilter_8u_AC4R, 1033
 - nppiFilter_8u_C1R, 1033
 - nppiFilter_8u_C3R, 1034
 - nppiFilter_8u_C4R, 1034
- image_copy
 - nppiCopy_16s_AC4MR, 746
 - nppiCopy_16s_AC4R, 747
 - nppiCopy_16s_C1C3R, 747
 - nppiCopy_16s_C1C4R, 747
 - nppiCopy_16s_C1MR, 748
 - nppiCopy_16s_C1R, 748
 - nppiCopy_16s_C3C1R, 748

- nppiCopy_16s_C3CR, 749
- nppiCopy_16s_C3MR, 749
- nppiCopy_16s_C3P3R, 749
- nppiCopy_16s_C3R, 750
- nppiCopy_16s_C4C1R, 750
- nppiCopy_16s_C4CR, 750
- nppiCopy_16s_C4MR, 751
- nppiCopy_16s_C4P4R, 751
- nppiCopy_16s_C4R, 751
- nppiCopy_16s_P3C3R, 752
- nppiCopy_16s_P4C4R, 752
- nppiCopy_16sc_AC4R, 752
- nppiCopy_16sc_C1R, 753
- nppiCopy_16sc_C2R, 753
- nppiCopy_16sc_C3R, 753
- nppiCopy_16sc_C4R, 754
- nppiCopy_16u_AC4MR, 754
- nppiCopy_16u_AC4R, 754
- nppiCopy_16u_C1C3R, 755
- nppiCopy_16u_C1C4R, 755
- nppiCopy_16u_C1MR, 755
- nppiCopy_16u_C1R, 756
- nppiCopy_16u_C3C1R, 756
- nppiCopy_16u_C3CR, 756
- nppiCopy_16u_C3MR, 757
- nppiCopy_16u_C3P3R, 757
- nppiCopy_16u_C3R, 757
- nppiCopy_16u_C4C1R, 758
- nppiCopy_16u_C4CR, 758
- nppiCopy_16u_C4MR, 758
- nppiCopy_16u_C4P4R, 759
- nppiCopy_16u_C4R, 759
- nppiCopy_16u_P3C3R, 759
- nppiCopy_16u_P4C4R, 760
- nppiCopy_32f_AC4MR, 760
- nppiCopy_32f_AC4R, 760
- nppiCopy_32f_C1C3R, 761
- nppiCopy_32f_C1C4R, 761
- nppiCopy_32f_C1MR, 761
- nppiCopy_32f_C1R, 762
- nppiCopy_32f_C3C1R, 762
- nppiCopy_32f_C3CR, 762
- nppiCopy_32f_C3MR, 763
- nppiCopy_32f_C3P3R, 763
- nppiCopy_32f_C3R, 763
- nppiCopy_32f_C4C1R, 764
- nppiCopy_32f_C4CR, 764
- nppiCopy_32f_C4MR, 764
- nppiCopy_32f_C4P4R, 765
- nppiCopy_32f_C4R, 765
- nppiCopy_32f_P3C3R, 765
- nppiCopy_32f_P4C4R, 766
- nppiCopy_32fc_AC4R, 766
- nppiCopy_32fc_C1R, 766
- nppiCopy_32fc_C2R, 767
- nppiCopy_32fc_C3R, 767
- nppiCopy_32fc_C4R, 767
- nppiCopy_32s_AC4MR, 768
- nppiCopy_32s_AC4R, 768
- nppiCopy_32s_C1C3R, 768
- nppiCopy_32s_C1C4R, 769
- nppiCopy_32s_C1MR, 769
- nppiCopy_32s_C1R, 769
- nppiCopy_32s_C3C1R, 770
- nppiCopy_32s_C3CR, 770
- nppiCopy_32s_C3MR, 770
- nppiCopy_32s_C3P3R, 771
- nppiCopy_32s_C3R, 771
- nppiCopy_32s_C4C1R, 771
- nppiCopy_32s_C4CR, 772
- nppiCopy_32s_C4MR, 772
- nppiCopy_32s_C4P4R, 772
- nppiCopy_32s_C4R, 773
- nppiCopy_32s_P3C3R, 773
- nppiCopy_32s_P4C4R, 773
- nppiCopy_32sc_AC4R, 774
- nppiCopy_32sc_C1R, 774
- nppiCopy_32sc_C2R, 774
- nppiCopy_32sc_C3R, 775
- nppiCopy_32sc_C4R, 775
- nppiCopy_8s_AC4R, 775
- nppiCopy_8s_C1R, 776
- nppiCopy_8s_C2R, 776
- nppiCopy_8s_C3R, 776
- nppiCopy_8s_C4R, 777
- nppiCopy_8u_AC4MR, 777
- nppiCopy_8u_AC4R, 777
- nppiCopy_8u_C1C3R, 778
- nppiCopy_8u_C1C4R, 778
- nppiCopy_8u_C1MR, 778
- nppiCopy_8u_C1R, 779
- nppiCopy_8u_C3C1R, 779
- nppiCopy_8u_C3CR, 779
- nppiCopy_8u_C3MR, 780
- nppiCopy_8u_C3P3R, 780
- nppiCopy_8u_C3R, 780
- nppiCopy_8u_C4C1R, 781
- nppiCopy_8u_C4CR, 781
- nppiCopy_8u_C4MR, 781
- nppiCopy_8u_C4P4R, 782
- nppiCopy_8u_C4R, 782
- nppiCopy_8u_P3C3R, 782
- nppiCopy_8u_P4C4R, 783
- image_copy_constant_border
 - nppiCopyConstBorder_16s_AC4R, 845
 - nppiCopyConstBorder_16s_C1R, 845
 - nppiCopyConstBorder_16s_C3R, 846
 - nppiCopyConstBorder_16s_C4R, 846

- nppiCopyConstBorder_16u_AC4R, 847
- nppiCopyConstBorder_16u_C1R, 847
- nppiCopyConstBorder_16u_C3R, 848
- nppiCopyConstBorder_16u_C4R, 848
- nppiCopyConstBorder_32f_AC4R, 849
- nppiCopyConstBorder_32f_C1R, 849
- nppiCopyConstBorder_32f_C3R, 850
- nppiCopyConstBorder_32f_C4R, 850
- nppiCopyConstBorder_32s_AC4R, 851
- nppiCopyConstBorder_32s_C1R, 851
- nppiCopyConstBorder_32s_C3R, 852
- nppiCopyConstBorder_32s_C4R, 852
- nppiCopyConstBorder_8u_AC4R, 853
- nppiCopyConstBorder_8u_C1R, 853
- nppiCopyConstBorder_8u_C3R, 854
- nppiCopyConstBorder_8u_C4R, 854
- image_copy_replicate_border
 - nppiCopyReplicateBorder_16s_AC4R, 858
 - nppiCopyReplicateBorder_16s_C1R, 858
 - nppiCopyReplicateBorder_16s_C3R, 859
 - nppiCopyReplicateBorder_16s_C4R, 859
 - nppiCopyReplicateBorder_16u_AC4R, 860
 - nppiCopyReplicateBorder_16u_C1R, 860
 - nppiCopyReplicateBorder_16u_C3R, 861
 - nppiCopyReplicateBorder_16u_C4R, 861
 - nppiCopyReplicateBorder_32f_AC4R, 861
 - nppiCopyReplicateBorder_32f_C1R, 862
 - nppiCopyReplicateBorder_32f_C3R, 862
 - nppiCopyReplicateBorder_32f_C4R, 863
 - nppiCopyReplicateBorder_32s_AC4R, 863
 - nppiCopyReplicateBorder_32s_C1R, 864
 - nppiCopyReplicateBorder_32s_C3R, 864
 - nppiCopyReplicateBorder_32s_C4R, 865
 - nppiCopyReplicateBorder_8u_AC4R, 865
 - nppiCopyReplicateBorder_8u_C1R, 866
 - nppiCopyReplicateBorder_8u_C3R, 866
 - nppiCopyReplicateBorder_8u_C4R, 867
- image_copy_sub_pixel
 - nppiCopySubpix_16s_AC4R, 882
 - nppiCopySubpix_16s_C1R, 883
 - nppiCopySubpix_16s_C3R, 883
 - nppiCopySubpix_16s_C4R, 884
 - nppiCopySubpix_16u_AC4R, 884
 - nppiCopySubpix_16u_C1R, 884
 - nppiCopySubpix_16u_C3R, 885
 - nppiCopySubpix_16u_C4R, 885
 - nppiCopySubpix_32f_AC4R, 886
 - nppiCopySubpix_32f_C1R, 886
 - nppiCopySubpix_32f_C3R, 886
 - nppiCopySubpix_32f_C4R, 887
 - nppiCopySubpix_32s_AC4R, 887
 - nppiCopySubpix_32s_C1R, 888
 - nppiCopySubpix_32s_C3R, 888
 - nppiCopySubpix_32s_C4R, 889
- nppiCopySubpix_8u_AC4R, 889
- nppiCopySubpix_8u_C1R, 889
- nppiCopySubpix_8u_C3R, 890
- nppiCopySubpix_8u_C4R, 890
- image_copy_wrap_border
 - nppiCopyWrapBorder_16s_AC4R, 870
 - nppiCopyWrapBorder_16s_C1R, 870
 - nppiCopyWrapBorder_16s_C3R, 871
 - nppiCopyWrapBorder_16s_C4R, 871
 - nppiCopyWrapBorder_16u_AC4R, 872
 - nppiCopyWrapBorder_16u_C1R, 872
 - nppiCopyWrapBorder_16u_C3R, 873
 - nppiCopyWrapBorder_16u_C4R, 873
 - nppiCopyWrapBorder_32f_AC4R, 874
 - nppiCopyWrapBorder_32f_C1R, 874
 - nppiCopyWrapBorder_32f_C3R, 875
 - nppiCopyWrapBorder_32f_C4R, 875
 - nppiCopyWrapBorder_32s_AC4R, 876
 - nppiCopyWrapBorder_32s_C1R, 876
 - nppiCopyWrapBorder_32s_C3R, 877
 - nppiCopyWrapBorder_32s_C4R, 877
 - nppiCopyWrapBorder_8u_AC4R, 878
 - nppiCopyWrapBorder_8u_C1R, 878
 - nppiCopyWrapBorder_8u_C3R, 879
 - nppiCopyWrapBorder_8u_C4R, 879
- image_count_in_range
 - nppiCountInRange_32f_AC4R, 1668
 - nppiCountInRange_32f_C1R, 1668
 - nppiCountInRange_32f_C3R, 1669
 - nppiCountInRange_8u_AC4R, 1669
 - nppiCountInRange_8u_C1R, 1670
 - nppiCountInRange_8u_C3R, 1670
 - nppiCountInRangeGetBufferSize_32f_-AC4R, 1671
 - nppiCountInRangeGetBufferSize_32f_-C1R, 1671
 - nppiCountInRangeGetBufferSize_32f_-C3R, 1671
 - nppiCountInRangeGetBufferSize_8u_-AC4R, 1671
 - nppiCountInRangeGetBufferSize_8u_-C1R, 1672
 - nppiCountInRangeGetBufferSize_8u_-C3R, 1672
- image_dilate
 - nppiDilate_16u_AC4R, 1274
 - nppiDilate_16u_C1R, 1274
 - nppiDilate_16u_C3R, 1275
 - nppiDilate_16u_C4R, 1275
 - nppiDilate_32f_AC4R, 1275
 - nppiDilate_32f_C1R, 1276
 - nppiDilate_32f_C3R, 1276
 - nppiDilate_32f_C4R, 1277
 - nppiDilate_8u_AC4R, 1277

- nppiDilate_8u_C1R, 1278
- nppiDilate_8u_C3R, 1278
- nppiDilate_8u_C4R, 1278
- image_dilate_3x3
 - nppiDilate3x3_16u_AC4R, 1288
 - nppiDilate3x3_16u_C1R, 1288
 - nppiDilate3x3_16u_C3R, 1288
 - nppiDilate3x3_16u_C4R, 1289
 - nppiDilate3x3_32f_AC4R, 1289
 - nppiDilate3x3_32f_C1R, 1289
 - nppiDilate3x3_32f_C3R, 1290
 - nppiDilate3x3_32f_C4R, 1290
 - nppiDilate3x3_64f_C1R, 1290
 - nppiDilate3x3_8u_AC4R, 1291
 - nppiDilate3x3_8u_C1R, 1291
 - nppiDilate3x3_8u_C3R, 1291
 - nppiDilate3x3_8u_C4R, 1292
- image_div
 - nppiDiv_16s_AC4IRSfs, 281
 - nppiDiv_16s_AC4RSfs, 281
 - nppiDiv_16s_C1IRSfs, 282
 - nppiDiv_16s_C1RSfs, 282
 - nppiDiv_16s_C3IRSfs, 282
 - nppiDiv_16s_C3RSfs, 283
 - nppiDiv_16s_C4IRSfs, 283
 - nppiDiv_16s_C4RSfs, 284
 - nppiDiv_16sc_AC4IRSfs, 284
 - nppiDiv_16sc_AC4RSfs, 284
 - nppiDiv_16sc_C1IRSfs, 285
 - nppiDiv_16sc_C1RSfs, 285
 - nppiDiv_16sc_C3IRSfs, 286
 - nppiDiv_16sc_C3RSfs, 286
 - nppiDiv_16u_AC4IRSfs, 287
 - nppiDiv_16u_AC4RSfs, 287
 - nppiDiv_16u_C1IRSfs, 287
 - nppiDiv_16u_C1RSfs, 288
 - nppiDiv_16u_C3IRSfs, 288
 - nppiDiv_16u_C3RSfs, 289
 - nppiDiv_16u_C4IRSfs, 289
 - nppiDiv_16u_C4RSfs, 289
 - nppiDiv_32f_AC4IR, 290
 - nppiDiv_32f_AC4R, 290
 - nppiDiv_32f_C1IR, 291
 - nppiDiv_32f_C1R, 291
 - nppiDiv_32f_C3IR, 291
 - nppiDiv_32f_C3R, 292
 - nppiDiv_32f_C4IR, 292
 - nppiDiv_32f_C4R, 292
 - nppiDiv_32fc_AC4IR, 293
 - nppiDiv_32fc_AC4R, 293
 - nppiDiv_32fc_C1IR, 294
 - nppiDiv_32fc_C1R, 294
 - nppiDiv_32fc_C3IR, 294
 - nppiDiv_32fc_C3R, 295
 - nppiDiv_32fc_C4IR, 295
 - nppiDiv_32fc_C4R, 295
 - nppiDiv_32s_C1IRSfs, 296
 - nppiDiv_32s_C1R, 296
 - nppiDiv_32s_C1RSfs, 297
 - nppiDiv_32s_C3IRSfs, 297
 - nppiDiv_32s_C3RSfs, 297
 - nppiDiv_32sc_AC4IRSfs, 298
 - nppiDiv_32sc_AC4RSfs, 298
 - nppiDiv_32sc_C1IRSfs, 299
 - nppiDiv_32sc_C1RSfs, 299
 - nppiDiv_32sc_C3IRSfs, 300
 - nppiDiv_32sc_C3RSfs, 300
 - nppiDiv_8u_AC4IRSfs, 300
 - nppiDiv_8u_AC4RSfs, 301
 - nppiDiv_8u_C1IRSfs, 301
 - nppiDiv_8u_C1RSfs, 302
 - nppiDiv_8u_C3IRSfs, 302
 - nppiDiv_8u_C3RSfs, 302
 - nppiDiv_8u_C4IRSfs, 303
 - nppiDiv_8u_C4RSfs, 303
- image_divc
 - nppiDivC_16s_AC4IRSfs, 145
 - nppiDivC_16s_AC4RSfs, 145
 - nppiDivC_16s_C1IRSfs, 145
 - nppiDivC_16s_C1RSfs, 146
 - nppiDivC_16s_C3IRSfs, 146
 - nppiDivC_16s_C3RSfs, 146
 - nppiDivC_16s_C4IRSfs, 147
 - nppiDivC_16s_C4RSfs, 147
 - nppiDivC_16sc_AC4IRSfs, 148
 - nppiDivC_16sc_AC4RSfs, 148
 - nppiDivC_16sc_C1IRSfs, 148
 - nppiDivC_16sc_C1RSfs, 149
 - nppiDivC_16sc_C3IRSfs, 149
 - nppiDivC_16sc_C3RSfs, 150
 - nppiDivC_16u_AC4IRSfs, 150
 - nppiDivC_16u_AC4RSfs, 150
 - nppiDivC_16u_C1IRSfs, 151
 - nppiDivC_16u_C1RSfs, 151
 - nppiDivC_16u_C3IRSfs, 152
 - nppiDivC_16u_C3RSfs, 152
 - nppiDivC_16u_C4IRSfs, 152
 - nppiDivC_16u_C4RSfs, 153
 - nppiDivC_32f_AC4IR, 153
 - nppiDivC_32f_AC4R, 153
 - nppiDivC_32f_C1IR, 154
 - nppiDivC_32f_C1R, 154
 - nppiDivC_32f_C3IR, 154
 - nppiDivC_32f_C3R, 155
 - nppiDivC_32f_C4IR, 155
 - nppiDivC_32f_C4R, 155
 - nppiDivC_32fc_AC4IR, 156
 - nppiDivC_32fc_AC4R, 156

- nppiDivC_32fc_C1IR, 156
- nppiDivC_32fc_C1R, 157
- nppiDivC_32fc_C3IR, 157
- nppiDivC_32fc_C3R, 157
- nppiDivC_32fc_C4IR, 158
- nppiDivC_32fc_C4R, 158
- nppiDivC_32s_C1IRSfs, 159
- nppiDivC_32s_C1RSfs, 159
- nppiDivC_32s_C3IRSfs, 159
- nppiDivC_32s_C3RSfs, 160
- nppiDivC_32sc_AC4IRSfs, 160
- nppiDivC_32sc_AC4RSfs, 160
- nppiDivC_32sc_C1IRSfs, 161
- nppiDivC_32sc_C1RSfs, 161
- nppiDivC_32sc_C3IRSfs, 162
- nppiDivC_32sc_C3RSfs, 162
- nppiDivC_8u_AC4IRSfs, 162
- nppiDivC_8u_AC4RSfs, 163
- nppiDivC_8u_C1IRSfs, 163
- nppiDivC_8u_C1RSfs, 164
- nppiDivC_8u_C3IRSfs, 164
- nppiDivC_8u_C3RSfs, 164
- nppiDivC_8u_C4IRSfs, 165
- nppiDivC_8u_C4RSfs, 165
- image_divround
 - nppiDiv_Round_16s_AC4IRSfs, 307
 - nppiDiv_Round_16s_AC4RSfs, 308
 - nppiDiv_Round_16s_C1IRSfs, 308
 - nppiDiv_Round_16s_C1RSfs, 309
 - nppiDiv_Round_16s_C3IRSfs, 309
 - nppiDiv_Round_16s_C3RSfs, 309
 - nppiDiv_Round_16s_C4IRSfs, 310
 - nppiDiv_Round_16s_C4RSfs, 310
 - nppiDiv_Round_16u_AC4IRSfs, 311
 - nppiDiv_Round_16u_AC4RSfs, 311
 - nppiDiv_Round_16u_C1IRSfs, 312
 - nppiDiv_Round_16u_C1RSfs, 312
 - nppiDiv_Round_16u_C3IRSfs, 313
 - nppiDiv_Round_16u_C3RSfs, 313
 - nppiDiv_Round_16u_C4IRSfs, 314
 - nppiDiv_Round_16u_C4RSfs, 314
 - nppiDiv_Round_8u_AC4IRSfs, 315
 - nppiDiv_Round_8u_AC4RSfs, 315
 - nppiDiv_Round_8u_C1IRSfs, 316
 - nppiDiv_Round_8u_C1RSfs, 316
 - nppiDiv_Round_8u_C3IRSfs, 317
 - nppiDiv_Round_8u_C3RSfs, 317
 - nppiDiv_Round_8u_C4IRSfs, 318
 - nppiDiv_Round_8u_C4RSfs, 318
- image_dot_prod
 - nppiDotProd_16s64f_AC4R, 1646
 - nppiDotProd_16s64f_C1R, 1646
 - nppiDotProd_16s64f_C3R, 1647
 - nppiDotProd_16s64f_C4R, 1647
 - nppiDotProd_16u64f_AC4R, 1648
 - nppiDotProd_16u64f_C1R, 1648
 - nppiDotProd_16u64f_C3R, 1649
 - nppiDotProd_16u64f_C4R, 1649
 - nppiDotProd_32f64f_AC4R, 1649
 - nppiDotProd_32f64f_C1R, 1650
 - nppiDotProd_32f64f_C3R, 1650
 - nppiDotProd_32f64f_C4R, 1651
 - nppiDotProd_32s64f_AC4R, 1651
 - nppiDotProd_32s64f_C1R, 1652
 - nppiDotProd_32s64f_C3R, 1652
 - nppiDotProd_32s64f_C4R, 1652
 - nppiDotProd_32u64f_AC4R, 1653
 - nppiDotProd_32u64f_C1R, 1653
 - nppiDotProd_32u64f_C3R, 1654
 - nppiDotProd_32u64f_C4R, 1654
 - nppiDotProd_8s64f_AC4R, 1655
 - nppiDotProd_8s64f_C1R, 1655
 - nppiDotProd_8s64f_C3R, 1655
 - nppiDotProd_8s64f_C4R, 1656
 - nppiDotProd_8u64f_AC4R, 1656
 - nppiDotProd_8u64f_C1R, 1657
 - nppiDotProd_8u64f_C3R, 1657
 - nppiDotProd_8u64f_C4R, 1658
 - nppiDotProdGetBufferSize_16s64f_-
 - AC4R, 1658
 - nppiDotProdGetBufferSize_16s64f_C1R,
 - 1658
 - nppiDotProdGetBufferSize_16s64f_C3R,
 - 1659
 - nppiDotProdGetBufferSize_16s64f_C4R,
 - 1659
 - nppiDotProdGetBufferSize_16u64f_-
 - AC4R, 1659
 - nppiDotProdGetBufferSize_16u64f_C1R,
 - 1659
 - nppiDotProdGetBufferSize_16u64f_C3R,
 - 1660
 - nppiDotProdGetBufferSize_16u64f_C4R,
 - 1660
 - nppiDotProdGetBufferSize_32f64f_-
 - AC4R, 1660
 - nppiDotProdGetBufferSize_32f64f_C1R,
 - 1661
 - nppiDotProdGetBufferSize_32f64f_C3R,
 - 1661
 - nppiDotProdGetBufferSize_32f64f_C4R,
 - 1661
 - nppiDotProdGetBufferSize_32s64f_-
 - AC4R, 1661
 - nppiDotProdGetBufferSize_32s64f_C1R,
 - 1662
 - nppiDotProdGetBufferSize_32s64f_C3R,
 - 1662

- nppiDotProdGetBufferHostSize_32s64f_C4R, 1662
- nppiDotProdGetBufferHostSize_32u64f_-AC4R, 1663
- nppiDotProdGetBufferHostSize_32u64f_C1R, 1663
- nppiDotProdGetBufferHostSize_32u64f_C3R, 1663
- nppiDotProdGetBufferHostSize_32u64f_C4R, 1663
- nppiDotProdGetBufferHostSize_8s64f_-AC4R, 1664
- nppiDotProdGetBufferHostSize_8s64f_C1R, 1664
- nppiDotProdGetBufferHostSize_8s64f_C3R, 1664
- nppiDotProdGetBufferHostSize_8s64f_C4R, 1665
- nppiDotProdGetBufferHostSize_8u64f_-AC4R, 1665
- nppiDotProdGetBufferHostSize_8u64f_C1R, 1665
- nppiDotProdGetBufferHostSize_8u64f_C3R, 1665
- nppiDotProdGetBufferHostSize_8u64f_C4R, 1666
- image_duplicate_channel
 - nppiDup_16s_C1AC4R, 893
 - nppiDup_16s_C1C3R, 893
 - nppiDup_16s_C1C4R, 894
 - nppiDup_16u_C1AC4R, 894
 - nppiDup_16u_C1C3R, 894
 - nppiDup_16u_C1C4R, 895
 - nppiDup_32f_C1AC4R, 895
 - nppiDup_32f_C1C3R, 895
 - nppiDup_32f_C1C4R, 896
 - nppiDup_32s_C1AC4R, 896
 - nppiDup_32s_C1C3R, 896
 - nppiDup_32s_C1C4R, 897
 - nppiDup_8u_C1AC4R, 897
 - nppiDup_8u_C1C3R, 897
 - nppiDup_8u_C1C4R, 898
- image_erode
 - nppiErode_16u_AC4R, 1281
 - nppiErode_16u_C1R, 1281
 - nppiErode_16u_C3R, 1282
 - nppiErode_16u_C4R, 1282
 - nppiErode_32f_AC4R, 1282
 - nppiErode_32f_C1R, 1283
 - nppiErode_32f_C3R, 1283
 - nppiErode_32f_C4R, 1284
 - nppiErode_8u_AC4R, 1284
 - nppiErode_8u_C1R, 1285
 - nppiErode_8u_C3R, 1285
 - nppiErode_8u_C4R, 1285
- image_erode_3x3
 - nppiErode3x3_16u_AC4R, 1294
 - nppiErode3x3_16u_C1R, 1294
 - nppiErode3x3_16u_C3R, 1294
 - nppiErode3x3_16u_C4R, 1295
 - nppiErode3x3_32f_AC4R, 1295
 - nppiErode3x3_32f_C1R, 1295
 - nppiErode3x3_32f_C3R, 1296
 - nppiErode3x3_32f_C4R, 1296
 - nppiErode3x3_64f_C1R, 1296
 - nppiErode3x3_8u_AC4R, 1297
 - nppiErode3x3_8u_C1R, 1297
 - nppiErode3x3_8u_C3R, 1297
 - nppiErode3x3_8u_C4R, 1298
- image_exp
 - nppiExp_16s_C1IRSfs, 364
 - nppiExp_16s_C1RSfs, 364
 - nppiExp_16s_C3IRSfs, 365
 - nppiExp_16s_C3RSfs, 365
 - nppiExp_16u_C1IRSfs, 365
 - nppiExp_16u_C1RSfs, 366
 - nppiExp_16u_C3IRSfs, 366
 - nppiExp_16u_C3RSfs, 366
 - nppiExp_32f_C1IR, 367
 - nppiExp_32f_C1R, 367
 - nppiExp_32f_C3IR, 367
 - nppiExp_32f_C3R, 368
 - nppiExp_8u_C1IRSfs, 368
 - nppiExp_8u_C1RSfs, 368
 - nppiExp_8u_C3IRSfs, 369
 - nppiExp_8u_C3RSfs, 369
- image_fourier_transforms
 - nppiMagnitude_32fc32f_C1R, 1270
 - nppiMagnitudeSqr_32fc32f_C1R, 1270
- image_graphcut
 - nppiGraphcut8_32f8u, 700
 - nppiGraphcut8_32s8u, 700
 - nppiGraphcut8GetSize, 701
 - nppiGraphcut8InitAlloc, 702
 - nppiGraphcut_32f8u, 702
 - nppiGraphcut_32s8u, 703
 - nppiGraphcutFree, 704
 - nppiGraphcutGetSize, 704
 - nppiGraphcutInitAlloc, 704
- image_histogrameven
 - nppiEvenLevelsHost_32s, 1697
 - nppiHistogramEven_16s_AC4R, 1698
 - nppiHistogramEven_16s_C1R, 1698
 - nppiHistogramEven_16s_C3R, 1698
 - nppiHistogramEven_16s_C4R, 1699
 - nppiHistogramEven_16u_AC4R, 1699
 - nppiHistogramEven_16u_C1R, 1700
 - nppiHistogramEven_16u_C3R, 1700

- nppiHistogramEven_16u_C4R, [1701](#)
- nppiHistogramEven_8u_AC4R, [1701](#)
- nppiHistogramEven_8u_C1R, [1702](#)
- nppiHistogramEven_8u_C3R, [1702](#)
- nppiHistogramEven_8u_C4R, [1703](#)
- nppiHistogramEvenGetBufferSize_16s_-AC4R, [1703](#)
- nppiHistogramEvenGetBufferSize_16s_C1R, [1703](#)
- nppiHistogramEvenGetBufferSize_16s_C3R, [1704](#)
- nppiHistogramEvenGetBufferSize_16s_C4R, [1704](#)
- nppiHistogramEvenGetBufferSize_16u_-AC4R, [1704](#)
- nppiHistogramEvenGetBufferSize_16u_C1R, [1705](#)
- nppiHistogramEvenGetBufferSize_16u_C3R, [1705](#)
- nppiHistogramEvenGetBufferSize_16u_C4R, [1705](#)
- nppiHistogramEvenGetBufferSize_8u_AC4R, [1706](#)
- nppiHistogramEvenGetBufferSize_8u_C1R, [1706](#)
- nppiHistogramEvenGetBufferSize_8u_C3R, [1706](#)
- nppiHistogramEvenGetBufferSize_8u_C4R, [1707](#)
- image_histogramrange
 - nppiHistogramRange_16s_AC4R, [1711](#)
 - nppiHistogramRange_16s_C1R, [1711](#)
 - nppiHistogramRange_16s_C3R, [1711](#)
 - nppiHistogramRange_16s_C4R, [1712](#)
 - nppiHistogramRange_16u_AC4R, [1712](#)
 - nppiHistogramRange_16u_C1R, [1713](#)
 - nppiHistogramRange_16u_C3R, [1713](#)
 - nppiHistogramRange_16u_C4R, [1714](#)
 - nppiHistogramRange_32f_AC4R, [1714](#)
 - nppiHistogramRange_32f_C1R, [1715](#)
 - nppiHistogramRange_32f_C3R, [1715](#)
 - nppiHistogramRange_32f_C4R, [1715](#)
 - nppiHistogramRange_8u_AC4R, [1716](#)
 - nppiHistogramRange_8u_C1R, [1716](#)
 - nppiHistogramRange_8u_C3R, [1717](#)
 - nppiHistogramRange_8u_C4R, [1717](#)
 - nppiHistogramRangeGetBufferSize_16s_-AC4R, [1718](#)
 - nppiHistogramRangeGetBufferSize_16s_-C1R, [1718](#)
 - nppiHistogramRangeGetBufferSize_16s_-C3R, [1718](#)
 - nppiHistogramRangeGetBufferSize_16s_-C4R, [1719](#)
 - nppiHistogramRangeGetBufferSize_16u_-AC4R, [1719](#)
 - nppiHistogramRangeGetBufferSize_16u_-C1R, [1719](#)
 - nppiHistogramRangeGetBufferSize_16u_-C3R, [1720](#)
 - nppiHistogramRangeGetBufferSize_16u_-C4R, [1720](#)
 - nppiHistogramRangeGetBufferSize_32f_-AC4R, [1720](#)
 - nppiHistogramRangeGetBufferSize_32f_C1R, [1721](#)
 - nppiHistogramRangeGetBufferSize_32f_C3R, [1721](#)
 - nppiHistogramRangeGetBufferSize_32f_C4R, [1721](#)
 - nppiHistogramRangeGetBufferSize_8u_-AC4R, [1722](#)
 - nppiHistogramRangeGetBufferSize_8u_C1R, [1722](#)
 - nppiHistogramRangeGetBufferSize_8u_C3R, [1722](#)
 - nppiHistogramRangeGetBufferSize_8u_C4R, [1723](#)
- image_inf_norm
 - nppiNorm_Inf_16s_AC4R, [1444](#)
 - nppiNorm_Inf_16s_C1R, [1444](#)
 - nppiNorm_Inf_16s_C3R, [1444](#)
 - nppiNorm_Inf_16s_C4R, [1445](#)
 - nppiNorm_Inf_16u_AC4R, [1445](#)
 - nppiNorm_Inf_16u_C1MR, [1445](#)
 - nppiNorm_Inf_16u_C1R, [1446](#)
 - nppiNorm_Inf_16u_C3CMR, [1446](#)
 - nppiNorm_Inf_16u_C3R, [1447](#)
 - nppiNorm_Inf_16u_C4R, [1447](#)
 - nppiNorm_Inf_32f_AC4R, [1447](#)
 - nppiNorm_Inf_32f_C1MR, [1448](#)
 - nppiNorm_Inf_32f_C1R, [1448](#)
 - nppiNorm_Inf_32f_C3CMR, [1449](#)
 - nppiNorm_Inf_32f_C3R, [1449](#)
 - nppiNorm_Inf_32f_C4R, [1449](#)
 - nppiNorm_Inf_32s_C1R, [1450](#)
 - nppiNorm_Inf_8s_C1MR, [1450](#)
 - nppiNorm_Inf_8s_C3CMR, [1451](#)
 - nppiNorm_Inf_8u_AC4R, [1451](#)
 - nppiNorm_Inf_8u_C1MR, [1451](#)
 - nppiNorm_Inf_8u_C1R, [1452](#)
 - nppiNorm_Inf_8u_C3CMR, [1452](#)
 - nppiNorm_Inf_8u_C3R, [1453](#)
 - nppiNorm_Inf_8u_C4R, [1453](#)
 - nppiNormInfGetBufferHostSize_16s_AC4R, [1453](#)
 - nppiNormInfGetBufferHostSize_16s_C1R, [1454](#)

- nppiNormInfGetBufferHostSize_16s_C3R, 1454
- nppiNormInfGetBufferHostSize_16s_C4R, 1454
- nppiNormInfGetBufferHostSize_16u_AC4R, 1455
- nppiNormInfGetBufferHostSize_16u_C1MR, 1455
- nppiNormInfGetBufferHostSize_16u_C1R, 1455
- nppiNormInfGetBufferHostSize_16u_-C3CMR, 1455
- nppiNormInfGetBufferHostSize_16u_C3R, 1456
- nppiNormInfGetBufferHostSize_16u_C4R, 1456
- nppiNormInfGetBufferHostSize_32f_AC4R, 1456
- nppiNormInfGetBufferHostSize_32f_C1MR, 1457
- nppiNormInfGetBufferHostSize_32f_C1R, 1457
- nppiNormInfGetBufferHostSize_32f_-C3CMR, 1457
- nppiNormInfGetBufferHostSize_32f_C3R, 1457
- nppiNormInfGetBufferHostSize_32f_C4R, 1458
- nppiNormInfGetBufferHostSize_32s_C1R, 1458
- nppiNormInfGetBufferHostSize_8s_C1MR, 1458
- nppiNormInfGetBufferHostSize_8s_C3CMR, 1459
- nppiNormInfGetBufferHostSize_8u_AC4R, 1459
- nppiNormInfGetBufferHostSize_8u_C1MR, 1459
- nppiNormInfGetBufferHostSize_8u_C1R, 1459
- nppiNormInfGetBufferHostSize_8u_C3CMR, 1460
- nppiNormInfGetBufferHostSize_8u_C3R, 1460
- nppiNormInfGetBufferHostSize_8u_C4R, 1460
- image_inf_normdiff
 - nppiNormDiff_Inf_16s_AC4R, 1508
 - nppiNormDiff_Inf_16s_C1R, 1508
 - nppiNormDiff_Inf_16s_C3R, 1509
 - nppiNormDiff_Inf_16s_C4R, 1509
 - nppiNormDiff_Inf_16u_AC4R, 1510
 - nppiNormDiff_Inf_16u_C1MR, 1510
 - nppiNormDiff_Inf_16u_C1R, 1511
 - nppiNormDiff_Inf_16u_C3CMR, 1511
 - nppiNormDiff_Inf_16u_C3R, 1512
 - nppiNormDiff_Inf_16u_C4R, 1512
 - nppiNormDiff_Inf_32f_AC4R, 1512
 - nppiNormDiff_Inf_32f_C1MR, 1513
 - nppiNormDiff_Inf_32f_C1R, 1513
 - nppiNormDiff_Inf_32f_C3CMR, 1514
 - nppiNormDiff_Inf_32f_C3R, 1514
 - nppiNormDiff_Inf_32f_C4R, 1515
 - nppiNormDiff_Inf_8s_C1MR, 1515
 - nppiNormDiff_Inf_8s_C3CMR, 1516
 - nppiNormDiff_Inf_8u_AC4R, 1516
 - nppiNormDiff_Inf_8u_C1MR, 1517
 - nppiNormDiff_Inf_8u_C1R, 1517
 - nppiNormDiff_Inf_8u_C3CMR, 1518
 - nppiNormDiff_Inf_8u_C3R, 1518
 - nppiNormDiff_Inf_8u_C4R, 1519
 - nppiNormDiffInfGetBufferHostSize_16s_-AC4R, 1519
 - nppiNormDiffInfGetBufferHostSize_16s_-C1R, 1519
 - nppiNormDiffInfGetBufferHostSize_16s_-C3R, 1520
 - nppiNormDiffInfGetBufferHostSize_16s_-C4R, 1520
 - nppiNormDiffInfGetBufferHostSize_16u_-AC4R, 1520
 - nppiNormDiffInfGetBufferHostSize_16u_-C1MR, 1521
 - nppiNormDiffInfGetBufferHostSize_16u_-C1R, 1521
 - nppiNormDiffInfGetBufferHostSize_16u_-C3CMR, 1521
 - nppiNormDiffInfGetBufferHostSize_16u_-C3R, 1521
 - nppiNormDiffInfGetBufferHostSize_16u_-C4R, 1522
 - nppiNormDiffInfGetBufferHostSize_32f_-AC4R, 1522
 - nppiNormDiffInfGetBufferHostSize_32f_-C1MR, 1522
 - nppiNormDiffInfGetBufferHostSize_32f_-C1R, 1523
 - nppiNormDiffInfGetBufferHostSize_32f_-C3CMR, 1523
 - nppiNormDiffInfGetBufferHostSize_32f_-C3R, 1523
 - nppiNormDiffInfGetBufferHostSize_32f_-C4R, 1523
 - nppiNormDiffInfGetBufferHostSize_8s_-C1MR, 1524
 - nppiNormDiffInfGetBufferHostSize_8s_-C3CMR, 1524

- nppiNormDiffInfGetBufferHostSize_8u_-AC4R, [1524](#)
- nppiNormDiffInfGetBufferHostSize_8u_-C1MR, [1525](#)
- nppiNormDiffInfGetBufferHostSize_8u_C1R, [1525](#)
- nppiNormDiffInfGetBufferHostSize_8u_-C3CMR, [1525](#)
- nppiNormDiffInfGetBufferHostSize_8u_C3R, [1525](#)
- nppiNormDiffInfGetBufferHostSize_8u_C4R, [1526](#)
- image_inf_normrel
 - nppiNormRel_Inf_16s_AC4R, [1577](#)
 - nppiNormRel_Inf_16s_C1R, [1577](#)
 - nppiNormRel_Inf_16s_C3R, [1578](#)
 - nppiNormRel_Inf_16s_C4R, [1578](#)
 - nppiNormRel_Inf_16u_AC4R, [1579](#)
 - nppiNormRel_Inf_16u_C1MR, [1579](#)
 - nppiNormRel_Inf_16u_C1R, [1580](#)
 - nppiNormRel_Inf_16u_C3CMR, [1580](#)
 - nppiNormRel_Inf_16u_C3R, [1581](#)
 - nppiNormRel_Inf_16u_C4R, [1581](#)
 - nppiNormRel_Inf_32f_AC4R, [1581](#)
 - nppiNormRel_Inf_32f_C1MR, [1582](#)
 - nppiNormRel_Inf_32f_C1R, [1582](#)
 - nppiNormRel_Inf_32f_C3CMR, [1583](#)
 - nppiNormRel_Inf_32f_C3R, [1583](#)
 - nppiNormRel_Inf_32f_C4R, [1584](#)
 - nppiNormRel_Inf_8s_C1MR, [1584](#)
 - nppiNormRel_Inf_8s_C3CMR, [1585](#)
 - nppiNormRel_Inf_8u_AC4R, [1585](#)
 - nppiNormRel_Inf_8u_C1MR, [1586](#)
 - nppiNormRel_Inf_8u_C1R, [1586](#)
 - nppiNormRel_Inf_8u_C3CMR, [1587](#)
 - nppiNormRel_Inf_8u_C3R, [1587](#)
 - nppiNormRel_Inf_8u_C4R, [1588](#)
 - nppiNormRelInfGetBufferHostSize_16s_-AC4R, [1588](#)
 - nppiNormRelInfGetBufferHostSize_16s_-C1R, [1589](#)
 - nppiNormRelInfGetBufferHostSize_16s_-C3R, [1589](#)
 - nppiNormRelInfGetBufferHostSize_16s_-C4R, [1589](#)
 - nppiNormRelInfGetBufferHostSize_16u_-AC4R, [1589](#)
 - nppiNormRelInfGetBufferHostSize_16u_-C1MR, [1590](#)
 - nppiNormRelInfGetBufferHostSize_16u_-C1R, [1590](#)
 - nppiNormRelInfGetBufferHostSize_16u_-C3CMR, [1590](#)
 - nppiNormRelInfGetBufferHostSize_16u_-C3R, [1591](#)
 - nppiNormRelInfGetBufferHostSize_16u_-C4R, [1591](#)
 - nppiNormRelInfGetBufferHostSize_32f_-AC4R, [1591](#)
 - nppiNormRelInfGetBufferHostSize_32f_-C1MR, [1591](#)
 - nppiNormRelInfGetBufferHostSize_32f_C1R, [1592](#)
 - nppiNormRelInfGetBufferHostSize_32f_C3CMR, [1592](#)
 - nppiNormRelInfGetBufferHostSize_32f_C3R, [1592](#)
 - nppiNormRelInfGetBufferHostSize_32f_C4R, [1593](#)
 - nppiNormRelInfGetBufferHostSize_32s_-C1R, [1593](#)
 - nppiNormRelInfGetBufferHostSize_8s_-C1MR, [1593](#)
 - nppiNormRelInfGetBufferHostSize_8s_-C3CMR, [1593](#)
 - nppiNormRelInfGetBufferHostSize_8u_-AC4R, [1594](#)
 - nppiNormRelInfGetBufferHostSize_8u_-C1MR, [1594](#)
 - nppiNormRelInfGetBufferHostSize_8u_C1R, [1594](#)
 - nppiNormRelInfGetBufferHostSize_8u_-C3CMR, [1595](#)
 - nppiNormRelInfGetBufferHostSize_8u_C3R, [1595](#)
 - nppiNormRelInfGetBufferHostSize_8u_C4R, [1595](#)
- image_integral
 - nppiIntegral_8u32f_C1R, [1687](#)
 - nppiIntegral_8u32s_C1R, [1687](#)
- image_L1_norm
 - nppiNorm_L1_16s_AC4R, [1466](#)
 - nppiNorm_L1_16s_C1R, [1466](#)
 - nppiNorm_L1_16s_C3R, [1466](#)
 - nppiNorm_L1_16s_C4R, [1467](#)
 - nppiNorm_L1_16u_AC4R, [1467](#)
 - nppiNorm_L1_16u_C1MR, [1467](#)
 - nppiNorm_L1_16u_C1R, [1468](#)
 - nppiNorm_L1_16u_C3CMR, [1468](#)
 - nppiNorm_L1_16u_C3R, [1469](#)
 - nppiNorm_L1_16u_C4R, [1469](#)
 - nppiNorm_L1_32f_AC4R, [1469](#)
 - nppiNorm_L1_32f_C1MR, [1470](#)
 - nppiNorm_L1_32f_C1R, [1470](#)
 - nppiNorm_L1_32f_C3CMR, [1470](#)
 - nppiNorm_L1_32f_C3R, [1471](#)
 - nppiNorm_L1_32f_C4R, [1471](#)

- nppiNorm_L1_8s_C1MR, 1472
- nppiNorm_L1_8s_C3CMR, 1472
- nppiNorm_L1_8u_AC4R, 1472
- nppiNorm_L1_8u_C1MR, 1473
- nppiNorm_L1_8u_C1R, 1473
- nppiNorm_L1_8u_C3CMR, 1474
- nppiNorm_L1_8u_C3R, 1474
- nppiNorm_L1_8u_C4R, 1474
- nppiNormL1GetBufferHostSize_16s_AC4R, 1475
- nppiNormL1GetBufferHostSize_16s_C1R, 1475
- nppiNormL1GetBufferHostSize_16s_C3R, 1475
- nppiNormL1GetBufferHostSize_16s_C4R, 1476
- nppiNormL1GetBufferHostSize_16u_AC4R, 1476
- nppiNormL1GetBufferHostSize_16u_C1MR, 1476
- nppiNormL1GetBufferHostSize_16u_C1R, 1477
- nppiNormL1GetBufferHostSize_16u_-C3CMR, 1477
- nppiNormL1GetBufferHostSize_16u_C3R, 1477
- nppiNormL1GetBufferHostSize_16u_C4R, 1477
- nppiNormL1GetBufferHostSize_32f_AC4R, 1478
- nppiNormL1GetBufferHostSize_32f_C1MR, 1478
- nppiNormL1GetBufferHostSize_32f_C1R, 1478
- nppiNormL1GetBufferHostSize_32f_-C3CMR, 1479
- nppiNormL1GetBufferHostSize_32f_C3R, 1479
- nppiNormL1GetBufferHostSize_32f_C4R, 1479
- nppiNormL1GetBufferHostSize_8s_C1MR, 1479
- nppiNormL1GetBufferHostSize_8s_C3CMR, 1480
- nppiNormL1GetBufferHostSize_8u_AC4R, 1480
- nppiNormL1GetBufferHostSize_8u_C1MR, 1480
- nppiNormL1GetBufferHostSize_8u_C1R, 1481
- nppiNormL1GetBufferHostSize_8u_C3CMR, 1481
- nppiNormL1GetBufferHostSize_8u_C3R, 1481
- nppiNormL1GetBufferHostSize_8u_C4R, 1481
- image_L1_normdiff
 - nppiNormDiff_L1_16s_AC4R, 1531
 - nppiNormDiff_L1_16s_C1R, 1531
 - nppiNormDiff_L1_16s_C3R, 1532
 - nppiNormDiff_L1_16s_C4R, 1532
 - nppiNormDiff_L1_16u_AC4R, 1533
 - nppiNormDiff_L1_16u_C1MR, 1533
 - nppiNormDiff_L1_16u_C1R, 1533
 - nppiNormDiff_L1_16u_C3CMR, 1534
 - nppiNormDiff_L1_16u_C3R, 1534
 - nppiNormDiff_L1_16u_C4R, 1535
 - nppiNormDiff_L1_32f_AC4R, 1535
 - nppiNormDiff_L1_32f_C1MR, 1536
 - nppiNormDiff_L1_32f_C1R, 1536
 - nppiNormDiff_L1_32f_C3CMR, 1537
 - nppiNormDiff_L1_32f_C3R, 1537
 - nppiNormDiff_L1_32f_C4R, 1538
 - nppiNormDiff_L1_8s_C1MR, 1538
 - nppiNormDiff_L1_8s_C3CMR, 1539
 - nppiNormDiff_L1_8u_AC4R, 1539
 - nppiNormDiff_L1_8u_C1MR, 1540
 - nppiNormDiff_L1_8u_C1R, 1540
 - nppiNormDiff_L1_8u_C3CMR, 1540
 - nppiNormDiff_L1_8u_C3R, 1541
 - nppiNormDiff_L1_8u_C4R, 1541
 - nppiNormDiffL1GetBufferHostSize_16s_-AC4R, 1542
 - nppiNormDiffL1GetBufferHostSize_16s_-C1R, 1542
 - nppiNormDiffL1GetBufferHostSize_16s_-C3R, 1542
 - nppiNormDiffL1GetBufferHostSize_16s_-C4R, 1543
 - nppiNormDiffL1GetBufferHostSize_16u_-AC4R, 1543
 - nppiNormDiffL1GetBufferHostSize_16u_-C1MR, 1543
 - nppiNormDiffL1GetBufferHostSize_16u_-C1R, 1544
 - nppiNormDiffL1GetBufferHostSize_16u_-C3CMR, 1544
 - nppiNormDiffL1GetBufferHostSize_16u_-C3R, 1544
 - nppiNormDiffL1GetBufferHostSize_16u_-C4R, 1544
 - nppiNormDiffL1GetBufferHostSize_32f_-AC4R, 1545
 - nppiNormDiffL1GetBufferHostSize_32f_-C1MR, 1545
 - nppiNormDiffL1GetBufferHostSize_32f_-C1R, 1545

- nppiNormDiffL1GetBufferHostSize_32f_-C3CMR, 1546
- nppiNormDiffL1GetBufferHostSize_32f_-C3R, 1546
- nppiNormDiffL1GetBufferHostSize_32f_-C4R, 1546
- nppiNormDiffL1GetBufferHostSize_8s_-C1MR, 1546
- nppiNormDiffL1GetBufferHostSize_8s_-C3CMR, 1547
- nppiNormDiffL1GetBufferHostSize_8u_-AC4R, 1547
- nppiNormDiffL1GetBufferHostSize_8u_-C1MR, 1547
- nppiNormDiffL1GetBufferHostSize_8u_C1R, 1548
- nppiNormDiffL1GetBufferHostSize_8u_-C3CMR, 1548
- nppiNormDiffL1GetBufferHostSize_8u_C3R, 1548
- nppiNormDiffL1GetBufferHostSize_8u_C4R, 1548
- image_L1_normrel
 - nppiNormRel_L1_16s_AC4R, 1600
 - nppiNormRel_L1_16s_C1R, 1600
 - nppiNormRel_L1_16s_C3R, 1601
 - nppiNormRel_L1_16s_C4R, 1601
 - nppiNormRel_L1_16u_AC4R, 1602
 - nppiNormRel_L1_16u_C1MR, 1602
 - nppiNormRel_L1_16u_C1R, 1603
 - nppiNormRel_L1_16u_C3CMR, 1603
 - nppiNormRel_L1_16u_C3R, 1603
 - nppiNormRel_L1_16u_C4R, 1604
 - nppiNormRel_L1_32f_AC4R, 1604
 - nppiNormRel_L1_32f_C1MR, 1605
 - nppiNormRel_L1_32f_C1R, 1605
 - nppiNormRel_L1_32f_C3CMR, 1606
 - nppiNormRel_L1_32f_C3R, 1606
 - nppiNormRel_L1_32f_C4R, 1607
 - nppiNormRel_L1_8s_C1MR, 1607
 - nppiNormRel_L1_8s_C3CMR, 1608
 - nppiNormRel_L1_8u_AC4R, 1608
 - nppiNormRel_L1_8u_C1MR, 1609
 - nppiNormRel_L1_8u_C1R, 1609
 - nppiNormRel_L1_8u_C3CMR, 1610
 - nppiNormRel_L1_8u_C3R, 1610
 - nppiNormRel_L1_8u_C4R, 1611
 - nppiNormRelL1GetBufferHostSize_16s_-AC4R, 1611
 - nppiNormRelL1GetBufferHostSize_16s_C1R, 1611
 - nppiNormRelL1GetBufferHostSize_16s_C3R, 1612
 - nppiNormRelL1GetBufferHostSize_16s_C4R, 1612
 - nppiNormRelL1GetBufferHostSize_16u_-AC4R, 1612
 - nppiNormRelL1GetBufferHostSize_16u_-C1MR, 1613
 - nppiNormRelL1GetBufferHostSize_16u_-C1R, 1613
 - nppiNormRelL1GetBufferHostSize_16u_-C3CMR, 1613
 - nppiNormRelL1GetBufferHostSize_16u_-C3R, 1613
 - nppiNormRelL1GetBufferHostSize_16u_-C4R, 1614
 - nppiNormRelL1GetBufferHostSize_32f_-AC4R, 1614
 - nppiNormRelL1GetBufferHostSize_32f_-C1MR, 1614
 - nppiNormRelL1GetBufferHostSize_32f_C1R, 1615
 - nppiNormRelL1GetBufferHostSize_32f_-C3CMR, 1615
 - nppiNormRelL1GetBufferHostSize_32f_C3R, 1615
 - nppiNormRelL1GetBufferHostSize_32f_C4R, 1615
 - nppiNormRelL1GetBufferHostSize_8s_-C1MR, 1616
 - nppiNormRelL1GetBufferHostSize_8s_-C3CMR, 1616
 - nppiNormRelL1GetBufferHostSize_8u_-AC4R, 1616
 - nppiNormRelL1GetBufferHostSize_8u_-C1MR, 1617
 - nppiNormRelL1GetBufferHostSize_8u_C1R, 1617
 - nppiNormRelL1GetBufferHostSize_8u_-C3CMR, 1617
 - nppiNormRelL1GetBufferHostSize_8u_C3R, 1617
 - nppiNormRelL1GetBufferHostSize_8u_C4R, 1618
- image_L2_norm
 - nppiNorm_L2_16s_AC4R, 1487
 - nppiNorm_L2_16s_C1R, 1487
 - nppiNorm_L2_16s_C3R, 1487
 - nppiNorm_L2_16s_C4R, 1488
 - nppiNorm_L2_16u_AC4R, 1488
 - nppiNorm_L2_16u_C1MR, 1488
 - nppiNorm_L2_16u_C1R, 1489
 - nppiNorm_L2_16u_C3CMR, 1489
 - nppiNorm_L2_16u_C3R, 1490
 - nppiNorm_L2_16u_C4R, 1490
 - nppiNorm_L2_32f_AC4R, 1490

- nppiNorm_L2_32f_C1MR, 1491
- nppiNorm_L2_32f_C1R, 1491
- nppiNorm_L2_32f_C3CMR, 1491
- nppiNorm_L2_32f_C3R, 1492
- nppiNorm_L2_32f_C4R, 1492
- nppiNorm_L2_8s_C1MR, 1493
- nppiNorm_L2_8s_C3CMR, 1493
- nppiNorm_L2_8u_AC4R, 1493
- nppiNorm_L2_8u_C1MR, 1494
- nppiNorm_L2_8u_C1R, 1494
- nppiNorm_L2_8u_C3CMR, 1495
- nppiNorm_L2_8u_C3R, 1495
- nppiNorm_L2_8u_C4R, 1495
- nppiNormL2GetBufferHostSize_16s_AC4R, 1496
- nppiNormL2GetBufferHostSize_16s_C1R, 1496
- nppiNormL2GetBufferHostSize_16s_C3R, 1496
- nppiNormL2GetBufferHostSize_16s_C4R, 1497
- nppiNormL2GetBufferHostSize_16u_AC4R, 1497
- nppiNormL2GetBufferHostSize_16u_C1MR, 1497
- nppiNormL2GetBufferHostSize_16u_C1R, 1498
- nppiNormL2GetBufferHostSize_16u_-C3CMR, 1498
- nppiNormL2GetBufferHostSize_16u_C3R, 1498
- nppiNormL2GetBufferHostSize_16u_C4R, 1498
- nppiNormL2GetBufferHostSize_32f_AC4R, 1499
- nppiNormL2GetBufferHostSize_32f_C1MR, 1499
- nppiNormL2GetBufferHostSize_32f_C1R, 1499
- nppiNormL2GetBufferHostSize_32f_-C3CMR, 1500
- nppiNormL2GetBufferHostSize_32f_C3R, 1500
- nppiNormL2GetBufferHostSize_32f_C4R, 1500
- nppiNormL2GetBufferHostSize_8s_C1MR, 1500
- nppiNormL2GetBufferHostSize_8s_C3CMR, 1501
- nppiNormL2GetBufferHostSize_8u_AC4R, 1501
- nppiNormL2GetBufferHostSize_8u_C1MR, 1501
- nppiNormL2GetBufferHostSize_8u_C1R, 1502
- nppiNormL2GetBufferHostSize_8u_C3CMR, 1502
- nppiNormL2GetBufferHostSize_8u_C3R, 1502
- nppiNormL2GetBufferHostSize_8u_C4R, 1502
- image_L2_normdiff
 - nppiNormDiff_L2_16s_AC4R, 1554
 - nppiNormDiff_L2_16s_C1R, 1554
 - nppiNormDiff_L2_16s_C3R, 1555
 - nppiNormDiff_L2_16s_C4R, 1555
 - nppiNormDiff_L2_16u_AC4R, 1556
 - nppiNormDiff_L2_16u_C1MR, 1556
 - nppiNormDiff_L2_16u_C1R, 1556
 - nppiNormDiff_L2_16u_C3CMR, 1557
 - nppiNormDiff_L2_16u_C3R, 1557
 - nppiNormDiff_L2_16u_C4R, 1558
 - nppiNormDiff_L2_32f_AC4R, 1558
 - nppiNormDiff_L2_32f_C1MR, 1559
 - nppiNormDiff_L2_32f_C1R, 1559
 - nppiNormDiff_L2_32f_C3CMR, 1560
 - nppiNormDiff_L2_32f_C3R, 1560
 - nppiNormDiff_L2_32f_C4R, 1561
 - nppiNormDiff_L2_8s_C1MR, 1561
 - nppiNormDiff_L2_8s_C3CMR, 1562
 - nppiNormDiff_L2_8u_AC4R, 1562
 - nppiNormDiff_L2_8u_C1MR, 1563
 - nppiNormDiff_L2_8u_C1R, 1563
 - nppiNormDiff_L2_8u_C3CMR, 1563
 - nppiNormDiff_L2_8u_C3R, 1564
 - nppiNormDiff_L2_8u_C4R, 1564
 - nppiNormDiffL2GetBufferHostSize_16s_-AC4R, 1565
 - nppiNormDiffL2GetBufferHostSize_16s_-C1R, 1565
 - nppiNormDiffL2GetBufferHostSize_16s_-C3R, 1565
 - nppiNormDiffL2GetBufferHostSize_16s_-C4R, 1566
 - nppiNormDiffL2GetBufferHostSize_16u_-AC4R, 1566
 - nppiNormDiffL2GetBufferHostSize_16u_-C1MR, 1566
 - nppiNormDiffL2GetBufferHostSize_16u_-C1R, 1567
 - nppiNormDiffL2GetBufferHostSize_16u_-C3CMR, 1567
 - nppiNormDiffL2GetBufferHostSize_16u_-C3R, 1567
 - nppiNormDiffL2GetBufferHostSize_16u_-C4R, 1567

- nppiNormDiffL2GetBufferHostSize_32f_-AC4R, 1568
- nppiNormDiffL2GetBufferHostSize_32f_-C1MR, 1568
- nppiNormDiffL2GetBufferHostSize_32f_-C1R, 1568
- nppiNormDiffL2GetBufferHostSize_32f_-C3CMR, 1569
- nppiNormDiffL2GetBufferHostSize_32f_-C3R, 1569
- nppiNormDiffL2GetBufferHostSize_32f_-C4R, 1569
- nppiNormDiffL2GetBufferHostSize_8s_-C1MR, 1569
- nppiNormDiffL2GetBufferHostSize_8s_-C3CMR, 1570
- nppiNormDiffL2GetBufferHostSize_8u_-AC4R, 1570
- nppiNormDiffL2GetBufferHostSize_8u_-C1MR, 1570
- nppiNormDiffL2GetBufferHostSize_8u_C1R, 1571
- nppiNormDiffL2GetBufferHostSize_8u_-C3CMR, 1571
- nppiNormDiffL2GetBufferHostSize_8u_C3R, 1571
- nppiNormDiffL2GetBufferHostSize_8u_C4R, 1571
- image_L2_normrel
 - nppiNormRel_L2_16s_AC4R, 1623
 - nppiNormRel_L2_16s_C1R, 1623
 - nppiNormRel_L2_16s_C3R, 1624
 - nppiNormRel_L2_16s_C4R, 1624
 - nppiNormRel_L2_16u_AC4R, 1625
 - nppiNormRel_L2_16u_C1MR, 1625
 - nppiNormRel_L2_16u_C1R, 1626
 - nppiNormRel_L2_16u_C3CMR, 1626
 - nppiNormRel_L2_16u_C3R, 1626
 - nppiNormRel_L2_16u_C4R, 1627
 - nppiNormRel_L2_32f_AC4R, 1627
 - nppiNormRel_L2_32f_C1MR, 1628
 - nppiNormRel_L2_32f_C1R, 1628
 - nppiNormRel_L2_32f_C3CMR, 1629
 - nppiNormRel_L2_32f_C3R, 1629
 - nppiNormRel_L2_32f_C4R, 1630
 - nppiNormRel_L2_8s_C1MR, 1630
 - nppiNormRel_L2_8s_C3CMR, 1631
 - nppiNormRel_L2_8u_AC4R, 1631
 - nppiNormRel_L2_8u_C1MR, 1632
 - nppiNormRel_L2_8u_C1R, 1632
 - nppiNormRel_L2_8u_C3CMR, 1633
 - nppiNormRel_L2_8u_C3R, 1633
 - nppiNormRel_L2_8u_C4R, 1634
- nppiNormRelL2GetBufferHostSize_16s_-AC4R, 1634
- nppiNormRelL2GetBufferHostSize_16s_C1R, 1634
- nppiNormRelL2GetBufferHostSize_16s_C3R, 1635
- nppiNormRelL2GetBufferHostSize_16s_C4R, 1635
- nppiNormRelL2GetBufferHostSize_16u_-AC4R, 1635
- nppiNormRelL2GetBufferHostSize_16u_-C1MR, 1636
- nppiNormRelL2GetBufferHostSize_16u_-C1R, 1636
- nppiNormRelL2GetBufferHostSize_16u_-C3CMR, 1636
- nppiNormRelL2GetBufferHostSize_16u_-C3R, 1636
- nppiNormRelL2GetBufferHostSize_16u_-C4R, 1637
- nppiNormRelL2GetBufferHostSize_32f_-AC4R, 1637
- nppiNormRelL2GetBufferHostSize_32f_-C1MR, 1637
- nppiNormRelL2GetBufferHostSize_32f_C1R, 1638
- nppiNormRelL2GetBufferHostSize_32f_-C3CMR, 1638
- nppiNormRelL2GetBufferHostSize_32f_C3R, 1638
- nppiNormRelL2GetBufferHostSize_32f_C4R, 1638
- nppiNormRelL2GetBufferHostSize_8s_-C1MR, 1639
- nppiNormRelL2GetBufferHostSize_8s_-C3CMR, 1639
- nppiNormRelL2GetBufferHostSize_8u_-AC4R, 1639
- nppiNormRelL2GetBufferHostSize_8u_-C1MR, 1640
- nppiNormRelL2GetBufferHostSize_8u_C1R, 1640
- nppiNormRelL2GetBufferHostSize_8u_-C3CMR, 1640
- nppiNormRelL2GetBufferHostSize_8u_C3R, 1640
- nppiNormRelL2GetBufferHostSize_8u_C4R, 1641
- image_labeling_and_segmentation
 - NppiGraphcutState, 698
- image_ln
 - nppiLn_16s_C1RSfs, 357
 - nppiLn_16s_C1RSfs, 357
 - nppiLn_16s_C3RSfs, 358

- nppiLn_16s_C3RSfs, 358
- nppiLn_16u_C1IRSfs, 358
- nppiLn_16u_C1RSfs, 359
- nppiLn_16u_C3IRSfs, 359
- nppiLn_16u_C3RSfs, 359
- nppiLn_32f_C1IR, 360
- nppiLn_32f_C1R, 360
- nppiLn_32f_C3IR, 360
- nppiLn_32f_C3R, 361
- nppiLn_8u_C1IRSfs, 361
- nppiLn_8u_C1RSfs, 361
- nppiLn_8u_C3IRSfs, 362
- nppiLn_8u_C3RSfs, 362
- image_lshifc
 - nppiLShiftC_16u_AC4IR, 423
 - nppiLShiftC_16u_AC4R, 423
 - nppiLShiftC_16u_C1IR, 423
 - nppiLShiftC_16u_C1R, 424
 - nppiLShiftC_16u_C3IR, 424
 - nppiLShiftC_16u_C3R, 424
 - nppiLShiftC_16u_C4IR, 425
 - nppiLShiftC_16u_C4R, 425
 - nppiLShiftC_32s_AC4IR, 425
 - nppiLShiftC_32s_AC4R, 426
 - nppiLShiftC_32s_C1IR, 426
 - nppiLShiftC_32s_C1R, 426
 - nppiLShiftC_32s_C3IR, 427
 - nppiLShiftC_32s_C3R, 427
 - nppiLShiftC_32s_C4IR, 427
 - nppiLShiftC_32s_C4R, 428
 - nppiLShiftC_8u_AC4IR, 428
 - nppiLShiftC_8u_AC4R, 428
 - nppiLShiftC_8u_C1IR, 429
 - nppiLShiftC_8u_C1R, 429
 - nppiLShiftC_8u_C3IR, 429
 - nppiLShiftC_8u_C3R, 430
 - nppiLShiftC_8u_C4IR, 430
 - nppiLShiftC_8u_C4R, 430
- image_max
 - nppiMax_16s_AC4R, 1345
 - nppiMax_16s_C1R, 1345
 - nppiMax_16s_C3R, 1346
 - nppiMax_16s_C4R, 1346
 - nppiMax_16u_AC4R, 1346
 - nppiMax_16u_C1R, 1347
 - nppiMax_16u_C3R, 1347
 - nppiMax_16u_C4R, 1348
 - nppiMax_32f_AC4R, 1348
 - nppiMax_32f_C1R, 1348
 - nppiMax_32f_C3R, 1349
 - nppiMax_32f_C4R, 1349
 - nppiMax_8u_AC4R, 1349
 - nppiMax_8u_C1R, 1350
 - nppiMax_8u_C3R, 1350
 - nppiMax_8u_C4R, 1351
 - nppiMaxGetBufferHostSize_16s_AC4R, 1351
 - nppiMaxGetBufferHostSize_16s_C1R, 1351
 - nppiMaxGetBufferHostSize_16s_C3R, 1351
 - nppiMaxGetBufferHostSize_16s_C4R, 1352
 - nppiMaxGetBufferHostSize_16u_AC4R, 1352
 - nppiMaxGetBufferHostSize_16u_C1R, 1352
 - nppiMaxGetBufferHostSize_16u_C3R, 1353
 - nppiMaxGetBufferHostSize_16u_C4R, 1353
 - nppiMaxGetBufferHostSize_32f_AC4R, 1353
 - nppiMaxGetBufferHostSize_32f_C1R, 1353
 - nppiMaxGetBufferHostSize_32f_C3R, 1354
 - nppiMaxGetBufferHostSize_32f_C4R, 1354
 - nppiMaxGetBufferHostSize_8u_AC4R, 1354
 - nppiMaxGetBufferHostSize_8u_C1R, 1355
 - nppiMaxGetBufferHostSize_8u_C3R, 1355
 - nppiMaxGetBufferHostSize_8u_C4R, 1355
- image_max_index
 - nppiMaxIndx_16s_AC4R, 1358
 - nppiMaxIndx_16s_C1R, 1359
 - nppiMaxIndx_16s_C3R, 1359
 - nppiMaxIndx_16s_C4R, 1359
 - nppiMaxIndx_16u_AC4R, 1360
 - nppiMaxIndx_16u_C1R, 1360
 - nppiMaxIndx_16u_C3R, 1361
 - nppiMaxIndx_16u_C4R, 1361
 - nppiMaxIndx_32f_AC4R, 1361
 - nppiMaxIndx_32f_C1R, 1362
 - nppiMaxIndx_32f_C3R, 1362
 - nppiMaxIndx_32f_C4R, 1363
 - nppiMaxIndx_8u_AC4R, 1363
 - nppiMaxIndx_8u_C1R, 1363
 - nppiMaxIndx_8u_C3R, 1364
 - nppiMaxIndx_8u_C4R, 1364
 - nppiMaxIndxGetBufferHostSize_16s_AC4R, 1365
 - nppiMaxIndxGetBufferHostSize_16s_C1R, 1365
 - nppiMaxIndxGetBufferHostSize_16s_C3R, 1365
 - nppiMaxIndxGetBufferHostSize_16s_C4R, 1366
 - nppiMaxIndxGetBufferHostSize_16u_AC4R, 1366
 - nppiMaxIndxGetBufferHostSize_16u_C1R, 1366
 - nppiMaxIndxGetBufferHostSize_16u_C3R, 1366
 - nppiMaxIndxGetBufferHostSize_16u_C4R, 1367
 - nppiMaxIndxGetBufferHostSize_32f_AC4R, 1367
 - nppiMaxIndxGetBufferHostSize_32f_C1R, 1367

- nppiMaxIdxGetBufferHostSize_32f_C3R, 1368
- nppiMaxIdxGetBufferHostSize_32f_C4R, 1368
- nppiMaxIdxGetBufferHostSize_8u_AC4R, 1368
- nppiMaxIdxGetBufferHostSize_8u_C1R, 1368
- nppiMaxIdxGetBufferHostSize_8u_C3R, 1369
- nppiMaxIdxGetBufferHostSize_8u_C4R, 1369
- image_maxevery
 - nppiMaxEvery_16s_AC4IR, 1674
 - nppiMaxEvery_16s_C1IR, 1674
 - nppiMaxEvery_16s_C3IR, 1675
 - nppiMaxEvery_16s_C4IR, 1675
 - nppiMaxEvery_16u_AC4IR, 1675
 - nppiMaxEvery_16u_C1IR, 1676
 - nppiMaxEvery_16u_C3IR, 1676
 - nppiMaxEvery_16u_C4IR, 1676
 - nppiMaxEvery_32f_AC4IR, 1677
 - nppiMaxEvery_32f_C1IR, 1677
 - nppiMaxEvery_32f_C3IR, 1677
 - nppiMaxEvery_32f_C4IR, 1678
 - nppiMaxEvery_8u_AC4IR, 1678
 - nppiMaxEvery_8u_C1IR, 1678
 - nppiMaxEvery_8u_C3IR, 1679
 - nppiMaxEvery_8u_C4IR, 1679
- image_mean
 - nppiMean_16s_AC4R, 1405
 - nppiMean_16s_C1R, 1405
 - nppiMean_16s_C3R, 1405
 - nppiMean_16s_C4R, 1406
 - nppiMean_16u_AC4R, 1406
 - nppiMean_16u_C1MR, 1406
 - nppiMean_16u_C1R, 1407
 - nppiMean_16u_C3CMR, 1407
 - nppiMean_16u_C3R, 1407
 - nppiMean_16u_C4R, 1408
 - nppiMean_32f_AC4R, 1408
 - nppiMean_32f_C1MR, 1409
 - nppiMean_32f_C1R, 1409
 - nppiMean_32f_C3CMR, 1409
 - nppiMean_32f_C3R, 1410
 - nppiMean_32f_C4R, 1410
 - nppiMean_8s_C1MR, 1411
 - nppiMean_8s_C3CMR, 1411
 - nppiMean_8u_AC4R, 1412
 - nppiMean_8u_C1MR, 1412
 - nppiMean_8u_C1R, 1412
 - nppiMean_8u_C3CMR, 1413
 - nppiMean_8u_C3R, 1413
 - nppiMean_8u_C4R, 1414
 - nppiMeanGetBufferHostSize_16s_AC4R, 1414
 - nppiMeanGetBufferHostSize_16s_C1R, 1414
 - nppiMeanGetBufferHostSize_16s_C3R, 1415
 - nppiMeanGetBufferHostSize_16s_C4R, 1415
 - nppiMeanGetBufferHostSize_16u_AC4R, 1415
 - nppiMeanGetBufferHostSize_16u_C1MR, 1415
 - nppiMeanGetBufferHostSize_16u_C1R, 1416
 - nppiMeanGetBufferHostSize_16u_C3CMR, 1416
 - nppiMeanGetBufferHostSize_16u_C3R, 1416
 - nppiMeanGetBufferHostSize_16u_C4R, 1417
 - nppiMeanGetBufferHostSize_32f_AC4R, 1417
 - nppiMeanGetBufferHostSize_32f_C1MR, 1417
 - nppiMeanGetBufferHostSize_32f_C1R, 1417
 - nppiMeanGetBufferHostSize_32f_C3CMR, 1418
 - nppiMeanGetBufferHostSize_32f_C3R, 1418
 - nppiMeanGetBufferHostSize_32f_C4R, 1418
 - nppiMeanGetBufferHostSize_8s_C1MR, 1419
 - nppiMeanGetBufferHostSize_8s_C3CMR, 1419
 - nppiMeanGetBufferHostSize_8u_AC4R, 1419
 - nppiMeanGetBufferHostSize_8u_C1MR, 1419
 - nppiMeanGetBufferHostSize_8u_C1R, 1420
 - nppiMeanGetBufferHostSize_8u_C3CMR, 1420
 - nppiMeanGetBufferHostSize_8u_C3R, 1420
 - nppiMeanGetBufferHostSize_8u_C4R, 1421
- image_mean_stddev
 - nppiMean_StdDev_16u_C1MR, 1425
 - nppiMean_StdDev_16u_C1R, 1425
 - nppiMean_StdDev_16u_C3CMR, 1426
 - nppiMean_StdDev_16u_C3CR, 1426
 - nppiMean_StdDev_32f_C1MR, 1427
 - nppiMean_StdDev_32f_C1R, 1427
 - nppiMean_StdDev_32f_C3CMR, 1428
 - nppiMean_StdDev_32f_C3CR, 1428
 - nppiMean_StdDev_8s_C1MR, 1429
 - nppiMean_StdDev_8s_C1R, 1429
 - nppiMean_StdDev_8s_C3CMR, 1430
 - nppiMean_StdDev_8s_C3CR, 1430
 - nppiMean_StdDev_8u_C1MR, 1431
 - nppiMean_StdDev_8u_C1R, 1431
 - nppiMean_StdDev_8u_C3CMR, 1432
 - nppiMean_StdDev_8u_C3CR, 1432
 - nppiMeanStdDevGetBufferHostSize_16u_C1MR, 1433

- nppiMeanStdDevGetBufferHostSize_16u_C1R, 1433
- nppiMeanStdDevGetBufferHostSize_16u_C3CMR, 1433
- nppiMeanStdDevGetBufferHostSize_16u_C3CR, 1434
- nppiMeanStdDevGetBufferHostSize_32f_C1MR, 1434
- nppiMeanStdDevGetBufferHostSize_32f_C1R, 1434
- nppiMeanStdDevGetBufferHostSize_32f_C3CMR, 1435
- nppiMeanStdDevGetBufferHostSize_32f_C3CR, 1435
- nppiMeanStdDevGetBufferHostSize_8s_C1MR, 1435
- nppiMeanStdDevGetBufferHostSize_8s_C3CMR, 1436
- nppiMeanStdDevGetBufferHostSize_8s_C3CR, 1436
- nppiMeanStdDevGetBufferHostSize_8u_C1MR, 1436
- nppiMeanStdDevGetBufferHostSize_8u_C1R, 1437
- nppiMeanStdDevGetBufferHostSize_8u_C3CMR, 1437
- nppiMeanStdDevGetBufferHostSize_8u_C3CR, 1437
- image_memory_management
 - nppiFree, 1867
 - nppiMalloc_16s_C1, 1867
 - nppiMalloc_16s_C2, 1867
 - nppiMalloc_16s_C4, 1868
 - nppiMalloc_16sc_C1, 1868
 - nppiMalloc_16sc_C2, 1868
 - nppiMalloc_16sc_C3, 1869
 - nppiMalloc_16sc_C4, 1869
 - nppiMalloc_16u_C1, 1869
 - nppiMalloc_16u_C2, 1869
 - nppiMalloc_16u_C3, 1870
 - nppiMalloc_16u_C4, 1870
 - nppiMalloc_32f_C1, 1870
 - nppiMalloc_32f_C2, 1871
 - nppiMalloc_32f_C3, 1871
 - nppiMalloc_32f_C4, 1871
 - nppiMalloc_32fc_C1, 1871
 - nppiMalloc_32fc_C2, 1872
 - nppiMalloc_32fc_C3, 1872
 - nppiMalloc_32fc_C4, 1872
 - nppiMalloc_32s_C1, 1873
 - nppiMalloc_32s_C3, 1873
 - nppiMalloc_32s_C4, 1873
 - nppiMalloc_32sc_C1, 1873
 - nppiMalloc_32sc_C2, 1874
 - nppiMalloc_32sc_C3, 1874
 - nppiMalloc_32sc_C4, 1874
 - nppiMalloc_8u_C1, 1875
 - nppiMalloc_8u_C2, 1875
 - nppiMalloc_8u_C3, 1875
 - nppiMalloc_8u_C4, 1875
- image_min
 - nppiMin_16s_AC4R, 1318
 - nppiMin_16s_C1R, 1318
 - nppiMin_16s_C3R, 1319
 - nppiMin_16s_C4R, 1319
 - nppiMin_16u_AC4R, 1319
 - nppiMin_16u_C1R, 1320
 - nppiMin_16u_C3R, 1320
 - nppiMin_16u_C4R, 1321
 - nppiMin_32f_AC4R, 1321
 - nppiMin_32f_C1R, 1321
 - nppiMin_32f_C3R, 1322
 - nppiMin_32f_C4R, 1322
 - nppiMin_8u_AC4R, 1322
 - nppiMin_8u_C1R, 1323
 - nppiMin_8u_C3R, 1323
 - nppiMin_8u_C4R, 1324
 - nppiMinGetBufferHostSize_16s_AC4R, 1324
 - nppiMinGetBufferHostSize_16s_C1R, 1324
 - nppiMinGetBufferHostSize_16s_C3R, 1324
 - nppiMinGetBufferHostSize_16s_C4R, 1325
 - nppiMinGetBufferHostSize_16u_AC4R, 1325
 - nppiMinGetBufferHostSize_16u_C1R, 1325
 - nppiMinGetBufferHostSize_16u_C3R, 1326
 - nppiMinGetBufferHostSize_16u_C4R, 1326
 - nppiMinGetBufferHostSize_32f_AC4R, 1326
 - nppiMinGetBufferHostSize_32f_C1R, 1326
 - nppiMinGetBufferHostSize_32f_C3R, 1327
 - nppiMinGetBufferHostSize_32f_C4R, 1327
 - nppiMinGetBufferHostSize_8u_AC4R, 1327
 - nppiMinGetBufferHostSize_8u_C1R, 1328
 - nppiMinGetBufferHostSize_8u_C3R, 1328
 - nppiMinGetBufferHostSize_8u_C4R, 1328
- image_min_index
 - nppiMinIndx_16s_AC4R, 1331
 - nppiMinIndx_16s_C1R, 1332
 - nppiMinIndx_16s_C3R, 1332
 - nppiMinIndx_16s_C4R, 1332
 - nppiMinIndx_16u_AC4R, 1333
 - nppiMinIndx_16u_C1R, 1333
 - nppiMinIndx_16u_C3R, 1334
 - nppiMinIndx_16u_C4R, 1334
 - nppiMinIndx_32f_AC4R, 1334
 - nppiMinIndx_32f_C1R, 1335
 - nppiMinIndx_32f_C3R, 1335
 - nppiMinIndx_32f_C4R, 1336

- nppiMinIndx_8u_AC4R, 1336
- nppiMinIndx_8u_C1R, 1336
- nppiMinIndx_8u_C3R, 1337
- nppiMinIndx_8u_C4R, 1337
- nppiMinIndxGetBufferHostSize_16s_AC4R, 1338
- nppiMinIndxGetBufferHostSize_16s_C1R, 1338
- nppiMinIndxGetBufferHostSize_16s_C3R, 1338
- nppiMinIndxGetBufferHostSize_16s_C4R, 1339
- nppiMinIndxGetBufferHostSize_16u_AC4R, 1339
- nppiMinIndxGetBufferHostSize_16u_C1R, 1339
- nppiMinIndxGetBufferHostSize_16u_C3R, 1339
- nppiMinIndxGetBufferHostSize_16u_C4R, 1340
- nppiMinIndxGetBufferHostSize_32f_AC4R, 1340
- nppiMinIndxGetBufferHostSize_32f_C1R, 1340
- nppiMinIndxGetBufferHostSize_32f_C3R, 1341
- nppiMinIndxGetBufferHostSize_32f_C4R, 1341
- nppiMinIndxGetBufferHostSize_8u_AC4R, 1341
- nppiMinIndxGetBufferHostSize_8u_C1R, 1341
- nppiMinIndxGetBufferHostSize_8u_C3R, 1342
- nppiMinIndxGetBufferHostSize_8u_C4R, 1342
- image_min_max
 - nppiMinMax_16s_AC4R, 1372
 - nppiMinMax_16s_C1R, 1372
 - nppiMinMax_16s_C3R, 1373
 - nppiMinMax_16s_C4R, 1373
 - nppiMinMax_16u_AC4R, 1374
 - nppiMinMax_16u_C1R, 1374
 - nppiMinMax_16u_C3R, 1374
 - nppiMinMax_16u_C4R, 1375
 - nppiMinMax_32f_AC4R, 1375
 - nppiMinMax_32f_C1R, 1376
 - nppiMinMax_32f_C3R, 1376
 - nppiMinMax_32f_C4R, 1376
 - nppiMinMax_8u_AC4R, 1377
 - nppiMinMax_8u_C1R, 1377
 - nppiMinMax_8u_C3R, 1378
 - nppiMinMax_8u_C4R, 1378
- nppiMinMaxGetBufferHostSize_16s_AC4R, 1378
- nppiMinMaxGetBufferHostSize_16s_C1R, 1379
- nppiMinMaxGetBufferHostSize_16s_C3R, 1379
- nppiMinMaxGetBufferHostSize_16s_C4R, 1379
- nppiMinMaxGetBufferHostSize_16u_AC4R, 1380
- nppiMinMaxGetBufferHostSize_16u_C1R, 1380
- nppiMinMaxGetBufferHostSize_16u_C3R, 1380
- nppiMinMaxGetBufferHostSize_16u_C4R, 1380
- nppiMinMaxGetBufferHostSize_32f_AC4R, 1381
- nppiMinMaxGetBufferHostSize_32f_C1R, 1381
- nppiMinMaxGetBufferHostSize_32f_C3R, 1381
- nppiMinMaxGetBufferHostSize_32f_C4R, 1382
- nppiMinMaxGetBufferHostSize_8u_AC4R, 1382
- nppiMinMaxGetBufferHostSize_8u_C1R, 1382
- nppiMinMaxGetBufferHostSize_8u_C3R, 1382
- nppiMinMaxGetBufferHostSize_8u_C4R, 1383
- image_min_max_index
 - nppiMinMaxIndx_16u_C1MR, 1387
 - nppiMinMaxIndx_16u_C1R, 1388
 - nppiMinMaxIndx_16u_C3CMR, 1388
 - nppiMinMaxIndx_16u_C3CR, 1389
 - nppiMinMaxIndx_32f_C1MR, 1389
 - nppiMinMaxIndx_32f_C1R, 1390
 - nppiMinMaxIndx_32f_C3CMR, 1390
 - nppiMinMaxIndx_32f_C3CR, 1391
 - nppiMinMaxIndx_8s_C1MR, 1392
 - nppiMinMaxIndx_8s_C1R, 1392
 - nppiMinMaxIndx_8s_C3CMR, 1393
 - nppiMinMaxIndx_8s_C3CR, 1393
 - nppiMinMaxIndx_8u_C1MR, 1394
 - nppiMinMaxIndx_8u_C1R, 1394
 - nppiMinMaxIndx_8u_C3CMR, 1395
 - nppiMinMaxIndx_8u_C3CR, 1395
 - nppiMinMaxIndxGetBufferHostSize_16u_C1MR, 1396
 - nppiMinMaxIndxGetBufferHostSize_16u_C1R, 1396

- nppiMinMaxIdxGetBufferHostSize_16u_-C3CMR, 1396
- nppiMinMaxIdxGetBufferHostSize_16u_-C3CR, 1397
- nppiMinMaxIdxGetBufferHostSize_32f_-C1MR, 1397
- nppiMinMaxIdxGetBufferHostSize_32f_-C1R, 1397
- nppiMinMaxIdxGetBufferHostSize_32f_-C3CMR, 1398
- nppiMinMaxIdxGetBufferHostSize_32f_-C3CR, 1398
- nppiMinMaxIdxGetBufferHostSize_8s_-C1MR, 1398
- nppiMinMaxIdxGetBufferHostSize_8s_C1R, 1398
- nppiMinMaxIdxGetBufferHostSize_8s_-C3CMR, 1399
- nppiMinMaxIdxGetBufferHostSize_8s_-C3CR, 1399
- nppiMinMaxIdxGetBufferHostSize_8u_-C1MR, 1399
- nppiMinMaxIdxGetBufferHostSize_8u_-C1R, 1400
- nppiMinMaxIdxGetBufferHostSize_8u_-C3CMR, 1400
- nppiMinMaxIdxGetBufferHostSize_8u_-C3CR, 1400
- image_minevery
 - nppiMinEvery_16s_AC4IR, 1681
 - nppiMinEvery_16s_C1IR, 1681
 - nppiMinEvery_16s_C3IR, 1682
 - nppiMinEvery_16s_C4IR, 1682
 - nppiMinEvery_16u_AC4IR, 1682
 - nppiMinEvery_16u_C1IR, 1683
 - nppiMinEvery_16u_C3IR, 1683
 - nppiMinEvery_16u_C4IR, 1683
 - nppiMinEvery_32f_AC4IR, 1684
 - nppiMinEvery_32f_C1IR, 1684
 - nppiMinEvery_32f_C3IR, 1684
 - nppiMinEvery_32f_C4IR, 1685
 - nppiMinEvery_8u_AC4IR, 1685
 - nppiMinEvery_8u_C1IR, 1685
 - nppiMinEvery_8u_C3IR, 1686
 - nppiMinEvery_8u_C4IR, 1686
- image_mirror
 - nppiMirror_16s_AC4IR, 1159
 - nppiMirror_16s_AC4R, 1159
 - nppiMirror_16s_C1IR, 1160
 - nppiMirror_16s_C1R, 1160
 - nppiMirror_16s_C3IR, 1160
 - nppiMirror_16s_C3R, 1161
 - nppiMirror_16s_C4IR, 1161
 - nppiMirror_16s_C4R, 1161
 - nppiMirror_16u_AC4IR, 1162
 - nppiMirror_16u_AC4R, 1162
 - nppiMirror_16u_C1IR, 1162
 - nppiMirror_16u_C1R, 1163
 - nppiMirror_16u_C3IR, 1163
 - nppiMirror_16u_C3R, 1163
 - nppiMirror_16u_C4IR, 1164
 - nppiMirror_16u_C4R, 1164
 - nppiMirror_32f_AC4IR, 1164
 - nppiMirror_32f_AC4R, 1165
 - nppiMirror_32f_C1IR, 1165
 - nppiMirror_32f_C1R, 1165
 - nppiMirror_32f_C3IR, 1166
 - nppiMirror_32f_C3R, 1166
 - nppiMirror_32f_C4IR, 1166
 - nppiMirror_32f_C4R, 1167
 - nppiMirror_32s_AC4IR, 1167
 - nppiMirror_32s_AC4R, 1167
 - nppiMirror_32s_C1IR, 1168
 - nppiMirror_32s_C1R, 1168
 - nppiMirror_32s_C3IR, 1168
 - nppiMirror_32s_C3R, 1169
 - nppiMirror_32s_C4IR, 1169
 - nppiMirror_32s_C4R, 1169
 - nppiMirror_8u_AC4IR, 1170
 - nppiMirror_8u_AC4R, 1170
 - nppiMirror_8u_C1IR, 1170
 - nppiMirror_8u_C1R, 1171
 - nppiMirror_8u_C3IR, 1171
 - nppiMirror_8u_C3R, 1171
 - nppiMirror_8u_C4IR, 1172
 - nppiMirror_8u_C4R, 1172
- image_mul
 - nppiMul_16s_AC4IRSfs, 213
 - nppiMul_16s_AC4RSfs, 213
 - nppiMul_16s_C1IRSfs, 214
 - nppiMul_16s_C1RSfs, 214
 - nppiMul_16s_C3IRSfs, 215
 - nppiMul_16s_C3RSfs, 215
 - nppiMul_16s_C4IRSfs, 215
 - nppiMul_16s_C4RSfs, 216
 - nppiMul_16sc_AC4IRSfs, 216
 - nppiMul_16sc_AC4RSfs, 217
 - nppiMul_16sc_C1IRSfs, 217
 - nppiMul_16sc_C1RSfs, 217
 - nppiMul_16sc_C3IRSfs, 218
 - nppiMul_16sc_C3RSfs, 218
 - nppiMul_16u_AC4IRSfs, 219
 - nppiMul_16u_AC4RSfs, 219
 - nppiMul_16u_C1IRSfs, 220
 - nppiMul_16u_C1RSfs, 220
 - nppiMul_16u_C3IRSfs, 220
 - nppiMul_16u_C3RSfs, 221
 - nppiMul_16u_C4IRSfs, 221

- nppiMul_16u_C4RSfs, 222
- nppiMul_32f_AC4IR, 222
- nppiMul_32f_AC4R, 222
- nppiMul_32f_C1IR, 223
- nppiMul_32f_C1R, 223
- nppiMul_32f_C3IR, 224
- nppiMul_32f_C3R, 224
- nppiMul_32f_C4IR, 224
- nppiMul_32f_C4R, 225
- nppiMul_32fc_AC4IR, 225
- nppiMul_32fc_AC4R, 225
- nppiMul_32fc_C1IR, 226
- nppiMul_32fc_C1R, 226
- nppiMul_32fc_C3IR, 227
- nppiMul_32fc_C3R, 227
- nppiMul_32fc_C4IR, 227
- nppiMul_32fc_C4R, 228
- nppiMul_32s_C1IRSfs, 228
- nppiMul_32s_C1R, 229
- nppiMul_32s_C1RSfs, 229
- nppiMul_32s_C3IRSfs, 229
- nppiMul_32s_C3RSfs, 230
- nppiMul_32sc_AC4IRSfs, 230
- nppiMul_32sc_AC4RSfs, 231
- nppiMul_32sc_C1IRSfs, 231
- nppiMul_32sc_C1RSfs, 231
- nppiMul_32sc_C3IRSfs, 232
- nppiMul_32sc_C3RSfs, 232
- nppiMul_8u_AC4IRSfs, 233
- nppiMul_8u_AC4RSfs, 233
- nppiMul_8u_C1IRSfs, 234
- nppiMul_8u_C1RSfs, 234
- nppiMul_8u_C3IRSfs, 234
- nppiMul_8u_C3RSfs, 235
- nppiMul_8u_C4IRSfs, 235
- nppiMul_8u_C4RSfs, 236
- image_mulc
 - nppiMulC_16s_AC4IRSfs, 86
 - nppiMulC_16s_AC4RSfs, 86
 - nppiMulC_16s_C1IRSfs, 86
 - nppiMulC_16s_C1RSfs, 87
 - nppiMulC_16s_C3IRSfs, 87
 - nppiMulC_16s_C3RSfs, 87
 - nppiMulC_16s_C4IRSfs, 88
 - nppiMulC_16s_C4RSfs, 88
 - nppiMulC_16sc_AC4IRSfs, 89
 - nppiMulC_16sc_AC4RSfs, 89
 - nppiMulC_16sc_C1IRSfs, 89
 - nppiMulC_16sc_C1RSfs, 90
 - nppiMulC_16sc_C3IRSfs, 90
 - nppiMulC_16sc_C3RSfs, 91
 - nppiMulC_16u_AC4IRSfs, 91
 - nppiMulC_16u_AC4RSfs, 91
 - nppiMulC_16u_C1IRSfs, 92
- nppiMulC_16u_C1RSfs, 92
- nppiMulC_16u_C3IRSfs, 93
- nppiMulC_16u_C3RSfs, 93
- nppiMulC_16u_C4IRSfs, 93
- nppiMulC_16u_C4RSfs, 94
- nppiMulC_32f_AC4IR, 94
- nppiMulC_32f_AC4R, 94
- nppiMulC_32f_C1IR, 95
- nppiMulC_32f_C1R, 95
- nppiMulC_32f_C3IR, 95
- nppiMulC_32f_C3R, 96
- nppiMulC_32f_C4IR, 96
- nppiMulC_32f_C4R, 96
- nppiMulC_32fc_AC4IR, 97
- nppiMulC_32fc_AC4R, 97
- nppiMulC_32fc_C1IR, 97
- nppiMulC_32fc_C1R, 98
- nppiMulC_32fc_C3IR, 98
- nppiMulC_32fc_C3R, 98
- nppiMulC_32fc_C4IR, 99
- nppiMulC_32fc_C4R, 99
- nppiMulC_32s_C1IRSfs, 100
- nppiMulC_32s_C1RSfs, 100
- nppiMulC_32s_C3IRSfs, 100
- nppiMulC_32s_C3RSfs, 101
- nppiMulC_32sc_AC4IRSfs, 101
- nppiMulC_32sc_AC4RSfs, 101
- nppiMulC_32sc_C1IRSfs, 102
- nppiMulC_32sc_C1RSfs, 102
- nppiMulC_32sc_C3IRSfs, 103
- nppiMulC_32sc_C3RSfs, 103
- nppiMulC_8u_AC4IRSfs, 103
- nppiMulC_8u_AC4RSfs, 104
- nppiMulC_8u_C1IRSfs, 104
- nppiMulC_8u_C1RSfs, 105
- nppiMulC_8u_C3IRSfs, 105
- nppiMulC_8u_C3RSfs, 105
- nppiMulC_8u_C4IRSfs, 106
- nppiMulC_8u_C4RSfs, 106
- image_mulcscale
 - nppiMulCScale_16u_AC4IR, 108
 - nppiMulCScale_16u_AC4R, 108
 - nppiMulCScale_16u_C1IR, 109
 - nppiMulCScale_16u_C1R, 109
 - nppiMulCScale_16u_C3IR, 109
 - nppiMulCScale_16u_C3R, 110
 - nppiMulCScale_16u_C4IR, 110
 - nppiMulCScale_16u_C4R, 110
 - nppiMulCScale_8u_AC4IR, 111
 - nppiMulCScale_8u_AC4R, 111
 - nppiMulCScale_8u_C1IR, 111
 - nppiMulCScale_8u_C1R, 112
 - nppiMulCScale_8u_C3IR, 112
 - nppiMulCScale_8u_C3R, 112

- nppiMulCScale_8u_C4IR, 113
- nppiMulCScale_8u_C4R, 113
- image_mulscale
 - nppiMulScale_16u_AC4IR, 238
 - nppiMulScale_16u_AC4R, 239
 - nppiMulScale_16u_C1IR, 239
 - nppiMulScale_16u_C1R, 239
 - nppiMulScale_16u_C3IR, 240
 - nppiMulScale_16u_C3R, 240
 - nppiMulScale_16u_C4IR, 241
 - nppiMulScale_16u_C4R, 241
 - nppiMulScale_8u_AC4IR, 241
 - nppiMulScale_8u_AC4R, 242
 - nppiMulScale_8u_C1IR, 242
 - nppiMulScale_8u_C1R, 243
 - nppiMulScale_8u_C3IR, 243
 - nppiMulScale_8u_C3R, 243
 - nppiMulScale_8u_C4IR, 244
 - nppiMulScale_8u_C4R, 244
- image_not
 - nppiNot_8u_AC4IR, 468
 - nppiNot_8u_AC4R, 469
 - nppiNot_8u_C1IR, 469
 - nppiNot_8u_C1R, 469
 - nppiNot_8u_C3IR, 469
 - nppiNot_8u_C3R, 470
 - nppiNot_8u_C4IR, 470
 - nppiNot_8u_C4R, 470
- image_or
 - nppiOr_16u_AC4IR, 446
 - nppiOr_16u_AC4R, 446
 - nppiOr_16u_C1IR, 446
 - nppiOr_16u_C1R, 447
 - nppiOr_16u_C3IR, 447
 - nppiOr_16u_C3R, 447
 - nppiOr_16u_C4IR, 448
 - nppiOr_16u_C4R, 448
 - nppiOr_32s_AC4IR, 449
 - nppiOr_32s_AC4R, 449
 - nppiOr_32s_C1IR, 449
 - nppiOr_32s_C1R, 450
 - nppiOr_32s_C3IR, 450
 - nppiOr_32s_C3R, 450
 - nppiOr_32s_C4IR, 451
 - nppiOr_32s_C4R, 451
 - nppiOr_8u_AC4IR, 452
 - nppiOr_8u_AC4R, 452
 - nppiOr_8u_C1IR, 452
 - nppiOr_8u_C1R, 453
 - nppiOr_8u_C3IR, 453
 - nppiOr_8u_C3R, 453
 - nppiOr_8u_C4IR, 454
 - nppiOr_8u_C4R, 454
- image_orc
 - nppiOrC_16u_AC4IR, 384
 - nppiOrC_16u_AC4R, 384
 - nppiOrC_16u_C1IR, 384
 - nppiOrC_16u_C1R, 385
 - nppiOrC_16u_C3IR, 385
 - nppiOrC_16u_C3R, 385
 - nppiOrC_16u_C4IR, 386
 - nppiOrC_16u_C4R, 386
 - nppiOrC_32s_AC4IR, 386
 - nppiOrC_32s_AC4R, 387
 - nppiOrC_32s_C1IR, 387
 - nppiOrC_32s_C1R, 387
 - nppiOrC_32s_C3IR, 388
 - nppiOrC_32s_C3R, 388
 - nppiOrC_32s_C4IR, 388
 - nppiOrC_32s_C4R, 389
 - nppiOrC_8u_AC4IR, 389
 - nppiOrC_8u_AC4R, 389
 - nppiOrC_8u_C1IR, 390
 - nppiOrC_8u_C1R, 390
 - nppiOrC_8u_C3IR, 390
 - nppiOrC_8u_C3R, 391
 - nppiOrC_8u_C4IR, 391
 - nppiOrC_8u_C4R, 391
- image_perspective_transforms
 - nppiGetPerspectiveBound, 1231
 - nppiGetPerspectiveQuad, 1231
 - nppiGetPerspectiveTransform, 1232
 - nppiWarpPerspective_16u_AC4R, 1232
 - nppiWarpPerspective_16u_C1R, 1233
 - nppiWarpPerspective_16u_C3R, 1233
 - nppiWarpPerspective_16u_C4R, 1234
 - nppiWarpPerspective_16u_P3R, 1234
 - nppiWarpPerspective_16u_P4R, 1235
 - nppiWarpPerspective_32f_AC4R, 1235
 - nppiWarpPerspective_32f_C1R, 1236
 - nppiWarpPerspective_32f_C3R, 1236
 - nppiWarpPerspective_32f_C4R, 1237
 - nppiWarpPerspective_32f_P3R, 1237
 - nppiWarpPerspective_32f_P4R, 1238
 - nppiWarpPerspective_32s_AC4R, 1238
 - nppiWarpPerspective_32s_C1R, 1239
 - nppiWarpPerspective_32s_C3R, 1239
 - nppiWarpPerspective_32s_C4R, 1240
 - nppiWarpPerspective_32s_P3R, 1240
 - nppiWarpPerspective_32s_P4R, 1240
 - nppiWarpPerspective_8u_AC4R, 1241
 - nppiWarpPerspective_8u_C1R, 1241
 - nppiWarpPerspective_8u_C3R, 1242
 - nppiWarpPerspective_8u_C4R, 1242
 - nppiWarpPerspective_8u_P3R, 1243
 - nppiWarpPerspective_8u_P4R, 1243
 - nppiWarpPerspectiveBack_16u_AC4R, 1244
 - nppiWarpPerspectiveBack_16u_C1R, 1244

- nppiWarpPerspectiveBack_16u_C3R, 1245
- nppiWarpPerspectiveBack_16u_C4R, 1245
- nppiWarpPerspectiveBack_16u_P3R, 1246
- nppiWarpPerspectiveBack_16u_P4R, 1246
- nppiWarpPerspectiveBack_32f_AC4R, 1247
- nppiWarpPerspectiveBack_32f_C1R, 1247
- nppiWarpPerspectiveBack_32f_C3R, 1248
- nppiWarpPerspectiveBack_32f_C4R, 1248
- nppiWarpPerspectiveBack_32f_P3R, 1249
- nppiWarpPerspectiveBack_32f_P4R, 1249
- nppiWarpPerspectiveBack_32s_AC4R, 1250
- nppiWarpPerspectiveBack_32s_C1R, 1250
- nppiWarpPerspectiveBack_32s_C3R, 1251
- nppiWarpPerspectiveBack_32s_C4R, 1251
- nppiWarpPerspectiveBack_32s_P3R, 1252
- nppiWarpPerspectiveBack_32s_P4R, 1252
- nppiWarpPerspectiveBack_8u_AC4R, 1253
- nppiWarpPerspectiveBack_8u_C1R, 1253
- nppiWarpPerspectiveBack_8u_C3R, 1254
- nppiWarpPerspectiveBack_8u_C4R, 1254
- nppiWarpPerspectiveBack_8u_P3R, 1255
- nppiWarpPerspectiveBack_8u_P4R, 1255
- nppiWarpPerspectiveQuad_16u_AC4R, 1256
- nppiWarpPerspectiveQuad_16u_C1R, 1256
- nppiWarpPerspectiveQuad_16u_C3R, 1257
- nppiWarpPerspectiveQuad_16u_C4R, 1257
- nppiWarpPerspectiveQuad_16u_P3R, 1258
- nppiWarpPerspectiveQuad_16u_P4R, 1258
- nppiWarpPerspectiveQuad_32f_AC4R, 1259
- nppiWarpPerspectiveQuad_32f_C1R, 1259
- nppiWarpPerspectiveQuad_32f_C3R, 1260
- nppiWarpPerspectiveQuad_32f_C4R, 1260
- nppiWarpPerspectiveQuad_32f_P3R, 1261
- nppiWarpPerspectiveQuad_32f_P4R, 1261
- nppiWarpPerspectiveQuad_32s_AC4R, 1262
- nppiWarpPerspectiveQuad_32s_C1R, 1262
- nppiWarpPerspectiveQuad_32s_C3R, 1263
- nppiWarpPerspectiveQuad_32s_C4R, 1263
- nppiWarpPerspectiveQuad_32s_P3R, 1264
- nppiWarpPerspectiveQuad_32s_P4R, 1264
- nppiWarpPerspectiveQuad_8u_AC4R, 1265
- nppiWarpPerspectiveQuad_8u_C1R, 1265
- nppiWarpPerspectiveQuad_8u_C3R, 1266
- nppiWarpPerspectiveQuad_8u_C4R, 1266
- nppiWarpPerspectiveQuad_8u_P3R, 1267
- nppiWarpPerspectiveQuad_8u_P4R, 1267
- image_quality_index
 - nppiQualityIndex_16u32f_AC4R, 1858
 - nppiQualityIndex_16u32f_C1R, 1858
 - nppiQualityIndex_16u32f_C3R, 1859
 - nppiQualityIndex_32f_AC4R, 1859
 - nppiQualityIndex_32f_C1R, 1860
 - nppiQualityIndex_32f_C3R, 1860
 - nppiQualityIndex_8u32f_AC4R, 1860
 - nppiQualityIndex_8u32f_C1R, 1861
 - nppiQualityIndex_8u32f_C3R, 1861
 - nppiQualityIndexGetBufferHostSize_16u32f_AC4R, 1862
 - nppiQualityIndexGetBufferHostSize_16u32f_C1R, 1862
 - nppiQualityIndexGetBufferHostSize_16u32f_C3R, 1862
 - nppiQualityIndexGetBufferHostSize_32f_AC4R, 1863
 - nppiQualityIndexGetBufferHostSize_32f_C1R, 1863
 - nppiQualityIndexGetBufferHostSize_32f_C3R, 1863
 - nppiQualityIndexGetBufferHostSize_8u32f_AC4R, 1864
 - nppiQualityIndexGetBufferHostSize_8u32f_C1R, 1864
 - nppiQualityIndexGetBufferHostSize_8u32f_C3R, 1864
- image_quantization
 - nppiDCTFree, 693
 - nppiDCTInitAlloc, 693
 - nppiDCTQuantFwd8x8LS_JPEG_8u16s_C1R, 693
 - nppiDCTQuantFwd8x8LS_JPEG_8u16s_C1R_NEW, 694
 - nppiDCTQuantInv8x8LS_JPEG_16s8u_C1R, 694
 - nppiDCTQuantInv8x8LS_JPEG_16s8u_C1R_NEW, 695
 - NppiDCTState, 693
 - nppiQuantFwdRawTableInit_JPEG_8u, 695
 - nppiQuantFwdTableInit_JPEG_8u16u, 696
 - nppiQuantInvTableInit_JPEG_8u16u, 696
- image_rank_filters
 - nppiFilterMax_16s_AC4R, 1047
 - nppiFilterMax_16s_C1R, 1048
 - nppiFilterMax_16s_C3R, 1048
 - nppiFilterMax_16s_C4R, 1048
 - nppiFilterMax_16u_AC4R, 1049
 - nppiFilterMax_16u_C1R, 1049
 - nppiFilterMax_16u_C3R, 1050
 - nppiFilterMax_16u_C4R, 1050
 - nppiFilterMax_32f_AC4R, 1050
 - nppiFilterMax_32f_C1R, 1051
 - nppiFilterMax_32f_C3R, 1051
 - nppiFilterMax_32f_C4R, 1052
 - nppiFilterMax_8u_AC4R, 1052
 - nppiFilterMax_8u_C1R, 1052
 - nppiFilterMax_8u_C3R, 1053
 - nppiFilterMax_8u_C4R, 1053
 - nppiFilterMin_16s_AC4R, 1054
 - nppiFilterMin_16s_C1R, 1054

- nppiFilterMin_16s_C3R, 1054
- nppiFilterMin_16s_C4R, 1055
- nppiFilterMin_16u_AC4R, 1055
- nppiFilterMin_16u_C1R, 1056
- nppiFilterMin_16u_C3R, 1056
- nppiFilterMin_16u_C4R, 1056
- nppiFilterMin_32f_AC4R, 1057
- nppiFilterMin_32f_C1R, 1057
- nppiFilterMin_32f_C3R, 1058
- nppiFilterMin_32f_C4R, 1058
- nppiFilterMin_8u_AC4R, 1058
- nppiFilterMin_8u_C1R, 1059
- nppiFilterMin_8u_C3R, 1059
- nppiFilterMin_8u_C4R, 1060
- image_rectstddev
 - nppiRectStdDev_32f_C1R, 1692
 - nppiRectStdDev_32s32f_C1R, 1693
 - nppiRectStdDev_32s_C1RSfs, 1693
- image_remap
 - nppiRemap_16s_AC4R, 1128
 - nppiRemap_16s_C1R, 1129
 - nppiRemap_16s_C3R, 1129
 - nppiRemap_16s_C4R, 1130
 - nppiRemap_16s_P3R, 1131
 - nppiRemap_16s_P4R, 1131
 - nppiRemap_16u_AC4R, 1132
 - nppiRemap_16u_C1R, 1132
 - nppiRemap_16u_C3R, 1133
 - nppiRemap_16u_C4R, 1134
 - nppiRemap_16u_P3R, 1134
 - nppiRemap_16u_P4R, 1135
 - nppiRemap_32f_AC4R, 1135
 - nppiRemap_32f_C1R, 1136
 - nppiRemap_32f_C3R, 1137
 - nppiRemap_32f_C4R, 1137
 - nppiRemap_32f_P3R, 1138
 - nppiRemap_32f_P4R, 1138
 - nppiRemap_64f_AC4R, 1139
 - nppiRemap_64f_C1R, 1140
 - nppiRemap_64f_C3R, 1140
 - nppiRemap_64f_C4R, 1141
 - nppiRemap_64f_P3R, 1141
 - nppiRemap_64f_P4R, 1142
 - nppiRemap_8u_AC4R, 1143
 - nppiRemap_8u_C1R, 1143
 - nppiRemap_8u_C3R, 1144
 - nppiRemap_8u_C4R, 1144
 - nppiRemap_8u_P3R, 1145
 - nppiRemap_8u_P4R, 1146
- image_resize
 - nppiResize_16u_AC4R, 1115
 - nppiResize_16u_C1R, 1116
 - nppiResize_16u_C3R, 1116
 - nppiResize_16u_C4R, 1117
 - nppiResize_16u_P3R, 1117
 - nppiResize_16u_P4R, 1118
 - nppiResize_32f_AC4R, 1118
 - nppiResize_32f_C1R, 1119
 - nppiResize_32f_C3R, 1119
 - nppiResize_32f_C4R, 1120
 - nppiResize_32f_P3R, 1120
 - nppiResize_32f_P4R, 1121
 - nppiResize_8u_AC4R, 1121
 - nppiResize_8u_C1R, 1122
 - nppiResize_8u_C3R, 1122
 - nppiResize_8u_C4R, 1123
 - nppiResize_8u_P3R, 1123
 - nppiResize_8u_P4R, 1124
- image_resize_square_pixel
 - nppiGetResizeRect, 1095
 - nppiResizeSqrPixel_16s_AC4R, 1095
 - nppiResizeSqrPixel_16s_C1R, 1095
 - nppiResizeSqrPixel_16s_C3R, 1096
 - nppiResizeSqrPixel_16s_C4R, 1096
 - nppiResizeSqrPixel_16s_P3R, 1097
 - nppiResizeSqrPixel_16s_P4R, 1098
 - nppiResizeSqrPixel_16u_AC4R, 1098
 - nppiResizeSqrPixel_16u_C1R, 1099
 - nppiResizeSqrPixel_16u_C3R, 1099
 - nppiResizeSqrPixel_16u_C4R, 1100
 - nppiResizeSqrPixel_16u_P3R, 1100
 - nppiResizeSqrPixel_16u_P4R, 1101
 - nppiResizeSqrPixel_32f_AC4R, 1102
 - nppiResizeSqrPixel_32f_C1R, 1102
 - nppiResizeSqrPixel_32f_C3R, 1103
 - nppiResizeSqrPixel_32f_C4R, 1103
 - nppiResizeSqrPixel_32f_P3R, 1104
 - nppiResizeSqrPixel_32f_P4R, 1104
 - nppiResizeSqrPixel_64f_AC4R, 1105
 - nppiResizeSqrPixel_64f_C1R, 1106
 - nppiResizeSqrPixel_64f_C3R, 1106
 - nppiResizeSqrPixel_64f_C4R, 1107
 - nppiResizeSqrPixel_64f_P3R, 1107
 - nppiResizeSqrPixel_64f_P4R, 1108
 - nppiResizeSqrPixel_8u_AC4R, 1108
 - nppiResizeSqrPixel_8u_C1R, 1109
 - nppiResizeSqrPixel_8u_C3R, 1109
 - nppiResizeSqrPixel_8u_C4R, 1110
 - nppiResizeSqrPixel_8u_P3R, 1110
 - nppiResizeSqrPixel_8u_P4R, 1111
- image_rotate
 - nppiGetRotateBound, 1148
 - nppiGetRotateQuad, 1149
 - nppiRotate_16u_AC4R, 1149
 - nppiRotate_16u_C1R, 1150
 - nppiRotate_16u_C3R, 1150
 - nppiRotate_16u_C4R, 1151
 - nppiRotate_32f_AC4R, 1151

- nppiRotate_32f_C1R, 1152
- nppiRotate_32f_C3R, 1152
- nppiRotate_32f_C4R, 1153
- nppiRotate_8u_AC4R, 1153
- nppiRotate_8u_C1R, 1154
- nppiRotate_8u_C3R, 1154
- nppiRotate_8u_C4R, 1155
- image_rshiftc
 - nppiRShiftC_16s_AC4IR, 407
 - nppiRShiftC_16s_AC4R, 407
 - nppiRShiftC_16s_C1IR, 408
 - nppiRShiftC_16s_C1R, 408
 - nppiRShiftC_16s_C3IR, 408
 - nppiRShiftC_16s_C3R, 409
 - nppiRShiftC_16s_C4IR, 409
 - nppiRShiftC_16s_C4R, 409
 - nppiRShiftC_16u_AC4IR, 410
 - nppiRShiftC_16u_AC4R, 410
 - nppiRShiftC_16u_C1IR, 410
 - nppiRShiftC_16u_C1R, 411
 - nppiRShiftC_16u_C3IR, 411
 - nppiRShiftC_16u_C3R, 411
 - nppiRShiftC_16u_C4IR, 412
 - nppiRShiftC_16u_C4R, 412
 - nppiRShiftC_32s_AC4IR, 412
 - nppiRShiftC_32s_AC4R, 413
 - nppiRShiftC_32s_C1IR, 413
 - nppiRShiftC_32s_C1R, 413
 - nppiRShiftC_32s_C3IR, 414
 - nppiRShiftC_32s_C3R, 414
 - nppiRShiftC_32s_C4IR, 414
 - nppiRShiftC_32s_C4R, 415
 - nppiRShiftC_8s_AC4IR, 415
 - nppiRShiftC_8s_AC4R, 415
 - nppiRShiftC_8s_C1IR, 416
 - nppiRShiftC_8s_C1R, 416
 - nppiRShiftC_8s_C3IR, 416
 - nppiRShiftC_8s_C3R, 417
 - nppiRShiftC_8s_C4IR, 417
 - nppiRShiftC_8s_C4R, 417
 - nppiRShiftC_8u_AC4IR, 418
 - nppiRShiftC_8u_AC4R, 418
 - nppiRShiftC_8u_C1IR, 418
 - nppiRShiftC_8u_C1R, 419
 - nppiRShiftC_8u_C3IR, 419
 - nppiRShiftC_8u_C3R, 419
 - nppiRShiftC_8u_C4IR, 420
 - nppiRShiftC_8u_C4R, 420
- image_scale
 - nppiScale_16s8u_AC4R, 831
 - nppiScale_16s8u_C1R, 831
 - nppiScale_16s8u_C3R, 831
 - nppiScale_16s8u_C4R, 832
 - nppiScale_16u8u_AC4R, 832
 - nppiScale_16u8u_C1R, 832
 - nppiScale_16u8u_C3R, 833
 - nppiScale_16u8u_C4R, 833
 - nppiScale_32f8u_AC4R, 833
 - nppiScale_32f8u_C1R, 834
 - nppiScale_32f8u_C3R, 834
 - nppiScale_32f8u_C4R, 835
 - nppiScale_32s8u_AC4R, 835
 - nppiScale_32s8u_C1R, 835
 - nppiScale_32s8u_C3R, 836
 - nppiScale_32s8u_C4R, 836
 - nppiScale_8u16s_AC4R, 836
 - nppiScale_8u16s_C1R, 837
 - nppiScale_8u16s_C3R, 837
 - nppiScale_8u16s_C4R, 837
 - nppiScale_8u16u_AC4R, 838
 - nppiScale_8u16u_C1R, 838
 - nppiScale_8u16u_C3R, 838
 - nppiScale_8u16u_C4R, 839
 - nppiScale_8u32f_AC4R, 839
 - nppiScale_8u32f_C1R, 839
 - nppiScale_8u32f_C3R, 840
 - nppiScale_8u32f_C4R, 840
 - nppiScale_8u32s_AC4R, 841
 - nppiScale_8u32s_C1R, 841
 - nppiScale_8u32s_C3R, 841
 - nppiScale_8u32s_C4R, 842
- image_set
 - nppiSet_16s_AC4MR, 712
 - nppiSet_16s_AC4R, 713
 - nppiSet_16s_C1MR, 713
 - nppiSet_16s_C1R, 713
 - nppiSet_16s_C2R, 714
 - nppiSet_16s_C3CR, 714
 - nppiSet_16s_C3MR, 714
 - nppiSet_16s_C3R, 715
 - nppiSet_16s_C4CR, 715
 - nppiSet_16s_C4MR, 715
 - nppiSet_16s_C4R, 716
 - nppiSet_16sc_AC4R, 716
 - nppiSet_16sc_C1R, 716
 - nppiSet_16sc_C2R, 717
 - nppiSet_16sc_C3R, 717
 - nppiSet_16sc_C4R, 717
 - nppiSet_16u_AC4MR, 718
 - nppiSet_16u_AC4R, 718
 - nppiSet_16u_C1MR, 718
 - nppiSet_16u_C1R, 719
 - nppiSet_16u_C2R, 719
 - nppiSet_16u_C3CR, 719
 - nppiSet_16u_C3MR, 720
 - nppiSet_16u_C3R, 720
 - nppiSet_16u_C4CR, 720
 - nppiSet_16u_C4MR, 721

- nppiSet_16u_C4R, 721
- nppiSet_32f_AC4MR, 721
- nppiSet_32f_AC4R, 722
- nppiSet_32f_C1MR, 722
- nppiSet_32f_C1R, 722
- nppiSet_32f_C3CR, 723
- nppiSet_32f_C3MR, 723
- nppiSet_32f_C3R, 723
- nppiSet_32f_C4CR, 724
- nppiSet_32f_C4MR, 724
- nppiSet_32f_C4R, 724
- nppiSet_32fc_AC4R, 725
- nppiSet_32fc_C1R, 725
- nppiSet_32fc_C2R, 725
- nppiSet_32fc_C3R, 726
- nppiSet_32fc_C4R, 726
- nppiSet_32s_AC4MR, 726
- nppiSet_32s_AC4R, 727
- nppiSet_32s_C1MR, 727
- nppiSet_32s_C1R, 727
- nppiSet_32s_C3CR, 728
- nppiSet_32s_C3MR, 728
- nppiSet_32s_C3R, 728
- nppiSet_32s_C4CR, 729
- nppiSet_32s_C4MR, 729
- nppiSet_32s_C4R, 729
- nppiSet_32sc_AC4R, 730
- nppiSet_32sc_C1R, 730
- nppiSet_32sc_C2R, 730
- nppiSet_32sc_C3R, 731
- nppiSet_32sc_C4R, 731
- nppiSet_8s_AC4R, 731
- nppiSet_8s_C1R, 732
- nppiSet_8s_C2R, 732
- nppiSet_8s_C3R, 732
- nppiSet_8s_C4R, 733
- nppiSet_8u_AC4MR, 733
- nppiSet_8u_AC4R, 733
- nppiSet_8u_C1MR, 734
- nppiSet_8u_C1R, 734
- nppiSet_8u_C3CR, 734
- nppiSet_8u_C3MR, 735
- nppiSet_8u_C3R, 735
- nppiSet_8u_C4CR, 735
- nppiSet_8u_C4MR, 736
- nppiSet_8u_C4R, 736
- image_sqr
 - nppiSqr_16s_AC4IRSfs, 333
 - nppiSqr_16s_AC4RSfs, 333
 - nppiSqr_16s_C1IRSfs, 333
 - nppiSqr_16s_C1RSfs, 333
 - nppiSqr_16s_C3IRSfs, 334
 - nppiSqr_16s_C3RSfs, 334
 - nppiSqr_16s_C4IRSfs, 334
 - nppiSqr_16s_C4RSfs, 335
 - nppiSqr_16u_AC4IRSfs, 335
 - nppiSqr_16u_AC4RSfs, 335
 - nppiSqr_16u_C1IRSfs, 336
 - nppiSqr_16u_C1RSfs, 336
 - nppiSqr_16u_C3IRSfs, 337
 - nppiSqr_16u_C3RSfs, 337
 - nppiSqr_16u_C4IRSfs, 337
 - nppiSqr_16u_C4RSfs, 338
 - nppiSqr_32f_AC4IR, 338
 - nppiSqr_32f_AC4R, 338
 - nppiSqr_32f_C1IR, 339
 - nppiSqr_32f_C1R, 339
 - nppiSqr_32f_C3IR, 339
 - nppiSqr_32f_C3R, 339
 - nppiSqr_32f_C4IR, 340
 - nppiSqr_32f_C4R, 340
 - nppiSqr_8u_AC4IRSfs, 340
 - nppiSqr_8u_AC4RSfs, 341
 - nppiSqr_8u_C1IRSfs, 341
 - nppiSqr_8u_C1RSfs, 341
 - nppiSqr_8u_C3IRSfs, 342
 - nppiSqr_8u_C3RSfs, 342
 - nppiSqr_8u_C4IRSfs, 342
 - nppiSqr_8u_C4RSfs, 343
- image_sqrintegral
 - nppiSqrIntegral_8u32f64f_C1R, 1689
 - nppiSqrIntegral_8u32s64f_C1R, 1690
 - nppiSqrIntegral_8u32s_C1R, 1690
- image_sqrt
 - nppiSqrt_16s_AC4IRSfs, 346
 - nppiSqrt_16s_AC4RSfs, 346
 - nppiSqrt_16s_C1IRSfs, 347
 - nppiSqrt_16s_C1RSfs, 347
 - nppiSqrt_16s_C3IRSfs, 348
 - nppiSqrt_16s_C3RSfs, 348
 - nppiSqrt_16u_AC4IRSfs, 348
 - nppiSqrt_16u_AC4RSfs, 349
 - nppiSqrt_16u_C1IRSfs, 349
 - nppiSqrt_16u_C1RSfs, 349
 - nppiSqrt_16u_C3IRSfs, 350
 - nppiSqrt_16u_C3RSfs, 350
 - nppiSqrt_32f_AC4IR, 350
 - nppiSqrt_32f_AC4R, 351
 - nppiSqrt_32f_C1IR, 351
 - nppiSqrt_32f_C1R, 351
 - nppiSqrt_32f_C3IR, 352
 - nppiSqrt_32f_C3R, 352
 - nppiSqrt_32f_C4IR, 352
 - nppiSqrt_32f_C4R, 353
 - nppiSqrt_8u_AC4IRSfs, 353
 - nppiSqrt_8u_AC4RSfs, 353
 - nppiSqrt_8u_C1IRSfs, 354
 - nppiSqrt_8u_C1RSfs, 354

- nppiSqrt_8u_C3IRSfs, 355
- nppiSqrt_8u_C3RSfs, 355
- image_sub
 - nppiSub_16s_AC4IRSfs, 251
 - nppiSub_16s_AC4RSfs, 252
 - nppiSub_16s_C1IRSfs, 252
 - nppiSub_16s_C1RSfs, 252
 - nppiSub_16s_C3IRSfs, 253
 - nppiSub_16s_C3RSfs, 253
 - nppiSub_16s_C4IRSfs, 254
 - nppiSub_16s_C4RSfs, 254
 - nppiSub_16sc_AC4IRSfs, 254
 - nppiSub_16sc_AC4RSfs, 255
 - nppiSub_16sc_C1IRSfs, 255
 - nppiSub_16sc_C1RSfs, 256
 - nppiSub_16sc_C3IRSfs, 256
 - nppiSub_16sc_C3RSfs, 256
 - nppiSub_16u_AC4IRSfs, 257
 - nppiSub_16u_AC4RSfs, 257
 - nppiSub_16u_C1IRSfs, 258
 - nppiSub_16u_C1RSfs, 258
 - nppiSub_16u_C3IRSfs, 259
 - nppiSub_16u_C3RSfs, 259
 - nppiSub_16u_C4IRSfs, 259
 - nppiSub_16u_C4RSfs, 260
 - nppiSub_32f_AC4IR, 260
 - nppiSub_32f_AC4R, 261
 - nppiSub_32f_C1IR, 261
 - nppiSub_32f_C1R, 261
 - nppiSub_32f_C3IR, 262
 - nppiSub_32f_C3R, 262
 - nppiSub_32f_C4IR, 263
 - nppiSub_32f_C4R, 263
 - nppiSub_32fc_AC4IR, 263
 - nppiSub_32fc_AC4R, 264
 - nppiSub_32fc_C1IR, 264
 - nppiSub_32fc_C1R, 265
 - nppiSub_32fc_C3IR, 265
 - nppiSub_32fc_C3R, 265
 - nppiSub_32fc_C4IR, 266
 - nppiSub_32fc_C4R, 266
 - nppiSub_32s_C1IRSfs, 267
 - nppiSub_32s_C1R, 267
 - nppiSub_32s_C1RSfs, 267
 - nppiSub_32s_C3IRSfs, 268
 - nppiSub_32s_C3RSfs, 268
 - nppiSub_32s_C4IRSfs, 269
 - nppiSub_32s_C4RSfs, 269
 - nppiSub_32sc_AC4IRSfs, 270
 - nppiSub_32sc_AC4RSfs, 270
 - nppiSub_32sc_C1IRSfs, 270
 - nppiSub_32sc_C1RSfs, 271
 - nppiSub_32sc_C3IRSfs, 271
 - nppiSub_32sc_C3RSfs, 272
- nppiSub_8u_AC4IRSfs, 272
- nppiSub_8u_AC4RSfs, 272
- nppiSub_8u_C1IRSfs, 273
- nppiSub_8u_C1RSfs, 273
- nppiSub_8u_C3IRSfs, 274
- nppiSub_8u_C3RSfs, 274
- nppiSub_8u_C4IRSfs, 274
- nppiSub_8u_C4RSfs, 275
- image_subc
 - nppiSubC_16s_AC4IRSfs, 119
 - nppiSubC_16s_AC4RSfs, 119
 - nppiSubC_16s_C1IRSfs, 119
 - nppiSubC_16s_C1RSfs, 120
 - nppiSubC_16s_C3IRSfs, 120
 - nppiSubC_16s_C3RSfs, 120
 - nppiSubC_16s_C4IRSfs, 121
 - nppiSubC_16s_C4RSfs, 121
 - nppiSubC_16sc_AC4IRSfs, 122
 - nppiSubC_16sc_AC4RSfs, 122
 - nppiSubC_16sc_C1IRSfs, 122
 - nppiSubC_16sc_C1RSfs, 123
 - nppiSubC_16sc_C3IRSfs, 123
 - nppiSubC_16sc_C3RSfs, 124
 - nppiSubC_16u_AC4IRSfs, 124
 - nppiSubC_16u_AC4RSfs, 124
 - nppiSubC_16u_C1IRSfs, 125
 - nppiSubC_16u_C1RSfs, 125
 - nppiSubC_16u_C3IRSfs, 126
 - nppiSubC_16u_C3RSfs, 126
 - nppiSubC_16u_C4IRSfs, 126
 - nppiSubC_16u_C4RSfs, 127
 - nppiSubC_32f_AC4IR, 127
 - nppiSubC_32f_AC4R, 127
 - nppiSubC_32f_C1IR, 128
 - nppiSubC_32f_C1R, 128
 - nppiSubC_32f_C3IR, 128
 - nppiSubC_32f_C3R, 129
 - nppiSubC_32f_C4IR, 129
 - nppiSubC_32f_C4R, 129
 - nppiSubC_32fc_AC4IR, 130
 - nppiSubC_32fc_AC4R, 130
 - nppiSubC_32fc_C1IR, 130
 - nppiSubC_32fc_C1R, 131
 - nppiSubC_32fc_C3IR, 131
 - nppiSubC_32fc_C3R, 131
 - nppiSubC_32fc_C4IR, 132
 - nppiSubC_32fc_C4R, 132
 - nppiSubC_32s_C1IRSfs, 133
 - nppiSubC_32s_C1RSfs, 133
 - nppiSubC_32s_C3IRSfs, 133
 - nppiSubC_32s_C3RSfs, 134
 - nppiSubC_32sc_AC4IRSfs, 134
 - nppiSubC_32sc_AC4RSfs, 134
 - nppiSubC_32sc_C1IRSfs, 135

- nppiSubC_32sc_C1RSfs, 135
- nppiSubC_32sc_C3RSfs, 136
- nppiSubC_32sc_C3RSfs, 136
- nppiSubC_8u_AC4IRSfs, 136
- nppiSubC_8u_AC4RSfs, 137
- nppiSubC_8u_C1IRSfs, 137
- nppiSubC_8u_C1RSfs, 138
- nppiSubC_8u_C3IRSfs, 138
- nppiSubC_8u_C3RSfs, 138
- nppiSubC_8u_C4IRSfs, 139
- nppiSubC_8u_C4RSfs, 139
- image_sum
 - nppiSum_16s_AC4R, 1304
 - nppiSum_16s_C1R, 1304
 - nppiSum_16s_C3R, 1304
 - nppiSum_16s_C4R, 1305
 - nppiSum_16u_AC4R, 1305
 - nppiSum_16u_C1R, 1305
 - nppiSum_16u_C3R, 1306
 - nppiSum_16u_C4R, 1306
 - nppiSum_32f_AC4R, 1306
 - nppiSum_32f_C1R, 1307
 - nppiSum_32f_C3R, 1307
 - nppiSum_32f_C4R, 1307
 - nppiSum_8u64s_C1R, 1308
 - nppiSum_8u64s_C4R, 1308
 - nppiSum_8u_AC4R, 1309
 - nppiSum_8u_C1R, 1309
 - nppiSum_8u_C3R, 1309
 - nppiSum_8u_C4R, 1310
 - nppiSumGetBufferHostSize_16s_AC4R, 1310
 - nppiSumGetBufferHostSize_16s_C1R, 1310
 - nppiSumGetBufferHostSize_16s_C3R, 1311
 - nppiSumGetBufferHostSize_16s_C4R, 1311
 - nppiSumGetBufferHostSize_16u_AC4R, 1311
 - nppiSumGetBufferHostSize_16u_C1R, 1312
 - nppiSumGetBufferHostSize_16u_C3R, 1312
 - nppiSumGetBufferHostSize_16u_C4R, 1312
 - nppiSumGetBufferHostSize_32f_AC4R, 1312
 - nppiSumGetBufferHostSize_32f_C1R, 1313
 - nppiSumGetBufferHostSize_32f_C3R, 1313
 - nppiSumGetBufferHostSize_32f_C4R, 1313
 - nppiSumGetBufferHostSize_8u64s_C1R, 1314
 - nppiSumGetBufferHostSize_8u64s_C4R, 1314
 - nppiSumGetBufferHostSize_8u_AC4R, 1314
 - nppiSumGetBufferHostSize_8u_C1R, 1314
 - nppiSumGetBufferHostSize_8u_C3R, 1315
 - nppiSumGetBufferHostSize_8u_C4R, 1315
- image_swap_channels
 - nppiSwapChannels_16s_AC4R, 909
 - nppiSwapChannels_16s_C3C4R, 909
 - nppiSwapChannels_16s_C3IR, 909
 - nppiSwapChannels_16s_C3R, 910
 - nppiSwapChannels_16s_C4C3R, 910
 - nppiSwapChannels_16s_C4IR, 911
 - nppiSwapChannels_16s_C4R, 911
 - nppiSwapChannels_16u_AC4R, 911
 - nppiSwapChannels_16u_C3C4R, 912
 - nppiSwapChannels_16u_C3IR, 912
 - nppiSwapChannels_16u_C3R, 913
 - nppiSwapChannels_16u_C4C3R, 913
 - nppiSwapChannels_16u_C4IR, 914
 - nppiSwapChannels_16u_C4R, 914
 - nppiSwapChannels_32f_AC4R, 914
 - nppiSwapChannels_32f_C3C4R, 915
 - nppiSwapChannels_32f_C3IR, 915
 - nppiSwapChannels_32f_C3R, 916
 - nppiSwapChannels_32f_C4C3R, 916
 - nppiSwapChannels_32f_C4IR, 917
 - nppiSwapChannels_32f_C4R, 917
 - nppiSwapChannels_32s_AC4R, 917
 - nppiSwapChannels_32s_C3C4R, 918
 - nppiSwapChannels_32s_C3IR, 918
 - nppiSwapChannels_32s_C3R, 919
 - nppiSwapChannels_32s_C4C3R, 919
 - nppiSwapChannels_32s_C4IR, 920
 - nppiSwapChannels_32s_C4R, 920
 - nppiSwapChannels_8u_AC4R, 920
 - nppiSwapChannels_8u_C3C4R, 921
 - nppiSwapChannels_8u_C3IR, 921
 - nppiSwapChannels_8u_C3R, 922
 - nppiSwapChannels_8u_C4C3R, 922
 - nppiSwapChannels_8u_C4IR, 923
 - nppiSwapChannels_8u_C4R, 923
- image_threshold_operations
 - nppiThreshold_16s_AC4IR, 1892
 - nppiThreshold_16s_AC4R, 1892
 - nppiThreshold_16s_C1IR, 1893
 - nppiThreshold_16s_C1R, 1893
 - nppiThreshold_16s_C3IR, 1894
 - nppiThreshold_16s_C3R, 1894
 - nppiThreshold_16u_AC4IR, 1895
 - nppiThreshold_16u_AC4R, 1895
 - nppiThreshold_16u_C1IR, 1895
 - nppiThreshold_16u_C1R, 1896
 - nppiThreshold_16u_C3IR, 1896
 - nppiThreshold_16u_C3R, 1897
 - nppiThreshold_32f_AC4IR, 1897
 - nppiThreshold_32f_AC4R, 1898
 - nppiThreshold_32f_C1IR, 1898
 - nppiThreshold_32f_C1R, 1899
 - nppiThreshold_32f_C3IR, 1899
 - nppiThreshold_32f_C3R, 1899
 - nppiThreshold_8u_AC4IR, 1900
 - nppiThreshold_8u_AC4R, 1900
 - nppiThreshold_8u_C1IR, 1901

- [nppiThreshold_8u_C1R, 1901](#)
[nppiThreshold_8u_C3IR, 1902](#)
[nppiThreshold_8u_C3R, 1902](#)
[nppiThreshold_GT_16s_AC4IR, 1903](#)
[nppiThreshold_GT_16s_AC4R, 1903](#)
[nppiThreshold_GT_16s_C1IR, 1904](#)
[nppiThreshold_GT_16s_C1R, 1904](#)
[nppiThreshold_GT_16s_C3IR, 1904](#)
[nppiThreshold_GT_16s_C3R, 1905](#)
[nppiThreshold_GT_16u_AC4IR, 1905](#)
[nppiThreshold_GT_16u_AC4R, 1906](#)
[nppiThreshold_GT_16u_C1IR, 1906](#)
[nppiThreshold_GT_16u_C1R, 1906](#)
[nppiThreshold_GT_16u_C3IR, 1907](#)
[nppiThreshold_GT_16u_C3R, 1907](#)
[nppiThreshold_GT_32f_AC4IR, 1908](#)
[nppiThreshold_GT_32f_AC4R, 1908](#)
[nppiThreshold_GT_32f_C1IR, 1908](#)
[nppiThreshold_GT_32f_C1R, 1909](#)
[nppiThreshold_GT_32f_C3IR, 1909](#)
[nppiThreshold_GT_32f_C3R, 1910](#)
[nppiThreshold_GT_8u_AC4IR, 1910](#)
[nppiThreshold_GT_8u_AC4R, 1910](#)
[nppiThreshold_GT_8u_C1IR, 1911](#)
[nppiThreshold_GT_8u_C1R, 1911](#)
[nppiThreshold_GT_8u_C3IR, 1912](#)
[nppiThreshold_GT_8u_C3R, 1912](#)
[nppiThreshold_GTVVal_16s_AC4IR, 1912](#)
[nppiThreshold_GTVVal_16s_AC4R, 1913](#)
[nppiThreshold_GTVVal_16s_C1IR, 1913](#)
[nppiThreshold_GTVVal_16s_C1R, 1914](#)
[nppiThreshold_GTVVal_16s_C3IR, 1914](#)
[nppiThreshold_GTVVal_16s_C3R, 1914](#)
[nppiThreshold_GTVVal_16u_AC4IR, 1915](#)
[nppiThreshold_GTVVal_16u_AC4R, 1915](#)
[nppiThreshold_GTVVal_16u_C1IR, 1916](#)
[nppiThreshold_GTVVal_16u_C1R, 1916](#)
[nppiThreshold_GTVVal_16u_C3IR, 1917](#)
[nppiThreshold_GTVVal_16u_C3R, 1917](#)
[nppiThreshold_GTVVal_32f_AC4IR, 1917](#)
[nppiThreshold_GTVVal_32f_AC4R, 1918](#)
[nppiThreshold_GTVVal_32f_C1IR, 1918](#)
[nppiThreshold_GTVVal_32f_C1R, 1919](#)
[nppiThreshold_GTVVal_32f_C3IR, 1919](#)
[nppiThreshold_GTVVal_32f_C3R, 1919](#)
[nppiThreshold_GTVVal_8u_AC4IR, 1920](#)
[nppiThreshold_GTVVal_8u_AC4R, 1920](#)
[nppiThreshold_GTVVal_8u_C1IR, 1921](#)
[nppiThreshold_GTVVal_8u_C1R, 1921](#)
[nppiThreshold_GTVVal_8u_C3IR, 1922](#)
[nppiThreshold_GTVVal_8u_C3R, 1922](#)
[nppiThreshold_LT_16s_AC4IR, 1922](#)
[nppiThreshold_LT_16s_AC4R, 1923](#)
[nppiThreshold_LT_16s_C1IR, 1923](#)
[nppiThreshold_LT_16s_C1R, 1924](#)
[nppiThreshold_LT_16s_C3IR, 1924](#)
[nppiThreshold_LT_16s_C3R, 1924](#)
[nppiThreshold_LT_16u_AC4IR, 1925](#)
[nppiThreshold_LT_16u_AC4R, 1925](#)
[nppiThreshold_LT_16u_C1IR, 1926](#)
[nppiThreshold_LT_16u_C1R, 1926](#)
[nppiThreshold_LT_16u_C3IR, 1926](#)
[nppiThreshold_LT_16u_C3R, 1927](#)
[nppiThreshold_LT_32f_AC4IR, 1927](#)
[nppiThreshold_LT_32f_AC4R, 1928](#)
[nppiThreshold_LT_32f_C1IR, 1928](#)
[nppiThreshold_LT_32f_C1R, 1928](#)
[nppiThreshold_LT_32f_C3IR, 1929](#)
[nppiThreshold_LT_32f_C3R, 1929](#)
[nppiThreshold_LT_8u_AC4IR, 1930](#)
[nppiThreshold_LT_8u_AC4R, 1930](#)
[nppiThreshold_LT_8u_C1IR, 1930](#)
[nppiThreshold_LT_8u_C1R, 1931](#)
[nppiThreshold_LT_8u_C3IR, 1931](#)
[nppiThreshold_LT_8u_C3R, 1932](#)
[nppiThreshold_LTVVal_16s_AC4IR, 1932](#)
[nppiThreshold_LTVVal_16s_AC4R, 1932](#)
[nppiThreshold_LTVVal_16s_C1IR, 1933](#)
[nppiThreshold_LTVVal_16s_C1R, 1933](#)
[nppiThreshold_LTVVal_16s_C3IR, 1934](#)
[nppiThreshold_LTVVal_16s_C3R, 1934](#)
[nppiThreshold_LTVVal_16u_AC4IR, 1935](#)
[nppiThreshold_LTVVal_16u_AC4R, 1935](#)
[nppiThreshold_LTVVal_16u_C1IR, 1935](#)
[nppiThreshold_LTVVal_16u_C1R, 1936](#)
[nppiThreshold_LTVVal_16u_C3IR, 1936](#)
[nppiThreshold_LTVVal_16u_C3R, 1937](#)
[nppiThreshold_LTVVal_32f_AC4IR, 1937](#)
[nppiThreshold_LTVVal_32f_AC4R, 1937](#)
[nppiThreshold_LTVVal_32f_C1IR, 1938](#)
[nppiThreshold_LTVVal_32f_C1R, 1938](#)
[nppiThreshold_LTVVal_32f_C3IR, 1939](#)
[nppiThreshold_LTVVal_32f_C3R, 1939](#)
[nppiThreshold_LTVVal_8u_AC4IR, 1940](#)
[nppiThreshold_LTVVal_8u_AC4R, 1940](#)
[nppiThreshold_LTVVal_8u_C1IR, 1940](#)
[nppiThreshold_LTVVal_8u_C1R, 1941](#)
[nppiThreshold_LTVVal_8u_C3IR, 1941](#)
[nppiThreshold_LTVVal_8u_C3R, 1942](#)
[nppiThreshold_LTVValGTVVal_16s_AC4IR,
1942](#)
[nppiThreshold_LTVValGTVVal_16s_AC4R,
1943](#)
[nppiThreshold_LTVValGTVVal_16s_C1IR, 1943](#)
[nppiThreshold_LTVValGTVVal_16s_C1R, 1944](#)
[nppiThreshold_LTVValGTVVal_16s_C3IR, 1944](#)
[nppiThreshold_LTVValGTVVal_16s_C3R, 1945](#)

- nppiThreshold_LTValGTVal_16u_AC4IR, 1945
- nppiThreshold_LTValGTVal_16u_AC4R, 1946
- nppiThreshold_LTValGTVal_16u_C1IR, 1946
- nppiThreshold_LTValGTVal_16u_C1R, 1947
- nppiThreshold_LTValGTVal_16u_C3IR, 1947
- nppiThreshold_LTValGTVal_16u_C3R, 1948
- nppiThreshold_LTValGTVal_32f_AC4IR, 1948
- nppiThreshold_LTValGTVal_32f_AC4R, 1949
- nppiThreshold_LTValGTVal_32f_C1IR, 1949
- nppiThreshold_LTValGTVal_32f_C1R, 1950
- nppiThreshold_LTValGTVal_32f_C3IR, 1950
- nppiThreshold_LTValGTVal_32f_C3R, 1951
- nppiThreshold_LTValGTVal_8u_AC4IR, 1951
- nppiThreshold_LTValGTVal_8u_AC4R, 1952
- nppiThreshold_LTValGTVal_8u_C1IR, 1952
- nppiThreshold_LTValGTVal_8u_C1R, 1953
- nppiThreshold_LTValGTVal_8u_C3IR, 1953
- nppiThreshold_LTValGTVal_8u_C3R, 1954
- nppiThreshold_Val_16s_AC4IR, 1954
- nppiThreshold_Val_16s_AC4R, 1955
- nppiThreshold_Val_16s_C1IR, 1955
- nppiThreshold_Val_16s_C1R, 1956
- nppiThreshold_Val_16s_C3IR, 1956
- nppiThreshold_Val_16s_C3R, 1957
- nppiThreshold_Val_16u_AC4IR, 1957
- nppiThreshold_Val_16u_AC4R, 1958
- nppiThreshold_Val_16u_C1IR, 1958
- nppiThreshold_Val_16u_C1R, 1959
- nppiThreshold_Val_16u_C3IR, 1959
- nppiThreshold_Val_16u_C3R, 1960
- nppiThreshold_Val_32f_AC4IR, 1960
- nppiThreshold_Val_32f_AC4R, 1961
- nppiThreshold_Val_32f_C1IR, 1961
- nppiThreshold_Val_32f_C1R, 1962
- nppiThreshold_Val_32f_C3IR, 1962
- nppiThreshold_Val_32f_C3R, 1963
- nppiThreshold_Val_8u_AC4IR, 1963
- nppiThreshold_Val_8u_AC4R, 1964
- nppiThreshold_Val_8u_C1IR, 1964
- nppiThreshold_Val_8u_C1R, 1965
- nppiThreshold_Val_8u_C3IR, 1965
- nppiThreshold_Val_8u_C3R, 1966
- image_transpose
 - nppiTranspose_16s_C1R, 900
 - nppiTranspose_16s_C3R, 900
 - nppiTranspose_16s_C4R, 901
 - nppiTranspose_16u_C1R, 901
 - nppiTranspose_16u_C3R, 901
 - nppiTranspose_16u_C4R, 902
 - nppiTranspose_32f_C1R, 902
 - nppiTranspose_32f_C3R, 902
 - nppiTranspose_32f_C4R, 903
 - nppiTranspose_32s_C1R, 903
 - nppiTranspose_32s_C3R, 903
 - nppiTranspose_32s_C4R, 904
 - nppiTranspose_8u_C1R, 904
 - nppiTranspose_8u_C3R, 904
 - nppiTranspose_8u_C4R, 905
- image_xor
 - nppiXor_16u_AC4IR, 458
 - nppiXor_16u_AC4R, 458
 - nppiXor_16u_C1IR, 458
 - nppiXor_16u_C1R, 459
 - nppiXor_16u_C3IR, 459
 - nppiXor_16u_C3R, 459
 - nppiXor_16u_C4IR, 460
 - nppiXor_16u_C4R, 460
 - nppiXor_32s_AC4IR, 461
 - nppiXor_32s_AC4R, 461
 - nppiXor_32s_C1IR, 461
 - nppiXor_32s_C1R, 462
 - nppiXor_32s_C3IR, 462
 - nppiXor_32s_C3R, 462
 - nppiXor_32s_C4IR, 463
 - nppiXor_32s_C4R, 463
 - nppiXor_8u_AC4IR, 464
 - nppiXor_8u_AC4R, 464
 - nppiXor_8u_C1IR, 464
 - nppiXor_8u_C1R, 465
 - nppiXor_8u_C3IR, 465
 - nppiXor_8u_C3R, 465
 - nppiXor_8u_C4IR, 466
 - nppiXor_8u_C4R, 466
- image_xorc
 - nppiXorC_16u_AC4IR, 395
 - nppiXorC_16u_AC4R, 395
 - nppiXorC_16u_C1IR, 395
 - nppiXorC_16u_C1R, 396
 - nppiXorC_16u_C3IR, 396
 - nppiXorC_16u_C3R, 396
 - nppiXorC_16u_C4IR, 397
 - nppiXorC_16u_C4R, 397
 - nppiXorC_32s_AC4IR, 397
 - nppiXorC_32s_AC4R, 398
 - nppiXorC_32s_C1IR, 398
 - nppiXorC_32s_C1R, 398
 - nppiXorC_32s_C3IR, 399
 - nppiXorC_32s_C3R, 399
 - nppiXorC_32s_C4IR, 399
 - nppiXorC_32s_C4R, 400
 - nppiXorC_8u_AC4IR, 400
 - nppiXorC_8u_AC4R, 400
 - nppiXorC_8u_C1IR, 401

- nppiXorC_8u_C1R, 401
 - nppiXorC_8u_C3IR, 401
 - nppiXorC_8u_C3R, 402
 - nppiXorC_8u_C4IR, 402
 - nppiXorC_8u_C4R, 402
- Infinity Norm, 2260
- Infinity Norm Diff, 2277
- Initialization, 2190
- Integral, 1687, 2189
- L1 Norm, 2265
- L1 Norm Diff, 2282
- L2 Norm, 2271
- L2 Norm Diff, 2288
- Labeling and Segmentation, 698
- Linear Transforms, 1269
- Ln, 356, 2113
- Logical And Shift Operations, 2129
- Logical Operations, 370
- LShiftC, 421, 2151
- major
 - NppLibraryVersion, 2334
- Malloc, 2318
- Max, 1343
- MaxEvery, 1673
- Maximum, 2215
- MaxIdx, 1356
- Mean, 1401, 2235
- Mean And Standard Deviation, 2244
- Mean_StdDev, 1422
- Memory Management, 1865, 2317
- Min, 1316
- MinEvery, 1680
- MinEvery And MaxEvery Functions, 2204
- Minimum, 2225
- Minimum_Maximum, 2248
- MinIdx, 1329
- MinMax, 1370
- MinMaxIdx, 1384
- minor
 - NppLibraryVersion, 2334
- Mirror, 1156
- Morphological Operations, 1272
- Mul, 208, 2057
- MulC, 81, 2004
- MulCScale, 107
- MulScale, 237
- Norm_Inf, 1440
- Norm_L1, 1462
- Norm_L2, 1483
- Normalize, 2124
- NormDiff_Inf, 1504
- NormDiff_L1, 1527
- NormDiff_L2, 1550
- NormRel_Inf, 1573
- NormRel_L1, 1596
- NormRel_L2, 1619
- Not, 468, 2148
- NPP Core, 31
- NPP Image Processing, 51
- NPP Signal Processing, 1990
- NPP Type Definitions and Constants, 34
- Npp16s
 - npp_basic_types, 48
- Npp16sc
 - npp_basic_types, 50
- Npp16u
 - npp_basic_types, 48
- Npp16uc
 - npp_basic_types, 50
- Npp32f
 - npp_basic_types, 48
- Npp32fc
 - npp_basic_types, 48
- Npp32s
 - npp_basic_types, 48
- Npp32sc
 - npp_basic_types, 48
- Npp32u
 - npp_basic_types, 49
- Npp32uc
 - npp_basic_types, 49
- Npp64f
 - npp_basic_types, 49
- Npp64fc
 - npp_basic_types, 49
- Npp64s
 - npp_basic_types, 49
- Npp64sc
 - npp_basic_types, 49
- Npp64u
 - npp_basic_types, 49
- Npp8s
 - npp_basic_types, 49
- Npp8u
 - npp_basic_types, 49
- Npp8uc
 - npp_basic_types, 50
- NPP_AFFINE_QUAD_INCORRECT_WARNING
 - typedefs_npp, 45
- NPP_ALG_HINT_ACCURATE
 - typedefs_npp, 41
- NPP_ALG_HINT_FAST
 - typedefs_npp, 41
- NPP_ALG_HINT_NONE
 - typedefs_npp, 41

- NPP_ALIGNMENT_ERROR
typedefs_npp, 44
- NPP_ANCHOR_ERROR
typedefs_npp, 44
- NPP_BAD_ARGUMENT_ERROR
typedefs_npp, 45
- NPP_BORDER_CONSTANT
typedefs_npp, 42
- NPP_BORDER_NONE
typedefs_npp, 42
- NPP_BORDER_REPLICATE
typedefs_npp, 42
- NPP_BORDER_UNDEFINED
typedefs_npp, 42
- NPP_BORDER_WRAP
typedefs_npp, 42
- NPP_BOTH_AXIS
typedefs_npp, 42
- NPP_CHANNEL_ERROR
typedefs_npp, 44
- NPP_CHANNEL_ORDER_ERROR
typedefs_npp, 44
- NPP_CMP_EQ
typedefs_npp, 41
- NPP_CMP_GREATER
typedefs_npp, 41
- NPP_CMP_GREATER_EQ
typedefs_npp, 41
- NPP_CMP_LESS
typedefs_npp, 41
- NPP_CMP_LESS_EQ
typedefs_npp, 41
- NPP_COEFFICIENT_ERROR
typedefs_npp, 44
- NPP_COI_ERROR
typedefs_npp, 44
- NPP_CONTEXT_MATCH_ERROR
typedefs_npp, 45
- NPP_CUDA_1_0
typedefs_npp, 41
- NPP_CUDA_1_1
typedefs_npp, 41
- NPP_CUDA_1_2
typedefs_npp, 41
- NPP_CUDA_1_3
typedefs_npp, 41
- NPP_CUDA_2_0
typedefs_npp, 41
- NPP_CUDA_2_1
typedefs_npp, 41
- NPP_CUDA_3_0
typedefs_npp, 41
- NPP_CUDA_3_5
typedefs_npp, 41
- NPP_CUDA_KERNEL_EXECUTION_ERROR
typedefs_npp, 44
- NPP_CUDA_NOT_CAPABLE
typedefs_npp, 41
- NPP_CUDA_UNKNOWN_VERSION
typedefs_npp, 41
- NPP_DATA_TYPE_ERROR
typedefs_npp, 45
- NPP_DIVIDE_BY_ZERO_ERROR
typedefs_npp, 45
- NPP_DIVIDE_BY_ZERO_WARNING
typedefs_npp, 45
- NPP_DIVISOR_ERROR
typedefs_npp, 44
- NPP_DOUBLE_SIZE_WARNING
typedefs_npp, 45
- NPP_ERROR
typedefs_npp, 45
- NPP_ERROR_RESERVED
typedefs_npp, 45
- NPP_FFT_FLAG_ERROR
typedefs_npp, 45
- NPP_FFT_ORDER_ERROR
typedefs_npp, 45
- NPP_HAAR_CLASSIFIER_PIXEL_MATCH_-
ERROR
typedefs_npp, 44
- NPP_HISTOGRAM_NUMBER_OF_LEVELS_-
ERROR
typedefs_npp, 44
- NPP_HORIZONTAL_AXIS
typedefs_npp, 42
- NPP_INTERPOLATION_ERROR
typedefs_npp, 44
- NPP_INVALID_DEVICE_POINTER_ERROR
typedefs_npp, 44
- NPP_INVALID_HOST_POINTER_ERROR
typedefs_npp, 44
- NPP_LUT_NUMBER_OF_LEVELS_ERROR
typedefs_npp, 44
- NPP_LUT_PALETTE_BITSIZE_ERROR
typedefs_npp, 44
- NPP_MASK_SIZE_1_X_3
typedefs_npp, 43
- NPP_MASK_SIZE_1_X_5
typedefs_npp, 43
- NPP_MASK_SIZE_3_X_1
typedefs_npp, 43
- NPP_MASK_SIZE_3_X_3
typedefs_npp, 43
- NPP_MASK_SIZE_5_X_1
typedefs_npp, 43
- NPP_MASK_SIZE_5_X_5
typedefs_npp, 43

- NPP_MASK_SIZE_ERROR
 - typedefs_npp, 44
- NPP_MEMCPY_ERROR
 - typedefs_npp, 44
- NPP_MEMFREE_ERR
 - typedefs_npp, 44
- NPP_MEMORY_ALLOCATION_ERR
 - typedefs_npp, 45
- NPP_MEMSET_ERR
 - typedefs_npp, 44
- NPP_MIRROR_FLIP_ERR
 - typedefs_npp, 45
- NPP_MISALIGNED_DST_ROI_WARNING
 - typedefs_npp, 45
- NPP_MOMENT_00_ZERO_ERROR
 - typedefs_npp, 45
- NPP_NO_ERROR
 - typedefs_npp, 45
- NPP_NO_MEMORY_ERROR
 - typedefs_npp, 45
- NPP_NO_OPERATION_WARNING
 - typedefs_npp, 45
- NPP_NOT_EVEN_STEP_ERROR
 - typedefs_npp, 44
- NPP_NOT_IMPLEMENTED_ERROR
 - typedefs_npp, 45
- NPP_NOT_SUFFICIENT_COMPUTE_ -
CAPABILITY
 - typedefs_npp, 44
- NPP_NOT_SUPPORTED_MODE_ERROR
 - typedefs_npp, 44
- NPP_NULL_POINTER_ERROR
 - typedefs_npp, 45
- NPP_NUMBER_OF_CHANNELS_ERROR
 - typedefs_npp, 44
- NPP_OUT_OFF_RANGE_ERROR
 - typedefs_npp, 45
- NPP_QUADRANGLE_ERROR
 - typedefs_npp, 44
- NPP_QUALITY_INDEX_ERROR
 - typedefs_npp, 44
- NPP_RANGE_ERROR
 - typedefs_npp, 45
- NPP_RECTANGLE_ERROR
 - typedefs_npp, 44
- NPP_RESIZE_FACTOR_ERROR
 - typedefs_npp, 44
- NPP_RESIZE_NO_OPERATION_ERROR
 - typedefs_npp, 44
- NPP_RND_FINANCIAL
 - typedefs_npp, 43
- NPP_RND_NEAR
 - typedefs_npp, 43
- NPP_RND_ZERO
 - typedefs_npp, 43
- NPP_ROUND_MODE_NOT_SUPPORTED_ -
ERROR
 - typedefs_npp, 44
- NPP_ROUND_NEAREST_TIES_AWAY_ -
FROM_ZERO
 - typedefs_npp, 43
- NPP_ROUND_NEAREST_TIES_TO_EVEN
 - typedefs_npp, 43
- NPP_ROUND_TOWARD_ZERO
 - typedefs_npp, 43
- NPP_SCALE_RANGE_ERROR
 - typedefs_npp, 45
- NPP_SIZE_ERROR
 - typedefs_npp, 45
- NPP_STEP_ERROR
 - typedefs_npp, 45
- NPP_STRIDE_ERROR
 - typedefs_npp, 44
- NPP_SUCCESS
 - typedefs_npp, 45
- NPP_TEXTURE_BIND_ERROR
 - typedefs_npp, 44
- NPP_THRESHOLD_ERROR
 - typedefs_npp, 45
- NPP_THRESHOLD_NEGATIVE_LEVEL_ -
ERROR
 - typedefs_npp, 45
- NPP_VERTICAL_AXIS
 - typedefs_npp, 42
- NPP_WRONG_INTERSECTION_QUAD_ -
WARNING
 - typedefs_npp, 45
- NPP_WRONG_INTERSECTION_ROI_ERROR
 - typedefs_npp, 44
- NPP_WRONG_INTERSECTION_ROI_ -
WARNING
 - typedefs_npp, 45
- NPP_ZC_MODE_NOT_SUPPORTED_ERROR
 - typedefs_npp, 44
- NPP_ZERO_MASK_VALUE_ERROR
 - typedefs_npp, 44
- NPP_ALIGN_16, 2325
 - im, 2325
 - re, 2326
- NPP_ALIGN_8, 2327
 - im, 2327
 - re, 2327, 2328
- npp_basic_types
 - __align__, 49, 50
 - Npp16s, 48
 - Npp16sc, 50
 - Npp16u, 48
 - Npp16uc, 50

- Npp32f, 48
- Npp32fc, 48
- Npp32s, 48
- Npp32sc, 48
- Npp32u, 49
- Npp32uc, 49
- Npp64f, 49
- Npp64fc, 49
- Npp64s, 49
- Npp64sc, 49
- Npp64u, 49
- Npp8s, 49
- Npp8u, 49
- Npp8uc, 50
- NPP_MAX_16S
 - typedefs_npp, 39
- NPP_MAX_16U
 - typedefs_npp, 39
- NPP_MAX_32S
 - typedefs_npp, 39
- NPP_MAX_32U
 - typedefs_npp, 39
- NPP_MAX_64S
 - typedefs_npp, 39
- NPP_MAX_64U
 - typedefs_npp, 39
- NPP_MAX_8S
 - typedefs_npp, 39
- NPP_MAX_8U
 - typedefs_npp, 39
- NPP_MAXABS_32F
 - typedefs_npp, 39
- NPP_MAXABS_64F
 - typedefs_npp, 40
- NPP_MIN_16S
 - typedefs_npp, 40
- NPP_MIN_16U
 - typedefs_npp, 40
- NPP_MIN_32S
 - typedefs_npp, 40
- NPP_MIN_32U
 - typedefs_npp, 40
- NPP_MIN_64S
 - typedefs_npp, 40
- NPP_MIN_64U
 - typedefs_npp, 40
- NPP_MIN_8S
 - typedefs_npp, 40
- NPP_MIN_8U
 - typedefs_npp, 40
- NPP_MINABS_32F
 - typedefs_npp, 40
- NPP_MINABS_64F
 - typedefs_npp, 40
- NppCmpOp
 - typedefs_npp, 41
- nppGetGpuComputeCapability
 - core_npp, 32
- nppGetGpuName
 - core_npp, 32
- nppGetGpuNumSMs
 - core_npp, 32
- nppGetLibVersion
 - core_npp, 32
- nppGetMaxThreadsPerBlock
 - core_npp, 32
- nppGetMaxThreadsPerSM
 - core_npp, 32
- nppGetStream
 - core_npp, 33
- NppGpuComputeCapability
 - typedefs_npp, 41
- NppHintAlgorithm
 - typedefs_npp, 41
- NPPI_INTER_CUBIC
 - typedefs_npp, 42
- NPPI_INTER_CUBIC2P_B05C03
 - typedefs_npp, 42
- NPPI_INTER_CUBIC2P_BSPLINE
 - typedefs_npp, 42
- NPPI_INTER_CUBIC2P_CATMULLROM
 - typedefs_npp, 42
- NPPI_INTER_LANCZOS
 - typedefs_npp, 42
- NPPI_INTER_LINEAR
 - typedefs_npp, 42
- NPPI_INTER_NN
 - typedefs_npp, 42
- NPPI_INTER_SUPER
 - typedefs_npp, 42
- NPPI_INTER_UNDEFINED
 - typedefs_npp, 42
- NPPI_OP_ALPHA_ATOP
 - typedefs_npp, 41
- NPPI_OP_ALPHA_ATOP_PREMUL
 - typedefs_npp, 42
- NPPI_OP_ALPHA_IN
 - typedefs_npp, 41
- NPPI_OP_ALPHA_IN_PREMUL
 - typedefs_npp, 42
- NPPI_OP_ALPHA_OUT
 - typedefs_npp, 41
- NPPI_OP_ALPHA_OUT_PREMUL
 - typedefs_npp, 42
- NPPI_OP_ALPHA_OVER
 - typedefs_npp, 41
- NPPI_OP_ALPHA_OVER_PREMUL
 - typedefs_npp, 42

NPPI_OP_ALPHA_PLUS
typedefs_npp, 42

NPPI_OP_ALPHA_PLUS_PREMUL
typedefs_npp, 42

NPPI_OP_ALPHA_PREMUL
typedefs_npp, 42

NPPI_OP_ALPHA_XOR
typedefs_npp, 42

NPPI_OP_ALPHA_XOR_PREMUL
typedefs_npp, 42

NPPI_SMOOTH_EDGE
typedefs_npp, 42

nppiAbs_16s_AC4IR
image_abs, 321

nppiAbs_16s_AC4R
image_abs, 321

nppiAbs_16s_C1IR
image_abs, 321

nppiAbs_16s_C1R
image_abs, 322

nppiAbs_16s_C3IR
image_abs, 322

nppiAbs_16s_C3R
image_abs, 322

nppiAbs_16s_C4IR
image_abs, 323

nppiAbs_16s_C4R
image_abs, 323

nppiAbs_32f_AC4IR
image_abs, 323

nppiAbs_32f_AC4R
image_abs, 324

nppiAbs_32f_C1IR
image_abs, 324

nppiAbs_32f_C3IR
image_abs, 325

nppiAbs_32f_C3R
image_abs, 325

nppiAbs_32f_C4IR
image_abs, 325

nppiAbs_32f_C4R
image_abs, 326

nppiAbsDiff_16u_C1R
image_absdiff, 327

nppiAbsDiff_32f_C1R
image_absdiff, 328

nppiAbsDiff_8u_C1R
image_absdiff, 328

nppiAbsDiff_8u_C3R
image_absdiff, 328

nppiAbsDiff_8u_C4R
image_absdiff, 329

nppiAbsDiffC_16u_C1R
image_absdiffc, 166

nppiAbsDiffC_32f_C1R
image_absdiffc, 166

nppiAbsDiffC_8u_C1R
image_absdiffc, 167

nppiAdd_16s_AC4IRSfs
image_add, 173

nppiAdd_16s_AC4RSfs
image_add, 173

nppiAdd_16s_C1IRSfs
image_add, 174

nppiAdd_16s_C1RSfs
image_add, 174

nppiAdd_16s_C3IRSfs
image_add, 175

nppiAdd_16s_C3RSfs
image_add, 175

nppiAdd_16s_C4IRSfs
image_add, 175

nppiAdd_16s_C4RSfs
image_add, 176

nppiAdd_16sc_AC4IRSfs
image_add, 176

nppiAdd_16sc_AC4RSfs
image_add, 177

nppiAdd_16sc_C1IRSfs
image_add, 177

nppiAdd_16sc_C1RSfs
image_add, 177

nppiAdd_16sc_C3IRSfs
image_add, 178

nppiAdd_16sc_C3RSfs
image_add, 178

nppiAdd_16u_AC4IRSfs
image_add, 179

nppiAdd_16u_AC4RSfs
image_add, 179

nppiAdd_16u_C1IRSfs
image_add, 180

nppiAdd_16u_C1RSfs
image_add, 180

nppiAdd_16u_C3IRSfs
image_add, 180

nppiAdd_16u_C3RSfs
image_add, 181

nppiAdd_16u_C4IRSfs
image_add, 181

nppiAdd_16u_C4RSfs
image_add, 182

nppiAdd_32f_AC4IR
image_add, 182

nppiAdd_32f_AC4R
image_add, 182

- nppiAdd_32f_C1IR
 image_add, 183
 nppiAdd_32f_C1R
 image_add, 183
 nppiAdd_32f_C3IR
 image_add, 184
 nppiAdd_32f_C3R
 image_add, 184
 nppiAdd_32f_C4IR
 image_add, 184
 nppiAdd_32f_C4R
 image_add, 185
 nppiAdd_32fc_AC4IR
 image_add, 185
 nppiAdd_32fc_AC4R
 image_add, 185
 nppiAdd_32fc_C1IR
 image_add, 186
 nppiAdd_32fc_C1R
 image_add, 186
 nppiAdd_32fc_C3IR
 image_add, 187
 nppiAdd_32fc_C3R
 image_add, 187
 nppiAdd_32fc_C4IR
 image_add, 187
 nppiAdd_32fc_C4R
 image_add, 188
 nppiAdd_32s_C1IRSfs
 image_add, 188
 nppiAdd_32s_C1R
 image_add, 189
 nppiAdd_32s_C1RSfs
 image_add, 189
 nppiAdd_32s_C3IRSfs
 image_add, 189
 nppiAdd_32s_C3RSfs
 image_add, 190
 nppiAdd_32sc_AC4IRSfs
 image_add, 190
 nppiAdd_32sc_AC4RSfs
 image_add, 191
 nppiAdd_32sc_C1IRSfs
 image_add, 191
 nppiAdd_32sc_C1RSfs
 image_add, 191
 nppiAdd_32sc_C3IRSfs
 image_add, 192
 nppiAdd_32sc_C3RSfs
 image_add, 192
 nppiAdd_8u_AC4IRSfs
 image_add, 193
 nppiAdd_8u_AC4RSfs
 image_add, 193
 nppiAdd_8u_C1IRSfs
 image_add, 194
 nppiAdd_8u_C1RSfs
 image_add, 194
 nppiAdd_8u_C3IRSfs
 image_add, 194
 nppiAdd_8u_C3RSfs
 image_add, 195
 nppiAdd_8u_C4IRSfs
 image_add, 195
 nppiAdd_8u_C4RSfs
 image_add, 196
 nppiAddC_16s_AC4IRSfs
 image_addc, 60
 nppiAddC_16s_AC4RSfs
 image_addc, 60
 nppiAddC_16s_C1IRSfs
 image_addc, 60
 nppiAddC_16s_C1RSfs
 image_addc, 61
 nppiAddC_16s_C3IRSfs
 image_addc, 61
 nppiAddC_16s_C3RSfs
 image_addc, 61
 nppiAddC_16s_C4IRSfs
 image_addc, 62
 nppiAddC_16s_C4RSfs
 image_addc, 62
 nppiAddC_16sc_AC4IRSfs
 image_addc, 63
 nppiAddC_16sc_AC4RSfs
 image_addc, 63
 nppiAddC_16sc_C1IRSfs
 image_addc, 63
 nppiAddC_16sc_C1RSfs
 image_addc, 64
 nppiAddC_16sc_C3IRSfs
 image_addc, 64
 nppiAddC_16sc_C3RSfs
 image_addc, 65
 nppiAddC_16u_AC4IRSfs
 image_addc, 65
 nppiAddC_16u_AC4RSfs
 image_addc, 65
 nppiAddC_16u_C1IRSfs
 image_addc, 66
 nppiAddC_16u_C1RSfs
 image_addc, 66
 nppiAddC_16u_C3IRSfs
 image_addc, 67
 nppiAddC_16u_C3RSfs
 image_addc, 67
 nppiAddC_16u_C4IRSfs
 image_addc, 67

- nppiAddC_16u_C4RSfs
image_addc, 68
- nppiAddC_32f_AC4IR
image_addc, 68
- nppiAddC_32f_AC4R
image_addc, 68
- nppiAddC_32f_C1IR
image_addc, 69
- nppiAddC_32f_C1R
image_addc, 69
- nppiAddC_32f_C3IR
image_addc, 69
- nppiAddC_32f_C3R
image_addc, 70
- nppiAddC_32f_C4IR
image_addc, 70
- nppiAddC_32f_C4R
image_addc, 70
- nppiAddC_32fc_AC4IR
image_addc, 71
- nppiAddC_32fc_AC4R
image_addc, 71
- nppiAddC_32fc_C1IR
image_addc, 71
- nppiAddC_32fc_C1R
image_addc, 72
- nppiAddC_32fc_C3IR
image_addc, 72
- nppiAddC_32fc_C3R
image_addc, 72
- nppiAddC_32fc_C4IR
image_addc, 73
- nppiAddC_32fc_C4R
image_addc, 73
- nppiAddC_32s_C1IRSfs
image_addc, 74
- nppiAddC_32s_C1RSfs
image_addc, 74
- nppiAddC_32s_C3IRSfs
image_addc, 74
- nppiAddC_32s_C3RSfs
image_addc, 75
- nppiAddC_32sc_AC4IRSfs
image_addc, 75
- nppiAddC_32sc_AC4RSfs
image_addc, 75
- nppiAddC_32sc_C1IRSfs
image_addc, 76
- nppiAddC_32sc_C1RSfs
image_addc, 76
- nppiAddC_32sc_C3IRSfs
image_addc, 77
- nppiAddC_32sc_C3RSfs
image_addc, 77
- nppiAddC_8u_AC4IRSfs
image_addc, 77
- nppiAddC_8u_AC4RSfs
image_addc, 78
- nppiAddC_8u_C1IRSfs
image_addc, 78
- nppiAddC_8u_C1RSfs
image_addc, 79
- nppiAddC_8u_C3IRSfs
image_addc, 79
- nppiAddC_8u_C3RSfs
image_addc, 79
- nppiAddC_8u_C4IRSfs
image_addc, 80
- nppiAddC_8u_C4RSfs
image_addc, 80
- nppiAddProduct_16u32f_C1IMR
image_addproduct, 200
- nppiAddProduct_16u32f_C1IR
image_addproduct, 201
- nppiAddProduct_32f_C1IMR
image_addproduct, 201
- nppiAddProduct_32f_C1IR
image_addproduct, 202
- nppiAddProduct_8u32f_C1IMR
image_addproduct, 202
- nppiAddProduct_8u32f_C1IR
image_addproduct, 202
- nppiAddSquare_16u32f_C1IMR
image_addsquare, 197
- nppiAddSquare_16u32f_C1IR
image_addsquare, 198
- nppiAddSquare_32f_C1IMR
image_addsquare, 198
- nppiAddSquare_32f_C1IR
image_addsquare, 198
- nppiAddSquare_8u32f_C1IMR
image_addsquare, 199
- nppiAddSquare_8u32f_C1IR
image_addsquare, 199
- nppiAddWeighted_16u32f_C1IMR
image_addweighted, 204
- nppiAddWeighted_16u32f_C1IR
image_addweighted, 205
- nppiAddWeighted_32f_C1IMR
image_addweighted, 205
- nppiAddWeighted_32f_C1IR
image_addweighted, 206
- nppiAddWeighted_8u32f_C1IMR
image_addweighted, 206
- nppiAddWeighted_8u32f_C1IR
image_addweighted, 206
- nppiAlphaComp_16s_AC1R
image_alphacomp, 489

- nppiAlphaComp_16u_AC1R
 image_alphacomp, 489
- nppiAlphaComp_16u_AC4R
 image_alphacomp, 490
- nppiAlphaComp_32f_AC1R
 image_alphacomp, 490
- nppiAlphaComp_32f_AC4R
 image_alphacomp, 491
- nppiAlphaComp_32s_AC1R
 image_alphacomp, 491
- nppiAlphaComp_32s_AC4R
 image_alphacomp, 491
- nppiAlphaComp_32u_AC1R
 image_alphacomp, 492
- nppiAlphaComp_32u_AC4R
 image_alphacomp, 492
- nppiAlphaComp_8s_AC1R
 image_alphacomp, 493
- nppiAlphaComp_8u_AC1R
 image_alphacomp, 493
- nppiAlphaComp_8u_AC4R
 image_alphacomp, 494
- nppiAlphaCompC_16s_C1R
 image_alphacompc, 474
- nppiAlphaCompC_16u_AC4R
 image_alphacompc, 474
- nppiAlphaCompC_16u_C1R
 image_alphacompc, 475
- nppiAlphaCompC_16u_C3R
 image_alphacompc, 475
- nppiAlphaCompC_16u_C4R
 image_alphacompc, 476
- nppiAlphaCompC_32f_C1R
 image_alphacompc, 476
- nppiAlphaCompC_32s_C1R
 image_alphacompc, 477
- nppiAlphaCompC_32u_C1R
 image_alphacompc, 477
- nppiAlphaCompC_8s_C1R
 image_alphacompc, 478
- nppiAlphaCompC_8u_AC4R
 image_alphacompc, 478
- nppiAlphaCompC_8u_C1R
 image_alphacompc, 479
- nppiAlphaCompC_8u_C3R
 image_alphacompc, 479
- nppiAlphaCompC_8u_C4R
 image_alphacompc, 480
- nppiAlphaCompColorKey_8u_AC4R
 image_complement_color_key, 606
- NppiAlphaOp
 typedefs_npp, 41
- nppiAlphaPremul_16u_AC4IR
 image_alphapremul, 495
- nppiAlphaPremul_8u_AC4IR
 image_alphapremul, 496
- nppiAlphaPremul_8u_AC4R
 image_alphapremul, 496
- nppiAlphaPremulC_16u_AC4IR
 image_alphapremulc, 482
- nppiAlphaPremulC_16u_AC4R
 image_alphapremulc, 482
- nppiAlphaPremulC_16u_C1IR
 image_alphapremulc, 483
- nppiAlphaPremulC_16u_C1R
 image_alphapremulc, 483
- nppiAlphaPremulC_16u_C3IR
 image_alphapremulc, 483
- nppiAlphaPremulC_16u_C3R
 image_alphapremulc, 484
- nppiAlphaPremulC_16u_C4IR
 image_alphapremulc, 484
- nppiAlphaPremulC_16u_C4R
 image_alphapremulc, 484
- nppiAlphaPremulC_8u_AC4IR
 image_alphapremulc, 485
- nppiAlphaPremulC_8u_AC4R
 image_alphapremulc, 485
- nppiAlphaPremulC_8u_C1IR
 image_alphapremulc, 485
- nppiAlphaPremulC_8u_C1R
 image_alphapremulc, 486
- nppiAlphaPremulC_8u_C3IR
 image_alphapremulc, 486
- nppiAlphaPremulC_8u_C3R
 image_alphapremulc, 486
- nppiAlphaPremulC_8u_C4IR
 image_alphapremulc, 487
- nppiAlphaPremulC_8u_C4R
 image_alphapremulc, 487
- nppiAnd_16u_AC4IR
 image_and, 434
- nppiAnd_16u_AC4R
 image_and, 434
- nppiAnd_16u_C1IR
 image_and, 434
- nppiAnd_16u_C1R
 image_and, 435
- nppiAnd_16u_C3IR
 image_and, 435
- nppiAnd_16u_C3R
 image_and, 435
- nppiAnd_16u_C4IR
 image_and, 436
- nppiAnd_16u_C4R
 image_and, 436

- nppiAnd_32s_AC4IR
 - image_and, [437](#)
- nppiAnd_32s_AC4R
 - image_and, [437](#)
- nppiAnd_32s_C1IR
 - image_and, [437](#)
- nppiAnd_32s_C1R
 - image_and, [438](#)
- nppiAnd_32s_C3IR
 - image_and, [438](#)
- nppiAnd_32s_C3R
 - image_and, [438](#)
- nppiAnd_32s_C4IR
 - image_and, [439](#)
- nppiAnd_32s_C4R
 - image_and, [439](#)
- nppiAnd_8u_AC4IR
 - image_and, [440](#)
- nppiAnd_8u_AC4R
 - image_and, [440](#)
- nppiAnd_8u_C1IR
 - image_and, [440](#)
- nppiAnd_8u_C1R
 - image_and, [441](#)
- nppiAnd_8u_C3IR
 - image_and, [441](#)
- nppiAnd_8u_C3R
 - image_and, [441](#)
- nppiAnd_8u_C4IR
 - image_and, [442](#)
- nppiAnd_8u_C4R
 - image_and, [442](#)
- nppiAndC_16u_AC4IR
 - image_andc, [373](#)
- nppiAndC_16u_AC4R
 - image_andc, [373](#)
- nppiAndC_16u_C1IR
 - image_andc, [373](#)
- nppiAndC_16u_C1R
 - image_andc, [374](#)
- nppiAndC_16u_C3IR
 - image_andc, [374](#)
- nppiAndC_16u_C3R
 - image_andc, [374](#)
- nppiAndC_16u_C4IR
 - image_andc, [375](#)
- nppiAndC_16u_C4R
 - image_andc, [375](#)
- nppiAndC_32s_AC4IR
 - image_andc, [375](#)
- nppiAndC_32s_AC4R
 - image_andc, [376](#)
- nppiAndC_32s_C1IR
 - image_andc, [376](#)
- nppiAndC_32s_C3IR
 - image_andc, [377](#)
- nppiAndC_32s_C3R
 - image_andc, [377](#)
- nppiAndC_32s_C4IR
 - image_andc, [377](#)
- nppiAndC_32s_C4R
 - image_andc, [378](#)
- nppiAndC_8u_AC4IR
 - image_andc, [378](#)
- nppiAndC_8u_AC4R
 - image_andc, [378](#)
- nppiAndC_8u_C1IR
 - image_andc, [379](#)
- nppiAndC_8u_C1R
 - image_andc, [379](#)
- nppiAndC_8u_C3IR
 - image_andc, [379](#)
- nppiAndC_8u_C3R
 - image_andc, [380](#)
- nppiAndC_8u_C4IR
 - image_andc, [380](#)
- nppiAndC_8u_C4R
 - image_andc, [380](#)
- NppiAxis
 - typedefs_npp, [42](#)
- nppiBGRToCbYCr422_709HDTV_8u_AC4C2R
 - image_color_model_conversion, [523](#)
- nppiBGRToCbYCr422_709HDTV_8u_C3C2R
 - image_color_model_conversion, [523](#)
- nppiBGRToCbYCr422_8u_AC4C2R
 - image_color_model_conversion, [523](#)
- nppiBGRToHLS_8u_AC4P4R
 - image_color_model_conversion, [524](#)
- nppiBGRToHLS_8u_AC4R
 - image_color_model_conversion, [524](#)
- nppiBGRToHLS_8u_AP4C4R
 - image_color_model_conversion, [524](#)
- nppiBGRToHLS_8u_AP4R
 - image_color_model_conversion, [525](#)
- nppiBGRToHLS_8u_C3P3R
 - image_color_model_conversion, [525](#)
- nppiBGRToHLS_8u_P3C3R
 - image_color_model_conversion, [525](#)
- nppiBGRToHLS_8u_P3R
 - image_color_model_conversion, [526](#)
- nppiBGRToLab_8u_C3R
 - image_color_model_conversion, [526](#)
- nppiBGRToYCbCr411_8u_AC4P3R
 - image_color_model_conversion, [526](#)
- nppiBGRToYCbCr411_8u_C3P3R
 - image_color_model_conversion, [527](#)

- nppiBGRToYCbCr420_709CSC_8u_AC4P3R
 - image_color_model_conversion, [527](#)
- nppiBGRToYCbCr420_709CSC_8u_C3P3R
 - image_color_model_conversion, [528](#)
- nppiBGRToYCbCr420_709HDTV_8u_AC4P3R
 - image_color_model_conversion, [528](#)
- nppiBGRToYCbCr420_8u_AC4P3R
 - image_color_model_conversion, [528](#)
- nppiBGRToYCbCr420_8u_C3P3R
 - image_color_model_conversion, [529](#)
- nppiBGRToYCbCr422_8u_AC4C2R
 - image_color_model_conversion, [529](#)
- nppiBGRToYCbCr422_8u_AC4P3R
 - image_color_model_conversion, [530](#)
- nppiBGRToYCbCr422_8u_C3C2R
 - image_color_model_conversion, [530](#)
- nppiBGRToYCbCr422_8u_C3P3R
 - image_color_model_conversion, [530](#)
- nppiBGRToYCrCb420_709CSC_8u_AC4P3R
 - image_color_model_conversion, [531](#)
- nppiBGRToYCrCb420_709CSC_8u_C3P3R
 - image_color_model_conversion, [531](#)
- nppiBGRToYCrCb420_8u_AC4P3R
 - image_color_model_conversion, [532](#)
- nppiBGRToYCrCb420_8u_C3P3R
 - image_color_model_conversion, [532](#)
- nppiBGRToYUV420_8u_AC4P3R
 - image_color_model_conversion, [532](#)
- NppiBorderType
 - typedefs_npp, [42](#)
- nppiCbYCr422ToBGR_709HDTV_8u_C2C3R
 - image_color_model_conversion, [533](#)
- nppiCbYCr422ToBGR_709HDTV_8u_C2C4R
 - image_color_model_conversion, [533](#)
- nppiCbYCr422ToBGR_8u_C2C4R
 - image_color_model_conversion, [534](#)
- nppiCbYCr422ToRGB_8u_C2C3R
 - image_color_model_conversion, [534](#)
- nppiCbYCr422ToYCbCr411_8u_C2P3R
 - image_color_sampling_format_conversion, [579](#)
- nppiCbYCr422ToYCbCr420_8u_C2P2R
 - image_color_sampling_format_conversion, [580](#)
- nppiCbYCr422ToYCbCr420_8u_C2P3R
 - image_color_sampling_format_conversion, [580](#)
- nppiCbYCr422ToYCbCr422_8u_C2P3R
 - image_color_sampling_format_conversion, [580](#)
- nppiCbYCr422ToYCbCr422_8u_C2R
 - image_color_sampling_format_conversion, [581](#)
- nppiCbYCr422ToYCrCb420_8u_C2P3R
 - image_color_sampling_format_conversion, [581](#)
- nppiColorToGray_16s_AC4C1R
 - image_color_model_conversion, [534](#)
- nppiColorToGray_16s_C3C1R
 - image_color_model_conversion, [535](#)
- nppiColorToGray_16u_AC4C1R
 - image_color_model_conversion, [535](#)
- nppiColorToGray_16u_C3C1R
 - image_color_model_conversion, [535](#)
- nppiColorToGray_32f_AC4C1R
 - image_color_model_conversion, [536](#)
- nppiColorToGray_32f_C3C1R
 - image_color_model_conversion, [536](#)
- nppiColorToGray_8u_AC4C1R
 - image_color_model_conversion, [537](#)
- nppiColorToGray_8u_C3C1R
 - image_color_model_conversion, [537](#)
- nppiColorTwist32f_16s_AC4IR
 - image_color_processing, [621](#)
- nppiColorTwist32f_16s_AC4R
 - image_color_processing, [621](#)
- nppiColorTwist32f_16s_C3IR
 - image_color_processing, [621](#)
- nppiColorTwist32f_16s_C3R
 - image_color_processing, [622](#)
- nppiColorTwist32f_16s_IP3R
 - image_color_processing, [622](#)
- nppiColorTwist32f_16s_P3R
 - image_color_processing, [622](#)
- nppiColorTwist32f_16u_AC4IR
 - image_color_processing, [623](#)
- nppiColorTwist32f_16u_AC4R
 - image_color_processing, [623](#)
- nppiColorTwist32f_16u_C3IR
 - image_color_processing, [624](#)
- nppiColorTwist32f_16u_C3R
 - image_color_processing, [624](#)
- nppiColorTwist32f_16u_IP3R
 - image_color_processing, [624](#)
- nppiColorTwist32f_16u_P3R
 - image_color_processing, [625](#)
- nppiColorTwist32f_8s_AC4IR
 - image_color_processing, [625](#)
- nppiColorTwist32f_8s_AC4R
 - image_color_processing, [626](#)
- nppiColorTwist32f_8s_C3IR
 - image_color_processing, [626](#)
- nppiColorTwist32f_8s_C3R
 - image_color_processing, [626](#)
- nppiColorTwist32f_8s_IP3R
 - image_color_processing, [627](#)
- nppiColorTwist32f_8s_P3R
 - image_color_processing, [627](#)

- nppiColorTwist32f_8u_AC4R
 - image_color_processing, [627](#)
- nppiColorTwist32f_8u_AC4R
 - image_color_processing, [628](#)
- nppiColorTwist32f_8u_C3IR
 - image_color_processing, [628](#)
- nppiColorTwist32f_8u_C3R
 - image_color_processing, [629](#)
- nppiColorTwist32f_8u_IP3R
 - image_color_processing, [629](#)
- nppiColorTwist32f_8u_P3R
 - image_color_processing, [629](#)
- nppiColorTwist_32f_AC4IR
 - image_color_processing, [630](#)
- nppiColorTwist_32f_AC4R
 - image_color_processing, [630](#)
- nppiColorTwist_32f_C3IR
 - image_color_processing, [631](#)
- nppiColorTwist_32f_C3R
 - image_color_processing, [631](#)
- nppiColorTwist_32f_IP3R
 - image_color_processing, [631](#)
- nppiColorTwist_32f_P3R
 - image_color_processing, [632](#)
- nppiCompare_16s_AC4R
 - image_compare_operations, [1970](#)
- nppiCompare_16s_C1R
 - image_compare_operations, [1971](#)
- nppiCompare_16s_C3R
 - image_compare_operations, [1971](#)
- nppiCompare_16s_C4R
 - image_compare_operations, [1971](#)
- nppiCompare_16u_AC4R
 - image_compare_operations, [1972](#)
- nppiCompare_16u_C1R
 - image_compare_operations, [1972](#)
- nppiCompare_16u_C3R
 - image_compare_operations, [1973](#)
- nppiCompare_16u_C4R
 - image_compare_operations, [1973](#)
- nppiCompare_32f_AC4R
 - image_compare_operations, [1974](#)
- nppiCompare_32f_C1R
 - image_compare_operations, [1974](#)
- nppiCompare_32f_C3R
 - image_compare_operations, [1975](#)
- nppiCompare_32f_C4R
 - image_compare_operations, [1975](#)
- nppiCompare_8u_AC4R
 - image_compare_operations, [1976](#)
- nppiCompare_8u_C1R
 - image_compare_operations, [1976](#)
- nppiCompare_8u_C3R
 - image_compare_operations, [1977](#)
- nppiCompare_8u_C4R
 - image_compare_operations, [1977](#)
- nppiCompareC_16s_AC4R
 - image_compare_operations, [1978](#)
- nppiCompareC_16s_C1R
 - image_compare_operations, [1978](#)
- nppiCompareC_16s_C3R
 - image_compare_operations, [1979](#)
- nppiCompareC_16s_C4R
 - image_compare_operations, [1979](#)
- nppiCompareC_16u_AC4R
 - image_compare_operations, [1980](#)
- nppiCompareC_16u_C1R
 - image_compare_operations, [1980](#)
- nppiCompareC_16u_C3R
 - image_compare_operations, [1980](#)
- nppiCompareC_16u_C4R
 - image_compare_operations, [1981](#)
- nppiCompareC_32f_AC4R
 - image_compare_operations, [1981](#)
- nppiCompareC_32f_C1R
 - image_compare_operations, [1982](#)
- nppiCompareC_32f_C3R
 - image_compare_operations, [1982](#)
- nppiCompareC_32f_C4R
 - image_compare_operations, [1983](#)
- nppiCompareC_8u_AC4R
 - image_compare_operations, [1983](#)
- nppiCompareC_8u_C1R
 - image_compare_operations, [1983](#)
- nppiCompareC_8u_C3R
 - image_compare_operations, [1984](#)
- nppiCompareC_8u_C4R
 - image_compare_operations, [1984](#)
- nppiCompareEqualEps_32f_AC4R
 - image_compare_operations, [1985](#)
- nppiCompareEqualEps_32f_C1R
 - image_compare_operations, [1985](#)
- nppiCompareEqualEps_32f_C3R
 - image_compare_operations, [1986](#)
- nppiCompareEqualEps_32f_C4R
 - image_compare_operations, [1986](#)
- nppiCompareEqualEpsC_32f_AC4R
 - image_compare_operations, [1987](#)
- nppiCompareEqualEpsC_32f_C1R
 - image_compare_operations, [1987](#)
- nppiCompareEqualEpsC_32f_C3R
 - image_compare_operations, [1988](#)
- nppiCompareEqualEpsC_32f_C4R
 - image_compare_operations, [1988](#)
- nppiCompColorKey_8u_C1R
 - image_complement_color_key, [607](#)
- nppiCompColorKey_8u_C3R
 - image_complement_color_key, [607](#)

- nppiCompColorKey_8u_C4R
image_complement_color_key, 608
- nppiConvert_16s16u_C1Rs
image_convert, 792
- nppiConvert_16s32f_AC4R
image_convert, 792
- nppiConvert_16s32f_C1R
image_convert, 793
- nppiConvert_16s32f_C3R
image_convert, 793
- nppiConvert_16s32f_C4R
image_convert, 793
- nppiConvert_16s32s_AC4R
image_convert, 794
- nppiConvert_16s32s_C1R
image_convert, 794
- nppiConvert_16s32s_C3R
image_convert, 794
- nppiConvert_16s32s_C4R
image_convert, 795
- nppiConvert_16s32u_C1Rs
image_convert, 795
- nppiConvert_16s8s_C1RSfs
image_convert, 795
- nppiConvert_16s8u_AC4R
image_convert, 796
- nppiConvert_16s8u_C1R
image_convert, 796
- nppiConvert_16s8u_C3R
image_convert, 796
- nppiConvert_16s8u_C4R
image_convert, 797
- nppiConvert_16u16s_C1RSfs
image_convert, 797
- nppiConvert_16u32f_AC4R
image_convert, 797
- nppiConvert_16u32f_C1R
image_convert, 798
- nppiConvert_16u32f_C3R
image_convert, 798
- nppiConvert_16u32f_C4R
image_convert, 798
- nppiConvert_16u32s_AC4R
image_convert, 799
- nppiConvert_16u32s_C1R
image_convert, 799
- nppiConvert_16u32s_C3R
image_convert, 799
- nppiConvert_16u32s_C4R
image_convert, 800
- nppiConvert_16u32u_C1R
image_convert, 800
- nppiConvert_16u8s_C1RSfs
image_convert, 800
- nppiConvert_16u8u_AC4R
image_convert, 801
- nppiConvert_16u8u_C1R
image_convert, 801
- nppiConvert_16u8u_C3R
image_convert, 801
- nppiConvert_16u8u_C4R
image_convert, 802
- nppiConvert_32f16s_AC4R
image_convert, 802
- nppiConvert_32f16s_C1R
image_convert, 802
- nppiConvert_32f16s_C1RSfs
image_convert, 803
- nppiConvert_32f16s_C3R
image_convert, 803
- nppiConvert_32f16s_C4R
image_convert, 804
- nppiConvert_32f16u_AC4R
image_convert, 804
- nppiConvert_32f16u_C1R
image_convert, 804
- nppiConvert_32f16u_C1RSfs
image_convert, 805
- nppiConvert_32f16u_C3R
image_convert, 805
- nppiConvert_32f16u_C4R
image_convert, 806
- nppiConvert_32f32s_C1RSfs
image_convert, 806
- nppiConvert_32f32u_C1RSfs
image_convert, 806
- nppiConvert_32f8s_AC4R
image_convert, 807
- nppiConvert_32f8s_C1R
image_convert, 807
- nppiConvert_32f8s_C1RSfs
image_convert, 808
- nppiConvert_32f8s_C3R
image_convert, 808
- nppiConvert_32f8s_C4R
image_convert, 808
- nppiConvert_32f8u_AC4R
image_convert, 809
- nppiConvert_32f8u_C1R
image_convert, 809
- nppiConvert_32f8u_C1RSfs
image_convert, 809
- nppiConvert_32f8u_C3R
image_convert, 810
- nppiConvert_32f8u_C4R
image_convert, 810
- nppiConvert_32s16s_C1RSfs
image_convert, 811

- nppiConvert_32s16u_C1RSfs
 image_convert, [811](#)
- nppiConvert_32s32f_C1R
 image_convert, [811](#)
- nppiConvert_32s32u_C1Rs
 image_convert, [812](#)
- nppiConvert_32s8s_AC4R
 image_convert, [812](#)
- nppiConvert_32s8s_C1R
 image_convert, [812](#)
- nppiConvert_32s8s_C3R
 image_convert, [813](#)
- nppiConvert_32s8s_C4R
 image_convert, [813](#)
- nppiConvert_32s8u_AC4R
 image_convert, [813](#)
- nppiConvert_32s8u_C1R
 image_convert, [814](#)
- nppiConvert_32s8u_C3R
 image_convert, [814](#)
- nppiConvert_32s8u_C4R
 image_convert, [814](#)
- nppiConvert_32u16s_C1RSfs
 image_convert, [815](#)
- nppiConvert_32u16u_C1RSfs
 image_convert, [815](#)
- nppiConvert_32u32f_C1R
 image_convert, [816](#)
- nppiConvert_32u32s_C1RSfs
 image_convert, [816](#)
- nppiConvert_32u8s_C1RSfs
 image_convert, [816](#)
- nppiConvert_32u8u_C1RSfs
 image_convert, [817](#)
- nppiConvert_8s16s_C1R
 image_convert, [817](#)
- nppiConvert_8s16u_C1Rs
 image_convert, [818](#)
- nppiConvert_8s32f_AC4R
 image_convert, [818](#)
- nppiConvert_8s32f_C1R
 image_convert, [818](#)
- nppiConvert_8s32f_C3R
 image_convert, [819](#)
- nppiConvert_8s32f_C4R
 image_convert, [819](#)
- nppiConvert_8s32s_AC4R
 image_convert, [819](#)
- nppiConvert_8s32s_C1R
 image_convert, [820](#)
- nppiConvert_8s32s_C3R
 image_convert, [820](#)
- nppiConvert_8s32s_C4R
 image_convert, [820](#)
- nppiConvert_8s32u_C1Rs
 image_convert, [821](#)
- nppiConvert_8s8u_C1Rs
 image_convert, [821](#)
- nppiConvert_8u16s_AC4R
 image_convert, [821](#)
- nppiConvert_8u16s_C1R
 image_convert, [822](#)
- nppiConvert_8u16s_C3R
 image_convert, [822](#)
- nppiConvert_8u16s_C4R
 image_convert, [822](#)
- nppiConvert_8u16u_AC4R
 image_convert, [823](#)
- nppiConvert_8u16u_C1R
 image_convert, [823](#)
- nppiConvert_8u16u_C3R
 image_convert, [823](#)
- nppiConvert_8u16u_C4R
 image_convert, [824](#)
- nppiConvert_8u32f_AC4R
 image_convert, [824](#)
- nppiConvert_8u32f_C1R
 image_convert, [824](#)
- nppiConvert_8u32f_C3R
 image_convert, [825](#)
- nppiConvert_8u32f_C4R
 image_convert, [825](#)
- nppiConvert_8u32s_AC4R
 image_convert, [825](#)
- nppiConvert_8u32s_C1R
 image_convert, [826](#)
- nppiConvert_8u32s_C3R
 image_convert, [826](#)
- nppiConvert_8u32s_C4R
 image_convert, [826](#)
- nppiConvert_8u8s_C1RSfs
 image_convert, [827](#)
- nppiCopy_16s_AC4MR
 image_copy, [746](#)
- nppiCopy_16s_AC4R
 image_copy, [747](#)
- nppiCopy_16s_C1C3R
 image_copy, [747](#)
- nppiCopy_16s_C1C4R
 image_copy, [747](#)
- nppiCopy_16s_C1MR
 image_copy, [748](#)
- nppiCopy_16s_C1R
 image_copy, [748](#)
- nppiCopy_16s_C3C1R
 image_copy, [748](#)
- nppiCopy_16s_C3CR
 image_copy, [749](#)

- nppiCopy_16s_C3MR
image_copy, 749
- nppiCopy_16s_C3P3R
image_copy, 749
- nppiCopy_16s_C3R
image_copy, 750
- nppiCopy_16s_C4C1R
image_copy, 750
- nppiCopy_16s_C4CR
image_copy, 750
- nppiCopy_16s_C4MR
image_copy, 751
- nppiCopy_16s_C4P4R
image_copy, 751
- nppiCopy_16s_C4R
image_copy, 751
- nppiCopy_16s_P3C3R
image_copy, 752
- nppiCopy_16s_P4C4R
image_copy, 752
- nppiCopy_16sc_AC4R
image_copy, 752
- nppiCopy_16sc_C1R
image_copy, 753
- nppiCopy_16sc_C2R
image_copy, 753
- nppiCopy_16sc_C3R
image_copy, 753
- nppiCopy_16sc_C4R
image_copy, 754
- nppiCopy_16u_AC4MR
image_copy, 754
- nppiCopy_16u_AC4R
image_copy, 754
- nppiCopy_16u_C1C3R
image_copy, 755
- nppiCopy_16u_C1C4R
image_copy, 755
- nppiCopy_16u_C1MR
image_copy, 755
- nppiCopy_16u_C1R
image_copy, 756
- nppiCopy_16u_C3C1R
image_copy, 756
- nppiCopy_16u_C3CR
image_copy, 756
- nppiCopy_16u_C3MR
image_copy, 757
- nppiCopy_16u_C3P3R
image_copy, 757
- nppiCopy_16u_C3R
image_copy, 757
- nppiCopy_16u_C4C1R
image_copy, 758
- nppiCopy_16u_C4CR
image_copy, 758
- nppiCopy_16u_C4MR
image_copy, 758
- nppiCopy_16u_C4P4R
image_copy, 759
- nppiCopy_16u_C4R
image_copy, 759
- nppiCopy_16u_P3C3R
image_copy, 759
- nppiCopy_16u_P4C4R
image_copy, 760
- nppiCopy_32f_AC4MR
image_copy, 760
- nppiCopy_32f_AC4R
image_copy, 760
- nppiCopy_32f_C1C3R
image_copy, 761
- nppiCopy_32f_C1C4R
image_copy, 761
- nppiCopy_32f_C1MR
image_copy, 761
- nppiCopy_32f_C1R
image_copy, 762
- nppiCopy_32f_C3C1R
image_copy, 762
- nppiCopy_32f_C3CR
image_copy, 762
- nppiCopy_32f_C3MR
image_copy, 763
- nppiCopy_32f_C3P3R
image_copy, 763
- nppiCopy_32f_C3R
image_copy, 763
- nppiCopy_32f_C4C1R
image_copy, 764
- nppiCopy_32f_C4CR
image_copy, 764
- nppiCopy_32f_C4MR
image_copy, 764
- nppiCopy_32f_C4P4R
image_copy, 765
- nppiCopy_32f_C4R
image_copy, 765
- nppiCopy_32f_P3C3R
image_copy, 765
- nppiCopy_32f_P4C4R
image_copy, 766
- nppiCopy_32fc_AC4R
image_copy, 766
- nppiCopy_32fc_C1R
image_copy, 766
- nppiCopy_32fc_C2R
image_copy, 767

- nppiCopy_32fc_C3R
 - image_copy, [767](#)
- nppiCopy_32fc_C4R
 - image_copy, [767](#)
- nppiCopy_32s_AC4MR
 - image_copy, [768](#)
- nppiCopy_32s_AC4R
 - image_copy, [768](#)
- nppiCopy_32s_C1C3R
 - image_copy, [768](#)
- nppiCopy_32s_C1C4R
 - image_copy, [769](#)
- nppiCopy_32s_C1MR
 - image_copy, [769](#)
- nppiCopy_32s_C1R
 - image_copy, [769](#)
- nppiCopy_32s_C3C1R
 - image_copy, [770](#)
- nppiCopy_32s_C3CR
 - image_copy, [770](#)
- nppiCopy_32s_C3MR
 - image_copy, [770](#)
- nppiCopy_32s_C3P3R
 - image_copy, [771](#)
- nppiCopy_32s_C3R
 - image_copy, [771](#)
- nppiCopy_32s_C4C1R
 - image_copy, [771](#)
- nppiCopy_32s_C4CR
 - image_copy, [772](#)
- nppiCopy_32s_C4MR
 - image_copy, [772](#)
- nppiCopy_32s_C4P4R
 - image_copy, [772](#)
- nppiCopy_32s_C4R
 - image_copy, [773](#)
- nppiCopy_32s_P3C3R
 - image_copy, [773](#)
- nppiCopy_32s_P4C4R
 - image_copy, [773](#)
- nppiCopy_32sc_AC4R
 - image_copy, [774](#)
- nppiCopy_32sc_C1R
 - image_copy, [774](#)
- nppiCopy_32sc_C2R
 - image_copy, [774](#)
- nppiCopy_32sc_C3R
 - image_copy, [775](#)
- nppiCopy_32sc_C4R
 - image_copy, [775](#)
- nppiCopy_8s_AC4R
 - image_copy, [775](#)
- nppiCopy_8s_C1R
 - image_copy, [776](#)
- nppiCopy_8s_C2R
 - image_copy, [776](#)
- nppiCopy_8s_C3R
 - image_copy, [776](#)
- nppiCopy_8s_C4R
 - image_copy, [777](#)
- nppiCopy_8u_AC4MR
 - image_copy, [777](#)
- nppiCopy_8u_AC4R
 - image_copy, [777](#)
- nppiCopy_8u_C1C3R
 - image_copy, [778](#)
- nppiCopy_8u_C1C4R
 - image_copy, [778](#)
- nppiCopy_8u_C1MR
 - image_copy, [778](#)
- nppiCopy_8u_C1R
 - image_copy, [779](#)
- nppiCopy_8u_C3C1R
 - image_copy, [779](#)
- nppiCopy_8u_C3CR
 - image_copy, [779](#)
- nppiCopy_8u_C3MR
 - image_copy, [780](#)
- nppiCopy_8u_C3P3R
 - image_copy, [780](#)
- nppiCopy_8u_C3R
 - image_copy, [780](#)
- nppiCopy_8u_C4C1R
 - image_copy, [781](#)
- nppiCopy_8u_C4CR
 - image_copy, [781](#)
- nppiCopy_8u_C4MR
 - image_copy, [781](#)
- nppiCopy_8u_C4P4R
 - image_copy, [782](#)
- nppiCopy_8u_C4R
 - image_copy, [782](#)
- nppiCopy_8u_P3C3R
 - image_copy, [782](#)
- nppiCopy_8u_P4C4R
 - image_copy, [783](#)
- nppiCopyConstBorder_16s_AC4R
 - image_copy_constant_border, [845](#)
- nppiCopyConstBorder_16s_C1R
 - image_copy_constant_border, [845](#)
- nppiCopyConstBorder_16s_C3R
 - image_copy_constant_border, [846](#)
- nppiCopyConstBorder_16s_C4R
 - image_copy_constant_border, [846](#)
- nppiCopyConstBorder_16u_AC4R
 - image_copy_constant_border, [847](#)
- nppiCopyConstBorder_16u_C1R
 - image_copy_constant_border, [847](#)

- nppiCopyConstBorder_16u_C3R
 - image_copy_constant_border, 848
- nppiCopyConstBorder_16u_C4R
 - image_copy_constant_border, 848
- nppiCopyConstBorder_32f_AC4R
 - image_copy_constant_border, 849
- nppiCopyConstBorder_32f_C1R
 - image_copy_constant_border, 849
- nppiCopyConstBorder_32f_C3R
 - image_copy_constant_border, 850
- nppiCopyConstBorder_32f_C4R
 - image_copy_constant_border, 850
- nppiCopyConstBorder_32s_AC4R
 - image_copy_constant_border, 851
- nppiCopyConstBorder_32s_C1R
 - image_copy_constant_border, 851
- nppiCopyConstBorder_32s_C3R
 - image_copy_constant_border, 852
- nppiCopyConstBorder_32s_C4R
 - image_copy_constant_border, 852
- nppiCopyConstBorder_8u_AC4R
 - image_copy_constant_border, 853
- nppiCopyConstBorder_8u_C1R
 - image_copy_constant_border, 853
- nppiCopyConstBorder_8u_C3R
 - image_copy_constant_border, 854
- nppiCopyConstBorder_8u_C4R
 - image_copy_constant_border, 854
- nppiCopyReplicateBorder_16s_AC4R
 - image_copy_replicate_border, 858
- nppiCopyReplicateBorder_16s_C1R
 - image_copy_replicate_border, 858
- nppiCopyReplicateBorder_16s_C3R
 - image_copy_replicate_border, 859
- nppiCopyReplicateBorder_16s_C4R
 - image_copy_replicate_border, 859
- nppiCopyReplicateBorder_16u_AC4R
 - image_copy_replicate_border, 860
- nppiCopyReplicateBorder_16u_C1R
 - image_copy_replicate_border, 860
- nppiCopyReplicateBorder_16u_C3R
 - image_copy_replicate_border, 861
- nppiCopyReplicateBorder_16u_C4R
 - image_copy_replicate_border, 861
- nppiCopyReplicateBorder_32f_AC4R
 - image_copy_replicate_border, 861
- nppiCopyReplicateBorder_32f_C1R
 - image_copy_replicate_border, 862
- nppiCopyReplicateBorder_32f_C3R
 - image_copy_replicate_border, 862
- nppiCopyReplicateBorder_32f_C4R
 - image_copy_replicate_border, 863
- nppiCopyReplicateBorder_32s_AC4R
 - image_copy_replicate_border, 863
- nppiCopyReplicateBorder_32s_C1R
 - image_copy_replicate_border, 864
- nppiCopyReplicateBorder_32s_C3R
 - image_copy_replicate_border, 864
- nppiCopyReplicateBorder_32s_C4R
 - image_copy_replicate_border, 865
- nppiCopyReplicateBorder_8u_AC4R
 - image_copy_replicate_border, 865
- nppiCopyReplicateBorder_8u_C1R
 - image_copy_replicate_border, 866
- nppiCopyReplicateBorder_8u_C3R
 - image_copy_replicate_border, 866
- nppiCopyReplicateBorder_8u_C4R
 - image_copy_replicate_border, 867
- nppiCopySubpix_16s_AC4R
 - image_copy_sub_pixel, 882
- nppiCopySubpix_16s_C1R
 - image_copy_sub_pixel, 883
- nppiCopySubpix_16s_C3R
 - image_copy_sub_pixel, 883
- nppiCopySubpix_16s_C4R
 - image_copy_sub_pixel, 884
- nppiCopySubpix_16u_AC4R
 - image_copy_sub_pixel, 884
- nppiCopySubpix_16u_C1R
 - image_copy_sub_pixel, 884
- nppiCopySubpix_16u_C3R
 - image_copy_sub_pixel, 885
- nppiCopySubpix_16u_C4R
 - image_copy_sub_pixel, 885
- nppiCopySubpix_32f_AC4R
 - image_copy_sub_pixel, 886
- nppiCopySubpix_32f_C1R
 - image_copy_sub_pixel, 886
- nppiCopySubpix_32f_C3R
 - image_copy_sub_pixel, 886
- nppiCopySubpix_32f_C4R
 - image_copy_sub_pixel, 887
- nppiCopySubpix_32s_AC4R
 - image_copy_sub_pixel, 887
- nppiCopySubpix_32s_C1R
 - image_copy_sub_pixel, 888
- nppiCopySubpix_32s_C3R
 - image_copy_sub_pixel, 888
- nppiCopySubpix_32s_C4R
 - image_copy_sub_pixel, 889
- nppiCopySubpix_8u_AC4R
 - image_copy_sub_pixel, 889
- nppiCopySubpix_8u_C1R
 - image_copy_sub_pixel, 889
- nppiCopySubpix_8u_C3R
 - image_copy_sub_pixel, 890
- nppiCopySubpix_8u_C4R
 - image_copy_sub_pixel, 890

- nppiCopyWrapBorder_16s_AC4R
image_copy_wrap_border, 870
- nppiCopyWrapBorder_16s_C1R
image_copy_wrap_border, 870
- nppiCopyWrapBorder_16s_C3R
image_copy_wrap_border, 871
- nppiCopyWrapBorder_16s_C4R
image_copy_wrap_border, 871
- nppiCopyWrapBorder_16u_AC4R
image_copy_wrap_border, 872
- nppiCopyWrapBorder_16u_C1R
image_copy_wrap_border, 872
- nppiCopyWrapBorder_16u_C3R
image_copy_wrap_border, 873
- nppiCopyWrapBorder_16u_C4R
image_copy_wrap_border, 873
- nppiCopyWrapBorder_32f_AC4R
image_copy_wrap_border, 874
- nppiCopyWrapBorder_32f_C1R
image_copy_wrap_border, 874
- nppiCopyWrapBorder_32f_C3R
image_copy_wrap_border, 875
- nppiCopyWrapBorder_32f_C4R
image_copy_wrap_border, 875
- nppiCopyWrapBorder_32s_AC4R
image_copy_wrap_border, 876
- nppiCopyWrapBorder_32s_C1R
image_copy_wrap_border, 876
- nppiCopyWrapBorder_32s_C3R
image_copy_wrap_border, 877
- nppiCopyWrapBorder_32s_C4R
image_copy_wrap_border, 877
- nppiCopyWrapBorder_8u_AC4R
image_copy_wrap_border, 878
- nppiCopyWrapBorder_8u_C1R
image_copy_wrap_border, 878
- nppiCopyWrapBorder_8u_C3R
image_copy_wrap_border, 879
- nppiCopyWrapBorder_8u_C4R
image_copy_wrap_border, 879
- nppiCountInRange_32f_AC4R
image_count_in_range, 1668
- nppiCountInRange_32f_C1R
image_count_in_range, 1668
- nppiCountInRange_32f_C3R
image_count_in_range, 1669
- nppiCountInRange_8u_AC4R
image_count_in_range, 1669
- nppiCountInRange_8u_C1R
image_count_in_range, 1670
- nppiCountInRange_8u_C3R
image_count_in_range, 1670
- nppiCountInRangeGetBufferHostSize_32f_AC4R
image_count_in_range, 1671
- nppiCountInRangeGetBufferHostSize_32f_C1R
image_count_in_range, 1671
- nppiCountInRangeGetBufferHostSize_32f_C3R
image_count_in_range, 1671
- nppiCountInRangeGetBufferHostSize_8u_AC4R
image_count_in_range, 1671
- nppiCountInRangeGetBufferHostSize_8u_C1R
image_count_in_range, 1672
- nppiCountInRangeGetBufferHostSize_8u_C3R
image_count_in_range, 1672
- nppiCrossCorrFull_Norm_16u32f_AC4R
crosscorrfullnorm, 1762
- nppiCrossCorrFull_Norm_16u32f_C1R
crosscorrfullnorm, 1762
- nppiCrossCorrFull_Norm_16u32f_C3R
crosscorrfullnorm, 1762
- nppiCrossCorrFull_Norm_16u32f_C4R
crosscorrfullnorm, 1763
- nppiCrossCorrFull_Norm_32f_AC4R
crosscorrfullnorm, 1763
- nppiCrossCorrFull_Norm_32f_C1R
crosscorrfullnorm, 1764
- nppiCrossCorrFull_Norm_32f_C3R
crosscorrfullnorm, 1764
- nppiCrossCorrFull_Norm_32f_C4R
crosscorrfullnorm, 1765
- nppiCrossCorrFull_Norm_8s32f_AC4R
crosscorrfullnorm, 1765
- nppiCrossCorrFull_Norm_8s32f_C1R
crosscorrfullnorm, 1765
- nppiCrossCorrFull_Norm_8s32f_C3R
crosscorrfullnorm, 1766
- nppiCrossCorrFull_Norm_8s32f_C4R
crosscorrfullnorm, 1766
- nppiCrossCorrFull_Norm_8u32f_AC4R
crosscorrfullnorm, 1767
- nppiCrossCorrFull_Norm_8u32f_C1R
crosscorrfullnorm, 1767
- nppiCrossCorrFull_Norm_8u32f_C3R
crosscorrfullnorm, 1768
- nppiCrossCorrFull_Norm_8u32f_C4R
crosscorrfullnorm, 1768
- nppiCrossCorrFull_Norm_8u_AC4RSfs
crosscorrfullnorm, 1768
- nppiCrossCorrFull_Norm_8u_C1RSfs
crosscorrfullnorm, 1769
- nppiCrossCorrFull_Norm_8u_C3RSfs
crosscorrfullnorm, 1769
- nppiCrossCorrFull_Norm_8u_C4RSfs
crosscorrfullnorm, 1770
- nppiCrossCorrFull_NormLevel_16u32f_AC4R
crosscorrfullnormlevel, 1800
- nppiCrossCorrFull_NormLevel_16u32f_C1R
crosscorrfullnormlevel, 1800

- nppiCrossCorrFull_NormLevel_16u32f_C3R
 crosscorrfullnormlevel, 1800
 nppiCrossCorrFull_NormLevel_16u32f_C4R
 crosscorrfullnormlevel, 1801
 nppiCrossCorrFull_NormLevel_32f_AC4R
 crosscorrfullnormlevel, 1801
 nppiCrossCorrFull_NormLevel_32f_C1R
 crosscorrfullnormlevel, 1802
 nppiCrossCorrFull_NormLevel_32f_C3R
 crosscorrfullnormlevel, 1802
 nppiCrossCorrFull_NormLevel_32f_C4R
 crosscorrfullnormlevel, 1803
 nppiCrossCorrFull_NormLevel_8s32f_AC4R
 crosscorrfullnormlevel, 1803
 nppiCrossCorrFull_NormLevel_8s32f_C1R
 crosscorrfullnormlevel, 1804
 nppiCrossCorrFull_NormLevel_8s32f_C3R
 crosscorrfullnormlevel, 1804
 nppiCrossCorrFull_NormLevel_8s32f_C4R
 crosscorrfullnormlevel, 1805
 nppiCrossCorrFull_NormLevel_8u32f_AC4R
 crosscorrfullnormlevel, 1805
 nppiCrossCorrFull_NormLevel_8u32f_C1R
 crosscorrfullnormlevel, 1806
 nppiCrossCorrFull_NormLevel_8u32f_C3R
 crosscorrfullnormlevel, 1806
 nppiCrossCorrFull_NormLevel_8u32f_C4R
 crosscorrfullnormlevel, 1807
 nppiCrossCorrFull_NormLevel_8u_AC4RSfs
 crosscorrfullnormlevel, 1807
 nppiCrossCorrFull_NormLevel_8u_C1RSfs
 crosscorrfullnormlevel, 1808
 nppiCrossCorrFull_NormLevel_8u_C3RSfs
 crosscorrfullnormlevel, 1808
 nppiCrossCorrFull_NormLevel_8u_C4RSfs
 crosscorrfullnormlevel, 1809
 nppiCrossCorrSame_Norm_16u32f_AC4R
 crosscorrssamenorm, 1773
 nppiCrossCorrSame_Norm_16u32f_C1R
 crosscorrssamenorm, 1773
 nppiCrossCorrSame_Norm_16u32f_C3R
 crosscorrssamenorm, 1773
 nppiCrossCorrSame_Norm_16u32f_C4R
 crosscorrssamenorm, 1774
 nppiCrossCorrSame_Norm_32f_AC4R
 crosscorrssamenorm, 1774
 nppiCrossCorrSame_Norm_32f_C1R
 crosscorrssamenorm, 1775
 nppiCrossCorrSame_Norm_32f_C3R
 crosscorrssamenorm, 1775
 nppiCrossCorrSame_Norm_32f_C4R
 crosscorrssamenorm, 1776
 nppiCrossCorrSame_Norm_8s32f_AC4R
 crosscorrssamenorm, 1776
 nppiCrossCorrSame_Norm_8s32f_C1R
 crosscorrssamenorm, 1776
 nppiCrossCorrSame_Norm_8s32f_C3R
 crosscorrssamenorm, 1777
 nppiCrossCorrSame_Norm_8s32f_C4R
 crosscorrssamenorm, 1777
 nppiCrossCorrSame_Norm_8u32f_AC4R
 crosscorrssamenorm, 1778
 nppiCrossCorrSame_Norm_8u32f_C1R
 crosscorrssamenorm, 1778
 nppiCrossCorrSame_Norm_8u32f_C3R
 crosscorrssamenorm, 1779
 nppiCrossCorrSame_Norm_8u32f_C4R
 crosscorrssamenorm, 1779
 nppiCrossCorrSame_Norm_8u_AC4RSfs
 crosscorrssamenorm, 1779
 nppiCrossCorrSame_Norm_8u_C1RSfs
 crosscorrssamenorm, 1780
 nppiCrossCorrSame_Norm_8u_C3RSfs
 crosscorrssamenorm, 1780
 nppiCrossCorrSame_Norm_8u_C4RSfs
 crosscorrssamenorm, 1781
 nppiCrossCorrSame_NormLevel_16u32f_AC4R
 crosscorrssamenormlevel, 1820
 nppiCrossCorrSame_NormLevel_16u32f_C1R
 crosscorrssamenormlevel, 1820
 nppiCrossCorrSame_NormLevel_16u32f_C3R
 crosscorrssamenormlevel, 1820
 nppiCrossCorrSame_NormLevel_16u32f_C4R
 crosscorrssamenormlevel, 1821
 nppiCrossCorrSame_NormLevel_32f_AC4R
 crosscorrssamenormlevel, 1821
 nppiCrossCorrSame_NormLevel_32f_C1R
 crosscorrssamenormlevel, 1822
 nppiCrossCorrSame_NormLevel_32f_C3R
 crosscorrssamenormlevel, 1822
 nppiCrossCorrSame_NormLevel_32f_C4R
 crosscorrssamenormlevel, 1823
 nppiCrossCorrSame_NormLevel_8s32f_AC4R
 crosscorrssamenormlevel, 1823
 nppiCrossCorrSame_NormLevel_8s32f_C1R
 crosscorrssamenormlevel, 1824
 nppiCrossCorrSame_NormLevel_8s32f_C3R
 crosscorrssamenormlevel, 1824
 nppiCrossCorrSame_NormLevel_8s32f_C4R
 crosscorrssamenormlevel, 1825
 nppiCrossCorrSame_NormLevel_8u32f_AC4R
 crosscorrssamenormlevel, 1825
 nppiCrossCorrSame_NormLevel_8u32f_C1R
 crosscorrssamenormlevel, 1826
 nppiCrossCorrSame_NormLevel_8u32f_C3R
 crosscorrssamenormlevel, 1826
 nppiCrossCorrSame_NormLevel_8u32f_C4R
 crosscorrssamenormlevel, 1827

- nppiCrossCorrSame_NormLevel_8u_AC4RSfs
crosscorrvalidnorm, 1827
- nppiCrossCorrSame_NormLevel_8u_C1RSfs
crosscorrvalidnorm, 1828
- nppiCrossCorrSame_NormLevel_8u_C3RSfs
crosscorrvalidnorm, 1828
- nppiCrossCorrSame_NormLevel_8u_C4RSfs
crosscorrvalidnorm, 1829
- nppiCrossCorrValid_16u32f_C1R
crosscorrvalid, 1793
- nppiCrossCorrValid_32f_C1R
crosscorrvalid, 1794
- nppiCrossCorrValid_8s32f_C1R
crosscorrvalid, 1794
- nppiCrossCorrValid_8u32f_C1R
crosscorrvalid, 1794
- nppiCrossCorrValid_Norm_16u32f_AC4R
crosscorrvalidnorm, 1784
- nppiCrossCorrValid_Norm_16u32f_C1R
crosscorrvalidnorm, 1784
- nppiCrossCorrValid_Norm_16u32f_C3R
crosscorrvalidnorm, 1784
- nppiCrossCorrValid_Norm_16u32f_C4R
crosscorrvalidnorm, 1785
- nppiCrossCorrValid_Norm_32f_AC4R
crosscorrvalidnorm, 1785
- nppiCrossCorrValid_Norm_32f_C1R
crosscorrvalidnorm, 1786
- nppiCrossCorrValid_Norm_32f_C3R
crosscorrvalidnorm, 1786
- nppiCrossCorrValid_Norm_32f_C4R
crosscorrvalidnorm, 1787
- nppiCrossCorrValid_Norm_8s32f_AC4R
crosscorrvalidnorm, 1787
- nppiCrossCorrValid_Norm_8s32f_C1R
crosscorrvalidnorm, 1787
- nppiCrossCorrValid_Norm_8s32f_C3R
crosscorrvalidnorm, 1788
- nppiCrossCorrValid_Norm_8s32f_C4R
crosscorrvalidnorm, 1788
- nppiCrossCorrValid_Norm_8u32f_AC4R
crosscorrvalidnorm, 1789
- nppiCrossCorrValid_Norm_8u32f_C1R
crosscorrvalidnorm, 1789
- nppiCrossCorrValid_Norm_8u32f_C3R
crosscorrvalidnorm, 1790
- nppiCrossCorrValid_Norm_8u32f_C4R
crosscorrvalidnorm, 1790
- nppiCrossCorrValid_Norm_8u_AC4RSfs
crosscorrvalidnorm, 1790
- nppiCrossCorrValid_Norm_8u_C1RSfs
crosscorrvalidnorm, 1791
- nppiCrossCorrValid_Norm_8u_C3RSfs
crosscorrvalidnorm, 1791
- nppiCrossCorrValid_Norm_8u_C4RSfs
crosscorrvalidnorm, 1792
- nppiCrossCorrValid_NormLevel_16u32f_AC4R
crosscorrvalidnormlevel, 1840
- nppiCrossCorrValid_NormLevel_16u32f_C1R
crosscorrvalidnormlevel, 1840
- nppiCrossCorrValid_NormLevel_16u32f_C3R
crosscorrvalidnormlevel, 1840
- nppiCrossCorrValid_NormLevel_16u32f_C4R
crosscorrvalidnormlevel, 1841
- nppiCrossCorrValid_NormLevel_32f_AC4R
crosscorrvalidnormlevel, 1841
- nppiCrossCorrValid_NormLevel_32f_C1R
crosscorrvalidnormlevel, 1842
- nppiCrossCorrValid_NormLevel_32f_C3R
crosscorrvalidnormlevel, 1842
- nppiCrossCorrValid_NormLevel_32f_C4R
crosscorrvalidnormlevel, 1843
- nppiCrossCorrValid_NormLevel_8s32f_AC4R
crosscorrvalidnormlevel, 1843
- nppiCrossCorrValid_NormLevel_8s32f_C1R
crosscorrvalidnormlevel, 1844
- nppiCrossCorrValid_NormLevel_8s32f_C3R
crosscorrvalidnormlevel, 1844
- nppiCrossCorrValid_NormLevel_8s32f_C4R
crosscorrvalidnormlevel, 1845
- nppiCrossCorrValid_NormLevel_8u32f_AC4R
crosscorrvalidnormlevel, 1845
- nppiCrossCorrValid_NormLevel_8u32f_C1R
crosscorrvalidnormlevel, 1846
- nppiCrossCorrValid_NormLevel_8u32f_C3R
crosscorrvalidnormlevel, 1846
- nppiCrossCorrValid_NormLevel_8u32f_C4R
crosscorrvalidnormlevel, 1847
- nppiCrossCorrValid_NormLevel_8u_AC4RSfs
crosscorrvalidnormlevel, 1847
- nppiCrossCorrValid_NormLevel_8u_C1RSfs
crosscorrvalidnormlevel, 1848
- nppiCrossCorrValid_NormLevel_8u_C3RSfs
crosscorrvalidnormlevel, 1848
- nppiCrossCorrValid_NormLevel_8u_C4RSfs
crosscorrvalidnormlevel, 1849
- nppiDCTFree
image_quantization, 693
- nppiDCTInitAlloc
image_quantization, 693
- nppiDCTQuantFwd8x8LS_JPEG_8u16s_C1R
image_quantization, 693
- nppiDCTQuantFwd8x8LS_JPEG_8u16s_C1R_-
NEW
image_quantization, 694
- nppiDCTQuantInv8x8LS_JPEG_16s8u_C1R
image_quantization, 694

- nppiDCTQuantInv8x8LS_JPEG_16s8u_C1R_-NEW
 - image_quantization, 695
- NppiDCTState
 - image_quantization, 693
- nppiDecodeHuffmanScanHost_JPEG_8u16s_P1R
 - image_compression, 690
- nppiDecodeHuffmanScanHost_JPEG_8u16s_P3R
 - image_compression, 691
- nppiDilate3x3_16u_AC4R
 - image_dilate_3x3, 1288
- nppiDilate3x3_16u_C1R
 - image_dilate_3x3, 1288
- nppiDilate3x3_16u_C3R
 - image_dilate_3x3, 1288
- nppiDilate3x3_16u_C4R
 - image_dilate_3x3, 1289
- nppiDilate3x3_32f_AC4R
 - image_dilate_3x3, 1289
- nppiDilate3x3_32f_C1R
 - image_dilate_3x3, 1289
- nppiDilate3x3_32f_C3R
 - image_dilate_3x3, 1290
- nppiDilate3x3_32f_C4R
 - image_dilate_3x3, 1290
- nppiDilate3x3_64f_C1R
 - image_dilate_3x3, 1290
- nppiDilate3x3_8u_AC4R
 - image_dilate_3x3, 1291
- nppiDilate3x3_8u_C1R
 - image_dilate_3x3, 1291
- nppiDilate3x3_8u_C3R
 - image_dilate_3x3, 1291
- nppiDilate3x3_8u_C4R
 - image_dilate_3x3, 1292
- nppiDilate_16u_AC4R
 - image_dilate, 1274
- nppiDilate_16u_C1R
 - image_dilate, 1274
- nppiDilate_16u_C3R
 - image_dilate, 1275
- nppiDilate_16u_C4R
 - image_dilate, 1275
- nppiDilate_32f_AC4R
 - image_dilate, 1275
- nppiDilate_32f_C1R
 - image_dilate, 1276
- nppiDilate_32f_C3R
 - image_dilate, 1276
- nppiDilate_32f_C4R
 - image_dilate, 1277
- nppiDilate_8u_AC4R
 - image_dilate, 1277
- nppiDilate_8u_C1R
 - image_dilate, 1278
- nppiDilate_8u_C3R
 - image_dilate, 1278
- nppiDilate_8u_C4R
 - image_dilate, 1278
- nppiDiv_16s_AC4IRSfs
 - image_div, 281
- nppiDiv_16s_AC4RSfs
 - image_div, 281
- nppiDiv_16s_C1IRSfs
 - image_div, 282
- nppiDiv_16s_C1RSfs
 - image_div, 282
- nppiDiv_16s_C3IRSfs
 - image_div, 282
- nppiDiv_16s_C3RSfs
 - image_div, 283
- nppiDiv_16s_C4IRSfs
 - image_div, 283
- nppiDiv_16s_C4RSfs
 - image_div, 284
- nppiDiv_16sc_AC4IRSfs
 - image_div, 284
- nppiDiv_16sc_AC4RSfs
 - image_div, 284
- nppiDiv_16sc_C1IRSfs
 - image_div, 285
- nppiDiv_16sc_C1RSfs
 - image_div, 285
- nppiDiv_16sc_C3IRSfs
 - image_div, 286
- nppiDiv_16sc_C3RSfs
 - image_div, 286
- nppiDiv_16u_AC4IRSfs
 - image_div, 287
- nppiDiv_16u_AC4RSfs
 - image_div, 287
- nppiDiv_16u_C1IRSfs
 - image_div, 287
- nppiDiv_16u_C1RSfs
 - image_div, 288
- nppiDiv_16u_C3IRSfs
 - image_div, 288
- nppiDiv_16u_C3RSfs
 - image_div, 289
- nppiDiv_16u_C4IRSfs
 - image_div, 289
- nppiDiv_16u_C4RSfs
 - image_div, 289
- nppiDiv_32f_AC4IR
 - image_div, 290
- nppiDiv_32f_AC4R
 - image_div, 290
- nppiDiv_32f_C1IR

- image_div, 291
- nppiDiv_32f_C1R
 - image_div, 291
- nppiDiv_32f_C3IR
 - image_div, 291
- nppiDiv_32f_C3R
 - image_div, 292
- nppiDiv_32f_C4IR
 - image_div, 292
- nppiDiv_32f_C4R
 - image_div, 292
- nppiDiv_32fc_AC4IR
 - image_div, 293
- nppiDiv_32fc_AC4R
 - image_div, 293
- nppiDiv_32fc_C1IR
 - image_div, 294
- nppiDiv_32fc_C1R
 - image_div, 294
- nppiDiv_32fc_C3IR
 - image_div, 294
- nppiDiv_32fc_C3R
 - image_div, 295
- nppiDiv_32fc_C4IR
 - image_div, 295
- nppiDiv_32fc_C4R
 - image_div, 295
- nppiDiv_32s_C1IRSfs
 - image_div, 296
- nppiDiv_32s_C1R
 - image_div, 296
- nppiDiv_32s_C1RSfs
 - image_div, 297
- nppiDiv_32s_C3IRSfs
 - image_div, 297
- nppiDiv_32s_C3RSfs
 - image_div, 297
- nppiDiv_32sc_AC4IRSfs
 - image_div, 298
- nppiDiv_32sc_AC4RSfs
 - image_div, 298
- nppiDiv_32sc_C1IRSfs
 - image_div, 299
- nppiDiv_32sc_C1RSfs
 - image_div, 299
- nppiDiv_32sc_C3IRSfs
 - image_div, 300
- nppiDiv_32sc_C3RSfs
 - image_div, 300
- nppiDiv_8u_AC4IRSfs
 - image_div, 300
- nppiDiv_8u_AC4RSfs
 - image_div, 301
- nppiDiv_8u_C1IRSfs
 - image_div, 301
- nppiDiv_8u_C1RSfs
 - image_div, 302
- nppiDiv_8u_C3IRSfs
 - image_div, 302
- nppiDiv_8u_C3RSfs
 - image_div, 302
- nppiDiv_8u_C4IRSfs
 - image_div, 303
- nppiDiv_8u_C4RSfs
 - image_div, 303
- nppiDiv_Round_16s_AC4IRSfs
 - image_divround, 307
- nppiDiv_Round_16s_AC4RSfs
 - image_divround, 308
- nppiDiv_Round_16s_C1IRSfs
 - image_divround, 308
- nppiDiv_Round_16s_C1RSfs
 - image_divround, 309
- nppiDiv_Round_16s_C3IRSfs
 - image_divround, 309
- nppiDiv_Round_16s_C3RSfs
 - image_divround, 309
- nppiDiv_Round_16s_C4IRSfs
 - image_divround, 310
- nppiDiv_Round_16s_C4RSfs
 - image_divround, 310
- nppiDiv_Round_16u_AC4IRSfs
 - image_divround, 311
- nppiDiv_Round_16u_AC4RSfs
 - image_divround, 311
- nppiDiv_Round_16u_C1IRSfs
 - image_divround, 312
- nppiDiv_Round_16u_C1RSfs
 - image_divround, 312
- nppiDiv_Round_16u_C3IRSfs
 - image_divround, 313
- nppiDiv_Round_16u_C3RSfs
 - image_divround, 313
- nppiDiv_Round_16u_C4IRSfs
 - image_divround, 314
- nppiDiv_Round_16u_C4RSfs
 - image_divround, 314
- nppiDiv_Round_8u_AC4IRSfs
 - image_divround, 315
- nppiDiv_Round_8u_AC4RSfs
 - image_divround, 315
- nppiDiv_Round_8u_C1IRSfs
 - image_divround, 316
- nppiDiv_Round_8u_C1RSfs
 - image_divround, 316
- nppiDiv_Round_8u_C3IRSfs
 - image_divround, 317
- nppiDiv_Round_8u_C3RSfs
 - image_divround, 317

- image_divround, 317
- nppiDiv_Round_8u_C4IRSfs
 - image_divround, 318
- nppiDiv_Round_8u_C4RSfs
 - image_divround, 318
- nppiDivC_16s_AC4IRSfs
 - image_divc, 145
- nppiDivC_16s_AC4RSfs
 - image_divc, 145
- nppiDivC_16s_C1IRSfs
 - image_divc, 145
- nppiDivC_16s_C1RSfs
 - image_divc, 146
- nppiDivC_16s_C3IRSfs
 - image_divc, 146
- nppiDivC_16s_C3RSfs
 - image_divc, 146
- nppiDivC_16s_C4IRSfs
 - image_divc, 147
- nppiDivC_16s_C4RSfs
 - image_divc, 147
- nppiDivC_16sc_AC4IRSfs
 - image_divc, 148
- nppiDivC_16sc_AC4RSfs
 - image_divc, 148
- nppiDivC_16sc_C1IRSfs
 - image_divc, 148
- nppiDivC_16sc_C1RSfs
 - image_divc, 149
- nppiDivC_16sc_C3IRSfs
 - image_divc, 149
- nppiDivC_16sc_C3RSfs
 - image_divc, 150
- nppiDivC_16u_AC4IRSfs
 - image_divc, 150
- nppiDivC_16u_AC4RSfs
 - image_divc, 150
- nppiDivC_16u_C1IRSfs
 - image_divc, 151
- nppiDivC_16u_C1RSfs
 - image_divc, 151
- nppiDivC_16u_C3IRSfs
 - image_divc, 152
- nppiDivC_16u_C3RSfs
 - image_divc, 152
- nppiDivC_16u_C4IRSfs
 - image_divc, 152
- nppiDivC_16u_C4RSfs
 - image_divc, 153
- nppiDivC_32f_AC4IR
 - image_divc, 153
- nppiDivC_32f_AC4R
 - image_divc, 153
- nppiDivC_32f_C1IR
 - image_divc, 154
- nppiDivC_32f_C1R
 - image_divc, 154
- nppiDivC_32f_C3IR
 - image_divc, 154
- nppiDivC_32f_C3R
 - image_divc, 155
- nppiDivC_32f_C4IR
 - image_divc, 155
- nppiDivC_32f_C4R
 - image_divc, 155
- nppiDivC_32fc_AC4IR
 - image_divc, 156
- nppiDivC_32fc_AC4R
 - image_divc, 156
- nppiDivC_32fc_C1IR
 - image_divc, 156
- nppiDivC_32fc_C1R
 - image_divc, 157
- nppiDivC_32fc_C3IR
 - image_divc, 157
- nppiDivC_32fc_C3R
 - image_divc, 157
- nppiDivC_32fc_C4IR
 - image_divc, 158
- nppiDivC_32fc_C4R
 - image_divc, 158
- nppiDivC_32s_C1IRSfs
 - image_divc, 159
- nppiDivC_32s_C1RSfs
 - image_divc, 159
- nppiDivC_32s_C3IRSfs
 - image_divc, 159
- nppiDivC_32s_C3RSfs
 - image_divc, 160
- nppiDivC_32sc_AC4IRSfs
 - image_divc, 160
- nppiDivC_32sc_AC4RSfs
 - image_divc, 160
- nppiDivC_32sc_C1IRSfs
 - image_divc, 161
- nppiDivC_32sc_C1RSfs
 - image_divc, 161
- nppiDivC_32sc_C3IRSfs
 - image_divc, 162
- nppiDivC_32sc_C3RSfs
 - image_divc, 162
- nppiDivC_8u_AC4IRSfs
 - image_divc, 162
- nppiDivC_8u_AC4RSfs
 - image_divc, 163
- nppiDivC_8u_C1IRSfs
 - image_divc, 163
- nppiDivC_8u_C1RSfs

- image_divc, 164
- nppiDivC_8u_C3IRSfs
 - image_divc, 164
- nppiDivC_8u_C3RSfs
 - image_divc, 164
- nppiDivC_8u_C4IRSfs
 - image_divc, 165
- nppiDivC_8u_C4RSfs
 - image_divc, 165
- nppiDotProd_16s64f_AC4R
 - image_dot_prod, 1646
- nppiDotProd_16s64f_C1R
 - image_dot_prod, 1646
- nppiDotProd_16s64f_C3R
 - image_dot_prod, 1647
- nppiDotProd_16s64f_C4R
 - image_dot_prod, 1647
- nppiDotProd_16u64f_AC4R
 - image_dot_prod, 1648
- nppiDotProd_16u64f_C1R
 - image_dot_prod, 1648
- nppiDotProd_16u64f_C3R
 - image_dot_prod, 1649
- nppiDotProd_16u64f_C4R
 - image_dot_prod, 1649
- nppiDotProd_32f64f_AC4R
 - image_dot_prod, 1649
- nppiDotProd_32f64f_C1R
 - image_dot_prod, 1650
- nppiDotProd_32f64f_C3R
 - image_dot_prod, 1650
- nppiDotProd_32f64f_C4R
 - image_dot_prod, 1651
- nppiDotProd_32s64f_AC4R
 - image_dot_prod, 1651
- nppiDotProd_32s64f_C1R
 - image_dot_prod, 1652
- nppiDotProd_32s64f_C3R
 - image_dot_prod, 1652
- nppiDotProd_32s64f_C4R
 - image_dot_prod, 1652
- nppiDotProd_32u64f_AC4R
 - image_dot_prod, 1653
- nppiDotProd_32u64f_C1R
 - image_dot_prod, 1653
- nppiDotProd_32u64f_C3R
 - image_dot_prod, 1654
- nppiDotProd_32u64f_C4R
 - image_dot_prod, 1654
- nppiDotProd_8s64f_AC4R
 - image_dot_prod, 1655
- nppiDotProd_8s64f_C1R
 - image_dot_prod, 1655
- nppiDotProd_8s64f_C3R
 - image_dot_prod, 1655
- nppiDotProd_8s64f_C4R
 - image_dot_prod, 1656
- nppiDotProd_8u64f_AC4R
 - image_dot_prod, 1656
- nppiDotProd_8u64f_C1R
 - image_dot_prod, 1657
- nppiDotProd_8u64f_C3R
 - image_dot_prod, 1657
- nppiDotProd_8u64f_C4R
 - image_dot_prod, 1658
- nppiDotProdGetBufferHostSize_16s64f_AC4R
 - image_dot_prod, 1658
- nppiDotProdGetBufferHostSize_16s64f_C1R
 - image_dot_prod, 1658
- nppiDotProdGetBufferHostSize_16s64f_C3R
 - image_dot_prod, 1659
- nppiDotProdGetBufferHostSize_16s64f_C4R
 - image_dot_prod, 1659
- nppiDotProdGetBufferHostSize_16u64f_AC4R
 - image_dot_prod, 1659
- nppiDotProdGetBufferHostSize_16u64f_C1R
 - image_dot_prod, 1659
- nppiDotProdGetBufferHostSize_16u64f_C3R
 - image_dot_prod, 1660
- nppiDotProdGetBufferHostSize_16u64f_C4R
 - image_dot_prod, 1660
- nppiDotProdGetBufferHostSize_32f64f_AC4R
 - image_dot_prod, 1660
- nppiDotProdGetBufferHostSize_32f64f_C1R
 - image_dot_prod, 1661
- nppiDotProdGetBufferHostSize_32f64f_C3R
 - image_dot_prod, 1661
- nppiDotProdGetBufferHostSize_32f64f_C4R
 - image_dot_prod, 1661
- nppiDotProdGetBufferHostSize_32s64f_AC4R
 - image_dot_prod, 1661
- nppiDotProdGetBufferHostSize_32s64f_C1R
 - image_dot_prod, 1662
- nppiDotProdGetBufferHostSize_32s64f_C3R
 - image_dot_prod, 1662
- nppiDotProdGetBufferHostSize_32s64f_C4R
 - image_dot_prod, 1662
- nppiDotProdGetBufferHostSize_32u64f_AC4R
 - image_dot_prod, 1663
- nppiDotProdGetBufferHostSize_32u64f_C1R
 - image_dot_prod, 1663
- nppiDotProdGetBufferHostSize_32u64f_C3R
 - image_dot_prod, 1663
- nppiDotProdGetBufferHostSize_32u64f_C4R
 - image_dot_prod, 1663
- nppiDotProdGetBufferHostSize_8s64f_AC4R
 - image_dot_prod, 1664
- nppiDotProdGetBufferHostSize_8s64f_C1R

- image_dot_prod, 1664
- nppiDotProdGetBufferHostSize_8s64f_C3R
 - image_dot_prod, 1664
- nppiDotProdGetBufferHostSize_8s64f_C4R
 - image_dot_prod, 1665
- nppiDotProdGetBufferHostSize_8u64f_AC4R
 - image_dot_prod, 1665
- nppiDotProdGetBufferHostSize_8u64f_C1R
 - image_dot_prod, 1665
- nppiDotProdGetBufferHostSize_8u64f_C3R
 - image_dot_prod, 1665
- nppiDotProdGetBufferHostSize_8u64f_C4R
 - image_dot_prod, 1666
- nppiDup_16s_C1AC4R
 - image_duplicate_channel, 893
- nppiDup_16s_C1C3R
 - image_duplicate_channel, 893
- nppiDup_16s_C1C4R
 - image_duplicate_channel, 894
- nppiDup_16u_C1AC4R
 - image_duplicate_channel, 894
- nppiDup_16u_C1C3R
 - image_duplicate_channel, 894
- nppiDup_16u_C1C4R
 - image_duplicate_channel, 895
- nppiDup_32f_C1AC4R
 - image_duplicate_channel, 895
- nppiDup_32f_C1C3R
 - image_duplicate_channel, 895
- nppiDup_32f_C1C4R
 - image_duplicate_channel, 896
- nppiDup_32s_C1AC4R
 - image_duplicate_channel, 896
- nppiDup_32s_C1C3R
 - image_duplicate_channel, 896
- nppiDup_32s_C1C4R
 - image_duplicate_channel, 897
- nppiDup_8u_C1AC4R
 - image_duplicate_channel, 897
- nppiDup_8u_C1C3R
 - image_duplicate_channel, 897
- nppiDup_8u_C1C4R
 - image_duplicate_channel, 898
- nppiErode3x3_16u_AC4R
 - image_erode_3x3, 1294
- nppiErode3x3_16u_C1R
 - image_erode_3x3, 1294
- nppiErode3x3_16u_C3R
 - image_erode_3x3, 1294
- nppiErode3x3_16u_C4R
 - image_erode_3x3, 1295
- nppiErode3x3_32f_AC4R
 - image_erode_3x3, 1295
- nppiErode3x3_32f_C1R
 - image_erode_3x3, 1295
- nppiErode3x3_32f_C3R
 - image_erode_3x3, 1296
- nppiErode3x3_32f_C4R
 - image_erode_3x3, 1296
- nppiErode3x3_64f_C1R
 - image_erode_3x3, 1296
- nppiErode3x3_8u_AC4R
 - image_erode_3x3, 1297
- nppiErode3x3_8u_C1R
 - image_erode_3x3, 1297
- nppiErode3x3_8u_C3R
 - image_erode_3x3, 1297
- nppiErode3x3_8u_C4R
 - image_erode_3x3, 1298
- nppiErode_16u_AC4R
 - image_erode, 1281
- nppiErode_16u_C1R
 - image_erode, 1281
- nppiErode_16u_C3R
 - image_erode, 1282
- nppiErode_16u_C4R
 - image_erode, 1282
- nppiErode_32f_AC4R
 - image_erode, 1282
- nppiErode_32f_C1R
 - image_erode, 1283
- nppiErode_32f_C3R
 - image_erode, 1283
- nppiErode_32f_C4R
 - image_erode, 1284
- nppiErode_8u_AC4R
 - image_erode, 1284
- nppiErode_8u_C1R
 - image_erode, 1285
- nppiErode_8u_C3R
 - image_erode, 1285
- nppiErode_8u_C4R
 - image_erode, 1285
- nppiEvenLevelsHost_32s
 - image_histogrameval, 1697
- nppiExp_16s_C1IRSfs
 - image_exp, 364
- nppiExp_16s_C1RSfs
 - image_exp, 364
- nppiExp_16s_C3IRSfs
 - image_exp, 365
- nppiExp_16s_C3RSfs
 - image_exp, 365
- nppiExp_16u_C1IRSfs
 - image_exp, 365
- nppiExp_16u_C1RSfs
 - image_exp, 366
- nppiExp_16u_C3IRSfs

- image_exp, 366
- nppiExp_16u_C3RSfs
 - image_exp, 366
- nppiExp_32f_C1IR
 - image_exp, 367
- nppiExp_32f_C1R
 - image_exp, 367
- nppiExp_32f_C3IR
 - image_exp, 367
- nppiExp_32f_C3R
 - image_exp, 368
- nppiExp_8u_C1IRSfs
 - image_exp, 368
- nppiExp_8u_C1RSfs
 - image_exp, 368
- nppiExp_8u_C3IRSfs
 - image_exp, 369
- nppiExp_8u_C3RSfs
 - image_exp, 369
- nppiFilter32f_16s_AC4R
 - image_convolution, 1013
- nppiFilter32f_16s_C1R
 - image_convolution, 1013
- nppiFilter32f_16s_C3R
 - image_convolution, 1013
- nppiFilter32f_16s_C4R
 - image_convolution, 1014
- nppiFilter32f_16u_AC4R
 - image_convolution, 1014
- nppiFilter32f_16u_C1R
 - image_convolution, 1015
- nppiFilter32f_16u_C3R
 - image_convolution, 1015
- nppiFilter32f_16u_C4R
 - image_convolution, 1016
- nppiFilter32f_32s_AC4R
 - image_convolution, 1016
- nppiFilter32f_32s_C1R
 - image_convolution, 1017
- nppiFilter32f_32s_C3R
 - image_convolution, 1017
- nppiFilter32f_32s_C4R
 - image_convolution, 1018
- nppiFilter32f_8s16s_AC4R
 - image_convolution, 1018
- nppiFilter32f_8s16s_C1R
 - image_convolution, 1019
- nppiFilter32f_8s16s_C3R
 - image_convolution, 1019
- nppiFilter32f_8s16s_C4R
 - image_convolution, 1020
- nppiFilter32f_8s_AC4R
 - image_convolution, 1020
- nppiFilter32f_8s_C1R
 - image_convolution, 1021
- nppiFilter32f_8s_C3R
 - image_convolution, 1021
- nppiFilter32f_8s_C4R
 - image_convolution, 1022
- nppiFilter32f_8u16s_AC4R
 - image_convolution, 1022
- nppiFilter32f_8u16s_C1R
 - image_convolution, 1023
- nppiFilter32f_8u16s_C3R
 - image_convolution, 1023
- nppiFilter32f_8u16s_C4R
 - image_convolution, 1024
- nppiFilter32f_8u_AC4R
 - image_convolution, 1024
- nppiFilter32f_8u_C1R
 - image_convolution, 1025
- nppiFilter32f_8u_C3R
 - image_convolution, 1025
- nppiFilter32f_8u_C4R
 - image_convolution, 1026
- nppiFilter_16s_AC4R
 - image_convolution, 1026
- nppiFilter_16s_C1R
 - image_convolution, 1027
- nppiFilter_16s_C3R
 - image_convolution, 1027
- nppiFilter_16s_C4R
 - image_convolution, 1028
- nppiFilter_16u_AC4R
 - image_convolution, 1028
- nppiFilter_16u_C1R
 - image_convolution, 1029
- nppiFilter_16u_C3R
 - image_convolution, 1029
- nppiFilter_16u_C4R
 - image_convolution, 1030
- nppiFilter_32f_AC4R
 - image_convolution, 1030
- nppiFilter_32f_C1R
 - image_convolution, 1031
- nppiFilter_32f_C3R
 - image_convolution, 1031
- nppiFilter_32f_C4R
 - image_convolution, 1032
- nppiFilter_64f_C1R
 - image_convolution, 1032
- nppiFilter_8u_AC4R
 - image_convolution, 1033
- nppiFilter_8u_C1R
 - image_convolution, 1033
- nppiFilter_8u_C3R
 - image_convolution, 1034
- nppiFilter_8u_C4R

- image_convolution, 1034
- nppiFilterBox_16s_AC4R
 - image_2D_fixed_linear_filters, 1037
- nppiFilterBox_16s_C1R
 - image_2D_fixed_linear_filters, 1037
- nppiFilterBox_16s_C3R
 - image_2D_fixed_linear_filters, 1038
- nppiFilterBox_16s_C4R
 - image_2D_fixed_linear_filters, 1038
- nppiFilterBox_16u_AC4R
 - image_2D_fixed_linear_filters, 1039
- nppiFilterBox_16u_C1R
 - image_2D_fixed_linear_filters, 1039
- nppiFilterBox_16u_C3R
 - image_2D_fixed_linear_filters, 1039
- nppiFilterBox_16u_C4R
 - image_2D_fixed_linear_filters, 1040
- nppiFilterBox_32f_AC4R
 - image_2D_fixed_linear_filters, 1040
- nppiFilterBox_32f_C1R
 - image_2D_fixed_linear_filters, 1041
- nppiFilterBox_32f_C3R
 - image_2D_fixed_linear_filters, 1041
- nppiFilterBox_32f_C4R
 - image_2D_fixed_linear_filters, 1041
- nppiFilterBox_64f_C1R
 - image_2D_fixed_linear_filters, 1042
- nppiFilterBox_8u_AC4R
 - image_2D_fixed_linear_filters, 1042
- nppiFilterBox_8u_C1R
 - image_2D_fixed_linear_filters, 1043
- nppiFilterBox_8u_C3R
 - image_2D_fixed_linear_filters, 1043
- nppiFilterBox_8u_C4R
 - image_2D_fixed_linear_filters, 1043
- nppiFilterColumn32f_16s_AC4R
 - image_1D_linear_filter, 941
- nppiFilterColumn32f_16s_C1R
 - image_1D_linear_filter, 941
- nppiFilterColumn32f_16s_C3R
 - image_1D_linear_filter, 942
- nppiFilterColumn32f_16s_C4R
 - image_1D_linear_filter, 942
- nppiFilterColumn32f_16u_AC4R
 - image_1D_linear_filter, 942
- nppiFilterColumn32f_16u_C1R
 - image_1D_linear_filter, 943
- nppiFilterColumn32f_16u_C3R
 - image_1D_linear_filter, 943
- nppiFilterColumn32f_16u_C4R
 - image_1D_linear_filter, 944
- nppiFilterColumn32f_8u_AC4R
 - image_1D_linear_filter, 944
- nppiFilterColumn32f_8u_C1R
 - image_1D_linear_filter, 945
- nppiFilterColumn32f_8u_C3R
 - image_1D_linear_filter, 945
- nppiFilterColumn32f_8u_C4R
 - image_1D_linear_filter, 946
- nppiFilterColumn_16s_AC4R
 - image_1D_linear_filter, 946
- nppiFilterColumn_16s_C1R
 - image_1D_linear_filter, 947
- nppiFilterColumn_16s_C3R
 - image_1D_linear_filter, 947
- nppiFilterColumn_16s_C4R
 - image_1D_linear_filter, 948
- nppiFilterColumn_16u_AC4R
 - image_1D_linear_filter, 948
- nppiFilterColumn_16u_C1R
 - image_1D_linear_filter, 949
- nppiFilterColumn_16u_C3R
 - image_1D_linear_filter, 949
- nppiFilterColumn_16u_C4R
 - image_1D_linear_filter, 950
- nppiFilterColumn_32f_AC4R
 - image_1D_linear_filter, 950
- nppiFilterColumn_32f_C1R
 - image_1D_linear_filter, 951
- nppiFilterColumn_32f_C3R
 - image_1D_linear_filter, 951
- nppiFilterColumn_32f_C4R
 - image_1D_linear_filter, 952
- nppiFilterColumn_64f_C1R
 - image_1D_linear_filter, 952
- nppiFilterColumn_8u_AC4R
 - image_1D_linear_filter, 953
- nppiFilterColumn_8u_C1R
 - image_1D_linear_filter, 953
- nppiFilterColumn_8u_C3R
 - image_1D_linear_filter, 954
- nppiFilterColumn_8u_C4R
 - image_1D_linear_filter, 954
- nppiFilterGauss_16s_AC4R
 - image_1D_linear_filter, 955
- nppiFilterGauss_16s_C1R
 - image_1D_linear_filter, 955
- nppiFilterGauss_16s_C3R
 - image_1D_linear_filter, 956
- nppiFilterGauss_16s_C4R
 - image_1D_linear_filter, 956
- nppiFilterGauss_16u_AC4R
 - image_1D_linear_filter, 956
- nppiFilterGauss_16u_C1R
 - image_1D_linear_filter, 957
- nppiFilterGauss_16u_C3R
 - image_1D_linear_filter, 957
- nppiFilterGauss_16u_C4R
 - image_1D_linear_filter, 957

- image_1D_linear_filter, 957
- nppiFilterGauss_32f_AC4R
 - image_1D_linear_filter, 958
- nppiFilterGauss_32f_C1R
 - image_1D_linear_filter, 958
- nppiFilterGauss_32f_C3R
 - image_1D_linear_filter, 958
- nppiFilterGauss_32f_C4R
 - image_1D_linear_filter, 959
- nppiFilterGauss_8u_AC4R
 - image_1D_linear_filter, 959
- nppiFilterGauss_8u_C1R
 - image_1D_linear_filter, 959
- nppiFilterGauss_8u_C3R
 - image_1D_linear_filter, 960
- nppiFilterGauss_8u_C4R
 - image_1D_linear_filter, 960
- nppiFilterHighPass_16s_AC4R
 - image_1D_linear_filter, 960
- nppiFilterHighPass_16s_C1R
 - image_1D_linear_filter, 961
- nppiFilterHighPass_16s_C3R
 - image_1D_linear_filter, 961
- nppiFilterHighPass_16s_C4R
 - image_1D_linear_filter, 961
- nppiFilterHighPass_16u_AC4R
 - image_1D_linear_filter, 962
- nppiFilterHighPass_16u_C1R
 - image_1D_linear_filter, 962
- nppiFilterHighPass_16u_C3R
 - image_1D_linear_filter, 962
- nppiFilterHighPass_16u_C4R
 - image_1D_linear_filter, 963
- nppiFilterHighPass_32f_AC4R
 - image_1D_linear_filter, 963
- nppiFilterHighPass_32f_C1R
 - image_1D_linear_filter, 963
- nppiFilterHighPass_32f_C3R
 - image_1D_linear_filter, 964
- nppiFilterHighPass_32f_C4R
 - image_1D_linear_filter, 964
- nppiFilterHighPass_8u_AC4R
 - image_1D_linear_filter, 964
- nppiFilterHighPass_8u_C1R
 - image_1D_linear_filter, 965
- nppiFilterHighPass_8u_C3R
 - image_1D_linear_filter, 965
- nppiFilterHighPass_8u_C4R
 - image_1D_linear_filter, 965
- nppiFilterLaplace_16s_AC4R
 - image_1D_linear_filter, 966
- nppiFilterLaplace_16s_C1R
 - image_1D_linear_filter, 966
- nppiFilterLaplace_16s_C3R
 - image_1D_linear_filter, 966
- nppiFilterLaplace_16s_C4R
 - image_1D_linear_filter, 967
- nppiFilterLaplace_32f_AC4R
 - image_1D_linear_filter, 967
- nppiFilterLaplace_32f_C1R
 - image_1D_linear_filter, 967
- nppiFilterLaplace_32f_C3R
 - image_1D_linear_filter, 968
- nppiFilterLaplace_32f_C4R
 - image_1D_linear_filter, 968
- nppiFilterLaplace_8s16s_C1R
 - image_1D_linear_filter, 968
- nppiFilterLaplace_8u16s_C1R
 - image_1D_linear_filter, 969
- nppiFilterLaplace_8u_AC4R
 - image_1D_linear_filter, 969
- nppiFilterLaplace_8u_C1R
 - image_1D_linear_filter, 969
- nppiFilterLaplace_8u_C3R
 - image_1D_linear_filter, 970
- nppiFilterLaplace_8u_C4R
 - image_1D_linear_filter, 970
- nppiFilterLowPass_16s_AC4R
 - image_1D_linear_filter, 970
- nppiFilterLowPass_16s_C1R
 - image_1D_linear_filter, 971
- nppiFilterLowPass_16s_C3R
 - image_1D_linear_filter, 971
- nppiFilterLowPass_16s_C4R
 - image_1D_linear_filter, 971
- nppiFilterLowPass_16u_AC4R
 - image_1D_linear_filter, 972
- nppiFilterLowPass_16u_C1R
 - image_1D_linear_filter, 972
- nppiFilterLowPass_16u_C3R
 - image_1D_linear_filter, 972
- nppiFilterLowPass_16u_C4R
 - image_1D_linear_filter, 973
- nppiFilterLowPass_32f_AC4R
 - image_1D_linear_filter, 973
- nppiFilterLowPass_32f_C1R
 - image_1D_linear_filter, 973
- nppiFilterLowPass_32f_C3R
 - image_1D_linear_filter, 974
- nppiFilterLowPass_32f_C4R
 - image_1D_linear_filter, 974
- nppiFilterLowPass_8u_AC4R
 - image_1D_linear_filter, 974
- nppiFilterLowPass_8u_C1R
 - image_1D_linear_filter, 975
- nppiFilterLowPass_8u_C3R
 - image_1D_linear_filter, 975
- nppiFilterLowPass_8u_C4R

- image_1D_linear_filter, 975
- nppiFilterMax_16s_AC4R
 - image_rank_filters, 1047
- nppiFilterMax_16s_C1R
 - image_rank_filters, 1048
- nppiFilterMax_16s_C3R
 - image_rank_filters, 1048
- nppiFilterMax_16s_C4R
 - image_rank_filters, 1048
- nppiFilterMax_16u_AC4R
 - image_rank_filters, 1049
- nppiFilterMax_16u_C1R
 - image_rank_filters, 1049
- nppiFilterMax_16u_C3R
 - image_rank_filters, 1050
- nppiFilterMax_16u_C4R
 - image_rank_filters, 1050
- nppiFilterMax_32f_AC4R
 - image_rank_filters, 1050
- nppiFilterMax_32f_C1R
 - image_rank_filters, 1051
- nppiFilterMax_32f_C3R
 - image_rank_filters, 1051
- nppiFilterMax_32f_C4R
 - image_rank_filters, 1052
- nppiFilterMax_8u_AC4R
 - image_rank_filters, 1052
- nppiFilterMax_8u_C1R
 - image_rank_filters, 1052
- nppiFilterMax_8u_C3R
 - image_rank_filters, 1053
- nppiFilterMax_8u_C4R
 - image_rank_filters, 1053
- nppiFilterMin_16s_AC4R
 - image_rank_filters, 1054
- nppiFilterMin_16s_C1R
 - image_rank_filters, 1054
- nppiFilterMin_16s_C3R
 - image_rank_filters, 1054
- nppiFilterMin_16s_C4R
 - image_rank_filters, 1055
- nppiFilterMin_16u_AC4R
 - image_rank_filters, 1055
- nppiFilterMin_16u_C1R
 - image_rank_filters, 1056
- nppiFilterMin_16u_C3R
 - image_rank_filters, 1056
- nppiFilterMin_16u_C4R
 - image_rank_filters, 1056
- nppiFilterMin_32f_AC4R
 - image_rank_filters, 1057
- nppiFilterMin_32f_C1R
 - image_rank_filters, 1057
- nppiFilterMin_32f_C3R
 - image_rank_filters, 1058
- nppiFilterMin_32f_C4R
 - image_rank_filters, 1058
- nppiFilterMin_8u_AC4R
 - image_rank_filters, 1058
- nppiFilterMin_8u_C1R
 - image_rank_filters, 1059
- nppiFilterMin_8u_C3R
 - image_rank_filters, 1059
- nppiFilterMin_8u_C4R
 - image_rank_filters, 1060
- nppiFilterPrewittHoriz_16s_AC4R
 - fixed_filters, 1067
- nppiFilterPrewittHoriz_16s_C1R
 - fixed_filters, 1067
- nppiFilterPrewittHoriz_16s_C3R
 - fixed_filters, 1068
- nppiFilterPrewittHoriz_16s_C4R
 - fixed_filters, 1068
- nppiFilterPrewittHoriz_32f_AC4R
 - fixed_filters, 1068
- nppiFilterPrewittHoriz_32f_C1R
 - fixed_filters, 1069
- nppiFilterPrewittHoriz_32f_C3R
 - fixed_filters, 1069
- nppiFilterPrewittHoriz_32f_C4R
 - fixed_filters, 1069
- nppiFilterPrewittHoriz_8u_AC4R
 - fixed_filters, 1070
- nppiFilterPrewittHoriz_8u_C1R
 - fixed_filters, 1070
- nppiFilterPrewittHoriz_8u_C3R
 - fixed_filters, 1070
- nppiFilterPrewittHoriz_8u_C4R
 - fixed_filters, 1071
- nppiFilterPrewittVert_16s_AC4R
 - fixed_filters, 1071
- nppiFilterPrewittVert_16s_C1R
 - fixed_filters, 1071
- nppiFilterPrewittVert_16s_C3R
 - fixed_filters, 1072
- nppiFilterPrewittVert_16s_C4R
 - fixed_filters, 1072
- nppiFilterPrewittVert_32f_AC4R
 - fixed_filters, 1072
- nppiFilterPrewittVert_32f_C1R
 - fixed_filters, 1073
- nppiFilterPrewittVert_32f_C3R
 - fixed_filters, 1073
- nppiFilterPrewittVert_32f_C4R
 - fixed_filters, 1073
- nppiFilterPrewittVert_8u_AC4R
 - fixed_filters, 1074
- nppiFilterPrewittVert_8u_C1R

- fixed_filters, [1074](#)
- nppiFilterPrewittVert_8u_C3R
 - fixed_filters, [1074](#)
- nppiFilterPrewittVert_8u_C4R
 - fixed_filters, [1075](#)
- nppiFilterRobertsDown_16s_AC4R
 - image_1D_linear_filter, [976](#)
- nppiFilterRobertsDown_16s_C1R
 - image_1D_linear_filter, [976](#)
- nppiFilterRobertsDown_16s_C3R
 - image_1D_linear_filter, [976](#)
- nppiFilterRobertsDown_16s_C4R
 - image_1D_linear_filter, [977](#)
- nppiFilterRobertsDown_32f_AC4R
 - image_1D_linear_filter, [977](#)
- nppiFilterRobertsDown_32f_C1R
 - image_1D_linear_filter, [977](#)
- nppiFilterRobertsDown_32f_C3R
 - image_1D_linear_filter, [978](#)
- nppiFilterRobertsDown_32f_C4R
 - image_1D_linear_filter, [978](#)
- nppiFilterRobertsDown_8u_AC4R
 - image_1D_linear_filter, [978](#)
- nppiFilterRobertsDown_8u_C1R
 - image_1D_linear_filter, [979](#)
- nppiFilterRobertsDown_8u_C3R
 - image_1D_linear_filter, [979](#)
- nppiFilterRobertsDown_8u_C4R
 - image_1D_linear_filter, [979](#)
- nppiFilterRobertsUp_16s_AC4R
 - image_1D_linear_filter, [980](#)
- nppiFilterRobertsUp_16s_C1R
 - image_1D_linear_filter, [980](#)
- nppiFilterRobertsUp_16s_C3R
 - image_1D_linear_filter, [980](#)
- nppiFilterRobertsUp_16s_C4R
 - image_1D_linear_filter, [981](#)
- nppiFilterRobertsUp_32f_AC4R
 - image_1D_linear_filter, [981](#)
- nppiFilterRobertsUp_32f_C1R
 - image_1D_linear_filter, [981](#)
- nppiFilterRobertsUp_32f_C3R
 - image_1D_linear_filter, [982](#)
- nppiFilterRobertsUp_32f_C4R
 - image_1D_linear_filter, [982](#)
- nppiFilterRobertsUp_8u_AC4R
 - image_1D_linear_filter, [982](#)
- nppiFilterRobertsUp_8u_C1R
 - image_1D_linear_filter, [983](#)
- nppiFilterRobertsUp_8u_C3R
 - image_1D_linear_filter, [983](#)
- nppiFilterRobertsUp_8u_C4R
 - image_1D_linear_filter, [983](#)
- nppiFilterRow32f_16s_AC4R
 - image_1D_linear_filter, [984](#)
- nppiFilterRow32f_16s_C1R
 - image_1D_linear_filter, [984](#)
- nppiFilterRow32f_16s_C3R
 - image_1D_linear_filter, [985](#)
- nppiFilterRow32f_16s_C4R
 - image_1D_linear_filter, [985](#)
- nppiFilterRow32f_16u_AC4R
 - image_1D_linear_filter, [986](#)
- nppiFilterRow32f_16u_C1R
 - image_1D_linear_filter, [986](#)
- nppiFilterRow32f_16u_C3R
 - image_1D_linear_filter, [986](#)
- nppiFilterRow32f_16u_C4R
 - image_1D_linear_filter, [987](#)
- nppiFilterRow32f_8u_AC4R
 - image_1D_linear_filter, [987](#)
- nppiFilterRow32f_8u_C1R
 - image_1D_linear_filter, [988](#)
- nppiFilterRow32f_8u_C3R
 - image_1D_linear_filter, [988](#)
- nppiFilterRow32f_8u_C4R
 - image_1D_linear_filter, [989](#)
- nppiFilterRow_16s_AC4R
 - image_1D_linear_filter, [989](#)
- nppiFilterRow_16s_C1R
 - image_1D_linear_filter, [990](#)
- nppiFilterRow_16s_C3R
 - image_1D_linear_filter, [990](#)
- nppiFilterRow_16s_C4R
 - image_1D_linear_filter, [991](#)
- nppiFilterRow_16u_AC4R
 - image_1D_linear_filter, [991](#)
- nppiFilterRow_16u_C1R
 - image_1D_linear_filter, [992](#)
- nppiFilterRow_16u_C3R
 - image_1D_linear_filter, [992](#)
- nppiFilterRow_16u_C4R
 - image_1D_linear_filter, [993](#)
- nppiFilterRow_32f_AC4R
 - image_1D_linear_filter, [993](#)
- nppiFilterRow_32f_C1R
 - image_1D_linear_filter, [994](#)
- nppiFilterRow_32f_C3R
 - image_1D_linear_filter, [994](#)
- nppiFilterRow_32f_C4R
 - image_1D_linear_filter, [995](#)
- nppiFilterRow_64f_C1R
 - image_1D_linear_filter, [995](#)
- nppiFilterRow_8u_AC4R
 - image_1D_linear_filter, [996](#)
- nppiFilterRow_8u_C1R
 - image_1D_linear_filter, [996](#)
- nppiFilterRow_8u_C3R

- image_1D_linear_filter, 997
- nppiFilterRow_8u_C4R
 - image_1D_linear_filter, 997
- nppiFilterScharrHoriz_32f_C1R
 - fixed_filters, 1075
- nppiFilterScharrHoriz_8s16s_C1R
 - fixed_filters, 1075
- nppiFilterScharrHoriz_8u16s_C1R
 - fixed_filters, 1076
- nppiFilterScharrVert_32f_C1R
 - fixed_filters, 1076
- nppiFilterScharrVert_8s16s_C1R
 - fixed_filters, 1076
- nppiFilterScharrVert_8u16s_C1R
 - fixed_filters, 1077
- nppiFilterSharpen_16s_AC4R
 - image_1D_linear_filter, 998
- nppiFilterSharpen_16s_C1R
 - image_1D_linear_filter, 998
- nppiFilterSharpen_16s_C3R
 - image_1D_linear_filter, 999
- nppiFilterSharpen_16s_C4R
 - image_1D_linear_filter, 999
- nppiFilterSharpen_16u_AC4R
 - image_1D_linear_filter, 999
- nppiFilterSharpen_16u_C1R
 - image_1D_linear_filter, 1000
- nppiFilterSharpen_16u_C3R
 - image_1D_linear_filter, 1000
- nppiFilterSharpen_16u_C4R
 - image_1D_linear_filter, 1000
- nppiFilterSharpen_32f_AC4R
 - image_1D_linear_filter, 1001
- nppiFilterSharpen_32f_C1R
 - image_1D_linear_filter, 1001
- nppiFilterSharpen_32f_C3R
 - image_1D_linear_filter, 1001
- nppiFilterSharpen_32f_C4R
 - image_1D_linear_filter, 1002
- nppiFilterSharpen_8u_AC4R
 - image_1D_linear_filter, 1002
- nppiFilterSharpen_8u_C1R
 - image_1D_linear_filter, 1002
- nppiFilterSharpen_8u_C3R
 - image_1D_linear_filter, 1003
- nppiFilterSharpen_8u_C4R
 - image_1D_linear_filter, 1003
- nppiFilterSobelCross_32f_C1R
 - image_1D_linear_filter, 1003
- nppiFilterSobelCross_8s16s_C1R
 - image_1D_linear_filter, 1004
- nppiFilterSobelCross_8u16s_C1R
 - image_1D_linear_filter, 1004
- nppiFilterSobelHoriz_16s_AC4R
 - fixed_filters, 1077
- nppiFilterSobelHoriz_16s_C1R
 - fixed_filters, 1077
- nppiFilterSobelHoriz_16s_C3R
 - fixed_filters, 1078
- nppiFilterSobelHoriz_16s_C4R
 - fixed_filters, 1078
- nppiFilterSobelHoriz_32f_AC4R
 - fixed_filters, 1078
- nppiFilterSobelHoriz_32f_C1R
 - fixed_filters, 1079
- nppiFilterSobelHoriz_32f_C3R
 - fixed_filters, 1079
- nppiFilterSobelHoriz_32f_C4R
 - fixed_filters, 1079
- nppiFilterSobelHoriz_8s16s_C1R
 - fixed_filters, 1080
- nppiFilterSobelHoriz_8u16s_C1R
 - fixed_filters, 1080
- nppiFilterSobelHoriz_8u_AC4R
 - fixed_filters, 1080
- nppiFilterSobelHoriz_8u_C1R
 - fixed_filters, 1081
- nppiFilterSobelHoriz_8u_C3R
 - fixed_filters, 1081
- nppiFilterSobelHoriz_8u_C4R
 - fixed_filters, 1081
- nppiFilterSobelHorizMask_32f_C1R
 - fixed_filters, 1082
- nppiFilterSobelHorizSecond_32f_C1R
 - fixed_filters, 1082
- nppiFilterSobelHorizSecond_8s16s_C1R
 - fixed_filters, 1082
- nppiFilterSobelHorizSecond_8u16s_C1R
 - fixed_filters, 1083
- nppiFilterSobelVert_16s_AC4R
 - fixed_filters, 1083
- nppiFilterSobelVert_16s_C1R
 - fixed_filters, 1084
- nppiFilterSobelVert_16s_C3R
 - fixed_filters, 1084
- nppiFilterSobelVert_16s_C4R
 - fixed_filters, 1084
- nppiFilterSobelVert_32f_AC4R
 - fixed_filters, 1085
- nppiFilterSobelVert_32f_C1R
 - fixed_filters, 1085
- nppiFilterSobelVert_32f_C3R
 - fixed_filters, 1085
- nppiFilterSobelVert_32f_C4R
 - fixed_filters, 1086
- nppiFilterSobelVert_8s16s_C1R
 - fixed_filters, 1086
- nppiFilterSobelVert_8u16s_C1R

- fixed_filters, 1086
- nppiFilterSobelVert_8u_AC4R
 - fixed_filters, 1087
- nppiFilterSobelVert_8u_C1R
 - fixed_filters, 1087
- nppiFilterSobelVert_8u_C3R
 - fixed_filters, 1087
- nppiFilterSobelVert_8u_C4R
 - fixed_filters, 1088
- nppiFilterSobelVertMask_32f_C1R
 - fixed_filters, 1088
- nppiFilterSobelVertSecond_32f_C1R
 - image_1D_linear_filter, 1004
- nppiFilterSobelVertSecond_8s16s_C1R
 - image_1D_linear_filter, 1005
- nppiFilterSobelVertSecond_8u16s_C1R
 - image_1D_linear_filter, 1005
- nppiFree
 - image_memory_management, 1867
- nppiFullNormLevelGetBufferHostSize_16u32f_-AC4R
 - crosscorrfullnormlevel, 1809
- nppiFullNormLevelGetBufferHostSize_16u32f_-C1R
 - crosscorrfullnormlevel, 1810
- nppiFullNormLevelGetBufferHostSize_16u32f_-C3R
 - crosscorrfullnormlevel, 1810
- nppiFullNormLevelGetBufferHostSize_16u32f_-C4R
 - crosscorrfullnormlevel, 1810
- nppiFullNormLevelGetBufferHostSize_32f_AC4R
 - crosscorrfullnormlevel, 1811
- nppiFullNormLevelGetBufferHostSize_32f_C1R
 - crosscorrfullnormlevel, 1811
- nppiFullNormLevelGetBufferHostSize_32f_C3R
 - crosscorrfullnormlevel, 1811
- nppiFullNormLevelGetBufferHostSize_32f_C4R
 - crosscorrfullnormlevel, 1811
- nppiFullNormLevelGetBufferHostSize_8s32f_-AC4R
 - crosscorrfullnormlevel, 1812
- nppiFullNormLevelGetBufferHostSize_8s32f_C1R
 - crosscorrfullnormlevel, 1812
- nppiFullNormLevelGetBufferHostSize_8s32f_C3R
 - crosscorrfullnormlevel, 1812
- nppiFullNormLevelGetBufferHostSize_8s32f_C4R
 - crosscorrfullnormlevel, 1813
- nppiFullNormLevelGetBufferHostSize_8u32f_-AC4R
 - crosscorrfullnormlevel, 1813
- nppiFullNormLevelGetBufferHostSize_8u32f_-C1R
 - crosscorrfullnormlevel, 1813
- nppiFullNormLevelGetBufferHostSize_8u32f_-C3R
 - crosscorrfullnormlevel, 1813
- nppiFullNormLevelGetBufferHostSize_8u32f_-C4R
 - crosscorrfullnormlevel, 1814
- nppiFullNormLevelGetBufferHostSize_8u_C1RSfs
 - crosscorrfullnormlevel, 1814
- nppiFullNormLevelGetBufferHostSize_8u_C3RSfs
 - crosscorrfullnormlevel, 1815
- nppiFullNormLevelGetBufferHostSize_8u_C4RSfs
 - crosscorrfullnormlevel, 1815
- nppiGammaFwd_8u_AC4IR
 - image_color_gamma_correction, 601
- nppiGammaFwd_8u_AC4R
 - image_color_gamma_correction, 601
- nppiGammaFwd_8u_C3IR
 - image_color_gamma_correction, 601
- nppiGammaFwd_8u_C3R
 - image_color_gamma_correction, 602
- nppiGammaFwd_8u_IP3R
 - image_color_gamma_correction, 602
- nppiGammaFwd_8u_P3R
 - image_color_gamma_correction, 602
- nppiGammaInv_8u_AC4IR
 - image_color_gamma_correction, 603
- nppiGammaInv_8u_AC4R
 - image_color_gamma_correction, 603
- nppiGammaInv_8u_C3IR
 - image_color_gamma_correction, 603
- nppiGammaInv_8u_C3R
 - image_color_gamma_correction, 604
- nppiGammaInv_8u_IP3R
 - image_color_gamma_correction, 604
- nppiGammaInv_8u_P3R
 - image_color_gamma_correction, 604
- nppiGetAffineBound
 - image_affine_transform, 1182
- nppiGetAffineQuad
 - image_affine_transform, 1182
- nppiGetAffineTransform
 - image_affine_transform, 1183
- nppiGetPerspectiveBound
 - image_perspective_transforms, 1231
- nppiGetPerspectiveQuad
 - image_perspective_transforms, 1231
- nppiGetPerspectiveTransform
 - image_perspective_transforms, 1232
- nppiGetResizeRect
 - image_resize_square_pixel, 1095
- nppiGetRotateBound

- image_rotate, 1148
- nppiGetRotateQuad
 - image_rotate, 1149
- nppiGraphcut8_32f8u
 - image_graphcut, 700
- nppiGraphcut8_32s8u
 - image_graphcut, 700
- nppiGraphcut8GetSize
 - image_graphcut, 701
- nppiGraphcut8InitAlloc
 - image_graphcut, 702
- nppiGraphcut_32f8u
 - image_graphcut, 702
- nppiGraphcut_32s8u
 - image_graphcut, 703
- nppiGraphcutFree
 - image_graphcut, 704
- nppiGraphcutGetSize
 - image_graphcut, 704
- nppiGraphcutInitAlloc
 - image_graphcut, 704
- NppiGraphcutState
 - image_labeling_and_segmentation, 698
- NppiHaarBuffer, 2329
 - haarBuffer, 2329
 - haarBufferSize, 2329
- NppiHaarClassifier_32f, 2330
 - classifiers, 2330
 - classifierSize, 2330
 - classifierStep, 2330
 - counterDevice, 2330
 - numClassifiers, 2330
- nppiHistogramEven_16s_AC4R
 - image_histogrameven, 1698
- nppiHistogramEven_16s_C1R
 - image_histogrameven, 1698
- nppiHistogramEven_16s_C3R
 - image_histogrameven, 1698
- nppiHistogramEven_16s_C4R
 - image_histogrameven, 1699
- nppiHistogramEven_16u_AC4R
 - image_histogrameven, 1699
- nppiHistogramEven_16u_C1R
 - image_histogrameven, 1700
- nppiHistogramEven_16u_C3R
 - image_histogrameven, 1700
- nppiHistogramEven_16u_C4R
 - image_histogrameven, 1701
- nppiHistogramEven_8u_AC4R
 - image_histogrameven, 1701
- nppiHistogramEven_8u_C1R
 - image_histogrameven, 1702
- nppiHistogramEven_8u_C3R
 - image_histogrameven, 1702
- nppiHistogramEven_8u_C4R
 - image_histogrameven, 1703
- nppiHistogramEvenGetBufferSize_16s_AC4R
 - image_histogrameven, 1703
- nppiHistogramEvenGetBufferSize_16s_C1R
 - image_histogrameven, 1703
- nppiHistogramEvenGetBufferSize_16s_C3R
 - image_histogrameven, 1704
- nppiHistogramEvenGetBufferSize_16s_C4R
 - image_histogrameven, 1704
- nppiHistogramEvenGetBufferSize_16u_AC4R
 - image_histogrameven, 1704
- nppiHistogramEvenGetBufferSize_16u_C1R
 - image_histogrameven, 1705
- nppiHistogramEvenGetBufferSize_16u_C3R
 - image_histogrameven, 1705
- nppiHistogramEvenGetBufferSize_16u_C4R
 - image_histogrameven, 1705
- nppiHistogramEvenGetBufferSize_8u_AC4R
 - image_histogrameven, 1706
- nppiHistogramEvenGetBufferSize_8u_C1R
 - image_histogrameven, 1706
- nppiHistogramEvenGetBufferSize_8u_C3R
 - image_histogrameven, 1706
- nppiHistogramEvenGetBufferSize_8u_C4R
 - image_histogrameven, 1707
- nppiHistogramRange_16s_AC4R
 - image_histogramrange, 1711
- nppiHistogramRange_16s_C1R
 - image_histogramrange, 1711
- nppiHistogramRange_16s_C3R
 - image_histogramrange, 1711
- nppiHistogramRange_16s_C4R
 - image_histogramrange, 1712
- nppiHistogramRange_16u_AC4R
 - image_histogramrange, 1712
- nppiHistogramRange_16u_C1R
 - image_histogramrange, 1713
- nppiHistogramRange_16u_C3R
 - image_histogramrange, 1713
- nppiHistogramRange_16u_C4R
 - image_histogramrange, 1714
- nppiHistogramRange_32f_AC4R
 - image_histogramrange, 1714
- nppiHistogramRange_32f_C1R
 - image_histogramrange, 1715
- nppiHistogramRange_32f_C3R
 - image_histogramrange, 1715
- nppiHistogramRange_32f_C4R
 - image_histogramrange, 1715
- nppiHistogramRange_8u_AC4R
 - image_histogramrange, 1716
- nppiHistogramRange_8u_C1R
 - image_histogramrange, 1716

- nppiHistogramRange_8u_C3R
 - image_histogramrange, [1717](#)
- nppiHistogramRange_8u_C4R
 - image_histogramrange, [1717](#)
- nppiHistogramRangeGetBufferSize_16s_AC4R
 - image_histogramrange, [1718](#)
- nppiHistogramRangeGetBufferSize_16s_C1R
 - image_histogramrange, [1718](#)
- nppiHistogramRangeGetBufferSize_16s_C3R
 - image_histogramrange, [1718](#)
- nppiHistogramRangeGetBufferSize_16s_C4R
 - image_histogramrange, [1719](#)
- nppiHistogramRangeGetBufferSize_16u_AC4R
 - image_histogramrange, [1719](#)
- nppiHistogramRangeGetBufferSize_16u_C1R
 - image_histogramrange, [1719](#)
- nppiHistogramRangeGetBufferSize_16u_C3R
 - image_histogramrange, [1720](#)
- nppiHistogramRangeGetBufferSize_16u_C4R
 - image_histogramrange, [1720](#)
- nppiHistogramRangeGetBufferSize_32f_AC4R
 - image_histogramrange, [1720](#)
- nppiHistogramRangeGetBufferSize_32f_C1R
 - image_histogramrange, [1721](#)
- nppiHistogramRangeGetBufferSize_32f_C3R
 - image_histogramrange, [1721](#)
- nppiHistogramRangeGetBufferSize_32f_C4R
 - image_histogramrange, [1721](#)
- nppiHistogramRangeGetBufferSize_8u_AC4R
 - image_histogramrange, [1722](#)
- nppiHistogramRangeGetBufferSize_8u_C1R
 - image_histogramrange, [1722](#)
- nppiHistogramRangeGetBufferSize_8u_C3R
 - image_histogramrange, [1722](#)
- nppiHistogramRangeGetBufferSize_8u_C4R
 - image_histogramrange, [1723](#)
- nppiHLSToBGR_8u_AC4P4R
 - image_color_model_conversion, [537](#)
- nppiHLSToBGR_8u_AC4R
 - image_color_model_conversion, [538](#)
- nppiHLSToBGR_8u_AP4C4R
 - image_color_model_conversion, [538](#)
- nppiHLSToBGR_8u_AP4R
 - image_color_model_conversion, [538](#)
- nppiHLSToBGR_8u_C3P3R
 - image_color_model_conversion, [539](#)
- nppiHLSToBGR_8u_P3C3R
 - image_color_model_conversion, [539](#)
- nppiHLSToBGR_8u_P3R
 - image_color_model_conversion, [539](#)
- nppiHLSToRGB_8u_AC4R
 - image_color_model_conversion, [540](#)
- nppiHLSToRGB_8u_C3R
 - image_color_model_conversion, [540](#)
- nppiHSVToRGB_8u_AC4R
 - image_color_model_conversion, [540](#)
- nppiHSVToRGB_8u_C3R
 - image_color_model_conversion, [541](#)
- nppiIntegral_8u32f_C1R
 - image_integral, [1687](#)
- nppiIntegral_8u32s_C1R
 - image_integral, [1687](#)
- NppiInterpolationMode
 - typedefs_npp, [42](#)
- nppiLabToBGR_8u_C3R
 - image_color_model_conversion, [541](#)
- nppiLn_16s_C1RSfs
 - image_ln, [357](#)
- nppiLn_16s_C1RSfs
 - image_ln, [357](#)
- nppiLn_16s_C3RSfs
 - image_ln, [358](#)
- nppiLn_16s_C3RSfs
 - image_ln, [358](#)
- nppiLn_16u_C1RSfs
 - image_ln, [358](#)
- nppiLn_16u_C1RSfs
 - image_ln, [359](#)
- nppiLn_16u_C3RSfs
 - image_ln, [359](#)
- nppiLn_16u_C3RSfs
 - image_ln, [359](#)
- nppiLn_32f_C1IR
 - image_ln, [360](#)
- nppiLn_32f_C1R
 - image_ln, [360](#)
- nppiLn_32f_C3IR
 - image_ln, [360](#)
- nppiLn_32f_C3R
 - image_ln, [361](#)
- nppiLn_8u_C1RSfs
 - image_ln, [361](#)
- nppiLn_8u_C1RSfs
 - image_ln, [361](#)
- nppiLn_8u_C3RSfs
 - image_ln, [362](#)
- nppiLn_8u_C3RSfs
 - image_ln, [362](#)
- nppiLShiftC_16u_AC4IR
 - image_lshiftc, [423](#)
- nppiLShiftC_16u_AC4R
 - image_lshiftc, [423](#)
- nppiLShiftC_16u_C1IR
 - image_lshiftc, [423](#)
- nppiLShiftC_16u_C1R
 - image_lshiftc, [424](#)
- nppiLShiftC_16u_C3IR
 - image_lshiftc, [424](#)

- nppiLShiftC_16u_C3R
 - image_lshiftc, [424](#)
- nppiLShiftC_16u_C4IR
 - image_lshiftc, [425](#)
- nppiLShiftC_16u_C4R
 - image_lshiftc, [425](#)
- nppiLShiftC_32s_AC4IR
 - image_lshiftc, [425](#)
- nppiLShiftC_32s_AC4R
 - image_lshiftc, [426](#)
- nppiLShiftC_32s_C1IR
 - image_lshiftc, [426](#)
- nppiLShiftC_32s_C1R
 - image_lshiftc, [426](#)
- nppiLShiftC_32s_C3IR
 - image_lshiftc, [427](#)
- nppiLShiftC_32s_C3R
 - image_lshiftc, [427](#)
- nppiLShiftC_32s_C4IR
 - image_lshiftc, [427](#)
- nppiLShiftC_32s_C4R
 - image_lshiftc, [428](#)
- nppiLShiftC_8u_AC4IR
 - image_lshiftc, [428](#)
- nppiLShiftC_8u_AC4R
 - image_lshiftc, [428](#)
- nppiLShiftC_8u_C1IR
 - image_lshiftc, [429](#)
- nppiLShiftC_8u_C1R
 - image_lshiftc, [429](#)
- nppiLShiftC_8u_C3IR
 - image_lshiftc, [429](#)
- nppiLShiftC_8u_C3R
 - image_lshiftc, [430](#)
- nppiLShiftC_8u_C4IR
 - image_lshiftc, [430](#)
- nppiLShiftC_8u_C4R
 - image_lshiftc, [430](#)
- nppiLUT_16s_AC4IR
 - image_color_processing, [632](#)
- nppiLUT_16s_AC4R
 - image_color_processing, [633](#)
- nppiLUT_16s_C1IR
 - image_color_processing, [633](#)
- nppiLUT_16s_C1R
 - image_color_processing, [634](#)
- nppiLUT_16s_C3IR
 - image_color_processing, [634](#)
- nppiLUT_16s_C3R
 - image_color_processing, [635](#)
- nppiLUT_16s_C4IR
 - image_color_processing, [635](#)
- nppiLUT_16s_C4R
 - image_color_processing, [636](#)
- nppiLUT_16u_AC4IR
 - image_color_processing, [636](#)
- nppiLUT_16u_AC4R
 - image_color_processing, [637](#)
- nppiLUT_16u_C1IR
 - image_color_processing, [637](#)
- nppiLUT_16u_C1R
 - image_color_processing, [638](#)
- nppiLUT_16u_C3IR
 - image_color_processing, [638](#)
- nppiLUT_16u_C3R
 - image_color_processing, [639](#)
- nppiLUT_16u_C4IR
 - image_color_processing, [639](#)
- nppiLUT_16u_C4R
 - image_color_processing, [640](#)
- nppiLUT_32f_AC4IR
 - image_color_processing, [640](#)
- nppiLUT_32f_AC4R
 - image_color_processing, [641](#)
- nppiLUT_32f_C1IR
 - image_color_processing, [641](#)
- nppiLUT_32f_C1R
 - image_color_processing, [642](#)
- nppiLUT_32f_C3IR
 - image_color_processing, [642](#)
- nppiLUT_32f_C3R
 - image_color_processing, [643](#)
- nppiLUT_32f_C4IR
 - image_color_processing, [643](#)
- nppiLUT_32f_C4R
 - image_color_processing, [644](#)
- nppiLUT_8u_AC4IR
 - image_color_processing, [644](#)
- nppiLUT_8u_AC4R
 - image_color_processing, [645](#)
- nppiLUT_8u_C1IR
 - image_color_processing, [645](#)
- nppiLUT_8u_C1R
 - image_color_processing, [646](#)
- nppiLUT_8u_C3IR
 - image_color_processing, [646](#)
- nppiLUT_8u_C3R
 - image_color_processing, [647](#)
- nppiLUT_8u_C4IR
 - image_color_processing, [647](#)
- nppiLUT_8u_C4R
 - image_color_processing, [648](#)
- nppiLUT_Cubic_16s_AC4IR
 - image_color_processing, [648](#)
- nppiLUT_Cubic_16s_AC4R
 - image_color_processing, [649](#)
- nppiLUT_Cubic_16s_C1IR
 - image_color_processing, [649](#)

- nppiLUT_Cubic_16s_C1R
 - image_color_processing, 650
- nppiLUT_Cubic_16s_C3IR
 - image_color_processing, 650
- nppiLUT_Cubic_16s_C3R
 - image_color_processing, 651
- nppiLUT_Cubic_16s_C4IR
 - image_color_processing, 651
- nppiLUT_Cubic_16s_C4R
 - image_color_processing, 652
- nppiLUT_Cubic_16u_AC4IR
 - image_color_processing, 652
- nppiLUT_Cubic_16u_AC4R
 - image_color_processing, 653
- nppiLUT_Cubic_16u_C1IR
 - image_color_processing, 653
- nppiLUT_Cubic_16u_C1R
 - image_color_processing, 654
- nppiLUT_Cubic_16u_C3IR
 - image_color_processing, 654
- nppiLUT_Cubic_16u_C3R
 - image_color_processing, 655
- nppiLUT_Cubic_16u_C4IR
 - image_color_processing, 655
- nppiLUT_Cubic_16u_C4R
 - image_color_processing, 656
- nppiLUT_Cubic_32f_AC4IR
 - image_color_processing, 656
- nppiLUT_Cubic_32f_AC4R
 - image_color_processing, 657
- nppiLUT_Cubic_32f_C1IR
 - image_color_processing, 657
- nppiLUT_Cubic_32f_C1R
 - image_color_processing, 658
- nppiLUT_Cubic_32f_C3IR
 - image_color_processing, 658
- nppiLUT_Cubic_32f_C3R
 - image_color_processing, 659
- nppiLUT_Cubic_32f_C4IR
 - image_color_processing, 659
- nppiLUT_Cubic_32f_C4R
 - image_color_processing, 660
- nppiLUT_Cubic_8u_AC4IR
 - image_color_processing, 660
- nppiLUT_Cubic_8u_AC4R
 - image_color_processing, 661
- nppiLUT_Cubic_8u_C1IR
 - image_color_processing, 661
- nppiLUT_Cubic_8u_C1R
 - image_color_processing, 662
- nppiLUT_Cubic_8u_C3IR
 - image_color_processing, 662
- nppiLUT_Cubic_8u_C3R
 - image_color_processing, 663
- nppiLUT_Cubic_8u_C4IR
 - image_color_processing, 663
- nppiLUT_Cubic_8u_C4R
 - image_color_processing, 664
- nppiLUT_Linear_16s_AC4IR
 - image_color_processing, 664
- nppiLUT_Linear_16s_AC4R
 - image_color_processing, 665
- nppiLUT_Linear_16s_C1IR
 - image_color_processing, 665
- nppiLUT_Linear_16s_C1R
 - image_color_processing, 666
- nppiLUT_Linear_16s_C3IR
 - image_color_processing, 666
- nppiLUT_Linear_16s_C3R
 - image_color_processing, 667
- nppiLUT_Linear_16s_C4IR
 - image_color_processing, 667
- nppiLUT_Linear_16s_C4R
 - image_color_processing, 668
- nppiLUT_Linear_16u_AC4IR
 - image_color_processing, 668
- nppiLUT_Linear_16u_AC4R
 - image_color_processing, 669
- nppiLUT_Linear_16u_C1IR
 - image_color_processing, 670
- nppiLUT_Linear_16u_C1R
 - image_color_processing, 670
- nppiLUT_Linear_16u_C3IR
 - image_color_processing, 670
- nppiLUT_Linear_16u_C3R
 - image_color_processing, 671
- nppiLUT_Linear_16u_C4IR
 - image_color_processing, 671
- nppiLUT_Linear_16u_C4R
 - image_color_processing, 672
- nppiLUT_Linear_32f_AC4IR
 - image_color_processing, 672
- nppiLUT_Linear_32f_AC4R
 - image_color_processing, 673
- nppiLUT_Linear_32f_C1IR
 - image_color_processing, 673
- nppiLUT_Linear_32f_C1R
 - image_color_processing, 674
- nppiLUT_Linear_32f_C3IR
 - image_color_processing, 674
- nppiLUT_Linear_32f_C3R
 - image_color_processing, 675
- nppiLUT_Linear_32f_C4IR
 - image_color_processing, 675
- nppiLUT_Linear_32f_C4R
 - image_color_processing, 676
- nppiLUT_Linear_8u_AC4IR
 - image_color_processing, 676

- nppiLUT_Linear_8u_AC4R
 - image_color_processing, 677
- nppiLUT_Linear_8u_C1R
 - image_color_processing, 678
- nppiLUT_Linear_8u_C1R
 - image_color_processing, 678
- nppiLUT_Linear_8u_C3R
 - image_color_processing, 679
- nppiLUT_Linear_8u_C3R
 - image_color_processing, 679
- nppiLUT_Linear_8u_C4R
 - image_color_processing, 680
- nppiLUT_Linear_8u_C4R
 - image_color_processing, 680
- nppiLUTPalette_16u24u_C1R
 - image_color_processing, 681
- nppiLUTPalette_16u32u_C1R
 - image_color_processing, 681
- nppiLUTPalette_16u8u_C1R
 - image_color_processing, 682
- nppiLUTPalette_16u_AC4R
 - image_color_processing, 682
- nppiLUTPalette_16u_C1R
 - image_color_processing, 683
- nppiLUTPalette_16u_C3R
 - image_color_processing, 683
- nppiLUTPalette_16u_C4R
 - image_color_processing, 684
- nppiLUTPalette_8u24u_C1R
 - image_color_processing, 684
- nppiLUTPalette_8u32u_C1R
 - image_color_processing, 685
- nppiLUTPalette_8u_AC4R
 - image_color_processing, 685
- nppiLUTPalette_8u_C1R
 - image_color_processing, 686
- nppiLUTPalette_8u_C3R
 - image_color_processing, 686
- nppiLUTPalette_8u_C4R
 - image_color_processing, 687
- nppiLUTPaletteSwap_16u_C3A0C4R
 - image_color_processing, 687
- nppiLUTPaletteSwap_8u_C3A0C4R
 - image_color_processing, 688
- nppiLUVToRGB_8u_AC4R
 - image_color_model_conversion, 541
- nppiLUVToRGB_8u_C3R
 - image_color_model_conversion, 542
- nppiMagnitude_32fc32f_C1R
 - image_fourier_transforms, 1270
- nppiMagnitudeSqr_32fc32f_C1R
 - image_fourier_transforms, 1270
- nppiMalloc_16s_C1
 - image_memory_management, 1867
- nppiMalloc_16s_C2
 - image_memory_management, 1867
- nppiMalloc_16s_C4
 - image_memory_management, 1868
- nppiMalloc_16sc_C1
 - image_memory_management, 1868
- nppiMalloc_16sc_C2
 - image_memory_management, 1868
- nppiMalloc_16sc_C3
 - image_memory_management, 1869
- nppiMalloc_16sc_C4
 - image_memory_management, 1869
- nppiMalloc_16u_C1
 - image_memory_management, 1869
- nppiMalloc_16u_C2
 - image_memory_management, 1869
- nppiMalloc_16u_C3
 - image_memory_management, 1870
- nppiMalloc_16u_C4
 - image_memory_management, 1870
- nppiMalloc_32f_C1
 - image_memory_management, 1870
- nppiMalloc_32f_C2
 - image_memory_management, 1871
- nppiMalloc_32f_C3
 - image_memory_management, 1871
- nppiMalloc_32f_C4
 - image_memory_management, 1871
- nppiMalloc_32fc_C1
 - image_memory_management, 1871
- nppiMalloc_32fc_C2
 - image_memory_management, 1872
- nppiMalloc_32fc_C3
 - image_memory_management, 1872
- nppiMalloc_32fc_C4
 - image_memory_management, 1872
- nppiMalloc_32s_C1
 - image_memory_management, 1873
- nppiMalloc_32s_C3
 - image_memory_management, 1873
- nppiMalloc_32s_C4
 - image_memory_management, 1873
- nppiMalloc_32sc_C1
 - image_memory_management, 1873
- nppiMalloc_32sc_C2
 - image_memory_management, 1874
- nppiMalloc_32sc_C3
 - image_memory_management, 1874
- nppiMalloc_32sc_C4
 - image_memory_management, 1874
- nppiMalloc_8u_C1
 - image_memory_management, 1875
- nppiMalloc_8u_C2
 - image_memory_management, 1875

- nppiMalloc_8u_C3
 - image_memory_management, 1875
- nppiMalloc_8u_C4
 - image_memory_management, 1875
- NppiMaskSize
 - typedefs_npp, 42
- nppiMax_16s_AC4R
 - image_max, 1345
- nppiMax_16s_C1R
 - image_max, 1345
- nppiMax_16s_C3R
 - image_max, 1346
- nppiMax_16s_C4R
 - image_max, 1346
- nppiMax_16u_AC4R
 - image_max, 1346
- nppiMax_16u_C1R
 - image_max, 1347
- nppiMax_16u_C3R
 - image_max, 1347
- nppiMax_16u_C4R
 - image_max, 1348
- nppiMax_32f_AC4R
 - image_max, 1348
- nppiMax_32f_C1R
 - image_max, 1348
- nppiMax_32f_C3R
 - image_max, 1349
- nppiMax_32f_C4R
 - image_max, 1349
- nppiMax_8u_AC4R
 - image_max, 1349
- nppiMax_8u_C1R
 - image_max, 1350
- nppiMax_8u_C3R
 - image_max, 1350
- nppiMax_8u_C4R
 - image_max, 1351
- nppiMaxEvery_16s_AC4IR
 - image_maxevery, 1674
- nppiMaxEvery_16s_C1IR
 - image_maxevery, 1674
- nppiMaxEvery_16s_C3IR
 - image_maxevery, 1675
- nppiMaxEvery_16s_C4IR
 - image_maxevery, 1675
- nppiMaxEvery_16u_AC4IR
 - image_maxevery, 1675
- nppiMaxEvery_16u_C1IR
 - image_maxevery, 1676
- nppiMaxEvery_16u_C3IR
 - image_maxevery, 1676
- nppiMaxEvery_16u_C4IR
 - image_maxevery, 1676
- nppiMaxEvery_32f_AC4IR
 - image_maxevery, 1677
- nppiMaxEvery_32f_C1IR
 - image_maxevery, 1677
- nppiMaxEvery_32f_C3IR
 - image_maxevery, 1677
- nppiMaxEvery_32f_C4IR
 - image_maxevery, 1678
- nppiMaxEvery_8u_AC4IR
 - image_maxevery, 1678
- nppiMaxEvery_8u_C1IR
 - image_maxevery, 1678
- nppiMaxEvery_8u_C3IR
 - image_maxevery, 1679
- nppiMaxEvery_8u_C4IR
 - image_maxevery, 1679
- nppiMaxGetBufferHostSize_16s_AC4R
 - image_max, 1351
- nppiMaxGetBufferHostSize_16s_C1R
 - image_max, 1351
- nppiMaxGetBufferHostSize_16s_C3R
 - image_max, 1351
- nppiMaxGetBufferHostSize_16s_C4R
 - image_max, 1352
- nppiMaxGetBufferHostSize_16u_AC4R
 - image_max, 1352
- nppiMaxGetBufferHostSize_16u_C1R
 - image_max, 1352
- nppiMaxGetBufferHostSize_16u_C3R
 - image_max, 1353
- nppiMaxGetBufferHostSize_16u_C4R
 - image_max, 1353
- nppiMaxGetBufferHostSize_32f_AC4R
 - image_max, 1353
- nppiMaxGetBufferHostSize_32f_C1R
 - image_max, 1353
- nppiMaxGetBufferHostSize_32f_C3R
 - image_max, 1354
- nppiMaxGetBufferHostSize_32f_C4R
 - image_max, 1354
- nppiMaxGetBufferHostSize_8u_AC4R
 - image_max, 1354
- nppiMaxGetBufferHostSize_8u_C1R
 - image_max, 1355
- nppiMaxGetBufferHostSize_8u_C3R
 - image_max, 1355
- nppiMaxGetBufferHostSize_8u_C4R
 - image_max, 1355
- nppiMaxIdx_16s_AC4R
 - image_max_index, 1358
- nppiMaxIdx_16s_C1R
 - image_max_index, 1359
- nppiMaxIdx_16s_C3R
 - image_max_index, 1359

- nppiMaxIndx_16s_C4R
 image_max_index, 1359
- nppiMaxIndx_16u_AC4R
 image_max_index, 1360
- nppiMaxIndx_16u_C1R
 image_max_index, 1360
- nppiMaxIndx_16u_C3R
 image_max_index, 1361
- nppiMaxIndx_16u_C4R
 image_max_index, 1361
- nppiMaxIndx_32f_AC4R
 image_max_index, 1361
- nppiMaxIndx_32f_C1R
 image_max_index, 1362
- nppiMaxIndx_32f_C3R
 image_max_index, 1362
- nppiMaxIndx_32f_C4R
 image_max_index, 1363
- nppiMaxIndx_8u_AC4R
 image_max_index, 1363
- nppiMaxIndx_8u_C1R
 image_max_index, 1363
- nppiMaxIndx_8u_C3R
 image_max_index, 1364
- nppiMaxIndx_8u_C4R
 image_max_index, 1364
- nppiMaxIndxGetBufferHostSize_16s_AC4R
 image_max_index, 1365
- nppiMaxIndxGetBufferHostSize_16s_C1R
 image_max_index, 1365
- nppiMaxIndxGetBufferHostSize_16s_C3R
 image_max_index, 1365
- nppiMaxIndxGetBufferHostSize_16s_C4R
 image_max_index, 1366
- nppiMaxIndxGetBufferHostSize_16u_AC4R
 image_max_index, 1366
- nppiMaxIndxGetBufferHostSize_16u_C1R
 image_max_index, 1366
- nppiMaxIndxGetBufferHostSize_16u_C3R
 image_max_index, 1366
- nppiMaxIndxGetBufferHostSize_16u_C4R
 image_max_index, 1367
- nppiMaxIndxGetBufferHostSize_32f_AC4R
 image_max_index, 1367
- nppiMaxIndxGetBufferHostSize_32f_C1R
 image_max_index, 1367
- nppiMaxIndxGetBufferHostSize_32f_C3R
 image_max_index, 1368
- nppiMaxIndxGetBufferHostSize_32f_C4R
 image_max_index, 1368
- nppiMaxIndxGetBufferHostSize_8u_AC4R
 image_max_index, 1368
- nppiMaxIndxGetBufferHostSize_8u_C1R
 image_max_index, 1368
- nppiMaxIndxGetBufferHostSize_8u_C3R
 image_max_index, 1369
- nppiMaxIndxGetBufferHostSize_8u_C4R
 image_max_index, 1369
- nppiMean_16s_AC4R
 image_mean, 1405
- nppiMean_16s_C1R
 image_mean, 1405
- nppiMean_16s_C3R
 image_mean, 1405
- nppiMean_16s_C4R
 image_mean, 1406
- nppiMean_16u_AC4R
 image_mean, 1406
- nppiMean_16u_C1MR
 image_mean, 1406
- nppiMean_16u_C1R
 image_mean, 1407
- nppiMean_16u_C3CMR
 image_mean, 1407
- nppiMean_16u_C3R
 image_mean, 1407
- nppiMean_16u_C4R
 image_mean, 1408
- nppiMean_32f_AC4R
 image_mean, 1408
- nppiMean_32f_C1MR
 image_mean, 1409
- nppiMean_32f_C1R
 image_mean, 1409
- nppiMean_32f_C3CMR
 image_mean, 1409
- nppiMean_32f_C3R
 image_mean, 1410
- nppiMean_32f_C4R
 image_mean, 1410
- nppiMean_8s_C1MR
 image_mean, 1411
- nppiMean_8s_C3CMR
 image_mean, 1411
- nppiMean_8u_AC4R
 image_mean, 1412
- nppiMean_8u_C1MR
 image_mean, 1412
- nppiMean_8u_C1R
 image_mean, 1412
- nppiMean_8u_C3CMR
 image_mean, 1413
- nppiMean_8u_C3R
 image_mean, 1413
- nppiMean_8u_C4R
 image_mean, 1414
- nppiMean_StdDev_16u_C1MR
 image_mean_stddev, 1425

- nppiMean_StdDev_16u_C1R
image_mean_stddev, 1425
- nppiMean_StdDev_16u_C3CMR
image_mean_stddev, 1426
- nppiMean_StdDev_16u_C3CR
image_mean_stddev, 1426
- nppiMean_StdDev_32f_C1MR
image_mean_stddev, 1427
- nppiMean_StdDev_32f_C1R
image_mean_stddev, 1427
- nppiMean_StdDev_32f_C3CMR
image_mean_stddev, 1428
- nppiMean_StdDev_32f_C3CR
image_mean_stddev, 1428
- nppiMean_StdDev_8s_C1MR
image_mean_stddev, 1429
- nppiMean_StdDev_8s_C1R
image_mean_stddev, 1429
- nppiMean_StdDev_8s_C3CMR
image_mean_stddev, 1430
- nppiMean_StdDev_8s_C3CR
image_mean_stddev, 1430
- nppiMean_StdDev_8u_C1MR
image_mean_stddev, 1431
- nppiMean_StdDev_8u_C1R
image_mean_stddev, 1431
- nppiMean_StdDev_8u_C3CMR
image_mean_stddev, 1432
- nppiMean_StdDev_8u_C3CR
image_mean_stddev, 1432
- nppiMeanGetBufferHostSize_16s_AC4R
image_mean, 1414
- nppiMeanGetBufferHostSize_16s_C1R
image_mean, 1414
- nppiMeanGetBufferHostSize_16s_C3R
image_mean, 1415
- nppiMeanGetBufferHostSize_16s_C4R
image_mean, 1415
- nppiMeanGetBufferHostSize_16u_AC4R
image_mean, 1415
- nppiMeanGetBufferHostSize_16u_C1MR
image_mean, 1415
- nppiMeanGetBufferHostSize_16u_C1R
image_mean, 1416
- nppiMeanGetBufferHostSize_16u_C3CMR
image_mean, 1416
- nppiMeanGetBufferHostSize_16u_C3R
image_mean, 1416
- nppiMeanGetBufferHostSize_16u_C4R
image_mean, 1417
- nppiMeanGetBufferHostSize_32f_AC4R
image_mean, 1417
- nppiMeanGetBufferHostSize_32f_C1MR
image_mean, 1417
- nppiMeanGetBufferHostSize_32f_C1R
image_mean, 1417
- nppiMeanGetBufferHostSize_32f_C3CMR
image_mean, 1418
- nppiMeanGetBufferHostSize_32f_C3R
image_mean, 1418
- nppiMeanGetBufferHostSize_32f_C4R
image_mean, 1418
- nppiMeanGetBufferHostSize_8s_C1MR
image_mean, 1419
- nppiMeanGetBufferHostSize_8s_C3CMR
image_mean, 1419
- nppiMeanGetBufferHostSize_8u_AC4R
image_mean, 1419
- nppiMeanGetBufferHostSize_8u_C1MR
image_mean, 1419
- nppiMeanGetBufferHostSize_8u_C1R
image_mean, 1420
- nppiMeanGetBufferHostSize_8u_C3CMR
image_mean, 1420
- nppiMeanGetBufferHostSize_8u_C3R
image_mean, 1420
- nppiMeanGetBufferHostSize_8u_C4R
image_mean, 1421
- nppiMeanStdDevGetBufferHostSize_16u_C1MR
image_mean_stddev, 1433
- nppiMeanStdDevGetBufferHostSize_16u_C1R
image_mean_stddev, 1433
- nppiMeanStdDevGetBufferHostSize_16u_C3CMR
image_mean_stddev, 1433
- nppiMeanStdDevGetBufferHostSize_16u_C3CR
image_mean_stddev, 1434
- nppiMeanStdDevGetBufferHostSize_32f_C1MR
image_mean_stddev, 1434
- nppiMeanStdDevGetBufferHostSize_32f_C1R
image_mean_stddev, 1434
- nppiMeanStdDevGetBufferHostSize_32f_C3CMR
image_mean_stddev, 1435
- nppiMeanStdDevGetBufferHostSize_32f_C3CR
image_mean_stddev, 1435
- nppiMeanStdDevGetBufferHostSize_8s_C1MR
image_mean_stddev, 1435
- nppiMeanStdDevGetBufferHostSize_8s_C1R
image_mean_stddev, 1435
- nppiMeanStdDevGetBufferHostSize_8s_C3CMR
image_mean_stddev, 1436
- nppiMeanStdDevGetBufferHostSize_8s_C3CR
image_mean_stddev, 1436
- nppiMeanStdDevGetBufferHostSize_8u_C1MR
image_mean_stddev, 1436
- nppiMeanStdDevGetBufferHostSize_8u_C1R
image_mean_stddev, 1437
- nppiMeanStdDevGetBufferHostSize_8u_C3CMR
image_mean_stddev, 1437

- nppiMeanStdDevGetBufferHostSize_8u_C3CR
 image_mean_stddev, 1437
 nppiMin_16s_AC4R
 image_min, 1318
 nppiMin_16s_C1R
 image_min, 1318
 nppiMin_16s_C3R
 image_min, 1319
 nppiMin_16s_C4R
 image_min, 1319
 nppiMin_16u_AC4R
 image_min, 1319
 nppiMin_16u_C1R
 image_min, 1320
 nppiMin_16u_C3R
 image_min, 1320
 nppiMin_16u_C4R
 image_min, 1321
 nppiMin_32f_AC4R
 image_min, 1321
 nppiMin_32f_C1R
 image_min, 1321
 nppiMin_32f_C3R
 image_min, 1322
 nppiMin_32f_C4R
 image_min, 1322
 nppiMin_8u_AC4R
 image_min, 1322
 nppiMin_8u_C1R
 image_min, 1323
 nppiMin_8u_C3R
 image_min, 1323
 nppiMin_8u_C4R
 image_min, 1324
 nppiMinEvery_16s_AC4IR
 image_minevery, 1681
 nppiMinEvery_16s_C1IR
 image_minevery, 1681
 nppiMinEvery_16s_C3IR
 image_minevery, 1682
 nppiMinEvery_16s_C4IR
 image_minevery, 1682
 nppiMinEvery_16u_AC4IR
 image_minevery, 1682
 nppiMinEvery_16u_C1IR
 image_minevery, 1683
 nppiMinEvery_16u_C3IR
 image_minevery, 1683
 nppiMinEvery_16u_C4IR
 image_minevery, 1683
 nppiMinEvery_32f_AC4IR
 image_minevery, 1684
 nppiMinEvery_32f_C1IR
 image_minevery, 1684
 nppiMinEvery_32f_C3IR
 image_minevery, 1684
 nppiMinEvery_32f_C4IR
 image_minevery, 1685
 nppiMinEvery_8u_AC4IR
 image_minevery, 1685
 nppiMinEvery_8u_C1IR
 image_minevery, 1685
 nppiMinEvery_8u_C3IR
 image_minevery, 1686
 nppiMinEvery_8u_C4IR
 image_minevery, 1686
 nppiMinGetBufferHostSize_16s_AC4R
 image_min, 1324
 nppiMinGetBufferHostSize_16s_C1R
 image_min, 1324
 nppiMinGetBufferHostSize_16s_C3R
 image_min, 1324
 nppiMinGetBufferHostSize_16s_C4R
 image_min, 1325
 nppiMinGetBufferHostSize_16u_AC4R
 image_min, 1325
 nppiMinGetBufferHostSize_16u_C1R
 image_min, 1325
 nppiMinGetBufferHostSize_16u_C3R
 image_min, 1326
 nppiMinGetBufferHostSize_16u_C4R
 image_min, 1326
 nppiMinGetBufferHostSize_32f_AC4R
 image_min, 1326
 nppiMinGetBufferHostSize_32f_C1R
 image_min, 1326
 nppiMinGetBufferHostSize_32f_C3R
 image_min, 1327
 nppiMinGetBufferHostSize_32f_C4R
 image_min, 1327
 nppiMinGetBufferHostSize_8u_AC4R
 image_min, 1327
 nppiMinGetBufferHostSize_8u_C1R
 image_min, 1328
 nppiMinGetBufferHostSize_8u_C3R
 image_min, 1328
 nppiMinGetBufferHostSize_8u_C4R
 image_min, 1328
 nppiMinIndx_16s_AC4R
 image_min_index, 1331
 nppiMinIndx_16s_C1R
 image_min_index, 1332
 nppiMinIndx_16s_C3R
 image_min_index, 1332
 nppiMinIndx_16s_C4R
 image_min_index, 1332
 nppiMinIndx_16u_AC4R
 image_min_index, 1333

- [nppiMinIndx_16u_C1R](#)
 [image_min_index](#), [1333](#)
- [nppiMinIndx_16u_C3R](#)
 [image_min_index](#), [1334](#)
- [nppiMinIndx_16u_C4R](#)
 [image_min_index](#), [1334](#)
- [nppiMinIndx_32f_AC4R](#)
 [image_min_index](#), [1334](#)
- [nppiMinIndx_32f_C1R](#)
 [image_min_index](#), [1335](#)
- [nppiMinIndx_32f_C3R](#)
 [image_min_index](#), [1335](#)
- [nppiMinIndx_32f_C4R](#)
 [image_min_index](#), [1336](#)
- [nppiMinIndx_8u_AC4R](#)
 [image_min_index](#), [1336](#)
- [nppiMinIndx_8u_C1R](#)
 [image_min_index](#), [1336](#)
- [nppiMinIndx_8u_C3R](#)
 [image_min_index](#), [1337](#)
- [nppiMinIndx_8u_C4R](#)
 [image_min_index](#), [1337](#)
- [nppiMinIndxGetBufferHostSize_16s_AC4R](#)
 [image_min_index](#), [1338](#)
- [nppiMinIndxGetBufferHostSize_16s_C1R](#)
 [image_min_index](#), [1338](#)
- [nppiMinIndxGetBufferHostSize_16s_C3R](#)
 [image_min_index](#), [1338](#)
- [nppiMinIndxGetBufferHostSize_16s_C4R](#)
 [image_min_index](#), [1339](#)
- [nppiMinIndxGetBufferHostSize_16u_AC4R](#)
 [image_min_index](#), [1339](#)
- [nppiMinIndxGetBufferHostSize_16u_C1R](#)
 [image_min_index](#), [1339](#)
- [nppiMinIndxGetBufferHostSize_16u_C3R](#)
 [image_min_index](#), [1339](#)
- [nppiMinIndxGetBufferHostSize_16u_C4R](#)
 [image_min_index](#), [1340](#)
- [nppiMinIndxGetBufferHostSize_32f_AC4R](#)
 [image_min_index](#), [1340](#)
- [nppiMinIndxGetBufferHostSize_32f_C1R](#)
 [image_min_index](#), [1340](#)
- [nppiMinIndxGetBufferHostSize_32f_C3R](#)
 [image_min_index](#), [1341](#)
- [nppiMinIndxGetBufferHostSize_32f_C4R](#)
 [image_min_index](#), [1341](#)
- [nppiMinIndxGetBufferHostSize_8u_AC4R](#)
 [image_min_index](#), [1341](#)
- [nppiMinIndxGetBufferHostSize_8u_C1R](#)
 [image_min_index](#), [1341](#)
- [nppiMinIndxGetBufferHostSize_8u_C3R](#)
 [image_min_index](#), [1342](#)
- [nppiMinIndxGetBufferHostSize_8u_C4R](#)
 [image_min_index](#), [1342](#)
- [nppiMinMax_16s_AC4R](#)
 [image_min_max](#), [1372](#)
- [nppiMinMax_16s_C1R](#)
 [image_min_max](#), [1372](#)
- [nppiMinMax_16s_C3R](#)
 [image_min_max](#), [1373](#)
- [nppiMinMax_16s_C4R](#)
 [image_min_max](#), [1373](#)
- [nppiMinMax_16u_AC4R](#)
 [image_min_max](#), [1374](#)
- [nppiMinMax_16u_C1R](#)
 [image_min_max](#), [1374](#)
- [nppiMinMax_16u_C3R](#)
 [image_min_max](#), [1374](#)
- [nppiMinMax_16u_C4R](#)
 [image_min_max](#), [1375](#)
- [nppiMinMax_32f_AC4R](#)
 [image_min_max](#), [1375](#)
- [nppiMinMax_32f_C1R](#)
 [image_min_max](#), [1376](#)
- [nppiMinMax_32f_C3R](#)
 [image_min_max](#), [1376](#)
- [nppiMinMax_32f_C4R](#)
 [image_min_max](#), [1376](#)
- [nppiMinMax_8u_AC4R](#)
 [image_min_max](#), [1377](#)
- [nppiMinMax_8u_C1R](#)
 [image_min_max](#), [1377](#)
- [nppiMinMax_8u_C3R](#)
 [image_min_max](#), [1378](#)
- [nppiMinMax_8u_C4R](#)
 [image_min_max](#), [1378](#)
- [nppiMinMaxGetBufferHostSize_16s_AC4R](#)
 [image_min_max](#), [1378](#)
- [nppiMinMaxGetBufferHostSize_16s_C1R](#)
 [image_min_max](#), [1379](#)
- [nppiMinMaxGetBufferHostSize_16s_C3R](#)
 [image_min_max](#), [1379](#)
- [nppiMinMaxGetBufferHostSize_16s_C4R](#)
 [image_min_max](#), [1379](#)
- [nppiMinMaxGetBufferHostSize_16u_AC4R](#)
 [image_min_max](#), [1380](#)
- [nppiMinMaxGetBufferHostSize_16u_C1R](#)
 [image_min_max](#), [1380](#)
- [nppiMinMaxGetBufferHostSize_16u_C3R](#)
 [image_min_max](#), [1380](#)
- [nppiMinMaxGetBufferHostSize_16u_C4R](#)
 [image_min_max](#), [1380](#)
- [nppiMinMaxGetBufferHostSize_32f_AC4R](#)
 [image_min_max](#), [1381](#)
- [nppiMinMaxGetBufferHostSize_32f_C1R](#)
 [image_min_max](#), [1381](#)
- [nppiMinMaxGetBufferHostSize_32f_C3R](#)
 [image_min_max](#), [1381](#)

- nppiMinMaxGetBufferHostSize_32f_C4R
 image_min_max, 1382
- nppiMinMaxGetBufferHostSize_8u_AC4R
 image_min_max, 1382
- nppiMinMaxGetBufferHostSize_8u_C1R
 image_min_max, 1382
- nppiMinMaxGetBufferHostSize_8u_C3R
 image_min_max, 1382
- nppiMinMaxGetBufferHostSize_8u_C4R
 image_min_max, 1383
- nppiMinMaxIndx_16u_C1MR
 image_min_max_index, 1387
- nppiMinMaxIndx_16u_C1R
 image_min_max_index, 1388
- nppiMinMaxIndx_16u_C3CMR
 image_min_max_index, 1388
- nppiMinMaxIndx_16u_C3CR
 image_min_max_index, 1389
- nppiMinMaxIndx_32f_C1MR
 image_min_max_index, 1389
- nppiMinMaxIndx_32f_C1R
 image_min_max_index, 1390
- nppiMinMaxIndx_32f_C3CMR
 image_min_max_index, 1390
- nppiMinMaxIndx_32f_C3CR
 image_min_max_index, 1391
- nppiMinMaxIndx_8s_C1MR
 image_min_max_index, 1392
- nppiMinMaxIndx_8s_C1R
 image_min_max_index, 1392
- nppiMinMaxIndx_8s_C3CMR
 image_min_max_index, 1393
- nppiMinMaxIndx_8s_C3CR
 image_min_max_index, 1393
- nppiMinMaxIndx_8u_C1MR
 image_min_max_index, 1394
- nppiMinMaxIndx_8u_C1R
 image_min_max_index, 1394
- nppiMinMaxIndx_8u_C3CMR
 image_min_max_index, 1395
- nppiMinMaxIndx_8u_C3CR
 image_min_max_index, 1395
- nppiMinMaxIndxGetBufferHostSize_16u_C1MR
 image_min_max_index, 1396
- nppiMinMaxIndxGetBufferHostSize_16u_C1R
 image_min_max_index, 1396
- nppiMinMaxIndxGetBufferHostSize_16u_C3CMR
 image_min_max_index, 1396
- nppiMinMaxIndxGetBufferHostSize_16u_C3CR
 image_min_max_index, 1397
- nppiMinMaxIndxGetBufferHostSize_32f_C1MR
 image_min_max_index, 1397
- nppiMinMaxIndxGetBufferHostSize_32f_C1R
 image_min_max_index, 1397
- nppiMinMaxIndxGetBufferHostSize_32f_C3CMR
 image_min_max_index, 1398
- nppiMinMaxIndxGetBufferHostSize_32f_C3CR
 image_min_max_index, 1398
- nppiMinMaxIndxGetBufferHostSize_8s_C1MR
 image_min_max_index, 1398
- nppiMinMaxIndxGetBufferHostSize_8s_C1R
 image_min_max_index, 1398
- nppiMinMaxIndxGetBufferHostSize_8s_C3CMR
 image_min_max_index, 1399
- nppiMinMaxIndxGetBufferHostSize_8s_C3CR
 image_min_max_index, 1399
- nppiMinMaxIndxGetBufferHostSize_8u_C1MR
 image_min_max_index, 1399
- nppiMinMaxIndxGetBufferHostSize_8u_C1R
 image_min_max_index, 1400
- nppiMinMaxIndxGetBufferHostSize_8u_C3CMR
 image_min_max_index, 1400
- nppiMinMaxIndxGetBufferHostSize_8u_C3CR
 image_min_max_index, 1400
- nppiMirror_16s_AC4IR
 image_mirror, 1159
- nppiMirror_16s_AC4R
 image_mirror, 1159
- nppiMirror_16s_C1IR
 image_mirror, 1160
- nppiMirror_16s_C1R
 image_mirror, 1160
- nppiMirror_16s_C3IR
 image_mirror, 1160
- nppiMirror_16s_C3R
 image_mirror, 1161
- nppiMirror_16s_C4IR
 image_mirror, 1161
- nppiMirror_16s_C4R
 image_mirror, 1161
- nppiMirror_16u_AC4IR
 image_mirror, 1162
- nppiMirror_16u_AC4R
 image_mirror, 1162
- nppiMirror_16u_C1IR
 image_mirror, 1162
- nppiMirror_16u_C1R
 image_mirror, 1163
- nppiMirror_16u_C3IR
 image_mirror, 1163
- nppiMirror_16u_C3R
 image_mirror, 1163
- nppiMirror_16u_C4IR
 image_mirror, 1164
- nppiMirror_16u_C4R
 image_mirror, 1164
- nppiMirror_32f_AC4IR
 image_mirror, 1164

- nppiMirror_32f_AC4R
 - image_mirror, 1165
- nppiMirror_32f_C1IR
 - image_mirror, 1165
- nppiMirror_32f_C1R
 - image_mirror, 1165
- nppiMirror_32f_C3IR
 - image_mirror, 1166
- nppiMirror_32f_C3R
 - image_mirror, 1166
- nppiMirror_32f_C4IR
 - image_mirror, 1166
- nppiMirror_32f_C4R
 - image_mirror, 1167
- nppiMirror_32s_AC4IR
 - image_mirror, 1167
- nppiMirror_32s_AC4R
 - image_mirror, 1167
- nppiMirror_32s_C1IR
 - image_mirror, 1168
- nppiMirror_32s_C1R
 - image_mirror, 1168
- nppiMirror_32s_C3IR
 - image_mirror, 1168
- nppiMirror_32s_C3R
 - image_mirror, 1169
- nppiMirror_32s_C4IR
 - image_mirror, 1169
- nppiMirror_32s_C4R
 - image_mirror, 1169
- nppiMirror_8u_AC4IR
 - image_mirror, 1170
- nppiMirror_8u_AC4R
 - image_mirror, 1170
- nppiMirror_8u_C1IR
 - image_mirror, 1170
- nppiMirror_8u_C1R
 - image_mirror, 1171
- nppiMirror_8u_C3IR
 - image_mirror, 1171
- nppiMirror_8u_C3R
 - image_mirror, 1171
- nppiMirror_8u_C4IR
 - image_mirror, 1172
- nppiMirror_8u_C4R
 - image_mirror, 1172
- nppiMul_16s_AC4IRSfs
 - image_mul, 213
- nppiMul_16s_AC4RSfs
 - image_mul, 213
- nppiMul_16s_C1IRSfs
 - image_mul, 214
- nppiMul_16s_C1RSfs
 - image_mul, 214
- nppiMul_16s_C3IRSfs
 - image_mul, 215
- nppiMul_16s_C3RSfs
 - image_mul, 215
- nppiMul_16s_C4IRSfs
 - image_mul, 215
- nppiMul_16s_C4RSfs
 - image_mul, 216
- nppiMul_16sc_AC4IRSfs
 - image_mul, 216
- nppiMul_16sc_AC4RSfs
 - image_mul, 217
- nppiMul_16sc_C1IRSfs
 - image_mul, 217
- nppiMul_16sc_C1RSfs
 - image_mul, 217
- nppiMul_16sc_C3IRSfs
 - image_mul, 218
- nppiMul_16sc_C3RSfs
 - image_mul, 218
- nppiMul_16u_AC4IRSfs
 - image_mul, 219
- nppiMul_16u_AC4RSfs
 - image_mul, 219
- nppiMul_16u_C1IRSfs
 - image_mul, 220
- nppiMul_16u_C1RSfs
 - image_mul, 220
- nppiMul_16u_C3IRSfs
 - image_mul, 220
- nppiMul_16u_C3RSfs
 - image_mul, 221
- nppiMul_16u_C4IRSfs
 - image_mul, 221
- nppiMul_16u_C4RSfs
 - image_mul, 222
- nppiMul_32f_AC4IR
 - image_mul, 222
- nppiMul_32f_AC4R
 - image_mul, 222
- nppiMul_32f_C1IR
 - image_mul, 223
- nppiMul_32f_C1R
 - image_mul, 223
- nppiMul_32f_C3IR
 - image_mul, 224
- nppiMul_32f_C3R
 - image_mul, 224
- nppiMul_32f_C4IR
 - image_mul, 224
- nppiMul_32f_C4R
 - image_mul, 225
- nppiMul_32fc_AC4IR
 - image_mul, 225

- nppiMul_32fc_AC4R
image_mul, 225
- nppiMul_32fc_C1IR
image_mul, 226
- nppiMul_32fc_C1R
image_mul, 226
- nppiMul_32fc_C3IR
image_mul, 227
- nppiMul_32fc_C3R
image_mul, 227
- nppiMul_32fc_C4IR
image_mul, 227
- nppiMul_32fc_C4R
image_mul, 228
- nppiMul_32s_C1IRSfs
image_mul, 228
- nppiMul_32s_C1R
image_mul, 229
- nppiMul_32s_C1RSfs
image_mul, 229
- nppiMul_32s_C3IRSfs
image_mul, 229
- nppiMul_32s_C3RSfs
image_mul, 230
- nppiMul_32sc_AC4IRSfs
image_mul, 230
- nppiMul_32sc_AC4RSfs
image_mul, 231
- nppiMul_32sc_C1IRSfs
image_mul, 231
- nppiMul_32sc_C1RSfs
image_mul, 231
- nppiMul_32sc_C3IRSfs
image_mul, 232
- nppiMul_32sc_C3RSfs
image_mul, 232
- nppiMul_8u_AC4IRSfs
image_mul, 233
- nppiMul_8u_AC4RSfs
image_mul, 233
- nppiMul_8u_C1IRSfs
image_mul, 234
- nppiMul_8u_C1RSfs
image_mul, 234
- nppiMul_8u_C3IRSfs
image_mul, 234
- nppiMul_8u_C3RSfs
image_mul, 235
- nppiMul_8u_C4IRSfs
image_mul, 235
- nppiMul_8u_C4RSfs
image_mul, 236
- nppiMulC_16s_AC4IRSfs
image_mulc, 86
- nppiMulC_16s_AC4RSfs
image_mulc, 86
- nppiMulC_16s_C1IRSfs
image_mulc, 86
- nppiMulC_16s_C1RSfs
image_mulc, 87
- nppiMulC_16s_C3IRSfs
image_mulc, 87
- nppiMulC_16s_C3RSfs
image_mulc, 87
- nppiMulC_16s_C4IRSfs
image_mulc, 88
- nppiMulC_16s_C4RSfs
image_mulc, 88
- nppiMulC_16sc_AC4IRSfs
image_mulc, 89
- nppiMulC_16sc_AC4RSfs
image_mulc, 89
- nppiMulC_16sc_C1IRSfs
image_mulc, 89
- nppiMulC_16sc_C1RSfs
image_mulc, 90
- nppiMulC_16sc_C3IRSfs
image_mulc, 90
- nppiMulC_16sc_C3RSfs
image_mulc, 91
- nppiMulC_16u_AC4IRSfs
image_mulc, 91
- nppiMulC_16u_AC4RSfs
image_mulc, 91
- nppiMulC_16u_C1IRSfs
image_mulc, 92
- nppiMulC_16u_C1RSfs
image_mulc, 92
- nppiMulC_16u_C3IRSfs
image_mulc, 93
- nppiMulC_16u_C3RSfs
image_mulc, 93
- nppiMulC_16u_C4IRSfs
image_mulc, 93
- nppiMulC_16u_C4RSfs
image_mulc, 94
- nppiMulC_32f_AC4IR
image_mulc, 94
- nppiMulC_32f_AC4R
image_mulc, 94
- nppiMulC_32f_C1IR
image_mulc, 95
- nppiMulC_32f_C1R
image_mulc, 95
- nppiMulC_32f_C3IR
image_mulc, 95
- nppiMulC_32f_C3R
image_mulc, 96

- nppiMulC_32f_C4IR
 - image_mulc, 96
- nppiMulC_32f_C4R
 - image_mulc, 96
- nppiMulC_32fc_AC4IR
 - image_mulc, 97
- nppiMulC_32fc_AC4R
 - image_mulc, 97
- nppiMulC_32fc_C1IR
 - image_mulc, 97
- nppiMulC_32fc_C1R
 - image_mulc, 98
- nppiMulC_32fc_C3IR
 - image_mulc, 98
- nppiMulC_32fc_C3R
 - image_mulc, 98
- nppiMulC_32fc_C4IR
 - image_mulc, 99
- nppiMulC_32fc_C4R
 - image_mulc, 99
- nppiMulC_32s_C1IRSfs
 - image_mulc, 100
- nppiMulC_32s_C1RSfs
 - image_mulc, 100
- nppiMulC_32s_C3IRSfs
 - image_mulc, 100
- nppiMulC_32s_C3RSfs
 - image_mulc, 101
- nppiMulC_32sc_AC4IRSfs
 - image_mulc, 101
- nppiMulC_32sc_AC4RSfs
 - image_mulc, 101
- nppiMulC_32sc_C1IRSfs
 - image_mulc, 102
- nppiMulC_32sc_C1RSfs
 - image_mulc, 102
- nppiMulC_32sc_C3IRSfs
 - image_mulc, 103
- nppiMulC_32sc_C3RSfs
 - image_mulc, 103
- nppiMulC_8u_AC4IRSfs
 - image_mulc, 103
- nppiMulC_8u_AC4RSfs
 - image_mulc, 104
- nppiMulC_8u_C1IRSfs
 - image_mulc, 104
- nppiMulC_8u_C1RSfs
 - image_mulc, 105
- nppiMulC_8u_C3IRSfs
 - image_mulc, 105
- nppiMulC_8u_C3RSfs
 - image_mulc, 105
- nppiMulC_8u_C4IRSfs
 - image_mulc, 106
- nppiMulC_8u_C4RSfs
 - image_mulc, 106
- nppiMulCScale_16u_AC4IR
 - image_mulcscale, 108
- nppiMulCScale_16u_AC4R
 - image_mulcscale, 108
- nppiMulCScale_16u_C1IR
 - image_mulcscale, 109
- nppiMulCScale_16u_C1R
 - image_mulcscale, 109
- nppiMulCScale_16u_C3IR
 - image_mulcscale, 109
- nppiMulCScale_16u_C3R
 - image_mulcscale, 110
- nppiMulCScale_16u_C4IR
 - image_mulcscale, 110
- nppiMulCScale_16u_C4R
 - image_mulcscale, 110
- nppiMulCScale_8u_AC4IR
 - image_mulcscale, 111
- nppiMulCScale_8u_AC4R
 - image_mulcscale, 111
- nppiMulCScale_8u_C1IR
 - image_mulcscale, 111
- nppiMulCScale_8u_C1R
 - image_mulcscale, 112
- nppiMulCScale_8u_C3IR
 - image_mulcscale, 112
- nppiMulCScale_8u_C3R
 - image_mulcscale, 112
- nppiMulCScale_8u_C4IR
 - image_mulcscale, 113
- nppiMulCScale_8u_C4R
 - image_mulcscale, 113
- nppiMulScale_16u_AC4IR
 - image_mulscale, 238
- nppiMulScale_16u_AC4R
 - image_mulscale, 239
- nppiMulScale_16u_C1IR
 - image_mulscale, 239
- nppiMulScale_16u_C1R
 - image_mulscale, 239
- nppiMulScale_16u_C3IR
 - image_mulscale, 240
- nppiMulScale_16u_C3R
 - image_mulscale, 240
- nppiMulScale_16u_C4IR
 - image_mulscale, 241
- nppiMulScale_16u_C4R
 - image_mulscale, 241
- nppiMulScale_8u_AC4IR
 - image_mulscale, 241
- nppiMulScale_8u_AC4R
 - image_mulscale, 242

- nppiMulScale_8u_C1IR
 image_mulscale, 242
- nppiMulScale_8u_C1R
 image_mulscale, 243
- nppiMulScale_8u_C3IR
 image_mulscale, 243
- nppiMulScale_8u_C3R
 image_mulscale, 243
- nppiMulScale_8u_C4IR
 image_mulscale, 244
- nppiMulScale_8u_C4R
 image_mulscale, 244
- nppiNorm_Inf_16s_AC4R
 image_inf_norm, 1444
- nppiNorm_Inf_16s_C1R
 image_inf_norm, 1444
- nppiNorm_Inf_16s_C3R
 image_inf_norm, 1444
- nppiNorm_Inf_16s_C4R
 image_inf_norm, 1445
- nppiNorm_Inf_16u_AC4R
 image_inf_norm, 1445
- nppiNorm_Inf_16u_C1MR
 image_inf_norm, 1445
- nppiNorm_Inf_16u_C1R
 image_inf_norm, 1446
- nppiNorm_Inf_16u_C3CMR
 image_inf_norm, 1446
- nppiNorm_Inf_16u_C3R
 image_inf_norm, 1447
- nppiNorm_Inf_16u_C4R
 image_inf_norm, 1447
- nppiNorm_Inf_32f_AC4R
 image_inf_norm, 1447
- nppiNorm_Inf_32f_C1MR
 image_inf_norm, 1448
- nppiNorm_Inf_32f_C1R
 image_inf_norm, 1448
- nppiNorm_Inf_32f_C3CMR
 image_inf_norm, 1449
- nppiNorm_Inf_32f_C3R
 image_inf_norm, 1449
- nppiNorm_Inf_32f_C4R
 image_inf_norm, 1449
- nppiNorm_Inf_32s_C1R
 image_inf_norm, 1450
- nppiNorm_Inf_8s_C1MR
 image_inf_norm, 1450
- nppiNorm_Inf_8s_C3CMR
 image_inf_norm, 1451
- nppiNorm_Inf_8u_AC4R
 image_inf_norm, 1451
- nppiNorm_Inf_8u_C1MR
 image_inf_norm, 1451
- nppiNorm_Inf_8u_C1R
 image_inf_norm, 1452
- nppiNorm_Inf_8u_C3CMR
 image_inf_norm, 1452
- nppiNorm_Inf_8u_C3R
 image_inf_norm, 1453
- nppiNorm_Inf_8u_C4R
 image_inf_norm, 1453
- nppiNorm_L1_16s_AC4R
 image_L1_norm, 1466
- nppiNorm_L1_16s_C1R
 image_L1_norm, 1466
- nppiNorm_L1_16s_C3R
 image_L1_norm, 1466
- nppiNorm_L1_16s_C4R
 image_L1_norm, 1467
- nppiNorm_L1_16u_AC4R
 image_L1_norm, 1467
- nppiNorm_L1_16u_C1MR
 image_L1_norm, 1467
- nppiNorm_L1_16u_C1R
 image_L1_norm, 1468
- nppiNorm_L1_16u_C3CMR
 image_L1_norm, 1468
- nppiNorm_L1_16u_C3R
 image_L1_norm, 1469
- nppiNorm_L1_16u_C4R
 image_L1_norm, 1469
- nppiNorm_L1_32f_AC4R
 image_L1_norm, 1469
- nppiNorm_L1_32f_C1MR
 image_L1_norm, 1470
- nppiNorm_L1_32f_C1R
 image_L1_norm, 1470
- nppiNorm_L1_32f_C3CMR
 image_L1_norm, 1470
- nppiNorm_L1_32f_C3R
 image_L1_norm, 1471
- nppiNorm_L1_32f_C4R
 image_L1_norm, 1471
- nppiNorm_L1_8s_C1MR
 image_L1_norm, 1472
- nppiNorm_L1_8s_C3CMR
 image_L1_norm, 1472
- nppiNorm_L1_8u_AC4R
 image_L1_norm, 1472
- nppiNorm_L1_8u_C1MR
 image_L1_norm, 1473
- nppiNorm_L1_8u_C1R
 image_L1_norm, 1473
- nppiNorm_L1_8u_C3CMR
 image_L1_norm, 1474
- nppiNorm_L1_8u_C3R
 image_L1_norm, 1474

- nppiNorm_L1_8u_C4R
 - image_L1_norm, [1474](#)
- nppiNorm_L2_16s_AC4R
 - image_L2_norm, [1487](#)
- nppiNorm_L2_16s_C1R
 - image_L2_norm, [1487](#)
- nppiNorm_L2_16s_C3R
 - image_L2_norm, [1487](#)
- nppiNorm_L2_16s_C4R
 - image_L2_norm, [1488](#)
- nppiNorm_L2_16u_AC4R
 - image_L2_norm, [1488](#)
- nppiNorm_L2_16u_C1MR
 - image_L2_norm, [1488](#)
- nppiNorm_L2_16u_C1R
 - image_L2_norm, [1489](#)
- nppiNorm_L2_16u_C3CMR
 - image_L2_norm, [1489](#)
- nppiNorm_L2_16u_C3R
 - image_L2_norm, [1490](#)
- nppiNorm_L2_16u_C4R
 - image_L2_norm, [1490](#)
- nppiNorm_L2_32f_AC4R
 - image_L2_norm, [1490](#)
- nppiNorm_L2_32f_C1MR
 - image_L2_norm, [1491](#)
- nppiNorm_L2_32f_C1R
 - image_L2_norm, [1491](#)
- nppiNorm_L2_32f_C3CMR
 - image_L2_norm, [1491](#)
- nppiNorm_L2_32f_C3R
 - image_L2_norm, [1492](#)
- nppiNorm_L2_32f_C4R
 - image_L2_norm, [1492](#)
- nppiNorm_L2_8s_C1MR
 - image_L2_norm, [1493](#)
- nppiNorm_L2_8s_C3CMR
 - image_L2_norm, [1493](#)
- nppiNorm_L2_8u_AC4R
 - image_L2_norm, [1493](#)
- nppiNorm_L2_8u_C1MR
 - image_L2_norm, [1494](#)
- nppiNorm_L2_8u_C1R
 - image_L2_norm, [1494](#)
- nppiNorm_L2_8u_C3CMR
 - image_L2_norm, [1495](#)
- nppiNorm_L2_8u_C3R
 - image_L2_norm, [1495](#)
- nppiNorm_L2_8u_C4R
 - image_L2_norm, [1495](#)
- nppiNormDiff_Inf_16s_AC4R
 - image_inf_normdiff, [1508](#)
- nppiNormDiff_Inf_16s_C1R
 - image_inf_normdiff, [1508](#)
- nppiNormDiff_Inf_16s_C3R
 - image_inf_normdiff, [1509](#)
- nppiNormDiff_Inf_16s_C4R
 - image_inf_normdiff, [1509](#)
- nppiNormDiff_Inf_16u_AC4R
 - image_inf_normdiff, [1510](#)
- nppiNormDiff_Inf_16u_C1MR
 - image_inf_normdiff, [1510](#)
- nppiNormDiff_Inf_16u_C1R
 - image_inf_normdiff, [1511](#)
- nppiNormDiff_Inf_16u_C3CMR
 - image_inf_normdiff, [1511](#)
- nppiNormDiff_Inf_16u_C3R
 - image_inf_normdiff, [1512](#)
- nppiNormDiff_Inf_16u_C4R
 - image_inf_normdiff, [1512](#)
- nppiNormDiff_Inf_32f_AC4R
 - image_inf_normdiff, [1512](#)
- nppiNormDiff_Inf_32f_C1MR
 - image_inf_normdiff, [1513](#)
- nppiNormDiff_Inf_32f_C1R
 - image_inf_normdiff, [1513](#)
- nppiNormDiff_Inf_32f_C3CMR
 - image_inf_normdiff, [1514](#)
- nppiNormDiff_Inf_32f_C3R
 - image_inf_normdiff, [1514](#)
- nppiNormDiff_Inf_32f_C4R
 - image_inf_normdiff, [1515](#)
- nppiNormDiff_Inf_8s_C1MR
 - image_inf_normdiff, [1515](#)
- nppiNormDiff_Inf_8s_C3CMR
 - image_inf_normdiff, [1516](#)
- nppiNormDiff_Inf_8u_AC4R
 - image_inf_normdiff, [1516](#)
- nppiNormDiff_Inf_8u_C1MR
 - image_inf_normdiff, [1517](#)
- nppiNormDiff_Inf_8u_C1R
 - image_inf_normdiff, [1517](#)
- nppiNormDiff_Inf_8u_C3CMR
 - image_inf_normdiff, [1518](#)
- nppiNormDiff_Inf_8u_C3R
 - image_inf_normdiff, [1518](#)
- nppiNormDiff_Inf_8u_C4R
 - image_inf_normdiff, [1519](#)
- nppiNormDiff_L1_16s_AC4R
 - image_L1_normdiff, [1531](#)
- nppiNormDiff_L1_16s_C1R
 - image_L1_normdiff, [1531](#)
- nppiNormDiff_L1_16s_C3R
 - image_L1_normdiff, [1532](#)
- nppiNormDiff_L1_16s_C4R
 - image_L1_normdiff, [1532](#)
- nppiNormDiff_L1_16u_AC4R
 - image_L1_normdiff, [1533](#)

- nppiNormDiff_L1_16u_C1MR
image_L1_normdiff, 1533
- nppiNormDiff_L1_16u_C1R
image_L1_normdiff, 1533
- nppiNormDiff_L1_16u_C3CMR
image_L1_normdiff, 1534
- nppiNormDiff_L1_16u_C3R
image_L1_normdiff, 1534
- nppiNormDiff_L1_16u_C4R
image_L1_normdiff, 1535
- nppiNormDiff_L1_32f_AC4R
image_L1_normdiff, 1535
- nppiNormDiff_L1_32f_C1MR
image_L1_normdiff, 1536
- nppiNormDiff_L1_32f_C1R
image_L1_normdiff, 1536
- nppiNormDiff_L1_32f_C3CMR
image_L1_normdiff, 1537
- nppiNormDiff_L1_32f_C3R
image_L1_normdiff, 1537
- nppiNormDiff_L1_32f_C4R
image_L1_normdiff, 1538
- nppiNormDiff_L1_8s_C1MR
image_L1_normdiff, 1538
- nppiNormDiff_L1_8s_C3CMR
image_L1_normdiff, 1539
- nppiNormDiff_L1_8u_AC4R
image_L1_normdiff, 1539
- nppiNormDiff_L1_8u_C1MR
image_L1_normdiff, 1540
- nppiNormDiff_L1_8u_C1R
image_L1_normdiff, 1540
- nppiNormDiff_L1_8u_C3CMR
image_L1_normdiff, 1540
- nppiNormDiff_L1_8u_C3R
image_L1_normdiff, 1541
- nppiNormDiff_L1_8u_C4R
image_L1_normdiff, 1541
- nppiNormDiff_L2_16s_AC4R
image_L2_normdiff, 1554
- nppiNormDiff_L2_16s_C1R
image_L2_normdiff, 1554
- nppiNormDiff_L2_16s_C3R
image_L2_normdiff, 1555
- nppiNormDiff_L2_16s_C4R
image_L2_normdiff, 1555
- nppiNormDiff_L2_16u_AC4R
image_L2_normdiff, 1556
- nppiNormDiff_L2_16u_C1MR
image_L2_normdiff, 1556
- nppiNormDiff_L2_16u_C1R
image_L2_normdiff, 1556
- nppiNormDiff_L2_16u_C3CMR
image_L2_normdiff, 1557
- nppiNormDiff_L2_16u_C3R
image_L2_normdiff, 1557
- nppiNormDiff_L2_16u_C4R
image_L2_normdiff, 1558
- nppiNormDiff_L2_32f_AC4R
image_L2_normdiff, 1558
- nppiNormDiff_L2_32f_C1MR
image_L2_normdiff, 1559
- nppiNormDiff_L2_32f_C1R
image_L2_normdiff, 1559
- nppiNormDiff_L2_32f_C3CMR
image_L2_normdiff, 1560
- nppiNormDiff_L2_32f_C3R
image_L2_normdiff, 1560
- nppiNormDiff_L2_32f_C4R
image_L2_normdiff, 1561
- nppiNormDiff_L2_8s_C1MR
image_L2_normdiff, 1561
- nppiNormDiff_L2_8s_C3CMR
image_L2_normdiff, 1562
- nppiNormDiff_L2_8u_AC4R
image_L2_normdiff, 1562
- nppiNormDiff_L2_8u_C1MR
image_L2_normdiff, 1563
- nppiNormDiff_L2_8u_C1R
image_L2_normdiff, 1563
- nppiNormDiff_L2_8u_C3CMR
image_L2_normdiff, 1563
- nppiNormDiff_L2_8u_C3R
image_L2_normdiff, 1564
- nppiNormDiff_L2_8u_C4R
image_L2_normdiff, 1564
- nppiNormDiffInfGetBufferHostSize_16s_AC4R
image_inf_normdiff, 1519
- nppiNormDiffInfGetBufferHostSize_16s_C1R
image_inf_normdiff, 1519
- nppiNormDiffInfGetBufferHostSize_16s_C3R
image_inf_normdiff, 1520
- nppiNormDiffInfGetBufferHostSize_16s_C4R
image_inf_normdiff, 1520
- nppiNormDiffInfGetBufferHostSize_16u_AC4R
image_inf_normdiff, 1520
- nppiNormDiffInfGetBufferHostSize_16u_C1MR
image_inf_normdiff, 1521
- nppiNormDiffInfGetBufferHostSize_16u_C1R
image_inf_normdiff, 1521
- nppiNormDiffInfGetBufferHostSize_16u_C3CMR
image_inf_normdiff, 1521
- nppiNormDiffInfGetBufferHostSize_16u_C3R
image_inf_normdiff, 1521
- nppiNormDiffInfGetBufferHostSize_16u_C4R
image_inf_normdiff, 1522
- nppiNormDiffInfGetBufferHostSize_32f_AC4R
image_inf_normdiff, 1522

- [nppiNormDiffInfGetBufferHostSize_32f_C1MR image_inf_normdiff](#), 1522
- [nppiNormDiffInfGetBufferHostSize_32f_C1R image_inf_normdiff](#), 1523
- [nppiNormDiffInfGetBufferHostSize_32f_C3CMR image_inf_normdiff](#), 1523
- [nppiNormDiffInfGetBufferHostSize_32f_C3R image_inf_normdiff](#), 1523
- [nppiNormDiffInfGetBufferHostSize_32f_C4R image_inf_normdiff](#), 1523
- [nppiNormDiffInfGetBufferHostSize_8s_C1MR image_inf_normdiff](#), 1524
- [nppiNormDiffInfGetBufferHostSize_8s_C3CMR image_inf_normdiff](#), 1524
- [nppiNormDiffInfGetBufferHostSize_8u_AC4R image_inf_normdiff](#), 1524
- [nppiNormDiffInfGetBufferHostSize_8u_C1MR image_inf_normdiff](#), 1525
- [nppiNormDiffInfGetBufferHostSize_8u_C1R image_inf_normdiff](#), 1525
- [nppiNormDiffInfGetBufferHostSize_8u_C3CMR image_inf_normdiff](#), 1525
- [nppiNormDiffInfGetBufferHostSize_8u_C3R image_inf_normdiff](#), 1525
- [nppiNormDiffInfGetBufferHostSize_8u_C4R image_inf_normdiff](#), 1526
- [nppiNormDiffL1GetBufferHostSize_16s_AC4R image_L1_normdiff](#), 1542
- [nppiNormDiffL1GetBufferHostSize_16s_C1R image_L1_normdiff](#), 1542
- [nppiNormDiffL1GetBufferHostSize_16s_C3R image_L1_normdiff](#), 1542
- [nppiNormDiffL1GetBufferHostSize_16s_C4R image_L1_normdiff](#), 1543
- [nppiNormDiffL1GetBufferHostSize_16u_AC4R image_L1_normdiff](#), 1543
- [nppiNormDiffL1GetBufferHostSize_16u_C1MR image_L1_normdiff](#), 1543
- [nppiNormDiffL1GetBufferHostSize_16u_C1R image_L1_normdiff](#), 1544
- [nppiNormDiffL1GetBufferHostSize_16u_C3CMR image_L1_normdiff](#), 1544
- [nppiNormDiffL1GetBufferHostSize_16u_C3R image_L1_normdiff](#), 1544
- [nppiNormDiffL1GetBufferHostSize_16u_C4R image_L1_normdiff](#), 1544
- [nppiNormDiffL1GetBufferHostSize_32f_AC4R image_L1_normdiff](#), 1545
- [nppiNormDiffL1GetBufferHostSize_32f_C1MR image_L1_normdiff](#), 1545
- [nppiNormDiffL1GetBufferHostSize_32f_C1R image_L1_normdiff](#), 1545
- [nppiNormDiffL1GetBufferHostSize_32f_C3CMR image_L1_normdiff](#), 1546
- [nppiNormDiffL1GetBufferHostSize_32f_C3R image_L1_normdiff](#), 1546
- [nppiNormDiffL1GetBufferHostSize_32f_C4R image_L1_normdiff](#), 1546
- [nppiNormDiffL1GetBufferHostSize_8s_C1MR image_L1_normdiff](#), 1546
- [nppiNormDiffL1GetBufferHostSize_8s_C3CMR image_L1_normdiff](#), 1547
- [nppiNormDiffL1GetBufferHostSize_8u_AC4R image_L1_normdiff](#), 1547
- [nppiNormDiffL1GetBufferHostSize_8u_C1MR image_L1_normdiff](#), 1547
- [nppiNormDiffL1GetBufferHostSize_8u_C1R image_L1_normdiff](#), 1548
- [nppiNormDiffL1GetBufferHostSize_8u_C3CMR image_L1_normdiff](#), 1548
- [nppiNormDiffL1GetBufferHostSize_8u_C3R image_L1_normdiff](#), 1548
- [nppiNormDiffL1GetBufferHostSize_8u_C4R image_L1_normdiff](#), 1548
- [nppiNormDiffL2GetBufferHostSize_16s_AC4R image_L2_normdiff](#), 1565
- [nppiNormDiffL2GetBufferHostSize_16s_C1R image_L2_normdiff](#), 1565
- [nppiNormDiffL2GetBufferHostSize_16s_C3R image_L2_normdiff](#), 1565
- [nppiNormDiffL2GetBufferHostSize_16s_C4R image_L2_normdiff](#), 1566
- [nppiNormDiffL2GetBufferHostSize_16u_AC4R image_L2_normdiff](#), 1566
- [nppiNormDiffL2GetBufferHostSize_16u_C1MR image_L2_normdiff](#), 1566
- [nppiNormDiffL2GetBufferHostSize_16u_C1R image_L2_normdiff](#), 1567
- [nppiNormDiffL2GetBufferHostSize_16u_C3CMR image_L2_normdiff](#), 1567
- [nppiNormDiffL2GetBufferHostSize_16u_C3R image_L2_normdiff](#), 1567
- [nppiNormDiffL2GetBufferHostSize_16u_C4R image_L2_normdiff](#), 1567
- [nppiNormDiffL2GetBufferHostSize_32f_AC4R image_L2_normdiff](#), 1568
- [nppiNormDiffL2GetBufferHostSize_32f_C1MR image_L2_normdiff](#), 1568
- [nppiNormDiffL2GetBufferHostSize_32f_C1R image_L2_normdiff](#), 1568
- [nppiNormDiffL2GetBufferHostSize_32f_C3CMR image_L2_normdiff](#), 1569
- [nppiNormDiffL2GetBufferHostSize_32f_C3R image_L2_normdiff](#), 1569
- [nppiNormDiffL2GetBufferHostSize_32f_C4R image_L2_normdiff](#), 1569
- [nppiNormDiffL2GetBufferHostSize_8s_C1MR image_L2_normdiff](#), 1569

- nppiNormDiffL2GetBufferHostSize_8s_C3CMR
 image_L2_normdiff, 1570
 nppiNormDiffL2GetBufferHostSize_8u_AC4R
 image_L2_normdiff, 1570
 nppiNormDiffL2GetBufferHostSize_8u_C1MR
 image_L2_normdiff, 1570
 nppiNormDiffL2GetBufferHostSize_8u_C1R
 image_L2_normdiff, 1571
 nppiNormDiffL2GetBufferHostSize_8u_C3CMR
 image_L2_normdiff, 1571
 nppiNormDiffL2GetBufferHostSize_8u_C3R
 image_L2_normdiff, 1571
 nppiNormDiffL2GetBufferHostSize_8u_C4R
 image_L2_normdiff, 1571
 nppiNormInfGetBufferHostSize_16s_AC4R
 image_inf_norm, 1453
 nppiNormInfGetBufferHostSize_16s_C1R
 image_inf_norm, 1454
 nppiNormInfGetBufferHostSize_16s_C3R
 image_inf_norm, 1454
 nppiNormInfGetBufferHostSize_16s_C4R
 image_inf_norm, 1454
 nppiNormInfGetBufferHostSize_16u_AC4R
 image_inf_norm, 1455
 nppiNormInfGetBufferHostSize_16u_C1MR
 image_inf_norm, 1455
 nppiNormInfGetBufferHostSize_16u_C1R
 image_inf_norm, 1455
 nppiNormInfGetBufferHostSize_16u_C3CMR
 image_inf_norm, 1455
 nppiNormInfGetBufferHostSize_16u_C3R
 image_inf_norm, 1456
 nppiNormInfGetBufferHostSize_16u_C4R
 image_inf_norm, 1456
 nppiNormInfGetBufferHostSize_32f_AC4R
 image_inf_norm, 1456
 nppiNormInfGetBufferHostSize_32f_C1MR
 image_inf_norm, 1457
 nppiNormInfGetBufferHostSize_32f_C1R
 image_inf_norm, 1457
 nppiNormInfGetBufferHostSize_32f_C3CMR
 image_inf_norm, 1457
 nppiNormInfGetBufferHostSize_32f_C3R
 image_inf_norm, 1457
 nppiNormInfGetBufferHostSize_32f_C4R
 image_inf_norm, 1458
 nppiNormInfGetBufferHostSize_32s_C1R
 image_inf_norm, 1458
 nppiNormInfGetBufferHostSize_8s_C1MR
 image_inf_norm, 1458
 nppiNormInfGetBufferHostSize_8s_C3CMR
 image_inf_norm, 1459
 nppiNormInfGetBufferHostSize_8u_AC4R
 image_inf_norm, 1459
 nppiNormInfGetBufferHostSize_8u_C1MR
 image_inf_norm, 1459
 nppiNormInfGetBufferHostSize_8u_C1R
 image_inf_norm, 1459
 nppiNormInfGetBufferHostSize_8u_C3CMR
 image_inf_norm, 1460
 nppiNormInfGetBufferHostSize_8u_C3R
 image_inf_norm, 1460
 nppiNormInfGetBufferHostSize_8u_C4R
 image_inf_norm, 1460
 nppiNormL1GetBufferHostSize_16s_AC4R
 image_L1_norm, 1475
 nppiNormL1GetBufferHostSize_16s_C1R
 image_L1_norm, 1475
 nppiNormL1GetBufferHostSize_16s_C3R
 image_L1_norm, 1475
 nppiNormL1GetBufferHostSize_16s_C4R
 image_L1_norm, 1476
 nppiNormL1GetBufferHostSize_16u_AC4R
 image_L1_norm, 1476
 nppiNormL1GetBufferHostSize_16u_C1MR
 image_L1_norm, 1476
 nppiNormL1GetBufferHostSize_16u_C1R
 image_L1_norm, 1477
 nppiNormL1GetBufferHostSize_16u_C3CMR
 image_L1_norm, 1477
 nppiNormL1GetBufferHostSize_16u_C3R
 image_L1_norm, 1477
 nppiNormL1GetBufferHostSize_16u_C4R
 image_L1_norm, 1477
 nppiNormL1GetBufferHostSize_32f_AC4R
 image_L1_norm, 1478
 nppiNormL1GetBufferHostSize_32f_C1MR
 image_L1_norm, 1478
 nppiNormL1GetBufferHostSize_32f_C1R
 image_L1_norm, 1478
 nppiNormL1GetBufferHostSize_32f_C3CMR
 image_L1_norm, 1479
 nppiNormL1GetBufferHostSize_32f_C3R
 image_L1_norm, 1479
 nppiNormL1GetBufferHostSize_32f_C4R
 image_L1_norm, 1479
 nppiNormL1GetBufferHostSize_8s_C1MR
 image_L1_norm, 1479
 nppiNormL1GetBufferHostSize_8s_C3CMR
 image_L1_norm, 1480
 nppiNormL1GetBufferHostSize_8u_AC4R
 image_L1_norm, 1480
 nppiNormL1GetBufferHostSize_8u_C1MR
 image_L1_norm, 1480
 nppiNormL1GetBufferHostSize_8u_C1R
 image_L1_norm, 1481
 nppiNormL1GetBufferHostSize_8u_C3CMR
 image_L1_norm, 1481

- `nppiNormL1GetBufferHostSize_8u_C3R`
 `image_L1_norm`, 1481
- `nppiNormL1GetBufferHostSize_8u_C4R`
 `image_L1_norm`, 1481
- `nppiNormL2GetBufferHostSize_16s_AC4R`
 `image_L2_norm`, 1496
- `nppiNormL2GetBufferHostSize_16s_C1R`
 `image_L2_norm`, 1496
- `nppiNormL2GetBufferHostSize_16s_C3R`
 `image_L2_norm`, 1496
- `nppiNormL2GetBufferHostSize_16s_C4R`
 `image_L2_norm`, 1497
- `nppiNormL2GetBufferHostSize_16u_AC4R`
 `image_L2_norm`, 1497
- `nppiNormL2GetBufferHostSize_16u_C1MR`
 `image_L2_norm`, 1497
- `nppiNormL2GetBufferHostSize_16u_C1R`
 `image_L2_norm`, 1498
- `nppiNormL2GetBufferHostSize_16u_C3CMR`
 `image_L2_norm`, 1498
- `nppiNormL2GetBufferHostSize_16u_C3R`
 `image_L2_norm`, 1498
- `nppiNormL2GetBufferHostSize_16u_C4R`
 `image_L2_norm`, 1498
- `nppiNormL2GetBufferHostSize_32f_AC4R`
 `image_L2_norm`, 1499
- `nppiNormL2GetBufferHostSize_32f_C1MR`
 `image_L2_norm`, 1499
- `nppiNormL2GetBufferHostSize_32f_C1R`
 `image_L2_norm`, 1499
- `nppiNormL2GetBufferHostSize_32f_C3CMR`
 `image_L2_norm`, 1500
- `nppiNormL2GetBufferHostSize_32f_C3R`
 `image_L2_norm`, 1500
- `nppiNormL2GetBufferHostSize_32f_C4R`
 `image_L2_norm`, 1500
- `nppiNormL2GetBufferHostSize_8s_C1MR`
 `image_L2_norm`, 1500
- `nppiNormL2GetBufferHostSize_8s_C3CMR`
 `image_L2_norm`, 1501
- `nppiNormL2GetBufferHostSize_8u_AC4R`
 `image_L2_norm`, 1501
- `nppiNormL2GetBufferHostSize_8u_C1MR`
 `image_L2_norm`, 1501
- `nppiNormL2GetBufferHostSize_8u_C1R`
 `image_L2_norm`, 1502
- `nppiNormL2GetBufferHostSize_8u_C3CMR`
 `image_L2_norm`, 1502
- `nppiNormL2GetBufferHostSize_8u_C3R`
 `image_L2_norm`, 1502
- `nppiNormL2GetBufferHostSize_8u_C4R`
 `image_L2_norm`, 1502
- `nppiNormRel_Inf_16s_AC4R`
 `image_inf_normrel`, 1577
- `nppiNormRel_Inf_16s_C1R`
 `image_inf_normrel`, 1577
- `nppiNormRel_Inf_16s_C3R`
 `image_inf_normrel`, 1578
- `nppiNormRel_Inf_16s_C4R`
 `image_inf_normrel`, 1578
- `nppiNormRel_Inf_16u_AC4R`
 `image_inf_normrel`, 1579
- `nppiNormRel_Inf_16u_C1MR`
 `image_inf_normrel`, 1579
- `nppiNormRel_Inf_16u_C1R`
 `image_inf_normrel`, 1580
- `nppiNormRel_Inf_16u_C3CMR`
 `image_inf_normrel`, 1580
- `nppiNormRel_Inf_16u_C3R`
 `image_inf_normrel`, 1581
- `nppiNormRel_Inf_16u_C4R`
 `image_inf_normrel`, 1581
- `nppiNormRel_Inf_32f_AC4R`
 `image_inf_normrel`, 1581
- `nppiNormRel_Inf_32f_C1MR`
 `image_inf_normrel`, 1582
- `nppiNormRel_Inf_32f_C1R`
 `image_inf_normrel`, 1582
- `nppiNormRel_Inf_32f_C3CMR`
 `image_inf_normrel`, 1583
- `nppiNormRel_Inf_32f_C3R`
 `image_inf_normrel`, 1583
- `nppiNormRel_Inf_32f_C4R`
 `image_inf_normrel`, 1584
- `nppiNormRel_Inf_8s_C1MR`
 `image_inf_normrel`, 1584
- `nppiNormRel_Inf_8s_C3CMR`
 `image_inf_normrel`, 1585
- `nppiNormRel_Inf_8u_AC4R`
 `image_inf_normrel`, 1585
- `nppiNormRel_Inf_8u_C1MR`
 `image_inf_normrel`, 1586
- `nppiNormRel_Inf_8u_C1R`
 `image_inf_normrel`, 1586
- `nppiNormRel_Inf_8u_C3CMR`
 `image_inf_normrel`, 1587
- `nppiNormRel_Inf_8u_C3R`
 `image_inf_normrel`, 1587
- `nppiNormRel_Inf_8u_C4R`
 `image_inf_normrel`, 1588
- `nppiNormRel_L1_16s_AC4R`
 `image_L1_normrel`, 1600
- `nppiNormRel_L1_16s_C1R`
 `image_L1_normrel`, 1600
- `nppiNormRel_L1_16s_C3R`
 `image_L1_normrel`, 1601
- `nppiNormRel_L1_16s_C4R`
 `image_L1_normrel`, 1601

- nppiNormRel_L1_16u_AC4R
 image_L1_normrel, 1602
 nppiNormRel_L1_16u_C1MR
 image_L1_normrel, 1602
 nppiNormRel_L1_16u_C1R
 image_L1_normrel, 1603
 nppiNormRel_L1_16u_C3CMR
 image_L1_normrel, 1603
 nppiNormRel_L1_16u_C3R
 image_L1_normrel, 1603
 nppiNormRel_L1_16u_C4R
 image_L1_normrel, 1604
 nppiNormRel_L1_32f_AC4R
 image_L1_normrel, 1604
 nppiNormRel_L1_32f_C1MR
 image_L1_normrel, 1605
 nppiNormRel_L1_32f_C1R
 image_L1_normrel, 1605
 nppiNormRel_L1_32f_C3CMR
 image_L1_normrel, 1606
 nppiNormRel_L1_32f_C3R
 image_L1_normrel, 1606
 nppiNormRel_L1_32f_C4R
 image_L1_normrel, 1607
 nppiNormRel_L1_8s_C1MR
 image_L1_normrel, 1607
 nppiNormRel_L1_8s_C3CMR
 image_L1_normrel, 1608
 nppiNormRel_L1_8u_AC4R
 image_L1_normrel, 1608
 nppiNormRel_L1_8u_C1MR
 image_L1_normrel, 1609
 nppiNormRel_L1_8u_C1R
 image_L1_normrel, 1609
 nppiNormRel_L1_8u_C3CMR
 image_L1_normrel, 1610
 nppiNormRel_L1_8u_C3R
 image_L1_normrel, 1610
 nppiNormRel_L1_8u_C4R
 image_L1_normrel, 1611
 nppiNormRel_L2_16s_AC4R
 image_L2_normrel, 1623
 nppiNormRel_L2_16s_C1R
 image_L2_normrel, 1623
 nppiNormRel_L2_16s_C3R
 image_L2_normrel, 1624
 nppiNormRel_L2_16s_C4R
 image_L2_normrel, 1624
 nppiNormRel_L2_16u_AC4R
 image_L2_normrel, 1625
 nppiNormRel_L2_16u_C1MR
 image_L2_normrel, 1625
 nppiNormRel_L2_16u_C1R
 image_L2_normrel, 1626
 nppiNormRel_L2_16u_C3CMR
 image_L2_normrel, 1626
 nppiNormRel_L2_16u_C3R
 image_L2_normrel, 1626
 nppiNormRel_L2_16u_C4R
 image_L2_normrel, 1627
 nppiNormRel_L2_32f_AC4R
 image_L2_normrel, 1627
 nppiNormRel_L2_32f_C1MR
 image_L2_normrel, 1628
 nppiNormRel_L2_32f_C1R
 image_L2_normrel, 1628
 nppiNormRel_L2_32f_C3CMR
 image_L2_normrel, 1629
 nppiNormRel_L2_32f_C3R
 image_L2_normrel, 1629
 nppiNormRel_L2_32f_C4R
 image_L2_normrel, 1630
 nppiNormRel_L2_8s_C1MR
 image_L2_normrel, 1630
 nppiNormRel_L2_8s_C3CMR
 image_L2_normrel, 1631
 nppiNormRel_L2_8u_AC4R
 image_L2_normrel, 1631
 nppiNormRel_L2_8u_C1MR
 image_L2_normrel, 1632
 nppiNormRel_L2_8u_C1R
 image_L2_normrel, 1632
 nppiNormRel_L2_8u_C3CMR
 image_L2_normrel, 1633
 nppiNormRel_L2_8u_C3R
 image_L2_normrel, 1633
 nppiNormRel_L2_8u_C4R
 image_L2_normrel, 1634
 nppiNormRelInfGetBufferHostSize_16s_AC4R
 image_inf_normrel, 1588
 nppiNormRelInfGetBufferHostSize_16s_C1R
 image_inf_normrel, 1589
 nppiNormRelInfGetBufferHostSize_16s_C3R
 image_inf_normrel, 1589
 nppiNormRelInfGetBufferHostSize_16s_C4R
 image_inf_normrel, 1589
 nppiNormRelInfGetBufferHostSize_16u_AC4R
 image_inf_normrel, 1589
 nppiNormRelInfGetBufferHostSize_16u_C1MR
 image_inf_normrel, 1590
 nppiNormRelInfGetBufferHostSize_16u_C1R
 image_inf_normrel, 1590
 nppiNormRelInfGetBufferHostSize_16u_C3CMR
 image_inf_normrel, 1590
 nppiNormRelInfGetBufferHostSize_16u_C3R
 image_inf_normrel, 1591
 nppiNormRelInfGetBufferHostSize_16u_C4R
 image_inf_normrel, 1591

- nppiNormRelInfGetBufferHostSize_32f_AC4R
image_inf_normrel, 1591
- nppiNormRelInfGetBufferHostSize_32f_C1MR
image_inf_normrel, 1591
- nppiNormRelInfGetBufferHostSize_32f_C1R
image_inf_normrel, 1592
- nppiNormRelInfGetBufferHostSize_32f_C3CMR
image_inf_normrel, 1592
- nppiNormRelInfGetBufferHostSize_32f_C3R
image_inf_normrel, 1592
- nppiNormRelInfGetBufferHostSize_32f_C4R
image_inf_normrel, 1593
- nppiNormRelInfGetBufferHostSize_32s_C1R
image_inf_normrel, 1593
- nppiNormRelInfGetBufferHostSize_8s_C1MR
image_inf_normrel, 1593
- nppiNormRelInfGetBufferHostSize_8s_C3CMR
image_inf_normrel, 1593
- nppiNormRelInfGetBufferHostSize_8u_AC4R
image_inf_normrel, 1594
- nppiNormRelInfGetBufferHostSize_8u_C1MR
image_inf_normrel, 1594
- nppiNormRelInfGetBufferHostSize_8u_C1R
image_inf_normrel, 1594
- nppiNormRelInfGetBufferHostSize_8u_C3CMR
image_inf_normrel, 1595
- nppiNormRelInfGetBufferHostSize_8u_C3R
image_inf_normrel, 1595
- nppiNormRelInfGetBufferHostSize_8u_C4R
image_inf_normrel, 1595
- nppiNormRelL1GetBufferHostSize_16s_AC4R
image_L1_normrel, 1611
- nppiNormRelL1GetBufferHostSize_16s_C1R
image_L1_normrel, 1611
- nppiNormRelL1GetBufferHostSize_16s_C3R
image_L1_normrel, 1612
- nppiNormRelL1GetBufferHostSize_16s_C4R
image_L1_normrel, 1612
- nppiNormRelL1GetBufferHostSize_16u_AC4R
image_L1_normrel, 1612
- nppiNormRelL1GetBufferHostSize_16u_C1MR
image_L1_normrel, 1613
- nppiNormRelL1GetBufferHostSize_16u_C1R
image_L1_normrel, 1613
- nppiNormRelL1GetBufferHostSize_16u_C3CMR
image_L1_normrel, 1613
- nppiNormRelL1GetBufferHostSize_16u_C3R
image_L1_normrel, 1613
- nppiNormRelL1GetBufferHostSize_16u_C4R
image_L1_normrel, 1614
- nppiNormRelL1GetBufferHostSize_32f_AC4R
image_L1_normrel, 1614
- nppiNormRelL1GetBufferHostSize_32f_C1MR
image_L1_normrel, 1614
- nppiNormRelL1GetBufferHostSize_32f_C1R
image_L1_normrel, 1615
- nppiNormRelL1GetBufferHostSize_32f_C3CMR
image_L1_normrel, 1615
- nppiNormRelL1GetBufferHostSize_32f_C3R
image_L1_normrel, 1615
- nppiNormRelL1GetBufferHostSize_32f_C4R
image_L1_normrel, 1615
- nppiNormRelL1GetBufferHostSize_8s_C1MR
image_L1_normrel, 1616
- nppiNormRelL1GetBufferHostSize_8s_C3CMR
image_L1_normrel, 1616
- nppiNormRelL1GetBufferHostSize_8u_AC4R
image_L1_normrel, 1616
- nppiNormRelL1GetBufferHostSize_8u_C1MR
image_L1_normrel, 1617
- nppiNormRelL1GetBufferHostSize_8u_C1R
image_L1_normrel, 1617
- nppiNormRelL1GetBufferHostSize_8u_C3CMR
image_L1_normrel, 1617
- nppiNormRelL1GetBufferHostSize_8u_C3R
image_L1_normrel, 1617
- nppiNormRelL1GetBufferHostSize_8u_C4R
image_L1_normrel, 1618
- nppiNormRelL2GetBufferHostSize_16s_AC4R
image_L2_normrel, 1634
- nppiNormRelL2GetBufferHostSize_16s_C1R
image_L2_normrel, 1634
- nppiNormRelL2GetBufferHostSize_16s_C3R
image_L2_normrel, 1635
- nppiNormRelL2GetBufferHostSize_16s_C4R
image_L2_normrel, 1635
- nppiNormRelL2GetBufferHostSize_16u_AC4R
image_L2_normrel, 1635
- nppiNormRelL2GetBufferHostSize_16u_C1MR
image_L2_normrel, 1636
- nppiNormRelL2GetBufferHostSize_16u_C1R
image_L2_normrel, 1636
- nppiNormRelL2GetBufferHostSize_16u_C3CMR
image_L2_normrel, 1636
- nppiNormRelL2GetBufferHostSize_16u_C3R
image_L2_normrel, 1636
- nppiNormRelL2GetBufferHostSize_16u_C4R
image_L2_normrel, 1637
- nppiNormRelL2GetBufferHostSize_32f_AC4R
image_L2_normrel, 1637
- nppiNormRelL2GetBufferHostSize_32f_C1MR
image_L2_normrel, 1637
- nppiNormRelL2GetBufferHostSize_32f_C1R
image_L2_normrel, 1638
- nppiNormRelL2GetBufferHostSize_32f_C3CMR
image_L2_normrel, 1638
- nppiNormRelL2GetBufferHostSize_32f_C3R
image_L2_normrel, 1638

- nppiNormRelL2GetBufferHostSize_32f_C4R
image_L2_normrel, 1638
- nppiNormRelL2GetBufferHostSize_8s_C1MR
image_L2_normrel, 1639
- nppiNormRelL2GetBufferHostSize_8s_C3CMR
image_L2_normrel, 1639
- nppiNormRelL2GetBufferHostSize_8u_AC4R
image_L2_normrel, 1639
- nppiNormRelL2GetBufferHostSize_8u_C1MR
image_L2_normrel, 1640
- nppiNormRelL2GetBufferHostSize_8u_C1R
image_L2_normrel, 1640
- nppiNormRelL2GetBufferHostSize_8u_C3CMR
image_L2_normrel, 1640
- nppiNormRelL2GetBufferHostSize_8u_C3R
image_L2_normrel, 1640
- nppiNormRelL2GetBufferHostSize_8u_C4R
image_L2_normrel, 1641
- nppiNot_8u_AC4IR
image_not, 468
- nppiNot_8u_AC4R
image_not, 469
- nppiNot_8u_C1IR
image_not, 469
- nppiNot_8u_C1R
image_not, 469
- nppiNot_8u_C3IR
image_not, 469
- nppiNot_8u_C3R
image_not, 470
- nppiNot_8u_C4IR
image_not, 470
- nppiNot_8u_C4R
image_not, 470
- nppiOr_16u_AC4IR
image_or, 446
- nppiOr_16u_AC4R
image_or, 446
- nppiOr_16u_C1IR
image_or, 446
- nppiOr_16u_C1R
image_or, 447
- nppiOr_16u_C3IR
image_or, 447
- nppiOr_16u_C3R
image_or, 447
- nppiOr_16u_C4IR
image_or, 448
- nppiOr_16u_C4R
image_or, 448
- nppiOr_32s_AC4IR
image_or, 449
- nppiOr_32s_AC4R
image_or, 449
- nppiOr_32s_C1IR
image_or, 449
- nppiOr_32s_C1R
image_or, 449
- nppiOr_32s_C3IR
image_or, 450
- nppiOr_32s_C3R
image_or, 450
- nppiOr_32s_C4IR
image_or, 451
- nppiOr_32s_C4R
image_or, 451
- nppiOr_8u_AC4IR
image_or, 452
- nppiOr_8u_AC4R
image_or, 452
- nppiOr_8u_C1IR
image_or, 452
- nppiOr_8u_C1R
image_or, 453
- nppiOr_8u_C3IR
image_or, 453
- nppiOr_8u_C3R
image_or, 453
- nppiOr_8u_C4IR
image_or, 454
- nppiOr_8u_C4R
image_or, 454
- nppiOrC_16u_AC4IR
image_orc, 384
- nppiOrC_16u_AC4R
image_orc, 384
- nppiOrC_16u_C1IR
image_orc, 384
- nppiOrC_16u_C1R
image_orc, 385
- nppiOrC_16u_C3IR
image_orc, 385
- nppiOrC_16u_C3R
image_orc, 385
- nppiOrC_16u_C4IR
image_orc, 386
- nppiOrC_16u_C4R
image_orc, 386
- nppiOrC_32s_AC4IR
image_orc, 386
- nppiOrC_32s_AC4R
image_orc, 387
- nppiOrC_32s_C1IR
image_orc, 387
- nppiOrC_32s_C1R
image_orc, 387
- nppiOrC_32s_C3IR
image_orc, 388

- nppiOrC_32s_C3R
 - image_orc, [388](#)
- nppiOrC_32s_C4IR
 - image_orc, [388](#)
- nppiOrC_32s_C4R
 - image_orc, [389](#)
- nppiOrC_8u_AC4IR
 - image_orc, [389](#)
- nppiOrC_8u_AC4R
 - image_orc, [389](#)
- nppiOrC_8u_C1IR
 - image_orc, [390](#)
- nppiOrC_8u_C1R
 - image_orc, [390](#)
- nppiOrC_8u_C3IR
 - image_orc, [390](#)
- nppiOrC_8u_C3R
 - image_orc, [391](#)
- nppiOrC_8u_C4IR
 - image_orc, [391](#)
- nppiOrC_8u_C4R
 - image_orc, [391](#)
- NppiPoint, [2331](#)
 - x, [2331](#)
 - y, [2331](#)
- nppiQualityIndex_16u32f_AC4R
 - image_quality_index, [1858](#)
- nppiQualityIndex_16u32f_C1R
 - image_quality_index, [1858](#)
- nppiQualityIndex_16u32f_C3R
 - image_quality_index, [1859](#)
- nppiQualityIndex_32f_AC4R
 - image_quality_index, [1859](#)
- nppiQualityIndex_32f_C1R
 - image_quality_index, [1860](#)
- nppiQualityIndex_32f_C3R
 - image_quality_index, [1860](#)
- nppiQualityIndex_8u32f_AC4R
 - image_quality_index, [1860](#)
- nppiQualityIndex_8u32f_C1R
 - image_quality_index, [1861](#)
- nppiQualityIndex_8u32f_C3R
 - image_quality_index, [1861](#)
- nppiQualityIndexGetBufferHostSize_16u32f_-AC4R
 - image_quality_index, [1862](#)
- nppiQualityIndexGetBufferHostSize_16u32f_C1R
 - image_quality_index, [1862](#)
- nppiQualityIndexGetBufferHostSize_16u32f_C3R
 - image_quality_index, [1862](#)
- nppiQualityIndexGetBufferHostSize_32f_AC4R
 - image_quality_index, [1863](#)
- nppiQualityIndexGetBufferHostSize_32f_C1R
 - image_quality_index, [1863](#)
- nppiQualityIndexGetBufferHostSize_32f_C3R
 - image_quality_index, [1863](#)
- nppiQualityIndexGetBufferHostSize_8u32f_AC4R
 - image_quality_index, [1864](#)
- nppiQualityIndexGetBufferHostSize_8u32f_C1R
 - image_quality_index, [1864](#)
- nppiQualityIndexGetBufferHostSize_8u32f_C3R
 - image_quality_index, [1864](#)
- nppiQuantFwdRawTableInit_JPEG_8u
 - image_quantization, [695](#)
- nppiQuantFwdTableInit_JPEG_8u16u
 - image_quantization, [696](#)
- nppiQuantInvTableInit_JPEG_8u16u
 - image_quantization, [696](#)
- NppiRect, [2332](#)
 - height, [2332](#)
 - width, [2332](#)
 - x, [2332](#)
 - y, [2332](#)
- nppiRectStdDev_32f_C1R
 - image_rectstddev, [1692](#)
- nppiRectStdDev_32s32f_C1R
 - image_rectstddev, [1693](#)
- nppiRectStdDev_32s_C1RSfs
 - image_rectstddev, [1693](#)
- nppiRemap_16s_AC4R
 - image_remap, [1128](#)
- nppiRemap_16s_C1R
 - image_remap, [1129](#)
- nppiRemap_16s_C3R
 - image_remap, [1129](#)
- nppiRemap_16s_C4R
 - image_remap, [1130](#)
- nppiRemap_16s_P3R
 - image_remap, [1131](#)
- nppiRemap_16s_P4R
 - image_remap, [1131](#)
- nppiRemap_16u_AC4R
 - image_remap, [1132](#)
- nppiRemap_16u_C1R
 - image_remap, [1132](#)
- nppiRemap_16u_C3R
 - image_remap, [1133](#)
- nppiRemap_16u_C4R
 - image_remap, [1134](#)
- nppiRemap_16u_P3R
 - image_remap, [1134](#)
- nppiRemap_16u_P4R
 - image_remap, [1135](#)
- nppiRemap_32f_AC4R
 - image_remap, [1135](#)
- nppiRemap_32f_C1R
 - image_remap, [1136](#)
- nppiRemap_32f_C3R

- image_remap, 1137
- nppiRemap_32f_C4R
 - image_remap, 1137
- nppiRemap_32f_P3R
 - image_remap, 1138
- nppiRemap_32f_P4R
 - image_remap, 1138
- nppiRemap_64f_AC4R
 - image_remap, 1139
- nppiRemap_64f_C1R
 - image_remap, 1140
- nppiRemap_64f_C3R
 - image_remap, 1140
- nppiRemap_64f_C4R
 - image_remap, 1141
- nppiRemap_64f_P3R
 - image_remap, 1141
- nppiRemap_64f_P4R
 - image_remap, 1142
- nppiRemap_8u_AC4R
 - image_remap, 1143
- nppiRemap_8u_C1R
 - image_remap, 1143
- nppiRemap_8u_C3R
 - image_remap, 1144
- nppiRemap_8u_C4R
 - image_remap, 1144
- nppiRemap_8u_P3R
 - image_remap, 1145
- nppiRemap_8u_P4R
 - image_remap, 1146
- nppiResize_16u_AC4R
 - image_resize, 1115
- nppiResize_16u_C1R
 - image_resize, 1116
- nppiResize_16u_C3R
 - image_resize, 1116
- nppiResize_16u_C4R
 - image_resize, 1117
- nppiResize_16u_P3R
 - image_resize, 1117
- nppiResize_16u_P4R
 - image_resize, 1118
- nppiResize_32f_AC4R
 - image_resize, 1118
- nppiResize_32f_C1R
 - image_resize, 1119
- nppiResize_32f_C3R
 - image_resize, 1119
- nppiResize_32f_C4R
 - image_resize, 1120
- nppiResize_32f_P3R
 - image_resize, 1120
- nppiResize_32f_P4R
 - image_resize, 1121
- nppiResize_8u_AC4R
 - image_resize, 1121
- nppiResize_8u_C1R
 - image_resize, 1122
- nppiResize_8u_C3R
 - image_resize, 1122
- nppiResize_8u_C4R
 - image_resize, 1123
- nppiResize_8u_P3R
 - image_resize, 1123
- nppiResize_8u_P4R
 - image_resize, 1124
- nppiResizeSqrPixel_16s_AC4R
 - image_resize_square_pixel, 1095
- nppiResizeSqrPixel_16s_C1R
 - image_resize_square_pixel, 1095
- nppiResizeSqrPixel_16s_C3R
 - image_resize_square_pixel, 1096
- nppiResizeSqrPixel_16s_C4R
 - image_resize_square_pixel, 1096
- nppiResizeSqrPixel_16s_P3R
 - image_resize_square_pixel, 1097
- nppiResizeSqrPixel_16s_P4R
 - image_resize_square_pixel, 1098
- nppiResizeSqrPixel_16u_AC4R
 - image_resize_square_pixel, 1098
- nppiResizeSqrPixel_16u_C1R
 - image_resize_square_pixel, 1099
- nppiResizeSqrPixel_16u_C3R
 - image_resize_square_pixel, 1099
- nppiResizeSqrPixel_16u_C4R
 - image_resize_square_pixel, 1100
- nppiResizeSqrPixel_16u_P3R
 - image_resize_square_pixel, 1100
- nppiResizeSqrPixel_16u_P4R
 - image_resize_square_pixel, 1101
- nppiResizeSqrPixel_32f_AC4R
 - image_resize_square_pixel, 1102
- nppiResizeSqrPixel_32f_C1R
 - image_resize_square_pixel, 1102
- nppiResizeSqrPixel_32f_C3R
 - image_resize_square_pixel, 1103
- nppiResizeSqrPixel_32f_C4R
 - image_resize_square_pixel, 1103
- nppiResizeSqrPixel_32f_P3R
 - image_resize_square_pixel, 1104
- nppiResizeSqrPixel_32f_P4R
 - image_resize_square_pixel, 1104
- nppiResizeSqrPixel_64f_AC4R
 - image_resize_square_pixel, 1105
- nppiResizeSqrPixel_64f_C1R
 - image_resize_square_pixel, 1106
- nppiResizeSqrPixel_64f_C3R

- image_resize_square_pixel, 1106
- nppiResizeSqrPixel_64f_C4R
 - image_resize_square_pixel, 1107
- nppiResizeSqrPixel_64f_P3R
 - image_resize_square_pixel, 1107
- nppiResizeSqrPixel_64f_P4R
 - image_resize_square_pixel, 1108
- nppiResizeSqrPixel_8u_AC4R
 - image_resize_square_pixel, 1108
- nppiResizeSqrPixel_8u_C1R
 - image_resize_square_pixel, 1109
- nppiResizeSqrPixel_8u_C3R
 - image_resize_square_pixel, 1109
- nppiResizeSqrPixel_8u_C4R
 - image_resize_square_pixel, 1110
- nppiResizeSqrPixel_8u_P3R
 - image_resize_square_pixel, 1110
- nppiResizeSqrPixel_8u_P4R
 - image_resize_square_pixel, 1111
- nppiRGBToCbYCr422_8u_C3C2R
 - image_color_model_conversion, 542
- nppiRGBToCbYCr422Gamma_8u_C3C2R
 - image_color_model_conversion, 542
- nppiRGBToGray_16s_AC4C1R
 - image_color_model_conversion, 543
- nppiRGBToGray_16s_C3C1R
 - image_color_model_conversion, 543
- nppiRGBToGray_16u_AC4C1R
 - image_color_model_conversion, 543
- nppiRGBToGray_16u_C3C1R
 - image_color_model_conversion, 544
- nppiRGBToGray_32f_AC4C1R
 - image_color_model_conversion, 544
- nppiRGBToGray_32f_C3C1R
 - image_color_model_conversion, 544
- nppiRGBToGray_8u_AC4C1R
 - image_color_model_conversion, 545
- nppiRGBToGray_8u_C3C1R
 - image_color_model_conversion, 545
- nppiRGBToHLS_8u_AC4R
 - image_color_model_conversion, 545
- nppiRGBToHLS_8u_C3R
 - image_color_model_conversion, 546
- nppiRGBToHSV_8u_AC4R
 - image_color_model_conversion, 546
- nppiRGBToHSV_8u_C3R
 - image_color_model_conversion, 546
- nppiRGBToLUV_8u_AC4R
 - image_color_model_conversion, 547
- nppiRGBToLUV_8u_C3R
 - image_color_model_conversion, 547
- nppiRGBToXYZ_8u_AC4R
 - image_color_model_conversion, 547
- nppiRGBToXYZ_8u_C3R
 - image_color_model_conversion, 548
- nppiRGBToYCbCr420_8u_C3P3R
 - image_color_model_conversion, 548
- nppiRGBToYCbCr422_8u_C3C2R
 - image_color_model_conversion, 548
- nppiRGBToYCbCr422_8u_C3P3R
 - image_color_model_conversion, 549
- nppiRGBToYCbCr422_8u_P3C2R
 - image_color_model_conversion, 549
- nppiRGBToYCbCr_8u_AC4P3R
 - image_color_model_conversion, 550
- nppiRGBToYCbCr_8u_AC4R
 - image_color_model_conversion, 550
- nppiRGBToYCbCr_8u_C3P3R
 - image_color_model_conversion, 550
- nppiRGBToYCbCr_8u_C3R
 - image_color_model_conversion, 551
- nppiRGBToYCbCr_8u_P3R
 - image_color_model_conversion, 551
- nppiRGBToYCC_8u_AC4R
 - image_color_model_conversion, 551
- nppiRGBToYCC_8u_C3R
 - image_color_model_conversion, 552
- nppiRGBToYCrCb420_8u_AC4P3R
 - image_color_model_conversion, 552
- nppiRGBToYCrCb422_8u_C3C2R
 - image_color_model_conversion, 552
- nppiRGBToYCrCb422_8u_P3C2R
 - image_color_model_conversion, 553
- nppiRGBToYUV420_8u_C3P3R
 - image_color_model_conversion, 553
- nppiRGBToYUV420_8u_P3R
 - image_color_model_conversion, 553
- nppiRGBToYUV422_8u_C3C2R
 - image_color_model_conversion, 554
- nppiRGBToYUV422_8u_C3P3R
 - image_color_model_conversion, 554
- nppiRGBToYUV422_8u_P3R
 - image_color_model_conversion, 554
- nppiRGBToYUV_8u_AC4P4R
 - image_color_model_conversion, 555
- nppiRGBToYUV_8u_AC4R
 - image_color_model_conversion, 555
- nppiRGBToYUV_8u_C3P3R
 - image_color_model_conversion, 556
- nppiRGBToYUV_8u_C3R
 - image_color_model_conversion, 556
- nppiRGBToYUV_8u_P3R
 - image_color_model_conversion, 556
- nppiRotate_16u_AC4R
 - image_rotate, 1149
- nppiRotate_16u_C1R
 - image_rotate, 1150
- nppiRotate_16u_C3R

- image_rotate, 1150
- nppiRotate_16u_C4R
 - image_rotate, 1151
- nppiRotate_32f_AC4R
 - image_rotate, 1151
- nppiRotate_32f_C1R
 - image_rotate, 1152
- nppiRotate_32f_C3R
 - image_rotate, 1152
- nppiRotate_32f_C4R
 - image_rotate, 1153
- nppiRotate_8u_AC4R
 - image_rotate, 1153
- nppiRotate_8u_C1R
 - image_rotate, 1154
- nppiRotate_8u_C3R
 - image_rotate, 1154
- nppiRotate_8u_C4R
 - image_rotate, 1155
- nppiRShiftC_16s_AC4IR
 - image_rshiftc, 407
- nppiRShiftC_16s_AC4R
 - image_rshiftc, 407
- nppiRShiftC_16s_C1IR
 - image_rshiftc, 408
- nppiRShiftC_16s_C1R
 - image_rshiftc, 408
- nppiRShiftC_16s_C3IR
 - image_rshiftc, 408
- nppiRShiftC_16s_C3R
 - image_rshiftc, 409
- nppiRShiftC_16s_C4IR
 - image_rshiftc, 409
- nppiRShiftC_16s_C4R
 - image_rshiftc, 409
- nppiRShiftC_16u_AC4IR
 - image_rshiftc, 410
- nppiRShiftC_16u_AC4R
 - image_rshiftc, 410
- nppiRShiftC_16u_C1IR
 - image_rshiftc, 410
- nppiRShiftC_16u_C1R
 - image_rshiftc, 411
- nppiRShiftC_16u_C3IR
 - image_rshiftc, 411
- nppiRShiftC_16u_C3R
 - image_rshiftc, 411
- nppiRShiftC_16u_C4IR
 - image_rshiftc, 412
- nppiRShiftC_16u_C4R
 - image_rshiftc, 412
- nppiRShiftC_32s_AC4IR
 - image_rshiftc, 412
- nppiRShiftC_32s_AC4R
 - image_rshiftc, 413
- nppiRShiftC_32s_C1IR
 - image_rshiftc, 413
- nppiRShiftC_32s_C1R
 - image_rshiftc, 413
- nppiRShiftC_32s_C3IR
 - image_rshiftc, 414
- nppiRShiftC_32s_C3R
 - image_rshiftc, 414
- nppiRShiftC_32s_C4IR
 - image_rshiftc, 414
- nppiRShiftC_32s_C4R
 - image_rshiftc, 415
- nppiRShiftC_8s_AC4IR
 - image_rshiftc, 415
- nppiRShiftC_8s_AC4R
 - image_rshiftc, 415
- nppiRShiftC_8s_C1IR
 - image_rshiftc, 416
- nppiRShiftC_8s_C1R
 - image_rshiftc, 416
- nppiRShiftC_8s_C3IR
 - image_rshiftc, 416
- nppiRShiftC_8s_C3R
 - image_rshiftc, 417
- nppiRShiftC_8s_C4IR
 - image_rshiftc, 417
- nppiRShiftC_8s_C4R
 - image_rshiftc, 417
- nppiRShiftC_8u_AC4IR
 - image_rshiftc, 418
- nppiRShiftC_8u_AC4R
 - image_rshiftc, 418
- nppiRShiftC_8u_C1IR
 - image_rshiftc, 418
- nppiRShiftC_8u_C1R
 - image_rshiftc, 419
- nppiRShiftC_8u_C3IR
 - image_rshiftc, 419
- nppiRShiftC_8u_C3R
 - image_rshiftc, 419
- nppiRShiftC_8u_C4IR
 - image_rshiftc, 420
- nppiRShiftC_8u_C4R
 - image_rshiftc, 420
- nppiSameNormLevelGetBufferHostSize_16u32f_-AC4R
 - crosscorrnormlevel, 1829
- nppiSameNormLevelGetBufferHostSize_16u32f_-C1R
 - crosscorrnormlevel, 1830
- nppiSameNormLevelGetBufferHostSize_16u32f_-C3R
 - crosscorrnormlevel, 1830

- nppiSameNormLevelGetBufferHostSize_16u32f_-
 C4R
 crosscorrsmenormlevel, [1830](#)
 nppiSameNormLevelGetBufferHostSize_32f_-
 AC4R
 crosscorrsmenormlevel, [1831](#)
 nppiSameNormLevelGetBufferHostSize_32f_C1R
 crosscorrsmenormlevel, [1831](#)
 nppiSameNormLevelGetBufferHostSize_32f_C3R
 crosscorrsmenormlevel, [1831](#)
 nppiSameNormLevelGetBufferHostSize_32f_C4R
 crosscorrsmenormlevel, [1831](#)
 nppiSameNormLevelGetBufferHostSize_8s32f_-
 AC4R
 crosscorrsmenormlevel, [1832](#)
 nppiSameNormLevelGetBufferHostSize_8s32f_-
 C1R
 crosscorrsmenormlevel, [1832](#)
 nppiSameNormLevelGetBufferHostSize_8s32f_-
 C3R
 crosscorrsmenormlevel, [1832](#)
 nppiSameNormLevelGetBufferHostSize_8s32f_-
 C4R
 crosscorrsmenormlevel, [1833](#)
 nppiSameNormLevelGetBufferHostSize_8u32f_-
 AC4R
 crosscorrsmenormlevel, [1833](#)
 nppiSameNormLevelGetBufferHostSize_8u32f_-
 C1R
 crosscorrsmenormlevel, [1833](#)
 nppiSameNormLevelGetBufferHostSize_8u32f_-
 C3R
 crosscorrsmenormlevel, [1833](#)
 nppiSameNormLevelGetBufferHostSize_8u32f_-
 C4R
 crosscorrsmenormlevel, [1834](#)
 nppiSameNormLevelGetBufferHostSize_8u_-
 AC4RSfs
 crosscorrsmenormlevel, [1834](#)
 nppiSameNormLevelGetBufferHostSize_8u_-
 C1RSfs
 crosscorrsmenormlevel, [1834](#)
 nppiSameNormLevelGetBufferHostSize_8u_-
 C3RSfs
 crosscorrsmenormlevel, [1835](#)
 nppiSameNormLevelGetBufferHostSize_8u_-
 C4RSfs
 crosscorrsmenormlevel, [1835](#)
 nppiScale_16s8u_AC4R
 image_scale, [831](#)
 nppiScale_16s8u_C1R
 image_scale, [831](#)
 nppiScale_16s8u_C3R
 image_scale, [831](#)
 nppiScale_16s8u_C4R
 image_scale, [832](#)
 nppiScale_16u8u_AC4R
 image_scale, [832](#)
 nppiScale_16u8u_C1R
 image_scale, [832](#)
 nppiScale_16u8u_C3R
 image_scale, [833](#)
 nppiScale_16u8u_C4R
 image_scale, [833](#)
 nppiScale_32f8u_AC4R
 image_scale, [833](#)
 nppiScale_32f8u_C1R
 image_scale, [834](#)
 nppiScale_32f8u_C3R
 image_scale, [834](#)
 nppiScale_32f8u_C4R
 image_scale, [835](#)
 nppiScale_32s8u_AC4R
 image_scale, [835](#)
 nppiScale_32s8u_C1R
 image_scale, [835](#)
 nppiScale_32s8u_C3R
 image_scale, [836](#)
 nppiScale_32s8u_C4R
 image_scale, [836](#)
 nppiScale_8u16s_AC4R
 image_scale, [836](#)
 nppiScale_8u16s_C1R
 image_scale, [837](#)
 nppiScale_8u16s_C3R
 image_scale, [837](#)
 nppiScale_8u16s_C4R
 image_scale, [837](#)
 nppiScale_8u16u_AC4R
 image_scale, [838](#)
 nppiScale_8u16u_C1R
 image_scale, [838](#)
 nppiScale_8u16u_C3R
 image_scale, [838](#)
 nppiScale_8u16u_C4R
 image_scale, [839](#)
 nppiScale_8u32f_AC4R
 image_scale, [839](#)
 nppiScale_8u32f_C1R
 image_scale, [839](#)
 nppiScale_8u32f_C3R
 image_scale, [840](#)
 nppiScale_8u32f_C4R
 image_scale, [840](#)
 nppiScale_8u32s_AC4R
 image_scale, [841](#)
 nppiScale_8u32s_C1R
 image_scale, [841](#)

- nppiScale_8u32s_C3R
 - image_scale, [841](#)
- nppiScale_8u32s_C4R
 - image_scale, [842](#)
- nppiSet_16s_AC4MR
 - image_set, [712](#)
- nppiSet_16s_AC4R
 - image_set, [713](#)
- nppiSet_16s_C1MR
 - image_set, [713](#)
- nppiSet_16s_C1R
 - image_set, [713](#)
- nppiSet_16s_C2R
 - image_set, [714](#)
- nppiSet_16s_C3CR
 - image_set, [714](#)
- nppiSet_16s_C3MR
 - image_set, [714](#)
- nppiSet_16s_C3R
 - image_set, [715](#)
- nppiSet_16s_C4CR
 - image_set, [715](#)
- nppiSet_16s_C4MR
 - image_set, [715](#)
- nppiSet_16s_C4R
 - image_set, [716](#)
- nppiSet_16sc_AC4R
 - image_set, [716](#)
- nppiSet_16sc_C1R
 - image_set, [716](#)
- nppiSet_16sc_C2R
 - image_set, [717](#)
- nppiSet_16sc_C3R
 - image_set, [717](#)
- nppiSet_16sc_C4R
 - image_set, [717](#)
- nppiSet_16u_AC4MR
 - image_set, [718](#)
- nppiSet_16u_AC4R
 - image_set, [718](#)
- nppiSet_16u_C1MR
 - image_set, [718](#)
- nppiSet_16u_C1R
 - image_set, [719](#)
- nppiSet_16u_C2R
 - image_set, [719](#)
- nppiSet_16u_C3CR
 - image_set, [719](#)
- nppiSet_16u_C3MR
 - image_set, [720](#)
- nppiSet_16u_C3R
 - image_set, [720](#)
- nppiSet_16u_C4CR
 - image_set, [720](#)
- nppiSet_16u_C4MR
 - image_set, [721](#)
- nppiSet_16u_C4R
 - image_set, [721](#)
- nppiSet_32f_AC4MR
 - image_set, [721](#)
- nppiSet_32f_AC4R
 - image_set, [722](#)
- nppiSet_32f_C1MR
 - image_set, [722](#)
- nppiSet_32f_C1R
 - image_set, [722](#)
- nppiSet_32f_C3CR
 - image_set, [723](#)
- nppiSet_32f_C3MR
 - image_set, [723](#)
- nppiSet_32f_C3R
 - image_set, [723](#)
- nppiSet_32f_C4CR
 - image_set, [724](#)
- nppiSet_32f_C4MR
 - image_set, [724](#)
- nppiSet_32f_C4R
 - image_set, [724](#)
- nppiSet_32fc_AC4R
 - image_set, [725](#)
- nppiSet_32fc_C1R
 - image_set, [725](#)
- nppiSet_32fc_C2R
 - image_set, [725](#)
- nppiSet_32fc_C3R
 - image_set, [726](#)
- nppiSet_32fc_C4R
 - image_set, [726](#)
- nppiSet_32s_AC4MR
 - image_set, [726](#)
- nppiSet_32s_AC4R
 - image_set, [727](#)
- nppiSet_32s_C1MR
 - image_set, [727](#)
- nppiSet_32s_C1R
 - image_set, [727](#)
- nppiSet_32s_C3CR
 - image_set, [728](#)
- nppiSet_32s_C3MR
 - image_set, [728](#)
- nppiSet_32s_C3R
 - image_set, [728](#)
- nppiSet_32s_C4CR
 - image_set, [729](#)
- nppiSet_32s_C4MR
 - image_set, [729](#)
- nppiSet_32s_C4R
 - image_set, [729](#)

- nppiSet_32sc_AC4R
 - image_set, 730
- nppiSet_32sc_C1R
 - image_set, 730
- nppiSet_32sc_C2R
 - image_set, 730
- nppiSet_32sc_C3R
 - image_set, 731
- nppiSet_32sc_C4R
 - image_set, 731
- nppiSet_8s_AC4R
 - image_set, 731
- nppiSet_8s_C1R
 - image_set, 732
- nppiSet_8s_C2R
 - image_set, 732
- nppiSet_8s_C3R
 - image_set, 732
- nppiSet_8s_C4R
 - image_set, 733
- nppiSet_8u_AC4MR
 - image_set, 733
- nppiSet_8u_AC4R
 - image_set, 733
- nppiSet_8u_C1MR
 - image_set, 734
- nppiSet_8u_C1R
 - image_set, 734
- nppiSet_8u_C3CR
 - image_set, 734
- nppiSet_8u_C3MR
 - image_set, 735
- nppiSet_8u_C3R
 - image_set, 735
- nppiSet_8u_C4CR
 - image_set, 735
- nppiSet_8u_C4MR
 - image_set, 736
- nppiSet_8u_C4R
 - image_set, 736
- NppiSize, 2333
 - height, 2333
 - width, 2333
- nppiSqr_16s_AC4IRSfs
 - image_sqr, 333
- nppiSqr_16s_AC4RSfs
 - image_sqr, 333
- nppiSqr_16s_C1IRSfs
 - image_sqr, 333
- nppiSqr_16s_C1RSfs
 - image_sqr, 333
- nppiSqr_16s_C3IRSfs
 - image_sqr, 334
- nppiSqr_16s_C3RSfs
 - image_sqr, 334
- image_sqr, 334
- nppiSqr_16s_C4IRSfs
 - image_sqr, 334
- nppiSqr_16s_C4RSfs
 - image_sqr, 335
- nppiSqr_16u_AC4IRSfs
 - image_sqr, 335
- nppiSqr_16u_AC4RSfs
 - image_sqr, 335
- nppiSqr_16u_C1IRSfs
 - image_sqr, 336
- nppiSqr_16u_C1RSfs
 - image_sqr, 336
- nppiSqr_16u_C3IRSfs
 - image_sqr, 337
- nppiSqr_16u_C3RSfs
 - image_sqr, 337
- nppiSqr_16u_C4IRSfs
 - image_sqr, 337
- nppiSqr_16u_C4RSfs
 - image_sqr, 338
- nppiSqr_32f_AC4IR
 - image_sqr, 338
- nppiSqr_32f_AC4R
 - image_sqr, 338
- nppiSqr_32f_C1IR
 - image_sqr, 339
- nppiSqr_32f_C1R
 - image_sqr, 339
- nppiSqr_32f_C3IR
 - image_sqr, 339
- nppiSqr_32f_C3R
 - image_sqr, 339
- nppiSqr_32f_C4IR
 - image_sqr, 340
- nppiSqr_32f_C4R
 - image_sqr, 340
- nppiSqr_8u_AC4IRSfs
 - image_sqr, 340
- nppiSqr_8u_AC4RSfs
 - image_sqr, 341
- nppiSqr_8u_C1IRSfs
 - image_sqr, 341
- nppiSqr_8u_C1RSfs
 - image_sqr, 341
- nppiSqr_8u_C3IRSfs
 - image_sqr, 342
- nppiSqr_8u_C3RSfs
 - image_sqr, 342
- nppiSqr_8u_C4IRSfs
 - image_sqr, 342
- nppiSqr_8u_C4RSfs
 - image_sqr, 343
- nppiSqrDistanceFull_Norm_16u32f_AC4R

- sqrdistancefullnorm, 1729
- nppiSqrDistanceFull_Norm_16u32f_C1R
 - sqrdistancefullnorm, 1729
- nppiSqrDistanceFull_Norm_16u32f_C3R
 - sqrdistancefullnorm, 1729
- nppiSqrDistanceFull_Norm_16u32f_C4R
 - sqrdistancefullnorm, 1730
- nppiSqrDistanceFull_Norm_32f_AC4R
 - sqrdistancefullnorm, 1730
- nppiSqrDistanceFull_Norm_32f_C1R
 - sqrdistancefullnorm, 1731
- nppiSqrDistanceFull_Norm_32f_C3R
 - sqrdistancefullnorm, 1731
- nppiSqrDistanceFull_Norm_32f_C4R
 - sqrdistancefullnorm, 1732
- nppiSqrDistanceFull_Norm_8s32f_AC4R
 - sqrdistancefullnorm, 1732
- nppiSqrDistanceFull_Norm_8s32f_C1R
 - sqrdistancefullnorm, 1732
- nppiSqrDistanceFull_Norm_8s32f_C3R
 - sqrdistancefullnorm, 1733
- nppiSqrDistanceFull_Norm_8s32f_C4R
 - sqrdistancefullnorm, 1733
- nppiSqrDistanceFull_Norm_8u32f_AC4R
 - sqrdistancefullnorm, 1734
- nppiSqrDistanceFull_Norm_8u32f_C1R
 - sqrdistancefullnorm, 1734
- nppiSqrDistanceFull_Norm_8u32f_C3R
 - sqrdistancefullnorm, 1735
- nppiSqrDistanceFull_Norm_8u32f_C4R
 - sqrdistancefullnorm, 1735
- nppiSqrDistanceFull_Norm_8u_AC4RSfs
 - sqrdistancefullnorm, 1735
- nppiSqrDistanceFull_Norm_8u_C1RSfs
 - sqrdistancefullnorm, 1736
- nppiSqrDistanceFull_Norm_8u_C3RSfs
 - sqrdistancefullnorm, 1736
- nppiSqrDistanceFull_Norm_8u_C4RSfs
 - sqrdistancefullnorm, 1737
- nppiSqrDistanceSame_Norm_16u32f_AC4R
 - sqrdistancesamenorm, 1740
- nppiSqrDistanceSame_Norm_16u32f_C1R
 - sqrdistancesamenorm, 1740
- nppiSqrDistanceSame_Norm_16u32f_C3R
 - sqrdistancesamenorm, 1741
- nppiSqrDistanceSame_Norm_16u32f_C4R
 - sqrdistancesamenorm, 1741
- nppiSqrDistanceSame_Norm_32f_AC4R
 - sqrdistancesamenorm, 1741
- nppiSqrDistanceSame_Norm_32f_C1R
 - sqrdistancesamenorm, 1742
- nppiSqrDistanceSame_Norm_32f_C3R
 - sqrdistancesamenorm, 1742
- nppiSqrDistanceSame_Norm_32f_C4R
 - sqrdistancesamenorm, 1743
- nppiSqrDistanceSame_Norm_8s32f_AC4R
 - sqrdistancesamenorm, 1743
- nppiSqrDistanceSame_Norm_8s32f_C1R
 - sqrdistancesamenorm, 1744
- nppiSqrDistanceSame_Norm_8s32f_C3R
 - sqrdistancesamenorm, 1744
- nppiSqrDistanceSame_Norm_8s32f_C4R
 - sqrdistancesamenorm, 1744
- nppiSqrDistanceSame_Norm_8u32f_AC4R
 - sqrdistancesamenorm, 1745
- nppiSqrDistanceSame_Norm_8u32f_C1R
 - sqrdistancesamenorm, 1745
- nppiSqrDistanceSame_Norm_8u32f_C3R
 - sqrdistancesamenorm, 1746
- nppiSqrDistanceSame_Norm_8u32f_C4R
 - sqrdistancesamenorm, 1746
- nppiSqrDistanceSame_Norm_8u_AC4RSfs
 - sqrdistancesamenorm, 1747
- nppiSqrDistanceSame_Norm_8u_C1RSfs
 - sqrdistancesamenorm, 1747
- nppiSqrDistanceSame_Norm_8u_C3RSfs
 - sqrdistancesamenorm, 1748
- nppiSqrDistanceSame_Norm_8u_C4RSfs
 - sqrdistancesamenorm, 1748
- nppiSqrDistanceValid_Norm_16u32f_AC4R
 - sqrdistancevalidnorm, 1751
- nppiSqrDistanceValid_Norm_16u32f_C1R
 - sqrdistancevalidnorm, 1751
- nppiSqrDistanceValid_Norm_16u32f_C3R
 - sqrdistancevalidnorm, 1752
- nppiSqrDistanceValid_Norm_16u32f_C4R
 - sqrdistancevalidnorm, 1752
- nppiSqrDistanceValid_Norm_32f_AC4R
 - sqrdistancevalidnorm, 1752
- nppiSqrDistanceValid_Norm_32f_C1R
 - sqrdistancevalidnorm, 1753
- nppiSqrDistanceValid_Norm_32f_C3R
 - sqrdistancevalidnorm, 1753
- nppiSqrDistanceValid_Norm_32f_C4R
 - sqrdistancevalidnorm, 1754
- nppiSqrDistanceValid_Norm_8s32f_AC4R
 - sqrdistancevalidnorm, 1754
- nppiSqrDistanceValid_Norm_8s32f_C1R
 - sqrdistancevalidnorm, 1755
- nppiSqrDistanceValid_Norm_8s32f_C3R
 - sqrdistancevalidnorm, 1755
- nppiSqrDistanceValid_Norm_8s32f_C4R
 - sqrdistancevalidnorm, 1755
- nppiSqrDistanceValid_Norm_8u32f_AC4R
 - sqrdistancevalidnorm, 1756
- nppiSqrDistanceValid_Norm_8u32f_C1R
 - sqrdistancevalidnorm, 1756
- nppiSqrDistanceValid_Norm_8u32f_C3R

- sqrdistancevalidnorm, [1757](#)
- nppiSqrDistanceValid_Norm_8u32f_C4R
 - sqrdistancevalidnorm, [1757](#)
- nppiSqrDistanceValid_Norm_8u_AC4RSfs
 - sqrdistancevalidnorm, [1758](#)
- nppiSqrDistanceValid_Norm_8u_C1RSfs
 - sqrdistancevalidnorm, [1758](#)
- nppiSqrDistanceValid_Norm_8u_C3RSfs
 - sqrdistancevalidnorm, [1759](#)
- nppiSqrDistanceValid_Norm_8u_C4RSfs
 - sqrdistancevalidnorm, [1759](#)
- nppiSqrIntegral_8u32f64f_C1R
 - image_sqrtintegral, [1689](#)
- nppiSqrIntegral_8u32s64f_C1R
 - image_sqrtintegral, [1690](#)
- nppiSqrIntegral_8u32s_C1R
 - image_sqrtintegral, [1690](#)
- nppiSqrt_16s_AC4IRSfs
 - image_sqrt, [346](#)
- nppiSqrt_16s_AC4RSfs
 - image_sqrt, [346](#)
- nppiSqrt_16s_C1IRSfs
 - image_sqrt, [347](#)
- nppiSqrt_16s_C1RSfs
 - image_sqrt, [347](#)
- nppiSqrt_16s_C3IRSfs
 - image_sqrt, [348](#)
- nppiSqrt_16s_C3RSfs
 - image_sqrt, [348](#)
- nppiSqrt_16u_AC4IRSfs
 - image_sqrt, [348](#)
- nppiSqrt_16u_AC4RSfs
 - image_sqrt, [349](#)
- nppiSqrt_16u_C1IRSfs
 - image_sqrt, [349](#)
- nppiSqrt_16u_C1RSfs
 - image_sqrt, [349](#)
- nppiSqrt_16u_C3IRSfs
 - image_sqrt, [350](#)
- nppiSqrt_16u_C3RSfs
 - image_sqrt, [350](#)
- nppiSqrt_32f_AC4IR
 - image_sqrt, [350](#)
- nppiSqrt_32f_AC4R
 - image_sqrt, [351](#)
- nppiSqrt_32f_C1IR
 - image_sqrt, [351](#)
- nppiSqrt_32f_C1R
 - image_sqrt, [351](#)
- nppiSqrt_32f_C3IR
 - image_sqrt, [352](#)
- nppiSqrt_32f_C3R
 - image_sqrt, [352](#)
- nppiSqrt_32f_C4IR
 - image_sqrt, [352](#)
- nppiSqrt_32f_C4R
 - image_sqrt, [353](#)
- nppiSqrt_8u_AC4IRSfs
 - image_sqrt, [353](#)
- nppiSqrt_8u_AC4RSfs
 - image_sqrt, [353](#)
- nppiSqrt_8u_C1IRSfs
 - image_sqrt, [354](#)
- nppiSqrt_8u_C1RSfs
 - image_sqrt, [354](#)
- nppiSqrt_8u_C3IRSfs
 - image_sqrt, [355](#)
- nppiSqrt_8u_C3RSfs
 - image_sqrt, [355](#)
- nppiSub_16s_AC4IRSfs
 - image_sub, [251](#)
- nppiSub_16s_AC4RSfs
 - image_sub, [252](#)
- nppiSub_16s_C1IRSfs
 - image_sub, [252](#)
- nppiSub_16s_C1RSfs
 - image_sub, [252](#)
- nppiSub_16s_C3IRSfs
 - image_sub, [253](#)
- nppiSub_16s_C3RSfs
 - image_sub, [253](#)
- nppiSub_16s_C4IRSfs
 - image_sub, [254](#)
- nppiSub_16s_C4RSfs
 - image_sub, [254](#)
- nppiSub_16sc_AC4IRSfs
 - image_sub, [254](#)
- nppiSub_16sc_AC4RSfs
 - image_sub, [255](#)
- nppiSub_16sc_C1IRSfs
 - image_sub, [255](#)
- nppiSub_16sc_C1RSfs
 - image_sub, [256](#)
- nppiSub_16sc_C3IRSfs
 - image_sub, [256](#)
- nppiSub_16sc_C3RSfs
 - image_sub, [256](#)
- nppiSub_16u_AC4IRSfs
 - image_sub, [257](#)
- nppiSub_16u_AC4RSfs
 - image_sub, [257](#)
- nppiSub_16u_C1IRSfs
 - image_sub, [258](#)
- nppiSub_16u_C1RSfs
 - image_sub, [258](#)
- nppiSub_16u_C3IRSfs
 - image_sub, [259](#)
- nppiSub_16u_C3RSfs

image_sub, 259
 nppiSub_16u_C4IRSfs
 image_sub, 259
 nppiSub_16u_C4RSfs
 image_sub, 260
 nppiSub_32f_AC4IR
 image_sub, 260
 nppiSub_32f_AC4R
 image_sub, 261
 nppiSub_32f_C1IR
 image_sub, 261
 nppiSub_32f_C1R
 image_sub, 261
 nppiSub_32f_C3IR
 image_sub, 262
 nppiSub_32f_C3R
 image_sub, 262
 nppiSub_32f_C4IR
 image_sub, 263
 nppiSub_32f_C4R
 image_sub, 263
 nppiSub_32fc_AC4IR
 image_sub, 263
 nppiSub_32fc_AC4R
 image_sub, 264
 nppiSub_32fc_C1IR
 image_sub, 264
 nppiSub_32fc_C1R
 image_sub, 265
 nppiSub_32fc_C3IR
 image_sub, 265
 nppiSub_32fc_C3R
 image_sub, 265
 nppiSub_32fc_C4IR
 image_sub, 266
 nppiSub_32fc_C4R
 image_sub, 266
 nppiSub_32s_C1IRSfs
 image_sub, 267
 nppiSub_32s_C1R
 image_sub, 267
 nppiSub_32s_C1RSfs
 image_sub, 267
 nppiSub_32s_C3IRSfs
 image_sub, 268
 nppiSub_32s_C3RSfs
 image_sub, 268
 nppiSub_32s_C4IRSfs
 image_sub, 269
 nppiSub_32s_C4RSfs
 image_sub, 269
 nppiSub_32sc_AC4IRSfs
 image_sub, 270
 nppiSub_32sc_AC4RSfs

image_sub, 270
 nppiSub_32sc_C1IRSfs
 image_sub, 270
 nppiSub_32sc_C1RSfs
 image_sub, 271
 nppiSub_32sc_C3IRSfs
 image_sub, 271
 nppiSub_32sc_C3RSfs
 image_sub, 272
 nppiSub_8u_AC4IRSfs
 image_sub, 272
 nppiSub_8u_AC4RSfs
 image_sub, 272
 nppiSub_8u_C1IRSfs
 image_sub, 273
 nppiSub_8u_C1RSfs
 image_sub, 273
 nppiSub_8u_C3IRSfs
 image_sub, 274
 nppiSub_8u_C3RSfs
 image_sub, 274
 nppiSub_8u_C4IRSfs
 image_sub, 274
 nppiSub_8u_C4RSfs
 image_sub, 275
 nppiSubC_16s_AC4IRSfs
 image_subc, 119
 nppiSubC_16s_AC4RSfs
 image_subc, 119
 nppiSubC_16s_C1IRSfs
 image_subc, 119
 nppiSubC_16s_C1RSfs
 image_subc, 120
 nppiSubC_16s_C3IRSfs
 image_subc, 120
 nppiSubC_16s_C3RSfs
 image_subc, 120
 nppiSubC_16s_C4IRSfs
 image_subc, 121
 nppiSubC_16s_C4RSfs
 image_subc, 121
 nppiSubC_16sc_AC4IRSfs
 image_subc, 122
 nppiSubC_16sc_AC4RSfs
 image_subc, 122
 nppiSubC_16sc_C1IRSfs
 image_subc, 122
 nppiSubC_16sc_C1RSfs
 image_subc, 123
 nppiSubC_16sc_C3IRSfs
 image_subc, 123
 nppiSubC_16sc_C3RSfs
 image_subc, 124
 nppiSubC_16u_AC4IRSfs

- image_subc, 124
- nppiSubC_16u_AC4RSfs
 - image_subc, 124
- nppiSubC_16u_C1IRSfs
 - image_subc, 125
- nppiSubC_16u_C1RSfs
 - image_subc, 125
- nppiSubC_16u_C3IRSfs
 - image_subc, 126
- nppiSubC_16u_C3RSfs
 - image_subc, 126
- nppiSubC_16u_C4IRSfs
 - image_subc, 126
- nppiSubC_16u_C4RSfs
 - image_subc, 127
- nppiSubC_32f_AC4IR
 - image_subc, 127
- nppiSubC_32f_AC4R
 - image_subc, 127
- nppiSubC_32f_C1IR
 - image_subc, 128
- nppiSubC_32f_C1R
 - image_subc, 128
- nppiSubC_32f_C3IR
 - image_subc, 128
- nppiSubC_32f_C3R
 - image_subc, 129
- nppiSubC_32f_C4IR
 - image_subc, 129
- nppiSubC_32f_C4R
 - image_subc, 129
- nppiSubC_32fc_AC4IR
 - image_subc, 130
- nppiSubC_32fc_AC4R
 - image_subc, 130
- nppiSubC_32fc_C1IR
 - image_subc, 130
- nppiSubC_32fc_C1R
 - image_subc, 131
- nppiSubC_32fc_C3IR
 - image_subc, 131
- nppiSubC_32fc_C3R
 - image_subc, 131
- nppiSubC_32fc_C4IR
 - image_subc, 132
- nppiSubC_32fc_C4R
 - image_subc, 132
- nppiSubC_32s_C1IRSfs
 - image_subc, 133
- nppiSubC_32s_C1RSfs
 - image_subc, 133
- nppiSubC_32s_C3IRSfs
 - image_subc, 133
- nppiSubC_32s_C3RSfs
 - image_subc, 134
- nppiSubC_32sc_AC4IRSfs
 - image_subc, 134
- nppiSubC_32sc_AC4RSfs
 - image_subc, 134
- nppiSubC_32sc_C1IRSfs
 - image_subc, 135
- nppiSubC_32sc_C1RSfs
 - image_subc, 135
- nppiSubC_32sc_C3IRSfs
 - image_subc, 136
- nppiSubC_32sc_C3RSfs
 - image_subc, 136
- nppiSubC_8u_AC4IRSfs
 - image_subc, 136
- nppiSubC_8u_AC4RSfs
 - image_subc, 137
- nppiSubC_8u_C1IRSfs
 - image_subc, 137
- nppiSubC_8u_C1RSfs
 - image_subc, 138
- nppiSubC_8u_C3IRSfs
 - image_subc, 138
- nppiSubC_8u_C3RSfs
 - image_subc, 138
- nppiSubC_8u_C4IRSfs
 - image_subc, 139
- nppiSubC_8u_C4RSfs
 - image_subc, 139
- nppiSum_16s_AC4R
 - image_sum, 1304
- nppiSum_16s_C1R
 - image_sum, 1304
- nppiSum_16s_C3R
 - image_sum, 1304
- nppiSum_16s_C4R
 - image_sum, 1305
- nppiSum_16u_AC4R
 - image_sum, 1305
- nppiSum_16u_C1R
 - image_sum, 1305
- nppiSum_16u_C3R
 - image_sum, 1306
- nppiSum_16u_C4R
 - image_sum, 1306
- nppiSum_32f_AC4R
 - image_sum, 1306
- nppiSum_32f_C1R
 - image_sum, 1307
- nppiSum_32f_C3R
 - image_sum, 1307
- nppiSum_32f_C4R
 - image_sum, 1307
- nppiSum_8u64s_C1R

- image_sum, 1308
- nppiSum_8u64s_C4R
 - image_sum, 1308
- nppiSum_8u_AC4R
 - image_sum, 1309
- nppiSum_8u_C1R
 - image_sum, 1309
- nppiSum_8u_C3R
 - image_sum, 1309
- nppiSum_8u_C4R
 - image_sum, 1310
- nppiSumGetBufferHostSize_16s_AC4R
 - image_sum, 1310
- nppiSumGetBufferHostSize_16s_C1R
 - image_sum, 1310
- nppiSumGetBufferHostSize_16s_C3R
 - image_sum, 1311
- nppiSumGetBufferHostSize_16s_C4R
 - image_sum, 1311
- nppiSumGetBufferHostSize_16u_AC4R
 - image_sum, 1311
- nppiSumGetBufferHostSize_16u_C1R
 - image_sum, 1312
- nppiSumGetBufferHostSize_16u_C3R
 - image_sum, 1312
- nppiSumGetBufferHostSize_16u_C4R
 - image_sum, 1312
- nppiSumGetBufferHostSize_32f_AC4R
 - image_sum, 1312
- nppiSumGetBufferHostSize_32f_C1R
 - image_sum, 1313
- nppiSumGetBufferHostSize_32f_C3R
 - image_sum, 1313
- nppiSumGetBufferHostSize_32f_C4R
 - image_sum, 1313
- nppiSumGetBufferHostSize_8u64s_C1R
 - image_sum, 1314
- nppiSumGetBufferHostSize_8u64s_C4R
 - image_sum, 1314
- nppiSumGetBufferHostSize_8u_AC4R
 - image_sum, 1314
- nppiSumGetBufferHostSize_8u_C1R
 - image_sum, 1314
- nppiSumGetBufferHostSize_8u_C3R
 - image_sum, 1315
- nppiSumGetBufferHostSize_8u_C4R
 - image_sum, 1315
- nppiSumWindowColumn_8u32f_C1R
 - image_1D_window_sum, 1007
- nppiSumWindowRow_8u32f_C1R
 - image_1D_window_sum, 1007
- nppiSwapChannels_16s_AC4R
 - image_swap_channels, 909
- nppiSwapChannels_16s_C3C4R
 - image_swap_channels, 909
- nppiSwapChannels_16s_C3R
 - image_swap_channels, 909
- nppiSwapChannels_16s_C4C3R
 - image_swap_channels, 910
- nppiSwapChannels_16s_C4R
 - image_swap_channels, 910
- nppiSwapChannels_16s_C4R
 - image_swap_channels, 911
- nppiSwapChannels_16u_AC4R
 - image_swap_channels, 911
- nppiSwapChannels_16u_C3C4R
 - image_swap_channels, 911
- nppiSwapChannels_16u_C3IR
 - image_swap_channels, 912
- nppiSwapChannels_16u_C3R
 - image_swap_channels, 912
- nppiSwapChannels_16u_C4C3R
 - image_swap_channels, 913
- nppiSwapChannels_16u_C4R
 - image_swap_channels, 913
- nppiSwapChannels_16u_C4IR
 - image_swap_channels, 914
- nppiSwapChannels_16u_C4R
 - image_swap_channels, 914
- nppiSwapChannels_32f_AC4R
 - image_swap_channels, 914
- nppiSwapChannels_32f_C3C4R
 - image_swap_channels, 915
- nppiSwapChannels_32f_C3IR
 - image_swap_channels, 915
- nppiSwapChannels_32f_C3R
 - image_swap_channels, 916
- nppiSwapChannels_32f_C4C3R
 - image_swap_channels, 916
- nppiSwapChannels_32f_C4IR
 - image_swap_channels, 917
- nppiSwapChannels_32f_C4R
 - image_swap_channels, 917
- nppiSwapChannels_32s_AC4R
 - image_swap_channels, 917
- nppiSwapChannels_32s_C3C4R
 - image_swap_channels, 918
- nppiSwapChannels_32s_C3IR
 - image_swap_channels, 918
- nppiSwapChannels_32s_C3R
 - image_swap_channels, 919
- nppiSwapChannels_32s_C4C3R
 - image_swap_channels, 919
- nppiSwapChannels_32s_C4IR
 - image_swap_channels, 920
- nppiSwapChannels_32s_C4R
 - image_swap_channels, 920
- nppiSwapChannels_8u_AC4R

- image_swap_channels, 920
- nppiSwapChannels_8u_C3C4R
 - image_swap_channels, 921
- nppiSwapChannels_8u_C3IR
 - image_swap_channels, 921
- nppiSwapChannels_8u_C3R
 - image_swap_channels, 922
- nppiSwapChannels_8u_C4C3R
 - image_swap_channels, 922
- nppiSwapChannels_8u_C4IR
 - image_swap_channels, 923
- nppiSwapChannels_8u_C4R
 - image_swap_channels, 923
- nppiThreshold_16s_AC4IR
 - image_threshold_operations, 1892
- nppiThreshold_16s_AC4R
 - image_threshold_operations, 1892
- nppiThreshold_16s_C1IR
 - image_threshold_operations, 1893
- nppiThreshold_16s_C1R
 - image_threshold_operations, 1893
- nppiThreshold_16s_C3IR
 - image_threshold_operations, 1894
- nppiThreshold_16s_C3R
 - image_threshold_operations, 1894
- nppiThreshold_16u_AC4IR
 - image_threshold_operations, 1895
- nppiThreshold_16u_AC4R
 - image_threshold_operations, 1895
- nppiThreshold_16u_C1IR
 - image_threshold_operations, 1895
- nppiThreshold_16u_C1R
 - image_threshold_operations, 1896
- nppiThreshold_16u_C3IR
 - image_threshold_operations, 1896
- nppiThreshold_16u_C3R
 - image_threshold_operations, 1897
- nppiThreshold_32f_AC4IR
 - image_threshold_operations, 1897
- nppiThreshold_32f_AC4R
 - image_threshold_operations, 1898
- nppiThreshold_32f_C1IR
 - image_threshold_operations, 1898
- nppiThreshold_32f_C1R
 - image_threshold_operations, 1899
- nppiThreshold_32f_C3IR
 - image_threshold_operations, 1899
- nppiThreshold_32f_C3R
 - image_threshold_operations, 1899
- nppiThreshold_8u_AC4IR
 - image_threshold_operations, 1900
- nppiThreshold_8u_AC4R
 - image_threshold_operations, 1900
- nppiThreshold_8u_C1IR
 - image_threshold_operations, 1901
- nppiThreshold_8u_C1R
 - image_threshold_operations, 1901
- nppiThreshold_8u_C3IR
 - image_threshold_operations, 1902
- nppiThreshold_8u_C3R
 - image_threshold_operations, 1902
- nppiThreshold_GT_16s_AC4IR
 - image_threshold_operations, 1902
- nppiThreshold_GT_16s_AC4R
 - image_threshold_operations, 1903
- nppiThreshold_GT_16s_C1IR
 - image_threshold_operations, 1903
- nppiThreshold_GT_16s_C1R
 - image_threshold_operations, 1904
- nppiThreshold_GT_16s_C3IR
 - image_threshold_operations, 1904
- nppiThreshold_GT_16s_C3R
 - image_threshold_operations, 1904
- nppiThreshold_GT_16u_AC4IR
 - image_threshold_operations, 1905
- nppiThreshold_GT_16u_AC4R
 - image_threshold_operations, 1905
- nppiThreshold_GT_16u_C1IR
 - image_threshold_operations, 1906
- nppiThreshold_GT_16u_C1R
 - image_threshold_operations, 1906
- nppiThreshold_GT_16u_C3IR
 - image_threshold_operations, 1906
- nppiThreshold_GT_16u_C3R
 - image_threshold_operations, 1907
- nppiThreshold_GT_32f_AC4IR
 - image_threshold_operations, 1908
- nppiThreshold_GT_32f_AC4R
 - image_threshold_operations, 1908
- nppiThreshold_GT_32f_C1IR
 - image_threshold_operations, 1908
- nppiThreshold_GT_32f_C1R
 - image_threshold_operations, 1909
- nppiThreshold_GT_32f_C3IR
 - image_threshold_operations, 1909
- nppiThreshold_GT_32f_C3R
 - image_threshold_operations, 1910
- nppiThreshold_GT_8u_AC4IR
 - image_threshold_operations, 1910
- nppiThreshold_GT_8u_AC4R
 - image_threshold_operations, 1910
- nppiThreshold_GT_8u_C1IR
 - image_threshold_operations, 1911
- nppiThreshold_GT_8u_C1R
 - image_threshold_operations, 1911
- nppiThreshold_GT_8u_C3IR
 - image_threshold_operations, 1912
- nppiThreshold_GT_8u_C3R
 - image_threshold_operations, 1912

- image_threshold_operations, 1912
- nppiThreshold_GTVal_16s_AC4IR
 - image_threshold_operations, 1912
- nppiThreshold_GTVal_16s_AC4R
 - image_threshold_operations, 1913
- nppiThreshold_GTVal_16s_C1IR
 - image_threshold_operations, 1913
- nppiThreshold_GTVal_16s_C1R
 - image_threshold_operations, 1914
- nppiThreshold_GTVal_16s_C3IR
 - image_threshold_operations, 1914
- nppiThreshold_GTVal_16s_C3R
 - image_threshold_operations, 1914
- nppiThreshold_GTVal_16u_AC4IR
 - image_threshold_operations, 1915
- nppiThreshold_GTVal_16u_AC4R
 - image_threshold_operations, 1915
- nppiThreshold_GTVal_16u_C1IR
 - image_threshold_operations, 1916
- nppiThreshold_GTVal_16u_C1R
 - image_threshold_operations, 1916
- nppiThreshold_GTVal_16u_C3IR
 - image_threshold_operations, 1917
- nppiThreshold_GTVal_16u_C3R
 - image_threshold_operations, 1917
- nppiThreshold_GTVal_32f_AC4IR
 - image_threshold_operations, 1917
- nppiThreshold_GTVal_32f_AC4R
 - image_threshold_operations, 1918
- nppiThreshold_GTVal_32f_C1IR
 - image_threshold_operations, 1918
- nppiThreshold_GTVal_32f_C1R
 - image_threshold_operations, 1919
- nppiThreshold_GTVal_32f_C3IR
 - image_threshold_operations, 1919
- nppiThreshold_GTVal_32f_C3R
 - image_threshold_operations, 1919
- nppiThreshold_GTVal_8u_AC4IR
 - image_threshold_operations, 1920
- nppiThreshold_GTVal_8u_AC4R
 - image_threshold_operations, 1920
- nppiThreshold_GTVal_8u_C1IR
 - image_threshold_operations, 1921
- nppiThreshold_GTVal_8u_C1R
 - image_threshold_operations, 1921
- nppiThreshold_GTVal_8u_C3IR
 - image_threshold_operations, 1922
- nppiThreshold_GTVal_8u_C3R
 - image_threshold_operations, 1922
- nppiThreshold_LT_16s_AC4IR
 - image_threshold_operations, 1922
- nppiThreshold_LT_16s_AC4R
 - image_threshold_operations, 1923
- nppiThreshold_LT_16s_C1IR
 - image_threshold_operations, 1923
- nppiThreshold_LT_16s_C1R
 - image_threshold_operations, 1924
- nppiThreshold_LT_16s_C3IR
 - image_threshold_operations, 1924
- nppiThreshold_LT_16s_C3R
 - image_threshold_operations, 1924
- nppiThreshold_LT_16u_AC4IR
 - image_threshold_operations, 1925
- nppiThreshold_LT_16u_AC4R
 - image_threshold_operations, 1925
- nppiThreshold_LT_16u_C1IR
 - image_threshold_operations, 1926
- nppiThreshold_LT_16u_C1R
 - image_threshold_operations, 1926
- nppiThreshold_LT_16u_C3IR
 - image_threshold_operations, 1926
- nppiThreshold_LT_16u_C3R
 - image_threshold_operations, 1927
- nppiThreshold_LT_32f_AC4IR
 - image_threshold_operations, 1927
- nppiThreshold_LT_32f_AC4R
 - image_threshold_operations, 1928
- nppiThreshold_LT_32f_C1IR
 - image_threshold_operations, 1928
- nppiThreshold_LT_32f_C1R
 - image_threshold_operations, 1928
- nppiThreshold_LT_32f_C3IR
 - image_threshold_operations, 1929
- nppiThreshold_LT_32f_C3R
 - image_threshold_operations, 1929
- nppiThreshold_LT_8u_AC4IR
 - image_threshold_operations, 1930
- nppiThreshold_LT_8u_AC4R
 - image_threshold_operations, 1930
- nppiThreshold_LT_8u_C1IR
 - image_threshold_operations, 1930
- nppiThreshold_LT_8u_C1R
 - image_threshold_operations, 1931
- nppiThreshold_LT_8u_C3IR
 - image_threshold_operations, 1931
- nppiThreshold_LT_8u_C3R
 - image_threshold_operations, 1932
- nppiThreshold_LTVal_16s_AC4IR
 - image_threshold_operations, 1932
- nppiThreshold_LTVal_16s_AC4R
 - image_threshold_operations, 1932
- nppiThreshold_LTVal_16s_C1IR
 - image_threshold_operations, 1933
- nppiThreshold_LTVal_16s_C1R
 - image_threshold_operations, 1933
- nppiThreshold_LTVal_16s_C3IR
 - image_threshold_operations, 1934
- nppiThreshold_LTVal_16s_C3R
 - image_threshold_operations, 1934

- image_threshold_operations, 1934
- nppiThreshold_LTVa1_16u_AC4IR
 - image_threshold_operations, 1935
- nppiThreshold_LTVa1_16u_AC4R
 - image_threshold_operations, 1935
- nppiThreshold_LTVa1_16u_C1IR
 - image_threshold_operations, 1935
- nppiThreshold_LTVa1_16u_C1R
 - image_threshold_operations, 1936
- nppiThreshold_LTVa1_16u_C3IR
 - image_threshold_operations, 1936
- nppiThreshold_LTVa1_16u_C3R
 - image_threshold_operations, 1937
- nppiThreshold_LTVa1_32f_AC4IR
 - image_threshold_operations, 1937
- nppiThreshold_LTVa1_32f_AC4R
 - image_threshold_operations, 1937
- nppiThreshold_LTVa1_32f_C1IR
 - image_threshold_operations, 1938
- nppiThreshold_LTVa1_32f_C1R
 - image_threshold_operations, 1938
- nppiThreshold_LTVa1_32f_C3IR
 - image_threshold_operations, 1939
- nppiThreshold_LTVa1_32f_C3R
 - image_threshold_operations, 1939
- nppiThreshold_LTVa1_8u_AC4IR
 - image_threshold_operations, 1940
- nppiThreshold_LTVa1_8u_AC4R
 - image_threshold_operations, 1940
- nppiThreshold_LTVa1_8u_C1IR
 - image_threshold_operations, 1940
- nppiThreshold_LTVa1_8u_C1R
 - image_threshold_operations, 1941
- nppiThreshold_LTVa1_8u_C3IR
 - image_threshold_operations, 1941
- nppiThreshold_LTVa1_8u_C3R
 - image_threshold_operations, 1942
- nppiThreshold_LTVa1GTVal_16s_AC4IR
 - image_threshold_operations, 1942
- nppiThreshold_LTVa1GTVal_16s_AC4R
 - image_threshold_operations, 1943
- nppiThreshold_LTVa1GTVal_16s_C1IR
 - image_threshold_operations, 1943
- nppiThreshold_LTVa1GTVal_16s_C1R
 - image_threshold_operations, 1944
- nppiThreshold_LTVa1GTVal_16s_C3IR
 - image_threshold_operations, 1944
- nppiThreshold_LTVa1GTVal_16s_C3R
 - image_threshold_operations, 1945
- nppiThreshold_LTVa1GTVal_16u_AC4IR
 - image_threshold_operations, 1945
- nppiThreshold_LTVa1GTVal_16u_AC4R
 - image_threshold_operations, 1946
- nppiThreshold_LTVa1GTVal_16u_C1IR
 - image_threshold_operations, 1946
- nppiThreshold_LTVa1GTVal_16u_C1R
 - image_threshold_operations, 1947
- nppiThreshold_LTVa1GTVal_16u_C3IR
 - image_threshold_operations, 1947
- nppiThreshold_LTVa1GTVal_16u_C3R
 - image_threshold_operations, 1948
- nppiThreshold_LTVa1GTVal_32f_AC4IR
 - image_threshold_operations, 1948
- nppiThreshold_LTVa1GTVal_32f_AC4R
 - image_threshold_operations, 1949
- nppiThreshold_LTVa1GTVal_32f_C1IR
 - image_threshold_operations, 1949
- nppiThreshold_LTVa1GTVal_32f_C1R
 - image_threshold_operations, 1950
- nppiThreshold_LTVa1GTVal_32f_C3IR
 - image_threshold_operations, 1950
- nppiThreshold_LTVa1GTVal_32f_C3R
 - image_threshold_operations, 1951
- nppiThreshold_LTVa1GTVal_8u_AC4IR
 - image_threshold_operations, 1951
- nppiThreshold_LTVa1GTVal_8u_AC4R
 - image_threshold_operations, 1952
- nppiThreshold_LTVa1GTVal_8u_C1IR
 - image_threshold_operations, 1952
- nppiThreshold_LTVa1GTVal_8u_C1R
 - image_threshold_operations, 1953
- nppiThreshold_LTVa1GTVal_8u_C3IR
 - image_threshold_operations, 1953
- nppiThreshold_LTVa1GTVal_8u_C3R
 - image_threshold_operations, 1954
- nppiThreshold_Val_16s_AC4IR
 - image_threshold_operations, 1954
- nppiThreshold_Val_16s_AC4R
 - image_threshold_operations, 1955
- nppiThreshold_Val_16s_C1IR
 - image_threshold_operations, 1955
- nppiThreshold_Val_16s_C1R
 - image_threshold_operations, 1956
- nppiThreshold_Val_16s_C3IR
 - image_threshold_operations, 1956
- nppiThreshold_Val_16s_C3R
 - image_threshold_operations, 1957
- nppiThreshold_Val_16u_AC4IR
 - image_threshold_operations, 1957
- nppiThreshold_Val_16u_AC4R
 - image_threshold_operations, 1958
- nppiThreshold_Val_16u_C1IR
 - image_threshold_operations, 1958
- nppiThreshold_Val_16u_C1R
 - image_threshold_operations, 1959
- nppiThreshold_Val_16u_C3IR
 - image_threshold_operations, 1959
- nppiThreshold_Val_16u_C3R

- image_threshold_operations, 1960
- nppiThreshold_Val_32f_AC4IR
 - image_threshold_operations, 1960
- nppiThreshold_Val_32f_AC4R
 - image_threshold_operations, 1961
- nppiThreshold_Val_32f_C1IR
 - image_threshold_operations, 1961
- nppiThreshold_Val_32f_C1R
 - image_threshold_operations, 1962
- nppiThreshold_Val_32f_C3IR
 - image_threshold_operations, 1962
- nppiThreshold_Val_32f_C3R
 - image_threshold_operations, 1963
- nppiThreshold_Val_8u_AC4IR
 - image_threshold_operations, 1963
- nppiThreshold_Val_8u_AC4R
 - image_threshold_operations, 1964
- nppiThreshold_Val_8u_C1IR
 - image_threshold_operations, 1964
- nppiThreshold_Val_8u_C1R
 - image_threshold_operations, 1965
- nppiThreshold_Val_8u_C3IR
 - image_threshold_operations, 1965
- nppiThreshold_Val_8u_C3R
 - image_threshold_operations, 1966
- nppiTranspose_16s_C1R
 - image_transpose, 900
- nppiTranspose_16s_C3R
 - image_transpose, 900
- nppiTranspose_16s_C4R
 - image_transpose, 901
- nppiTranspose_16u_C1R
 - image_transpose, 901
- nppiTranspose_16u_C3R
 - image_transpose, 901
- nppiTranspose_16u_C4R
 - image_transpose, 902
- nppiTranspose_32f_C1R
 - image_transpose, 902
- nppiTranspose_32f_C3R
 - image_transpose, 902
- nppiTranspose_32f_C4R
 - image_transpose, 903
- nppiTranspose_32s_C1R
 - image_transpose, 903
- nppiTranspose_32s_C3R
 - image_transpose, 903
- nppiTranspose_32s_C4R
 - image_transpose, 904
- nppiTranspose_8u_C1R
 - image_transpose, 904
- nppiTranspose_8u_C3R
 - image_transpose, 904
- nppiTranspose_8u_C4R
 - image_transpose, 905
- nppiValidNormLevelGetBufferSize_16u32f_-AC4R
 - crosscorrvalidnormlevel, 1849
- nppiValidNormLevelGetBufferSize_16u32f_-C1R
 - crosscorrvalidnormlevel, 1850
- nppiValidNormLevelGetBufferSize_16u32f_-C3R
 - crosscorrvalidnormlevel, 1850
- nppiValidNormLevelGetBufferSize_16u32f_-C4R
 - crosscorrvalidnormlevel, 1850
- nppiValidNormLevelGetBufferSize_32f_-AC4R
 - crosscorrvalidnormlevel, 1851
- nppiValidNormLevelGetBufferSize_32f_C1R
 - crosscorrvalidnormlevel, 1851
- nppiValidNormLevelGetBufferSize_32f_C3R
 - crosscorrvalidnormlevel, 1851
- nppiValidNormLevelGetBufferSize_32f_C4R
 - crosscorrvalidnormlevel, 1851
- nppiValidNormLevelGetBufferSize_8s32f_-AC4R
 - crosscorrvalidnormlevel, 1852
- nppiValidNormLevelGetBufferSize_8s32f_-C1R
 - crosscorrvalidnormlevel, 1852
- nppiValidNormLevelGetBufferSize_8s32f_-C3R
 - crosscorrvalidnormlevel, 1852
- nppiValidNormLevelGetBufferSize_8s32f_-C4R
 - crosscorrvalidnormlevel, 1853
- nppiValidNormLevelGetBufferSize_8u32f_-AC4R
 - crosscorrvalidnormlevel, 1853
- nppiValidNormLevelGetBufferSize_8u32f_-C1R
 - crosscorrvalidnormlevel, 1853
- nppiValidNormLevelGetBufferSize_8u32f_-C3R
 - crosscorrvalidnormlevel, 1853
- nppiValidNormLevelGetBufferSize_8u32f_-C4R
 - crosscorrvalidnormlevel, 1854
- nppiValidNormLevelGetBufferSize_8u_-AC4RSfs
 - crosscorrvalidnormlevel, 1854
- nppiValidNormLevelGetBufferSize_8u_-C1RSfs
 - crosscorrvalidnormlevel, 1854
- nppiValidNormLevelGetBufferSize_8u_-C3RSfs
 - crosscorrvalidnormlevel, 1854

- crosscorrvalidnormlevel, 1855
- nppiValidNormLevelGetBufferHostSize_8u_-C4RSfs
 - crosscorrvalidnormlevel, 1855
- nppiWarpAffine_16u_AC4R
 - image_affine_transform, 1183
- nppiWarpAffine_16u_C1R
 - image_affine_transform, 1184
- nppiWarpAffine_16u_C3R
 - image_affine_transform, 1184
- nppiWarpAffine_16u_C4R
 - image_affine_transform, 1185
- nppiWarpAffine_16u_P3R
 - image_affine_transform, 1185
- nppiWarpAffine_16u_P4R
 - image_affine_transform, 1186
- nppiWarpAffine_32f_AC4R
 - image_affine_transform, 1186
- nppiWarpAffine_32f_C1R
 - image_affine_transform, 1187
- nppiWarpAffine_32f_C3R
 - image_affine_transform, 1187
- nppiWarpAffine_32f_C4R
 - image_affine_transform, 1188
- nppiWarpAffine_32f_P3R
 - image_affine_transform, 1188
- nppiWarpAffine_32f_P4R
 - image_affine_transform, 1189
- nppiWarpAffine_32s_AC4R
 - image_affine_transform, 1189
- nppiWarpAffine_32s_C1R
 - image_affine_transform, 1190
- nppiWarpAffine_32s_C3R
 - image_affine_transform, 1190
- nppiWarpAffine_32s_C4R
 - image_affine_transform, 1191
- nppiWarpAffine_32s_P3R
 - image_affine_transform, 1191
- nppiWarpAffine_32s_P4R
 - image_affine_transform, 1192
- nppiWarpAffine_64f_AC4R
 - image_affine_transform, 1192
- nppiWarpAffine_64f_C1R
 - image_affine_transform, 1193
- nppiWarpAffine_64f_C3R
 - image_affine_transform, 1193
- nppiWarpAffine_64f_C4R
 - image_affine_transform, 1194
- nppiWarpAffine_64f_P3R
 - image_affine_transform, 1194
- nppiWarpAffine_64f_P4R
 - image_affine_transform, 1195
- nppiWarpAffine_8u_AC4R
 - image_affine_transform, 1195
- nppiWarpAffine_8u_C1R
 - image_affine_transform, 1196
- nppiWarpAffine_8u_C3R
 - image_affine_transform, 1196
- nppiWarpAffine_8u_C4R
 - image_affine_transform, 1197
- nppiWarpAffine_8u_P3R
 - image_affine_transform, 1197
- nppiWarpAffine_8u_P4R
 - image_affine_transform, 1198
- nppiWarpAffineBack_16u_AC4R
 - image_affine_transform, 1198
- nppiWarpAffineBack_16u_C1R
 - image_affine_transform, 1199
- nppiWarpAffineBack_16u_C3R
 - image_affine_transform, 1199
- nppiWarpAffineBack_16u_C4R
 - image_affine_transform, 1200
- nppiWarpAffineBack_16u_P3R
 - image_affine_transform, 1200
- nppiWarpAffineBack_16u_P4R
 - image_affine_transform, 1201
- nppiWarpAffineBack_32f_AC4R
 - image_affine_transform, 1201
- nppiWarpAffineBack_32f_C1R
 - image_affine_transform, 1202
- nppiWarpAffineBack_32f_C3R
 - image_affine_transform, 1202
- nppiWarpAffineBack_32f_C4R
 - image_affine_transform, 1203
- nppiWarpAffineBack_32f_P3R
 - image_affine_transform, 1203
- nppiWarpAffineBack_32f_P4R
 - image_affine_transform, 1204
- nppiWarpAffineBack_32s_AC4R
 - image_affine_transform, 1204
- nppiWarpAffineBack_32s_C1R
 - image_affine_transform, 1205
- nppiWarpAffineBack_32s_C3R
 - image_affine_transform, 1205
- nppiWarpAffineBack_32s_C4R
 - image_affine_transform, 1206
- nppiWarpAffineBack_32s_P3R
 - image_affine_transform, 1206
- nppiWarpAffineBack_32s_P4R
 - image_affine_transform, 1207
- nppiWarpAffineBack_8u_AC4R
 - image_affine_transform, 1207
- nppiWarpAffineBack_8u_C1R
 - image_affine_transform, 1208
- nppiWarpAffineBack_8u_C3R
 - image_affine_transform, 1208
- nppiWarpAffineBack_8u_C4R
 - image_affine_transform, 1209

nppiWarpAffineBack_8u_P3R
 image_affine_transform, 1209
 nppiWarpAffineBack_8u_P4R
 image_affine_transform, 1210
 nppiWarpAffineQuad_16u_AC4R
 image_affine_transform, 1210
 nppiWarpAffineQuad_16u_C1R
 image_affine_transform, 1211
 nppiWarpAffineQuad_16u_C3R
 image_affine_transform, 1211
 nppiWarpAffineQuad_16u_C4R
 image_affine_transform, 1212
 nppiWarpAffineQuad_16u_P3R
 image_affine_transform, 1212
 nppiWarpAffineQuad_16u_P4R
 image_affine_transform, 1213
 nppiWarpAffineQuad_32f_AC4R
 image_affine_transform, 1213
 nppiWarpAffineQuad_32f_C1R
 image_affine_transform, 1214
 nppiWarpAffineQuad_32f_C3R
 image_affine_transform, 1214
 nppiWarpAffineQuad_32f_C4R
 image_affine_transform, 1215
 nppiWarpAffineQuad_32f_P3R
 image_affine_transform, 1215
 nppiWarpAffineQuad_32f_P4R
 image_affine_transform, 1216
 nppiWarpAffineQuad_32s_AC4R
 image_affine_transform, 1216
 nppiWarpAffineQuad_32s_C1R
 image_affine_transform, 1217
 nppiWarpAffineQuad_32s_C3R
 image_affine_transform, 1217
 nppiWarpAffineQuad_32s_C4R
 image_affine_transform, 1218
 nppiWarpAffineQuad_32s_P3R
 image_affine_transform, 1218
 nppiWarpAffineQuad_32s_P4R
 image_affine_transform, 1219
 nppiWarpAffineQuad_8u_AC4R
 image_affine_transform, 1219
 nppiWarpAffineQuad_8u_C1R
 image_affine_transform, 1220
 nppiWarpAffineQuad_8u_C3R
 image_affine_transform, 1220
 nppiWarpAffineQuad_8u_C4R
 image_affine_transform, 1221
 nppiWarpAffineQuad_8u_P3R
 image_affine_transform, 1221
 nppiWarpAffineQuad_8u_P4R
 image_affine_transform, 1222
 nppiWarpPerspective_16u_AC4R
 image_perspective_transforms, 1232

nppiWarpPerspective_16u_C1R
 image_perspective_transforms, 1233
 nppiWarpPerspective_16u_C3R
 image_perspective_transforms, 1233
 nppiWarpPerspective_16u_C4R
 image_perspective_transforms, 1234
 nppiWarpPerspective_16u_P3R
 image_perspective_transforms, 1234
 nppiWarpPerspective_16u_P4R
 image_perspective_transforms, 1235
 nppiWarpPerspective_32f_AC4R
 image_perspective_transforms, 1235
 nppiWarpPerspective_32f_C1R
 image_perspective_transforms, 1236
 nppiWarpPerspective_32f_C3R
 image_perspective_transforms, 1236
 nppiWarpPerspective_32f_C4R
 image_perspective_transforms, 1237
 nppiWarpPerspective_32f_P3R
 image_perspective_transforms, 1237
 nppiWarpPerspective_32f_P4R
 image_perspective_transforms, 1238
 nppiWarpPerspective_32s_AC4R
 image_perspective_transforms, 1238
 nppiWarpPerspective_32s_C1R
 image_perspective_transforms, 1239
 nppiWarpPerspective_32s_C3R
 image_perspective_transforms, 1239
 nppiWarpPerspective_32s_C4R
 image_perspective_transforms, 1240
 nppiWarpPerspective_32s_P3R
 image_perspective_transforms, 1240
 nppiWarpPerspective_32s_P4R
 image_perspective_transforms, 1240
 nppiWarpPerspective_8u_AC4R
 image_perspective_transforms, 1241
 nppiWarpPerspective_8u_C1R
 image_perspective_transforms, 1241
 nppiWarpPerspective_8u_C3R
 image_perspective_transforms, 1242
 nppiWarpPerspective_8u_C4R
 image_perspective_transforms, 1242
 nppiWarpPerspective_8u_P3R
 image_perspective_transforms, 1243
 nppiWarpPerspective_8u_P4R
 image_perspective_transforms, 1243
 nppiWarpPerspectiveBack_16u_AC4R
 image_perspective_transforms, 1244
 nppiWarpPerspectiveBack_16u_C1R
 image_perspective_transforms, 1244
 nppiWarpPerspectiveBack_16u_C3R
 image_perspective_transforms, 1245
 nppiWarpPerspectiveBack_16u_C4R
 image_perspective_transforms, 1245

- nppiWarpPerspectiveBack_16u_P3R
 - image_perspective_transforms, [1246](#)
- nppiWarpPerspectiveBack_16u_P4R
 - image_perspective_transforms, [1246](#)
- nppiWarpPerspectiveBack_32f_AC4R
 - image_perspective_transforms, [1247](#)
- nppiWarpPerspectiveBack_32f_C1R
 - image_perspective_transforms, [1247](#)
- nppiWarpPerspectiveBack_32f_C3R
 - image_perspective_transforms, [1248](#)
- nppiWarpPerspectiveBack_32f_C4R
 - image_perspective_transforms, [1248](#)
- nppiWarpPerspectiveBack_32f_P3R
 - image_perspective_transforms, [1249](#)
- nppiWarpPerspectiveBack_32f_P4R
 - image_perspective_transforms, [1249](#)
- nppiWarpPerspectiveBack_32s_AC4R
 - image_perspective_transforms, [1250](#)
- nppiWarpPerspectiveBack_32s_C1R
 - image_perspective_transforms, [1250](#)
- nppiWarpPerspectiveBack_32s_C3R
 - image_perspective_transforms, [1251](#)
- nppiWarpPerspectiveBack_32s_C4R
 - image_perspective_transforms, [1251](#)
- nppiWarpPerspectiveBack_32s_P3R
 - image_perspective_transforms, [1252](#)
- nppiWarpPerspectiveBack_32s_P4R
 - image_perspective_transforms, [1252](#)
- nppiWarpPerspectiveBack_8u_AC4R
 - image_perspective_transforms, [1253](#)
- nppiWarpPerspectiveBack_8u_C1R
 - image_perspective_transforms, [1253](#)
- nppiWarpPerspectiveBack_8u_C3R
 - image_perspective_transforms, [1254](#)
- nppiWarpPerspectiveBack_8u_C4R
 - image_perspective_transforms, [1254](#)
- nppiWarpPerspectiveBack_8u_P3R
 - image_perspective_transforms, [1255](#)
- nppiWarpPerspectiveBack_8u_P4R
 - image_perspective_transforms, [1255](#)
- nppiWarpPerspectiveQuad_16u_AC4R
 - image_perspective_transforms, [1256](#)
- nppiWarpPerspectiveQuad_16u_C1R
 - image_perspective_transforms, [1256](#)
- nppiWarpPerspectiveQuad_16u_C3R
 - image_perspective_transforms, [1257](#)
- nppiWarpPerspectiveQuad_16u_C4R
 - image_perspective_transforms, [1257](#)
- nppiWarpPerspectiveQuad_16u_P3R
 - image_perspective_transforms, [1258](#)
- nppiWarpPerspectiveQuad_16u_P4R
 - image_perspective_transforms, [1258](#)
- nppiWarpPerspectiveQuad_32f_AC4R
 - image_perspective_transforms, [1259](#)
- nppiWarpPerspectiveQuad_32f_C1R
 - image_perspective_transforms, [1259](#)
- nppiWarpPerspectiveQuad_32f_C3R
 - image_perspective_transforms, [1260](#)
- nppiWarpPerspectiveQuad_32f_C4R
 - image_perspective_transforms, [1260](#)
- nppiWarpPerspectiveQuad_32f_P3R
 - image_perspective_transforms, [1261](#)
- nppiWarpPerspectiveQuad_32f_P4R
 - image_perspective_transforms, [1261](#)
- nppiWarpPerspectiveQuad_32s_AC4R
 - image_perspective_transforms, [1262](#)
- nppiWarpPerspectiveQuad_32s_C1R
 - image_perspective_transforms, [1262](#)
- nppiWarpPerspectiveQuad_32s_C3R
 - image_perspective_transforms, [1263](#)
- nppiWarpPerspectiveQuad_32s_C4R
 - image_perspective_transforms, [1263](#)
- nppiWarpPerspectiveQuad_32s_P3R
 - image_perspective_transforms, [1264](#)
- nppiWarpPerspectiveQuad_32s_P4R
 - image_perspective_transforms, [1264](#)
- nppiWarpPerspectiveQuad_8u_AC4R
 - image_perspective_transforms, [1265](#)
- nppiWarpPerspectiveQuad_8u_C1R
 - image_perspective_transforms, [1265](#)
- nppiWarpPerspectiveQuad_8u_C3R
 - image_perspective_transforms, [1266](#)
- nppiWarpPerspectiveQuad_8u_C4R
 - image_perspective_transforms, [1266](#)
- nppiWarpPerspectiveQuad_8u_P3R
 - image_perspective_transforms, [1267](#)
- nppiWarpPerspectiveQuad_8u_P4R
 - image_perspective_transforms, [1267](#)
- nppiXor_16u_AC4IR
 - image_xor, [458](#)
- nppiXor_16u_AC4R
 - image_xor, [458](#)
- nppiXor_16u_C1IR
 - image_xor, [458](#)
- nppiXor_16u_C1R
 - image_xor, [459](#)
- nppiXor_16u_C3IR
 - image_xor, [459](#)
- nppiXor_16u_C3R
 - image_xor, [459](#)
- nppiXor_16u_C4IR
 - image_xor, [460](#)
- nppiXor_16u_C4R
 - image_xor, [460](#)
- nppiXor_32s_AC4IR
 - image_xor, [461](#)
- nppiXor_32s_AC4R
 - image_xor, [461](#)

- nppiXor_32s_C1IR
 - image_xor, 461
- nppiXor_32s_C1R
 - image_xor, 462
- nppiXor_32s_C3IR
 - image_xor, 462
- nppiXor_32s_C3R
 - image_xor, 462
- nppiXor_32s_C4IR
 - image_xor, 463
- nppiXor_32s_C4R
 - image_xor, 463
- nppiXor_8u_AC4IR
 - image_xor, 464
- nppiXor_8u_AC4R
 - image_xor, 464
- nppiXor_8u_C1IR
 - image_xor, 464
- nppiXor_8u_C1R
 - image_xor, 465
- nppiXor_8u_C3IR
 - image_xor, 465
- nppiXor_8u_C3R
 - image_xor, 465
- nppiXor_8u_C4IR
 - image_xor, 466
- nppiXor_8u_C4R
 - image_xor, 466
- nppiXorC_16u_AC4IR
 - image_xorc, 395
- nppiXorC_16u_AC4R
 - image_xorc, 395
- nppiXorC_16u_C1IR
 - image_xorc, 395
- nppiXorC_16u_C1R
 - image_xorc, 396
- nppiXorC_16u_C3IR
 - image_xorc, 396
- nppiXorC_16u_C3R
 - image_xorc, 396
- nppiXorC_16u_C4IR
 - image_xorc, 397
- nppiXorC_16u_C4R
 - image_xorc, 397
- nppiXorC_32s_AC4IR
 - image_xorc, 397
- nppiXorC_32s_AC4R
 - image_xorc, 398
- nppiXorC_32s_C1IR
 - image_xorc, 398
- nppiXorC_32s_C1R
 - image_xorc, 398
- nppiXorC_32s_C3IR
 - image_xorc, 399
- nppiXorC_32s_C3R
 - image_xorc, 399
- nppiXorC_32s_C4IR
 - image_xorc, 399
- nppiXorC_32s_C4R
 - image_xorc, 400
- nppiXorC_8u_AC4IR
 - image_xorc, 400
- nppiXorC_8u_AC4R
 - image_xorc, 400
- nppiXorC_8u_C1IR
 - image_xorc, 401
- nppiXorC_8u_C1R
 - image_xorc, 401
- nppiXorC_8u_C3IR
 - image_xorc, 401
- nppiXorC_8u_C3R
 - image_xorc, 402
- nppiXorC_8u_C4IR
 - image_xorc, 402
- nppiXorC_8u_C4R
 - image_xorc, 402
- nppiXYZToRGB_8u_AC4R
 - image_color_model_conversion, 557
- nppiXYZToRGB_8u_C3R
 - image_color_model_conversion, 557
- nppiYCbCr411_8u_P2P3R
 - image_color_sampling_format_conversion, 582
- nppiYCbCr411_8u_P3P2R
 - image_color_sampling_format_conversion, 582
- nppiYCbCr411ToBGR_8u_P3C3R
 - image_color_model_conversion, 557
- nppiYCbCr411ToBGR_8u_P3C4R
 - image_color_model_conversion, 558
- nppiYCbCr411ToYCbCr420_8u_P2P3R
 - image_color_sampling_format_conversion, 582
- nppiYCbCr411ToYCbCr420_8u_P3P2R
 - image_color_sampling_format_conversion, 583
- nppiYCbCr411ToYCbCr420_8u_P3R
 - image_color_sampling_format_conversion, 583
- nppiYCbCr411ToYCbCr422_8u_P2C2R
 - image_color_sampling_format_conversion, 584
- nppiYCbCr411ToYCbCr422_8u_P2P3R
 - image_color_sampling_format_conversion, 584
- nppiYCbCr411ToYCbCr422_8u_P3C2R
 - image_color_sampling_format_conversion, 584

- nppiYCbCr411ToYCbCr422_8u_P3R
image_color_sampling_format_conversion, 585
- nppiYCbCr411ToYCrCb420_8u_P2P3R
image_color_sampling_format_conversion, 585
- nppiYCbCr411ToYCrCb422_8u_P3C2R
image_color_sampling_format_conversion, 586
- nppiYCbCr411ToYCrCb422_8u_P3R
image_color_sampling_format_conversion, 586
- nppiYCbCr420_8u_P2P3R
image_color_sampling_format_conversion, 586
- nppiYCbCr420_8u_P3P2R
image_color_sampling_format_conversion, 587
- nppiYCbCr420ToBGR_709CSC_8u_P3C3R
image_color_model_conversion, 558
- nppiYCbCr420ToBGR_709HDTV_8u_P3C4R
image_color_model_conversion, 558
- nppiYCbCr420ToBGR_8u_P3C3R
image_color_model_conversion, 559
- nppiYCbCr420ToBGR_8u_P3C4R
image_color_model_conversion, 559
- nppiYCbCr420ToCbYCr422_8u_P2C2R
image_color_sampling_format_conversion, 587
- nppiYCbCr420ToRGB_8u_P3C3R
image_color_model_conversion, 560
- nppiYCbCr420ToYCbCr411_8u_P2P3R
image_color_sampling_format_conversion, 588
- nppiYCbCr420ToYCbCr411_8u_P3P2R
image_color_sampling_format_conversion, 588
- nppiYCbCr420ToYCbCr422_8u_P2C2R
image_color_sampling_format_conversion, 589
- nppiYCbCr420ToYCbCr422_8u_P2P3R
image_color_sampling_format_conversion, 589
- nppiYCbCr420ToYCbCr422_8u_P3R
image_color_sampling_format_conversion, 589
- nppiYCbCr420ToYCrCb420_8u_P2P3R
image_color_sampling_format_conversion, 590
- nppiYCbCr422_8u_C2P3R
image_color_sampling_format_conversion, 590
- nppiYCbCr422_8u_P3C2R
image_color_sampling_format_conversion, 591
- nppiYCbCr422ToBGR_8u_C2C3R
image_color_model_conversion, 560
- nppiYCbCr422ToBGR_8u_C2C4R
image_color_model_conversion, 560
- nppiYCbCr422ToBGR_8u_P3C3R
image_color_model_conversion, 561
- nppiYCbCr422ToCbYCr422_8u_C2R
image_color_sampling_format_conversion, 591
- nppiYCbCr422ToRGB_8u_C2C3R
image_color_model_conversion, 561
- nppiYCbCr422ToRGB_8u_C2P3R
image_color_model_conversion, 561
- nppiYCbCr422ToRGB_8u_P3C3R
image_color_model_conversion, 562
- nppiYCbCr422ToYCbCr411_8u_C2P2R
image_color_sampling_format_conversion, 591
- nppiYCbCr422ToYCbCr411_8u_C2P3R
image_color_sampling_format_conversion, 592
- nppiYCbCr422ToYCbCr411_8u_P3P2R
image_color_sampling_format_conversion, 592
- nppiYCbCr422ToYCbCr411_8u_P3R
image_color_sampling_format_conversion, 593
- nppiYCbCr422ToYCbCr420_8u_C2P2R
image_color_sampling_format_conversion, 593
- nppiYCbCr422ToYCbCr420_8u_C2P3R
image_color_sampling_format_conversion, 594
- nppiYCbCr422ToYCbCr420_8u_P3P2R
image_color_sampling_format_conversion, 594
- nppiYCbCr422ToYCbCr420_8u_P3R
image_color_sampling_format_conversion, 594
- nppiYCbCr422ToYCrCb420_8u_C2P3R
image_color_sampling_format_conversion, 595
- nppiYCbCr422ToYCrCb422_8u_C2R
image_color_sampling_format_conversion, 595
- nppiYCbCr422ToYCrCb422_8u_P3C2R
image_color_sampling_format_conversion, 596
- nppiYCbCrToBGR_709CSC_8u_P3C3R
image_color_model_conversion, 562
- nppiYCbCrToBGR_709CSC_8u_P3C4R
image_color_model_conversion, 562

- nppiYCbCrToBGR_8u_P3C3R
 - image_color_model_conversion, [563](#)
- nppiYCbCrToBGR_8u_P3C4R
 - image_color_model_conversion, [563](#)
- nppiYCbCrToRGB_8u_AC4R
 - image_color_model_conversion, [564](#)
- nppiYCbCrToRGB_8u_C3R
 - image_color_model_conversion, [564](#)
- nppiYCbCrToRGB_8u_P3C3R
 - image_color_model_conversion, [564](#)
- nppiYCbCrToRGB_8u_P3C4R
 - image_color_model_conversion, [565](#)
- nppiYCbCrToRGB_8u_P3R
 - image_color_model_conversion, [565](#)
- nppiYCCToRGB_8u_AC4R
 - image_color_model_conversion, [565](#)
- nppiYCCToRGB_8u_C3R
 - image_color_model_conversion, [566](#)
- nppiYCrCb420ToCbYCr422_8u_P3C2R
 - image_color_sampling_format_conversion, [596](#)
- nppiYCrCb420ToRGB_8u_P3C4R
 - image_color_model_conversion, [566](#)
- nppiYCrCb420ToYCbCr411_8u_P3P2R
 - image_color_sampling_format_conversion, [596](#)
- nppiYCrCb420ToYCbCr420_8u_P3P2R
 - image_color_sampling_format_conversion, [597](#)
- nppiYCrCb420ToYCbCr422_8u_P3C2R
 - image_color_sampling_format_conversion, [597](#)
- nppiYCrCb420ToYCbCr422_8u_P3R
 - image_color_sampling_format_conversion, [598](#)
- nppiYCrCb422ToRGB_8u_C2C3R
 - image_color_model_conversion, [566](#)
- nppiYCrCb422ToRGB_8u_C2P3R
 - image_color_model_conversion, [567](#)
- nppiYCrCb422ToYCbCr411_8u_C2P3R
 - image_color_sampling_format_conversion, [598](#)
- nppiYCrCb422ToYCbCr420_8u_C2P3R
 - image_color_sampling_format_conversion, [599](#)
- nppiYCrCb422ToYCbCr422_8u_C2P3R
 - image_color_sampling_format_conversion, [599](#)
- nppiYUV420ToBGR_8u_P3C3R
 - image_color_model_conversion, [567](#)
- nppiYUV420ToRGB_8u_P3AC4R
 - image_color_model_conversion, [567](#)
- nppiYUV420ToRGB_8u_P3C3R
 - image_color_model_conversion, [568](#)
- nppiYUV420ToRGB_8u_P3R
 - image_color_model_conversion, [568](#)
- nppiYUV422ToRGB_8u_C2C3R
 - image_color_model_conversion, [568](#)
- nppiYUV422ToRGB_8u_P3AC4R
 - image_color_model_conversion, [569](#)
- nppiYUV422ToRGB_8u_P3C3R
 - image_color_model_conversion, [569](#)
- nppiYUV422ToRGB_8u_P3R
 - image_color_model_conversion, [569](#)
- nppiYUVToRGB_8u_AC4R
 - image_color_model_conversion, [570](#)
- nppiYUVToRGB_8u_C3R
 - image_color_model_conversion, [570](#)
- nppiYUVToRGB_8u_P3C3R
 - image_color_model_conversion, [570](#)
- nppiYUVToRGB_8u_P3R
 - image_color_model_conversion, [571](#)
- NppLibraryVersion, [2334](#)
 - build, [2334](#)
 - major, [2334](#)
 - minor, [2334](#)
- NppRoundMode
 - typedefs_npp, [43](#)
- npps10Log10_32s_ISfs
 - signal_10log10, [2117](#)
- npps10Log10_32s_Sfs
 - signal_10log10, [2117](#)
- nppsAbs_16s
 - signal_abs, [2091](#)
- nppsAbs_16s_I
 - signal_abs, [2091](#)
- nppsAbs_32f
 - signal_abs, [2092](#)
- nppsAbs_32f_I
 - signal_abs, [2092](#)
- nppsAbs_32s
 - signal_abs, [2092](#)
- nppsAbs_32s_I
 - signal_abs, [2092](#)
- nppsAbs_64f
 - signal_abs, [2093](#)
- nppsAbs_64f_I
 - signal_abs, [2093](#)
- nppsAdd_16s
 - signal_add, [2043](#)
- nppsAdd_16s32f
 - signal_add, [2043](#)
- nppsAdd_16s32s_I
 - signal_add, [2043](#)
- nppsAdd_16s_I
 - signal_add, [2044](#)
- nppsAdd_16s_ISfs
 - signal_add, [2044](#)

- nppsAdd_16s_Sfs
 - signal_add, 2044
- nppsAdd_16sc_ISfs
 - signal_add, 2045
- nppsAdd_16sc_Sfs
 - signal_add, 2045
- nppsAdd_16u
 - signal_add, 2045
- nppsAdd_16u_ISfs
 - signal_add, 2046
- nppsAdd_16u_Sfs
 - signal_add, 2046
- nppsAdd_32f
 - signal_add, 2046
- nppsAdd_32f_I
 - signal_add, 2047
- nppsAdd_32fc
 - signal_add, 2047
- nppsAdd_32fc_I
 - signal_add, 2047
- nppsAdd_32s_ISfs
 - signal_add, 2048
- nppsAdd_32s_Sfs
 - signal_add, 2048
- nppsAdd_32sc_ISfs
 - signal_add, 2048
- nppsAdd_32sc_Sfs
 - signal_add, 2049
- nppsAdd_32u
 - signal_add, 2049
- nppsAdd_64f
 - signal_add, 2049
- nppsAdd_64f_I
 - signal_add, 2050
- nppsAdd_64fc
 - signal_add, 2050
- nppsAdd_64fc_I
 - signal_add, 2050
- nppsAdd_64s_Sfs
 - signal_add, 2051
- nppsAdd_8u16u
 - signal_add, 2051
- nppsAdd_8u_ISfs
 - signal_add, 2051
- nppsAdd_8u_Sfs
 - signal_add, 2052
- nppsAddC_16s_ISfs
 - signal_addc, 1995
- nppsAddC_16s_Sfs
 - signal_addc, 1995
- nppsAddC_16sc_ISfs
 - signal_addc, 1996
- nppsAddC_16sc_Sfs
 - signal_addc, 1996
- nppsAddC_16u_ISfs
 - signal_addc, 1996
- nppsAddC_16u_Sfs
 - signal_addc, 1997
- nppsAddC_32f
 - signal_addc, 1997
- nppsAddC_32f_I
 - signal_addc, 1997
- nppsAddC_32fc
 - signal_addc, 1998
- nppsAddC_32fc_I
 - signal_addc, 1998
- nppsAddC_32s_ISfs
 - signal_addc, 1998
- nppsAddC_32s_Sfs
 - signal_addc, 1999
- nppsAddC_32sc_ISfs
 - signal_addc, 1999
- nppsAddC_32sc_Sfs
 - signal_addc, 1999
- nppsAddC_64f
 - signal_addc, 2000
- nppsAddC_64f_I
 - signal_addc, 2000
- nppsAddC_64fc
 - signal_addc, 2000
- nppsAddC_64fc_I
 - signal_addc, 2001
- nppsAddC_8u_ISfs
 - signal_addc, 2001
- nppsAddC_8u_Sfs
 - signal_addc, 2001
- nppsAddProduct_16s32s_Sfs
 - signal_addproduct, 2054
- nppsAddProduct_16s_Sfs
 - signal_addproduct, 2054
- nppsAddProduct_32f
 - signal_addproduct, 2054
- nppsAddProduct_32fc
 - signal_addproduct, 2055
- nppsAddProduct_32s_Sfs
 - signal_addproduct, 2055
- nppsAddProduct_64f
 - signal_addproduct, 2055
- nppsAddProduct_64fc
 - signal_addproduct, 2056
- nppsAddProductC_32f
 - signal_addproductc, 2003
- nppsAnd_16u
 - signal_and, 2133
- nppsAnd_16u_I
 - signal_and, 2133
- nppsAnd_32u
 - signal_and, 2134

- nppsAnd_32u_I
 - signal_and, [2134](#)
- nppsAnd_8u
 - signal_and, [2134](#)
- nppsAnd_8u_I
 - signal_and, [2135](#)
- nppsAndC_16u
 - signal_andc, [2130](#)
- nppsAndC_16u_I
 - signal_andc, [2130](#)
- nppsAndC_32u
 - signal_andc, [2131](#)
- nppsAndC_32u_I
 - signal_andc, [2131](#)
- nppsAndC_8u
 - signal_andc, [2131](#)
- nppsAndC_8u_I
 - signal_andc, [2132](#)
- nppsArctan_32f
 - signal_inversetan, [2122](#)
- nppsArctan_32f_I
 - signal_inversetan, [2122](#)
- nppsArctan_64f
 - signal_inversetan, [2122](#)
- nppsArctan_64f_I
 - signal_inversetan, [2123](#)
- nppsCauchy_32f_I
 - signal_cauchy, [2127](#)
- nppsCauchyD_32f_I
 - signal_cauchy, [2127](#)
- nppsCauchyDD2_32f_I
 - signal_cauchy, [2127](#)
- nppsConvert_16s32f
 - signal_convert, [2162](#)
- nppsConvert_16s32f_Sfs
 - signal_convert, [2162](#)
- nppsConvert_16s32s
 - signal_convert, [2162](#)
- nppsConvert_16s64f_Sfs
 - signal_convert, [2162](#)
- nppsConvert_16s8s_Sfs
 - signal_convert, [2162](#)
- nppsConvert_16u32f
 - signal_convert, [2162](#)
- nppsConvert_32f16s_Sfs
 - signal_convert, [2162](#)
- nppsConvert_32f16u_Sfs
 - signal_convert, [2162](#)
- nppsConvert_32f32s_Sfs
 - signal_convert, [2162](#)
- nppsConvert_32f64f
 - signal_convert, [2162](#)
- nppsConvert_32f8s_Sfs
 - signal_convert, [2162](#)
- nppsConvert_32f8u_Sfs
 - signal_convert, [2162](#)
- nppsConvert_32s16s
 - signal_convert, [2162](#)
- nppsConvert_32s16s_Sfs
 - signal_convert, [2162](#)
- nppsConvert_32s32f
 - signal_convert, [2162](#)
- nppsConvert_32s32f_Sfs
 - signal_convert, [2162](#)
- nppsConvert_32s64f
 - signal_convert, [2162](#)
- nppsConvert_32s64f_Sfs
 - signal_convert, [2162](#)
- nppsConvert_64f16s_Sfs
 - signal_convert, [2162](#)
- nppsConvert_64f32f
 - signal_convert, [2162](#)
- nppsConvert_64f32s_Sfs
 - signal_convert, [2162](#)
- nppsConvert_64f64s_Sfs
 - signal_convert, [2162](#)
- nppsConvert_64s32s_Sfs
 - signal_convert, [2162](#)
- nppsConvert_64s64f
 - signal_convert, [2162](#)
- nppsConvert_8s16s
 - signal_convert, [2162](#)
- nppsConvert_8s32f
 - signal_convert, [2162](#)
- nppsConvert_8u32f
 - signal_convert, [2162](#)
- nppsCopy_16s
 - signal_copy, [2199](#)
- nppsCopy_16sc
 - signal_copy, [2200](#)
- nppsCopy_32f
 - signal_copy, [2200](#)
- nppsCopy_32fc
 - signal_copy, [2200](#)
- nppsCopy_32s
 - signal_copy, [2200](#)
- nppsCopy_32sc
 - signal_copy, [2201](#)
- nppsCopy_64fc
 - signal_copy, [2201](#)
- nppsCopy_64s
 - signal_copy, [2201](#)
- nppsCopy_64sc
 - signal_copy, [2202](#)
- nppsCopy_8u
 - signal_copy, [2202](#)
- nppsCountInRange_32s
 - signal_count_in_range, [2314](#)

- nppsCountInRangeGetBufferSize_32s
 - signal_count_in_range, [2314](#)
- nppsCubrt_32f
 - signal_cuberoot, [2108](#)
- nppsCubrt_32s16s_Sfs
 - signal_cuberoot, [2108](#)
- nppsDiv_16s_ISfs
 - signal_div, [2081](#)
- nppsDiv_16s_Sfs
 - signal_div, [2081](#)
- nppsDiv_16sc_ISfs
 - signal_div, [2082](#)
- nppsDiv_16sc_Sfs
 - signal_div, [2082](#)
- nppsDiv_16u_ISfs
 - signal_div, [2082](#)
- nppsDiv_16u_Sfs
 - signal_div, [2083](#)
- nppsDiv_32f
 - signal_div, [2083](#)
- nppsDiv_32f_I
 - signal_div, [2083](#)
- nppsDiv_32fc
 - signal_div, [2084](#)
- nppsDiv_32fc_I
 - signal_div, [2084](#)
- nppsDiv_32s16s_Sfs
 - signal_div, [2084](#)
- nppsDiv_32s_ISfs
 - signal_div, [2085](#)
- nppsDiv_32s_Sfs
 - signal_div, [2085](#)
- nppsDiv_64f
 - signal_div, [2085](#)
- nppsDiv_64f_I
 - signal_div, [2086](#)
- nppsDiv_64fc
 - signal_div, [2086](#)
- nppsDiv_64fc_I
 - signal_div, [2086](#)
- nppsDiv_8u_ISfs
 - signal_div, [2087](#)
- nppsDiv_8u_Sfs
 - signal_div, [2087](#)
- nppsDiv_Round_16s_ISfs
 - signal_divround, [2088](#)
- nppsDiv_Round_16s_Sfs
 - signal_divround, [2089](#)
- nppsDiv_Round_16u_ISfs
 - signal_divround, [2089](#)
- nppsDiv_Round_16u_Sfs
 - signal_divround, [2089](#)
- nppsDiv_Round_8u_ISfs
 - signal_divround, [2090](#)
- nppsDiv_Round_8u_Sfs
 - signal_divround, [2090](#)
- nppsDivC_16s_ISfs
 - signal_divc, [2033](#)
- nppsDivC_16s_Sfs
 - signal_divc, [2033](#)
- nppsDivC_16sc_ISfs
 - signal_divc, [2033](#)
- nppsDivC_16sc_Sfs
 - signal_divc, [2034](#)
- nppsDivC_16u_ISfs
 - signal_divc, [2034](#)
- nppsDivC_16u_Sfs
 - signal_divc, [2034](#)
- nppsDivC_32f
 - signal_divc, [2035](#)
- nppsDivC_32f_I
 - signal_divc, [2035](#)
- nppsDivC_32fc
 - signal_divc, [2035](#)
- nppsDivC_32fc_I
 - signal_divc, [2036](#)
- nppsDivC_64f
 - signal_divc, [2036](#)
- nppsDivC_64f_I
 - signal_divc, [2036](#)
- nppsDivC_64fc
 - signal_divc, [2037](#)
- nppsDivC_64fc_I
 - signal_divc, [2037](#)
- nppsDivC_8u_ISfs
 - signal_divc, [2037](#)
- nppsDivC_8u_Sfs
 - signal_divc, [2038](#)
- nppsDivCRev_16u
 - signal_divcrev, [2039](#)
- nppsDivCRev_16u_I
 - signal_divcrev, [2039](#)
- nppsDivCRev_32f
 - signal_divcrev, [2040](#)
- nppsDivCRev_32f_I
 - signal_divcrev, [2040](#)
- nppsDotProd_16s16sc32fc
 - signal_dot_product, [2297](#)
- nppsDotProd_16s16sc32sc_Sfs
 - signal_dot_product, [2298](#)
- nppsDotProd_16s16sc64sc
 - signal_dot_product, [2298](#)
- nppsDotProd_16s16sc_Sfs
 - signal_dot_product, [2298](#)
- nppsDotProd_16s32f
 - signal_dot_product, [2299](#)
- nppsDotProd_16s32s32s_Sfs
 - signal_dot_product, [2299](#)

- nppsDotProd_16s32s_Sfs
 - signal_dot_product, 2300
- nppsDotProd_16s64s
 - signal_dot_product, 2300
- nppsDotProd_16s_Sfs
 - signal_dot_product, 2300
- nppsDotProd_16sc32fc
 - signal_dot_product, 2301
- nppsDotProd_16sc32sc_Sfs
 - signal_dot_product, 2301
- nppsDotProd_16sc64sc
 - signal_dot_product, 2302
- nppsDotProd_16sc_Sfs
 - signal_dot_product, 2302
- nppsDotProd_32f
 - signal_dot_product, 2302
- nppsDotProd_32f32fc
 - signal_dot_product, 2303
- nppsDotProd_32f32fc64fc
 - signal_dot_product, 2303
- nppsDotProd_32f64f
 - signal_dot_product, 2303
- nppsDotProd_32fc
 - signal_dot_product, 2304
- nppsDotProd_32fc64fc
 - signal_dot_product, 2304
- nppsDotProd_32s32sc_Sfs
 - signal_dot_product, 2304
- nppsDotProd_32s_Sfs
 - signal_dot_product, 2305
- nppsDotProd_32sc_Sfs
 - signal_dot_product, 2305
- nppsDotProd_64f
 - signal_dot_product, 2306
- nppsDotProd_64f64fc
 - signal_dot_product, 2306
- nppsDotProd_64fc
 - signal_dot_product, 2306
- nppsDotProdGetBufferSize_16s16sc32fc
 - signal_dot_product, 2307
- nppsDotProdGetBufferSize_16s16sc32sc_Sfs
 - signal_dot_product, 2307
- nppsDotProdGetBufferSize_16s16sc64sc
 - signal_dot_product, 2307
- nppsDotProdGetBufferSize_16s16sc_Sfs
 - signal_dot_product, 2308
- nppsDotProdGetBufferSize_16s32f
 - signal_dot_product, 2308
- nppsDotProdGetBufferSize_16s32s32s_Sfs
 - signal_dot_product, 2308
- nppsDotProdGetBufferSize_16s32s_Sfs
 - signal_dot_product, 2308
- nppsDotProdGetBufferSize_16s64s
 - signal_dot_product, 2309
- nppsDotProdGetBufferSize_16s_Sfs
 - signal_dot_product, 2309
- nppsDotProdGetBufferSize_16sc32fc
 - signal_dot_product, 2309
- nppsDotProdGetBufferSize_16sc32sc_Sfs
 - signal_dot_product, 2309
- nppsDotProdGetBufferSize_16sc64sc
 - signal_dot_product, 2310
- nppsDotProdGetBufferSize_16sc_Sfs
 - signal_dot_product, 2310
- nppsDotProdGetBufferSize_32f
 - signal_dot_product, 2310
- nppsDotProdGetBufferSize_32f32fc
 - signal_dot_product, 2310
- nppsDotProdGetBufferSize_32f32fc64fc
 - signal_dot_product, 2311
- nppsDotProdGetBufferSize_32f64f
 - signal_dot_product, 2311
- nppsDotProdGetBufferSize_32fc
 - signal_dot_product, 2311
- nppsDotProdGetBufferSize_32fc64fc
 - signal_dot_product, 2311
- nppsDotProdGetBufferSize_32s32sc_Sfs
 - signal_dot_product, 2312
- nppsDotProdGetBufferSize_32s_Sfs
 - signal_dot_product, 2312
- nppsDotProdGetBufferSize_32sc_Sfs
 - signal_dot_product, 2312
- nppsDotProdGetBufferSize_64f
 - signal_dot_product, 2312
- nppsDotProdGetBufferSize_64f64fc
 - signal_dot_product, 2313
- nppsDotProdGetBufferSize_64fc
 - signal_dot_product, 2313
- nppSetStream
 - core_npp, 33
- nppsExp_16s_ISfs
 - signal_exp, 2109
- nppsExp_16s_Sfs
 - signal_exp, 2110
- nppsExp_32f
 - signal_exp, 2110
- nppsExp_32f64f
 - signal_exp, 2110
- nppsExp_32f_I
 - signal_exp, 2110
- nppsExp_32s_ISfs
 - signal_exp, 2111
- nppsExp_32s_Sfs
 - signal_exp, 2111
- nppsExp_64f
 - signal_exp, 2111
- nppsExp_64f_I
 - signal_exp, 2112

- nppsExp_64s_ISfs
 - signal_exp, [2112](#)
- nppsExp_64s_Sfs
 - signal_exp, [2112](#)
- nppsFree
 - signal_free, [2323](#)
- nppsIntegral_32s
 - signal_integral, [2189](#)
- nppsIntegralGetBufferSize_32s
 - signal_integral, [2189](#)
- nppsLn_16s_ISfs
 - signal_ln, [2113](#)
- nppsLn_16s_Sfs
 - signal_ln, [2114](#)
- nppsLn_32f
 - signal_ln, [2114](#)
- nppsLn_32f_I
 - signal_ln, [2114](#)
- nppsLn_32s16s_Sfs
 - signal_ln, [2114](#)
- nppsLn_32s_ISfs
 - signal_ln, [2115](#)
- nppsLn_32s_Sfs
 - signal_ln, [2115](#)
- nppsLn_64f
 - signal_ln, [2115](#)
- nppsLn_64f32f
 - signal_ln, [2116](#)
- nppsLn_64f_I
 - signal_ln, [2116](#)
- nppsLShiftC_16s
 - signal_lshiftc, [2151](#)
- nppsLShiftC_16s_I
 - signal_lshiftc, [2152](#)
- nppsLShiftC_16u
 - signal_lshiftc, [2152](#)
- nppsLShiftC_16u_I
 - signal_lshiftc, [2152](#)
- nppsLShiftC_32s
 - signal_lshiftc, [2152](#)
- nppsLShiftC_32s_I
 - signal_lshiftc, [2153](#)
- nppsLShiftC_32u
 - signal_lshiftc, [2153](#)
- nppsLShiftC_32u_I
 - signal_lshiftc, [2153](#)
- nppsLShiftC_8u
 - signal_lshiftc, [2154](#)
- nppsLShiftC_8u_I
 - signal_lshiftc, [2154](#)
- nppsMalloc_16s
 - signal_malloc, [2319](#)
- nppsMalloc_16sc
 - signal_malloc, [2319](#)
- nppsMalloc_16u
 - signal_malloc, [2319](#)
- nppsMalloc_32f
 - signal_malloc, [2319](#)
- nppsMalloc_32fc
 - signal_malloc, [2320](#)
- nppsMalloc_32s
 - signal_malloc, [2320](#)
- nppsMalloc_32sc
 - signal_malloc, [2320](#)
- nppsMalloc_32u
 - signal_malloc, [2320](#)
- nppsMalloc_64f
 - signal_malloc, [2321](#)
- nppsMalloc_64fc
 - signal_malloc, [2321](#)
- nppsMalloc_64s
 - signal_malloc, [2321](#)
- nppsMalloc_64sc
 - signal_malloc, [2321](#)
- nppsMalloc_8s
 - signal_malloc, [2322](#)
- nppsMalloc_8u
 - signal_malloc, [2322](#)
- nppsMax_16s
 - signal_max, [2216](#)
- nppsMax_32f
 - signal_max, [2217](#)
- nppsMax_32s
 - signal_max, [2217](#)
- nppsMax_64f
 - signal_max, [2217](#)
- nppsMaxAbs_16s
 - signal_max, [2218](#)
- nppsMaxAbs_32s
 - signal_max, [2218](#)
- nppsMaxAbsGetBufferSize_16s
 - signal_max, [2218](#)
- nppsMaxAbsGetBufferSize_32s
 - signal_max, [2219](#)
- nppsMaxAbsIndx_16s
 - signal_max, [2219](#)
- nppsMaxAbsIndx_32s
 - signal_max, [2219](#)
- nppsMaxAbsIndxGetBufferSize_16s
 - signal_max, [2220](#)
- nppsMaxAbsIndxGetBufferSize_32s
 - signal_max, [2220](#)
- nppsMaxEvery_16s_I
 - signal_min_every_or_max_every, [2204](#)
- nppsMaxEvery_16u_I
 - signal_min_every_or_max_every, [2205](#)
- nppsMaxEvery_32f_I
 - signal_min_every_or_max_every, [2205](#)

- nppsMaxEvery_32s_I
 - signal_min_every_or_max_every, 2205
- nppsMaxEvery_8u_I
 - signal_min_every_or_max_every, 2205
- nppsMaxGetBufferSize_16s
 - signal_max, 2220
- nppsMaxGetBufferSize_32f
 - signal_max, 2220
- nppsMaxGetBufferSize_32s
 - signal_max, 2221
- nppsMaxGetBufferSize_64f
 - signal_max, 2221
- nppsMaxIdx_16s
 - signal_max, 2221
- nppsMaxIdx_32f
 - signal_max, 2222
- nppsMaxIdx_32s
 - signal_max, 2222
- nppsMaxIdx_64f
 - signal_max, 2222
- nppsMaxIdxGetBufferSize_16s
 - signal_max, 2223
- nppsMaxIdxGetBufferSize_32f
 - signal_max, 2223
- nppsMaxIdxGetBufferSize_32s
 - signal_max, 2223
- nppsMaxIdxGetBufferSize_64f
 - signal_max, 2224
- nppsMean_16s_Sfs
 - signal_mean, 2236
- nppsMean_16sc_Sfs
 - signal_mean, 2236
- nppsMean_32f
 - signal_mean, 2236
- nppsMean_32fc
 - signal_mean, 2237
- nppsMean_32s_Sfs
 - signal_mean, 2237
- nppsMean_64f
 - signal_mean, 2237
- nppsMean_64fc
 - signal_mean, 2238
- nppsMeanGetBufferSize_16s_Sfs
 - signal_mean, 2238
- nppsMeanGetBufferSize_16sc_Sfs
 - signal_mean, 2238
- nppsMeanGetBufferSize_32f
 - signal_mean, 2239
- nppsMeanGetBufferSize_32fc
 - signal_mean, 2239
- nppsMeanGetBufferSize_32s_Sfs
 - signal_mean, 2239
- nppsMeanGetBufferSize_64f
 - signal_mean, 2239
- nppsMeanGetBufferSize_64fc
 - signal_mean, 2240
- nppsMeanStdDev_16s32s_Sfs
 - signal_mean_and_standard_deviation, 2244
- nppsMeanStdDev_16s_Sfs
 - signal_mean_and_standard_deviation, 2245
- nppsMeanStdDev_32f
 - signal_mean_and_standard_deviation, 2245
- nppsMeanStdDev_64f
 - signal_mean_and_standard_deviation, 2245
- nppsMeanStdDevGetBufferSize_16s32s_Sfs
 - signal_mean_and_standard_deviation, 2246
- nppsMeanStdDevGetBufferSize_16s_Sfs
 - signal_mean_and_standard_deviation, 2246
- nppsMeanStdDevGetBufferSize_32f
 - signal_mean_and_standard_deviation, 2246
- nppsMeanStdDevGetBufferSize_64f
 - signal_mean_and_standard_deviation, 2246
- nppsMin_16s
 - signal_min, 2226
- nppsMin_32f
 - signal_min, 2227
- nppsMin_32s
 - signal_min, 2227
- nppsMin_64f
 - signal_min, 2227
- nppsMinAbs_16s
 - signal_min, 2228
- nppsMinAbs_32s
 - signal_min, 2228
- nppsMinAbsGetBufferSize_16s
 - signal_min, 2228
- nppsMinAbsGetBufferSize_32s
 - signal_min, 2229
- nppsMinAbsIdx_16s
 - signal_min, 2229
- nppsMinAbsIdx_32s
 - signal_min, 2229
- nppsMinAbsIdxGetBufferSize_16s
 - signal_min, 2230
- nppsMinAbsIdxGetBufferSize_32s
 - signal_min, 2230
- nppsMinEvery_16s_I
 - signal_min_every_or_max_every, 2206
- nppsMinEvery_16u_I
 - signal_min_every_or_max_every, 2206
- nppsMinEvery_32f_I
 - signal_min_every_or_max_every, 2206
- nppsMinEvery_32s_I
 - signal_min_every_or_max_every, 2207
- nppsMinEvery_64f_I
 - signal_min_every_or_max_every, 2207
- nppsMinEvery_8u_I
 - signal_min_every_or_max_every, 2207

- nppsMinGetBufferSize_16s
 - signal_min, [2230](#)
- nppsMinGetBufferSize_32f
 - signal_min, [2230](#)
- nppsMinGetBufferSize_32s
 - signal_min, [2231](#)
- nppsMinGetBufferSize_64f
 - signal_min, [2231](#)
- nppsMinIndx_16s
 - signal_min, [2231](#)
- nppsMinIndx_32f
 - signal_min, [2232](#)
- nppsMinIndx_32s
 - signal_min, [2232](#)
- nppsMinIndx_64f
 - signal_min, [2232](#)
- nppsMinIndxGetBufferSize_16s
 - signal_min, [2233](#)
- nppsMinIndxGetBufferSize_32f
 - signal_min, [2233](#)
- nppsMinIndxGetBufferSize_32s
 - signal_min, [2233](#)
- nppsMinIndxGetBufferSize_64f
 - signal_min, [2234](#)
- nppsMinMax_16s
 - signal_min_max, [2250](#)
- nppsMinMax_16u
 - signal_min_max, [2250](#)
- nppsMinMax_32f
 - signal_min_max, [2250](#)
- nppsMinMax_32s
 - signal_min_max, [2251](#)
- nppsMinMax_32u
 - signal_min_max, [2251](#)
- nppsMinMax_64f
 - signal_min_max, [2251](#)
- nppsMinMax_8u
 - signal_min_max, [2252](#)
- nppsMinMaxGetBufferSize_16s
 - signal_min_max, [2252](#)
- nppsMinMaxGetBufferSize_16u
 - signal_min_max, [2252](#)
- nppsMinMaxGetBufferSize_32f
 - signal_min_max, [2253](#)
- nppsMinMaxGetBufferSize_32s
 - signal_min_max, [2253](#)
- nppsMinMaxGetBufferSize_32u
 - signal_min_max, [2253](#)
- nppsMinMaxGetBufferSize_64f
 - signal_min_max, [2253](#)
- nppsMinMaxGetBufferSize_8u
 - signal_min_max, [2254](#)
- nppsMinMaxIndx_16s
 - signal_min_max, [2254](#)
- nppsMinMaxIndx_16u
 - signal_min_max, [2254](#)
- nppsMinMaxIndx_32f
 - signal_min_max, [2255](#)
- nppsMinMaxIndx_32s
 - signal_min_max, [2255](#)
- nppsMinMaxIndx_32u
 - signal_min_max, [2256](#)
- nppsMinMaxIndx_64f
 - signal_min_max, [2256](#)
- nppsMinMaxIndx_8u
 - signal_min_max, [2256](#)
- nppsMinMaxIndxGetBufferSize_16s
 - signal_min_max, [2257](#)
- nppsMinMaxIndxGetBufferSize_16u
 - signal_min_max, [2257](#)
- nppsMinMaxIndxGetBufferSize_32f
 - signal_min_max, [2257](#)
- nppsMinMaxIndxGetBufferSize_32s
 - signal_min_max, [2258](#)
- nppsMinMaxIndxGetBufferSize_32u
 - signal_min_max, [2258](#)
- nppsMinMaxIndxGetBufferSize_64f
 - signal_min_max, [2258](#)
- nppsMinMaxIndxGetBufferSize_8u
 - signal_min_max, [2258](#)
- nppsMul_16s
 - signal_mul, [2059](#)
- nppsMul_16s32f
 - signal_mul, [2059](#)
- nppsMul_16s32s_Sfs
 - signal_mul, [2060](#)
- nppsMul_16s_I
 - signal_mul, [2060](#)
- nppsMul_16s_ISfs
 - signal_mul, [2060](#)
- nppsMul_16s_Sfs
 - signal_mul, [2061](#)
- nppsMul_16sc_ISfs
 - signal_mul, [2061](#)
- nppsMul_16sc_Sfs
 - signal_mul, [2061](#)
- nppsMul_16u16s_Sfs
 - signal_mul, [2062](#)
- nppsMul_16u_ISfs
 - signal_mul, [2062](#)
- nppsMul_16u_Sfs
 - signal_mul, [2062](#)
- nppsMul_32f
 - signal_mul, [2063](#)
- nppsMul_32f32fc
 - signal_mul, [2063](#)
- nppsMul_32f32fc_I
 - signal_mul, [2063](#)

- nppsMul_32f_I
 - signal_mul, [2064](#)
- nppsMul_32fc
 - signal_mul, [2064](#)
- nppsMul_32fc_I
 - signal_mul, [2064](#)
- nppsMul_32s32sc_ISfs
 - signal_mul, [2065](#)
- nppsMul_32s32sc_Sfs
 - signal_mul, [2065](#)
- nppsMul_32s_ISfs
 - signal_mul, [2065](#)
- nppsMul_32s_Sfs
 - signal_mul, [2066](#)
- nppsMul_32sc_ISfs
 - signal_mul, [2066](#)
- nppsMul_32sc_Sfs
 - signal_mul, [2066](#)
- nppsMul_64f
 - signal_mul, [2067](#)
- nppsMul_64f_I
 - signal_mul, [2067](#)
- nppsMul_64fc
 - signal_mul, [2067](#)
- nppsMul_64fc_I
 - signal_mul, [2068](#)
- nppsMul_8u16u
 - signal_mul, [2068](#)
- nppsMul_8u_ISfs
 - signal_mul, [2068](#)
- nppsMul_8u_Sfs
 - signal_mul, [2069](#)
- nppsMul_Low_32s_Sfs
 - signal_mul, [2069](#)
- nppsMulC_16s_ISfs
 - signal_mulc, [2005](#)
- nppsMulC_16s_Sfs
 - signal_mulc, [2006](#)
- nppsMulC_16sc_ISfs
 - signal_mulc, [2006](#)
- nppsMulC_16sc_Sfs
 - signal_mulc, [2006](#)
- nppsMulC_16u_ISfs
 - signal_mulc, [2007](#)
- nppsMulC_16u_Sfs
 - signal_mulc, [2007](#)
- nppsMulC_32f
 - signal_mulc, [2007](#)
- nppsMulC_32f16s_Sfs
 - signal_mulc, [2008](#)
- nppsMulC_32f_I
 - signal_mulc, [2008](#)
- nppsMulC_32fc
 - signal_mulc, [2008](#)
- nppsMulC_32fc_I
 - signal_mulc, [2009](#)
- nppsMulC_32s_ISfs
 - signal_mulc, [2009](#)
- nppsMulC_32s_Sfs
 - signal_mulc, [2009](#)
- nppsMulC_32sc_ISfs
 - signal_mulc, [2010](#)
- nppsMulC_32sc_Sfs
 - signal_mulc, [2010](#)
- nppsMulC_64f
 - signal_mulc, [2010](#)
- nppsMulC_64f64s_ISfs
 - signal_mulc, [2011](#)
- nppsMulC_64f_I
 - signal_mulc, [2011](#)
- nppsMulC_64fc
 - signal_mulc, [2011](#)
- nppsMulC_64fc_I
 - signal_mulc, [2012](#)
- nppsMulC_8u_ISfs
 - signal_mulc, [2012](#)
- nppsMulC_8u_Sfs
 - signal_mulc, [2012](#)
- nppsMulC_Low_32f16s
 - signal_mulc, [2013](#)
- nppsNorm_Inf_16s32f
 - signal_infinity_norm, [2261](#)
- nppsNorm_Inf_16s32s_Sfs
 - signal_infinity_norm, [2261](#)
- nppsNorm_Inf_32f
 - signal_infinity_norm, [2261](#)
- nppsNorm_Inf_32fc32f
 - signal_infinity_norm, [2261](#)
- nppsNorm_Inf_64f
 - signal_infinity_norm, [2262](#)
- nppsNorm_Inf_64fc64f
 - signal_infinity_norm, [2262](#)
- nppsNorm_L1_16s32f
 - signal_L1_norm, [2266](#)
- nppsNorm_L1_16s32s_Sfs
 - signal_L1_norm, [2266](#)
- nppsNorm_L1_16s64s_Sfs
 - signal_L1_norm, [2266](#)
- nppsNorm_L1_32f
 - signal_L1_norm, [2267](#)
- nppsNorm_L1_32fc64f
 - signal_L1_norm, [2267](#)
- nppsNorm_L1_64f
 - signal_L1_norm, [2267](#)
- nppsNorm_L1_64fc64f
 - signal_L1_norm, [2268](#)
- nppsNorm_L2_16s32f
 - signal_L2_norm, [2272](#)

- nppsNorm_L2_16s32s_Sfs
 - signal_L2_norm, [2272](#)
- nppsNorm_L2_32f
 - signal_L2_norm, [2272](#)
- nppsNorm_L2_32fc64f
 - signal_L2_norm, [2273](#)
- nppsNorm_L2_64f
 - signal_L2_norm, [2273](#)
- nppsNorm_L2_64fc64f
 - signal_L2_norm, [2273](#)
- nppsNorm_L2Sqr_16s64s_Sfs
 - signal_L2_norm, [2274](#)
- nppsNormalize_16s_Sfs
 - signal_normalize, [2124](#)
- nppsNormalize_16sc_Sfs
 - signal_normalize, [2125](#)
- nppsNormalize_32f
 - signal_normalize, [2125](#)
- nppsNormalize_32fc
 - signal_normalize, [2125](#)
- nppsNormalize_64f
 - signal_normalize, [2126](#)
- nppsNormalize_64fc
 - signal_normalize, [2126](#)
- nppsNormDiff_Inf_16s32f
 - signal_infinity_norm_diff, [2278](#)
- nppsNormDiff_Inf_16s32s_Sfs
 - signal_infinity_norm_diff, [2278](#)
- nppsNormDiff_Inf_32f
 - signal_infinity_norm_diff, [2278](#)
- nppsNormDiff_Inf_32fc32f
 - signal_infinity_norm_diff, [2279](#)
- nppsNormDiff_Inf_64f
 - signal_infinity_norm_diff, [2279](#)
- nppsNormDiff_Inf_64fc64f
 - signal_infinity_norm_diff, [2279](#)
- nppsNormDiff_L1_16s32f
 - signal_L1_norm_diff, [2283](#)
- nppsNormDiff_L1_16s32s_Sfs
 - signal_L1_norm_diff, [2283](#)
- nppsNormDiff_L1_16s64s_Sfs
 - signal_L1_norm_diff, [2283](#)
- nppsNormDiff_L1_32f
 - signal_L1_norm_diff, [2284](#)
- nppsNormDiff_L1_32fc64f
 - signal_L1_norm_diff, [2284](#)
- nppsNormDiff_L1_64f
 - signal_L1_norm_diff, [2284](#)
- nppsNormDiff_L1_64fc64f
 - signal_L1_norm_diff, [2285](#)
- nppsNormDiff_L2_16s32f
 - signal_L2_norm_diff, [2289](#)
- nppsNormDiff_L2_16s32s_Sfs
 - signal_L2_norm_diff, [2289](#)
- nppsNormDiff_L2_32f
 - signal_L2_norm_diff, [2289](#)
- nppsNormDiff_L2_32fc64f
 - signal_L2_norm_diff, [2290](#)
- nppsNormDiff_L2_64f
 - signal_L2_norm_diff, [2290](#)
- nppsNormDiff_L2_64fc64f
 - signal_L2_norm_diff, [2290](#)
- nppsNormDiff_L2Sqr_16s64s_Sfs
 - signal_L2_norm_diff, [2291](#)
- nppsNormDiffInfGetBufferSize_16s32f
 - signal_infinity_norm_diff, [2280](#)
- nppsNormDiffInfGetBufferSize_16s32s_Sfs
 - signal_infinity_norm_diff, [2280](#)
- nppsNormDiffInfGetBufferSize_32f
 - signal_infinity_norm_diff, [2280](#)
- nppsNormDiffInfGetBufferSize_32fc32f
 - signal_infinity_norm_diff, [2281](#)
- nppsNormDiffInfGetBufferSize_64f
 - signal_infinity_norm_diff, [2281](#)
- nppsNormDiffInfGetBufferSize_64fc64f
 - signal_infinity_norm_diff, [2281](#)
- nppsNormDiffL1GetBufferSize_16s32f
 - signal_L1_norm_diff, [2285](#)
- nppsNormDiffL1GetBufferSize_16s32s_Sfs
 - signal_L1_norm_diff, [2285](#)
- nppsNormDiffL1GetBufferSize_16s64s_Sfs
 - signal_L1_norm_diff, [2286](#)
- nppsNormDiffL1GetBufferSize_32f
 - signal_L1_norm_diff, [2286](#)
- nppsNormDiffL1GetBufferSize_32fc64f
 - signal_L1_norm_diff, [2286](#)
- nppsNormDiffL1GetBufferSize_64f
 - signal_L1_norm_diff, [2286](#)
- nppsNormDiffL1GetBufferSize_64fc64f
 - signal_L1_norm_diff, [2287](#)
- nppsNormDiffL2GetBufferSize_16s32f
 - signal_L2_norm_diff, [2291](#)
- nppsNormDiffL2GetBufferSize_16s32s_Sfs
 - signal_L2_norm_diff, [2291](#)
- nppsNormDiffL2GetBufferSize_32f
 - signal_L2_norm_diff, [2292](#)
- nppsNormDiffL2GetBufferSize_32fc64f
 - signal_L2_norm_diff, [2292](#)
- nppsNormDiffL2GetBufferSize_64f
 - signal_L2_norm_diff, [2292](#)
- nppsNormDiffL2GetBufferSize_64fc64f
 - signal_L2_norm_diff, [2292](#)
- nppsNormDiffL2SqrGetBufferSize_16s64s_Sfs
 - signal_L2_norm_diff, [2293](#)
- nppsNormInfGetBufferSize_16s32f
 - signal_infinity_norm, [2262](#)
- nppsNormInfGetBufferSize_16s32s_Sfs
 - signal_infinity_norm, [2263](#)

- nppsNormInfGetBufferSize_32f
 - signal_infinity_norm, [2263](#)
- nppsNormInfGetBufferSize_32fc32f
 - signal_infinity_norm, [2263](#)
- nppsNormInfGetBufferSize_64f
 - signal_infinity_norm, [2263](#)
- nppsNormInfGetBufferSize_64fc64f
 - signal_infinity_norm, [2264](#)
- nppsNormL1GetBufferSize_16s32f
 - signal_L1_norm, [2268](#)
- nppsNormL1GetBufferSize_16s32s_Sfs
 - signal_L1_norm, [2268](#)
- nppsNormL1GetBufferSize_16s64s_Sfs
 - signal_L1_norm, [2268](#)
- nppsNormL1GetBufferSize_32f
 - signal_L1_norm, [2269](#)
- nppsNormL1GetBufferSize_32fc64f
 - signal_L1_norm, [2269](#)
- nppsNormL1GetBufferSize_64f
 - signal_L1_norm, [2269](#)
- nppsNormL1GetBufferSize_64fc64f
 - signal_L1_norm, [2269](#)
- nppsNormL2GetBufferSize_16s32f
 - signal_L2_norm, [2274](#)
- nppsNormL2GetBufferSize_16s32s_Sfs
 - signal_L2_norm, [2274](#)
- nppsNormL2GetBufferSize_32f
 - signal_L2_norm, [2274](#)
- nppsNormL2GetBufferSize_32fc64f
 - signal_L2_norm, [2275](#)
- nppsNormL2GetBufferSize_64f
 - signal_L2_norm, [2275](#)
- nppsNormL2GetBufferSize_64fc64f
 - signal_L2_norm, [2275](#)
- nppsNormL2SqrGetBufferSize_16s64s_Sfs
 - signal_L2_norm, [2275](#)
- nppsNot_16u
 - signal_not, [2148](#)
- nppsNot_16u_I
 - signal_not, [2148](#)
- nppsNot_32u
 - signal_not, [2149](#)
- nppsNot_32u_I
 - signal_not, [2149](#)
- nppsNot_8u
 - signal_not, [2149](#)
- nppsNot_8u_I
 - signal_not, [2149](#)
- nppsOr_16u
 - signal_or, [2139](#)
- nppsOr_16u_I
 - signal_or, [2139](#)
- nppsOr_32u
 - signal_or, [2140](#)
- nppsOr_32u_I
 - signal_or, [2140](#)
- nppsOr_8u
 - signal_or, [2140](#)
- nppsOr_8u_I
 - signal_or, [2141](#)
- nppsOrC_16u
 - signal_orc, [2136](#)
- nppsOrC_16u_I
 - signal_orc, [2136](#)
- nppsOrC_32u
 - signal_orc, [2137](#)
- nppsOrC_32u_I
 - signal_orc, [2137](#)
- nppsOrC_8u
 - signal_orc, [2137](#)
- nppsOrC_8u_I
 - signal_orc, [2138](#)
- nppsRShiftC_16s
 - signal_rshifc, [2155](#)
- nppsRShiftC_16s_I
 - signal_rshifc, [2156](#)
- nppsRShiftC_16u
 - signal_rshifc, [2156](#)
- nppsRShiftC_16u_I
 - signal_rshifc, [2156](#)
- nppsRShiftC_32s
 - signal_rshifc, [2156](#)
- nppsRShiftC_32s_I
 - signal_rshifc, [2157](#)
- nppsRShiftC_32u
 - signal_rshifc, [2157](#)
- nppsRShiftC_32u_I
 - signal_rshifc, [2157](#)
- nppsRShiftC_8u
 - signal_rshifc, [2158](#)
- nppsRShiftC_8u_I
 - signal_rshifc, [2158](#)
- nppsSet_16s
 - signal_set, [2191](#)
- nppsSet_16sc
 - signal_set, [2192](#)
- nppsSet_32f
 - signal_set, [2192](#)
- nppsSet_32fc
 - signal_set, [2192](#)
- nppsSet_32s
 - signal_set, [2192](#)
- nppsSet_32sc
 - signal_set, [2193](#)
- nppsSet_64f
 - signal_set, [2193](#)
- nppsSet_64fc
 - signal_set, [2193](#)

- nppsSet_64s
 - signal_set, 2194
- nppsSet_64sc
 - signal_set, 2194
- nppsSet_8u
 - signal_set, 2194
- nppsSqr_16s_ISfs
 - signal_square, 2095
- nppsSqr_16s_Sfs
 - signal_square, 2095
- nppsSqr_16sc_ISfs
 - signal_square, 2095
- nppsSqr_16sc_Sfs
 - signal_square, 2096
- nppsSqr_16u_ISfs
 - signal_square, 2096
- nppsSqr_16u_Sfs
 - signal_square, 2096
- nppsSqr_32f
 - signal_square, 2096
- nppsSqr_32f_I
 - signal_square, 2097
- nppsSqr_32fc
 - signal_square, 2097
- nppsSqr_32fc_I
 - signal_square, 2097
- nppsSqr_64f
 - signal_square, 2097
- nppsSqr_64f_I
 - signal_square, 2098
- nppsSqr_64fc
 - signal_square, 2098
- nppsSqr_64fc_I
 - signal_square, 2098
- nppsSqr_8u_ISfs
 - signal_square, 2098
- nppsSqr_8u_Sfs
 - signal_square, 2099
- nppsSqrt_16s_ISfs
 - signal_sqrt, 2101
- nppsSqrt_16s_Sfs
 - signal_sqrt, 2101
- nppsSqrt_16sc_ISfs
 - signal_sqrt, 2102
- nppsSqrt_16sc_Sfs
 - signal_sqrt, 2102
- nppsSqrt_16u_ISfs
 - signal_sqrt, 2102
- nppsSqrt_16u_Sfs
 - signal_sqrt, 2102
- nppsSqrt_32f
 - signal_sqrt, 2103
- nppsSqrt_32f_I
 - signal_sqrt, 2103
- nppsSqrt_32fc
 - signal_sqrt, 2103
- nppsSqrt_32fc_I
 - signal_sqrt, 2104
- nppsSqrt_32s16s_Sfs
 - signal_sqrt, 2104
- nppsSqrt_64f
 - signal_sqrt, 2104
- nppsSqrt_64f_I
 - signal_sqrt, 2104
- nppsSqrt_64fc
 - signal_sqrt, 2105
- nppsSqrt_64fc_I
 - signal_sqrt, 2105
- nppsSqrt_64s16s_Sfs
 - signal_sqrt, 2105
- nppsSqrt_64s_ISfs
 - signal_sqrt, 2105
- nppsSqrt_64s_Sfs
 - signal_sqrt, 2106
- nppsSqrt_8u_ISfs
 - signal_sqrt, 2106
- nppsSqrt_8u_Sfs
 - signal_sqrt, 2106
- nppsStdDev_16s32s_Sfs
 - signal_standard_deviation, 2241
- nppsStdDev_16s_Sfs
 - signal_standard_deviation, 2241
- nppsStdDev_32f
 - signal_standard_deviation, 2242
- nppsStdDev_64f
 - signal_standard_deviation, 2242
- nppsStdDevGetBufferSize_16s32s_Sfs
 - signal_standard_deviation, 2242
- nppsStdDevGetBufferSize_16s_Sfs
 - signal_standard_deviation, 2243
- nppsStdDevGetBufferSize_32f
 - signal_standard_deviation, 2243
- nppsStdDevGetBufferSize_64f
 - signal_standard_deviation, 2243
- nppsSub_16s
 - signal_sub, 2071
- nppsSub_16s32f
 - signal_sub, 2072
- nppsSub_16s_I
 - signal_sub, 2072
- nppsSub_16s_ISfs
 - signal_sub, 2072
- nppsSub_16s_Sfs
 - signal_sub, 2073
- nppsSub_16sc_ISfs
 - signal_sub, 2073
- nppsSub_16sc_Sfs
 - signal_sub, 2073

- nppsSub_16u_ISfs
 - signal_sub, [2074](#)
- nppsSub_16u_Sfs
 - signal_sub, [2074](#)
- nppsSub_32f
 - signal_sub, [2074](#)
- nppsSub_32f_I
 - signal_sub, [2075](#)
- nppsSub_32fc
 - signal_sub, [2075](#)
- nppsSub_32fc_I
 - signal_sub, [2075](#)
- nppsSub_32s_ISfs
 - signal_sub, [2075](#)
- nppsSub_32s_Sfs
 - signal_sub, [2076](#)
- nppsSub_32sc_ISfs
 - signal_sub, [2076](#)
- nppsSub_32sc_Sfs
 - signal_sub, [2076](#)
- nppsSub_64f
 - signal_sub, [2077](#)
- nppsSub_64f_I
 - signal_sub, [2077](#)
- nppsSub_64fc
 - signal_sub, [2077](#)
- nppsSub_64fc_I
 - signal_sub, [2078](#)
- nppsSub_8u_ISfs
 - signal_sub, [2078](#)
- nppsSub_8u_Sfs
 - signal_sub, [2078](#)
- nppsSubC_16s_ISfs
 - signal_subc, [2015](#)
- nppsSubC_16s_Sfs
 - signal_subc, [2015](#)
- nppsSubC_16sc_ISfs
 - signal_subc, [2016](#)
- nppsSubC_16sc_Sfs
 - signal_subc, [2016](#)
- nppsSubC_16u_ISfs
 - signal_subc, [2016](#)
- nppsSubC_16u_Sfs
 - signal_subc, [2017](#)
- nppsSubC_32f
 - signal_subc, [2017](#)
- nppsSubC_32f_I
 - signal_subc, [2017](#)
- nppsSubC_32fc
 - signal_subc, [2018](#)
- nppsSubC_32fc_I
 - signal_subc, [2018](#)
- nppsSubC_32s_ISfs
 - signal_subc, [2018](#)
- nppsSubC_32s_Sfs
 - signal_subc, [2019](#)
- nppsSubC_32sc_ISfs
 - signal_subc, [2019](#)
- nppsSubC_32sc_Sfs
 - signal_subc, [2019](#)
- nppsSubC_64f
 - signal_subc, [2020](#)
- nppsSubC_64f_I
 - signal_subc, [2020](#)
- nppsSubC_64fc
 - signal_subc, [2020](#)
- nppsSubC_64fc_I
 - signal_subc, [2021](#)
- nppsSubC_8u_ISfs
 - signal_subc, [2021](#)
- nppsSubC_8u_Sfs
 - signal_subc, [2021](#)
- nppsSubCRev_16s_ISfs
 - signal_subcrev, [2024](#)
- nppsSubCRev_16s_Sfs
 - signal_subcrev, [2025](#)
- nppsSubCRev_16sc_ISfs
 - signal_subcrev, [2025](#)
- nppsSubCRev_16sc_Sfs
 - signal_subcrev, [2025](#)
- nppsSubCRev_16u_ISfs
 - signal_subcrev, [2026](#)
- nppsSubCRev_16u_Sfs
 - signal_subcrev, [2026](#)
- nppsSubCRev_32f
 - signal_subcrev, [2026](#)
- nppsSubCRev_32f_I
 - signal_subcrev, [2027](#)
- nppsSubCRev_32fc
 - signal_subcrev, [2027](#)
- nppsSubCRev_32fc_I
 - signal_subcrev, [2027](#)
- nppsSubCRev_32s_ISfs
 - signal_subcrev, [2027](#)
- nppsSubCRev_32s_Sfs
 - signal_subcrev, [2028](#)
- nppsSubCRev_32sc_ISfs
 - signal_subcrev, [2028](#)
- nppsSubCRev_32sc_Sfs
 - signal_subcrev, [2028](#)
- nppsSubCRev_64f
 - signal_subcrev, [2029](#)
- nppsSubCRev_64f_I
 - signal_subcrev, [2029](#)
- nppsSubCRev_64fc
 - signal_subcrev, [2029](#)
- nppsSubCRev_64fc_I
 - signal_subcrev, [2030](#)

- nppsSubCRev_8u_ISfs
 - signal_subcrev, 2030
- nppsSubCRev_8u_Sfs
 - signal_subcrev, 2030
- nppsSum_16s32s_Sfs
 - signal_sum, 2209
- nppsSum_16s_Sfs
 - signal_sum, 2209
- nppsSum_16sc32sc_Sfs
 - signal_sum, 2210
- nppsSum_16sc_Sfs
 - signal_sum, 2210
- nppsSum_32f
 - signal_sum, 2210
- nppsSum_32fc
 - signal_sum, 2211
- nppsSum_32s_Sfs
 - signal_sum, 2211
- nppsSum_64f
 - signal_sum, 2211
- nppsSum_64fc
 - signal_sum, 2212
- nppsSumGetBufferSize_16s32s_Sfs
 - signal_sum, 2212
- nppsSumGetBufferSize_16s_Sfs
 - signal_sum, 2212
- nppsSumGetBufferSize_16sc32sc_Sfs
 - signal_sum, 2213
- nppsSumGetBufferSize_16sc_Sfs
 - signal_sum, 2213
- nppsSumGetBufferSize_32f
 - signal_sum, 2213
- nppsSumGetBufferSize_32fc
 - signal_sum, 2213
- nppsSumGetBufferSize_32s_Sfs
 - signal_sum, 2214
- nppsSumGetBufferSize_64f
 - signal_sum, 2214
- nppsSumGetBufferSize_64fc
 - signal_sum, 2214
- nppsSumLn_16s32f
 - signal_sumln, 2118
- nppsSumLn_32f
 - signal_sumln, 2119
- nppsSumLn_32f64f
 - signal_sumln, 2119
- nppsSumLn_64f
 - signal_sumln, 2119
- nppsSumLnGetBufferSize_16s32f
 - signal_sumln, 2120
- nppsSumLnGetBufferSize_32f
 - signal_sumln, 2120
- nppsSumLnGetBufferSize_32f64f
 - signal_sumln, 2120
- nppsSumLnGetBufferSize_64f
 - signal_sumln, 2120
- NppStatus
 - typedefs_npp, 43
- nppsThreshold_16s
 - signal_threshold, 2167
- nppsThreshold_16s_I
 - signal_threshold, 2168
- nppsThreshold_16sc
 - signal_threshold, 2168
- nppsThreshold_16sc_I
 - signal_threshold, 2168
- nppsThreshold_32f
 - signal_threshold, 2169
- nppsThreshold_32f_I
 - signal_threshold, 2169
- nppsThreshold_32fc
 - signal_threshold, 2169
- nppsThreshold_32fc_I
 - signal_threshold, 2170
- nppsThreshold_64f
 - signal_threshold, 2170
- nppsThreshold_64f_I
 - signal_threshold, 2170
- nppsThreshold_64fc
 - signal_threshold, 2171
- nppsThreshold_64fc_I
 - signal_threshold, 2171
- nppsThreshold_GT_16s
 - signal_threshold, 2171
- nppsThreshold_GT_16s_I
 - signal_threshold, 2172
- nppsThreshold_GT_16sc
 - signal_threshold, 2172
- nppsThreshold_GT_16sc_I
 - signal_threshold, 2172
- nppsThreshold_GT_32f
 - signal_threshold, 2173
- nppsThreshold_GT_32f_I
 - signal_threshold, 2173
- nppsThreshold_GT_32fc
 - signal_threshold, 2173
- nppsThreshold_GT_32fc_I
 - signal_threshold, 2174
- nppsThreshold_GT_64f
 - signal_threshold, 2174
- nppsThreshold_GT_64f_I
 - signal_threshold, 2174
- nppsThreshold_GT_64fc
 - signal_threshold, 2175
- nppsThreshold_GT_64fc_I
 - signal_threshold, 2175
- nppsThreshold_GTVal_16s
 - signal_threshold, 2175

- nppsThreshold_GTVal_16s_I
 - signal_threshold, 2176
- nppsThreshold_GTVal_16sc
 - signal_threshold, 2176
- nppsThreshold_GTVal_16sc_I
 - signal_threshold, 2176
- nppsThreshold_GTVal_32f
 - signal_threshold, 2177
- nppsThreshold_GTVal_32f_I
 - signal_threshold, 2177
- nppsThreshold_GTVal_32fc
 - signal_threshold, 2177
- nppsThreshold_GTVal_32fc_I
 - signal_threshold, 2178
- nppsThreshold_GTVal_64f
 - signal_threshold, 2178
- nppsThreshold_GTVal_64f_I
 - signal_threshold, 2178
- nppsThreshold_GTVal_64fc
 - signal_threshold, 2179
- nppsThreshold_GTVal_64fc_I
 - signal_threshold, 2179
- nppsThreshold_LT_16s
 - signal_threshold, 2179
- nppsThreshold_LT_16s_I
 - signal_threshold, 2180
- nppsThreshold_LT_16sc
 - signal_threshold, 2180
- nppsThreshold_LT_16sc_I
 - signal_threshold, 2180
- nppsThreshold_LT_32f
 - signal_threshold, 2181
- nppsThreshold_LT_32f_I
 - signal_threshold, 2181
- nppsThreshold_LT_32fc
 - signal_threshold, 2181
- nppsThreshold_LT_32fc_I
 - signal_threshold, 2182
- nppsThreshold_LT_64f
 - signal_threshold, 2182
- nppsThreshold_LT_64f_I
 - signal_threshold, 2182
- nppsThreshold_LT_64fc
 - signal_threshold, 2183
- nppsThreshold_LT_64fc_I
 - signal_threshold, 2183
- nppsThreshold_LTVal_16s
 - signal_threshold, 2183
- nppsThreshold_LTVal_16s_I
 - signal_threshold, 2184
- nppsThreshold_LTVal_16sc
 - signal_threshold, 2184
- nppsThreshold_LTVal_16sc_I
 - signal_threshold, 2184
- nppsThreshold_LTVal_32f
 - signal_threshold, 2185
- nppsThreshold_LTVal_32f_I
 - signal_threshold, 2185
- nppsThreshold_LTVal_32fc
 - signal_threshold, 2185
- nppsThreshold_LTVal_32fc_I
 - signal_threshold, 2186
- nppsThreshold_LTVal_64f
 - signal_threshold, 2186
- nppsThreshold_LTVal_64f_I
 - signal_threshold, 2186
- nppsThreshold_LTVal_64fc
 - signal_threshold, 2187
- nppsThreshold_LTVal_64fc_I
 - signal_threshold, 2187
- nppsXor_16u
 - signal_xor, 2145
- nppsXor_16u_I
 - signal_xor, 2145
- nppsXor_32u
 - signal_xor, 2146
- nppsXor_32u_I
 - signal_xor, 2146
- nppsXor_8u
 - signal_xor, 2146
- nppsXor_8u_I
 - signal_xor, 2147
- nppsXorC_16u
 - signal_xorc, 2142
- nppsXorC_16u_I
 - signal_xorc, 2142
- nppsXorC_32u
 - signal_xorc, 2143
- nppsXorC_32u_I
 - signal_xorc, 2143
- nppsXorC_8u
 - signal_xorc, 2143
- nppsXorC_8u_I
 - signal_xorc, 2144
- NppsZCType
 - typedefs_npp, 45
- nppsZero_16s
 - signal_zero, 2195
- nppsZero_16sc
 - signal_zero, 2196
- nppsZero_32f
 - signal_zero, 2196
- nppsZero_32fc
 - signal_zero, 2196
- nppsZero_32s
 - signal_zero, 2196
- nppsZero_32sc
 - signal_zero, 2196

- nppsZero_64f
 - signal_zero, 2197
- nppsZero_64fc
 - signal_zero, 2197
- nppsZero_64s
 - signal_zero, 2197
- nppsZero_64sc
 - signal_zero, 2197
- nppsZero_8u
 - signal_zero, 2198
- nppsZeroCrossing_16s32f
 - signal_count_zero_crossings, 2315
- nppsZeroCrossing_32f
 - signal_count_zero_crossings, 2315
- nppsZeroCrossingGetBufferSize_16s32f
 - signal_count_zero_crossings, 2316
- nppsZeroCrossingGetBufferSize_32f
 - signal_count_zero_crossings, 2316
- nppZCC
 - typedefs_npp, 46
- nppZCR
 - typedefs_npp, 46
- nppZCXor
 - typedefs_npp, 46
- numClassifiers
 - NppiHaarClassifier_32f, 2330
- Or, 444, 2139
- OrC, 382, 2136
- Perspective Transform, 1223
- Quantization Functions, 692
- Rank Filters, 1045
- re
 - NPP_ALIGN_16, 2326
 - NPP_ALIGN_8, 2327, 2328
- RectStdDev, 1692
- Remap, 1125
- Resize, 1113
- ResizeSqrPixel, 1091
- Rotate, 1147
- RShiftC, 404, 2155
- Scale, 828
- Set, 707, 2191
- signal_10log10
 - npps10Log10_32s_ISfs, 2117
 - npps10Log10_32s_Sfs, 2117
- signal_abs
 - nppsAbs_16s, 2091
 - nppsAbs_16s_I, 2091
 - nppsAbs_32f, 2092
 - nppsAbs_32f_I, 2092
- signal_add
 - nppsAdd_16s, 2043
 - nppsAdd_16s32f, 2043
 - nppsAdd_16s32s_I, 2043
 - nppsAdd_16s_I, 2044
 - nppsAdd_16s_ISfs, 2044
 - nppsAdd_16s_Sfs, 2044
 - nppsAdd_16sc_ISfs, 2045
 - nppsAdd_16sc_Sfs, 2045
 - nppsAdd_16u, 2045
 - nppsAdd_16u_ISfs, 2046
 - nppsAdd_16u_Sfs, 2046
 - nppsAdd_32f, 2046
 - nppsAdd_32f_I, 2047
 - nppsAdd_32fc, 2047
 - nppsAdd_32fc_I, 2047
 - nppsAdd_32s_ISfs, 2048
 - nppsAdd_32s_Sfs, 2048
 - nppsAdd_32sc_ISfs, 2048
 - nppsAdd_32sc_Sfs, 2049
 - nppsAdd_32u, 2049
 - nppsAdd_64f, 2049
 - nppsAdd_64f_I, 2050
 - nppsAdd_64fc, 2050
 - nppsAdd_64fc_I, 2050
 - nppsAdd_64s_Sfs, 2051
 - nppsAdd_8u16u, 2051
 - nppsAdd_8u_ISfs, 2051
 - nppsAdd_8u_Sfs, 2052
- signal_addc
 - nppsAddC_16s_ISfs, 1995
 - nppsAddC_16s_Sfs, 1995
 - nppsAddC_16sc_ISfs, 1996
 - nppsAddC_16sc_Sfs, 1996
 - nppsAddC_16u_ISfs, 1996
 - nppsAddC_16u_Sfs, 1997
 - nppsAddC_32f, 1997
 - nppsAddC_32f_I, 1997
 - nppsAddC_32fc, 1998
 - nppsAddC_32fc_I, 1998
 - nppsAddC_32s_ISfs, 1998
 - nppsAddC_32s_Sfs, 1999
 - nppsAddC_32sc_ISfs, 1999
 - nppsAddC_32sc_Sfs, 1999
 - nppsAddC_64f, 2000
 - nppsAddC_64f_I, 2000
 - nppsAddC_64fc, 2000
 - nppsAddC_64fc_I, 2001
 - nppsAddC_8u_ISfs, 2001
 - nppsAddC_8u_Sfs, 2001

- signal_addproduct
 - nppsAddProduct_16s32s_Sfs, 2054
 - nppsAddProduct_16s_Sfs, 2054
 - nppsAddProduct_32f, 2054
 - nppsAddProduct_32fc, 2055
 - nppsAddProduct_32s_Sfs, 2055
 - nppsAddProduct_64f, 2055
 - nppsAddProduct_64fc, 2056
- signal_addproductc
 - nppsAddProductC_32f, 2003
- signal_and
 - nppsAnd_16u, 2133
 - nppsAnd_16u_I, 2133
 - nppsAnd_32u, 2134
 - nppsAnd_32u_I, 2134
 - nppsAnd_8u, 2134
 - nppsAnd_8u_I, 2135
- signal_andc
 - nppsAndC_16u, 2130
 - nppsAndC_16u_I, 2130
 - nppsAndC_32u, 2131
 - nppsAndC_32u_I, 2131
 - nppsAndC_8u, 2131
 - nppsAndC_8u_I, 2132
- signal_cauchy
 - nppsCauchy_32f_I, 2127
 - nppsCauchyD_32f_I, 2127
 - nppsCauchyDD2_32f_I, 2127
- signal_convert
 - nppsConvert_16s32f, 2162
 - nppsConvert_16s32f_Sfs, 2162
 - nppsConvert_16s32s, 2162
 - nppsConvert_16s64f_Sfs, 2162
 - nppsConvert_16s8s_Sfs, 2162
 - nppsConvert_16u32f, 2162
 - nppsConvert_32f16s_Sfs, 2162
 - nppsConvert_32f16u_Sfs, 2162
 - nppsConvert_32f32s_Sfs, 2162
 - nppsConvert_32f64f, 2162
 - nppsConvert_32f8s_Sfs, 2162
 - nppsConvert_32f8u_Sfs, 2162
 - nppsConvert_32s16s, 2162
 - nppsConvert_32s16s_Sfs, 2162
 - nppsConvert_32s32f, 2162
 - nppsConvert_32s32f_Sfs, 2162
 - nppsConvert_32s64f, 2162
 - nppsConvert_32s64f_Sfs, 2162
 - nppsConvert_64f16s_Sfs, 2162
 - nppsConvert_64f32f, 2162
 - nppsConvert_64f32s_Sfs, 2162
 - nppsConvert_64f64s_Sfs, 2162
 - nppsConvert_64s32s_Sfs, 2162
 - nppsConvert_64s64f, 2162
 - nppsConvert_8s16s, 2162
 - nppsConvert_8s32f, 2162
 - nppsConvert_8u32f, 2162
- signal_copy
 - nppsCopy_16s, 2199
 - nppsCopy_16sc, 2200
 - nppsCopy_32f, 2200
 - nppsCopy_32fc, 2200
 - nppsCopy_32s, 2200
 - nppsCopy_32sc, 2201
 - nppsCopy_64fc, 2201
 - nppsCopy_64s, 2201
 - nppsCopy_64sc, 2202
 - nppsCopy_8u, 2202
- signal_count_in_range
 - nppsCountInRange_32s, 2314
 - nppsCountInRangeGetBufferSize_32s, 2314
- signal_count_zero_crossings
 - nppsZeroCrossing_16s32f, 2315
 - nppsZeroCrossing_32f, 2315
 - nppsZeroCrossingGetBufferSize_16s32f, 2316
 - nppsZeroCrossingGetBufferSize_32f, 2316
- signal_cuberoot
 - nppsCubrt_32f, 2108
 - nppsCubrt_32s16s_Sfs, 2108
- signal_div
 - nppsDiv_16s_ISfs, 2081
 - nppsDiv_16s_Sfs, 2081
 - nppsDiv_16sc_ISfs, 2082
 - nppsDiv_16sc_Sfs, 2082
 - nppsDiv_16u_ISfs, 2082
 - nppsDiv_16u_Sfs, 2083
 - nppsDiv_32f, 2083
 - nppsDiv_32f_I, 2083
 - nppsDiv_32fc, 2084
 - nppsDiv_32fc_I, 2084
 - nppsDiv_32s16s_Sfs, 2084
 - nppsDiv_32s_ISfs, 2085
 - nppsDiv_32s_Sfs, 2085
 - nppsDiv_64f, 2085
 - nppsDiv_64f_I, 2086
 - nppsDiv_64fc, 2086
 - nppsDiv_64fc_I, 2086
 - nppsDiv_8u_ISfs, 2087
 - nppsDiv_8u_Sfs, 2087
- signal_divc
 - nppsDivC_16s_ISfs, 2033
 - nppsDivC_16s_Sfs, 2033
 - nppsDivC_16sc_ISfs, 2033
 - nppsDivC_16sc_Sfs, 2034
 - nppsDivC_16u_ISfs, 2034
 - nppsDivC_16u_Sfs, 2034
 - nppsDivC_32f, 2035
 - nppsDivC_32f_I, 2035

- nppsDivC_32fc, 2035
- nppsDivC_32fc_I, 2036
- nppsDivC_64f, 2036
- nppsDivC_64f_I, 2036
- nppsDivC_64fc, 2037
- nppsDivC_64fc_I, 2037
- nppsDivC_8u_ISfs, 2037
- nppsDivC_8u_Sfs, 2038
- signal_divcrev
 - nppsDivCRev_16u, 2039
 - nppsDivCRev_16u_I, 2039
 - nppsDivCRev_32f, 2040
 - nppsDivCRev_32f_I, 2040
- signal_divround
 - nppsDiv_Round_16s_ISfs, 2088
 - nppsDiv_Round_16s_Sfs, 2089
 - nppsDiv_Round_16u_ISfs, 2089
 - nppsDiv_Round_16u_Sfs, 2089
 - nppsDiv_Round_8u_ISfs, 2090
 - nppsDiv_Round_8u_Sfs, 2090
- signal_dot_product
 - nppsDotProd_16s16sc32fc, 2297
 - nppsDotProd_16s16sc32sc_Sfs, 2298
 - nppsDotProd_16s16sc64sc, 2298
 - nppsDotProd_16s16sc_Sfs, 2298
 - nppsDotProd_16s32f, 2299
 - nppsDotProd_16s32s32s_Sfs, 2299
 - nppsDotProd_16s32s_Sfs, 2300
 - nppsDotProd_16s64s, 2300
 - nppsDotProd_16s_Sfs, 2300
 - nppsDotProd_16sc32fc, 2301
 - nppsDotProd_16sc32sc_Sfs, 2301
 - nppsDotProd_16sc64sc, 2302
 - nppsDotProd_16sc_Sfs, 2302
 - nppsDotProd_32f, 2302
 - nppsDotProd_32f32fc, 2303
 - nppsDotProd_32f32fc64fc, 2303
 - nppsDotProd_32f64f, 2303
 - nppsDotProd_32fc, 2304
 - nppsDotProd_32fc64fc, 2304
 - nppsDotProd_32s32sc_Sfs, 2304
 - nppsDotProd_32s_Sfs, 2305
 - nppsDotProd_32sc_Sfs, 2305
 - nppsDotProd_64f, 2306
 - nppsDotProd_64f64fc, 2306
 - nppsDotProd_64fc, 2306
 - nppsDotProdGetBufferSize_16s16sc32fc, 2307
 - nppsDotProdGetBufferSize_16s16sc32sc_Sfs, 2307
 - nppsDotProdGetBufferSize_16s16sc64sc, 2307
 - nppsDotProdGetBufferSize_16s16sc_Sfs, 2308
 - nppsDotProdGetBufferSize_16s32f, 2308
 - nppsDotProdGetBufferSize_16s32s32s_Sfs, 2308
 - nppsDotProdGetBufferSize_16s32s_Sfs, 2308
 - nppsDotProdGetBufferSize_16s64s, 2309
 - nppsDotProdGetBufferSize_16s_Sfs, 2309
 - nppsDotProdGetBufferSize_16sc32fc, 2309
 - nppsDotProdGetBufferSize_16sc32sc_Sfs, 2309
 - nppsDotProdGetBufferSize_16sc64sc, 2310
 - nppsDotProdGetBufferSize_16sc_Sfs, 2310
 - nppsDotProdGetBufferSize_32f, 2310
 - nppsDotProdGetBufferSize_32f32fc, 2310
 - nppsDotProdGetBufferSize_32f32fc64fc, 2311
 - nppsDotProdGetBufferSize_32f64f, 2311
 - nppsDotProdGetBufferSize_32fc, 2311
 - nppsDotProdGetBufferSize_32fc64fc, 2311
 - nppsDotProdGetBufferSize_32s32sc_Sfs, 2312
 - nppsDotProdGetBufferSize_32s_Sfs, 2312
 - nppsDotProdGetBufferSize_32sc_Sfs, 2312
 - nppsDotProdGetBufferSize_64f, 2312
 - nppsDotProdGetBufferSize_64f64fc, 2313
 - nppsDotProdGetBufferSize_64fc, 2313
- signal_exp
 - nppsExp_16s_ISfs, 2109
 - nppsExp_16s_Sfs, 2110
 - nppsExp_32f, 2110
 - nppsExp_32f64f, 2110
 - nppsExp_32f_I, 2110
 - nppsExp_32s_ISfs, 2111
 - nppsExp_32s_Sfs, 2111
 - nppsExp_64f, 2111
 - nppsExp_64f_I, 2112
 - nppsExp_64s_ISfs, 2112
 - nppsExp_64s_Sfs, 2112
- signal_free
 - nppsFree, 2323
- signal_infinity_norm
 - nppsNorm_Inf_16s32f, 2261
 - nppsNorm_Inf_16s32s_Sfs, 2261
 - nppsNorm_Inf_32f, 2261
 - nppsNorm_Inf_32fc32f, 2261
 - nppsNorm_Inf_64f, 2262
 - nppsNorm_Inf_64fc64f, 2262
 - nppsNormInfGetBufferSize_16s32f, 2262
 - nppsNormInfGetBufferSize_16s32s_Sfs, 2263
 - nppsNormInfGetBufferSize_32f, 2263
 - nppsNormInfGetBufferSize_32fc32f, 2263
 - nppsNormInfGetBufferSize_64f, 2263
 - nppsNormInfGetBufferSize_64fc64f, 2264
- signal_infinity_norm_diff
 - nppsNormDiff_Inf_16s32f, 2278

- nppsNormDiff_Inf_16s32s_Sfs, 2278
- nppsNormDiff_Inf_32f, 2278
- nppsNormDiff_Inf_32fc32f, 2279
- nppsNormDiff_Inf_64f, 2279
- nppsNormDiff_Inf_64fc64f, 2279
- nppsNormDiffInfGetBufferSize_16s32f, 2280
- nppsNormDiffInfGetBufferSize_16s32s_Sfs, 2280
- nppsNormDiffInfGetBufferSize_32f, 2280
- nppsNormDiffInfGetBufferSize_32fc32f, 2281
- nppsNormDiffInfGetBufferSize_64f, 2281
- nppsNormDiffInfGetBufferSize_64fc64f, 2281
- signal_integral
 - nppsIntegral_32s, 2189
 - nppsIntegralGetBufferSize_32s, 2189
- signal_inversetan
 - nppsArctan_32f, 2122
 - nppsArctan_32f_I, 2122
 - nppsArctan_64f, 2122
 - nppsArctan_64f_I, 2123
- signal_L1_norm
 - nppsNorm_L1_16s32f, 2266
 - nppsNorm_L1_16s32s_Sfs, 2266
 - nppsNorm_L1_16s64s_Sfs, 2266
 - nppsNorm_L1_32f, 2267
 - nppsNorm_L1_32fc64f, 2267
 - nppsNorm_L1_64f, 2267
 - nppsNorm_L1_64fc64f, 2268
 - nppsNormL1GetBufferSize_16s32f, 2268
 - nppsNormL1GetBufferSize_16s32s_Sfs, 2268
 - nppsNormL1GetBufferSize_16s64s_Sfs, 2268
 - nppsNormL1GetBufferSize_32f, 2269
 - nppsNormL1GetBufferSize_32fc64f, 2269
 - nppsNormL1GetBufferSize_64f, 2269
 - nppsNormL1GetBufferSize_64fc64f, 2269
- signal_L1_norm_diff
 - nppsNormDiff_L1_16s32f, 2283
 - nppsNormDiff_L1_16s32s_Sfs, 2283
 - nppsNormDiff_L1_16s64s_Sfs, 2283
 - nppsNormDiff_L1_32f, 2284
 - nppsNormDiff_L1_32fc64f, 2284
 - nppsNormDiff_L1_64f, 2284
 - nppsNormDiff_L1_64fc64f, 2285
 - nppsNormDiffL1GetBufferSize_16s32f, 2285
 - nppsNormDiffL1GetBufferSize_16s32s_Sfs, 2285
 - nppsNormDiffL1GetBufferSize_16s64s_Sfs, 2286
 - nppsNormDiffL1GetBufferSize_32f, 2286
 - nppsNormDiffL1GetBufferSize_32fc64f, 2286
 - nppsNormDiffL1GetBufferSize_64f, 2286
- nppsNormDiffL1GetBufferSize_64fc64f, 2287
- signal_L2_norm
 - nppsNorm_L2_16s32f, 2272
 - nppsNorm_L2_16s32s_Sfs, 2272
 - nppsNorm_L2_32f, 2272
 - nppsNorm_L2_32fc64f, 2273
 - nppsNorm_L2_64f, 2273
 - nppsNorm_L2_64fc64f, 2273
 - nppsNorm_L2Sqr_16s64s_Sfs, 2274
 - nppsNormL2GetBufferSize_16s32f, 2274
 - nppsNormL2GetBufferSize_16s32s_Sfs, 2274
 - nppsNormL2GetBufferSize_32f, 2274
 - nppsNormL2GetBufferSize_32fc64f, 2275
 - nppsNormL2GetBufferSize_64f, 2275
 - nppsNormL2GetBufferSize_64fc64f, 2275
 - nppsNormL2SqrGetBufferSize_16s64s_Sfs, 2275
- signal_L2_norm_diff
 - nppsNormDiff_L2_16s32f, 2289
 - nppsNormDiff_L2_16s32s_Sfs, 2289
 - nppsNormDiff_L2_32f, 2289
 - nppsNormDiff_L2_32fc64f, 2290
 - nppsNormDiff_L2_64f, 2290
 - nppsNormDiff_L2_64fc64f, 2290
 - nppsNormDiff_L2Sqr_16s64s_Sfs, 2291
 - nppsNormDiffL2GetBufferSize_16s32f, 2291
 - nppsNormDiffL2GetBufferSize_16s32s_Sfs, 2291
 - nppsNormDiffL2GetBufferSize_32f, 2292
 - nppsNormDiffL2GetBufferSize_32fc64f, 2292
 - nppsNormDiffL2GetBufferSize_64f, 2292
 - nppsNormDiffL2GetBufferSize_64fc64f, 2292
 - nppsNormDiffL2SqrGetBufferSize_16s64s_Sfs, 2293
- signal_ln
 - nppsLn_16s_ISfs, 2113
 - nppsLn_16s_Sfs, 2114
 - nppsLn_32f, 2114
 - nppsLn_32f_I, 2114
 - nppsLn_32s16s_Sfs, 2114
 - nppsLn_32s_ISfs, 2115
 - nppsLn_32s_Sfs, 2115
 - nppsLn_64f, 2115
 - nppsLn_64f32f, 2116
 - nppsLn_64f_I, 2116
- signal_lshiftc
 - nppsLShiftC_16s, 2151
 - nppsLShiftC_16s_I, 2152
 - nppsLShiftC_16u, 2152
 - nppsLShiftC_16u_I, 2152
 - nppsLShiftC_32s, 2152

- nppsLShiftC_32s_I, 2153
- nppsLShiftC_32u, 2153
- nppsLShiftC_32u_I, 2153
- nppsLShiftC_8u, 2154
- nppsLShiftC_8u_I, 2154
- signal_malloc
 - nppsMalloc_16s, 2319
 - nppsMalloc_16sc, 2319
 - nppsMalloc_16u, 2319
 - nppsMalloc_32f, 2319
 - nppsMalloc_32fc, 2320
 - nppsMalloc_32s, 2320
 - nppsMalloc_32sc, 2320
 - nppsMalloc_32u, 2320
 - nppsMalloc_64f, 2321
 - nppsMalloc_64fc, 2321
 - nppsMalloc_64s, 2321
 - nppsMalloc_64sc, 2321
 - nppsMalloc_8s, 2322
 - nppsMalloc_8u, 2322
- signal_max
 - nppsMax_16s, 2216
 - nppsMax_32f, 2217
 - nppsMax_32s, 2217
 - nppsMax_64f, 2217
 - nppsMaxAbs_16s, 2218
 - nppsMaxAbs_32s, 2218
 - nppsMaxAbsGetBufferSize_16s, 2218
 - nppsMaxAbsGetBufferSize_32s, 2219
 - nppsMaxAbsIdx_16s, 2219
 - nppsMaxAbsIdx_32s, 2219
 - nppsMaxAbsIdxGetBufferSize_16s, 2220
 - nppsMaxAbsIdxGetBufferSize_32s, 2220
 - nppsMaxGetBufferSize_16s, 2220
 - nppsMaxGetBufferSize_32f, 2220
 - nppsMaxGetBufferSize_32s, 2221
 - nppsMaxGetBufferSize_64f, 2221
 - nppsMaxIdx_16s, 2221
 - nppsMaxIdx_32f, 2222
 - nppsMaxIdx_32s, 2222
 - nppsMaxIdx_64f, 2222
 - nppsMaxIdxGetBufferSize_16s, 2223
 - nppsMaxIdxGetBufferSize_32f, 2223
 - nppsMaxIdxGetBufferSize_32s, 2223
 - nppsMaxIdxGetBufferSize_64f, 2224
- signal_mean
 - nppsMean_16s_Sfs, 2236
 - nppsMean_16sc_Sfs, 2236
 - nppsMean_32f, 2236
 - nppsMean_32fc, 2237
 - nppsMean_32s_Sfs, 2237
 - nppsMean_64f, 2237
 - nppsMean_64fc, 2238
 - nppsMeanGetBufferSize_16s_Sfs, 2238
 - nppsMeanGetBufferSize_16sc_Sfs, 2238
 - nppsMeanGetBufferSize_32f, 2239
 - nppsMeanGetBufferSize_32fc, 2239
 - nppsMeanGetBufferSize_32s_Sfs, 2239
 - nppsMeanGetBufferSize_64f, 2239
 - nppsMeanGetBufferSize_64fc, 2240
- signal_mean_and_standard_deviation
 - nppsMeanStdDev_16s32s_Sfs, 2244
 - nppsMeanStdDev_16s_Sfs, 2245
 - nppsMeanStdDev_32f, 2245
 - nppsMeanStdDev_64f, 2245
 - nppsMeanStdDevGetBufferSize_16s32s_Sfs, 2246
 - nppsMeanStdDevGetBufferSize_16s_Sfs, 2246
 - nppsMeanStdDevGetBufferSize_32f, 2246
 - nppsMeanStdDevGetBufferSize_64f, 2246
- signal_min
 - nppsMin_16s, 2226
 - nppsMin_32f, 2227
 - nppsMin_32s, 2227
 - nppsMin_64f, 2227
 - nppsMinAbs_16s, 2228
 - nppsMinAbs_32s, 2228
 - nppsMinAbsGetBufferSize_16s, 2228
 - nppsMinAbsGetBufferSize_32s, 2229
 - nppsMinAbsIdx_16s, 2229
 - nppsMinAbsIdx_32s, 2229
 - nppsMinAbsIdxGetBufferSize_16s, 2230
 - nppsMinAbsIdxGetBufferSize_32s, 2230
 - nppsMinGetBufferSize_16s, 2230
 - nppsMinGetBufferSize_32f, 2230
 - nppsMinGetBufferSize_32s, 2231
 - nppsMinGetBufferSize_64f, 2231
 - nppsMinIdx_16s, 2231
 - nppsMinIdx_32f, 2232
 - nppsMinIdx_32s, 2232
 - nppsMinIdx_64f, 2232
 - nppsMinIdxGetBufferSize_16s, 2233
 - nppsMinIdxGetBufferSize_32f, 2233
 - nppsMinIdxGetBufferSize_32s, 2233
 - nppsMinIdxGetBufferSize_64f, 2234
- signal_min_every_or_max_every
 - nppsMaxEvery_16s_I, 2204
 - nppsMaxEvery_16u_I, 2205
 - nppsMaxEvery_32f_I, 2205
 - nppsMaxEvery_32s_I, 2205
 - nppsMaxEvery_8u_I, 2205
 - nppsMinEvery_16s_I, 2206
 - nppsMinEvery_16u_I, 2206
 - nppsMinEvery_32f_I, 2206
 - nppsMinEvery_32s_I, 2207
 - nppsMinEvery_64f_I, 2207
 - nppsMinEvery_8u_I, 2207

- signal_min_max
 - nppsMinMax_16s, 2250
 - nppsMinMax_16u, 2250
 - nppsMinMax_32f, 2250
 - nppsMinMax_32s, 2251
 - nppsMinMax_32u, 2251
 - nppsMinMax_64f, 2251
 - nppsMinMax_8u, 2252
 - nppsMinMaxGetBufferSize_16s, 2252
 - nppsMinMaxGetBufferSize_16u, 2252
 - nppsMinMaxGetBufferSize_32f, 2253
 - nppsMinMaxGetBufferSize_32s, 2253
 - nppsMinMaxGetBufferSize_32u, 2253
 - nppsMinMaxGetBufferSize_64f, 2253
 - nppsMinMaxGetBufferSize_8u, 2254
 - nppsMinMaxIdx_16s, 2254
 - nppsMinMaxIdx_16u, 2254
 - nppsMinMaxIdx_32f, 2255
 - nppsMinMaxIdx_32s, 2255
 - nppsMinMaxIdx_32u, 2256
 - nppsMinMaxIdx_64f, 2256
 - nppsMinMaxIdx_8u, 2256
 - nppsMinMaxIdxGetBufferSize_16s, 2257
 - nppsMinMaxIdxGetBufferSize_16u, 2257
 - nppsMinMaxIdxGetBufferSize_32f, 2257
 - nppsMinMaxIdxGetBufferSize_32s, 2258
 - nppsMinMaxIdxGetBufferSize_32u, 2258
 - nppsMinMaxIdxGetBufferSize_64f, 2258
 - nppsMinMaxIdxGetBufferSize_8u, 2258
- signal_mul
 - nppsMul_16s, 2059
 - nppsMul_16s32f, 2059
 - nppsMul_16s32s_Sfs, 2060
 - nppsMul_16s_I, 2060
 - nppsMul_16s_ISfs, 2060
 - nppsMul_16s_Sfs, 2061
 - nppsMul_16sc_ISfs, 2061
 - nppsMul_16sc_Sfs, 2061
 - nppsMul_16u16s_Sfs, 2062
 - nppsMul_16u_ISfs, 2062
 - nppsMul_16u_Sfs, 2062
 - nppsMul_32f, 2063
 - nppsMul_32f32fc, 2063
 - nppsMul_32f32fc_I, 2063
 - nppsMul_32f_I, 2064
 - nppsMul_32fc, 2064
 - nppsMul_32fc_I, 2064
 - nppsMul_32s32sc_ISfs, 2065
 - nppsMul_32s32sc_Sfs, 2065
 - nppsMul_32s_ISfs, 2065
 - nppsMul_32s_Sfs, 2066
 - nppsMul_32sc_ISfs, 2066
 - nppsMul_32sc_Sfs, 2066
 - nppsMul_64f, 2067
 - nppsMul_64f_I, 2067
 - nppsMul_64fc, 2067
 - nppsMul_64fc_I, 2068
 - nppsMul_8u16u, 2068
 - nppsMul_8u_ISfs, 2068
 - nppsMul_8u_Sfs, 2069
 - nppsMul_Low_32s_Sfs, 2069
- signal_mulc
 - nppsMulC_16s_ISfs, 2005
 - nppsMulC_16s_Sfs, 2006
 - nppsMulC_16sc_ISfs, 2006
 - nppsMulC_16sc_Sfs, 2006
 - nppsMulC_16u_ISfs, 2007
 - nppsMulC_16u_Sfs, 2007
 - nppsMulC_32f, 2007
 - nppsMulC_32f16s_Sfs, 2008
 - nppsMulC_32f_I, 2008
 - nppsMulC_32fc, 2008
 - nppsMulC_32fc_I, 2009
 - nppsMulC_32s_ISfs, 2009
 - nppsMulC_32s_Sfs, 2009
 - nppsMulC_32sc_ISfs, 2010
 - nppsMulC_32sc_Sfs, 2010
 - nppsMulC_64f, 2010
 - nppsMulC_64f64s_ISfs, 2011
 - nppsMulC_64f_I, 2011
 - nppsMulC_64fc, 2011
 - nppsMulC_64fc_I, 2012
 - nppsMulC_8u_ISfs, 2012
 - nppsMulC_8u_Sfs, 2012
 - nppsMulC_Low_32f16s, 2013
- signal_normalize
 - nppsNormalize_16s_Sfs, 2124
 - nppsNormalize_16sc_Sfs, 2125
 - nppsNormalize_32f, 2125
 - nppsNormalize_32fc, 2125
 - nppsNormalize_64f, 2126
 - nppsNormalize_64fc, 2126
- signal_not
 - nppsNot_16u, 2148
 - nppsNot_16u_I, 2148
 - nppsNot_32u, 2149
 - nppsNot_32u_I, 2149
 - nppsNot_8u, 2149
 - nppsNot_8u_I, 2149
- signal_or
 - nppsOr_16u, 2139
 - nppsOr_16u_I, 2139
 - nppsOr_32u, 2140
 - nppsOr_32u_I, 2140
 - nppsOr_8u, 2140
 - nppsOr_8u_I, 2141
- signal_orc
 - nppsOrC_16u, 2136

- nppsOrC_16u_I, 2136
- nppsOrC_32u, 2137
- nppsOrC_32u_I, 2137
- nppsOrC_8u, 2137
- nppsOrC_8u_I, 2138
- signal_rshifc
 - nppsRShiftC_16s, 2155
 - nppsRShiftC_16s_I, 2156
 - nppsRShiftC_16u, 2156
 - nppsRShiftC_16u_I, 2156
 - nppsRShiftC_32s, 2156
 - nppsRShiftC_32s_I, 2157
 - nppsRShiftC_32u, 2157
 - nppsRShiftC_32u_I, 2157
 - nppsRShiftC_8u, 2158
 - nppsRShiftC_8u_I, 2158
- signal_set
 - nppsSet_16s, 2191
 - nppsSet_16sc, 2192
 - nppsSet_32f, 2192
 - nppsSet_32fc, 2192
 - nppsSet_32s, 2192
 - nppsSet_32sc, 2193
 - nppsSet_64f, 2193
 - nppsSet_64fc, 2193
 - nppsSet_64s, 2194
 - nppsSet_64sc, 2194
 - nppsSet_8u, 2194
- signal_sqrt
 - nppsSqrt_16s_ISfs, 2101
 - nppsSqrt_16s_Sfs, 2101
 - nppsSqrt_16sc_ISfs, 2102
 - nppsSqrt_16sc_Sfs, 2102
 - nppsSqrt_16u_ISfs, 2102
 - nppsSqrt_16u_Sfs, 2102
 - nppsSqrt_32f, 2103
 - nppsSqrt_32f_I, 2103
 - nppsSqrt_32fc, 2103
 - nppsSqrt_32fc_I, 2104
 - nppsSqrt_32s16s_Sfs, 2104
 - nppsSqrt_64f, 2104
 - nppsSqrt_64f_I, 2104
 - nppsSqrt_64fc, 2105
 - nppsSqrt_64fc_I, 2105
 - nppsSqrt_64s16s_Sfs, 2105
 - nppsSqrt_64s_ISfs, 2105
 - nppsSqrt_64s_Sfs, 2106
 - nppsSqrt_8u_ISfs, 2106
 - nppsSqrt_8u_Sfs, 2106
- signal_square
 - nppsSqr_16s_ISfs, 2095
 - nppsSqr_16s_Sfs, 2095
 - nppsSqr_16sc_ISfs, 2095
 - nppsSqr_16sc_Sfs, 2096
 - nppsSqr_16u_ISfs, 2096
 - nppsSqr_16u_Sfs, 2096
 - nppsSqr_32f, 2096
 - nppsSqr_32f_I, 2097
 - nppsSqr_32fc, 2097
 - nppsSqr_32fc_I, 2097
 - nppsSqr_64f, 2097
 - nppsSqr_64f_I, 2098
 - nppsSqr_64fc, 2098
 - nppsSqr_64fc_I, 2098
 - nppsSqr_8u_ISfs, 2098
 - nppsSqr_8u_Sfs, 2099
- signal_standard_deviation
 - nppsStdDev_16s32s_Sfs, 2241
 - nppsStdDev_16s_Sfs, 2241
 - nppsStdDev_32f, 2242
 - nppsStdDev_64f, 2242
 - nppsStdDevGetBufferSize_16s32s_Sfs, 2242
 - nppsStdDevGetBufferSize_16s_Sfs, 2243
 - nppsStdDevGetBufferSize_32f, 2243
 - nppsStdDevGetBufferSize_64f, 2243
- signal_sub
 - nppsSub_16s, 2071
 - nppsSub_16s32f, 2072
 - nppsSub_16s_I, 2072
 - nppsSub_16s_ISfs, 2072
 - nppsSub_16s_Sfs, 2073
 - nppsSub_16sc_ISfs, 2073
 - nppsSub_16sc_Sfs, 2073
 - nppsSub_16u_ISfs, 2074
 - nppsSub_16u_Sfs, 2074
 - nppsSub_32f, 2074
 - nppsSub_32f_I, 2075
 - nppsSub_32fc, 2075
 - nppsSub_32fc_I, 2075
 - nppsSub_32s_ISfs, 2075
 - nppsSub_32s_Sfs, 2076
 - nppsSub_32sc_ISfs, 2076
 - nppsSub_32sc_Sfs, 2076
 - nppsSub_64f, 2077
 - nppsSub_64f_I, 2077
 - nppsSub_64fc, 2077
 - nppsSub_64fc_I, 2078
 - nppsSub_8u_ISfs, 2078
 - nppsSub_8u_Sfs, 2078
- signal_subc
 - nppsSubC_16s_ISfs, 2015
 - nppsSubC_16s_Sfs, 2015
 - nppsSubC_16sc_ISfs, 2016
 - nppsSubC_16sc_Sfs, 2016
 - nppsSubC_16u_ISfs, 2016
 - nppsSubC_16u_Sfs, 2017
 - nppsSubC_32f, 2017
 - nppsSubC_32f_I, 2017

- nppsSubC_32fc, 2018
- nppsSubC_32fc_I, 2018
- nppsSubC_32s_ISfs, 2018
- nppsSubC_32s_Sfs, 2019
- nppsSubC_32sc_ISfs, 2019
- nppsSubC_32sc_Sfs, 2019
- nppsSubC_64f, 2020
- nppsSubC_64f_I, 2020
- nppsSubC_64fc, 2020
- nppsSubC_64fc_I, 2021
- nppsSubC_8u_ISfs, 2021
- nppsSubC_8u_Sfs, 2021
- signal_subcrev
 - nppsSubCRev_16s_ISfs, 2024
 - nppsSubCRev_16s_Sfs, 2025
 - nppsSubCRev_16sc_ISfs, 2025
 - nppsSubCRev_16sc_Sfs, 2025
 - nppsSubCRev_16u_ISfs, 2026
 - nppsSubCRev_16u_Sfs, 2026
 - nppsSubCRev_32f, 2026
 - nppsSubCRev_32f_I, 2027
 - nppsSubCRev_32fc, 2027
 - nppsSubCRev_32fc_I, 2027
 - nppsSubCRev_32s_ISfs, 2027
 - nppsSubCRev_32s_Sfs, 2028
 - nppsSubCRev_32sc_ISfs, 2028
 - nppsSubCRev_32sc_Sfs, 2028
 - nppsSubCRev_64f, 2029
 - nppsSubCRev_64f_I, 2029
 - nppsSubCRev_64fc, 2029
 - nppsSubCRev_64fc_I, 2030
 - nppsSubCRev_8u_ISfs, 2030
 - nppsSubCRev_8u_Sfs, 2030
- signal_sum
 - nppsSum_16s32s_Sfs, 2209
 - nppsSum_16s_Sfs, 2209
 - nppsSum_16sc32sc_Sfs, 2210
 - nppsSum_16sc_Sfs, 2210
 - nppsSum_32f, 2210
 - nppsSum_32fc, 2211
 - nppsSum_32s_Sfs, 2211
 - nppsSum_64f, 2211
 - nppsSum_64fc, 2212
 - nppsSumGetBufferSize_16s32s_Sfs, 2212
 - nppsSumGetBufferSize_16s_Sfs, 2212
 - nppsSumGetBufferSize_16sc32sc_Sfs, 2213
 - nppsSumGetBufferSize_16sc_Sfs, 2213
 - nppsSumGetBufferSize_32f, 2213
 - nppsSumGetBufferSize_32fc, 2213
 - nppsSumGetBufferSize_32s_Sfs, 2214
 - nppsSumGetBufferSize_64f, 2214
 - nppsSumGetBufferSize_64fc, 2214
- signal_sumln
 - nppsSumLn_16s32f, 2118
 - nppsSumLn_32f, 2119
 - nppsSumLn_32f64f, 2119
 - nppsSumLn_64f, 2119
 - nppsSumLnGetBufferSize_16s32f, 2120
 - nppsSumLnGetBufferSize_32f, 2120
 - nppsSumLnGetBufferSize_32f64f, 2120
 - nppsSumLnGetBufferSize_64f, 2120
- signal_threshold
 - nppsThreshold_16s, 2167
 - nppsThreshold_16s_I, 2168
 - nppsThreshold_16sc, 2168
 - nppsThreshold_16sc_I, 2168
 - nppsThreshold_32f, 2169
 - nppsThreshold_32f_I, 2169
 - nppsThreshold_32fc, 2169
 - nppsThreshold_32fc_I, 2170
 - nppsThreshold_64f, 2170
 - nppsThreshold_64f_I, 2170
 - nppsThreshold_64fc, 2171
 - nppsThreshold_64fc_I, 2171
 - nppsThreshold_GT_16s, 2171
 - nppsThreshold_GT_16s_I, 2172
 - nppsThreshold_GT_16sc, 2172
 - nppsThreshold_GT_16sc_I, 2172
 - nppsThreshold_GT_32f, 2173
 - nppsThreshold_GT_32f_I, 2173
 - nppsThreshold_GT_32fc, 2173
 - nppsThreshold_GT_32fc_I, 2174
 - nppsThreshold_GT_64f, 2174
 - nppsThreshold_GT_64f_I, 2174
 - nppsThreshold_GT_64fc, 2175
 - nppsThreshold_GT_64fc_I, 2175
 - nppsThreshold_GTVAl_16s, 2175
 - nppsThreshold_GTVAl_16s_I, 2176
 - nppsThreshold_GTVAl_16sc, 2176
 - nppsThreshold_GTVAl_16sc_I, 2176
 - nppsThreshold_GTVAl_32f, 2177
 - nppsThreshold_GTVAl_32f_I, 2177
 - nppsThreshold_GTVAl_32fc, 2177
 - nppsThreshold_GTVAl_32fc_I, 2178
 - nppsThreshold_GTVAl_64f, 2178
 - nppsThreshold_GTVAl_64f_I, 2178
 - nppsThreshold_GTVAl_64fc, 2179
 - nppsThreshold_GTVAl_64fc_I, 2179
 - nppsThreshold_LT_16s, 2179
 - nppsThreshold_LT_16s_I, 2180
 - nppsThreshold_LT_16sc, 2180
 - nppsThreshold_LT_16sc_I, 2180
 - nppsThreshold_LT_32f, 2181
 - nppsThreshold_LT_32f_I, 2181
 - nppsThreshold_LT_32fc, 2181
 - nppsThreshold_LT_32fc_I, 2182
 - nppsThreshold_LT_64f, 2182
 - nppsThreshold_LT_64f_I, 2182

- nppsThreshold_LT_64fc, 2183
- nppsThreshold_LT_64fc_I, 2183
- nppsThreshold_LTVAl_16s, 2183
- nppsThreshold_LTVAl_16s_I, 2184
- nppsThreshold_LTVAl_16sc, 2184
- nppsThreshold_LTVAl_16sc_I, 2184
- nppsThreshold_LTVAl_32f, 2185
- nppsThreshold_LTVAl_32f_I, 2185
- nppsThreshold_LTVAl_32fc, 2185
- nppsThreshold_LTVAl_32fc_I, 2186
- nppsThreshold_LTVAl_64f, 2186
- nppsThreshold_LTVAl_64f_I, 2186
- nppsThreshold_LTVAl_64fc, 2187
- nppsThreshold_LTVAl_64fc_I, 2187
- signal_xor
 - nppsXor_16u, 2145
 - nppsXor_16u_I, 2145
 - nppsXor_32u, 2146
 - nppsXor_32u_I, 2146
 - nppsXor_8u, 2146
 - nppsXor_8u_I, 2147
- signal_xorc
 - nppsXorC_16u, 2142
 - nppsXorC_16u_I, 2142
 - nppsXorC_32u, 2143
 - nppsXorC_32u_I, 2143
 - nppsXorC_8u, 2143
 - nppsXorC_8u_I, 2144
- signal_zero
 - nppsZero_16s, 2195
 - nppsZero_16sc, 2196
 - nppsZero_32f, 2196
 - nppsZero_32fc, 2196
 - nppsZero_32s, 2196
 - nppsZero_32sc, 2196
 - nppsZero_64f, 2197
 - nppsZero_64fc, 2197
 - nppsZero_64s, 2197
 - nppsZero_64sc, 2197
 - nppsZero_8u, 2198
- Sqr, 330, 2094
- SqrDistanceFull_Norm, 1727
- sqrdistancefullnorm
 - nppiSqrDistanceFull_Norm_16u32f_AC4R, 1729
 - nppiSqrDistanceFull_Norm_16u32f_C1R, 1729
 - nppiSqrDistanceFull_Norm_16u32f_C3R, 1729
 - nppiSqrDistanceFull_Norm_16u32f_C4R, 1730
 - nppiSqrDistanceFull_Norm_32f_AC4R, 1730
 - nppiSqrDistanceFull_Norm_32f_C1R, 1731
 - nppiSqrDistanceFull_Norm_32f_C3R, 1731
 - nppiSqrDistanceFull_Norm_32f_C4R, 1732
 - nppiSqrDistanceFull_Norm_8s32f_AC4R, 1732
 - nppiSqrDistanceFull_Norm_8s32f_C1R, 1732
 - nppiSqrDistanceFull_Norm_8s32f_C3R, 1733
 - nppiSqrDistanceFull_Norm_8s32f_C4R, 1733
 - nppiSqrDistanceFull_Norm_8u32f_AC4R, 1734
 - nppiSqrDistanceFull_Norm_8u32f_C1R, 1734
 - nppiSqrDistanceFull_Norm_8u32f_C3R, 1735
 - nppiSqrDistanceFull_Norm_8u32f_C4R, 1735
 - nppiSqrDistanceFull_Norm_8u_AC4RSfs, 1735
 - nppiSqrDistanceFull_Norm_8u_C1RSfs, 1736
 - nppiSqrDistanceFull_Norm_8u_C3RSfs, 1736
 - nppiSqrDistanceFull_Norm_8u_C4RSfs, 1737
- SqrDistanceSame_Norm, 1738
- sqrdistancesamenorm
 - nppiSqrDistanceSame_Norm_16u32f_AC4R, 1740
 - nppiSqrDistanceSame_Norm_16u32f_C1R, 1740
 - nppiSqrDistanceSame_Norm_16u32f_C3R, 1741
 - nppiSqrDistanceSame_Norm_16u32f_C4R, 1741
 - nppiSqrDistanceSame_Norm_32f_AC4R, 1741
 - nppiSqrDistanceSame_Norm_32f_C1R, 1742
 - nppiSqrDistanceSame_Norm_32f_C3R, 1742
 - nppiSqrDistanceSame_Norm_32f_C4R, 1743
 - nppiSqrDistanceSame_Norm_8s32f_AC4R, 1743
 - nppiSqrDistanceSame_Norm_8s32f_C1R, 1744
 - nppiSqrDistanceSame_Norm_8s32f_C3R, 1744
 - nppiSqrDistanceSame_Norm_8s32f_C4R, 1744
 - nppiSqrDistanceSame_Norm_8u32f_AC4R, 1745
 - nppiSqrDistanceSame_Norm_8u32f_C1R, 1745
 - nppiSqrDistanceSame_Norm_8u32f_C3R, 1746
 - nppiSqrDistanceSame_Norm_8u32f_C4R, 1746
 - nppiSqrDistanceSame_Norm_8u_AC4RSfs, 1747
 - nppiSqrDistanceSame_Norm_8u_C1RSfs, 1747
 - nppiSqrDistanceSame_Norm_8u_C3RSfs, 1748

- nppiSqrDistanceSame_Norm_8u_C4RSfs, 1748
- SqrDistanceValid_Norm, 1749
- sqrdistancevalidnorm
 - nppiSqrDistanceValid_Norm_16u32f_AC4R, 1751
 - nppiSqrDistanceValid_Norm_16u32f_C1R, 1751
 - nppiSqrDistanceValid_Norm_16u32f_C3R, 1752
 - nppiSqrDistanceValid_Norm_16u32f_C4R, 1752
 - nppiSqrDistanceValid_Norm_32f_AC4R, 1752
 - nppiSqrDistanceValid_Norm_32f_C1R, 1753
 - nppiSqrDistanceValid_Norm_32f_C3R, 1753
 - nppiSqrDistanceValid_Norm_32f_C4R, 1754
 - nppiSqrDistanceValid_Norm_8s32f_AC4R, 1754
 - nppiSqrDistanceValid_Norm_8s32f_C1R, 1755
 - nppiSqrDistanceValid_Norm_8s32f_C3R, 1755
 - nppiSqrDistanceValid_Norm_8s32f_C4R, 1755
 - nppiSqrDistanceValid_Norm_8u32f_AC4R, 1756
 - nppiSqrDistanceValid_Norm_8u32f_C1R, 1756
 - nppiSqrDistanceValid_Norm_8u32f_C3R, 1757
 - nppiSqrDistanceValid_Norm_8u32f_C4R, 1757
 - nppiSqrDistanceValid_Norm_8u_AC4RSfs, 1758
 - nppiSqrDistanceValid_Norm_8u_C1RSfs, 1758
 - nppiSqrDistanceValid_Norm_8u_C3RSfs, 1759
 - nppiSqrDistanceValid_Norm_8u_C4RSfs, 1759
- SqrIntegral, 1689
- Sqrt, 344, 2100
- Standard Deviation, 2241
- Statistical Functions, 2203
- Statistical Operations, 1299
- Sub, 246, 2070
- SubC, 114, 2014
- SubCRev, 2023
- Sum, 1301, 2208
- SumLn, 2118
- Swap Channels, 906
- Threshold, 2163
- Threshold and Compare Operations, 1877
- Threshold Operations, 1878
- Transpose, 899
- typedefs_npp
 - NPP_AFFINE_QUAD_INCORRECT_WARNING, 45
 - NPP_ALG_HINT_ACCURATE, 41
 - NPP_ALG_HINT_FAST, 41
 - NPP_ALG_HINT_NONE, 41
 - NPP_ALIGNMENT_ERROR, 44
 - NPP_ANCHOR_ERROR, 44
 - NPP_BAD_ARGUMENT_ERROR, 45
 - NPP_BORDER_CONSTANT, 42
 - NPP_BORDER_NONE, 42
 - NPP_BORDER_REPLICATE, 42
 - NPP_BORDER_UNDEFINED, 42
 - NPP_BORDER_WRAP, 42
 - NPP_BOTH_AXIS, 42
 - NPP_CHANNEL_ERROR, 44
 - NPP_CHANNEL_ORDER_ERROR, 44
 - NPP_CMP_EQ, 41
 - NPP_CMP_GREATER, 41
 - NPP_CMP_GREATER_EQ, 41
 - NPP_CMP_LESS, 41
 - NPP_CMP_LESS_EQ, 41
 - NPP_COEFFICIENT_ERROR, 44
 - NPP_COI_ERROR, 44
 - NPP_CONTEXT_MATCH_ERROR, 45
 - NPP_CUDA_1_0, 41
 - NPP_CUDA_1_1, 41
 - NPP_CUDA_1_2, 41
 - NPP_CUDA_1_3, 41
 - NPP_CUDA_2_0, 41
 - NPP_CUDA_2_1, 41
 - NPP_CUDA_3_0, 41
 - NPP_CUDA_3_5, 41
 - NPP_CUDA_KERNEL_EXECUTION_ERROR, 44
 - NPP_CUDA_NOT_CAPABLE, 41
 - NPP_CUDA_UNKNOWN_VERSION, 41
 - NPP_DATA_TYPE_ERROR, 45
 - NPP_DIVIDE_BY_ZERO_ERROR, 45
 - NPP_DIVIDE_BY_ZERO_WARNING, 45
 - NPP_DIVISOR_ERROR, 44
 - NPP_DOUBLE_SIZE_WARNING, 45
 - NPP_ERROR, 45
 - NPP_ERROR_RESERVED, 45
 - NPP_FFT_FLAG_ERROR, 45
 - NPP_FFT_ORDER_ERROR, 45
 - NPP_HAAR_CLASSIFIER_PIXEL_MATCH_ERROR, 44
 - NPP_HISTOGRAM_NUMBER_OF_LEVELS_ERROR, 44
 - NPP_HORIZONTAL_AXIS, 42

- NPP_INTERPOLATION_ERROR, 44
- NPP_INVALID_DEVICE_POINTER_ERROR, 44
- NPP_INVALID_HOST_POINTER_ERROR, 44
- NPP_LUT_NUMBER_OF_LEVELS_ERROR, 44
- NPP_LUT_PALETTE_BITSIZE_ERROR, 44
- NPP_MASK_SIZE_1_X_3, 43
- NPP_MASK_SIZE_1_X_5, 43
- NPP_MASK_SIZE_3_X_1, 43
- NPP_MASK_SIZE_3_X_3, 43
- NPP_MASK_SIZE_5_X_1, 43
- NPP_MASK_SIZE_5_X_5, 43
- NPP_MASK_SIZE_ERROR, 44
- NPP_MEMCPY_ERROR, 44
- NPP_MEMFREE_ERR, 44
- NPP_MEMORY_ALLOCATION_ERR, 45
- NPP_MEMSET_ERR, 44
- NPP_MIRROR_FLIP_ERR, 45
- NPP_MISALIGNED_DST_ROI_WARNING, 45
- NPP_MOMENT_00_ZERO_ERROR, 45
- NPP_NO_ERROR, 45
- NPP_NO_MEMORY_ERROR, 45
- NPP_NO_OPERATION_WARNING, 45
- NPP_NOT_EVEN_STEP_ERROR, 44
- NPP_NOT_IMPLEMENTED_ERROR, 45
- NPP_NOT_SUFFICIENT_COMPUTE_CAPABILITY, 44
- NPP_NOT_SUPPORTED_MODE_ERROR, 44
- NPP_NULL_POINTER_ERROR, 45
- NPP_NUMBER_OF_CHANNELS_ERROR, 44
- NPP_OUT_OFF_RANGE_ERROR, 45
- NPP_QUADRANGLE_ERROR, 44
- NPP_QUALITY_INDEX_ERROR, 44
- NPP_RANGE_ERROR, 45
- NPP_RECTANGLE_ERROR, 44
- NPP_RESIZE_FACTOR_ERROR, 44
- NPP_RESIZE_NO_OPERATION_ERROR, 44
- NPP_RND_FINANCIAL, 43
- NPP_RND_NEAR, 43
- NPP_RND_ZERO, 43
- NPP_ROUND_MODE_NOT_SUPPORTED_ERROR, 44
- NPP_ROUND_NEAREST_TIES_AWAY_FROM_ZERO, 43
- NPP_ROUND_NEAREST_TIES_TO_EVEN, 43
- NPP_ROUND_TOWARD_ZERO, 43
- NPP_SCALE_RANGE_ERROR, 45
- NPP_SIZE_ERROR, 45
- NPP_STEP_ERROR, 45
- NPP_STRIDE_ERROR, 44
- NPP_SUCCESS, 45
- NPP_TEXTURE_BIND_ERROR, 44
- NPP_THRESHOLD_ERROR, 45
- NPP_THRESHOLD_NEGATIVE_LEVEL_ERROR, 45
- NPP_VERTICAL_AXIS, 42
- NPP_WRONG_INTERSECTION_QUAD_WARNING, 45
- NPP_WRONG_INTERSECTION_ROI_ERROR, 44
- NPP_WRONG_INTERSECTION_ROI_WARNING, 45
- NPP_ZC_MODE_NOT_SUPPORTED_ERROR, 44
- NPP_ZERO_MASK_VALUE_ERROR, 44
- NPPI_INTER_CUBIC, 42
- NPPI_INTER_CUBIC2P_B05C03, 42
- NPPI_INTER_CUBIC2P_BSPLINE, 42
- NPPI_INTER_CUBIC2P_CATMULLROM, 42
- NPPI_INTER_LANCZOS, 42
- NPPI_INTER_LINEAR, 42
- NPPI_INTER_NN, 42
- NPPI_INTER_SUPER, 42
- NPPI_INTER_UNDEFINED, 42
- NPPI_OP_ALPHA_ATOP, 41
- NPPI_OP_ALPHA_ATOP_PREMUL, 42
- NPPI_OP_ALPHA_IN, 41
- NPPI_OP_ALPHA_IN_PREMUL, 42
- NPPI_OP_ALPHA_OUT, 41
- NPPI_OP_ALPHA_OUT_PREMUL, 42
- NPPI_OP_ALPHA_OVER, 41
- NPPI_OP_ALPHA_OVER_PREMUL, 42
- NPPI_OP_ALPHA_PLUS, 42
- NPPI_OP_ALPHA_PLUS_PREMUL, 42
- NPPI_OP_ALPHA_PREMUL, 42
- NPPI_OP_ALPHA_XOR, 42
- NPPI_OP_ALPHA_XOR_PREMUL, 42
- NPPI_SMOOTH_EDGE, 42
- nppZCC, 46
- nppZCR, 46
- nppZCxor, 46
- typedefs_npp
 - NPP_MAX_16S, 39
 - NPP_MAX_16U, 39
 - NPP_MAX_32S, 39
 - NPP_MAX_32U, 39
 - NPP_MAX_64S, 39
 - NPP_MAX_64U, 39
 - NPP_MAX_8S, 39
 - NPP_MAX_8U, 39

NPP_MAXABS_32F, 39
NPP_MAXABS_64F, 40
NPP_MIN_16S, 40
NPP_MIN_16U, 40
NPP_MIN_32S, 40
NPP_MIN_32U, 40
NPP_MIN_64S, 40
NPP_MIN_64U, 40
NPP_MIN_8S, 40
NPP_MIN_8U, 40
NPP_MINABS_32F, 40
NPP_MINABS_64F, 40
NppCmpOp, 41
NppGpuComputeCapability, 41
NppHintAlgorithm, 41
NppiAlphaOp, 41
NppiAxis, 42
NppiBorderType, 42
NppiInterpolationMode, 42
NppiMaskSize, 42
NppRoundMode, 43
NppStatus, 43
NppsZCType, 45

width

- NppiRect, 2332
- NppiSize, 2333

x

- NppiPoint, 2331
- NppiRect, 2332

Xor, 456, 2145
XorC, 393, 2142

y

- NppiPoint, 2331
- NppiRect, 2332

Zero, 2195